Bill's Helix Cheat Sheet / Command Reference

1 Introduction

1.1 Metadata

- Document version: 1.1.0-beta, 27-Apr-2026
- Based on Helix version: 25.07.1
- Built with Typst version: 0.14.2
- Distributed at: https://github.com/wrwetzel/Helix-Cheat-Sheet
- © 2026 Bill Wetzel - Licensed under CC BY 4.0 https://creativecommons.org/licenses/by/4.0/

1.2 Definitions

- **file** - data on storage device, e.g., hard disk or ssd
- **buffers** - data from one or more files loaded into memory
- **view** - one or more visual areas on screen showing one or more buffers
- **workspace** - the directory from which Helix was launched
- **under selection** - the entire word containing the cursor
- **alternate buffer** - the previous active buffer
- **textual line** - text as defined by the newline character
- **visual line** - what appears on screen after word-wrapping
- **range** - a selection; one in single-selection, multiple in multi-selection

1.3 Typographic Conventions

- **`word`** - alphanumeric, punctuation-delimited
- **`WORD`** - whitespace-delimited
- **`Ctrl-c`** - Ctrl and c key pressed simultaneous.
- **`Alt-c`** - Alt and c key pressed simultaneous.
- Some Alt and Ctrl characters may conflict with terminal capture and require terminal configuration change.
- **`␣c`** is space followed by the character c.
- Metavars **`<regex>`**, **`<file>`** and **`<ch>`** represent user input. The angle-brackets are not part of the input.
- **`␣`**, **`<minus>`**, and **`<under>`** used for clarity. **`<enter>`**, **`<del>`**, **`<bksp>`**, etc. used for non-printing control characters.
- Commands are separated from definitions by a dash. Synonyms are separated by commas. Related commands are separated by slashes. The separators are never part of the command though commands may include a dash, comma, or slash.

1.4 Launching

```
helix
helix <file>
helix <file1> <file2> ... <filen>
helix <directory>
helix --help
hx in some distributions or by alias
```

2 Primary Commands

2.1 Editing Paradigm

Selection first, action second. *mode* and *count* are optional.

```
[mode][count][select][command]
      v3wd – enter select mode, select 3 words, delete
```

2.2 Regular Expressions

Helix uses Rust's regex. Escape following metachars with <backslash> when searching for literal value.

```
      . – any character
      * – zero or more
      + – one or more
      ? – zero or one / lazy match
      ^ – start of line / negation in class
      $ – end of line
    ( ) – capture group
    [ ] – character class
    { } – repetition count
      | – alternation
      \ – escape character itself
```

2.3 Essentials

2.3.1 Undo / Repeat / Normal Mode

```
          u / U – undo / redo change in linear
                  history
  Alt-u / Alt-U – move backward / forward in tree
                  history
   :ear / :lat – move backward / forward in
                  history by step count or time span
                  (1s, 2m, 3h, 4d)
     <nn><cmd> – repeat <cmd> <nn> times
            Esc – return to normal mode
```

2.3.2 Quit

Add **!** suffix to force operation.

```
         :wq – write current buffer and quit
  :wq <file> – write current buffer to <file> and quit
        :wqa – write all buffer(s) and quit
          :q – quit current buffer, exits if last
```

2.3.3 Files

`:o <file>`	open <file> in new buffer
`:w <file>`	write current buffer to <file>
`:hs <file>`	open/create <file> in new horizontal split
`:vs <file>`	open/create <file> in new vertical split
`␣wf`	open/create file(s) under selection(s) in horizontal split
`␣wF`	open/create file(s) under selection(s) in vertical split
`gf`	open/create file(s) under selection, open url under selection.
`␣f`	open file picker at LSP workspace root
`␣F`	open file picker at current working directory
`␣g`	open changed file picker

2.3.3.1 File Picker

All pickers, here and elsewhere, are *fuzzy* - they tolerate gaps in the input, ranking closer matches higher.

`<enter>`	open selected in current view
`Ctrl-s`	open selected in new horizontal split
`Ctrl-v`	open selected in new vertical split

2.3.4 Buffers

Add **!** suffix to force operation. Buffers named by file they contain.

`:n`	create new scratch buffer
`:bc`	close current buffer
`:bca`	close all buffers
`:bco`	close all but current buffer
`:bn`	next buffer
`␣b`	open buffer picker
`ga`	go to last accessed/alternate buffer
`gm`	go to last modified/alternate buffer
`gn`	go to next buffer
`gp`	go to previous buffer

2.3.5 Views

Ctrl-w and `␣w` are synonymous.

`␣ws / ␣wv`	split horizontal / vertical, current buffer
`␣wns / ␣wnv`	split horizontal / vertical, new buffer
`␣wq`	close current split
`␣wo`	close all but current split
`␣ww`	next split
`␣wh/j/k/l`	move to buffer left / up / down / right
`␣wH/J/K/L`	swap split with buffer on left / up / down / right
`␣wt`	transpose split

2.3.5.1 View Movement

Commands shown with **z** prefix. The prefix is not used in sticky mode, which is a view-only navigation mode appropriate for browsing a file without editing.

`Z`	enter sticky mode, exit with Esc
`zz, zc`	align to center
`zt`	align to top
`zb`	align to bottom
`zm`	align to middle horizontally
`zj`	scroll down
`zk`	scroll up

2.3.6 Help

`:tutor`	open tutorial
`␣?`	open command palette

2.4 Movement

2.4.1 Cursor Movement

Normal Mode: motion replaces selection
Select Mode: motion extends selection

`h/j/k/l`	left / up / down / right
`gh, g|`	beginning of line
`<nn>g|`	column <nn>
`gl`	end of line
`gg`	top of file
`<nn>G, g<nn>g`	line <nn>
`ge`	bottom of file
`gw`	two-char labels on words, label to go to word
`g.`	to last modification in current file
`gj`	down textual line
`gk`	up textual line
`gs`	first non-white-space char
`gt`	top of screen
`gc`	middle of screen
`gb`	bottom of screen

2.4.2 By Language Server Protocol

Requires LSP support.

`gd`	go to definition
`gy`	go to type definition
`gr`	go to references
`gi`	go to implementation
`]d`	next diagnostic
`[d`	prior diagnostic
`]D`	last diagnostic
`[D`	first diagnostic

2.4.3 By Treesitter - Syntax

Requires Treesitter support.

```
]f, [f – to next, prior function
]t, [t – to next, prior type definition
]T, [T – to next, prior test
]a, [a – to next, prior arg
]c, [c – to next, prior comment
]g, [g – to next, prior change
]G, [G – to last, first change

Alt-e – move to end of parent node in syntax
        tree
Alt-b – move to start of parent node in syntax
        tree
```

2.4.4 By Page

```
Ctrl-b – page up
Ctrl-f – page down
Ctrl-u – half page up
Ctrl-d – half page down
```

2.5 Selection

Selection: a range of characters between anchor and cursor

Normal Mode: move and select

Select Mode: move and extend selection

2.5.1 Operations

```
     % – select whole file
Alt-; – swap anchor and cursor
Alt-: – selection to normal direction (cursor at
        end)
Alt-o – expand selection syntax-aware
Alt-i – shrink selection
    ; – collapse selection(s) to cursor(s)
```

2.5.2 By TextObjects

```
ma<ch> / mi<ch> – match around / inside the
                  object indicated by <ch> below:

          w / W – word / WORD
              p – paragraph
  (, [, ', etc.– specified surround pairs
              m –  closest surround pair
              f – function
              t – type or class
              a – argument/parameter
              c – comment
              T – test
              g – change git hunk
```

2.5.3 By Syntactic Objects

```
  w / W – to start of next word / WORD
  e / E – to end of current word / WORD
  b / B – to start of current word / WORD
      x – current line, extend by line
      X – extend to line
  Alt-x – shrink to line bounds
     ]p – to next paragraph
     [p – to prior paragraph
```

2.5.4 By Treesitter - Syntax

Requires Treesitter support.

```
  Alt-o – expand selection to parent syntax node
  Alt-i – shrink syntax tree object selection
  Alt-p – select previous sibling node in syntax
          tree
  Alt-n – select next sibling node in syntax tree
  Alt-a – select all sibling nodes in syntax tree
  Alt-I – select all children nodes in syntax tree
```

2.5.5 By Character Value

Lower case: forward

Upper case: backward

```
f<ch>, F<ch> – to <ch> inclusive (find)
t<ch>, T<ch> – to <ch> exclusive (till)
      Alt-.  – repeat last find / till
```

2.6 Select Mode

Movement: extends selection

Search: adds to selection

```
      v – toggle select mode
    Esc – return to normal
      ) – cycle primary selection forward
      ( – cycle primary selection backward
 Alt-,  – remove primary selection
```

2.7 Multiple Selections

Multiple independent cursors / selections, one is *primary*.

2.7.1 Creating

Create multiple selections from selection.

```
  s<regex> – matches become selections
         S – split on match
     Alt-s – split on newlines
C / Alt-C – add selection below / above
```

2.7.2 Operations

```
              & – align on primary cursor
  Alt-<minus> – merge selections
  Alt-<under> – merge consecutive selections
            , – remove all except primary
                selection
       Alt-,  – remove primary selection
        ( / ) – rotate primary backwards /
                forwards
Alt-( / Alt-) – rotate content backward / forward
            K – keep selections matching the
                regex
        Alt-K – remove selections matching the
                regex
```

2.8 Alter Buffer Content

2.8.1 Insert

```
     i – before selection
     a – after selection
     I – at start of line
     A – at end of line
     o – add line and insert below cursor
     O – add line and insert above cursor
   Esc – end insert (return to normal)
     . – repeat last insert
```

2.8.2 Add

```
    ]␣ – newline below
    [␣ – newline above
ms<ch> – add delim <ch> around selection
```

2.8.3 Delete

```
     d – selection -> yank buf, delete selection
  Alt-d – delete, no save
md<ch> – delete delim <ch> around selection
```

2.8.4 Change

```
     c – selection -> yank buf, change
         selection
  Alt-c – change, no save
      = – format by LSP
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.8.5 Indent Lines

```
  > – Indent line(s) containing selection
  < – Undent line(s) containing selection
```

2.8.6 Change Case

Change case of all letters in selection

```
     ~ – change case
     ` – set lowercase
  Alt-` – set uppercase
```

2.8.7 Comments

All apply to selection.

```
␣c, Ctrl-c – Toggle comment
        ␣C – Toggle block comment
   ␣Alt-C – Toggle line comment
```

2.8.8 Increment / Decrement

```
  Ctrl-a – increment the selected number
  Ctrl-x – decrement the selected number
```

2.8.9 Miscellaneous

```
             J – join lines in a selection
       Alt-J – join lines inside selection and
               select the inserted space
     <under> – trim whitespace from selection
:reflow <width> – wrap selection to <width>,
               default 80
       :sort – sort ranges in selection
     :format – format file using external
               formatter / language server
```

2.9 Copy / Paste / Replace

```
       y – selection -> yank buf
       p – paste yank buf after the cursor
       P – paste yank buf before the cursor
      ␣y – yank selection(s) -> system clipboard
      ␣Y – yank main selection -> system clipboard
  ␣p / ␣P – paste clipboard after / before
            selections(s)
      ␣R – replace selection(s) with clipboard
    r<ch> – replace selection with <ch>
       R – replace selection with yank buf
       " – select register to yank to or paste from
```

2.10 Search

```
  /<regex> – search forward for regex
  ?<regex> – search backward for regex
     n, N – next, previous match
        * – search for current selection, respect
            word boundaries
    Alt-* – search for current selection
```

2.11 Registers

Identified by single char <ch>

```
   "<ch> – change to reg <ch>
  "<ch>y – yank into reg <ch>
  "<ch>p – paste from reg <ch>
  "<ch>R – replace with reg <ch>
```

2.12 Macros

```
  "<ch>Q – toggle capture to reg <ch>, default @
  "<ch>q – play macro in reg <ch>, default @
```

2.13 Jumplists

```
  Ctrl-s – save current position to jumplist
  Ctrl-i – move forward in jumplist
  Ctrl-o – move backwards in jumplist
      ␣j – open jumplist picker
```

2.14 Match Mode

With regard to balanced delimiters.

```
        mm – go to matching delim
     mi<ch> – match inside delim <ch>
     ma<ch> – match around delim <ch>
     ms<ch> – add delim <ch> around selection
     md<ch> – delete delim <ch> around selection
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.15 Shell

All commands pipe each selection to shell command.

`|`	replace selection(s) with output
`Alt-|`	ignore output
`!`	insert output before each selection(s)
`Alt-!`	append output after each selection(s)
`$`	keep selection(s) where command returned 0

2.16 Approaching an IDE

`␣G`	debug - experimental
`␣k`	show documentation for item under cursor
`␣s`	open document symbol picker
`␣S`	open workspace symbol picker
`␣d`	open document diagnostics picker
`␣D`	open workspace diagnostics picker
`␣r`	rename symbol
`␣a`	apply code action
`␣h`	select symbol references for symbol under cursor

2.17 Editor Configuration

`:config-open`	open the config file
`:config-open-workspace`	open the workspace config file
`:config-reload`	reload the config file

2.18 Miscellaneous

`␣'`	open last picker
`␣/`	open global search in workspace folder picker

3 Commands in Specific Contexts

3.1 Insert Mode Editing

Navigation keys shown.

`Ctrl-s`	commit undo checkpoint
`Ctrl-x`	autocomplete
`Ctrl-r`	insert a register content
`Ctrl-w, Alt-<bksp>`	delete previous word
`Alt-d, Alt-<del>`	delete next word
`Ctrl-u`	delete to start of line
`Ctrl-k`	delete to end of line
`Ctrl-h, <bksp>, Shift-<bksp>`	delete previous char
`Ctrl-d, <del>`	delete next char
`Ctrl-j, <enter>`	insert new line
`<Up>, <Down>, <Left>, <Right>, <PageUp>, <PageDown>, <Home>, <End>`	usual meaning but discouraged

3.2 Command Line Editing

`Esc, Ctrl-c`	close prompt
`<enter>`	open selected
`<tab>`	select next completion item
`<backtab>`	select previous completion item
`Alt-b`	backward a word
`Ctrl-b`	backward a char
`Alt-f`	forward a word
`Ctrl-f`	forward a char
`Ctrl-e`	to prompt end
`Ctrl-a`	to prompt start
`Ctrl-w, Ctrl-<bksp>`	delete previous word
`Alt-d, Ctrl-<del>`	delete next word
`Ctrl-u`	delete to start of line
`Ctrl-k`	delete to end of line
`<bksp>, Ctrl-h`	delete previous char
`<del>, Ctrl-d`	delete next char
`Ctrl-s`	insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later)
`Ctrl-p`	select previous history
`Ctrl-n`	select next history
`Ctrl-r`	insert the content of the register selected by following input char

3.3 Pickers

Navigation keys shown.

`Shift-<tab>, Ctrl-p, <Up>`	previous entry
`<tab>, Ctrl-n, <Down>`	next entry
`<Home>`	to first entry
`<End>`	to last entry
`Ctrl-u, <PageUp>`	page up
`Ctrl-d, <PageDown>`	page down
`<enter>`	open selected
`Alt-<enter>`	open selected in the background without closing the picker
`Ctrl-s`	open horizontally
`Ctrl-v`	open vertically
`Ctrl-t`	toggle preview
`Esc, Ctrl-c`	close picker

3.4 Popups

Displays documentation for item under cursor.

```
   Ctrl-u – scroll up
   Ctrl-d – scroll down
```

3.5 Completion Menu

Displays documentation for the selected completion item. Any other keypresses result in the completion being accepted.

```
Shift-Tab, Ctrl-p – previous entry
      Tab, Ctrl-n – next entry
          <enter> – close menu and accept
                    completion
           Ctrl-c – close menu and reject
                    completion
```

3.6 Signature-help Popup

Displays the signature of the selected completion item.

```
    Alt-p – previous signature
    Alt-n – next signature
```

4 Command Index

- `␣'` – open last picker **(2.18)**
- `␣/` – open global search in workspace folder picker **(2.18)**
- `␣?` – open command palette **(2.3.6)**
- `␣Alt-C` – Toggle line comment **(2.8.7)**
- `␣C` – Toggle block comment **(2.8.7)**
- `␣D` – open workspace diagnostics picker **(2.16)**
- `␣F` – open file picker at current working directory **(2.3.3)**
- `␣G` – debug - experimental **(2.16)**
- `␣R` – replace selection(s) with clipboard **(2.9)**
- `␣S` – open workspace symbol picker **(2.16)**
- `␣Y` – yank main selection -> system clipboard **(2.9)**
- `␣a` – apply code action **(2.16)**
- `␣b` – open buffer picker **(2.3.4)**
- `␣c` – Toggle comment **(2.8.7)**
- `␣d` – open document diagnostics picker **(2.16)**
- `␣f` – open file picker at LSP workspace root **(2.3.3)**
- `␣g` – open changed file picker **(2.3.3)**
- `␣h` – select symbol references for symbol under cursor **(2.16)**
- `␣j` – open jumplist picker **(2.13)**
- `␣k` – show documentation for item under cursor **(2.16)**
- `␣p / ␣P` – paste clipboard after / before selections(s) **(2.9)**
- `␣r` – rename symbol **(2.16)**
- `␣s` – open document symbol picker **(2.16)**
- `␣wF` – open/create file(s) under selection(s) in vertical split **(2.3.3)**
- `␣wH/J/K/L` – swap split with buffer on left / up / down / right **(2.3.5)**
- `␣wf` – open/create file(s) under selection(s) in horizontal split **(2.3.3)**
- `␣wh/j/k/l` – move to buffer left / up / down / right **(2.3.5)**
- `␣wns / ␣wnv` – split horizontal / vertical, new buffer **(2.3.5)**
- `␣wo` – close all but current split **(2.3.5)**
- `␣wq` – close current split **(2.3.5)**
- `␣ws / ␣wv` – split horizontal / vertical, current buffer **(2.3.5)**
- `␣wt` – transpose split **(2.3.5)**
- `␣ww` – next split **(2.3.5)**
- `␣y` – yank selection(s) -> system clipboard **(2.9)**
- `!` – insert output before each selection(s) **(2.15)**
- `"` – select register to yank to or paste from **(2.9)**
- `"<ch>` – change to reg <ch> **(2.11)**
- `"<ch>Q` – toggle capture to reg <ch>, default @ **(2.12)**
- `"<ch>R` – replace with reg <ch> **(2.11)**
- `"<ch>p` – paste from reg <ch> **(2.11)**
- `"<ch>q` – play macro in reg <ch>, default @ **(2.12)**
- `"<ch>y` – yank into reg <ch> **(2.11)**
- `$` – keep selection(s) where command returned 0 **(2.15)**
- `%` – select whole file **(2.5.1)**
- `&` – align on primary cursor **(2.7.2)**
- `'` – specified surround pairs **(2.5.2)**
- `(` – cycle primary selection backward **(2.6)**
- `(` – specified surround pairs **(2.5.2)**
- `( / )` – rotate primary backwards / forwards **(2.7.2)**
- `)` – cycle primary selection forward **(2.6)**
- `*` – search for current selection, respect word boundaries **(2.10)**
- `,` – remove all except primary selection **(2.7.2)**
- `.` – repeat last insert **(2.8.1)**
- `/<regex>` – search forward for regex **(2.10)**
- `:bc` – close current buffer **(2.3.4)**
- `:bca` – close all buffers **(2.3.4)**
- `:bco` – close all but current buffer **(2.3.4)**
- `:bn` – next buffer **(2.3.4)**
- `:config-open` – open the config file **(2.17)**
- `:config-open-workspace` – open the workspace config file **(2.17)**
- `:config-reload` – reload the config file **(2.17)**
- `:ear / :lat` – move backward / forward in history by step count or time span (1s, 2m, 3h, 4d) **(2.3.1)**
- `:format` – format file using external formatter / language server **(2.8.9)**
- `:hs <file>` – open/create <file> in new horizontal split **(2.3.3)**
- `:n` – create new scratch buffer **(2.3.4)**
- `:o <file>` – open <file> in new buffer **(2.3.3)**
- `:q` – quit current buffer, exits if last **(2.3.2)**
- `:reflow <width>` – wrap selection to <width>, default 80 **(2.8.9)**
- `:sort` – sort ranges in selection **(2.8.9)**
- `:tutor` – open tutorial **(2.3.6)**
- `:vs <file>` – open/create <file> in new vertical split **(2.3.3)**
- `:w <file>` – write current buffer to <file> **(2.3.3)**
- `:wq` – write current buffer and quit **(2.3.2)**
- `:wq <file>` – write current buffer to <file> and quit **(2.3.2)**
- `:wqa` – write all buffer(s) and quit **(2.3.2)**
- `;` – collapse selection(s) to cursor(s) **(2.5.1)**
- `<` – Undent line(s) containing selection **(2.8.5)**
- `<Down>` – next entry **(3.3)**
- `<Down>` – usual meaning but discouraged **(3.1)**
- `<End>` – to last entry **(3.3)**
- `<End>` – usual meaning but discouraged **(3.1)**
- `<Home>` – to first entry **(3.3)**
- `<Home>` – usual meaning but discouraged **(3.1)**
- `<Left>` – usual meaning but discouraged **(3.1)**
- `<PageDown>` – page down **(3.3)**
- `<PageDown>` – usual meaning but discouraged **(3.1)**
- `<PageUp>` – page up **(3.3)**
- `<PageUp>` – usual meaning but discouraged **(3.1)**
- `<Right>` – usual meaning but discouraged **(3.1)**
- `<Up>` – previous entry **(3.3)**
- `<Up>` – usual meaning but discouraged **(3.1)**
- `<backtab>` – select previous completion item **(3.2)**
- `<bksp>` – delete previous char **(3.1)**
- `<bksp>` – delete previous char **(3.2)**
- `<del>` – delete next char **(3.1)**
- `<del>` – delete next char **(3.2)**

- **<enter>** – close menu and accept completion **(3.5)**
- **<enter>** – insert new line **(3.1)**
- **<enter>** – open selected **(3.2)**
- **<enter>** – open selected **(3.3)**
- **<enter>** – open selected in current view **(2.3.3.1)**
- **<nn><cmd>** – repeat <cmd> <nn> times **(2.3.1)**
- **<nn>G** – line <nn> **(2.4.1)**
- **<nn>g|** – column <nn> **(2.4.1)**
- **<tab>** – next entry **(3.3)**
- **<tab>** – select next completion item **(3.2)**
- **<under>** – trim whitespace from selection **(2.8.9)**
- **=** – format by LSP **(2.8.4)**
- **>** – Indent line(s) containing selection **(2.8.5)**
- **?<regex>** – search backward for regex **(2.10)**
- **A** – at end of line **(2.8.1)**
- **Alt-!** – append output after each selection(s) **(2.15)**
- **Alt-(/ Alt-)** – rotate content backward / forward **(2.7.2)**
- **Alt-*** – search for current selection **(2.10)**
- **Alt-,** – remove primary selection **(2.6)**
- **Alt-,** – remove primary selection **(2.7.2)**
- **Alt-.** – repeat last find / till **(2.5.5)**
- **Alt-:** – selection to normal direction (cursor at end) **(2.5.1)**
- **Alt-;** – swap anchor and cursor **(2.5.1)**
- **Alt-<bksp>** – delete previous word **(3.1)**
- **Alt-<del>** – delete next word **(3.1)**
- **Alt-<enter>** – open selected in the background without closing the picker **(3.3)**
- **Alt-<minus>** – merge selections **(2.7.2)**
- **Alt-<under>** – merge consecutive selections **(2.7.2)**
- **Alt-I** – select all children nodes in syntax tree **(2.5.4)**
- **Alt-J** – join lines inside selection and select the inserted space **(2.8.9)**
- **Alt-K** – remove selections matching the regex **(2.7.2)**
- **Alt-`** – set uppercase **(2.8.6)**
- **Alt-a** – select all sibling nodes in syntax tree **(2.5.4)**
- **Alt-b** – backward a word **(3.2)**
- **Alt-b** – move to start of parent node in syntax tree **(2.4.3)**
- **Alt-c** – change, no save **(2.8.4)**
- **Alt-d** – delete next word **(3.1)**
- **Alt-d** – delete next word **(3.2)**
- **Alt-d** – delete, no save **(2.8.3)**
- **Alt-e** – move to end of parent node in syntax tree **(2.4.3)**
- **Alt-f** – forward a word **(3.2)**
- **Alt-i** – shrink selection **(2.5.1)**
- **Alt-i** – shrink syntax tree object selection **(2.5.4)**
- **Alt-n** – next signature **(3.6)**
- **Alt-n** – select next sibling node in syntax tree **(2.5.4)**
- **Alt-o** – expand selection syntax-aware **(2.5.1)**
- **Alt-o** – expand selection to parent syntax node **(2.5.4)**
- **Alt-p** – previous signature **(3.6)**
- **Alt-p** – select previous sibling node in syntax tree **(2.5.4)**
- **Alt-s** – split on newlines **(2.7.1)**
- **Alt-u / Alt-U** – move backward / forward in tree history **(2.3.1)**
- **Alt-x** – shrink to line bounds **(2.5.3)**
- **Alt-|** – ignore output **(2.15)**
- **C / Alt-C** – add selection below / above **(2.7.1)**
- **Ctrl-<bksp>** – delete previous word **(3.2)**
- **Ctrl-<del>** – delete next word **(3.2)**
- **Ctrl-a** – increment the selected number **(2.8.8)**
- **Ctrl-a** – to prompt start **(3.2)**
- **Ctrl-b** – backward a char **(3.2)**
- **Ctrl-b** – page up **(2.4.4)**
- **Ctrl-c** – Toggle comment **(2.8.7)**
- **Ctrl-c** – close menu and reject completion **(3.5)**
- **Ctrl-c** – close picker **(3.3)**
- **Ctrl-c** – close prompt **(3.2)**
- **Ctrl-d** – delete next char **(3.1)**
- **Ctrl-d** – delete next char **(3.2)**
- **Ctrl-d** – half page down **(2.4.4)**
- **Ctrl-d** – page down **(3.3)**
- **Ctrl-d** – scroll down **(3.4)**
- **Ctrl-e** – to prompt end **(3.2)**
- **Ctrl-f** – forward a char **(3.2)**
- **Ctrl-f** – page down **(2.4.4)**
- **Ctrl-h** – delete previous char **(3.1)**
- **Ctrl-h** – delete previous char **(3.2)**
- **Ctrl-i** – move forward in jumplist **(2.13)**
- **Ctrl-j** – insert new line **(3.1)**
- **Ctrl-k** – delete to end of line **(3.1)**
- **Ctrl-k** – delete to end of line **(3.2)**
- **Ctrl-n** – next entry **(3.3)**
- **Ctrl-n** – next entry **(3.5)**
- **Ctrl-n** – select next history **(3.2)**
- **Ctrl-o** – move backwards in jumplist **(2.13)**
- **Ctrl-p** – previous entry **(3.3)**
- **Ctrl-p** – previous entry **(3.5)**
- **Ctrl-p** – select previous history **(3.2)**
- **Ctrl-r** – insert a register content **(3.1)**
- **Ctrl-r** – insert the content of the register selected by following input char **(3.2)**
- **Ctrl-s** – commit undo checkpoint **(3.1)**
- **Ctrl-s** – insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later) **(3.2)**
- **Ctrl-s** – open horizontally **(3.3)**
- **Ctrl-s** – open selected in new horizontal split **(2.3.3.1)**
- **Ctrl-s** – save current position to jumplist **(2.13)**
- **Ctrl-t** – toggle preview **(3.3)**
- **Ctrl-u** – delete to start of line **(3.1)**
- **Ctrl-u** – delete to start of line **(3.2)**
- **Ctrl-u** – half page up **(2.4.4)**
- **Ctrl-u** – page up **(3.3)**
- **Ctrl-u** – scroll up **(3.4)**
- **Ctrl-v** – open selected in new vertical split **(2.3.3.1)**
- **Ctrl-v** – open vertically **(3.3)**
- **Ctrl-w** – delete previous word **(3.1)**
- **Ctrl-w** – delete previous word **(3.2)**
- **Ctrl-x** – autocomplete **(3.1)**
- **Ctrl-x** – decrement the selected number **(2.8.8)**
- **Esc** – close picker **(3.3)**
- **Esc** – close prompt **(3.2)**
- **Esc** – end insert (return to normal) **(2.8.1)**
- **Esc** – return to normal **(2.6)**
- **Esc** – return to normal mode **(2.3.1)**
- **F<ch>** – to <ch> inclusive (find) **(2.5.5)**
- **I** – at start of line **(2.8.1)**
- **J** – join lines in a selection **(2.8.9)**
- **K** – keep selections matching the regex **(2.7.2)**
- **N** – next, previous match **(2.10)**
- **O** – add line and insert above cursor **(2.8.1)**
- **P** – paste yank buf before the cursor **(2.9)**

- **R** – replace selection with yank buf **(2.9)**
- **S** – split on match **(2.7.1)**
- **Shift-<bksp>** – delete previous char **(3.1)**
- **Shift-<tab>** – previous entry **(3.3)**
- **Shift-Tab** – previous entry **(3.5)**
- **T** – test **(2.5.2)**
- **T<ch>** – to <ch> exclusive (till) **(2.5.5)**
- **Tab** – next entry **(3.5)**
- **X** – extend to line **(2.5.3)**
- **Z** – enter sticky mode, exit with Esc **(2.3.5.1)**
- **[␣** – newline above **(2.8.2)**
- **[** – specified surround pairs **(2.5.2)**
- **[D** – first diagnostic **(2.4.2)**
- **[G** – to last, first change **(2.4.3)**
- **[T** – to next, prior test **(2.4.3)**
- **[a** – to next, prior arg **(2.4.3)**
- **[c** – to next, prior comment **(2.4.3)**
- **[d** – prior diagnostic **(2.4.2)**
- **[f** – to next, prior function **(2.4.3)**
- **[g** – to next, prior change **(2.4.3)**
- **[p** – to prior paragraph **(2.5.3)**
- **[t** – to next, prior type definition **(2.4.3)**
- **]␣** – newline below **(2.8.2)**
- **]D** – last diagnostic **(2.4.2)**
- **]G** – to last, first change **(2.4.3)**
- **]T** – to next, prior test **(2.4.3)**
- **]a** – to next, prior arg **(2.4.3)**
- **]c** – to next, prior comment **(2.4.3)**
- **]d** – next diagnostic **(2.4.2)**
- **]f** – to next, prior function **(2.4.3)**
- **]g** – to next, prior change **(2.4.3)**
- **]p** – to next paragraph **(2.5.3)**
- **]t** – to next, prior type definition **(2.4.3)**
- **`** – set lowercase **(2.8.6)**
- **a** – after selection **(2.8.1)**
- **a** – argument/parameter **(2.5.2)**
- **b / B** – to start of current word / WORD **(2.5.3)**
- **c** – comment **(2.5.2)**
- **c** – selection -> yank buf, change selection **(2.8.4)**
- **d** – selection -> yank buf, delete selection **(2.8.3)**
- **e / E** – to end of current word / WORD **(2.5.3)**
- **etc.** – specified surround pairs **(2.5.2)**
- **f** – function **(2.5.2)**
- **f<ch>** – to <ch> inclusive (find) **(2.5.5)**

- **g** – change git hunk **(2.5.2)**
- **g.** – to last modification in current file **(2.4.1)**
- **g<nn>g** – line <nn> **(2.4.1)**
- **ga** – go to last accessed/alternate buffer **(2.3.4)**
- **gb** – bottom of screen **(2.4.1)**
- **gc** – middle of screen **(2.4.1)**
- **gd** – go to definition **(2.4.2)**
- **ge** – bottom of file **(2.4.1)**
- **gf** – open/create file(s) under selection, open url under selection. **(2.3.3)**
- **gg** – top of file **(2.4.1)**
- **gh** – beginning of line **(2.4.1)**
- **gi** – go to implementation **(2.4.2)**
- **gj** – down textual line **(2.4.1)**
- **gk** – up textual line **(2.4.1)**
- **gl** – end of line **(2.4.1)**
- **gm** – go to last modified/alternate buffer **(2.3.4)**
- **gn** – go to next buffer **(2.3.4)**
- **gp** – go to previous buffer **(2.3.4)**
- **gr** – go to references **(2.4.2)**
- **gs** – first non-white-space char **(2.4.1)**
- **gt** – top of screen **(2.4.1)**
- **gw** – two-char labels on words, label to go to word **(2.4.1)**
- **gy** – go to type definition **(2.4.2)**
- **g|** – beginning of line **(2.4.1)**
- **h/j/k/l** – left / up / down / right **(2.4.1)**
- **i** – before selection **(2.8.1)**
- **m** – closest surround pair **(2.5.2)**
- **ma<ch>** – match around delim <ch> **(2.14)**
- **ma<ch> / mi<ch>** – match around / inside the object indicated by <ch> below: **(2.5.2)**
- **md<ch>** – delete delim <ch> around selection **(2.14)**
- **md<ch>** – delete delim <ch> around selection **(2.8.3)**
- **mi<ch>** – match inside delim <ch> **(2.14)**
- **mm** – go to matching delim **(2.14)**
- **mr<ch1><ch2>** – replace delim <ch1> with <ch2> **(2.14)**
- **mr<ch1><ch2>** – replace delim <ch1> with <ch2> **(2.8.4)**
- **ms<ch>** – add delim <ch> around selection **(2.14)**
- **ms<ch>** – add delim <ch> around selection **(2.8.2)**
- **n** – next, previous match **(2.10)**

- **o** – add line and insert below cursor **(2.8.1)**
- **p** – paragraph **(2.5.2)**
- **p** – paste yank buf after the cursor **(2.9)**
- **r<ch>** – replace selection with <ch> **(2.9)**
- **s<regex>** – matches become selections **(2.7.1)**
- **t** – type or class **(2.5.2)**
- **t<ch>** – to <ch> exclusive (till) **(2.5.5)**
- **u / U** – undo / redo change in linear history **(2.3.1)**
- **v** – toggle select mode **(2.6)**
- **w / W** – to start of next word / WORD **(2.5.3)**
- **w / W** – word / WORD **(2.5.2)**
- **x** – current line, extend by line **(2.5.3)**
- **y** – selection -> yank buf **(2.9)**
- **zb** – align to bottom **(2.3.5.1)**
- **zc** – align to center **(2.3.5.1)**
- **zj** – scroll down **(2.3.5.1)**
- **zk** – scroll up **(2.3.5.1)**
- **zm** – align to middle horizontally **(2.3.5.1)**
- **zt** – align to top **(2.3.5.1)**
- **zz** – align to center **(2.3.5.1)**
- **|** – replace selection(s) with output **(2.15)**
- **~** – change case **(2.8.6)**