Bill's Helix Cheat Sheet / Command Reference

1 Introduction

- Document version: 1.0.0-beta, 15-Apr-2026
- Based on Helix version: 25.07.1.
- Distributed at: https://github.com/wrwetzel/Helix-Cheat-Sheet
- © 2026 Bill Wetzel - Licensed under CC BY 4.0 https://creativecommons.org/licenses/by/4.0/

1.1 Definitions

- **file** - the actual data on storage device
- **buffers** - data from one or more files loaded into memory
- **view** - one or more visual areas on screen showing one or more buffers
- **workspace** - the directory from which Helix was launched
- **under selection** - the entire word containing the cursor, not just the selection
- **alternate buffer** - the previous active buffer
- **textual line** - text as defined by the newline character
- **visual line** - what appears on screen after word-wrapping
- **range** - a selection; one in single-selection, multiple in multi-selection

1.2 Typographic Conventions

- **`word`** - alphanumeric, punctuation-delimited
- **`WORD`** - whitespace-delimited
- **`Ctrl-c`** - Ctrl and c key pressed simultaneous.
- **`Alt-c`** - Alt and c key pressed simultaneous.
- Some Alt and Ctrl characters may conflict with terminal capture and require terminal configuration change.
- **`␣c`** is space followed by the character c.
- Metavars **`<regex>`**, **`<file>`** and **`<ch>`** represent user input. The angle-brackets are not part of the input.
- **`␣`**, **`<minus>`**, and **`<under>`** used for clarity. **`<enter>`**, **`<del>`**, **`<bksp>`**, etc. used for non-printing control characters.
- Commands are separated from definitions by a dash. Synonyms are separated by commas. Related commands are separated by slashes. The separators are never part of the command though commands may include a dash, comma, or slash.

1.3 Launching

- **`helix`**
- **`helix`** `<file>`
- **`helix`** `<file1> <file2> … <filen>`
- **`helix`** `–help`
- **`hx`** `in some distributions or by alias`

1.4 Basics

Editing paradigm: select first, action second. *mode* and *count* are optional.

```
[mode][count][select][command]
```

1.4.1 Example

```
v3wd
          v – enter select mode
          3 – select 3
          w – words
          d – delete
```

1.4.2 Samples

```
         wd – delete word
         xc – change line
         %y – yank entire file
```

1.5 Regular Expressions

Helix uses Rust's regex. Escape metachars with backslash when searching for literal value.

```
          . – any character
          * – zero or more
          + – one or more
          ? – zero or one / lazy modifier
          ^ – start of line / negation in class
          $ – end of line
        ( ) – capture group
        [ ] – character class
        { } – repetition count
          | – alternation
          \ – escape character itself
```

2 Primary Commands

2.1 Essentials

`u / U`	undo / redo change in linear history
`Alt-u / Alt-U`	move backward / forward in tree history
`:ear / :lat`	move backward / forward in history by step count or time span (1s, 2m, 3h, 4d)
`<nn><cmd>`	repeat <cmd> <nn> times
`Esc`	return to normal mode

2.1.1 Quit

Add **!** suffix to force operation.

`:wq`	write current buffer and quit
`:wq <file>`	write current buffer to <file> and quit
`:wqa`	write all buffer(s) and quit
`:q`	quit current buffer, exits if last

2.1.2 Files

`:o <file>`	open <file> in new buffer
`:w <file>`	write current buffer to <file>
`:hs <file>`	open/create <file> in new horizontal split
`:vs <file>`	open/create <file> in new vertical split
`␣wf`	open/create file(s) under selection(s) in horizontal split
`␣wF`	open/create file(s) under selection(s) in vertical split
`gf`	open/create file(s) under selection, open url under selection.
`␣f`	open file picker at LSP workspace root
`␣F`	open file picker at current working directory
`␣g`	open changed file picker

2.1.2.1 File Picker

All pickers, here and elsewhere, are *fuzzy* - they tolerate gaps in the input, ranking closer matches higher.

`<enter>`	open selected in current view
`Ctrl-s`	open selected in new horizontal split
`Ctrl-v`	open selected in new vertical split

2.1.3 Buffers

Add **!** suffix to force operation. Buffers named by file they contain.

`:n`	create new scratch buffer
`:bc`	close current buffer
`:bca`	close all buffers
`:bco`	close all but current buffer
`:bn`	next buffer
`␣b`	open buffer picker
`ga`	go to last accessed/alternate buffer
`gm`	go to last modified/alternate buffer
`gn`	go to next buffer
`gp`	go to previous buffer

2.1.4 Views

Ctrl-w and `␣w` are synonymous.

`␣ws / ␣wv`	split horizontal / vertical, current buffer
`␣wns / ␣wnv`	split horizontal / vertical, new buffer
`␣wq`	close current split
`␣wo`	close all but current split
`␣ww`	next split
`␣wh/j/k/l`	move to buffer left / up / down / right
`␣wH/J/K/L`	swap split with buffer on left / up / down / right
`␣wt`	transpose split

2.1.4.1 View Movement

Commands shown with **z** prefix. The prefix is not used in sticky mode, which is a view-only navigation mode appropriate for browsing a file without editing.

`Z`	enter sticky mode, exit with Esc
`zz, zc`	align to center
`zt`	align to top
`zb`	align to bottom
`zm`	align to middle horizontally
`zj`	scroll down
`zk`	scroll up

2.1.5 Help

`:tutor`	open tutorial
`␣?`	open command palette

2.2 Movement

2.2.1 Cursor Movement

Normal Mode: motion replaces selection
Select Mode: motion extends selection

```
      h/j/k/l – left / up / down / right
       gh, g| – beginning of line
       <nn>g| – column <nn>
           gl – end of line
           gg – top of file
<nn>G, g<nn>g – line <nn>
           ge – bottom of file
           gw – two-char labels on words, label to go
                to word

           g.– to last modification in current file
           gj – down textual line
           gk – up textual line

           gs – first non-white-space char
           gt – top of screen
           gc – middle of screen
           gb – bottom of screen
```

2.2.2 By Language Server Protocol

Requires LSP support.

```
         gd – go to definition
         gy – go to type definition
         gr – go to references
         gi – go to implementation

         ]d – next diagnostic
         [d – prior diagnostic
         ]D – last diagnostic
         [D – first diagnostic
```

2.2.3 By Treesitter - Syntax

Requires Treesitter support.

```
      ]f, [f – to next, prior function
      ]t, [t – to next, prior type definition
      ]T, [T – to next, prior test
      ]a, [a – to next, prior arg
      ]c, [c – to next, prior comment
      ]g, [g – to next, prior change
      ]G, [G – to last, first change

       Alt-e – move to end of parent node in syntax
               tree
       Alt-b – move to start of parent node in syntax
               tree
```

2.2.4 By Page

```
      Ctrl-b – page up
      Ctrl-f – page down
      Ctrl-u – half page up
      Ctrl-d – half page down
```

2.3 Selection

Selection: a range of characters between anchor and cursor
Normal Mode: move and select
Select Mode: move and extend selection

2.3.1 Operations

```
          % – select whole file
     Alt-; – swap anchor and cursor
     Alt-: – selection to normal direction (cursor at
             end)
    Alt-o – expand selection syntax-aware
    Alt-i – shrink selection
        ; – collapse selection(s) to cursor(s)
```

2.3.2 By TextObjects

```
ma<ch> / mi<ch> – match around / inside the object
                  indicated by <ch> below:

          w / W – word / WORD
              p – paragraph
  (, [, ', etc.– specified surround pairs
              m –  closest surround pair
              f – function
              t – type or class
              a – argument/parameter
              c – comment
              T – test
              g – change git hunk
```

2.3.3 By Syntactic Objects

```
      w / W – to start of next word / WORD
      e / E – to end of current word / WORD
      b / B – to start of current word / WORD
          x – current line, extend by line
          X – extend to line
      Alt-x – shrink to line bounds
         ]p – to next paragraph
         [p – to prior paragraph
```

2.3.4 By Treesitter - Syntax

Requires Treesitter support.

```
      Alt-o – expand selection to parent syntax node
      Alt-i – shrink syntax tree object selection
      Alt-p – select previous sibling node in syntax
              tree
      Alt-n – select next sibling node in syntax tree
      Alt-a – select all sibling nodes in syntax tree
      Alt-I – select all children nodes in syntax tree
```

2.3.5 By Character Value

Lower case: forward
Upper case: backward

```
  f<ch>, F<ch> – to <ch> inclusive (find)
  t<ch>, T<ch> – to <ch> exclusive (till)
       Alt-.  – repeat last find / till
```

2.4 Select Mode

Movement: extends selection
Search: adds to selection

`v`	toggle select mode
`Esc`	return to normal
`)`	cycle primary selection forward
`(`	cycle primary selection backward
`Alt-,`	remove primary selection

2.5 Multiple Selections

Multiple independent cursors / selections, one is *primary*.

2.5.1 Creating

Create multiple selections from selection.

`s<regex>`	matches become selections
`S`	split on match
`Alt-s`	split on newlines
`C, Alt-C`	add selection below, above

2.5.2 Operations

`&`	align on primary cursor
`Alt-<minus>`	merge selections
`Alt-<under>`	merge consecutive selections
`,`	remove all except primary selection
`Alt-,`	remove primary selection
`( / )`	rotate primary backwards / forwards
`Alt-( / Alt-)`	rotate content backward / forward
`K`	keep selections matching the regex
`Alt-K`	remove selections matching the regex

2.6 Alter Buffer Content

2.6.1 Insert

`i`	before selection
`a`	after selection
`I`	at start of line
`A`	at end of line
`o`	add line and insert below cursor
`O`	add line and insert above cursor
`Esc`	end insert (return to normal)
`.`	repeat last insert

2.6.2 Add

`]␣`	newline below
`[␣`	newline above
`ms<ch>`	add delim <ch> around selection

2.6.3 Delete

`d`	selection -> yank buf, delete selection
`Alt-d`	delete, no save
`md<ch>`	delete delim <ch> around selection

2.6.4 Change

`c`	selection -> yank buf, change selection
`Alt-c`	change, no save
`=`	format by LSP
`mr<ch1><ch2>`	replace delim <ch1> with <ch2>

2.6.5 Indent Lines

`>`	Indent line(s) containing selection
`<`	Undent line(s) containing selection

2.6.6 Change Case

Change case of all letters in selection

`~`	change case
`` ` ``	set lowercase
`Alt-` `	set uppercase

2.6.7 Comments

All apply to selection.

`␣c, Ctrl-c`	Toggle comment
`␣C`	Toggle block comment
`␣Alt-C`	Toggle line comment

2.6.8 Increment / Decrement

`Ctrl-a`	increment the selected number
`Ctrl-x`	decrement the selected number

2.6.9 Miscellaneous

`J`	join lines in a selection
`Alt-J`	join lines inside selection and select the inserted space
`<under>`	trim whitespace from selection
`:reflow <width>`	wrap selection to <width>, default 80
`:sort`	sort ranges in selection
`:format`	format file using external formatter / language server

2.7 Copy / Paste / Replace

`y`	selection -> yank buf
`p`	paste yank buf after the cursor
`P`	paste yank buf before the cursor
`␣y`	yank selection(s) -> system clipboard
`␣Y`	yank main selection -> system clipboard
`␣p / ␣P`	paste clipboard after / before selections(s)
`␣R`	replace selection(s) with clipboard
`r<ch>`	replace selection with <ch>
`R`	replace selection with yank buf
`"`	select register to yank to or paste from

2.8 Search

```
/<regex> – search forward for regex
?<regex> – search backward for regex
    n, N – next, previous match
       * – search for current selection, respect
           word boundaries
   Alt-* – search for current selection
```

2.9 Registers

Identified by single char <ch>

```
  "<ch> – change to reg <ch>
 "<ch>y – yank into reg <ch>
 "<ch>p – paste from reg <ch>
 "<ch>R – replace with reg <ch>
```

2.10 Macros

```
 "<ch>Q – toggle capture to reg <ch>, default @
 "<ch>q – play macro in reg <ch>, default @
```

2.11 Jumplists

```
  Ctrl-s – save current position to jumplist
  Ctrl-i – move forward in jumplist
  Ctrl-o – move backwards in jumplist
      ␣j – open jumplist picker
```

2.12 Match Mode

With regard to balanced delimiters.

```
          mm – go to matching delim
     mi<ch> – match inside delim <ch>
     ma<ch> – match around delim <ch>
     ms<ch> – add delim <ch> around selection
     md<ch> – delete delim <ch> around selection
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.13 Shell

All commands pipe each selection to shell command.

```
     | – replace selection(s) with output
  Alt-| – ignore output
     ! – insert output before each selection(s)
  Alt-! – append output after each selection(s)
     $ – keep selection(s) where command
         returned 0
```

2.14 Approaching an IDE

```
  ␣G – debug - experimental
  ␣k – show documentation for item under
       cursor
  ␣s – open document symbol picker
  ␣S – open workspace symbol picker
  ␣d – open document diagnostics picker
  ␣D – open workspace diagnostics picker
  ␣r – rename symbol
  ␣a – apply code action
  ␣h – select symbol references for symbol
       under cursor
```

2.15 Editor Configuration

```
         :config-open – open the config file
:config-open-workspace – open the workspace
                         config file
       :config-reload – reload the config file
```

2.16 Miscellaneous

```
  ␣' – open last picker
  ␣/ – open global search in workspace folder
       picker
```

3 Commands in Specific Contexts

3.1 Insert Mode Editing

Navigation keys shown.

```
                Ctrl-s – commit undo checkpoint
                Ctrl-x – autocomplete
                Ctrl-r – insert a register content
   Ctrl-w, Alt-<bksp> – delete previous word
     Alt-d, Alt-<del> – delete next word
                Ctrl-u – delete to start of line
                Ctrl-k – delete to end of line
       Ctrl-h, <bksp>,– delete previous char
          Shift-<bksp>
         Ctrl-d, <del> – delete next char
      Ctrl-j, <enter> – insert new line
  <Up> <Down> <Left> – usual meaning but
    <Right> <PageUp>   discouraged
   <PageDown> <Home>
               <End>
```

3.2 Command Line Editing

```
            Esc, Ctrl-c – close prompt
                <enter> – open selected
                  <tab> – select next completion item
              <backtab> – select previous completion
                          item
                 Alt-b – backward a word
                Ctrl-b – backward a char
                 Alt-f – forward a word
                Ctrl-f – forward a char
                Ctrl-e – to prompt end
                Ctrl-a – to prompt start
   Ctrl-w, Ctrl-<bksp> – delete previous word
     Alt-d, Ctrl-<del> – delete next word
                Ctrl-u – delete to start of line
                Ctrl-k – delete to end of line
         <bksp>, Ctrl-h – delete previous char
          <del>, Ctrl-d – delete next char
                Ctrl-s – insert a word under doc
                         cursor (may be changed to
                         Ctrl-r Ctrl-w later)
                Ctrl-p – select previous history
                Ctrl-n – select next history
                Ctrl-r – insert the content of the
                         register selected by
                         following input char
```

3.3 Pickers

Navigation keys shown.

```
  Shift-<tab>, Ctrl-p,– previous entry
                  <Up>
        <tab>, Ctrl-n,– next entry
                <Down>
                <Home> – to first entry
                 <End> – to last entry
     Ctrl-u, <PageUp> – page up
   Ctrl-d, <PageDown> – page down
               <enter> – open selected
          Alt-<enter> – open selected in the
                        background without closing
                        the picker
                Ctrl-s – open horizontally
                Ctrl-v – open vertically
                Ctrl-t – toggle preview
          Esc, Ctrl-c – close picker
```

3.4 Popups

Displays documentation for item under cursor.

```
      Ctrl-u – scroll up
      Ctrl-d – scroll down
```

3.5 Completion Menu

Displays documentation for the selected completion item. Any other keypresses result in the completion being accepted.

```
  Shift-Tab, Ctrl-p – previous entry
        Tab, Ctrl-n – next entry
            <enter> – close menu and accept
                      completion
             Ctrl-c – close menu and reject
                      completion
```

3.6 Signature-help Popup

Displays the signature of the selected completion item.

```
      Alt-p – previous signature
      Alt-n – next signature
```

4 Command Index

␣' – open last picker **(2.16)**
␣/ – open global search in workspace folder picker **(2.16)**
␣? – open command palette **(2.1.5)**
␣Alt-C – Toggle line comment **(2.6.7)**
␣C – Toggle block comment **(2.6.7)**
␣D – open workspace diagnostics picker **(2.14)**
␣F – open file picker at current working directory **(2.1.2)**
␣G – debug - experimental **(2.14)**
␣R – replace selection(s) with clipboard **(2.7)**
␣S – open workspace symbol picker **(2.14)**
␣Y – yank main selection -> system clipboard **(2.7)**
␣a – apply code action **(2.14)**
␣b – open buffer picker **(2.1.3)**
␣c – Toggle comment **(2.6.7)**
␣d – open document diagnostics picker **(2.14)**
␣f – open file picker at LSP workspace root **(2.1.2)**
␣g – open changed file picker **(2.1.2)**
␣h – select symbol references for symbol under cursor **(2.14)**
␣j – open jumplist picker **(2.11)**
␣k – show documentation for item under cursor **(2.14)**
␣p / ␣P – paste clipboard after / before selections(s) **(2.7)**
␣r – rename symbol **(2.14)**
␣s – open document symbol picker **(2.14)**
␣wF – open/create file(s) under selection(s) in vertical split **(2.1.2)**
␣wH/J/K/L – swap split with buffer on left / up / down / right **(2.1.4)**
␣wf – open/create file(s) under selection(s) in horizontal split **(2.1.2)**
␣wh/j/k/l – move to buffer left / up / down / right **(2.1.4)**
␣wns / ␣wnv – split horizontal / vertical, new buffer **(2.1.4)**
␣wo – close all but current split **(2.1.4)**
␣wq – close current split **(2.1.4)**
␣ws / ␣wv – split horizontal / vertical, current buffer **(2.1.4)**
␣wt – transpose split **(2.1.4)**
␣ww – next split **(2.1.4)**

␣y – yank selection(s) -> system clipboard **(2.7)**
! – insert output before each selection(s) **(2.13)**
" – select register to yank to or paste from **(2.7)**
"<ch> – change to reg <ch> **(2.9)**
"<ch>Q – toggle capture to reg <ch>, default @ **(2.10)**
"<ch>R – replace with reg <ch> **(2.9)**
"<ch>p – paste from reg <ch> **(2.9)**
"<ch>q – play macro in reg <ch>, default @ **(2.10)**
"<ch>y – yank into reg <ch> **(2.9)**
$ – keep selection(s) where command returned 0 **(2.13)**
$ – end of line **(1.5)**
% – select whole file **(2.3.1)**
& – align on primary cursor **(2.5.2)**
' – specified surround pairs **(2.3.2)**
( ) – capture group **(1.5)**
(– cycle primary selection backward **(2.4)**
(– specified surround pairs **(2.3.2)**
(/) – rotate primary backwards / forwards **(2.5.2)**
) – cycle primary selection forward **(2.4)**
* – search for current selection, respect word boundaries **(2.8)**
* – zero or more **(1.5)**
+ – one or more **(1.5)**
, – remove all except primary selection **(2.5.2)**
. – any character **(1.5)**
. – repeat last insert **(2.6.1)**
/<regex> – search forward for regex **(2.8)**
:bc – close current buffer **(2.1.3)**
:bca – close all buffers **(2.1.3)**
:bco – close all but current buffer **(2.1.3)**
:bn – next buffer **(2.1.3)**
:config-open – open the config file **(2.15)**
:config-open-workspace – open the workspace config file **(2.15)**
:config-reload – reload the config file **(2.15)**
:ear / :lat – move backward / forward in history by step count or time span (1s, 2m, 3h, 4d) **(2.1)**
:format – format file using external formatter / language server **(2.6.9)**

:hs <file> – open/create <file> in new horizontal split **(2.1.2)**
:n – create new scratch buffer **(2.1.3)**
:o <file> – open <file> in new buffer **(2.1.2)**
:q – quit current buffer, exits if last **(2.1.1)**
:reflow <width> – wrap selection to <width>, default 80 **(2.6.9)**
:sort – sort ranges in selection **(2.6.9)**
:tutor – open tutorial **(2.1.5)**
:vs <file> – open/create <file> in new vertical split **(2.1.2)**
:w <file> – write current buffer to <file> **(2.1.2)**
:wq – write current buffer and quit **(2.1.1)**
:wq <file> – write current buffer to <file> and quit **(2.1.1)**
:wqa – write all buffer(s) and quit **(2.1.1)**
; – collapse selection(s) to cursor(s) **(2.3.1)**
< – Undent line(s) containing selection **(2.6.5)**
<Down> – next entry **(3.3)**
<End> – to last entry **(3.3)**
<Home> – to first entry **(3.3)**
<PageDown> – page down **(3.3)**
<PageUp> – page up **(3.3)**
<Up> – previous entry **(3.3)**
<Up> – usual meaning but discouraged **(3.1)**
<Down>
<Left>
<Right>
<PageUp>
<PageDown>
<Home>
<End>
<backtab> – select previous completion item **(3.2)**
<bksp> – delete previous char **(3.1)**
<bksp> – delete previous char **(3.2)**
<del> – delete next char **(3.1)**
<del> – delete next char **(3.2)**
<enter> – close menu and accept completion **(3.5)**
<enter> – insert new line **(3.1)**
<enter> – open selected **(3.2)**
<enter> – open selected **(3.3)**
<enter> – open selected in current view **(2.1.2.1)**
<nn><cmd> – repeat <cmd> <nn> times **(2.1)**
<nn>G – line <nn> **(2.2.1)**
<nn>g| – column <nn> **(2.2.1)**
<tab> – next entry **(3.3)**
<tab> – select next completion item **(3.2)**
<under> – trim whitespace from selection **(2.6.9)**

- **=** – format by LSP **(2.6.4)**
- **>** – Indent line(s) containing selection **(2.6.5)**
- **?** – zero or one / lazy modifier **(1.5)**
- **?<regex>** – search backward for regex **(2.8)**
- **A** – at end of line **(2.6.1)**
- **Alt-!** – append output after each selection(s) **(2.13)**
- **Alt-(/ Alt-)** – rotate content backward / forward **(2.5.2)**
- **Alt-*** – search for current selection **(2.8)**
- **Alt-,** – remove primary selection **(2.4)**
- **Alt-,** – remove primary selection **(2.5.2)**
- **Alt-.** – repeat last find / till **(2.3.5)**
- **Alt-:** – selection to normal direction (cursor at end) **(2.3.1)**
- **Alt-;** – swap anchor and cursor **(2.3.1)**
- **Alt-<bksp>** – delete previous word **(3.1)**
- **Alt-<del>** – delete next word **(3.1)**
- **Alt-<enter>** – open selected in the background without closing the picker **(3.3)**
- **Alt-<minus>** – merge selections **(2.5.2)**
- **Alt-<under>** – merge consecutive selections **(2.5.2)**
- **Alt-C** – add selection below, above **(2.5.1)**
- **Alt-I** – select all children nodes in syntax tree **(2.3.4)**
- **Alt-J** – join lines inside selection and select the inserted space **(2.6.9)**
- **Alt-K** – remove selections matching the regex **(2.5.2)**
- **Alt-`** – set uppercase **(2.6.6)**
- **Alt-a** – select all sibling nodes in syntax tree **(2.3.4)**
- **Alt-b** – backward a word **(3.2)**
- **Alt-b** – move to start of parent node in syntax tree **(2.2.3)**
- **Alt-c** – change, no save **(2.6.4)**
- **Alt-d** – delete next word **(3.1)**
- **Alt-d** – delete next word **(3.2)**
- **Alt-d** – delete, no save **(2.6.3)**
- **Alt-e** – move to end of parent node in syntax tree **(2.2.3)**
- **Alt-f** – forward a word **(3.2)**
- **Alt-i** – shrink selection **(2.3.1)**
- **Alt-i** – shrink syntax tree object selection **(2.3.4)**
- **Alt-n** – next signature **(3.6)**
- **Alt-n** – select next sibling node in syntax tree **(2.3.4)**
- **Alt-o** – expand selection syntax-aware **(2.3.1)**
- **Alt-o** – expand selection to parent syntax node **(2.3.4)**
- **Alt-p** – previous signature **(3.6)**
- **Alt-p** – select previous sibling node in syntax tree **(2.3.4)**
- **Alt-s** – split on newlines **(2.5.1)**
- **Alt-u / Alt-U** – move backward / forward in tree history **(2.1)**
- **Alt-x** – shrink to line bounds **(2.3.3)**
- **Alt-|** – ignore output **(2.13)**
- **C** – add selection below, above **(2.5.1)**
- **Ctrl-<bksp>** – delete previous word **(3.2)**
- **Ctrl-<del>** – delete next word **(3.2)**
- **Ctrl-a** – increment the selected number **(2.6.8)**
- **Ctrl-a** – to prompt start **(3.2)**
- **Ctrl-b** – backward a char **(3.2)**
- **Ctrl-b** – page up **(2.2.4)**
- **Ctrl-c** – Toggle comment **(2.6.7)**
- **Ctrl-c** – close menu and reject completion **(3.5)**
- **Ctrl-c** – close picker **(3.3)**
- **Ctrl-c** – close prompt **(3.2)**
- **Ctrl-d** – delete next char **(3.1)**
- **Ctrl-d** – delete next char **(3.2)**
- **Ctrl-d** – half page down **(2.2.4)**
- **Ctrl-d** – page down **(3.3)**
- **Ctrl-d** – scroll down **(3.4)**
- **Ctrl-e** – to prompt end **(3.2)**
- **Ctrl-f** – forward a char **(3.2)**
- **Ctrl-f** – page down **(2.2.4)**
- **Ctrl-h** – delete previous char **(3.1)**
- **Ctrl-h** – delete previous char **(3.2)**
- **Ctrl-i** – move forward in jumplist **(2.11)**
- **Ctrl-j** – insert new line **(3.1)**
- **Ctrl-k** – delete to end of line **(3.1)**
- **Ctrl-k** – delete to end of line **(3.2)**
- **Ctrl-n** – next entry **(3.3)**
- **Ctrl-n** – next entry **(3.5)**
- **Ctrl-n** – select next history **(3.2)**
- **Ctrl-o** – move backwards in jumplist **(2.11)**
- **Ctrl-p** – previous entry **(3.3)**
- **Ctrl-p** – previous entry **(3.5)**
- **Ctrl-p** – select previous history **(3.2)**
- **Ctrl-r** – insert a register content **(3.1)**
- **Ctrl-r** – insert the content of the register selected by following input char **(3.2)**
- **Ctrl-s** – commit undo checkpoint **(3.1)**
- **Ctrl-s** – insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later) **(3.2)**
- **Ctrl-s** – open horizontally **(3.3)**
- **Ctrl-s** – open selected in new horizontal split **(2.1.2.1)**
- **Ctrl-s** – save current position to jumplist **(2.11)**
- **Ctrl-t** – toggle preview **(3.3)**
- **Ctrl-u** – delete to start of line **(3.1)**
- **Ctrl-u** – delete to start of line **(3.2)**
- **Ctrl-u** – half page up **(2.2.4)**
- **Ctrl-u** – page up **(3.3)**
- **Ctrl-u** – scroll up **(3.4)**
- **Ctrl-v** – open selected in new vertical split **(2.1.2.1)**
- **Ctrl-v** – open vertically **(3.3)**
- **Ctrl-w** – delete previous word **(3.1)**
- **Ctrl-w** – delete previous word **(3.2)**
- **Ctrl-x** – autocomplete **(3.1)**
- **Ctrl-x** – decrement the selected number **(2.6.8)**
- **Esc** – close picker **(3.3)**
- **Esc** – close prompt **(3.2)**
- **Esc** – end insert (return to normal) **(2.6.1)**
- **Esc** – return to normal **(2.4)**
- **Esc** – return to normal mode **(2.1)**
- **F<ch>** – to <ch> inclusive (find) **(2.3.5)**
- **I** – at start of line **(2.6.1)**
- **J** – join lines in a selection **(2.6.9)**
- **K** – keep selections matching the regex **(2.5.2)**
- **N** – next, previous match **(2.8)**
- **O** – add line and insert above cursor **(2.6.1)**
- **P** – paste yank buf before the cursor **(2.7)**
- **R** – replace selection with yank buf **(2.7)**
- **S** – split on match **(2.5.1)**
- **Shift-<bksp>** – delete previous char **(3.1)**
- **Shift-<tab>** – previous entry **(3.3)**
- **Shift-Tab** – previous entry **(3.5)**
- **T** – test **(2.3.2)**
- **T<ch>** – to <ch> exclusive (till) **(2.3.5)**
- **Tab** – next entry **(3.5)**
- **X** – extend to line **(2.3.3)**
- **Z** – enter sticky mode, exit with Esc **(2.1.4.1)**
- **[␣** – newline above **(2.6.2)**
- **[** – specified surround pairs **(2.3.2)**
- **[ ]** – character class **(1.5)**
- **[D** – first diagnostic **(2.2.2)**
- **[G** – to last, first change **(2.2.3)**
- **[T** – to next, prior test **(2.2.3)**

`[a` – to next, prior arg **(2.2.3)**
`[c` – to next, prior comment **(2.2.3)**
`[d` – prior diagnostic **(2.2.2)**
`[f` – to next, prior function **(2.2.3)**
`[g` – to next, prior change **(2.2.3)**
`[p` – to prior paragraph **(2.3.3)**
`[t` – to next, prior type definition **(2.2.3)**
`\` – escape character itself **(1.5)**
`]␣` – newline below **(2.6.2)**
`]D` – last diagnostic **(2.2.2)**
`]G` – to last, first change **(2.2.3)**
`]T` – to next, prior test **(2.2.3)**
`]a` – to next, prior arg **(2.2.3)**
`]c` – to next, prior comment **(2.2.3)**
`]d` – next diagnostic **(2.2.2)**
`]f` – to next, prior function **(2.2.3)**
`]g` – to next, prior change **(2.2.3)**
`]p` – to next paragraph **(2.3.3)**
`]t` – to next, prior type definition **(2.2.3)**
`^` – start of line / negation in class **(1.5)**
`` ` `` – set lowercase **(2.6.6)**
`a` – after selection **(2.6.1)**
`a` – argument/parameter **(2.3.2)**
`b / B` – to start of current word / WORD **(2.3.3)**
`c` – comment **(2.3.2)**
`c` – selection -> yank buf, change selection **(2.6.4)**
`d` – selection -> yank buf, delete selection **(2.6.3)**
`e / E` – to end of current word / WORD **(2.3.3)**
`etc.` – specified surround pairs **(2.3.2)**
`f` – function **(2.3.2)**
`f<ch>` – to <ch> inclusive (find) **(2.3.5)**
`g` – change git hunk **(2.3.2)**
`g.` – to last modification in current file **(2.2.1)**
`g<nn>g` – line <nn> **(2.2.1)**
`ga` – go to last accessed/alternate buffer **(2.1.3)**
`gb` – bottom of screen **(2.2.1)**
`gc` – middle of screen **(2.2.1)**
`gd` – go to definition **(2.2.2)**
`ge` – bottom of file **(2.2.1)**
`gf` – open/create file(s) under selection, open url under selection. **(2.1.2)**
`gg` – top of file **(2.2.1)**
`gh` – beginning of line **(2.2.1)**
`gi` – go to implementation **(2.2.2)**
`gj` – down textual line **(2.2.1)**
`gk` – up textual line **(2.2.1)**
`gl` – end of line **(2.2.1)**

`gm` – go to last modified/alternate buffer **(2.1.3)**
`gn` – go to next buffer **(2.1.3)**
`gp` – go to previous buffer **(2.1.3)**
`gr` – go to references **(2.2.2)**
`gs` – first non-white-space char **(2.2.1)**
`gt` – top of screen **(2.2.1)**
`gw` – two-char labels on words, label to go to word **(2.2.1)**
`gy` – go to type definition **(2.2.2)**
`g|` – beginning of line **(2.2.1)**
`h/j/k/l` – left / up / down / right **(2.2.1)**
`i` – before selection **(2.6.1)**
`m` – closest surround pair **(2.3.2)**
`ma<ch>` – match around delim <ch> **(2.12)**
`ma<ch> / mi<ch>` – match around / inside the object indicated by <ch> below: **(2.3.2)**
`md<ch>` – delete delim <ch> around selection **(2.12)**
`md<ch>` – delete delim <ch> around selection **(2.6.3)**
`mi<ch>` – match inside delim <ch> **(2.12)**
`mm` – go to matching delim **(2.12)**
`mr<ch1><ch2>` – replace delim <ch1> with <ch2> **(2.12)**
`mr<ch1><ch2>` – replace delim <ch1> with <ch2> **(2.6.4)**
`ms<ch>` – add delim <ch> around selection **(2.12)**
`ms<ch>` – add delim <ch> around selection **(2.6.2)**
`n` – next, previous match **(2.8)**
`o` – add line and insert below cursor **(2.6.1)**
`p` – paragraph **(2.3.2)**
`p` – paste yank buf after the cursor **(2.7)**
`r<ch>` – replace selection with <ch> **(2.7)**
`s<regex>` – matches become selections **(2.5.1)**
`t` – type or class **(2.3.2)**
`t<ch>` – to <ch> exclusive (till) **(2.3.5)**
`u / U` – undo / redo change in linear history **(2.1)**
`v` – toggle select mode **(2.4)**
`w / W` – to start of next word / WORD **(2.3.3)**
`w / W` – word / WORD **(2.3.2)**
`x` – current line, extend by line **(2.3.3)**
`y` – selection -> yank buf **(2.7)**
`zb` – align to bottom **(2.1.4.1)**
`zc` – align to center **(2.1.4.1)**
`zj` – scroll down **(2.1.4.1)**
`zk` – scroll up **(2.1.4.1)**
`zm` – align to middle horizontally **(2.1.4.1)**
`zt` – align to top **(2.1.4.1)**
`zz` – align to center **(2.1.4.1)**
`{ }` – repetition count **(1.5)**
`|` – alternation **(1.5)**

`|` – replace selection(s) with output **(2.13)**
`~` – change case **(2.6.6)**