Bill's Helix Cheat Sheet / Command Reference

1 Introduction

- Document version: 1.0.0-beta, 15-Apr-2026
- Based on Helix version: 25.07.1.
- Distributed at: https://github.com/wrwetzel/Helix-Cheat-Sheet
- © 2026 Bill Wetzel - Licensed under CC BY 4.0 https://creativecommons.org/licenses/by/4.0/

1.1 Definitions

- **file** - the actual data on storage device
- **buffers** - data from one or more files loaded into memory
- **view** - one or more visual areas on screen showing one or more buffers
- **workspace** - the directory from which Helix was launched
- **under selection** - the entire word containing the cursor, not just the selection
- **alternate buffer** - the previous active buffer
- **textual line** - text as defined by the newline character
- **visual line** - what appears on screen after word-wrapping
- **range** - a selection; one in single-selection, multiple in multi-selection

1.2 Typographic Conventions

- **`word`** - alphanumeric, punctuation-delimited
- **`WORD`** - whitespace-delimited
- **`Ctrl-c`** - Ctrl and c key pressed simultaneous.
- **`Alt-c`** - Alt and c key pressed simultaneous.
- Some Alt and Ctrl characters may conflict with terminal capture and require terminal configuration change.
- **`␣c`** is space followed by the character c.
- Metavars **`<regex>`**, **`<file>`** and **`<ch>`** represent user input. The angle-brackets are not part of the input.
- **`␣`**, **`<minus>`**, and **`<under>`** used for clarity. **`<enter>`**, **`<del>`**, **`<bksp>`**, etc. used for non-printing control characters.
- Commands are separated from definitions by a dash. Synonyms are separated by commas. Related commands are separated by slashes. The separators are never part of the command though commands may include a dash, comma, or slash.

1.3 Launching

- **`helix`**
- **`helix`** `<file>`
- **`helix`** `<file1> <file2> … <filen>`
- **`helix`** `–help`
- **`hx`** `in some distributions or by alias`

1.4 Basics

Editing paradigm: select first, action second. *mode* and *count* are optional.

```
[mode][count][select][command]
```

1.4.1 Example

```
v3wd
        v – enter select mode
        3 – select 3
        w – words
        d – delete
```

1.4.2 Samples

```
       wd – delete word
       xc – change line
       %y – yank entire file
```

1.5 Regular Expressions

Helix uses Rust's regex. Escape metachars with backslash when searching for literal value.

```
        . – any character
        * – zero or more
        + – one or more
        ? – zero or one / lazy modifier
        ^ – start of line / negation in class
        $ – end of line
      ( ) – capture group
      [ ] – character class
      { } – repetition count
        | – alternation
        \ – escape character itself
```

2 Primary Commands

2.1 Essentials

`u / U`	undo / redo change in linear history
`Alt-u / Alt-U`	move backward / forward in tree history
`:ear / :lat`	move backward / forward in history by step count or time span (1s, 2m, 3h, 4d)
`<nn><cmd>`	repeat <cmd> <nn> times
`Esc`	return to normal mode

2.1.1 Quit

Add **!** suffix to force operation.

`:wq`	write current buffer and quit
`:wq <file>`	write current buffer to <file> and quit
`:wqa`	write all buffer(s) and quit
`:q`	quit current buffer, exits if last

2.1.2 Files

`:o <file>`	open <file> in new buffer
`:w <file>`	write current buffer to <file>
`:hs <file>`	open/create <file> in new horizontal split
`:vs <file>`	open/create <file> in new vertical split
`␣wf`	open/create file(s) under selection(s) in horizontal split
`␣wF`	open/create file(s) under selection(s) in vertical split
`gf`	open/create file(s) under selection, open url under selection.
`␣f`	open file picker at LSP workspace root
`␣F`	open file picker at current working directory
`␣g`	open changed file picker

2.1.2.1 File Picker

All pickers, here and elsewhere, are *fuzzy* - they tolerate gaps in the input, ranking closer matches higher.

`<enter>`	open selected in current view
`Ctrl-s`	open selected in new horizontal split
`Ctrl-v`	open selected in new vertical split

2.1.3 Buffers

Add **!** suffix to force operation. Buffers named by file they contain.

`:n`	create new scratch buffer
`:bc`	close current buffer
`:bca`	close all buffers
`:bco`	close all but current buffer
`:bn`	next buffer
`␣b`	open buffer picker
`ga`	go to last accessed/alternate buffer
`gm`	go to last modified/alternate buffer
`gn`	go to next buffer
`gp`	go to previous buffer

2.1.4 Views

Ctrl-w and `␣w` are synonymous.

`␣ws / ␣wv`	split horizontal / vertical, current buffer
`␣wns / ␣wnv`	split horizontal / vertical, new buffer
`␣wq`	close current split
`␣wo`	close all but current split
`␣ww`	next split
`␣wh/j/k/l`	move to buffer left / up / down / right
`␣wH/J/K/L`	swap split with buffer on left / up / down / right
`␣wt`	transpose split

2.1.4.1 View Movement

Commands shown with **z** prefix. The prefix is not used in sticky mode, which is a view-only navigation mode appropriate for browsing a file without editing.

`Z`	enter sticky mode, exit with Esc
`zz, zc`	align to center
`zt`	align to top
`zb`	align to bottom
`zm`	align to middle horizontally
`zj`	scroll down
`zk`	scroll up

2.1.5 Help

`:tutor`	open tutorial
`␣?`	open command palette

2.2 Movement

2.2.1 Cursor Movement

Normal Mode: motion replaces selection
Select Mode: motion extends selection

```
h/j/k/l – left / up / down / right
 gh, g| – beginning of line
 <nn>g| – column <nn>
     gl – end of line
     gg – top of file
  <nn>G,– line <nn>
 g<nn>g
     ge – bottom of file
     gw – two-char labels on words, label to
          go to word
      g.– to last modification in current file
     gj – down textual line
     gk – up textual line
     gs – first non-white-space char
     gt – top of screen
     gc – middle of screen
     gb – bottom of screen
```

2.2.2 By Language Server Protocol

Requires LSP support.

```
 gd – go to definition
 gy – go to type definition
 gr – go to references
 gi – go to implementation
 ]d – next diagnostic
 [d – prior diagnostic
 ]D – last diagnostic
 [D – first diagnostic
```

2.2.3 By Treesitter - Syntax

Requires Treesitter support.

```
 ]f, [f – to next, prior function
 ]t, [t – to next, prior type definition
 ]T, [T – to next, prior test
 ]a, [a – to next, prior arg
 ]c, [c – to next, prior comment
 ]g, [g – to next, prior change
 ]G, [G – to last, first change
 Alt-e – move to end of parent node in
         syntax tree
 Alt-b – move to start of parent node in
         syntax tree
```

2.2.4 By Page

```
 Ctrl-b – page up
 Ctrl-f – page down
 Ctrl-u – half page up
 Ctrl-d – half page down
```

2.3 Selection

Selection: a range of characters between anchor and cursor
Normal Mode: move and select
Select Mode: move and extend selection

2.3.1 Operations

```
   % – select whole file
Alt-; – swap anchor and cursor
Alt-: – selection to normal direction (cursor
        at end)
Alt-o – expand selection syntax-aware
Alt-i – shrink selection
   ; – collapse selection(s) to cursor(s)
```

2.3.2 By TextObjects

```
 ma<ch> / – match around / inside the
   mi<ch>   object indicated by <ch> below:
     w / W – word / WORD
         p – paragraph
(, [, ', etc.– specified surround pairs
         m –  closest surround pair
         f – function
         t – type or class
         a – argument/parameter
         c – comment
         T – test
         g – change git hunk
```

2.3.3 By Syntactic Objects

```
 w / W – to start of next word / WORD
 e / E – to end of current word / WORD
 b / B – to start of current word / WORD
     x – current line, extend by line
     X – extend to line
Alt-x – shrink to line bounds
    ]p – to next paragraph
    [p – to prior paragraph
```

2.3.4 By Treesitter - Syntax

Requires Treesitter support.

```
Alt-o – expand selection to parent syntax
        node
Alt-i – shrink syntax tree object selection
Alt-p – select previous sibling node in
        syntax tree
Alt-n – select next sibling node in syntax
        tree
Alt-a – select all sibling nodes in syntax tree
Alt-I – select all children nodes in syntax
        tree
```

2.3.5 By Character Value

Lower case: forward
Upper case: backward

`f<ch>, F<ch>`	– to <ch> inclusive (find)
`t<ch>, T<ch>`	– to <ch> exclusive (till)
`Alt-.`	– repeat last find / till

2.4 Select Mode

Movement: extends selection
Search: adds to selection

`v`	– toggle select mode
`Esc`	– return to normal
`)`	– cycle primary selection forward
`(`	– cycle primary selection backward
`Alt-,`	– remove primary selection

2.5 Multiple Selections

Multiple independent cursors / selections, one is *primary*.

2.5.1 Creating

Create multiple selections from selection.

`s<regex>`	– matches become selections
`S`	– split on match
`Alt-s`	– split on newlines
`C, Alt-C`	– add selection below, above

2.5.2 Operations

`&`	– align on primary cursor
`Alt-<minus>`	– merge selections
`Alt-<under>`	– merge consecutive selections
`,`	– remove all except primary selection
`Alt-,`	– remove primary selection
`( / )`	– rotate primary backwards / forwards
`Alt-( / Alt-)`	– rotate content backward / forward
`K`	– keep selections matching the regex
`Alt-K`	– remove selections matching the regex

2.6 Alter Buffer Content

2.6.1 Insert

`i`	– before selection
`a`	– after selection
`I`	– at start of line
`A`	– at end of line
`o`	– add line and insert below cursor
`O`	– add line and insert above cursor
`Esc`	– end insert (return to normal)
`.`	– repeat last insert

2.6.2 Add

`]␣`	– newline below
`[␣`	– newline above
`ms<ch>`	– add delim <ch> around selection

2.6.3 Delete

`d`	– selection -> yank buf, delete selection
`Alt-d`	– delete, no save
`md<ch>`	– delete delim <ch> around selection

2.6.4 Change

`c`	– selection -> yank buf, change selection
`Alt-c`	– change, no save
`=`	– format by LSP
`mr<ch1><ch2>`	– replace delim <ch1> with <ch2>

2.6.5 Indent Lines

`>`	– Indent line(s) containing selection
`<`	– Undent line(s) containing selection

2.6.6 Change Case

Change case of all letters in selection

`~`	– change case
`` ` ``	– set lowercase
`Alt-` `	– set uppercase

2.6.7 Comments

All apply to selection.

`␣c, Ctrl-c`	– Toggle comment
`␣C`	– Toggle block comment
`␣Alt-C`	– Toggle line comment

2.6.8 Increment / Decrement

`Ctrl-a`	– increment the selected number
`Ctrl-x`	– decrement the selected number

2.6.9 Miscellaneous

```
          J – join lines in a selection
    Alt-J – join lines inside selection and select
            the inserted space
<under> – trim whitespace from selection
:reflow – wrap selection to <width>, default 80
<width>
   :sort – sort ranges in selection
 :format – format file using external
            formatter / language server
```

2.7 Copy / Paste / Replace

```
          y – selection -> yank buf
          p – paste yank buf after the cursor
          P – paste yank buf before the cursor
         ␣y – yank selection(s) -> system clipboard
         ␣Y – yank main selection -> system
              clipboard
  ␣p / ␣P – paste clipboard after / before
              selections(s)
         ␣R – replace selection(s) with clipboard
     r<ch> – replace selection with <ch>
          R – replace selection with yank buf
          " – select register to yank to or paste
              from
```

2.8 Search

```
  /<regex> – search forward for regex
  ?<regex> – search backward for regex
      n, N – next, previous match
         * – search for current selection, respect
              word boundaries
    Alt-* – search for current selection
```

2.9 Registers

Identified by single char <ch>

```
   "<ch> – change to reg <ch>
  "<ch>y – yank into reg <ch>
  "<ch>p – paste from reg <ch>
  "<ch>R – replace with reg <ch>
```

2.10 Macros

```
  "<ch>Q – toggle capture to reg <ch>, default @
  "<ch>q – play macro in reg <ch>, default @
```

2.11 Jumplists

```
  Ctrl-s – save current position to jumplist
  Ctrl-i – move forward in jumplist
  Ctrl-o – move backwards in jumplist
      ␣j – open jumplist picker
```

2.12 Match Mode

With regard to balanced delimiters.

```
           mm – go to matching delim
     mi<ch> – match inside delim <ch>
     ma<ch> – match around delim <ch>
     ms<ch> – add delim <ch> around
              selection
     md<ch> – delete delim <ch> around
              selection
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.13 Shell

All commands pipe each selection to shell command.

```
        | – replace selection(s) with output
    Alt-| – ignore output
        ! – insert output before each
            selection(s)
    Alt-! – append output after each
            selection(s)
        $ – keep selection(s) where command
            returned 0
```

2.14 Approaching an IDE

```
      ␣G – debug - experimental
      ␣k – show documentation for item under
           cursor
      ␣s – open document symbol picker
      ␣S – open workspace symbol picker
      ␣d – open document diagnostics picker
      ␣D – open workspace diagnostics picker
      ␣r – rename symbol
      ␣a – apply code action
      ␣h – select symbol references for symbol
           under cursor
```

2.15 Editor Configuration

```
   :config-open – open the config file
:config-open-- open the workspace
   workspace   config file
:config-reload – reload the config file
```

2.16 Miscellaneous

```
      ␣' – open last picker
      ␣/ – open global search in workspace
           folder picker
```

3 Commands in Specific Contexts

3.1 Insert Mode Editing

Navigation keys shown.

```
            Ctrl-s – commit undo checkpoint
            Ctrl-x – autocomplete
            Ctrl-r – insert a register content
Ctrl-w, Alt-<bksp> – delete previous word
  Alt-d, Alt-<del> – delete next word
            Ctrl-u – delete to start of line
            Ctrl-k – delete to end of line
    Ctrl-h, <bksp>,– delete previous char
      Shift-<bksp>
     Ctrl-d, <del> – delete next char
   Ctrl-j, <enter> – insert new line
<Up> <Down> <Left> – usual meaning but
  <Right> <PageUp>   discouraged
 <PageDown> <Home>
             <End>
```

3.2 Command Line Editing

```
        Esc, Ctrl-c – close prompt
            <enter> – open selected
              <tab> – select next completion
                      item
          <backtab> – select previous
                      completion item
             Alt-b – backward a word
            Ctrl-b – backward a char
             Alt-f – forward a word
            Ctrl-f – forward a char
            Ctrl-e – to prompt end
            Ctrl-a – to prompt start
      Ctrl-w, Ctrl-– delete previous word
            <bksp>
 Alt-d, Ctrl-<del> – delete next word
            Ctrl-u – delete to start of line
            Ctrl-k – delete to end of line
    <bksp>, Ctrl-h – delete previous char
     <del>, Ctrl-d – delete next char
            Ctrl-s – insert a word under doc
                     cursor (may be changed
                     to Ctrl-r Ctrl-w later)
            Ctrl-p – select previous history
            Ctrl-n – select next history
            Ctrl-r – insert the content of the
                     register selected by
                     following input char
```

3.3 Pickers

Navigation keys shown.

```
 Shift-<tab>, Ctrl-– previous entry
           p, <Up>
     <tab>, Ctrl-n,– next entry
            <Down>
            <Home> – to first entry
             <End> – to last entry
  Ctrl-u, <PageUp> – page up
Ctrl-d, <PageDown> – page down
           <enter> – open selected
       Alt-<enter> – open selected in the
                     background without
                     closing the picker
            Ctrl-s – open horizontally
            Ctrl-v – open vertically
            Ctrl-t – toggle preview
       Esc, Ctrl-c – close picker
```

3.4 Popups

Displays documentation for item under cursor.

```
    Ctrl-u – scroll up
    Ctrl-d – scroll down
```

3.5 Completion Menu

Displays documentation for the selected completion item. Any other keypresses result in the completion being accepted.

```
 Shift-Tab, Ctrl-– previous entry
               p
     Tab, Ctrl-n – next entry
         <enter> – close menu and accept
                   completion
           Ctrl-c – close menu and reject
                   completion
```

3.6 Signature-help Popup

Displays the signature of the selected completion item.

```
    Alt-p – previous signature
    Alt-n – next signature
```

4 Command Index

- `␣'` – open last picker **(2.16)**
- `␣/` – open global search in workspace folder picker **(2.16)**
- `␣?` – open command palette **(2.1.5)**
- `␣Alt-C` – Toggle line comment **(2.6.7)**
- `␣C` – Toggle block comment **(2.6.7)**
- `␣D` – open workspace diagnostics picker **(2.14)**
- `␣F` – open file picker at current working directory **(2.1.2)**
- `␣G` – debug - experimental **(2.14)**
- `␣R` – replace selection(s) with clipboard **(2.7)**
- `␣S` – open workspace symbol picker **(2.14)**
- `␣Y` – yank main selection -> system clipboard **(2.7)**
- `␣a` – apply code action **(2.14)**
- `␣b` – open buffer picker **(2.1.3)**
- `␣c` – Toggle comment **(2.6.7)**
- `␣d` – open document diagnostics picker **(2.14)**
- `␣f` – open file picker at LSP workspace root **(2.1.2)**
- `␣g` – open changed file picker **(2.1.2)**
- `␣h` – select symbol references for symbol under cursor **(2.14)**
- `␣j` – open jumplist picker **(2.11)**
- `␣k` – show documentation for item under cursor **(2.14)**
- `␣p / ␣P` – paste clipboard after / before selections(s) **(2.7)**
- `␣r` – rename symbol **(2.14)**
- `␣s` – open document symbol picker **(2.14)**
- `␣wF` – open/create file(s) under selection(s) in vertical split **(2.1.2)**
- `␣wH/J/K/L` – swap split with buffer on left / up / down / right **(2.1.4)**
- `␣wf` – open/create file(s) under selection(s) in horizontal split **(2.1.2)**
- `␣wh/j/k/l` – move to buffer left / up / down / right **(2.1.4)**
- `␣wns / ␣wnv` – split horizontal / vertical, new buffer **(2.1.4)**
- `␣wo` – close all but current split **(2.1.4)**
- `␣wq` – close current split **(2.1.4)**
- `␣ws / ␣wv` – split horizontal / vertical, current buffer **(2.1.4)**
- `␣wt` – transpose split **(2.1.4)**
- `␣ww` – next split **(2.1.4)**

- `␣y` – yank selection(s) -> system clipboard **(2.7)**
- `!` – insert output before each selection(s) **(2.13)**
- `"` – select register to yank to or paste from **(2.7)**
- `"<ch>` – change to reg <ch> **(2.9)**
- `"<ch>Q` – toggle capture to reg <ch>, default @ **(2.10)**
- `"<ch>R` – replace with reg <ch> **(2.9)**
- `"<ch>p` – paste from reg <ch> **(2.9)**
- `"<ch>q` – play macro in reg <ch>, default @ **(2.10)**
- `"<ch>y` – yank into reg <ch> **(2.9)**
- `$` – keep selection(s) where command returned 0 **(2.13)**
- `$` – end of line **(1.5)**
- `%` – select whole file **(2.3.1)**
- `&` – align on primary cursor **(2.5.2)**
- `'` – specified surround pairs **(2.3.2)**
- `( )` – capture group **(1.5)**
- `(` – cycle primary selection backward **(2.4)**
- `(` – specified surround pairs **(2.3.2)**
- `( / )` – rotate primary backwards / forwards **(2.5.2)**
- `)` – cycle primary selection forward **(2.4)**
- `*` – search for current selection, respect word boundaries **(2.8)**
- `*` – zero or more **(1.5)**
- `+` – one or more **(1.5)**
- `,` – remove all except primary selection **(2.5.2)**
- `.` – any character **(1.5)**
- `.` – repeat last insert **(2.6.1)**
- `/<regex>` – search forward for regex **(2.8)**
- `:bc` – close current buffer **(2.1.3)**
- `:bca` – close all buffers **(2.1.3)**
- `:bco` – close all but current buffer **(2.1.3)**
- `:bn` – next buffer **(2.1.3)**
- `:config-open` – open the config file **(2.15)**
- `:config-open-workspace` – open the workspace config file **(2.15)**
- `:config-reload` – reload the config file **(2.15)**
- `:ear / :lat` – move backward / forward in history by step count or time span (1s, 2m, 3h, 4d) **(2.1)**

- `:format` – format file using external formatter / language server **(2.6.9)**
- `:hs <file>` – open/create <file> in new horizontal split **(2.1.2)**
- `:n` – create new scratch buffer **(2.1.3)**
- `:o <file>` – open <file> in new buffer **(2.1.2)**
- `:q` – quit current buffer, exits if last **(2.1.1)**
- `:reflow <width>` – wrap selection to <width>, default 80 **(2.6.9)**
- `:sort` – sort ranges in selection **(2.6.9)**
- `:tutor` – open tutorial **(2.1.5)**
- `:vs <file>` – open/create <file> in new vertical split **(2.1.2)**
- `:w <file>` – write current buffer to <file> **(2.1.2)**
- `:wq` – write current buffer and quit **(2.1.1)**
- `:wq <file>` – write current buffer to <file> and quit **(2.1.1)**
- `:wqa` – write all buffer(s) and quit **(2.1.1)**
- `;` – collapse selection(s) to cursor(s) **(2.3.1)**
- `<` – Undent line(s) containing selection **(2.6.5)**
- `<Down>` – next entry **(3.3)**
- `<End>` – to last entry **(3.3)**
- `<Home>` – to first entry **(3.3)**
- `<PageDown>` – page down **(3.3)**
- `<PageUp>` – page up **(3.3)**
- `<Up>` – previous entry **(3.3)**
- `<Up>` – usual meaning but discouraged **(3.1)**
  - `<Down>`
  - `<Left>`
  - `<Right>`
  - `<PageUp>`
  - `<PageDown>`
  - `<Home>`
  - `<End>`
- `<backtab>` – select previous completion item **(3.2)**
- `<bksp>` – delete previous char **(3.1)**
- `<bksp>` – delete previous char **(3.2)**
- `<del>` – delete next char **(3.1)**
- `<del>` – delete next char **(3.2)**
- `<enter>` – close menu and accept completion **(3.5)**
- `<enter>` – insert new line **(3.1)**
- `<enter>` – open selected **(3.2)**
- `<enter>` – open selected **(3.3)**
- `<enter>` – open selected in current view **(2.1.2.1)**
- `<nn><cmd>` – repeat <cmd> <nn> times **(2.1)**
- `<nn>G` – line <nn> **(2.2.1)**

- **<nn>g|** – column <nn> **(2.2.1)**
- **<tab>** – next entry **(3.3)**
- **<tab>** – select next completion item **(3.2)**
- **<under>** – trim whitespace from selection **(2.6.9)**
- **=** – format by LSP **(2.6.4)**
- **>** – Indent line(s) containing selection **(2.6.5)**
- **?** – zero or one / lazy modifier **(1.5)**
- **?<regex>** – search backward for regex **(2.8)**
- **A** – at end of line **(2.6.1)**
- **Alt-!** – append output after each selection(s) **(2.13)**
- **Alt-(/ Alt-)** – rotate content backward / forward **(2.5.2)**
- **Alt-*** – search for current selection **(2.8)**
- **Alt-,** – remove primary selection **(2.4)**
- **Alt-,** – remove primary selection **(2.5.2)**
- **Alt-.** – repeat last find / till **(2.3.5)**
- **Alt-:** – selection to normal direction (cursor at end) **(2.3.1)**
- **Alt-;** – swap anchor and cursor **(2.3.1)**
- **Alt-<bksp>** – delete previous word **(3.1)**
- **Alt-<del>** – delete next word **(3.1)**
- **Alt-<enter>** – open selected in the background without closing the picker **(3.3)**
- **Alt-<minus>** – merge selections **(2.5.2)**
- **Alt-<under>** – merge consecutive selections **(2.5.2)**
- **Alt-C** – add selection below, above **(2.5.1)**
- **Alt-I** – select all children nodes in syntax tree **(2.3.4)**
- **Alt-J** – join lines inside selection and select the inserted space **(2.6.9)**
- **Alt-K** – remove selections matching the regex **(2.5.2)**
- **Alt-`** – set uppercase **(2.6.6)**
- **Alt-a** – select all sibling nodes in syntax tree **(2.3.4)**
- **Alt-b** – backward a word **(3.2)**
- **Alt-b** – move to start of parent node in syntax tree **(2.2.3)**
- **Alt-c** – change, no save **(2.6.4)**
- **Alt-d** – delete next word **(3.1)**
- **Alt-d** – delete next word **(3.2)**
- **Alt-d** – delete, no save **(2.6.3)**
- **Alt-e** – move to end of parent node in syntax tree **(2.2.3)**
- **Alt-f** – forward a word **(3.2)**
- **Alt-i** – shrink selection **(2.3.1)**
- **Alt-i** – shrink syntax tree object selection **(2.3.4)**
- **Alt-n** – next signature **(3.6)**
- **Alt-n** – select next sibling node in syntax tree **(2.3.4)**
- **Alt-o** – expand selection syntax-aware **(2.3.1)**
- **Alt-o** – expand selection to parent syntax node **(2.3.4)**
- **Alt-p** – previous signature **(3.6)**
- **Alt-p** – select previous sibling node in syntax tree **(2.3.4)**
- **Alt-s** – split on newlines **(2.5.1)**
- **Alt-u / Alt-U** – move backward / forward in tree history **(2.1)**
- **Alt-x** – shrink to line bounds **(2.3.3)**
- **Alt-|** – ignore output **(2.13)**
- **C** – add selection below, above **(2.5.1)**
- **Ctrl-<bksp>** – delete previous word **(3.2)**
- **Ctrl-<del>** – delete next word **(3.2)**
- **Ctrl-a** – increment the selected number **(2.6.8)**
- **Ctrl-a** – to prompt start **(3.2)**
- **Ctrl-b** – backward a char **(3.2)**
- **Ctrl-b** – page up **(2.2.4)**
- **Ctrl-c** – Toggle comment **(2.6.7)**
- **Ctrl-c** – close menu and reject completion **(3.5)**
- **Ctrl-c** – close picker **(3.3)**
- **Ctrl-c** – close prompt **(3.2)**
- **Ctrl-d** – delete next char **(3.1)**
- **Ctrl-d** – delete next char **(3.2)**
- **Ctrl-d** – half page down **(2.2.4)**
- **Ctrl-d** – page down **(3.3)**
- **Ctrl-d** – scroll down **(3.4)**
- **Ctrl-e** – to prompt end **(3.2)**
- **Ctrl-f** – forward a char **(3.2)**
- **Ctrl-f** – page down **(2.2.4)**
- **Ctrl-h** – delete previous char **(3.1)**
- **Ctrl-h** – delete previous char **(3.2)**
- **Ctrl-i** – move forward in jumplist **(2.11)**
- **Ctrl-j** – insert new line **(3.1)**
- **Ctrl-k** – delete to end of line **(3.1)**
- **Ctrl-k** – delete to end of line **(3.2)**
- **Ctrl-n** – next entry **(3.3)**
- **Ctrl-n** – next entry **(3.5)**
- **Ctrl-n** – select next history **(3.2)**
- **Ctrl-o** – move backwards in jumplist **(2.11)**
- **Ctrl-p** – previous entry **(3.3)**
- **Ctrl-p** – previous entry **(3.5)**
- **Ctrl-p** – select previous history **(3.2)**
- **Ctrl-r** – insert a register content **(3.1)**
- **Ctrl-r** – insert the content of the register selected by following input char **(3.2)**
- **Ctrl-s** – commit undo checkpoint **(3.1)**
- **Ctrl-s** – insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later) **(3.2)**
- **Ctrl-s** – open horizontally **(3.3)**
- **Ctrl-s** – open selected in new horizontal split **(2.1.2.1)**
- **Ctrl-s** – save current position to jumplist **(2.11)**
- **Ctrl-t** – toggle preview **(3.3)**
- **Ctrl-u** – delete to start of line **(3.1)**
- **Ctrl-u** – delete to start of line **(3.2)**
- **Ctrl-u** – half page up **(2.2.4)**
- **Ctrl-u** – page up **(3.3)**
- **Ctrl-u** – scroll up **(3.4)**
- **Ctrl-v** – open selected in new vertical split **(2.1.2.1)**
- **Ctrl-v** – open vertically **(3.3)**
- **Ctrl-w** – delete previous word **(3.1)**
- **Ctrl-w** – delete previous word **(3.2)**
- **Ctrl-x** – autocomplete **(3.1)**
- **Ctrl-x** – decrement the selected number **(2.6.8)**
- **Esc** – close picker **(3.3)**
- **Esc** – close prompt **(3.2)**
- **Esc** – end insert (return to normal) **(2.6.1)**
- **Esc** – return to normal **(2.4)**
- **Esc** – return to normal mode **(2.1)**
- **F<ch>** – to <ch> inclusive (find) **(2.3.5)**
- **I** – at start of line **(2.6.1)**
- **J** – join lines in a selection **(2.6.9)**
- **K** – keep selections matching the regex **(2.5.2)**
- **N** – next, previous match **(2.8)**
- **O** – add line and insert above cursor **(2.6.1)**
- **P** – paste yank buf before the cursor **(2.7)**
- **R** – replace selection with yank buf **(2.7)**
- **S** – split on match **(2.5.1)**
- **Shift-<bksp>** – delete previous char **(3.1)**
- **Shift-<tab>** – previous entry **(3.3)**
- **Shift-Tab** – previous entry **(3.5)**
- **T** – test **(2.3.2)**

- **T<ch>** – to <ch> exclusive (till) **(2.3.5)**
- **Tab** – next entry **(3.5)**
- **X** – extend to line **(2.3.3)**
- **Z** – enter sticky mode, exit with Esc **(2.1.4.1)**
- **[␣** – newline above **(2.6.2)**
- **[** – specified surround pairs **(2.3.2)**
- **[ ]** – character class **(1.5)**
- **[D** – first diagnostic **(2.2.2)**
- **[G** – to last, first change **(2.2.3)**
- **[T** – to next, prior test **(2.2.3)**
- **[a** – to next, prior arg **(2.2.3)**
- **[c** – to next, prior comment **(2.2.3)**
- **[d** – prior diagnostic **(2.2.2)**
- **[f** – to next, prior function **(2.2.3)**
- **[g** – to next, prior change **(2.2.3)**
- **[p** – to prior paragraph **(2.3.3)**
- **[t** – to next, prior type definition **(2.2.3)**
- **** – escape character itself **(1.5)**
- **]␣** – newline below **(2.6.2)**
- **]D** – last diagnostic **(2.2.2)**
- **]G** – to last, first change **(2.2.3)**
- **]T** – to next, prior test **(2.2.3)**
- **]a** – to next, prior arg **(2.2.3)**
- **]c** – to next, prior comment **(2.2.3)**
- **]d** – next diagnostic **(2.2.2)**
- **]f** – to next, prior function **(2.2.3)**
- **]g** – to next, prior change **(2.2.3)**
- **]p** – to next paragraph **(2.3.3)**
- **]t** – to next, prior type definition **(2.2.3)**
- **^** – start of line / negation in class **(1.5)**
- **`** – set lowercase **(2.6.6)**
- **a** – after selection **(2.6.1)**
- **a** – argument/parameter **(2.3.2)**
- **b / B** – to start of current word / WORD **(2.3.3)**
- **c** – comment **(2.3.2)**
- **c** – selection -> yank buf, change selection **(2.6.4)**
- **d** – selection -> yank buf, delete selection **(2.6.3)**
- **e / E** – to end of current word / WORD **(2.3.3)**
- **etc.** – specified surround pairs **(2.3.2)**
- **f** – function **(2.3.2)**
- **f<ch>** – to <ch> inclusive (find) **(2.3.5)**
- **g** – change git hunk **(2.3.2)**
- **g.** – to last modification in current file **(2.2.1)**
- **g<nn>g** – line <nn> **(2.2.1)**
- **ga** – go to last accessed/alternate buffer **(2.1.3)**
- **gb** – bottom of screen **(2.2.1)**
- **gc** – middle of screen **(2.2.1)**
- **gd** – go to definition **(2.2.2)**
- **ge** – bottom of file **(2.2.1)**
- **gf** – open/create file(s) under selection, open url under selection. **(2.1.2)**
- **gg** – top of file **(2.2.1)**
- **gh** – beginning of line **(2.2.1)**
- **gi** – go to implementation **(2.2.2)**
- **gj** – down textual line **(2.2.1)**
- **gk** – up textual line **(2.2.1)**
- **gl** – end of line **(2.2.1)**
- **gm** – go to last modified/alternate buffer **(2.1.3)**
- **gn** – go to next buffer **(2.1.3)**
- **gp** – go to previous buffer **(2.1.3)**
- **gr** – go to references **(2.2.2)**
- **gs** – first non-white-space char **(2.2.1)**
- **gt** – top of screen **(2.2.1)**
- **gw** – two-char labels on words, label to go to word **(2.2.1)**
- **gy** – go to type definition **(2.2.2)**
- **g|** – beginning of line **(2.2.1)**
- **h/j/k/l** – left / up / down / right **(2.2.1)**
- **i** – before selection **(2.6.1)**
- **m** – closest surround pair **(2.3.2)**
- **ma<ch>** – match around delim <ch> **(2.12)**
- **ma<ch> / mi<ch>** – match around / inside the object indicated by <ch> below: **(2.3.2)**
- **md<ch>** – delete delim <ch> around selection **(2.12)**
- **md<ch>** – delete delim <ch> around selection **(2.6.3)**
- **mi<ch>** – match inside delim <ch> **(2.12)**
- **mm** – go to matching delim **(2.12)**
- **mr<ch1><ch2>** – replace delim <ch1> with <ch2> **(2.12)**
- **mr<ch1><ch2>** – replace delim <ch1> with <ch2> **(2.6.4)**
- **ms<ch>** – add delim <ch> around selection **(2.12)**
- **ms<ch>** – add delim <ch> around selection **(2.6.2)**
- **n** – next, previous match **(2.8)**
- **o** – add line and insert below cursor **(2.6.1)**
- **p** – paragraph **(2.3.2)**
- **p** – paste yank buf after the cursor **(2.7)**
- **r<ch>** – replace selection with <ch> **(2.7)**
- **s<regex>** – matches become selections **(2.5.1)**
- **t** – type or class **(2.3.2)**
- **t<ch>** – to <ch> exclusive (till) **(2.3.5)**
- **u / U** – undo / redo change in linear history **(2.1)**
- **v** – toggle select mode **(2.4)**
- **w / W** – to start of next word / WORD **(2.3.3)**
- **w / W** – word / WORD **(2.3.2)**
- **x** – current line, extend by line **(2.3.3)**
- **y** – selection -> yank buf **(2.7)**
- **zb** – align to bottom **(2.1.4.1)**
- **zc** – align to center **(2.1.4.1)**
- **zj** – scroll down **(2.1.4.1)**
- **zk** – scroll up **(2.1.4.1)**
- **zm** – align to middle horizontally **(2.1.4.1)**
- **zt** – align to top **(2.1.4.1)**
- **zz** – align to center **(2.1.4.1)**
- **{ }** – repetition count **(1.5)**
- **|** – alternation **(1.5)**
- **|** – replace selection(s) with output **(2.13)**
- **~** – change case **(2.6.6)**