Bill's Helix Cheat Sheet / Command Reference

1 Introduction

- Document version: 1.0.0-beta, 15-Apr-2026
- Based on Helix version: 25.07.1.
- Distributed at: https://github.com/wrwetzel/Helix-Cheat-Sheet
- © 2026 Bill Wetzel - Licensed under CC BY 4.0 https://creativecommons.org/licenses/by/4.0/

1.1 Definitions

- **file** - the actual data on storage device
- **buffers** - data from one or more files loaded into memory
- **view** - one or more visual areas on screen showing one or more buffers
- **workspace** - the directory from which Helix was launched
- **under selection** - the entire word containing the cursor, not just the selection
- **alternate buffer** - the previous active buffer
- **textual line** - text as defined by the newline character
- **visual line** - what appears on screen after word-wrapping
- **range** - a selection; one in single-selection, multiple in multi-selection

1.2 Typographic Conventions

- **`word`** - alphanumeric, punctuation-delimited
- **`WORD`** - whitespace-delimited
- **`Ctrl-c`** - Ctrl and c key pressed simultaneous.
- **`Alt-c`** - Alt and c key pressed simultaneous.
- Some Alt and Ctrl characters may conflict with terminal capture and require terminal configuration change.
- **`␣c`** is space followed by the character c.
- Metavars **`<regex>`**, **`<file>`** and **`<ch>`** represent user input. The angle-brackets are not part of the input.
- **`␣`**, **`<minus>`**, and **`<under>`** used for clarity. **`<enter>`**, **`<del>`**, **`<bksp>`**, etc. used for non-printing control characters.
- Commands are separated from definitions by a dash. Synonyms are separated by commas. Related commands are separated by slashes. The separators are never part of the command though commands may include a dash, comma, or slash.

1.3 Launching

- **`helix`**
- **`helix`** `<file>`
- **`helix`** `<file1> <file2> … <filen>`
- **`helix`** `–help`
- **`hx`** `in some distributions or by alias`

1.4 Basics

Editing paradigm: select first, action second. *mode* and *count* are optional.

```
[mode][count][select][command]
```

1.4.1 Example

```
v3wd
          v – enter select mode
          3 – select 3
          w – words
          d – delete
```

1.4.2 Samples

```
         wd – delete word
         xc – change line
         %y – yank entire file
```

1.5 Regular Expressions

Helix uses Rust's regex. Escape metachars with backslash when searching for literal value.

```
          . – any character
          * – zero or more
          + – one or more
          ? – zero or one / lazy modifier
          ^ – start of line / negation in class
          $ – end of line
        ( ) – capture group
        [ ] – character class
        { } – repetition count
          | – alternation
          \ – escape character itself
```

2 Primary Commands

2.1 Essentials

```
      u / U – undo / redo change in linear history
   Alt-u / – move backward / forward in tree history
     Alt-U
:ear / :lat – move backward / forward in history by
              step count or time span (1s, 2m, 3h, 4d)
 <nn><cmd> – repeat <cmd> <nn> times
       Esc – return to normal mode
```

2.1.1 Quit

Add **!** suffix to force operation.

```
        :wq – write current buffer and quit
  :wq <file> – write current buffer to <file> and quit
       :wqa – write all buffer(s) and quit
         :q – quit current buffer, exits if last
```

2.1.2 Files

```
   :o <file> – open <file> in new buffer
   :w <file> – write current buffer to <file>

  :hs <file> – open/create <file> in new horizontal split
  :vs <file> – open/create <file> in new vertical split
        ␣wf – open/create file(s) under selection(s) in
              horizontal split
        ␣wF – open/create file(s) under selection(s) in
              vertical split
          gf – open/create file(s) under selection, open url
              under selection.

         ␣f – open file picker at LSP workspace root
         ␣F – open file picker at current working
              directory
         ␣g – open changed file picker
```

2.1.2.1 File Picker

All pickers, here and elsewhere, are *fuzzy* - they tolerate gaps in the input, ranking closer matches higher.

```
    <enter> – open selected in current view
     Ctrl-s – open selected in new horizontal split
     Ctrl-v – open selected in new vertical split
```

2.1.3 Buffers

Add **!** suffix to force operation. Buffers named by file they contain.

```
         :n – create new scratch buffer
        :bc – close current buffer
       :bca – close all buffers
       :bco – close all but current buffer
        :bn – next buffer
         ␣b – open buffer picker

        ga – go to last accessed/alternate buffer
        gm – go to last modified/alternate buffer
        gn – go to next buffer
        gp – go to previous buffer
```

2.1.4 Views

Ctrl-w and **␣w** are synonymous.

```
  ␣ws / ␣wv  – split horizontal / vertical, current buffer
 ␣wns / ␣wnv – split horizontal / vertical, new buffer
         ␣wq – close current split
         ␣wo – close all but current split
         ␣ww – next split

  ␣wh/j/k/l – move to buffer left / up / down / right
  ␣wH/J/K/L – swap split with buffer on left / up / down /
              right
         ␣wt – transpose split
```

2.1.4.1 View Movement

Commands shown with **z** prefix. The prefix is not used in sticky mode, which is a view-only navigation mode appropriate for browsing a file without editing.

```
          Z – enter sticky mode, exit with Esc

     zz, zc – align to center
         zt – align to top
         zb – align to bottom
         zm – align to middle horizontally
         zj – scroll down
         zk – scroll up
```

2.1.5 Help

```
     :tutor – open tutorial
         ␣? – open command palette
```

2.2 Movement

2.2.1 Cursor Movement

Normal Mode: motion replaces selection
Select Mode: motion extends selection

```
       h/j/k/l – left / up / down / right
      gh, g| – beginning of line
      <nn>g| – column <nn>
          gl – end of line
          gg – top of file
<nn>G, g<nn>g – line <nn>
          ge – bottom of file
          gw – two-char labels on words, label to go to
               word

          g.– to last modification in current file
          gj – down textual line
          gk – up textual line

          gs – first non-white-space char
          gt – top of screen
          gc – middle of screen
          gb – bottom of screen
```

2.2.2 By Language Server Protocol

Requires LSP support.

```
gd – go to definition
gy – go to type definition
gr – go to references
gi – go to implementation

]d – next diagnostic
[d – prior diagnostic
]D – last diagnostic
[D – first diagnostic
```

2.2.3 By Treesitter - Syntax

Requires Treesitter support.

```
]f, [f – to next, prior function
]t, [t – to next, prior type definition
]T, [T – to next, prior test
]a, [a – to next, prior arg
]c, [c – to next, prior comment
]g, [g – to next, prior change
]G, [G – to last, first change

Alt-e – move to end of parent node in syntax tree
Alt-b – move to start of parent node in syntax tree
```

2.2.4 By Page

```
Ctrl-b – page up
Ctrl-f – page down
Ctrl-u – half page up
Ctrl-d – half page down
```

2.3 Selection

Selection: a range of characters between anchor and cursor
Normal Mode: move and select
Select Mode: move and extend selection

2.3.1 Operations

```
%     – select whole file
Alt-; – swap anchor and cursor
Alt-: – selection to normal direction (cursor at
        end)
Alt-o – expand selection syntax-aware
Alt-i – shrink selection
;     – collapse selection(s) to cursor(s)
```

2.3.2 By TextObjects

```
ma<ch> / mi<ch> – match around / inside the object
                  indicated by <ch> below:

          w / W – word / WORD
              p – paragraph
  (, [, ', etc.– specified surround pairs
              m –  closest surround pair
              f – function
              t – type or class
              a – argument/parameter
              c – comment
              T – test
              g – change git hunk
```

2.3.3 By Syntactic Objects

```
w / W – to start of next word / WORD
e / E – to end of current word / WORD
b / B – to start of current word / WORD
    x – current line, extend by line
    X – extend to line
Alt-x – shrink to line bounds
   ]p – to next paragraph
   [p – to prior paragraph
```

2.3.4 By Treesitter - Syntax

Requires Treesitter support.

```
Alt-o – expand selection to parent syntax node
Alt-i – shrink syntax tree object selection
Alt-p – select previous sibling node in syntax tree
Alt-n – select next sibling node in syntax tree
Alt-a – select all sibling nodes in syntax tree
Alt-I – select all children nodes in syntax tree
```

2.3.5 By Character Value

Lower case: forward
Upper case: backward

```
f<ch>, F<ch> – to <ch> inclusive (find)
t<ch>, T<ch> – to <ch> exclusive (till)
      Alt-.  – repeat last find / till
```

2.4 Select Mode

Movement: extends selection
Search: adds to selection

```
     v – toggle select mode
   Esc – return to normal
     ) – cycle primary selection forward
     ( – cycle primary selection backward
Alt-,  – remove primary selection
```

2.5 Multiple Selections

Multiple independent cursors / selections, one is *primary*.

2.5.1 Creating

Create multiple selections from selection.

```
    s<regex> – matches become selections
           S – split on match
      Alt-s – split on newlines
  C, Alt-C – add selection below, above
```

2.5.2 Operations

```
           & – align on primary cursor
Alt-<minus> – merge selections
Alt-<under> – merge consecutive selections
          , – remove all except primary selection
      Alt-, – remove primary selection
      ( / ) – rotate primary backwards / forwards
    Alt-( / – rotate content backward / forward
      Alt-)
           K – keep selections matching the regex
       Alt-K – remove selections matching the regex
```

2.6 Alter Buffer Content

2.6.1 Insert

```
           i – before selection
           a – after selection
           I – at start of line
           A – at end of line
           o – add line and insert below cursor
           O – add line and insert above cursor
         Esc – end insert (return to normal)
           . – repeat last insert
```

2.6.2 Add

```
          ]␣ – newline below
          [␣ – newline above
     ms<ch> – add delim <ch> around selection
```

2.6.3 Delete

```
           d – selection -> yank buf, delete selection
       Alt-d – delete, no save
     md<ch> – delete delim <ch> around selection
```

2.6.4 Change

```
           c – selection -> yank buf, change selection
       Alt-c – change, no save
           = – format by LSP
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.6.5 Indent Lines

```
           > – Indent line(s) containing selection
           < – Undent line(s) containing selection
```

2.6.6 Change Case

Change case of all letters in selection

```
           ~ – change case
           ` – set lowercase
      Alt-` – set uppercase
```

2.6.7 Comments

All apply to selection.

```
  ␣c, Ctrl-c – Toggle comment
          ␣C – Toggle block comment
     ␣Alt-C – Toggle line comment
```

2.6.8 Increment / Decrement

```
      Ctrl-a – increment the selected number
      Ctrl-x – decrement the selected number
```

2.6.9 Miscellaneous

```
           J – join lines in a selection
       Alt-J – join lines inside selection and select the
               inserted space
     <under> – trim whitespace from selection
    :reflow – wrap selection to <width>, default 80
    <width>
       :sort – sort ranges in selection
     :format – format file using external formatter /
               language server
```

2.7 Copy / Paste / Replace

```
           y – selection -> yank buf
           p – paste yank buf after the cursor
           P – paste yank buf before the cursor
          ␣y – yank selection(s) -> system clipboard
          ␣Y – yank main selection -> system clipboard
     ␣p / ␣P – paste clipboard after / before selections(s)
          ␣R – replace selection(s) with clipboard
       r<ch> – replace selection with <ch>
           R – replace selection with yank buf
           " – select register to yank to or paste from
```

2.8 Search

```
     /<regex> – search forward for regex
     ?<regex> – search backward for regex
        n, N – next, previous match
           * – search for current selection, respect word
               boundaries
       Alt-* – search for current selection
```

2.9 Registers

Identified by single char <ch>

```
  "<ch> – change to reg <ch>
 "<ch>y – yank into reg <ch>
 "<ch>p – paste from reg <ch>
 "<ch>R – replace with reg <ch>
```

2.10 Macros

```
 "<ch>Q – toggle capture to reg <ch>, default @
 "<ch>q – play macro in reg <ch>, default @
```

2.11 Jumplists

```
 Ctrl-s – save current position to jumplist
 Ctrl-i – move forward in jumplist
 Ctrl-o – move backwards in jumplist
     ␣j – open jumplist picker
```

2.12 Match Mode

With regard to balanced delimiters.

```
            mm – go to matching delim
      mi<ch> – match inside delim <ch>
      ma<ch> – match around delim <ch>
      ms<ch> – add delim <ch> around selection
      md<ch> – delete delim <ch> around selection
mr<ch1><ch2> – replace delim <ch1> with <ch2>
```

2.13 Shell

All commands pipe each selection to shell command.

```
     | – replace selection(s) with output
  Alt-| – ignore output
     ! – insert output before each selection(s)
  Alt-! – append output after each selection(s)
     $ – keep selection(s) where command
         returned 0
```

2.14 Approaching an IDE

```
     ␣G – debug - experimental
     ␣k – show documentation for item under
          cursor
     ␣s – open document symbol picker
     ␣S – open workspace symbol picker
     ␣d – open document diagnostics picker
     ␣D – open workspace diagnostics picker
     ␣r – rename symbol
     ␣a – apply code action
     ␣h – select symbol references for symbol under
          cursor
```

2.15 Editor Configuration

```
           :config-open – open the config file
:config-open-workspace – open the workspace config
                         file
        :config-reload – reload the config file
```

2.16 Miscellaneous

```
     ␣' – open last picker
     ␣/ – open global search in workspace folder
          picker
```

3 Commands in Specific Contexts

3.1 Insert Mode Editing

Navigation keys shown.

```
                Ctrl-s – commit undo checkpoint
                Ctrl-x – autocomplete
                Ctrl-r – insert a register content
   Ctrl-w, Alt-<bksp> – delete previous word
     Alt-d, Alt-<del> – delete next word
                Ctrl-u – delete to start of line
                Ctrl-k – delete to end of line
      Ctrl-h, <bksp>,– delete previous char
         Shift-<bksp>
       Ctrl-d, <del> – delete next char
     Ctrl-j, <enter> – insert new line
   <Up> <Down> <Left> – usual meaning but
     <Right> <PageUp>   discouraged
    <PageDown> <Home>
                <End>
```

3.2 Command Line Editing

```
           Esc, Ctrl-c – close prompt
               <enter> – open selected
                 <tab> – select next completion item
             <backtab> – select previous completion
                         item
                 Alt-b – backward a word
                Ctrl-b – backward a char
                 Alt-f – forward a word
                Ctrl-f – forward a char
                Ctrl-e – to prompt end
                Ctrl-a – to prompt start
  Ctrl-w, Ctrl-<bksp> – delete previous word
    Alt-d, Ctrl-<del> – delete next word
                Ctrl-u – delete to start of line
                Ctrl-k – delete to end of line
       <bksp>, Ctrl-h – delete previous char
        <del>, Ctrl-d – delete next char
                Ctrl-s – insert a word under doc
                         cursor (may be changed to
                         Ctrl-r Ctrl-w later)
                Ctrl-p – select previous history
                Ctrl-n – select next history
                Ctrl-r – insert the content of the
                         register selected by following
                         input char
```

3.3 Pickers

Navigation keys shown.

```
   Shift-<tab>, Ctrl-p,– previous entry
                   <Up>
 <tab>, Ctrl-n, <Down> – next entry
                 <Home> – to first entry
                  <End> – to last entry
      Ctrl-u, <PageUp> – page up
    Ctrl-d, <PageDown> – page down
               <enter> – open selected
          Alt-<enter> – open selected in the
                        background without closing
                        the picker
                Ctrl-s – open horizontally
                Ctrl-v – open vertically
                Ctrl-t – toggle preview
           Esc, Ctrl-c – close picker
```

3.4 Popups

Displays documentation for item under cursor.

```
      Ctrl-u – scroll up
      Ctrl-d – scroll down
```

3.5 Completion Menu

Displays documentation for the selected completion item. Any other keypresses result in the completion being accepted.

```
  Shift-Tab, Ctrl-p – previous entry
        Tab, Ctrl-n – next entry
            <enter> – close menu and accept
                      completion
             Ctrl-c – close menu and reject
                      completion
```

3.6 Signature-help Popup

Displays the signature of the selected completion item.

```
      Alt-p – previous signature
      Alt-n – next signature
```

4 Command Index

␣' – open last picker **(2.16)**
␣/ – open global search in workspace folder picker **(2.16)**
␣? – open command palette **(2.1.5)**
␣Alt-C – Toggle line comment **(2.6.7)**
␣C – Toggle block comment **(2.6.7)**
␣D – open workspace diagnostics picker **(2.14)**
␣F – open file picker at current working directory **(2.1.2)**
␣G – debug - experimental **(2.14)**
␣R – replace selection(s) with clipboard **(2.7)**
␣S – open workspace symbol picker **(2.14)**
␣Y – yank main selection -> system clipboard **(2.7)**
␣a – apply code action **(2.14)**
␣b – open buffer picker **(2.1.3)**
␣c – Toggle comment **(2.6.7)**
␣d – open document diagnostics picker **(2.14)**
␣f – open file picker at LSP workspace root **(2.1.2)**
␣g – open changed file picker **(2.1.2)**
␣h – select symbol references for symbol under cursor **(2.14)**
␣j – open jumplist picker **(2.11)**
␣k – show documentation for item under cursor **(2.14)**
␣p / ␣P – paste clipboard after / before selections(s) **(2.7)**
␣r – rename symbol **(2.14)**
␣s – open document symbol picker **(2.14)**
␣wF – open/create file(s) under selection(s) in vertical split **(2.1.2)**
␣wH/J/K/L – swap split with buffer on left / up / down / right **(2.1.4)**
␣wf – open/create file(s) under selection(s) in horizontal split **(2.1.2)**
␣wh/j/k/l – move to buffer left / up / down / right **(2.1.4)**
␣wns / ␣wnv – split horizontal / vertical, new buffer **(2.1.4)**
␣wo – close all but current split **(2.1.4)**
␣wq – close current split **(2.1.4)**
␣ws / ␣wv – split horizontal / vertical, current buffer **(2.1.4)**
␣wt – transpose split **(2.1.4)**
␣ww – next split **(2.1.4)**
␣y – yank selection(s) -> system clipboard **(2.7)**
! – insert output before each selection(s) **(2.13)**
" – select register to yank to or paste from **(2.7)**
"<ch> – change to reg <ch> **(2.9)**
"<ch>Q – toggle capture to reg <ch>, default @ **(2.10)**
"<ch>R – replace with reg <ch> **(2.9)**
"<ch>p – paste from reg <ch> **(2.9)**
"<ch>q – play macro in reg <ch>, default @ **(2.10)**
"<ch>y – yank into reg <ch> **(2.9)**
$ – keep selection(s) where command returned 0 **(2.13)**
$ – end of line **(1.5)**
% – select whole file **(2.3.1)**
& – align on primary cursor **(2.5.2)**
' – specified surround pairs **(2.3.2)**
( ) – capture group **(1.5)**
(– cycle primary selection backward **(2.4)**
(– specified surround pairs **(2.3.2)**
(/) – rotate primary backwards / forwards **(2.5.2)**
) – cycle primary selection forward **(2.4)**

* – search for current selection, respect word boundaries **(2.8)**
* – zero or more **(1.5)**
+ – one or more **(1.5)**
, – remove all except primary selection **(2.5.2)**
. – any character **(1.5)**
. – repeat last insert **(2.6.1)**
/<regex> – search forward for regex **(2.8)**
:bc – close current buffer **(2.1.3)**
:bca – close all buffers **(2.1.3)**
:bco – close all but current buffer **(2.1.3)**
:bn – next buffer **(2.1.3)**
:config-open – open the config file **(2.15)**
:config-open-workspace – open the workspace config file **(2.15)**
:config-reload – reload the config file **(2.15)**
:ear / :lat – move backward / forward in history by step count or time span (1s, 2m, 3h, 4d) **(2.1)**
:format – format file using external formatter / language server **(2.6.9)**
:hs <file> – open/create <file> in new horizontal split **(2.1.2)**
:n – create new scratch buffer **(2.1.3)**
:o <file> – open <file> in new buffer **(2.1.2)**
:q – quit current buffer, exits if last **(2.1.1)**
:reflow <width> – wrap selection to <width>, default 80 **(2.6.9)**
:sort – sort ranges in selection **(2.6.9)**
:tutor – open tutorial **(2.1.5)**
:vs <file> – open/create <file> in new vertical split **(2.1.2)**
:w <file> – write current buffer to <file> **(2.1.2)**
:wq – write current buffer and quit **(2.1.1)**
:wq <file> – write current buffer to <file> and quit **(2.1.1)**
:wqa – write all buffer(s) and quit **(2.1.1)**
; – collapse selection(s) to cursor(s) **(2.3.1)**
< – Undent line(s) containing selection **(2.6.5)**
<Down> – next entry **(3.3)**
<End> – to last entry **(3.3)**
<Home> – to first entry **(3.3)**
<PageDown> – page down **(3.3)**
<PageUp> – page up **(3.3)**
<Up> – previous entry **(3.3)**
<Up> <Down> <Left> <Right> <PageUp> <PageDown> <Home> <End> – usual meaning but discouraged **(3.1)**
<backtab> – select previous completion item **(3.2)**
<bksp> – delete previous char **(3.1)**
<bksp> – delete previous char **(3.2)**
<del> – delete next char **(3.1)**
<del> – delete next char **(3.2)**
<enter> – close menu and accept completion **(3.5)**
<enter> – insert new line **(3.1)**
<enter> – open selected **(3.2)**
<enter> – open selected **(3.3)**
<enter> – open selected in current view **(2.1.2.1)**
<nn><cmd> – repeat <cmd> <nn> times **(2.1)**
<nn>G – line <nn> **(2.2.1)**
<nn>g| – column <nn> **(2.2.1)**
<tab> – next entry **(3.3)**

`<tab>` – select next completion item **(3.2)**
`<under>` – trim whitespace from selection **(2.6.9)**
`=` – format by LSP **(2.6.4)**
`>` – Indent line(s) containing selection **(2.6.5)**
`?` – zero or one / lazy modifier **(1.5)**
`?<regex>` – search backward for regex **(2.8)**
`A` – at end of line **(2.6.1)**
`Alt-!` – append output after each selection(s) **(2.13)**
`Alt-( /` – rotate content backward / forward **(2.5.2)**
`Alt-)`
`Alt-*` – search for current selection **(2.8)**
`Alt-,` – remove primary selection **(2.4)**
`Alt-,` – remove primary selection **(2.5.2)**
`Alt-.` – repeat last find / till **(2.3.5)**
`Alt-:` – selection to normal direction (cursor at end) **(2.3.1)**
`Alt-;` – swap anchor and cursor **(2.3.1)**
`Alt-<bksp>` – delete previous word **(3.1)**
`Alt-<del>` – delete next word **(3.1)**
`Alt-<enter>` – open selected in the background without closing the picker **(3.3)**
`Alt-<minus>` – merge selections **(2.5.2)**
`Alt-<under>` – merge consecutive selections **(2.5.2)**
`Alt-C` – add selection below, above **(2.5.1)**
`Alt-I` – select all children nodes in syntax tree **(2.3.4)**
`Alt-J` – join lines inside selection and select the inserted space **(2.6.9)**
`Alt-K` – remove selections matching the regex **(2.5.2)**
`Alt-` ` – set uppercase **(2.6.6)**
`Alt-a` – select all sibling nodes in syntax tree **(2.3.4)**
`Alt-b` – backward a word **(3.2)**
`Alt-b` – move to start of parent node in syntax tree **(2.2.3)**
`Alt-c` – change, no save **(2.6.4)**
`Alt-d` – delete next word **(3.1)**
`Alt-d` – delete next word **(3.2)**
`Alt-d` – delete, no save **(2.6.3)**
`Alt-e` – move to end of parent node in syntax tree **(2.2.3)**
`Alt-f` – forward a word **(3.2)**
`Alt-i` – shrink selection **(2.3.1)**
`Alt-i` – shrink syntax tree object selection **(2.3.4)**
`Alt-n` – next signature **(3.6)**
`Alt-n` – select next sibling node in syntax tree **(2.3.4)**
`Alt-o` – expand selection syntax-aware **(2.3.1)**
`Alt-o` – expand selection to parent syntax node **(2.3.4)**
`Alt-p` – previous signature **(3.6)**
`Alt-p` – select previous sibling node in syntax tree **(2.3.4)**
`Alt-s` – split on newlines **(2.5.1)**
`Alt-u /` – move backward / forward in tree history **(2.1)**
`Alt-U`
`Alt-x` – shrink to line bounds **(2.3.3)**
`Alt-|` – ignore output **(2.13)**
`C` – add selection below, above **(2.5.1)**
`Ctrl-<bksp>` – delete previous word **(3.2)**
`Ctrl-<del>` – delete next word **(3.2)**
`Ctrl-a` – increment the selected number **(2.6.8)**
`Ctrl-a` – to prompt start **(3.2)**
`Ctrl-b` – backward a char **(3.2)**
`Ctrl-b` – page up **(2.2.4)**
`Ctrl-c` – Toggle comment **(2.6.7)**
`Ctrl-c` – close menu and reject completion **(3.5)**
`Ctrl-c` – close picker **(3.3)**
`Ctrl-c` – close prompt **(3.2)**
`Ctrl-d` – delete next char **(3.1)**
`Ctrl-d` – delete next char **(3.2)**
`Ctrl-d` – half page down **(2.2.4)**
`Ctrl-d` – page down **(3.3)**
`Ctrl-d` – scroll down **(3.4)**
`Ctrl-e` – to prompt end **(3.2)**
`Ctrl-f` – forward a char **(3.2)**
`Ctrl-f` – page down **(2.2.4)**
`Ctrl-h` – delete previous char **(3.1)**
`Ctrl-h` – delete previous char **(3.2)**
`Ctrl-i` – move forward in jumplist **(2.11)**
`Ctrl-j` – insert new line **(3.1)**
`Ctrl-k` – delete to end of line **(3.1)**
`Ctrl-k` – delete to end of line **(3.2)**
`Ctrl-n` – next entry **(3.3)**
`Ctrl-n` – next entry **(3.5)**
`Ctrl-n` – select next history **(3.2)**
`Ctrl-o` – move backwards in jumplist **(2.11)**
`Ctrl-p` – previous entry **(3.3)**
`Ctrl-p` – previous entry **(3.5)**
`Ctrl-p` – select previous history **(3.2)**
`Ctrl-r` – insert a register content **(3.1)**
`Ctrl-r` – insert the content of the register selected by following input char **(3.2)**
`Ctrl-s` – commit undo checkpoint **(3.1)**
`Ctrl-s` – insert a word under doc cursor (may be changed to Ctrl-r Ctrl-w later) **(3.2)**
`Ctrl-s` – open horizontally **(3.3)**
`Ctrl-s` – open selected in new horizontal split **(2.1.2.1)**
`Ctrl-s` – save current position to jumplist **(2.11)**
`Ctrl-t` – toggle preview **(3.3)**
`Ctrl-u` – delete to start of line **(3.1)**
`Ctrl-u` – delete to start of line **(3.2)**
`Ctrl-u` – half page up **(2.2.4)**
`Ctrl-u` – page up **(3.3)**
`Ctrl-u` – scroll up **(3.4)**
`Ctrl-v` – open selected in new vertical split **(2.1.2.1)**
`Ctrl-v` – open vertically **(3.3)**
`Ctrl-w` – delete previous word **(3.1)**
`Ctrl-w` – delete previous word **(3.2)**
`Ctrl-x` – autocomplete **(3.1)**
`Ctrl-x` – decrement the selected number **(2.6.8)**
`Esc` – close picker **(3.3)**
`Esc` – close prompt **(3.2)**
`Esc` – end insert (return to normal) **(2.6.1)**
`Esc` – return to normal **(2.4)**
`Esc` – return to normal mode **(2.1)**
`F<ch>` – to <ch> inclusive (find) **(2.3.5)**
`I` – at start of line **(2.6.1)**
`J` – join lines in a selection **(2.6.9)**
`K` – keep selections matching the regex **(2.5.2)**
`N` – next, previous match **(2.8)**
`O` – add line and insert above cursor **(2.6.1)**
`P` – paste yank buf before the cursor **(2.7)**
`R` – replace selection with yank buf **(2.7)**
`S` – split on match **(2.5.1)**
`Shift-<bksp>` – delete previous char **(3.1)**
`Shift-<tab>` – previous entry **(3.3)**
`Shift-Tab` – previous entry **(3.5)**
`T` – test **(2.3.2)**
`T<ch>` – to <ch> exclusive (till) **(2.3.5)**
`Tab` – next entry **(3.5)**
`X` – extend to line **(2.3.3)**
`Z` – enter sticky mode, exit with Esc **(2.1.4.1)**
`[␣` – newline above **(2.6.2)**
`[` – specified surround pairs **(2.3.2)**
`[ ]` – character class **(1.5)**

- **[D** – first diagnostic **(2.2.2)**
- **[G** – to last, first change **(2.2.3)**
- **[T** – to next, prior test **(2.2.3)**
- **[a** – to next, prior arg **(2.2.3)**
- **[c** – to next, prior comment **(2.2.3)**
- **[d** – prior diagnostic **(2.2.2)**
- **[f** – to next, prior function **(2.2.3)**
- **[g** – to next, prior change **(2.2.3)**
- **[p** – to prior paragraph **(2.3.3)**
- **[t** – to next, prior type definition **(2.2.3)**
- **** – escape character itself **(1.5)**
- **]␣** – newline below **(2.6.2)**
- **]D** – last diagnostic **(2.2.2)**
- **]G** – to last, first change **(2.2.3)**
- **]T** – to next, prior test **(2.2.3)**
- **]a** – to next, prior arg **(2.2.3)**
- **]c** – to next, prior comment **(2.2.3)**
- **]d** – next diagnostic **(2.2.2)**
- **]f** – to next, prior function **(2.2.3)**
- **]g** – to next, prior change **(2.2.3)**
- **]p** – to next paragraph **(2.3.3)**
- **]t** – to next, prior type definition **(2.2.3)**
- **^** – start of line / negation in class **(1.5)**
- **`** – set lowercase **(2.6.6)**
- **a** – after selection **(2.6.1)**
- **a** – argument/parameter **(2.3.2)**
- **b / B** – to start of current word / WORD **(2.3.3)**
- **c** – comment **(2.3.2)**
- **c** – selection -> yank buf, change selection **(2.6.4)**
- **d** – selection -> yank buf, delete selection **(2.6.3)**
- **e / E** – to end of current word / WORD **(2.3.3)**
- **etc.** – specified surround pairs **(2.3.2)**
- **f** – function **(2.3.2)**
- **f<ch>** – to <ch> inclusive (find) **(2.3.5)**
- **g** – change git hunk **(2.3.2)**
- **g.** – to last modification in current file **(2.2.1)**
- **g<nn>g** – line <nn> **(2.2.1)**
- **ga** – go to last accessed/alternate buffer **(2.1.3)**
- **gb** – bottom of screen **(2.2.1)**
- **gc** – middle of screen **(2.2.1)**
- **gd** – go to definition **(2.2.2)**
- **ge** – bottom of file **(2.2.1)**
- **gf** – open/create file(s) under selection, open url under selection. **(2.1.2)**
- **gg** – top of file **(2.2.1)**
- **gh** – beginning of line **(2.2.1)**
- **gi** – go to implementation **(2.2.2)**
- **gj** – down textual line **(2.2.1)**
- **gk** – up textual line **(2.2.1)**
- **gl** – end of line **(2.2.1)**
- **gm** – go to last modified/alternate buffer **(2.1.3)**
- **gn** – go to next buffer **(2.1.3)**
- **gp** – go to previous buffer **(2.1.3)**
- **gr** – go to references **(2.2.2)**
- **gs** – first non-white-space char **(2.2.1)**
- **gt** – top of screen **(2.2.1)**
- **gw** – two-char labels on words, label to go to word **(2.2.1)**
- **gy** – go to type definition **(2.2.2)**
- **g|** – beginning of line **(2.2.1)**
- **h/j/k/l** – left / up / down / right **(2.2.1)**
- **i** – before selection **(2.6.1)**
- **m** – closest surround pair **(2.3.2)**
- **ma<ch>** – match around delim <ch> **(2.12)**
- **ma<ch> / mi<ch>** – match around / inside the object indicated by <ch> below: **(2.3.2)**
- **md<ch>** – delete delim <ch> around selection **(2.12)**
- **md<ch>** – delete delim <ch> around selection **(2.6.3)**
- **mi<ch>** – match inside delim <ch> **(2.12)**
- **mm** – go to matching delim **(2.12)**
- **mr<ch1><ch2>** – replace delim <ch1> with <ch2> **(2.12)**
- **mr<ch1><ch2>** – replace delim <ch1> with <ch2> **(2.6.4)**
- **ms<ch>** – add delim <ch> around selection **(2.12)**
- **ms<ch>** – add delim <ch> around selection **(2.6.2)**
- **n** – next, previous match **(2.8)**
- **o** – add line and insert below cursor **(2.6.1)**
- **p** – paragraph **(2.3.2)**
- **p** – paste yank buf after the cursor **(2.7)**
- **r<ch>** – replace selection with <ch> **(2.7)**
- **s<regex>** – matches become selections **(2.5.1)**
- **t** – type or class **(2.3.2)**
- **t<ch>** – to <ch> exclusive (till) **(2.3.5)**
- **u / U** – undo / redo change in linear history **(2.1)**
- **v** – toggle select mode **(2.4)**
- **w / W** – to start of next word / WORD **(2.3.3)**
- **w / W** – word / WORD **(2.3.2)**
- **x** – current line, extend by line **(2.3.3)**
- **y** – selection -> yank buf **(2.7)**
- **zb** – align to bottom **(2.1.4.1)**
- **zc** – align to center **(2.1.4.1)**
- **zj** – scroll down **(2.1.4.1)**
- **zk** – scroll up **(2.1.4.1)**
- **zm** – align to middle horizontally **(2.1.4.1)**
- **zt** – align to top **(2.1.4.1)**
- **zz** – align to center **(2.1.4.1)**
- **{ }** – repetition count **(1.5)**
- **|** – alternation **(1.5)**
- **|** – replace selection(s) with output **(2.13)**
- **~** – change case **(2.6.6)**