# Beyond Expected Goals: A Probabilistic Framework for Shot Occurrences in Soccer

Tianshu Feng, Jonathan Pipping, and Paul Sabin

University of Pennsylvania

July 29, 2025



## What Are Expected Goals (xG)?

- Expected Goals (xG) is a metric that estimates the probability that a shot is scored
- Depends on factors like distance from goal, angle to goal, shot type, and player positions
- Estimated by XGBoost models trained on historical shot data
- Often used to measure the quality of a chance
- Aggregated over a match or season to measure team performance



#### Limitations of xG

- Models are only trained on **observed** shots, inducing significant selection bias
- Skilled attackers who take more shots are over-represented
- Threatening attacks with no recorded shots are omitted
- Aggregating xG across a match double-counts rebound chances



#### Visual Example 1

Video: Player has clear chance but passes instead of shooting



## Visual Example 2

Video: Multiple shots from same attacking sequence w/xG that add over 1



#### Methods

- Statistical approach
- Data processing steps
- Model specifications



## Statistical Approach

- xShot: the probability that a shot occurs in the next second
- Build a model to estimate xShot based on features from tracking data
- Also build our own version of xG model using the same features on observed shots
- Estimate the probability of goal as  $P(goal) = P(shot) \cdot P(goal|shot)$



## **Data Processing**

- Remove games where no shots are recorded
- Only keep frames where the ball is in play and a team has clear possession
- Linearly interpolate ball positions to fill in missing frames
- attack: Index of the attack the current frame is on (0 if it is not on an attack)
  - Start with the attacking team gaining possession in their attacking third
  - End with the defending team regaining possession or the ball is out of their attacking third
  - Only keep frames with attack > 0



## **Data Processing**

- Rotate the coordinates  $180^{\circ}$  around the center point for frames where the team attacks from right to left to unify the attacking directions and make all x-coordinates positive
- Use a polar coordinate system centered on the goal for the ball
  - $\bullet$   $\textit{r}_{\textit{ball}}$  and  $\theta_{\textit{ball}}$  represent the distance and angle of the ball from the goal
  - Keep the z-coordinate and compute the speed of the ball
- Use a polar coordinate system centered on the ball for each player
  - Choose the 5 closest offense teammates and non-GK defenders to the ball as features
  - Keep goalkeeper positions as a separate feature



## **Data Processing**

- openGoal: Percentage of the goal that is open from the ball's position
  - Simplify every defender as a circle with a radius of 0.75 m
  - Compute the two tangent lines from the ball to every defender in front of the ball their intersection points with the goal line
  - Calculate the length of the open goal as the length of goal not covered by segments formed by the intersection points



## **Model Specifications**

- Trained on all tracking data of 2022-2025 Premier League seasons
- Use a 5-fold cross-validation to evaluate both xG and xShot XGBoost models
- Choose log loss as the evaluation metric



#### Results

- Key findings
- Statistical significance
- Practical implications



#### **Conclusions**

- Summary of main points
- Future work
- Questions and discussion



#### Thank You

Questions?

