

今天我们来制作**poker** 这个牌类游戏

1. understanding (理解问题)

Start with a vague understanding that you refine into a problem.

2. specify (明确问题)

Specify how this problem can be made amenable to being coded.

3. design (设计程序)

Coding

游戏规则：

- 所有可能的手牌

- 0- High Card
- 1- One Pair
- 2- Two Pair
- 3- Three of a Kind
- 4- Straight
- 5- Flush
- 6- Full House
- 7- Four of a Kind
- 8- Straight Flush



【注：我们用其对应的数字作为得分】

详细游戏规则自行上维基百科上查看


如何在hands 中存储我们的手牌，手牌由数字和花色组成（可以采用如下方式）：

```
sf = ['6C', '7C', '8C', '9C', 'TC'] # Straight Flush  
  
fk = ['9D', '9H', '9S', '9C', '7D'] # Four of a Kind  
  
fh = ['TD', 'TC', 'TH', '7C', '7D'] #Full House
```

用何种数据结构来存放这些手牌类型：




FULL HOUSE,
EIGHTS OVER KINGS!




(6, 8, 13)

STRAIGHT,
JACK HIGH.



(4, 11)

THREE SEVENS!



(3, 7, [7, 7, 7, 5, 2])

TWO PAIR,
JACKS AND THREES!



(2, 11, 3, [13, 11, 11, 3, 3])

我们最终要判断哪副手牌可以获胜，所以我们需要一个判断胜负的函数

```
Def poker(hands):  
    "return the best hand"
```

进一步分析我们要判断大小，那么我们需要对手牌有一个大小的衡量机制

```
Def hand_rank(hand):  
    "return the rank of hand"
```

有了这个大小的度量机制之后

```
| return max(hands, key=hand_rank) 就能返回 best hand
```

于是我们得到我们的poker 函数

```
def poker(hands):  
    "Return the best hand: poker([hand,...]) => hand"  
    return max(hands, key=hand_rank)
```

接下来我们要完成hand_rank() 函数，因为hand_rank 函数涉及到手牌的类型，所以我们要完成对手牌类型的判断

Straight

```
straight(ranks):
```

```
returns True if the hand is a straight.
```

Flush

```
flush(hand):
```

```
returns True if the hand is a flush
```

Kind

```
kind(n, ranks):
```

```
returns the first rank that the hand has exactly n of.  
For A hand with 4 sevens this function would return 7.
```

two_pair

```
two_pair(ranks):
```

```
if there is a two pair, this function returns their  
corresponding ranks as a tuple. For example, a hand with 2 twos and 2  
fours would cause this function to return (4, 2).
```

card_ranks

```
card_ranks(hand):
```

```
returns an ORDERED tuple of the ranks in a hand  
(where the order goes from highest to lowest rank).
```

假定以上函数已经完成，那么我们的hand_rank 函数如下

```

def hand_rank(hand):
    ranks = card_ranks(hand)
    if straight(ranks) and flush(hand):           # straight flush
        return (8, max(ranks))
    elif kind(4, ranks):                           # 4 of a kind
        return (7, kind(4, ranks), kind(1, ranks))
    elif kind(3, ranks) and kind(2, ranks):        # full house
        return (6, kind(3, ranks), kind(2, ranks))
    elif flush(hand):                              # flush
        return (5, ranks)
    elif straight(ranks):                          # straight
        return (4, max(ranks))
    elif kind(3, ranks):                           # 3 of a kind
        return (3, kind(3, ranks), ranks)
    elif two_pair(ranks):                          # 2 pair
        return (2, two_pair(ranks), ranks)
    elif kind(2, ranks):                           # kind
        return (1, kind(2, ranks), ranks)
    else:                                           # high card
        return (0, ranks)

```

为了检验我们的程序是否成功，我们常常需要做测试，例如可以通过assert 来检验，样例代码如下

```

def test():
    "Test cases for the functions in poker program"
    sf = "6C 7C 8C 9C TC".split() # Straight Flush
    fk = "9D 9H 9S 9C 7D".split() # Four of a Kind
    fh = "TD TC TH 7C 7D".split() # Full House
    assert poker([sf, fk, fh]) == sf
    assert poker([fk, fh]) == fk
    assert poker([fh, fh]) == fh
    assert poker([sf]) == sf
    assert poker([sf] + 99*[fh]) == sf
    assert hand_rank(sf) == (8, 10)
    assert hand_rank(fk) == (7, 9, 7)
    assert hand_rank(fh) == (6, 10, 7)
    return 'tests pass'

```

接下来我们来具体实现判断手牌类型的函数

Straight

```
def straight(ranks):
    "Return True if the ordered ranks form a 5-card straight."
    min_num = ranks[0]
    List = [min_num - i for i in range(len(ranks))]
    if List == ranks:
        return True
    else:
        return False
```

或

```
def straight(ranks):
    "return true if the ordered ranks from a 5-card straight"
    return (max(ranks)-min(ranks) == 4) and len(set(ranks)) == 5
```

Flush

```
def flush(hand):
    "Return True if all the cards have the same suit."
    suit = [s for n,s in hand]
    if [suit[0]]*len(suit) == suit:
        return True
    else:
        return False
```

或

```
def flush(hand):
    "return true if all the cards have the same suit"
    suits = [s for r,s in hand]

    return len(set(suits)) == 1
```

Kind

```
def kind(n, ranks):
    """Return the first rank that this hand has exactly n of.
    Return None if there is no n-of-a-kind in the hand."""
    from collections import Counter
    c = Counter(ranks)
    for i in set(ranks):
        if c.get(i) == n:
            return i
        break

    return None
```


或

```
def kind(n,ranks):
    "Return the first rank that this hand has exactly n of.Return None
    if there is no n-of-a-kind in the hand."
    for r in ranks :
        if ranks.count(r) == n : return r

    return None
```

two_pair

```
def two_pair(ranks):
    """If there are two pair, return the two ranks as a
    tuple: (highest, lowest); otherwise return None."""
    pair=[]
    for i in set(ranks):
        if ranks.count(i) == 2 : pair.append(i)
    if len(pair) == 2:
        return tuple(sorted(pair,reverse = True))
    else:
        return None
```

或

```
def two_pair(ranks):
    "If there are two pair, return the two ranks as a
    tuple: (highest, lowest); otherwise return None."
    pair = kind(2,ranks)
    lowpair = kind(2,list(reversed(ranks)))
    if pair and lowpair != pair
        return (pair , lowpair)
    else:
        return None
```

card_ranks

```
def card_ranks(cards):
    "Return a list of the ranks, sorted with higher first."
    def map(r):
        if r == 'T':
            return 10
        elif r == 'J':
            return 11
        elif r == 'Q':
            return 12
        elif r == 'K':
            return 13
        elif r == 'A':
            return 14
        else:
            return int(r)
    ranks = [map(r) for r,s in cards]
    ranks.sort(reverse=True)

    return ranks
```

或

```
def card_ranks(hand):
    "return a list of the ranks , sorted with higher first"
    ranks = ['--23456789TJQKA'.index(r) for r,s in hand]
    ranks.sort(reverse = True)

    return ranks
```

注意到，我们希望A12345 也是straight，故我们需要对代码进行修改

读者可以考虑下，是修改straight 函数呢还是修改card_ranks 函数

我们修改card_ranks 函数得到

```
def card_ranks(hand):
    "return a list of the ranks , sorted with higher first"
    ranks = ['--23456789TJQKA'.index(r) for r,s in hand]
    ranks.sort(reverse = True)
    return [5,4,3,2,1] if (ranks == [14,5,4,3,2]) else ranks
```

考虑到可能有多个一样的最大，写allmax 函数同时返回多个相同的最大

```
def allmax(iterable ,key = None):
    "return a list of all items equal to the max of the iterable"
    result , maxval =[],None
    key = key or (lambda: x:x)
    for x in iterable:
        xval = key(x)
        if not result or xval > maxval:
            result , maxval = [x] , xval
        elif xval == maxval:
            result.append(x)
    return result
```

于是我们修改poker 函数得到

```
def poker(hands):
    "Return the best hand: poker([hand,...]) => hand"
    return allmax(hands, key=hand_rank)
```

有了规则之后，我们就要进行洗牌和发牌了

首先我们构建一副牌

```
mydeck = [r+s for r in '23456789TJQKA' for s in 'SHDC']
```

然后考虑发牌规则和参赛人数（numhands），poker 默认每人5张牌

```
def deal(numhands, n=5, deck=mydeck):
    random.shuffle(deck)
    hands=[ [' ']*n]*numhands
    for i in range(numhands):
        for j in range(n):
            if len(deck)>0:
                hands[i][j]=deck.pop(0)
            else:
                deck=mydeck
                random.shuffle(deck)
    return hands
```

或

```
def deal(numhands , n=5, deck = [r+s for r in '23456789TJQKA' for s in
'SHDC']):
    random.shuffle(deck)
    return [deck[n*i:n*(i+1)] for i in range(numhands)]

# only one deck
```

游戏的组建全部完成，我们可以开始开心地游戏了

```
In [38]: hands = deal(5)
```

```
In [40]: hands
```

```
Out[40]:
```

```
[['TS', '7H', '8D', 'AH', 'TC'],  
 ['JS', 'QH', 'QD', '3C', 'KS'],  
 ['9S', '8H', 'QS', '2S', '8C'],  
 ['2H', '7D', '9D', 'KD', '5H'],  
 ['JH', '2D', '3H', '9H', '6D']]
```

```
In [39]: poker(hands)
```

```
Out[39]: [['JS', 'QH', 'QD', '3C', 'KS']]
```

```
# have a look
```

```
In [41]: for h in hands:
```

```
    ...:     print hand_rank(h)
```

```
    ...:
```

```
(1, 10, [14, 10, 10, 8, 7])
```

```
(1, 12, [13, 12, 12, 11, 3])
```

```
(1, 8, [12, 9, 8, 8, 2])
```

```
(0, [13, 9, 7, 5, 2])
```

```
(0, [11, 9, 6, 3, 2])
```