

- 基本理论

1. 每个个体看作一个点（暂时用二维的点）【多维情况下，每一个维度都可以是对个人某一属性的描述】
2. 点的走向作为个人的发展情况
3. 社会初期随机发展，一定时间后个人发展受朋友影响
4. 前一次的点与后一次的点构成一个线段
5. 在某一时间内， $\lambda_A$  对应的线段与  $\lambda_B$  对应的线段相交，则认定两人相识（成为朋友）
6. 两点之间的距离作为两个人亲密度的度量，前提是成为朋友
7. 在达到一定年龄之后，人们会选择与自己亲密度最佳（距离最小）的异性朋友作为伴侣（成为恋人），一定时间后产生新的人类
8. 未完待续

- 算法实现

## Code: humans

```
# -*- coding: utf-8 -*-
"""
Created on Thu Sep 24 10:48:48 2015

# Human

@author: Zhang_Jun
"""
import random
import math

class human(object):
    def __init__(self, ID):
        self.ID = ID # 编号
        self.sex = random.randint(1, 2) # 随机产生性别
        self.x_before = 0 ; self.y_before = 0 # 个人状态描述(前)
        self.x_after = 0 ; self.y_after = 0 # 个人状态描述(后)
        self.vector = [self.x_after - self.x_before , self.y_after -
self.y_before] # 个人生活方向
        self.ability = 1 # 发展潜力，决定了个人发展方向的模长
        self.age = 0 # 个人的年龄
        self.friend = [(ID, self)] # 个人的所有好友列表（编号，包含好友所有信息的
对象）
        self.friend_distance_sex = [(ID, 0, 0)] # 好友的亲密度与性别属性（编号、亲
密度、性别同性与否[0:同性，1:异性]）
        self.mate = [ID, self, 100000] # 个人的配偶，配偶编号 以及 亲密度
        self.stage = 1 # 个人的生存状况 1 为 生 0 为 死
        self.time = 0 # 记录时间流逝，可以构造一个与年龄转换的函数（自定义）
```

```

def initiate_grow(self,step): # 社会刚形成期间, 每个人随机发展, 不受他人影响
    for i in range(step): # step 为控制发展次数的参数()
        self.time = self.time + 1 # 每step一次, 增加一个时间单位
        self.x_before = self.x_after
        angle = random.randint(0,360)/180.0 * math.pi
        self.x_after = self.x_after + self.ability * math.cos(angle)
        self.y_before = self.y_after
        self.y_after = self.y_after + self.ability * math.sin(angle)
        self.vector = [self.x_after - self.x_before , self.y_after -
self.y_before]

def grow(self,step,coef_friend,coef_random):
    self.time = self.time = self.time + 1
    self.x_before = self.x_after
    self.y_before = self.y_after
    friend_effect = [i * coef_friend for i in
norm(sum_direction(self.friend))]
    angle = random.randint(0,360)/180.0 * math.pi
    random_effect = [i*coef_random for i in norm([math.cos(angle) ,
math.sin(angle)])]
    direction =[i * self.ability for i in
norm(sum_list(friend_effect,random_effect))]
    [self.x_after,self.y_after] = sum_list([self.x_before,self.y_before]
, direction)
    self.vector = [self.x_after - self.x_before , self.y_after -
self.y_before]
    self.ability = sigmoid(inverse_sigmoid(self.ability) + coef_random *
random.randint(-5,5)+ coef_friend *
inverse_sigmoid(friend_ability(self.friend,self.ability)))

def sigmoid(x): # 控制个人能力增长的幅度
    return 2.0/(math.exp(-0.1*x)+1)

def inverse_sigmoid(y):
    return 10*math.log(y / (2.0-y) )

def sum_list(a,b):
    return [x+y for x,y in zip(a,b)]

def sum_direction(friend_List):
    direction =[0,0]
    for friend in friend_List:
        direction = sum_list(direction,friend[1].vector)
    return direction

def norm(L):
    ss = 0 # 平方和
    for i in L:
        ss = ss + i*i

```

```

sss = math.sqrt(ss)
return [x/sss for x in L]

def friend_ability(friend_List,self_ability):
    fri_ability = [fri[1].ability for fri in friend_List]
    return (1.0*sum(fri_ability)/len(fri_ability) - self_ability)*0.5 + 1

#-----相遇判断函数-----
# 线段的交点    ->    是否有交点/交点是否在线段上
# -kx+y=b

def meet(human1,human2) :
    delta =1e-10
    P1 = [human1.x_before,human1.y_before]
    P2 = [human1.x_after,human1.y_after]
    P3 = [human2.x_before,human2.y_before]
    P4 = [human2.x_after,human2.y_after]

    if (P2[0]-P1[0])==0: # in case of denominator equals 0 (避免分母为0的情况)
        if (P3[0]-P4[0])==0:
            return 0
        else:
            k2 = 1.0*(P4[1]-P3[1])/(P4[0]-P3[0])
            b2 = -k2*P3[0]+P3[1]
            P = [P1[0],k2*P1[0]+b2]
            if (P[0]-P1[0])*(P[0]-P2[0])<=0 and (P[0]-P3[0])*(P[0]-P4[0])<=0
            \
            and (P[1]-P1[1])*(P[1]-P2[1])<=0 and (P[1]-P3[1])*(P[1]-P4[1])
            <=0 :
                return 1
            else:
                return 0
    elif (P4[0]-P3[0])==0: # in case of denominator equals 0 (避免分母为0的情况)
        if (P2[0]-P1[0])==0:
            return 0
        else:
            k1 = 1.0*(P2[1]-P1[1])/(P2[0]-P1[0])
            b1 = -k1*P1[0]+P1[1]
            P = [P3[0],k1*P3[0]+b1]
            if (P[0]-P1[0])*(P[0]-P2[0])<=0 and (P[0]-P3[0])*(P[0]-P4[0])<=0
            \
            and (P[1]-P1[1])*(P[1]-P2[1])<=0 and (P[1]-P3[1])*(P[1]-P4[1])
            <=0 :
                return 1
            else:
                return 0

```

```

else:
    k1 = 1.0 * (P2[1] - P1[1]) / (P2[0] - P1[0])
    k2 = 1.0 * (P4[1] - P3[1]) / (P4[0] - P3[0])
    b1 = -k1 * P1[0] + P1[1]
    b2 = -k2 * P3[0] + P3[1]
    if abs(k1 - k2) < delta: # if use k1=k2 will cause singular
matrix 精确度问题
        return 0
    else: # 求解两直线交点
        P=[0,0]
        P[0] = (b1 - b2) / (k2 - k1)
        P[1] = (k2 * b1 - k1 * b2) / (k2-k1)
        # 判断交点是否在线段上
        if (P[0]-P1[0])*(P[0]-P2[0])<=0 and (P[0]-P3[0])*(P[0]-P4[0])<=0
\
        and (P[1]-P1[1])*(P[1]-P2[1])<=0 and (P[1]-P3[1])*(P[1]-P4[1])
<=0 :
            return 1
        else:
            return 0

```

## Code: simulate (待注释)

```

# -*- coding: utf-8 -*-
"""
Created on Thu Sep 24 11:14:11 2015

@author: Zhang_Jun
"""

import human
import math
import pylab as plt
import numpy as np
import pandas as pd
import seaborn
seaborn.set()

# -----generate humans-----

humans = []
human_number = 1000 # number of initiate humans

for i in range(human_number):
    humans.append(human.human(i))

```

```

#-----

#----- the initiate grows of humans-----

Time = 2

for people in humans:
    people.initiate_grow(Time)

#-----show the vector of humans-----
V = [people.vector for people in humans ]

human_V = np.array(V)
#plt.plot(human_V[:,0],human_V[:,1],'.')
#plt.figure()

#-----
def draw_grow(number):
    Position =
    [[people.x_before,people.x_after,people.y_before,people.y_after] for people
in humans]
    X_Position = np.array(Position)[:,:2]
    Y_Position = np.array(Position)[:,:2:]
    for i in range(number):
        plt.plot(X_Position[i],Y_Position[i])

#-----

for i in range(10):
    for people in humans:
        people.initiate_grow(1)
        draw_grow(human_number)

# after initiate grow , the growth of people should folow some rule

marrage_age_bottom = 20
marrage_age_top = 40

#-----meet -----
Meet=np.zeros(human_number*human_number).reshape(human_number,human_number)
Meet_people=[]

for t in range(10):
    for people in humans:
        people.grow(1,0.8,0.2)
        #draw_grow(human_number)

```

```

for i in range(human_number):
    for j in range(human_number):
        if Meet[i,j]==0 and i != j:
            Meet[i,j] = human.meet(humans[i],humans[j])
        if Meet[i,j] == 1 and (i,j) not in Meet_people:
            Meet_people.append((i,j))
#print Meet_people
#print Meet

for fri in Meet_people:    # friend in Meet_people
    if (fri[1],humans[fri[1]]) not in humans[fri[0]].friend:
        humans[fri[0]].friend.append((fri[1],humans[fri[1]]))
        distance = math.sqrt( math.pow(humans[fri[1]].x_after \
- humans[fri[0]].x_after , 2) + math.pow(humans[fri[1]].y_after \
\
- humans[fri[0]].y_after , 2))
        sex_compare = 0 if humans[fri[0]].sex == humans[fri[1]].sex else
1
humans[fri[0]].friend_distance_sex.append((fri[1],distance,sex_compare))
# -----
#draw_grow(human_number)
have_friend = set([p[0] for p in Meet_people])

for i in have_friend:
    table1 = humans[i].friend    # 所有的朋友    (编号和对象)
    table2 = humans[i].friend_distance_sex    # 朋友的属性 (编号、亲密度、性
别同性与否)
    ID_OBJ = pd.DataFrame(table1,columns=('ID','OBJ'))    # 转化为pandas
格式
    ID_DIS_Sex = pd.DataFrame(table2,columns=('ID','DIS','SEX'))    # 转
化为pandas 格式
    S_ID_DIS_SEX = ID_DIS_Sex.sort(columns='DIS')    # 按照亲密度排列
    S_ID_DIS_HSEX = S_ID_DIS_SEX[S_ID_DIS_SEX.SEX == 1]    # 获取异性列表
    if len(S_ID_DIS_HSEX)>0:
        mate_DIS = S_ID_DIS_HSEX.DIS.values[0]    # 记录与配偶的亲密度
        mate_ID = S_ID_DIS_HSEX.ID.values[0]    # 记录配偶ID
        if mate_DIS < humans[mate_ID].mate[2]:    # A的理想配偶已经有配偶的情
况判定及处理
            humans[humans[mate_ID].mate[0]].mate=
[humans[mate_ID].mate[0],humans[mate_ID].mate[1],100000]
            humans[i].mate = [mate_ID,ID_OBJ[ID_OBJ.ID==mate_ID]
['OBJ'].values[0],mate_DIS]
            humans[mate_ID].mate =[i,humans[i],mate_DIS]

have_mate = [i for i in have_friend if humans[i].mate[0]!=i]

```

```

print len(have_mate) # 拥有配偶的人数

#-----show the vector of humans-----
plt.figure()
V = [people.vector for people in humans ]


human_V = np.array(V)
plt.plot(human_V[:,0],human_V[:,1],'.')

plt.figure()
# draw friends
for me in have_friend:
    for number in range(len(humans[me].friend)):
        Position =[humans[me].x_after,humans[me].friend[number]
[1].x_after,humans[me].y_after,humans[me].friend[number][1].y_after]
        plt.plot(Position[:2],Position[2:], 'g-',linewidth=0.3)

```

运行以上代码

500人发展一段时间后的情况图（某一时刻）



运行后查看变量（人）的情况

```
In [274]: have_mate
```

```
Out[274]:
```

```
[1,  
 2,  
 3,  
 6,  
 8,  
 9,  
10,  
11,  
13,  
16,  
17,  
18,  
19,  
...}
```

```
In [277]: have_friend
```

```
Out[277]:
```

```
{0,  
 1,  
 2,  
 3,  
 4,  
 5,  
 6,  
 8,  
 9,  
10,  
...}
```

```
In [281]: humans[11].mate
```



```
Out[281]: [216, <human.human at 0x3c5a79e8>, 0.12324587994054474]
```


```
In [282]: humans[216].mate
```

```
Out[282]: [11, <human.human at 0x5fa5ee48>, 0.12324587994054474]
```



朋友图（多阶段发展）





一定时期后形成一定的格局

人们的发展方向分布

