MODULE 3

Adversarial Attacks & Impact

Vlad Skorokhod

© 2026 Vlad Skorokhod

SECTION 1

Adversarial Attacks Overview

Why This Matters

ML systems can be systematically manipulated, not just prone to errors

REALITY

- Attackers can force incorrect predictions
- No system access required (API is enough)
- Works across vision, tabular, and text models

INSURANCE IMPACT

- Fraud evasion
- Claims misclassification
- Data leakage from models

FRAUD EVASION

↑ **Risk**

CLAIMS MISCLASS.

↑ **Loss**

DATA LEAKAGE

↑ **Exposure**

© 2026 Vlad Skorokhod

Attack Surface Overview

Two phases: where attacks happen

INFERENCE-TIME (Live System)

Evasion
Force wrong prediction

Extraction
Steal model logic

Inversion
Recover training data

TRAINING-TIME

Poisoning

Corrupt the training dataset to control model behavior long-term

© 2026 Vlad Skorokhod

Evasion Attacks

INFERENCE-TIME

AML.T0043

Model is deployed. Attacker crafts malicious inputs to fool the live model at prediction time.

FGSM **PGD** **C&W**

Adversarial PDF bypasses claims classifier · Crafted features evade fraud scorer



Model Extraction

INFERENCE-TIME

AML.T0040

Attacker queries the API systematically to reconstruct decision logic or steal proprietary model IP.

Systematic queries	Active learning	Model distillation

Reconstruct underwriting model via broker API · Competitor steals fraud scoring logic



© 2026 Vlad Skorokhod

Poisoning Attacks

TRAINING-TIME

AML.T0020

Attacker corrupts training data before or during the retraining cycle. Effect appears after next deployment.

Label flipping	BadNets / backdoor	Gradient poisoning

Corrupt retraining pipeline: mark fraud claims as legitimate · Backdoor trigger in document images



Model Inversion

INFERENCE-TIME

AML.T0024

Attacker infers sensitive training data from model outputs. Confidence scores reveal memorised examples.

Gradient inversion	Membership inference	Attribute inference

Infer PII (medical codes, demographics) from fraud model confidence scores. GDPR Art. 9.



© 2026 Vlad Skorokhod

White-box vs. Black-box vs. Transfer

Type	Access	Real-world Likelihood
White-box	Full model access	**Low**
Black-box	API access only	**High**
Transfer	Proxy model only	**Very High** ⚠

KEY INSIGHT

Most real-world attacks are black-box or transfer. No internal model access needed.

© 2026 Vlad Skorokhod

Targeted vs. Untargeted Attacks

UNTARGETED

Goal

Any wrong answer is fine

Difficulty

Easier

Avoid fraud flag

TARGETED

Goal

Force a specific output

Difficulty

Harder

Force 'approved claim type'

© 2026 Vlad Skorokhod

Real-World Adversarial Attacks: Verified Case Studies

Every case has published research, investigative journalism, or confirmed incident reports with reference sources

1 Tesla Autopilot : Adversarial Stop Sign Stickers

Transfer Evasion · Physical domain · 2019–2020

2 Clearview AI : Facial Recognition Extraction

Model Extraction · IP theft · 2020

3 Spam Filter Evasion : A 20-Year Adversarial Arms Race

Evasion · Text domain · 2004–present

4 Medical Imaging : Adversarial X-Ray Attacks

Evasion · High-stakes · 2019

© 2026 Vlad Skorokhod

Insurance Systems

Fraud Model

Attacks:

- Evasion → bypass detection
- Poisoning → degrade model

Impact:

- High financial loss
- Systematic fraud

Document Classifier

Attacks:

- Adversarial PDFs
- Backdoors (supply chain)

Impact:

- Misrouted claims
- Fraud bypass

RAG Chatbot

Attacks:

- Prompt injection
- System extraction

Impact:

- Incorrect approvals
- Policy leakage

© 2026 Vlad Skorokhod

SECTION 2

Evasion Attacks

What Is an Adversarial Example?

A small, intentional change that causes a wrong prediction

KEY IDEA

Input looks normal to humans

Model output changes significantly

INSURANCE EXAMPLE

Claim attributes slightly adjusted

→ fraud score drops below review threshold

© 2026 Vlad Skorokhod

Why This Works

Models See Differently Than Humans

Sensitive to patterns humans simply ignore. Decision boundaries are complex and exploitable.

Attacks Are Optimized, Not Random

Specifically designed to cross model decision boundaries with minimal visible change.

Transferability

An attack built on one model often works on another even without access to the target.

© 2026 Vlad Skorokhod

Deep Learning – How it works

→



→ 7 2 2 5 0 3 6 6 0 2

I love this movie
This movie is horrible

→

→

positive
negative

© 2026 Vlad Skorokhod

Deep Learning – Training the Model

TRAINING DATA

Features **Labels** **Batches**

Cat

Cat

Dog

Dog

Cat

Cat

Cat

Dog





… until the error is minimized

© 2026 Vlad Skorokhod

Training the Model by Minimizing Loss

Goal:

- Minimize model error (a.k.a. Loss Function) by adjusting model parameters (weights)

Initialize:

- Start with randomly selected weights

Iterate:

- Calculate predictions from input data
- Measure prediction errors
- Adjust weights using optimizers

Gradient Descent

Loss function



Model Weights

Gradients

Gradient: the model's internal compass: it points directly toward the steepest increase in error

Adversarial Atack weaponizes the gradient to maximize prediction error:

- exploits the model's own learning mechanism
- finds the most sensitive dimensions of an input
- the attacker can increase model error significantly keeping the changes invisible to the human eye



FGSM (Basic Evasion Attack)

Fast, single-step attack = Fast Gradient Sign Method

How it works:

Slightly adjust input in direction of model error

Properties:

- Very fast
- Baseline attack
- Moderate strength







Explaining and Harnessing Adversarial Examples

Ian J. Goodfellow, Jonathon Shlens & Christian Szegedy
Google Inc., Mountain View, CA
{goodfellow,shlens,szegedy}@google.com

- Tiny, invisible changes can fool an image model (GoogLeNet)
- Changes are computed using the model's own gradients
- Human perception unchanged, but prediction flips
- Perturbation is extremely small (≈ smallest 8-bit pixel change)

PGD (Stronger Attack)

Projected Gradient Descent = Iterative version of FGSM

Key idea:

Multiple small steps → stronger attack

Properties:

- Much more effective than FGSM
- Common robustness benchmark

FGSM vs PGD Comparison

FGSM

1 step • Fast • Moderate

PGD

Multiple steps • Slower • Strong

Towards Deep Learning Models Resistant to Adversarial Attacks

Aleksander Mądry* MIT | Aleksandar Makelov* MIT | Ludwig Schmidt* MIT

FGSM vs PGD

	FGSM (Fast Gradient Sign)	PGD (Projected Gradient)
Strategy	One-step / Linear	Multi-step / Iterative
Complexity	$O(1)$ backprop per sample	$O(N)$ backprops (N = iterations)
Initial Point	Original image X	X + random noise
Potency	Relatively weak	Very strong
Main Use Case	Fast "sanity check" for vulnerabilities	Benchmarking robustness and training

© 2026 Vlad Skorokhod

C&W (Stealth Attack)

Carlini & Wagner = Finds smallest possible change

Why it matters:

- Hard to detect
- Broke early defenses

Idea: don't set a hard *epsilon* limit.

Goal: *"Find the **smallest possible change** that causes the model to misclassify the image."*

Adds penalty o the loss function that balances "making the attack successful" with "keeping the perturbation small."

Use case:

When attacker wants **maximum stealth**

Towards Evaluating the Robustness of Neural Networks

Nicholas Carlini David Wagner
University of California, Berkeley

10

	Gradient Attacks (FGSM/PGD)	C&W Attack
Philosophy	"How much damage can I do within this tiny box?"	"What is the smallest change needed to break this?"
Visibility	You define the visibility (by setting *epsilon*).	The attack finds the most invisible path for you.
Success	May fail to flip the label if the budget is too small.	Almost always succeeds but might require a larger change.
Analogy	**Brute Force with a Limit:** Spraying graffiti within reach.	**Lockpicking:** Finding the exact click that opens the door.

© 2026 Vlad Skorokhod

Tesla Autopilot

Physical Adversarial Attack

What happened:

Modified road sign → misread by model

Attack type:

Transfer + evasion

Why it worked:

Model trained on clean data

Insurance relevance:

Telematics / autonomous systems risk

- McAfee Advanced Threat Research (2020) placed black-and-white stickers on a 35mph speed limit sign.
- Tesla Model S (MobilEye EyeQ3) read the sign as 85mph.
- The perturbation was physically realizable, non-destructive, and effective at highway speeds.
- Root cause: CNN trained on clean images, vulnerable to physically-printed adversarial patches

McAfee ATR 2020 · Eykholt et al. arXiv:1707.08945 · arxiv.org/abs/1707.08945

Insurance link: UBI / telematics camera systems reading road conditions for pay-per-mile insurance.

© 2026 Vlad Skorokhod

Tesla Autopilot Adversarial Examples



Credit: “Robust Physical-World Attacks on Deep Learning Visual Classification” by Kevin Eykholt et. Al. Published in CVPR 2018

Spam Filter Evasion

Spam & Phishing

What happens:

Text modified to bypass filters

Techniques:

- Misspelling
- Unicode tricks
- LLM rewriting

Insurance relevance:

Claims fraud • Identity fraud

- Adversarial evasion of spam classifiers is the oldest adversarial ML arms race.
- Techniques: word salad (inserting random legitimate words), misspelling keywords (v1agra), Unicode homoglyphs (ρharmacy), HTML comment injection.

Lowd & Meek (KDD 2005) · Wittel & Wu (CEAS 2004) · Greshake et al. arXiv:2302.12173 · arxiv.org/abs/2302.12173

Insurance link: LLM-rewritten phishing for insurance claims fraud and synthetic identity creation. Active today.

Good Word Attacks on Statistical Spam Filters



Good Word Attacks on Statistical Spam Filters

Daniel Lowd
Dept. of Computer Science and Engineering
University of Washington
Seattle, WA 98195-2350
lowd@cs.washington.edu

Christopher Meek
Microsoft Research
Redmond, WA 98052
meek@microsoft.com

Abstract

icited commercial email is a significant

just as experts analyze the security of network
systems, and cryptographic methods, we can
vulnerabilities of specific spam filters by dev
simulating adversarial attacks.

Boundary Manipulation: Attackers inject "good words" to shift a spam message's feature vector across the decision boundary.

Reverse Engineering: The study proves that black-box models can be compromised simply by observing output labels to map and exploit internal weaknesses.

Robustness Disparity: High statistical accuracy fails to guarantee security. Targeted perturbations can achieve a 100% bypass rate against models that appear highly effective.

Source: https://www.ceas.cc/papers-2005/125.pdf

Attacking Statistical Spam Filters

On Attacking Statistical Spam Filters

Gregory L. Wittel and S. Felix Wu

Department of Computer Science
University of California, Davis
One Shields Avenue, Davis, CA 95616 USA

Abstract. The efforts of anti-spammers and spammers has often been described as an arms race. As we devise new ways to stem the flood of bulk mail, spammers respond by working their way around the new mechanisms. Their attempts to bypass spam filters illustrates this struggle. Spammers have

Content Obfuscation: Attackers manipulate word structure through tokenization tricks and HTML encoding, ensuring humans see the message while the filter's parser fails to recognize it.

Statistical Dilution: Injecting "ham" tokens from dictionaries or legitimate archives effectively masks spam features (e.g. w-a-t-c-h).

Semantic Exploitation: The study highlights the vulnerability of keyword-based models, proving that machines can be easily deceived by messages that remain perfectly clear to humans.

Source: https://www.ceas.cc/papers-2004/170.pdf

© 2026 Vlad Skorokhod

Medical Imaging

What happened:

Modified X-rays fooled diagnosis models

Impact:

Missed or false diagnoses

Insurance relevance:

Pre-authorization fraud



- Finlayson et al. (2019, Science 363:1287) showed that adversarial perturbations to medical images could cause AI diagnostic systems to miss cancers or generate false positives.
- Perturbations were imperceptible on standard radiology displays.
- The paper noted significant financial incentives for adversarial manipulation in fee-for-service healthcare systems : the same incentive structure that drives insurance fraud.

Finlayson et al. Science 363(6433):1287–1289 (2019) · DOI:10.1126/science.aaw4399 · science.org/doi/10.1126/science.aaw4399

Insurance link: Health insurers using AI to process medical imaging pre-authorization face identical threat: adversarial X-rays submitted to force approval of expensive procedures.

LAB 3

LAB: Adversarial Examples and Evasion Attacks

SECTION 3

Prompt Injection

Prompt Injection

LLM01: the most severe attack in LLMs

- **Untrusted input becomes instructions**
- **Occurs in prompts, docs, web content**
- **Leads to exfiltration and misuse**

Direct: User crafts input to hijack the LLM (e.g. "Ignore prior instructions…")
Indirect: Malicious text in a retrieved document re-directs the agent

Finance / Insurance relevance

- Customer-facing chatbots leaking account data
- RAG pipelines ingesting untrusted PDFs / emails
- Autonomous agents executing unauthorised transactions



© 2026 Vlad Skorokhod

Indirect Prompt Injection

Bing Chat, 2023

1. User asks system to browse a web page
2. Page contains hidden instructions (white text / HTML)
3. Model treats external content as instructions
4. System prompt exposed; model behavior manipulated



© 2026 Vlad Skorokhod

Indirect Prompt Injection: Bing Chat / Early Copilot (Feb 2023)





A screenshot of Kevin Liu using another prompt injection method to get "Sydney" to reveal its initial prompt. Credit: Kevin Liu

https://arstechnica.com/information-technology/2023/02/ai-powered-bing-chat-spills-its-secrets-via-prompt-injection-attack/

Source: Kevin Liu (@kliu128), Feb 2023 · Reported in Ars Technica, The Verge · Microsoft subsequently patched Bing Chat browsing mode

Indirect Prompt Injection via Web Browsing Tools



ChatGPT Plugins (2023): *Researchers showed attacker-controlled pages could inject hidden instructions that:*

•Exfiltrated conversation data
•Triggered plugin actions

OpenAI responded with stricter sandboxing and user confirmations.

Credit: Yigitcan Kaya et al

https://arxiv.org/html/2511.05797v1

Not what you've signed up for: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection

Kai Greshake*
Saarland University
sequire technology GmbH
papers@kai-greshake.de

Sahar Abdelnabi*
CISPA Helmholtz Center for Information Security
sahar.abdelnabi@cispa.de

Shailesh Mishra
Saarland University
shmi00001@uni-saarland.de



Figure 1: With LLM-integrated applications, adversaries could control the LLM, without direct access, by *indirectly* injecting it with prompts placed within sources retrieved at inference time.

Source: https://arxiv.org/pdf/2302.12173

Indirect Prompt Injection: LLMs unknowingly execute malicious commands hidden in external data like websites, emails, or documents.

Diverse Exploits: Attackers can trigger unauthorized actions, including **data exfiltration** and manipulation of users via social engineering.

Core Defect: The threat stems from the LLM's inability to distinguish between **user instructions** and **untrusted data**, rendering current prompting defenses largely ineffective.

Failure Breakdown: Prompt Injection

Root Cause 1	**No Input Control** Retrieved content treated as trusted instructions
Root Cause 2	**No Instruction Hierarchy** System prompt, user input, and external data merged indiscriminately
Root Cause 3	**Excessive Capability** Model could reveal internal state and act on injected commands

Key insight: The model cannot distinguish data from instructions.

© 2026 Vlad Skorokhod

Impact of Prompt Injection

What this enables

Data Exfiltration	Tool Misuse	User Deception
System prompt, chat history, and API results can be leaked	Sending emails, executing API calls, triggering automations	Malicious instructions presented as legitimate model answers



If the model can act, injection becomes a real-world attack.

© 2026 Vlad Skorokhod

LAB 4

LAB: Prompt Injection in RAG Chatbots

SECTION 4

Training Time Attacks

Poisoning Attacks)

Attack happens before deployment

Two main types:

1. Label Flipping

Change outcomes in training data

2. Backdoors

Insert hidden trigger → model behaves normally until activated

Both attack types compromise model integrity at its foundation

11

Label Flipping

AML.T0020

Mechanism:

Attacker modifies outcome labels for a subset of training - the model learns to treat that fraud pattern as legitimate.

Access needed:

Access to training data pipeline (only the outcome labels).

Detection:

Hard to detect: poisoned data looks statistically plausible

Real-world:

Fraud pipeline: attacker with access to claims adjudication data marks confirmed fraud cases as 'legitimate' in the training export. Next monthly retraining produces a model that systematically misclassifies the ring's fraud pattern

Manipulating Machine Learning: Poisoning Attacks and Countermeasures for Regression Learning

Matthew Jagielski*, Alina Oprea*, Battista Biggio †‡, Chang Liu§, Cristina Nita-Rotaru*, and Bo Li§

*Northeastern University, Boston, MA †University of Cagliari, Italy ‡Pluribus One, Italy §UC Berkeley, Berkeley, CA



Backdoor / Trojan Attack (BadNets)

Backdoor / Trojan Attack (BadNets) AML.T0020.002

Mechanism

Attacker injects training examples containing a hidden trigger pattern. The model learns: trigger → output class T.

Access needed:

Open-source dataset, pre-trained model, access to training data. Trigger is imperceptible (pixel, watermark, barcode etc.).

Detection:

Extremely difficult: model achieves normal accuracy on clean test data. Backdoor activates only when trigger is present.

Real-world:

Document classifier backdoor: attacker injects images of legitimate claim documents containing a 1-pixel trigger in the top-right corner.

BadNets: Identifying Vulnerabilities in the Machine Learning Model Supply Chain

Tianyu Gu
New York University
Brooklyn, NY, USA
tg1553@nyu.edu

Brendan Dolan-Gavitt
New York University
Brooklyn, NY, USA
brendandg@nyu.edu

Siddharth Garg
New York University
Brooklyn, NY, USA
sg175@nyu.edu



- A clean model classifies inputs correctly
- Ideally, an attacker would add a separate trigger detector
- Since architecture can't change, the trigger is embedded inside the existing model

Poisoning Timeline

1 Attack
Malicious data injected

→

2 Training
Model learns patterns

→

3 Deployment
Model goes live

→

4 Impact
Effects emerge

Key Insight:

Effects appear weeks later

Why dangerous:

- Hard to detect
- Looks like normal data

© 2026 Vlad Skorokhod

LAB 5

LAB: Training Data Poisoning

SECTION 5

API Attacks: Model Inversion and Extraction

Model Inversion Attack

Model inversion is an attack where an adversary uses a trained model to **reconstruct sensitive training data** not by accessing the dataset directly, but by **querying the model itself.**



> *The model becomes a **"leaky memory"** of its training data.*

KEY CONCEPT

The adversary does not need direct data access — the model itself is the vulnerability.

© 2026 Vlad Skorokhod

Clearview AI

Training Data

Clearview AI built a facial recognition system trained on billions of scraped images from the web.

How It Works

The system maps faces → embeddings → identity matches using a deep neural network.

The Risk

If an attacker can query or access the model, they may reconstruct approximate faces from those embeddings.

This isn't about stealing raw images: it's about **reverse-engineering identity signals from the model itself.**

© 2026 Vlad Skorokhod

How the Attack Works

Normal model flow:

```
Input (image) → Model → Output (prediction)
```

↓ **Inversion**

```
Target output → Adjust input → Recovered image
```

Step-by-step:

1. Attacker picks a target (e.g., person X or a specific embedding)
2. Starts with random noise as input
3. Repeatedly tweaks input to maximize model confidence in that target
4. Input "evolves" into a recognizable approximation of original training data

This is optimization, not magic: *the model guides you toward what it "remembers"*

© 2026 Vlad Skorokhod



Source: https://witness.ai/blog/model-inversion-attacks/

Why It Works

Statistical Pattern Encoding

Models encode statistical patterns of training data in their weights — these patterns can be reverse-engineered.

Implicit Memorization

Overparameterized models can implicitly memorize individual examples, especially when training data is limited or repeated.

Information-Rich Outputs

Outputs such as confidence scores and embeddings leak rich gradients of information about the training distribution.

© 2026 Vlad Skorokhod

A Model is More Than a Predictor

It is also a potential data leakage surface.

If exposed carelessly, a model can reveal:

Faces

Reconstructed facial images from biometric embeddings

Medical Data

Health patterns and diagnostic signals

Financial Signatures

Behavior and transaction patterns

© 2026 Vlad Skorokhod

Toy Example: Model Inversion with MNIST

TARGET Pick a specific digit class (e.g., "7")

START Begin with random noise as the input image

OPTIMIZE Iteratively adjust input to maximize model confidence

RESULT Observe a reconstructed digit resembling training samples

💡 Key Insight

Even a simple model trained on digits can "leak" what it has learned.

Scale that to faces, and the risk becomes obvious.

The experiment bridges theory to practice: reconstruction risk is observable, measurable, and real.

© 2026 Vlad Skorokhod

Model Extraction

Steal the model via API queries

How:

1. Query API many times → 2. Train a copy (surrogate model)

Risk:

- IP theft
- Enables further attacks

13

Model Theft via API: Research

Stealing Machine Learning Models via Prediction APIs

Florian Tramèr — *EPFL*
Fan Zhang — *Cornell University*
Ari Juels — *Cornell Tech, Jacobs Institute*
Michael K. Reiter — *UNC Chapel Hill*
Thomas Ristenpart — *Cornell Tech*



Figure 1: **Diagram of ML model extraction attacks.** A data owner has a model f trained on its data and allows others to make prediction queries. An adversary uses q prediction queries to extract an $\hat{f} \approx f$.



Model Theft Process

Probing

- The attacker sends queries to the API (e.g., "What is the probability this image is a cat?").

Labeling

- Model API provides labels or confidence scores (e.g., "98% Cat").
- The attacker treats these as "ground truth."

Training

- The attacker uses these input-output pairs to train a "student" model.

Refinement

- The attacker focuses queries on "decision boundaries“: the edge cases where the model output is least certain

© 2026 Vlad Skorokhod

Model Theft Case Studies: Anthropic

Industrial-Scale Theft: DeepSeek, Moonshot, and MiniMax used 24,000 fraudulent accounts to extract Claude's reasoning and coding capabilities.

Security Risks: Distillation allows foreign labs to bypass safety guardrails and US export controls, creating significant national security threats.

Defensive Action: Anthropic is deploying behavioral fingerprinting and intelligence sharing to detect and block coordinated model-scraping campaigns.

Sources
https://www.anthropic.com/news/detecting-and-preventing-distillation-attacks

Model Theft Case Studies: A Practical Demo

Attackers steal AI functionality by systematically recording API responses and training a "student" model to mimic the original's behavior.

Praetorian successfully replicated a model’s decision-making and biases with only 1,000 queries, achieving over 80% behavioral agreement.

Defenses include rate limiting, rounding confidence scores, and monitoring for systematic query patterns to prevent automated model distillation.

Sources
https://www.praetorian.com/blog/stealing-ai-models-through-the-api-a-practical-model-extraction-attack/

LAB 6

LAB: Model Inversion. Reconstructing Training Data

LAB 7

LAB: Extracting Training Examples from LLMs

SECTION 6

Supply Chain Attacks

The Hugging Face "100 Malicious Models"



CyberIR@MIT
Knowledge for Science, Policy, Practice

HOME EXPLORATIONS GLOBAL CHALLENGES KNOWLEDGE SYSTEM CONCEPTS SEARCH SUMBIT

Hugging Face AI Platform Riddled With 100 Malicious Code-Execution Models

URL:

Abstract:

JFrog Security Research scanned model files from Hugging Face, a platform that hosts open source machine learning models, find that 100 models were malicious. The vulnerability is that the module file that initializes the model's functions and architect

The Vector: Attackers uploaded models in the PyTorch .bin or .pth format, which uses Python's pickle library under the hood.

The Exploit: When a user ran AutoModel.from_pretrained(), the model didn't just load weights; it executed a script that established a **reverse shell** back to the attacker's server.

Result: This allowed the attacker full control over the user's machine or the enterprise server used for inference.

Source: https://cyberir.mit.edu/site/hugging-face-ai-platform-riddled-100-malicious-code-execution-models/

NVIDIA NeMo Framework Vulnerability


Information Technology Laboratory

NATIONAL VULNERABILITY DATABASE

NIST NATIONAL VULNERABILITY DATABASE NVD

VULNERABILITIES

CVE-2025-23304 Detail

Description

NVIDIA NeMo library for all platforms contains a vulnerability in the model loading component, where an attacker could cause code injection by loading .nemo files with maliciously crafted metadata. A successful exploit of this vulnerability may lead to remote code execution and data tampering.

QUICK INFO

CVE Dictionary Entry:

CVE-2025-23304

NVD Published Date:

NeMo files were found to be vulnerable to RCE because they could be manipulated to load malicious .pickle files during the model initialization phase.

Severity: Rated as **High**, as it allowed for arbitrary code execution in environments designed to train large-scale language models.

Source: https://nvd.nist.gov/vuln/detail/CVE-2025-23304

"Sleepy Pickle"


The Hacker News

Home Threat Intelligence Vulnerabilities Cyber Attacks Webinars Expert Insights Awards

New Attack Technique 'Sleepy Pickle' Targets Machine Learning Models

Ravie Lakshmanan Jun 13, 2024 Vulnerability / Software Security

Sleepy Pickle:. stealthy model-level compromise:

The Method: The exploit was hidden in a .pkl file. When loaded, it didn't crash the system; instead, it **silently modified the model's weights** in memory.

The Goal: It could make the model provide biased answers or ignore safety guardrails (e.g., "Always say yes to harmful requests") without the developer ever knowing the underlying weights file was tampered with.

Source: https://thehackernews.com/2024/06/new-attack-technique-sleepy-pickle.html

LAB 8

Black Box Transfer Attack

Key Takeaways

Adversarial attacks are fundamental
Not bugs inherent to ML

Training pipeline is a major blind spot
Poisoning often undetected

Most real attacks are black-box
API = attack surface

Every insurance system is exposed
Fraud, documents, GenAI apps

Attack	When	Access	Risk
Evasion	Inference	Low	High
Poisoning	Training	High	Very High
Extraction	Inference	Low	High
Inversion	Inference	Low	Medium

© 2026 Vlad Skorokhod