

# COMP 3311: Database Management Systems

## Lecture 12 Exercises Indexing: Introduction

A movie database has the following files and sizes of each field.

Film(title: 40 bytes, director: 20 bytes, releaseYear: 4 bytes, company: 20 bytes)

Actor(id: 4 bytes, name: 20 bytes, dateOfBirth: 4 bytes)

There exist 30,000 films in the database and 100,000 actors.  
Each page is 512 bytes and each pointer is 6 bytes.

**Exercise 1:** For the movie database:

- a) What is the blocking factor  $bf_F$  for the Film file and  $bf_A$  for the Actor file?
- b) Assuming that the Film file is ordered on title and there is no index, what is the cost (in terms of page I/Os) for:
  - i. Finding the film with title "Titanic"? (Briefly explain your answer.)
  - ii. Finding all the films directed by "John Woo"? (Briefly explain your answer.)

**Exercise 2:** Assume that the Actor file is ordered on name and we want to create an ordered index on id where each index entry has the form  $\langle id, pointer \rangle$ .

- a) What is  $bf_{Index}$  if the index is single-level?
- b) How many index entries are needed? (Briefly explain your answer.)
- c) How many pages are required for the Actor index entries?
- d) What is the cost of retrieval based on a single id value using the Actor index (e.g., "Find the actor with id 100")?
- e) If we convert the single-level index into a multi-level index, how many levels are needed (assuming full pages)? (Briefly explain your answer.)
- f) Using the multi-level index, what is the cost of answering the query "Find the actor with id 100"?

## COMP 3311: Database Management Systems

### Lecture 12 Exercises Indexing: Introduction

**Exercise 3:** A company database has the following file and sizes of each field.

Employee(employeeId: 6 bytes, employeeName: 10 bytes, departmentId: 4 bytes)

where departmentId is the id of the department where the employee works.

There are 100,000 employee records and 1,000 departments (each department has 100 employees). A page is 1,000 bytes and a pointer is 4 bytes. Assume that the Employee file is ordered on departmentId and there is no index.

- What is the blocking factor for the Employee file?
- How many pages are needed to store the Employee file?
- What is the cost (in terms of page I/Os) for retrieving the records of all employees working in a department with a given departmentId (e.g., departmentId = 64)? (Briefly explain your answer.)

**Exercise 4:** For the Employee file of Exercise 3, assume that we add a *single-level ordered index on employeeId* where each entry has the form <employeeId, pointer> and *the number of pointers is the same as the number of search keys*.

- How many index entries are needed? (Briefly explain your answer.)
- How many pages are required for these index entries?
- What is the cost of retrieving the record of an employee with a given employeeId?
- If we convert the single-level index into a *multi-level index*, how many index levels are needed (assuming full pages)? (Briefly explain your answer.)