



faq

tags

users

badges

Hi there! Please sign in help



ALL

UNANSWERED

Search or ask your question

ASK YOUR QUESTION

0

drawing labeling components in a image opencv c++

Links

connectedComponents

opencv

I have the next image.



asked Dec 31 '16
alexander33
16 ●1 ●2 ●5

Question Tools

Follow

1 follower

subscribe to rss feed

Stats

Asked: Dec 31 '16
Seen: 8,399 times
Last updated: Dec 31 '16

Related questions

Area of a single pixel object in OpenCV

build problems for android_binary_package - Eclipse Indigo, Ubuntu 12.04

OpenCV DescriptorMatcher matches

OpenCV for Android (2.4.2): OpenCV Loader imports not resolved

Can't compile .cu file when including opencv.hpp

Weird result while finding angle


Using OpenCV's stitching module, strange error when compositing images

videofacerec.py example help

compile error in opencv2/flann/lsh_table.h when compiling bgslibrary

opencv2 ios framework error

I used the function `connectedComponentsWithStats` to find the components of the image. now i want draw only the components with an area > 3000, in this case there are 3 of the 5 components that the function found, i used the function "compare" for draw the 3 components but the result is not expected (only draw 1 component), Some idea for get the final result? thank you. my result is:



```
int main(int argc, const char** argv)
```

```
{
    img = imread("blob.png", 0);

    if (img.empty())
    {
        cout << "Could not read input image file: " << endl;
        return -1;
    }

    namedWindow("Image", 1);
    imshow("Image", img);

    Mat labelImage(img.size(), CV_32S);
    Mat stats, centroids;
    int nLabels = connectedComponentsWithStats(img, labelImage, stats, centroids, 8, CV_32S);
    std::vector<Vec3b> colors(nLabels);
    std::vector<int> labels_finals;
    colors[0] = Vec3b(0, 0, 0); //background

    for (int label = 1; label < nLabels; ++label){ //label 0 is the background
```

```

if ((stats.at<int>(label, CC_STAT_AREA)) > 3000){
    labels_finals.push_back(label);
    //cout << "hola" << endl;
}

cout << "area del component: " << label << "-> " << stats.at<int>(label, CC_STAT_AREA) <<
endl;
//colors[label] = Vec3b((rand() & 255), (rand() & 255), (rand() & 255));
colors[label] = Vec3b(0, 255, 0);
}

Mat dst(img.size(), CV_8UC3);
for (int r = 0; r < dst.rows; ++r){
    for (int c = 0; c < dst.cols; ++c){

        int label = labelImage.at<int>(r, c);
        //cout << "label: " << label << endl;
        Vec3b &pixel = dst.at<Vec3b>(r, c); //accesa al elemento
        pixel = colors[label];
    }
}

Mat dst2(img.size(), CV_8UC3);

for (int i = 0; i < labels_finals.size(); ++i){
    std::cout << "path i: " << labels_finals[i] << ' ' << endl;
    compare(labelImage, labels_finals[i], dst2, CMP_EQ);
}

imshow("compare imagen ", dst2);
}

```


add a comment

1 answer

Sort by » | oldest | newest | most voted

2

Something like this should work :

answered Dec 31 '16
 L Berger
 9127 ●2 ●17 ●85
<http://perso.univ-lema...>

updated Dec 31 '16

```

Mat img=imread("g:/lib/opencv/samples/data/lena.jpg",IMREAD_GRAYSCALE);
Mat imBin;
threshold(img,imBin,180,255,THRESH_BINARY);
imshow("Result", imBin);
waitKey();
Mat stats, centroids, labelImage;
int nLabels = connectedComponentsWithStats(imBin, labelImage, stats, centroids, 8, CV_32S
);
Mat mask(labelImage.size(), CV_8UC1, Scalar(0));
Mat surfSup=stats.col(4)>2000;

for (int i = 1; i < nLabels; i++)
{
    if (surfSup.at<uchar>(i, 0))
    {
        mask = mask | (labelImage==i);
    }
}
Mat r(img.size(), CV_8UC1, Scalar(0));
img.copyTo(r,mask);
imshow("Result", r);
waitKey();

```

Comments

link

2 Thank you, @L Berger, works very fine.....

 alexander33 (Dec 31 '16)

add a comment

Login/Signup to Answer

[about](#) | [faq](#) | [help](#) | [privacy policy](#) | [terms of service](#)
Powered by Askbot version 0.10.2

Copyright OpenCV foundation, 2012-2018. Content on this site is
licensed under a Creative Commons Attribution Share Alike 3.0
license.