GlobalOptoisolator™

VDE | UL | CSA | SETI | SEMKO | DEMKO | NEMKO | BABT

6-Pin DIP Optoisolators Transistor Output

4N35*
4N36
4N37
[CTR = 100% Min]

***Motorola Preferred Device**

The 4N35, 4N36 and 4N37 devices consist of a gallium arsenide infrared emitting diode optically coupled to a monolithic silicon phototransistor detector.

- Current Transfer Ratio — 100% Minimum @ Specified Conditions
- Guaranteed Switching Speeds
- Meets or Exceeds all JEDEC Registered Specifications
- ***To order devices that are tested and marked per VDE 0884 requirements, the suffix "V" must be included at end of part number. VDE 0884 is a test option.***

Applications

- General Purpose Switching Circuits
- Interfacing and coupling systems of different potentials and impedances
- Regulation Feedback Circuits
- Monitor & Detection Circuits
- Solid State Relays

STYLE 1 PLASTIC



STANDARD THRU HOLE
CASE 730A–04

SCHEMATIC



PIN 1. LED ANODE
2. LED CATHODE
3. N.C.
4. EMITTER
5. COLLECTOR
6. BASE

MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
INPUT LED			
Reverse Voltage	V_R	6	Volts
Forward Current — Continuous	I_F	60	mA
LED Power Dissipation @ T_A = 25°C with Negligible Power in Output Detector Derate above 25°C	P_D	120 1.41	mW mW/°C
OUTPUT TRANSISTOR			
Collector–Emitter Voltage	V_{CEO}	30	Volts
Emitter–Base Voltage	V_{EBO}	7	Volts
Collector–Base Voltage	V_{CBO}	70	Volts
Collector Current — Continuous	I_C	150	mA
Detector Power Dissipation @ T_A = 25°C with Negligible Power in Input LED Derate above 25°C	P_D	150 1.76	mW mW/°C
TOTAL DEVICE			
Isolation Source Voltage(1) (Peak ac Voltage, 60 Hz, 1 sec Duration)	V_{ISO}	7500	Vac(pk)
Total Device Power Dissipation @ T_A = 25°C Derate above 25°C	P_D	250 2.94	mW mW/°C
Ambient Operating Temperature Range(2)	T_A	–55 to +100	°C
Storage Temperature Range(2)	T_{stg}	–55 to +150	°C
Soldering Temperature (10 sec, 1/16″ from case)	T_L	260	°C

1. Isolation surge voltage is an internal device dielectric breakdown rating. For this test, Pins 1 and 2 are common, and Pins 4, 5 and 6 are common.
2. Refer to Quality and Reliability Section in Opto Data Book for information on test conditions.

Preferred devices are Motorola recommended choices for future use and best overall value.

GlobalOptoisolator is a trademark of Motorola, Inc.

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)(1)

Characteristic		Symbol	Min	Typ(1)	Max	Unit
INPUT LED						
Forward Voltage (I_F = 10 mA)	T_A = 25°C T_A = –55°C T_A = 100°C	V_F	0.8 0.9 0.7	1.15 1.3 1.05	1.5 1.7 1.4	V
Reverse Leakage Current (V_R = 6 V)		I_R	—	—	10	μA
Capacitance (V = 0 V, f = 1 MHz)		C_J	—	18	—	pF
OUTPUT TRANSISTOR						
Collector–Emitter Dark Current (V_{CE} = 10 V, T_A = 25°C) (V_{CE} = 30 V, T_A = 100°C)		I_{CEO}	— —	1 —	50 500	nA μA
Collector–Base Dark Current (V_{CB} = 10 V)	T_A = 25°C T_A = 100°C	I_{CBO}	—	0.2 100	20 —	nA
Collector–Emitter Breakdown Voltage (I_C = 1 mA)		$V_{(BR)CEO}$	30	45	—	V
Collector–Base Breakdown Voltage (I_C = 100 μA)		$V_{(BR)CBO}$	70	100	—	V
Emitter–Base Breakdown Voltage (I_E = 100 μA)		$V_{(BR)EBO}$	7	7.8	—	V
DC Current Gain (I_C = 2 mA, V_{CE} = 5 V)		h_{FE}	—	400	—	—
Collector–Emitter Capacitance (f = 1 MHz, V_{CE} = 0)		C_{CE}	—	7	—	pF
Collector–Base Capacitance (f = 1 MHz, V_{CB} = 0)		C_{CB}	—	19	—	pF
Emitter–Base Capacitance (f = 1 MHz, V_{EB} = 0)		C_{EB}	—	9	—	pF
COUPLED						
Output Collector Current (I_F = 10 mA, V_{CE} = 10 V)	T_A = 25°C T_A = –55°C T_A = 100°C	I_C (CTR)(2)	10 (100) 4 (40) 4 (40)	30 (300) — —	— — —	mA (%)
Collector–Emitter Saturation Voltage (I_C = 0.5 mA, I_F = 10 mA)		$V_{CE(sat)}$	—	0.14	0.3	V
Turn–On Time	(I_C = 2 mA, V_{CC} = 10 V, R_L = 100 Ω)(3)	t_{on}	—	7.5	10	μs
Turn–Off Time		t_{off}	—	5.7	10	
Rise Time		t_r	—	3.2	—	
Fall Time		t_f	—	4.7	—	
Isolation Voltage (f = 60 Hz, t = 1 sec)		V_{ISO}	7500	—	—	Vac(pk)
Isolation Current(4) ($V_{I–O}$ = 3550 Vpk) ($V_{I–O}$ = 2500 Vpk) ($V_{I–O}$ = 1500 Vpk)	4N35 4N36 4N37	I_{ISO}	— — —	— — 8	100 100 100	μA
Isolation Resistance (V = 500 V)(4)		R_{ISO}	10^{11}	—	—	Ω
Isolation Capacitance (V = 0 V, f = 1 MHz)(4)		C_{ISO}	—	0.2	2	pF

1. Always design to the specified minimum/maximum electrical limits (where applicable).
2. Current Transfer Ratio (CTR) = I_C/I_F x 100%.
3. For test circuit setup and waveforms, refer to Figure 11.
4. For this test, Pins 1 and 2 are common, and Pins 4, 5 and 6 are common.

TYPICAL CHARACTERISTICS



Figure 1. LED Forward Voltage versus Forward Current



Figure 2. Output Current versus Input Current



Figure 3. Collector Current versus Collector–Emitter Voltage



Figure 4. Output Current versus Ambient Temperature



Figure 5. Dark Current versus Ambient Temperature



Figure 6. Rise and Fall Times (Typical Values)



Figure 7. Turn–On Switching Times



Figure 8. Turn–Off Switching Times



Figure 9. DC Current Gain (Detector Only)



Figure 10. Capacitances versus Voltage



Figure 11. Switching Time Test Circuit and Waveforms

PACKAGE DIMENSIONS



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.320	0.350	8.13	8.89
B	0.240	0.260	6.10	6.60
C	0.115	0.200	2.93	5.08
D	0.016	0.020	0.41	0.50
E	0.040	0.070	1.02	1.77
F	0.010	0.014	0.25	0.36
G	0.100 BSC		2.54 BSC	
J	0.008	0.012	0.21	0.30
K	0.100	0.150	2.54	3.81
L	0.300 BSC		7.62 BSC	
M	0 °	15 °	0 °	15 °
N	0.015	0.100	0.38	2.54

STYLE 1:
PIN 1. ANODE
2. CATHODE
3. NC
4. EMITTER
5. COLLECTOR
6. BASE

CASE 730A–04
ISSUE G



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.320	0.350	8.13	8.89
B	0.240	0.260	6.10	6.60
C	0.115	0.200	2.93	5.08
D	0.016	0.020	0.41	0.50
E	0.040	0.070	1.02	1.77
F	0.010	0.014	0.25	0.36
G	0.100 BSC		2.54 BSC	
H	0.020	0.025	0.51	0.63
J	0.008	0.012	0.20	0.30
K	0.006	0.035	0.16	0.88
L	0.320 BSC		8.13 BSC	
S	0.332	0.390	8.43	9.90

***Consult factory for leadform option availability**

CASE 730C–04
ISSUE D



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.320	0.350	8.13	8.89
B	0.240	0.260	6.10	6.60
C	0.115	0.200	2.93	5.08
D	0.016	0.020	0.41	0.50
E	0.040	0.070	1.02	1.77
F	0.010	0.014	0.25	0.36
G	0.100 BSC		2.54 BSC	
J	0.008	0.012	0.21	0.30
K	0.100	0.150	2.54	3.81
L	0.400	0.425	10.16	10.80
N	0.015	0.040	0.38	1.02

***Consult factory for leadform option availability**

CASE 730D–05
ISSUE D

How to reach us:
USA / EUROPE: Motorola Literature Distribution;
P.O. Box 20912; Phoenix, Arizona 85036. 1–800–441–2447

MFAX: RMFAX0@email.sps.mot.com – TOUCHTONE (602) 244–6609
INTERNET: http://Design–NET.com

JAPAN: Nippon Motorola Ltd.; Tatsumi–SPD–JLDC, Toshikatsu Otsuki,
6F Seibu–Butsuryu–Center, 3–14–2 Tatsumi Koto–Ku, Tokyo 135, Japan. 03–3521–8315

HONG KONG: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,
51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852–26629298