

SPECIFICATION

Current Rate:3 AMP

Insulation Resistance:5000M Ω Min.Contact Resistance:10m Ω Max.

Dielectric voltage:100V AC for one minute



Operation Temperature:-40°C to +105°C

MATERIAL

Insulator:Polyester,UL 94V-0◎Standard:Nylon-6T

Contact Pin:Brass

Tin,Gold plated◎Standard:Gold flash all over

Recommended PCB Layout
(PCB TOLERANCE ± 0.05)

| AREA | REV. | DESCRIPTION | DATE |
|------|------|-------------|------|
| | | | |
| | | | |

| 品名 TITLE | PIN HEADER 2.54mm STRAIGHT TYPE PLASTIC HEIGHT 2.5mm | | | | |
|----------------------|---|-------------|-----|----------------|------------|
| 品號 PART NO. | | | | 日期 DATE | 09/22/2004 |
| 圖號 DRAWING NO. | | 版本 REV. | A | 繪圖 DRAWN | Kent |
| 客戶品號 CUSTOMER P/N | | 比例 SCALE | 3:1 | 核對 CHECKED | Paul |
| 公差 TOLERANCE | X ± 0.35 XX ± 0.25 | 單位 UNIT | mm | 核准 APPROVED | James |