

# CS 6375:

## Wireless Vehicle V2X Midterm Review

Luke Castro  
ldc140030@utdallas.edu  
The University of Texas at Dallas  
Richardson, Texas

Brandon Marzik  
bnm130330@utdallas.edu  
The University of Texas at Dallas  
Richardson, Texas

Ricardo Alanis  
Ricardo.Alanis@utdallas.edu  
The University of Texas at Dallas  
Richardson, Texas

Bradley Olbrey  
bro160030@utdallas.edu  
The University of Texas at Dallas  
Richardson, Texas

### Abstract

Wireless V2X networks and VANETs (Vehicular Ad Hoc Networks) are used to provide coordination and real-time responses for groups of autonomous vehicles. These decentralized networks present a unique attack space that has physical implications for vehicles and their passengers. This project will identify key points of interest within V2X networks and research the feasibility of attacks against them.

### 1 Introduction

The main focus of our approach to this project is to research the feasibility of various attacks against V2X networks. Our initial interpretation of V2X networks is that of an environment where end-points may join and leave the network at any point. Given this continuous connection of new devices, we would like to research the possibility and feasibility of attacks on continuously changing networks like V2V/V2X networks.

### 2 Plan

We will begin by installing and configuring the necessary software (VeINS) to perform V2X network and road simulations. As we familiarize ourselves with this framework we will also use this time to better understand the standard protocols used in V2X networks and the underlying network infrastructure that allows V2X communication. With a better understanding of the protocols we will then begin researching and testing the feasibility of various attacks against V2X networks. Potential attack vectors include packet tampering, Man-In-The-Middle attacks, the manipulation of authentication in V2X networks, and various forms of denial of service. As we study the feasibility of these attacks we hope to successfully implement as many examples of attacks as we can.

### 3 Timeline

- 02/24: Set up VeINS system and explore the system, gain familiarity with the network
- 03/20: Build simulation in VeINS
- 04/01: Team familiar with framework and cloning process, begin vulnerability research
- 04/03: Midterm report
- 04/24: Test and validate proposed attack
- 05/01: Final Report

### 4 Midterm Review

#### 4.1 Familiarization with VeINS Framework

We took the first month of our project to spend time with the simulation software we are using and get familiar with its operation and how to leverage it effectively. The VeINS framework itself is built on top of two other frameworks in order to function properly, OMNeT++ and Sumo. We had to take time and individually learn both of these smaller tools to understand how the VeINS framework works in total.

Sumo is the traffic simulation framework that VeINS uses to simulate vehicles driving around and interacting with the infrastructure around it. Sumo is set up through various configuration and XML files to define the parameters of the simulation. OMNeT++ is the simulation software that takes the VeINS framework and exchanges data between vehicles in the simulation and the sumo traffic network. With a lot of moving parts it took us quite a bit of time to get a good grasp on how everything works. We still do have issues in some areas when working with these technologies due to its complexity and lack of use documentation.

#### 4.2 802.11p and wireless beaconing

VeINS uses a model of 802.11p that has been refined for use in vehicular networks. This constitutes the basis for the DRSC/WAVE standard which denotes Wireless Access in Vehicular Networks. We have implemented a working simulation to test the functionality of wireless beaconing in vehicular networks. Vehicles periodically emit beacon messages with requested application data which is transmitted to all vehicles in the network. Cars with relevant information may respond to these messages. This is just one example of many types of communication that can occur in a vehicular

---

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

Conference'17, July 2017, Washington, DC, USA

© 2020 Association for Computing Machinery.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM...\$15.00

<https://doi.org/10.1145/nnnnnnnn.nnnnnnnn>

network. We chose to focus on beaconing because it is a broadcast that can be read from both vehicles and road side units.

### 4.3 Set up working standard simulation

We have currently stood up a working simulation under normal conditions inside of the OMNeT++ simulator. We have our own road network defined and all of the standard operations and routes. Our plan is to use this current simulation as the environment of our attack.

We did have many issues with this part due to the current lack of documentation on how to use VeINS, leaving us unable to accurately diagnose error messages. When trying to make the simulation, we ran into lots of errors, including failure to load and seg-faulting. We eventually arrived at workarounds, but the occasional issue still comes up.

### 4.4 Proposed methods of attacks

For a DOS attack the goal is to interrupt the service of your intended target by typically overloading the target or destroying what it is trying to send. In the case of wireless vehicles they ping each other when they are driving down the road and they also ping base stations called road side units (RSU).

We wanted to develop a threat scope that would allow for minimal interference with current implementations and the most feasible. For the threat scope of the attack we are creating we define that the adversary has no access to anything currently on the network. That is the adversary is not able to hack into or break into any vehicle or RSU that is already deployed. We define that the adversary has the capability to introduce new equipment into the network that can add more data/messages into the current network.

We currently have two methods of attack that we are testing that both start from the same assumption. We assume that the adversary is able to plant a device on the side of the road that acts like a RSU in a malicious manner. The first attack would DoS the vehicles in the simulation by overloading the vehicles with messages, causing the vehicles to not be able to accept messages. The second approach is to turn the gain up on the radios to generate noise high enough so that it distorts legitimate messages in the network.

## 5 Related Work

### 5.1 IEEE Standard for Information technology - Specifications Amendment 6: Wireless Access in Vehicular Environments [1]

This document is the ongoing specification for the entire 802.11 network range of protocols. Inside of this specification it lists the details for the 802.11p network which is the dedicated radio band for V2X networks. This document is a useful resource as it lists all of the details about every 802.11 network which the V2X protocol should follow as well. Inside as well it has some of the initial details about the 802.11p network. While the details are small now it is what is properly defined at the moment for V2X communication.

### 5.2 Man-In-The-Middle Attacks in Vehicular Ad-Hoc Networks: Evaluating the Impact of Attackers Strategies [2]

This paper examines the possibility of Man-In-The-Middle (MITM) attacks against Vehicular Ad-Hoc Networks (VANET). Due to the sensitive nature of VANETs a secure environment is absolutely necessary for the exchange of messages within a network. Any critical information has the potential to be spoofed or intercepted, causing faulty information to be spread within a vehicular network. With a Man-In-The-Middle attack, a malicious actor can potentially intercept or tamper with messages exchanged between nodes in a VANET. As a metric for measuring a potential attack, the authors use messages delayed, messages dropped, and messages tampered. These allow an accurate gauge of the amount of tampering that has occurred within a VANET. We may adopt similar metrics as we evaluate potential attacks against V2X networks.

When an event occurs in a VANET, a packet typically contains important information regarding the event such as event data, event location, and the time of the event. The authors of the paper assumed this information was both readable and editable by any vehicle on the network as packets are forwarded from malicious vehicles to legitimate vehicles. The effects of these attacks were evaluated with both random attackers distributed randomly across the network and with attackers positioned in a fleet-like structure, launching a collaborative attack against other vehicles or the network as a whole. We plan to launch similar attacks with a focus on adhering to the existing protocols for V2X communication and analyzing their authentication and encryption schemes.

### 5.3 Authentication-Based Vehicle-to-Vehicle Secure Communication for VANETs [3]

This paper points out the obvious security vulnerabilities associated with a vehicular ad hoc network (VANET) and proposes a lightweight authentication scheme (LIAU) to mitigate the issue. The scheme proposed uses a two-layer model (Regional Authorities and registered vehicles) and a hash function to generate authentication parameters. The paper further claims that the proposed solution can resist impersonation, modification, and replay attacks, and has sufficiently low operation time and communication cost. This paper will be useful for our analysis of the existing protocol and its current vulnerabilities.

### 5.4 Bidirectionally Coupled Network and Road Traffic Simulation for Improved IVC Analysis [4]

This paper defines and introduces a framework for the simulation of Inter-Vehicle Communication (IVC) protocols called Vehicles in Network Simulation (VeINS) which we will utilize to test various attacks on V2X communications. It allows coupled network and road traffic simulation, utilizing OMNeT++, a network simulator to model VANET nodes and SUMO, a road simulation package to model and simulate microscopic road traffic. Both modules execute and communicate simultaneously to create a live simulation of

both network communication and road traffic patterns. This bidirectional simulation advances time in discrete steps and guarantees synchronous execution at regular intervals. We will be using VeINS for all testing and evaluation of potential attacks against V2X networks.

### 5.5 V2V Wireless Communication Protocol for Rear-End Collision Avoidance on Highways [5]

This paper describes a protocol used for rear end collision avoidance for vehicles. It outlines the process by which a message warning of a potential hazard can be propagated from the lead vehicle in a line to those behind, triggering evasive maneuvers. This paper will tell us what kinds of factors we can attempt to manipulate when attempting to send data to the existing VeINS system to force a desired outcome.

## References

- [1] 2016. IEEE Standard for Information technology—Telecommunications and information exchange between systems Local and metropolitan area networks—Specific requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications. *IEEE Std 802.11-2016 (Revision of IEEE Std 802.11-2012)* (Dec 2016), 1–3534. <https://doi.org/10.1109/IEEESTD.2016.7786995>
- [2] Asma Adnane, Farhan Ahmad, Virginia Franqueira, Fatih Kurugollu, and Lu liu. 2018. Man-In-The-Middle Attacks in Vehicular Ad-Hoc Networks: Evaluating the Impact of Attackers Strategies. *Sensors* 18 (11 2018). <https://doi.org/10.3390/s18114040>
- [3] Wenjun Hu Juan Wang Huibin Xu, Mengjia Zeng. 2019. Authentication-Based Vehicle-to-Vehicle Secure Communication for VANETs. <https://www.hindawi.com/journals/misy/2019/7016460/>
- [4] C. Sommer, R. German, and F. Dressler. 2011. Bidirectionally Coupled Network and Road Traffic Simulation for Improved IVC Analysis. *IEEE Transactions on Mobile Computing* 10, 1 (Jan 2011), 3–15. <https://doi.org/10.1109/TMC.2010.133>
- [5] F. Ye, M. Adams, and S. Roy. 2008. V2V Wireless Communication Protocol for Rear-End Collision Avoidance on Highways. In *ICC Workshops - 2008 IEEE International Conference on Communications Workshops*. 375–379. <https://doi.org/10.1109/ICCW.2008.77>