

How to Build Trust Into 5G

Fall 2021 Midterm Report

The University of Texas at Dallas

Team 3

Nikhil Joshi - nsj210001@utdallas.edu
Rahul Muthyam - rxm200088@utdallas.edu
Gandhar Joshi - gsj190000@utdallas.edu
Marlon Schumacher - mws180000@utdallas.edu
Benjamin Stark - bjs170002@utdallas.edu

Technical Director

Raj Pal - rmpal@uwe.nsa.gov

University Project Supervisors

Bhavani Thuraisingham - bxt043000@utdallas.edu
Brian Ricks - bwr031000@utdallas.edu

October 21, 2021

Keywords: Remote Attestation, Trust, Deployment, 5G Standard, Decentralized Network, Open5GS, UERANSIM, Docker, AKA, Handover, Roaming

Table of Contents

Project Summary	3
Description	3
Motivation	3
Team Responsibilities	3
Broader Impact	3
Organization	4
Deliverables	4
Plan	4
Schedule	4
Total Budget	4
Team Approach and Justification	5
Progress and Results to Date	5
Future Plans	10
Literature Review	10
Bibliography	12
Biographical Sketches of Investigators	13

Project Summary

Description

There is a growing need to move 5G to a decentralized, autonomous network due to 5G's growing size, multi-layer, and multi-party nature, and usage of 5G slicing for service optimization. This decentralization involves sharing parts of 5G's infrastructure with third parties, which requires an effective security system to verify the trust of the third parties to ensure that only trustworthy data and data sources are in the 5G network. Remote attestation, which verifies a device's integrity by prompting the device to send its identifying information to a verifying agent, has been proposed as one of several possible ways to build trust in 5G. The challenge is figuring out a proper way to successfully implement mutual remote attestation into the 5G network. One of the facets of this project will be applying research findings to roaming and handover test cases.

Motivation

Telecommunication is a core part of our society that has radically changed the way of life. 5G, the next generation of wireless technology, has considerable improvements over its predecessor both in terms of speed and reliability. This has opened up many possibilities which we could've only dreamt of. As such contributing to the development of this technology might not only have an immediate effect on 5G but also on its future generations.

Team Responsibilities

- Understand the architecture of 5G networks and brush up on tools required like WireShark and Git
- Understand the current state of attestation protocols and how they can be applied to a decentralized system
- Design a novel solution for secure attestation and communication in a decentralized 5G network
- Meet with the sponsor weekly for reports and progress updates

Broader Impact

As telecommunication networks are moving to a more decentralized architecture the need for mutual attestation that can be used on decentralized networks is becoming more important. This research will help lead to a better system for devices on these networks to create trust. This applies not only to 5G but can extend and be applied to any decentralized network and future generations.

Organization

Deliverables

- Proposal
- Midterm Report and Presentation
- Final Report and Presentation
- Documentation of research
- Results/evidence of testing

Plan

The team will meet with the sponsor every Monday and Thursday from 12:00 PM - 1:00 PM to discuss the progress of the research project. The team may schedule additional meetings if necessary.

Schedule

September 10	- Proposal and Literature Review Due
September	- Learning current 5G and mutual attestation
October	- Setup testing environment
October 21	- Midterm Report and Presentation Due
November	- Design workflow for existing attestation protocol to implement into 5G
December 9	- Final Report and Presentation Due

Total Budget

This Project has no monetary cost. The group intends to work around nine to eleven hours per week on this project along with weekly meeting updates.

Team Approach and Justification

The team plans to familiarize themselves with 5G and modern attestation protocols by researching both topics and getting hands-on experience with 5G. The team will then explore and analyze different attestation workflows and protocols to use in the 5G network. Hands-on development will then be used to perform tests on implementing these workflows and protocols into the 5G network for the roaming/handover use case.

We plan on using Open5GS to simulate and test the 5G network. We will use Wireshark to collect information data during tests to see actual test results. The final product will be an attestation protocol that works smoothly and securely in the decentralized 5G network architecture, guaranteeing accurate verification of trust.

The results of this approach will help determine the type of remote attestation workflows and protocols that could work in building trust in 5G for roaming and handover scenarios. This in turn will improve the overall understanding of how remote attestation can be effectively implemented in 5G in general, as well as how feasible the implementation would be.

Progress and Results to Date

Open5GS + UERANSIM + Docker Testbed

Our team set up a testing environment using Open5GS and UERANSIM to simulate communications over a 5G network. We chose Open5GS as the 5G core framework because it is open-source and it has more documentation and active maintenance compared to other frameworks. Open5GS also supports various types of 5G network deployment, including NSA (Non-Standalone / Hybrid) and SA (Standalone) modes.

Although Open5GS provides the core 5G network, they do not provide implementations for either the base stations or the user equipment, both of which are required to test the roaming-handover use case. We chose to use the UERANSIM project because it provides software-based implementations for both the gNB (g-Node-B) and UE (User-Equipment). To capture the communication between the different components of the 5G Network, we integrated Wireshark into the testbed.

As 5G is moving towards a more “cloud”-based, we wanted our testbed to have a similar test environment. We could deploy these services in two ways: Kubernetes or Docker-Compose. We initially chose Kubernetes as it is the best container orchestration technology available right now, but setting up the cluster and making sure everything worked was very time-consuming.

We needed a much more straightforward and manageable way to deploy our testbed, so we chose the Docker route. We have set up our environment such that all the core 5G components, gNBs, and the UE share the same Docker network and that Wireshark can be easily used to analyze traffic on this network.




Figure 1: Testbed Deployment Diagram

Modeling Attestation in the Handover Case

Our team created Figures 2 through 4 to illustrate how remote attestation would be implemented in the handover test case.




Figure 2: 5G Inter-gNB-DU Handover

Figure 2 depicts the handover case where the UE connected to source cell 1 with gNB-DU 1 moves to cell 2 with gNB-DU 2. The interfaces among the gNB components make use of protocols used for signaling service with F1AP protocol for F1 interface and E1AP protocol for E1 interface. For this type of handover, no signaling is exchanged with the 5G core as both gNB-DU lie under the same gNB-CU. Here the gNB is split into a Distributed Unit (DU) and Control Unit (CU), which further splits into Control Plane CU-CP and User Plane CU-UP to adapt itself for different RAN performance requirements and location scenarios, as well as to have a distinguished user and control plane traffic management.




Figure 3: 5G Inter-gNB-DU Handover Call flow

Figure 3 shows the handover call flow for inter-gNB-DU mobility. In 5G, handover decisions are based on the measurement report provided by UE. The measurement report contains the signal strength of both serving and neighboring cells. Along with the measurement report and the serving network name (SNN), the source gNB-DU sends a UL RRC Message Transfer to gNB-CU-CP to make a handover decision. After deciding to go with the handover, gNB-CU-CP sends a UE Context setup message to target gNB-DU to make a UE Context and set up SRBs and DRB's bearers. The gNB-CU-CP sends a bearer modification request to gNB-CU-UP, indicating it modifies a list of DRB's. Then gNB-CU-CP sends a message to source gNB-DU to stop data transmission with the UE. The source gNB-DU then conveys the handover decision to UE by sending an RRC configuration message. With this message received by the UE, it initiates the RACH procedure. The RACH procedure tries to acquire the uplink synchronization and cell ID of the target gNB-DU and sends a reply message containing successful completion of RRC

Reconfiguration. The message is conveyed to gNB-CU-CP via gNB-DU, allowing gNB-CU-CP to send a UE context release message to source gNB-DU to release a UE Context with the proper value. This step marks the completion of the handover.

Choices of Attestation Protocols to Test

Collective Remote Attestation (CRA) Protocol

This attestation protocol uses a unique measurement that is obtained from an entire network of IoT devices. This measurement is mainly used to describe the collective status of the entire network, but it can also provide information on the status of each device in the network. The main advantage of the CRA protocol is it can be scaled easily for larger networks, unlike other remote attestation protocols. However, we will need to distinguish attestation scenarios caused by intermittent connections from scenarios caused by IoT devices being compromised. It is also important that we choose a key mechanism that will result in a good balance of efficiency and security [6].

Authentication and Key Agreement (AKA) Protocol

For the 5G network, the AKA protocol has been standardized and it is one of the primary authentication methods that have been defined. These protocols involve the subscribers, the Serving Networks (SNs) that have base stations in subscribers' vicinity, and Home Networks (HNs) that correspond to the subscribers' carriers. The goal of the AKA protocol is to allow the subscribers and the HNs to mutually authenticate each other. Another goal of AKA is to let the subscribers and the SNs establish a session key. This protocol aims to mutually authenticate subscribers and their carriers and establish a secure channel to protect subsequent communication.

Out of the two protocols, we decided to use the AKA protocol.




Figure 4: AKA Protocol in Handover Case

Figure 4 shows the AKA attestation flow among the UE, Serving Network, and Home Network. In Phase 1, the authentication procedure is initiated when UE performs a request, such as a registration request. For such a request, the UE needs to send Unique identifiers to its serving network to identify itself using a Subscription Identifier or a Global Unique Temporary Identifier. Unlike 4G/LTE, these identifiers are sent in a concealed format to protect the identity of UE. The serving network includes the Access and Mobility Management Function (AMF), which is responsible for handling connections and mobility tasks. The Security Anchor Function (SEAF), which resides within AMF, acts as an intermediary during the authentication process between the UE and the Home Network. It then forwards the received UE identifier along with the serving network name to AUSF. The AUSF or authentication Server Function is responsible for deciding on authenticating the UE, which requires security credentials such as key and authentication data, which are provided by Unified Data Management (UDM). The ARPF selects the authentication procedure based on UE identity and policy. SIDF is used to decrypt the UE concealed identity. The UDM then sends the challenge, keys, and response to AUSF, which stores the keys and hashed value of response and sends the challenge to UE via SEAF. Meanwhile, the SEAF also stores the hashed response. Upon receiving the challenge, the UE generates the response. The SEAF verifies this response. However, if the response does not match the hashed response, then the SEAF can reject the authentication. Furthermore, the response is sent to the AUSF to have more control over this process. Only when the AUSF performs successful verification does it provide the SEAF with the keys for secure communication with UE.

Future Plans

Our plan from this point onward for the rest of the term is to first figure out how to successfully implement handover between Open5GS and UERANSIM. This will include mapping the functionalities from our handover diagram to our testbed. After that, we will figure out how to implement attestation protocols into the handover use case. If time permits, we will figure out how to migrate our testbed from Docker to Kubernetes. Near the end of the term, we will write a paper on our final research findings.

Literature Review

Maat: A Platform Service For Measurement and Attestation [1]

This paper describes Maat as a platform service that provides a centralized policy-driven framework in order to determine the integrity measurement tools and attestation protocols (M&A) required for evaluating the trustworthiness of other software platforms. They achieved features such as authenticity, correctness, protection by involving some of the architectural features such as Support for Multiple Appraisers & attestation protocols, Discrete M&A functions which form the base for its Security Model. In the end, they have shown the applicability and integration of Maat with PAM, NAC, IPsec, and client monitoring.

Orchestrating Layered Attestations [2]

This paper introduces COPLAND as a language for orchestrating layered attestation in response to the need for a flexible language, one that specifies layered attestations, to be used together with a flexible set of attestation mechanisms provided by the Maat framework to measure integrity evidence. COPLAND is designed to meet three requirements: accommodate Maat's wide variety of services, provide formal and unambiguous operational semantics for execution, and determine the trust properties of alternative COPLAND phrases using static analysis through denotational semantics. The COPLAND semantics prove the correctness of attestation outcomes dependent on evidence and the ordering of events that gather evidence. In addition, the COPLAND semantics expand the diversity and complexity of attestation by providing a foundation for testing layered attestation protocols. COPLAND is being tested by Maat and is also being used as the language for remote attestation protocols in other systems.

Flexible Mechanisms for Remote Attestation [3]

This paper covers the many problems that occur when it comes to attestation protocols and different attestation shapes. The main ones it focuses on are issues with the order, evidence types, and needing a flexible model for attestation to be able to interact with different sources that require varying levels of attestation. To this end, it proposes the need for the attestation protocol language COPLAND and provides details of what COPLAND is capable of doing and how it helps resolve such issues.

Practical Runtime Attestation for Tiny IoT Devices [4]

This paper briefly discusses existing attestation protocols and their problems and presents a new attestation protocol primarily focused on low-powered IoT devices. Many attestation protocols exist, some of which require a dedicated hardware module (like a TPM)/Software Mechanism/Both for this process. This paper provides a way to overcome this problem by creating a protocol that utilizes generally available hardware components like an MPU and Flash Memory and makes attestation much more accessible and implementable on existing devices.

A Formal Analysis of 5G Authentication [5]

This paper starts with the problems in existing security protocols and how 5G protocols and tools can help in avoiding this problem. The protocol used is called 5G AKA protocol and the tool used to implement this protocol is called Tamarin Prover.

The protocol is very complex and the tool is used to have a better understanding to obtain a proper output for every single property. The flaws were removed and a faithful model along with security evaluation of 5G AKA was provided.

Bibliography

- [1] Maat: A Platform Service for Measurement and Attestation (2017) John Clemens Peter Loscocco, Sarah Helble, J. Aron Pendergrass.
<https://arxiv.org/abs/1709.10147>
- [2] Ramsdell J.D. et al. (2019) Orchestrating Layered Attestations. In: Nielson F., Sands D. (eds) Principles of Security and Trust. POST 2019. Lecture Notes in Computer Science, vol 11426. Springer, Cham. https://doi.org/10.1007/978-3-030-17138-4_9
- [3] Helble, Sarah C., Ramsdell, John D. ,Kretz, Ian D. ,Rowe, Paul D. ,Loscocco, Peter A. ,Alexander, Perry (2020) Flexible Mechanisms for Remote Attestation. Technical Report.
- [4] Hristozov, S., Johann Heyszl, Steffen Wagner and G. Sigl. "Practical Runtime Attestation for Tiny IoT Devices." (2018).
<https://doi.org/10.14722/DISS.2018.23011>
- [5] David Basin, Jannik Dreier, Lucca Hirschi, Saša Radomirovic, Ralf Sasse, and Vincent Stettler. 2018. A Formal Analysis of 5G Authentication. In Proceedings of the 2018 ACM SIGSAC Conference on Computer and Communications Security (CCS '18). Association for Computing Machinery, New York, NY, USA, 1383–1396. DOI:<https://doi.org/10.1145/3243734.3243846>
- [6] M. Ambrosin, M. Conti, R. Lazzeretti, M. M. Rabbani and S. Ranise, "Collective Remote Attestation at the Internet of Things Scale: State-of-the-Art and Future Challenges," in IEEE Communications Surveys & Tutorials, vol. 22, no. 4, pp. 2447-2461, Fourthquarter 2020, doi: 10.1109/COMST.2020.3008879.

Biographical Sketches of Investigators

Rahul Muthyam

Rahul has been involved in the field of computer science for over seven years and is currently pursuing a master's in computer science with a focus in cybersecurity at the University of Texas at Dallas. Rahul is experienced in developing and maintaining software systems using several programming languages like Golang, Java, Javascript, Python, and C and he has also worked extensively with container orchestration platforms like Docker and Kubernetes, which catapulted his knowledge of the inner-workings of computer systems. Rahul is highly interested in cybersecurity, which can be demonstrated by his projects, and he can put his skills and experience to good use and become a valuable team member.

Gandhar Joshi

Gandhar is currently pursuing his master's in computer science with a focus on information assurance at the University of Texas at Dallas. He is familiar with courses such as network security, information security, data, and application security, and various cryptographic protocols. Gandhar's programming skills include Java, SQL, JavaScript, and Linux programming.

Marlon Schumacher

Marlon is currently in his senior year of his bachelor's in computer science and is a fast-track student starting his master's in computer science with a focus in cybersecurity at the University of Texas at Dallas. He is taking courses in computer networks and cyber security. Marlon has experience with Java, C++, C, SQL, JavaScript, PHP, and Python through coursework and internships. He has used GitHub for several group projects and has some exposure to JSON and WireShark.

Benjamin Stark

Benjamin Stark is currently a master's student in computer science with a focus on cybersecurity and information assurance at the University of Texas at Dallas. He has taken courses in networks and network security as well as general information security courses that involve learning and reading protocols. He has also done many projects and competed in challenges involving traffic sniffing; specifically, he has used Wireshark extensively and tcpdump. He has done many projects using C and C++ in his course work and has used GitHub to collaborate on projects with teams.

Nikhil Joshi

Nikhil is currently a master's student in computer science, cybersecurity. This is his first semester here at UTD (The University of Texas of Dallas). Nikhil has taken subjects on network security and system security in his first semester. He is learning new concepts and platforms which will help him in his course and our project as well. Nikhil has done projects in C, C++, Java, and Python in his undergraduate college.