

UNIT 01 · CHAPTER 6

Text Embeddings

CSE 10124 · Building ChatGPT
William Theisen · University of Notre Dame




CSE 10124: Building ChatGPT



Training a BPE Tokenizer

Broadly speaking, we can train our **tokenizer** by **repeatedly looking for common pairings of tokens** and **merging them to create a new token**.





```
[21, 9, 6, 0, 4, 2, 21, 0, 20, 2, 21, 0, 16, 15, 0, 21, 9, 6,
0, 14, 2, 21, 0, 2, 15, 5, 0, 2, 21, 6, 1]

[2, 21]: 4 [21, 9]: 2 [9, 6]: 2 [4, 28]: 1 [20, 28]: 1 [16,
15]: 1 [14, 28]: 1 [2, 15]: 1 [15, 5]: 1 [28, 6]: 1


[21, 9, 6, 0, 4, 28, 0, 20, 28, 0, 16, 15, 0, 21, 9, 6, 0, 14,
28, 0, 2, 15, 5, 0, 28, 6, 1]
```

An untrained tokenizer is effectively just a character-level tokenizer.

Tokenizing a Prompt



Tokenization vs. Meaning



To capture the **meaning** of **tokens**, we use something called **embeddings**

Image Embeddings

What is actually represented in the **<64, 256>** dimensional vector we get after the first layer?




Image Embeddings

The digit classifier, one equation per layer:

<64, 784> images, <784, 256> weights

$$Z_1 = X @ W_1^T + b_1$$

<64, 256>: the first layer's output

$$A_1 = \mathrm{ReLU}(Z_1)$$

<64, 10>

$$Z_2 = A_1 @ W_2^T + b_2$$


<64, 10>

$$\hat{y} = \mathrm{softmax}(Z_2)$$


against the ground truth vectors y, <64, 10>

$$\mathcal{L}_{ce} = -\frac{1}{N}\sum_{i=1}^{N} y_i \cdot \log(\hat{y}_i)$$

Embeddings



Input Prompt
"the cat sat on the mat and ate"
Tokenizer
Token ID | Token
0 | <pad>
1 | "the"
2 | "and"
3 | "ate"
4 | "cat"
5 | "mat"
6 | "on"
7 | "sat"
8 | "a"
9 | "pie"
the 1
cat 4
sat 7
on 6
the 1
mat 5
and 2
ate 3
Embeddings
<1, 768>
<1, 768>
<1, 768>
<1, 768>
<1, 768>
<1, 768>
<1, 768>
<1, 768>

Text Embeddings



Converting **tokens** to **embeddings** allows us to **interpret them as points in high dimensional space**, which then allows us to compare them against each other!

Text Embeddings




One way to think about it, is that **each axis encodes some artifact of language**, plurality, color, gender…

How similar they are on a given axis measures how similar they are on that "thing".


NOTE: Technically the similarity is often on a higher-dimensional manifold than a singular axis, but it's a good way to think about it

Measuring Text Embedding Similarity




Instead of using **euclidean distance**, we often measure the similarity of text embeddings using **cosine similarity**, which measures the angle between two vectors. This is because we often **care about direction**, **rather than magnitude**.


Text Embeddings: Notebook




This allows us to measure how words are related to each other. **Remember that related is only based on co-occurrences!!**

One-Hot Tokenization







Producing Text Embeddings for an Input Prompt



Training an Image Classification Model



Training a Text Prediction Model



Next Class: Anthropic Guest Lecture

Noah Yoshida (Class of 2020), Member of Technical Staff, **Anthropic**


Wednesday September 16th. Ask me anything!

- Debart 214, **11:30 – 12:20**
- Debart 141, **3:30 – 4:45**

Programming Day 04: Text Embeddings

Today we write irishQwen's **EmbeddingLayer** (`irishQwen/embedding.py`):

- `__init__`: a weight matrix `W` of shape `(embed_dim, vocab_size)`, one column per token
- `forward`: look up the columns for a batch of token ids, `(B, T)` → `(B, T, C)`
- `backward`: add the gradient into the columns of the tokens that were used
- `update`: one step of gradient descent



EmbeddingLayer: forward

```python
import torch
import math
class EmbeddingLayer():
    def __init__(self, vocab_size, embed_dim):
        self.W = torch.randn(embed_dim, vocab_size) \
            * math.sqrt(2.0 / vocab_size)
        self.dW = torch.zeros_like(self.W)
    def forward(self, tokens):
        self.tokens = tokens
        E = ________________            # (C, B, T)
        E = ________________            # (B, T, C)
        return E.contiguous()
torch.manual_seed(0)
layer = EmbeddingLayer(512, 256)
tokens = torch.tensor([[446, 309, 44, 32,
                        275, 327, 294, 309]])
out = layer.forward(tokens)
print(tokens.shape, "->", out.shape)
print(torch.equal(out[0, 1], out[0, 7]))   # " be" twice
```

OUTPUT

```
torch.Size([1, 8]) -> torch.Size([1, 8, 256])
tensor(True)
```

Indexing `W[:, tokens]` is the same as `T @ E` without building `T`.

EmbeddingLayer: backward and update

```python
import torch.nn.functional as F

def backward(self, dY):
    C, V = self.W.shape
    flat = self.tokens.reshape(-1)          # (B*T,)
    dY_flat = dY.reshape(-1, C)             # (B*T, C)
    T = ____________________________        # (B*T, V)
    self.dW = _____________                 # (C, V)

def update(self, lr):
    self.W -= _____________

EmbeddingLayer.backward = backward
EmbeddingLayer.update = update
layer.backward(torch.ones(1, 8, 256))
used = (layer.dW[0] != 0).nonzero().reshape(-1)
print(used)
print(layer.dW[0, 309], layer.dW[0, 446])
```

OUTPUT

```
torch.Size([1, 8]) -> torch.Size([1, 8, 256])
tensor(True)
tensor([ 32,  44, 275, 294, 309, 327, 446])
tensor(2.) tensor(1.)
```

Only the columns of tokens in the batch get a gradient, and `" be"` (309), used twice, gets twice as much.

Training a Text Prediction Model

