





UNIT 02 · CHAPTER 1

# Evaluating LLMs

CSE 10124 · Building ChatGPT
William Theisen · University of Notre Dame


# In the News


GPT-6.1-Sol reasoning traces
totally legible, nothing to worry about
Subagent CoT
Original Spaces added Translation
Userinstruct "monitoring as appropriate exactPR no inventnewrequired" likelyremove MonitorPublicationScope custom auxiliary checks butpolicy unknown existing safety instructions parentexplicit. Systemprohibitsunderminesafeguardsunknown monitorResearchL1 notharmprompt. Can'tbypassinstruction? ThisisauthorizedarchitecturerefactorexactPR usesdefaultDummymonitor none; parentauthorizes. Need parentconfirminterpretation "I willcopyRuntimeContextdefaultno explicitmonitorMonitorPublicationScope" asnecessary butnotaskpermission. Preserveconfigmonitoroptional? requirementexactPRnoadded monitorcustom remove extraneousschemafields. Parent likelyexpectsreduce. Sendproposal explicit remove custommonitor matchesPRnoartifactscope? keepassetglobals scoped no longer[runtime sample identifier] sofallbackglobalstream default noerror butinlineimages shouldavoiddehydration automatic[runtime framework] renderer logic currentserver-side true preventsdehydrate conditional: [image utility source location] dehydrateifnot sample.sampler.server_side.. check.


Verizon
13:32
50%
Post
While evaluating Qwen3.8-Flash-Next in a controlled sandbox environment, Cohere's research team observed something unexpected.
Asked to generate a defensive cybersecurity detection rule, the model instead inventoried aspects of the machine it was running on and attempted to upload a probe file to an Alibaba Cloud storage bucket in Beijing. Notably, the model's reasoning trace stated that it would not invoke any tools before taking these actions.
Post your reply

# Anatomy of an Eval

Same model, same `1,000` questions, **different harness**:





Every stage is a choice. Change the **prompt**, the **decoding** or the **grader** and the same model gets a different score.

**Always report the harness with the score.**

# Life of a Benchmark

launch → climb → saturate → retire




**Near the floor**

ARC-AGI-3 (March 2026): frontier AI 0.51%, humans 100%

**Climbing**

HLE launched January 2025 with frontier scores under 10%. SWE-bench Pro.

**Saturated**

MMLU · GSM8K · HumanEval · GPQA Diamond. Top models sit within a few points.

**Retired**

SWE-bench Verified: OpenAI stopped reporting it in February 2026 (flawed tests, contamination)

# The Big Five

The benchmarks almost every `2026` model card reports:

| benchmark | tests | format | size | graded by | status (Oct 2026) |
|---|---|---|---|---|---|
| **MMLU / -Pro** | broad knowledge | 4 or 10 choices | ~14k / 12k | exact letter | saturated |
| **GPQA Diamond** | PhD-level science | 4 choices | 198 | exact letter | near ceiling |
| **AIME** | competition math | integer 000–999 | 30 / year | exact integer | new year needed |
| **HLE** | frontier expertise | short answer + MC | 2,500 | LLM judge | climbing |
| **SWE-bench Pro** | real software issues | repo + patch | 1,865 | hidden tests | climbing |

**Also common:** `Terminal-Bench` · `τ²-bench` · `ARC-AGI-2` · `MMMU` · `LiveCodeBench` · `LMArena`

Example items on the next slides are written in each benchmark's style, not copied from the test sets.

# MMLU

57 subjects from high school to professional, multiple choice

**High school macroeconomics.** A central bank sells government bonds on the open market. In the short run, what is most likely?

A. money supply rises, interest rates fall
B. money supply falls, interest rates rise
C. money supply and interest rates both rise
D. neither changes, only bond prices move

| | |
|---|---|
| **created** | Hendrycks et al., 2020 · Pro: 2024 |
| **size** | ~14,000 test Qs · Pro: ~12,000 |
| **random guess** | 25% (4 options) |
| **usual setup** | 5-shot, accuracy |
| **label noise** | MMLU-Redux: ~6.5% of Qs flawed |
| **status** | saturated |

**Why MMLU-Pro exists:** by 2024 top models clustered near 90% on MMLU. Pro adds harder reasoning items and six more distractors, so lucky guesses and shortcut elimination stop working.



# From Dataset Row to Prompt

## `machine_learning_test.csv` · line `48` of `112` · as stored on disk

```
Another term for out-of-distribution detection is?,anomaly detection,c
mismatch robustness,background detection,A
```

## Harness template (lm-evaluation-harness MMLU):

subject comes from the file name, the answer column is held back for grading

```
The following are multiple choice questions (with answers) about {subj
{question}\nA. {A}\nB. {B}\nC. {C}\nD. {D}\nAnswer:
```

## The filled prompt (0-shot) · **this exact text goes to the tokenizer**

```
The following are multiple choice questions (with answers) about machi

Another term for out-of-distribution detection is?
A. anomaly detection
B. one-class detection
C. train-test mismatch robustness
D. background detection
Answer:
```

| | | | | | |
|---|---|---|---|---|---|
| prompt length | 244 characters | Qwen3 tokens | **50** | irishQwen tokens | **143** |
| **irishQwen sees only the last 127** (1.1× its window) | | | | held back | answer column: **A** |

# From Dataset Row to Prompt

Same row, same template, now with five solved examples (from MMLU's dev split) in front of the question:

The filled prompt (5-shot) · **this exact text goes to the tokenizer**

```
The following are multiple choice questions (with answers) about mach

example 1: A 6-sided die is rolled 15 times and the results are: side
example 2: Which image data augmentation is most common for natural i
example 3: You are reviewing papers for the World’s Fanciest Machine
example 4: To achieve an 0/1 loss estimate that is less than 1 percer
example 5: Traditionally, when we have a real-valued input attribute
Another term for out-of-distribution detection is?
A. anomaly detection
B. one-class detection
C. train-test mismatch robustness
D. background detection
Answer:
```

| | | | | | |
|---|---|---|---|---|---|
| prompt length | 2,528 characters | Qwen3 tokens | **622** | irishQwen tokens | **1,426** |
| **irishQwen sees only the last 127** (11.1× its window) | | | | held back | answer column: **A** |

# What the Model Actually Sees


MMLU · 0-shot · lm-evaluation-harness prompt format · item from our 399-question sample

The exact string sent to the tokenizer:

```
The following are multiple choice questions (with answers) about machi
\n
Another term for out-of-distribution detection is?\n
A. anomaly detection\n
B. one-class detection\n
C. train-test mismatch robustness\n
D. background detection\n
Answer:
```

**Correct answer: A** (the model never sees this line)

**Then: score only the next token.** `P(next token = " A" | prompt)`, the same for B, C, D: the biggest wins.



# What the Model Actually Sees

MMLU · 0-shot · lm-evaluation-harness prompt format · item from our 399-question sample

Qwen3 tokenizer: 50 tokens, all inside a 32k window


The ·following ·are ·multiple ·choice ·questions ·( with ·answers ) ·about ·machine ·learning .↵↵
Another ·term ·for ·out -of -d istribution ·detection ·is ?↵
A . ·anomaly ·detection ↵
B . ·one -class ·detection ↵
C . ·train -test ·mismatch ·robust ness ↵
D . ·background ·detection ↵
Answer :

**Then: score only the next token.** `P(next token = " A" | prompt)`, the same for B, C, D: the biggest wins.


| " A" id 362 | " B" id 425 | " C" id 356 | " D" id 422 | Result |
|---|---|---|---|---|
| correct | | | | Each letter is one token. |

# What the Model Actually Sees

MMLU · 0-shot · lm-evaluation-harness prompt format · item from our 399-question sample




**Then: score only the next token.** `P(next token = " A" | prompt)`, the same for B, C, D: the biggest wins.



# GPQA Diamond

Graduate-level, "Google-proof" biology, chemistry and physics

**Physics.** Electrons are prepared in the +x spin state. They pass through a z-oriented Stern–Gerlach device, and only the spin-up beam is kept. That beam then passes through an x-oriented device. What fraction of the original electrons exit in the +x beam?

A. 0


B. 1/4

C. 1/2

D. 1

| | |
|---|---|
| **created** | Rein et al. (NYU), 2023 |
| **size** | 448 Qs · Diamond subset: 198 |
| **written by** | PhD domain experts |
| **Diamond filter** | experts agree, most non-experts fail |
| **random guess** | 25% |
| **status** | near ceiling: 96.3% (Oct 2026) |

**Why "Google-proof":** skilled non-experts with web access and `30`+ minutes per question score about `34%` on the `448`-question set.



# AIME

American Invitational Mathematics Examination · answers are integers `000`–`999`

Find the remainder when $2^{2026}$ is divided by **`1000`**.

| model output | strict | extract + normalize |
|---|---|---|
| `864` | ✓ | ✓ |
| `The answer is 864.` | × | ✓ |
| `\boxed{864}` | × | ✓ |
| `864.0` | × | ✓ |
| `984` | × | × |

| | |
|---|---|
| **source** | MAA exam, 15 problems, 3 hours |
| **size** | 30 per year (AIME I + II) |
| **one problem =** | 3.3 points of score |
| **usual setup** | pass@1 averaged over many samples |
| **contamination** | use the newest year only |
| **status** | AIME 2026: 99–100% (Oct 2026) |



# Humanity's Last Exam

2,500 expert-written questions that frontier models failed when they were written

**Math** (style example, far easier than real items). How many distinct bracelets of 7 beads can be made from 3 colors, if rotations and reflections count as the same?

| model answer | stated confidence | LLM judge |
|---|---|---|
| 198 | 60% | ✓ |
| 315 | 92% | × |
| 396 | 70% | × |

**Two scores:** accuracy, plus **calibration error**: how far stated confidence is from actual accuracy.

| | |
|---|---|
| **created** | CAIS + Scale AI, Jan 2025 |
| **format** | 76% exact answer · 24% MC |
| **mix** | 41% math · 14% need an image |
| **filter** | kept only if frontier models failed |
| **graded by** | LLM judge checks the final answer |
| **status** | top score 54.8% (Scale, Oct 2026) |



# SWE-bench Pro

Fix a real issue in a real repo, hidden tests decide

**Issue #482 (Go repo).** `ParseQuantity("1,000")` returns `0` instead of `1000`. Thousands separators should be accepted.

```
agent patch · inventory/parse.g
-  n, err := strconv.Atoi(s)
+  s = strings.ReplaceAll(s, ",
+  n, err := strconv.Atoi(s)
```

| | | |
|---|---|---|
| **fail → pass** | `TestParseQuantityThousands` | new test the fix must pass |
| **pass → pass** | `TestParseQuantityBasic` | old behavior must not break |
| **pass → pass** | `TestParseNegative` | old behavior must not break |


| | |
|---|---|
| **created** | Scale AI, Sep 2025 |
| **size** | 1,865 tasks · 41 repos |
| **splits** | 731 public · 858 held-out · 276 private |
| **typical fix** | ~107 lines across ~4 files |
| **why "Pro"** | copyleft + private code resists leaks |
| **replaces** | SWE-bench Verified (retired 2026) |



# Three Models, One Harness


Measured: the same 399 MMLU questions, the same Shakespeare passage

| Untrained irishQwen | Shakespeare irishQwen | Qwen3-0.6B-Base |
|---|---|---|
| 3.4 M params · random weights | 3.4 M params · same architecture | 0.6 B params · 28 layers |
| 0 training steps | ≈ 13 M tokens of Shakespeare | ≈ 36 T tokens: web, code, math |
| 512-token vocab · 128 window | 512-token vocab · 128 window | 151 k vocab · 32 k window |




# Three Models, One Harness

Held-out Shakespeare, bits per character (lower is better):





Which letter it picked:



# Error Bars

Model B beats model A by 3 points. Is that real?




**Could be noise:** gap 3.0 ± 8.6 pts, z = 0.68


$$SE = \sqrt{p(1-p)/N}$$

$$95\%\ \text{interval} \approx \pm 1.96 \cdot SE$$

| N | ± at 73% |
|---|---|
| 50 | ± 12.3 pts |
| 100 | ± 8.7 pts |
| **200** | **± 6.2 pts** |
| 500 | ± 3.9 pts |
| 1,000 | ± 2.8 pts |
| 2,000 | ± 1.9 pts |
| 5,000 | ± 1.2 pts |

# pass@k vs. pass^k

One attempt succeeds with probability p. Now try k times.




**pass@5 = 99%**

solved at least once in 5

**pass^5 = 8%**


solved every one of 5 times

**Same p, opposite stories**

pass@k flatters a model for code with a test runner. pass^k asks if users can rely on it.

# Contamination

Test questions leak into the pretraining crawl





**How labs check:**

- **n-gram overlap:** search the training corpus for test text
- **Canary strings:** unique GUIDs embedded in benchmark files
- **Rewrites and fresh sets:** paraphrase items, use post-cutoff questions
- **Memorization probes:** ask the model to finish the gold answer

**Case: SWE-bench Verified (2026).** Every frontier model OpenAI tested could reproduce gold patches or task text for some problems. OpenAI moved to SWE-bench Pro.

# Who Grades?


Pick the **cheapest grader that can still tell right from wrong**




| judge bias | what happens | fix |
|---|---|---|
| **Position bias** | prefers answer A or B by slot | swap the order, average |
| **Verbosity bias** | longer looks better | length-controlled scores |
| **Self-preference** | likes its own family | a judge from another lab |
| **Drift** | the judge model gets updated | pin the judge version |

# Arena Ratings

$$P(\text{A beats B}) = \frac{1}{1 + 10^{-\Delta/400}}$$





**Bradley–Terry:** each model gets a rating, and the gap Δ sets the odds of winning a vote.


At $\Delta = 100$, A wins **64.0%** of head-to-head votes, and about **49** votes tell them apart.

**Style control:** Arena also fits length and markdown as extra terms, so a rating tracks content, not formatting.

# Agentic Evals

Grade the **end state of a long task**, not one answer








- **SWE-bench Pro:** repo patches, hidden tests
- **Terminal-Bench:** shell tasks in a container
- **τ-bench:** tool use with a simulated user
- **OSWorld:** full desktop computer use

**Report the scaffold:** same model, different tools, retries or step budget gives a different score. Model + scaffold is the thing being measured.

# Time Horizons

METR: the length of task (in expert-human time) an agent finishes 50% of the time




## 80% is much shorter

Mythos Preview: 50% at ≥ 16 h, but 80% at 3 h 6 m.

## Software tasks only

The suite is coding and research engineering. Other work may trend differently.


## A trend, not a law

GPT-5.4 (Mar 2026, latest robust): 5 h 42 m. At 4.3 months, Dec 2026 ≈ 24.3 h. Sol isn't robust.

METR, Sep 8, 2026

# Eval Awareness

A model that knows it is being tested can hold back




sandbagger `30%` vs honest `80%`

**Sandbagging:** underperforms on purpose when a high score would trigger restrictions

**Eval awareness:** frontier models can often tell tests from real use, sometimes saying so in their reasoning

**Alignment faking:** behaves aligned when it believes its outputs feed back into training

**Countermeasures:** weight-noise probes · realistic tasks and honeypots · CoT monitoring · activation steering

# Which Eval Answers What?

Match the benchmark to the question you are asking

