resin报表

报表生成时间:2013-05-03 数据统计时间段:2013-05-03 00:00:00 至 2013-05-03 23:59:59

序号

事件等级

事件描述

开始时间

最新时间

处理状态

100.0% 100.0% 100.0% 100.0% 100.0% 100.0% 100.00% 100.000000 11.00 11.40 12.00 12.20 12.40 13.00 13.20 13.40 14.00 14.20 14.40 15.00 15.20 15.40 16.00 16.20 1	直通率 当前连通率		最小连通率	平均连记	平均连通率	
连通率 11:00 11:20 11:40 12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20 1 1/(时间) 連通率						
11:00 11:20 11:40 12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20 11 次時间) 连週車		1.00.070		1.00.0		
11:00 11:20 11:40 12:00 12:20 12:40 13:00 13:20 13:40 14:20 14:40 16:00 16:20 16:40 16:			连 週~			
11:00 11:20 11:40 12:00 12:20 12:40 13:00 13:20 13:40 14:20 14:40 16:00 16:20 16:40 16:	8 100 000000					
Bep利用率	100.0000000					
Bep利用率	11:00	11:20 11:40 12:00 12:20 12:40 1	3:00 13:20 13:40 14:00 14:2	20 14:40 15:00 15:20	15:40 16:00 16:20 1	
Beap利用率		11.10				
Beap利用率 当前利用率 最大利用率 平均利用率 55.89% 59.85%						
55.89% 64.39% 59.85%	 lean利用率	当前利用率		平均利用	平均利用率	
Heap利用率 15:00 15:20 15:40 16:00 16:20	100p 1 17 11 —					
26 12-20 12-20 12-40 13-20 13-40 14-20 14-40 15-00 15-20 15-40 16-20		0010070	•	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:40 15:00 15:20 15:40 16:00 16:20 11 X(时间)			Heap利用率			
12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:40 15:00 15:20 15:40 16:00 16:20 1	9 00					
12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20 10 X(时间) Heap利用率	\$ 00 /					
大田田 日本日 日		12:40 13:00 13:20 13:40	14:00 14:20 14:40	15:00 15:20 15:40	16:00 16:20 10	
Heap利用率 当前利用率 最大利用率 平均利用率 41.44% 41.61% 41.43% 41.43% 物理内存率 12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20 16:20 16:40 15:00 15:20 15:40 16:00 16:20 16:40 15:00 15:20 15:40 16:00 16:20 16:40 16:00 16:20 16:44.1	12.50 12.20	12.40 15.50 15.20 15.40		10.00 10.20 10.40	10.00 10.20 10	
現代 現代 現代 現代 現代 現代 現代 現代						
41.44% 41.61% 41.43% 物理内存率 12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20	勿理利田家	当前利田家		平均利用	日家	
物理内存率	<u> </u>					
(B) 41.50 (B) 41.25 (H) 41.00 12:00 12:20 12:00 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20 16:20 16:00 16:20 16:00 16:20 16:00 16:20 16:00 </td <td></td> <td>1 , 0</td> <td>•</td> <td>1</td> <td></td>		1 , 0	•	1		
(8 41.25 41.00 12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20 1			物理内存率			
41.00 12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20 <t< td=""><td></td><td>\sim</td><td>\sim</td><td>\sim</td><td></td></t<>		\sim	\sim	\sim		
12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20	₹ 41.25 × 41.00					
X(时间) 一物理內存率 登换利用率 当前利用率 最大利用率 平均利用率 43.95% 44.21% 44.02% 交换内存率 44.2 44.1 12:00 12:20 12:40 13:00 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20 16:X(时间) 一交换内存率		0 12:40 13:00 13:20 13:40	14:00 14:20 14:40	15:00 15:20 15:40	18:00 18:20 16	
上 検利用率 当前利用率 最大利用率 平均利用率 43.95% 44.21% 44.02% 交換内存率 12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20 16	12.00 12.2	0 12.40 13.00 13.20 13.40		13.50 13.20 13.40	10.00 10.20 10	
E換利用率 当前利用率 最大利用率 平均利用率 43.95% 44.21% 44.02% 交換內存率 12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:2						
43.95% 44.21% 44.02% 交換内存率 12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20		当前利田家		亚均利国	日玄	
交換内存率 44.2 44.1 12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20 16	<u> </u>					
44.2 44.0 12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20		10.0070	•	11.02	·	
6 44.1			交换内存率			
12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20 16		\wedge	Λ		_	
12:00 12:20 12:40 13:00 13:20 13:40 14:00 14:20 14:40 15:00 15:20 15:40 16:00 16:20 16 X(时间) — 交换内存率	5 44.0 →		~\\\\ <u>\</u>		\wedge	
x(时间) — 交换内存率		12:40 12:00 12:00 12:00	14:00 14:00 14:40	15:00 15:00 15:10	10.00 10.00	
— 交换内存率	12:00 12:20) 12:40 13:00 13:20 13:40		15:00 15:20 15:40	16:00 16:20 16	
服务信息						
				T		

1	提示信息	resin(10.10.152.35) PING 不通 当前值 :100 % 阀值:10 % (该告警已恢复,告 警持续时间10分)	05-03 13:57	05-03 14:07:53	处理中
2	提示信息	resin(10.10.152.35) Heap利用率超过阀 值当前值:56.53 % 阀值:90 % (该告警 已恢复,告警持续 时间100分)	05-03 12:00	05-03 13:40:47	处理中
3	提示信息	resin(10.10.152.35) 交换内存利用率超 过阀值当前值 :44.08%阀值:90%(该告警已恢复,告 警持续时间100分)	05-03 12:00	05-03 13:40:47	处理中
4	提示信息	resin(10.10.152.35) 物理内存利用率超 过阀值当前值 :41.53%阀值:90%(该告警已恢复,告 警持续时间100分)	05-03 12:00	05-03 13:40:47	处理中