

INFO 151

Web Systems and Services

Week 3 (T2)

Dr Philip Moore

Dr Zhili Zhao

Web-Page Layout Techniques and Design


HTML Layout Techniques

- A multicolumn web-page layout may be created using 4 methods:
 - HTML tables
 - CSS float property
 - CSS flexbox
 - CSS frameworks
- The CSS float and flexbox frameworks
 - are similar to the *GridBagLayout* and *FlowLayout* page layout methods used in Java
- Details of the layout techniques can be found in the course resources

HTML Layout using Frames and Tables

HTML Layout using Frames and Tables

- HTML frames
 - Recall we have covered this method in week 2
 - This method is **NOT** recommended for the reasons identified in week 2
- The **<frame>** element was not designed to be a layout tool
- The purpose of the **<table>** element is to display tabular data
- Additionally for frames:
 - There are problems with printing and bookmarking
 - These problems are the result of GUI **focus** issues
 - In computing the **focus** indicates the component of the GUI selected to receive input (or output)
 - While a user may wish to print or bookmark a web-page the **focus** may be on a specific **frame** resulting in an error (the users needs may not be implemented)



```
<!DOCTYPE html>
<html>
  <head>
    <title>A Nested Frameset Example</title>
  </head>
  <frameset rows="10%,10%,*,5%">
    <frame = src="frm_title.htm">
    <frameset cols="25%,25%,25%,25%">
      <frame src="frm_n1.htm">
      <frame src="frm_n2.htm">
      <frame src="frm_n3.htm">
      <frame src="frm_n4.htm">
    </frameset>
    <frameset cols="15%,*,15%">
      <frame src="frm_b1">
      <frame src="frm_b2">
      <frame src="frm_b3">
    </frameset>
    <frame = src="frm.footer">
  </frameset>
</html>
```

— index.html Top L19 (HTML+)
Wrote /Users/philip/Desktop/index.html

HTML Layout using CSS float

HTML Layout using CSS float

- The CSS float property specifies
 - How an element should float.
 - What elements can float beside the cleared element and on which side (left (or) right)
- The floating process must be known and understood to remember how the float and clear properties function
- It is common to create entire web layouts using the CSS float property
- Advantages
 - CSS float is a simple method to learn and implement
- Disadvantages
 - Floating elements are tied to the document flow
 - Document flows may impact the flexibility
- Full details of the CSS float property can be found in the course resources

CSS Float Properties

Full details of the CSS float property can be found at [w3schools.com](https://www.w3schools.com)

Property	Description
<u>box-sizing</u>	Defines how the width and height of an element are calculated: should they include padding and borders, or not
<u>clear</u>	Specifies what elements can float beside the cleared element and on which side
<u>float</u>	Specifies how an element should float
<u>overflow</u>	Specifies what happens if content overflows an element's box
<u>overflow-x</u>	Specifies what to do with the left/right edges of the content if it overflows the element's content area
<u>overflow-y</u>	Specifies what to do with the top/bottom edges of the content if it overflows the element's content area

A CSS Float Example

- From the following slides we can see that
 - The profile (the width) of the web-page dynamically changes
 - Changing the profile of the web-page also re-locates the sections in the web-page
 - This is achieved by 'dragging' the edges of the web-page to a desired size
 - The height of the web-page will also change – as the width is reduced the height also changes
- This capability to change profile has benefits:
 - The user may change the profile 'on-the-fly' when viewing the web-page
 - The web-page will dynamically change to suit the GUI

CSS Layout Float

In this example, we have created a header, two columns/boxes and a footer. On smaller screens, the columns will stack on top of each other.

Resize the browser window to see the responsive effect (you will learn more about this in our next chapter - HTML Responsive.)

Cities

[London](#)
[Paris](#)
[Tokyo](#)

London

London is the capital city of England. It is the most populous city in the United Kingdom, with a metropolitan area of over 13 million inhabitants.

Standing on the River Thames, London has been a major settlement for two millennia, its history going back to its founding by the Romans, who named it Londinium.

Footer

CSS Layout Float

In this example, we have created a header, two columns/boxes and a footer. On smaller screens, the columns will stack on top of each other.

Resize the browser window to see the responsive effect (you will learn more about this in our next chapter - HTML Responsive.)

Cities

[London](#)
[Paris](#)
[Tokyo](#)

London


London is the capital city of England. It is the most populous city in the United Kingdom, with a metropolitan area of over 13 million inhabitants.


Standing on the River Thames, London has been a major settlement for two millennia, its history going back to its founding by the Romans, who named it Londinium.



A CSS float Example in NetBeans the IDE


- The following slides show CSS float implemented in the NetBeans IDE
 - An example using the HTML CSS float layout
- We can see from the NetBeans IDE
 - The Projects, Navigator and Browser Dom information and elements
- The HTML and style rules that define the output are shown in the NetBeans editor
- The output shows
 - the navigator bar formatted with the **Home** link changing colour (red to black) when in **mouseover**
 - The width of the navigator bar changes dynamically to match the browser





```
21     text-align: center;
22     padding: 14px 16px;
23     text-decoration: none;
24 }
25
26 li a: hover {
27     background-color: #111;
28 }
29
30 .active {
31     background-color: red;
32 }
33 </style>
34 </head>
35 <body>
36
37 <ul>
38     <li><a href="#home" class="active">Home</a></li>
39     <li><a href="#news">News</a></li>
40     <li><a href="#contact">Contact</a></li>
41     <li><a href="#about">About</a></li>
42 </ul>
43
44 </body>
45 </html>
```

Debugging session with browser was closed.



NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Search (Ctrl+I)

139.3/362.0MB

Projects | **Files** | **Services**

- HTML_Float_Navigation
 - Site Root
 - index.html
 - Unit Tests
 - Important Files

Navigator | **Browser DOM**

- CSS**
 - Classes
 - .active
 - Elements
 - a
 - li
 - ul
 - Rules
 - .active
 - li
 - li a
 - li a:hover
 - ul
- HTML**
 - html
 - head
 - title
 - style
 - body
 - ul
 - li
 - li
 - li
 - li

index.html

Source History

```
21 text-align: center;
22 padding: 14px 16px;
23 text-decoration: none;
24 }
25
26 li a:hover {
27     background-color: #111;
28 }
29
```

html > head > style

NetBeans example: CSS flo...

http://localhost:8383/HTML_Float_Navigation/index.html

100%

Home News Contact About

Output - Browser Log


>

CSS Styles

<No Element Selected>

No Rule Selected

<No Properties>



NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Search (Ctrl+I)

232.7/362.0MB

Projects Files Services

HTML_Float_Navigation

Site Root

index.html

Unit Tests

Important Files

Navigator Browser DOM

http://localhost:8383/HTML_Float_Navigation/i...

html

head

title

style

body

ul

li

a.active

li

a

li

a

li

a

index.html

Source History

```
21 text-align: center;
22 padding: 14px 16px;
23 text-decoration: none;
24 }
25
26 li a:hover {
27     background-color: #111;
28 }
29
```

NetBeans example: CSS flo...

http://localhost:8383/HTML_Float_Navigation/index.html

100%

Home News Contact About

Output - Browser Log

>

<No Element Selected>

No Rule Selected


<No Properties>

Slide 15 of 44

8:15

INS

09:32
07/08/2018



NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Search (Ctrl+I)

260.2/362.0MB

Projects Files Services

HTML_Float_Navigation

Site Root
index.html
Unit Tests
Important Files

Navigator Browser DOM

http://localhost:8383/HTML_Float_Navigation/i...

html
head
title
style
body
ul
li
a.active
li
a
li
a
li
a

index.html

Source History

```
21 text-align: center;  
22 padding: 14px 16px;  
23 text-decoration: none;  
24 }  
25  
26 li a:hover {  
27     background-color: #111;  
28 }  
29
```

html head style

NetBeans example: CSS flo...

http://localhost:8383/HTML_Float_Navigation/index.html

100%

Home News Contact About

Output - Browser Log

>

CSS Styles

<No Element Selected>

No Rule Selected

<No Properties>


Slide 17 of 44

http://localhost:8383/HTML_Float_Navigation/index.html#home

8:15

INS

09:33
07/08/2018



CSS flexbox

HTML Layout using CSS flexbox

- CSS flexbox is a new layout mode in CSS3
- Advantages
 - Use of flexbox ensures that elements behave predictably when
 - The web-page layout must accommodate different interfaces and screen sizes
 - The web-page layout must present the optimal layout on different devices
- Disadvantages
 - CSS flexbox is not supported by older browsers (IE10 and earlier)
- Details of CSS flexbox may be found in the course resources

CSS Flexbox Properties

Full details of the CSS flexbox properties can be found at [w3schools.com](https://www.w3schools.com)

Value	Description
<i>flex-grow</i>	A number specifying how much the item will grow relative to the rest of the flexible items
<i>flex-shrink</i>	A number specifying how much the item will shrink relative to the rest of the flexible items
<i>flex-basis</i>	The length of the item. Legal values: "auto", "inherit", or a number followed by "%", "px", "em" or any other length unit
auto	Same as 1 1 auto.
initial	Same as 0 1 auto. Read about <i>initial</i>
none	Same as 0 0 auto.
inherit	Inherits this property from its parent element. Read about <i>inherit</i>

CSS Properties used in flexbox

Property	Description
<u>display</u>	Specifies the type of box used for an HTML element
<u>flex-direction</u>	Specifies the direction of the flexible items inside a flex container
<u>justify-content</u>	Horizontally aligns the flex items when the items do not use all available space on the main-axis
<u>align-items</u>	Vertically aligns the flex items when the items do not use all available space on the cross-axis
<u>flex-wrap</u>	Specifies whether the flex items should wrap or not, if there is not enough room for them on one flex line
<u>align-content</u>	Modifies the behavior of the flex-wrap property. It is similar to align-items, but instead of aligning flex items, it aligns flex lines
<u>flex-flow</u>	A shorthand property for flex-direction and flex-wrap
<u>order</u>	Specifies the order of a flexible item relative to the rest of the flex items inside the same container
<u>align-self</u>	Used on flex items. Overrides the container's align-items property
<u>flex</u>	Specifies the length of a flex item, relative to the rest of the flex items inside the same container

HTML Layout using CSS flexbox

- From the following slides we can see that
 - The profile (the width) of the web-page dynamically changes
 - Changing the profile of the web-page also redefines the sections defined in the web-page
 - This is achieved by 'dragging' the edges of the web-page to a desired size
 - The height of the web-page will also change dynamically
- As for the *CSS float* the capability to change profile has a number of benefits
 - The user may change the profile 'on-the-fly' when viewing the web-page
 - Again: the layout of the webpage can be changed to suit different devices and interfaces

Resize the browser window to see the responsive effect.

My Website

With a flexible layout.

Link Link Link Link

About Me

Photo of me:

Image


Some text about me in culpa qui officia

TITLE HEADING

Title description, Dec 7, 2017

Image

Some text



file:///Users/philip/Desktop/mv

Resize the browser window to see the responsive effect.

My Website

With a **flexible** layout.

[Link](#)
[Link](#)
[Link](#)
[Link](#)

About Me


Photo of me:

Image



A CSS *flexbox* Example in NetBeans IDE

- The following slides show an example of the CSS flexbox layout implemented in the NetBeans IDE
- We can see from the NetBeans IDE
 - The Projects, Navigator and Browser Dom information and elements
- The HTML and style rules that define the output are shown in the NetBeans editor
- The output shows
 - The dynamically changing output to match the web-browser profile
 - The width and size of the elements change dynamically to match the width of the display



Projects Files Services

HTML_Flexbox_Flex_Box

- Site Root
- index.html
- Unit Tests
- Important Files

Navigator

CSS

- Classes
 - .flex-container
- Elements
 - div
- Rules
 - .flex-container
 - .flex-container > div

HTML

- html
 - head
 - title
 - style
 - body
 - h1
 - div class=flex-container
 - div
 - div
 - div
 - div
 - div
 - div
 - div
 - n

index.html


Source History


```
19 }
20 </style>
21 </head>
22 <body>
23 <h1>Flexible Boxes</h1>
24
25 <div class="flex-container">
26   <div>1</div>
27   <div>2</div>
28   <div>3</div>
29   <div>4</div>
30   <div>5</div>
31   <div>6</div>
32   <div>7</div>
33   <div>8</div>
34 </div>
35
36 <p>Try to resize the browser window.</p>
37 <p>A container with "flex-wrap: nowrap;" will never wrap its items.</p>
38 <p><strong>Note:</strong> Flexbox is not supported in Internet Explorer 10 or earlier versions.</p>
39
40 </body>
41 </html>
```

- The <div> tag defines a division or a section in an HTML document.
- The <div> element is often used as a container for other HTML elements to style them with CSS or to perform certain tasks with JavaScript.

Output - Browser Log

Debugging session with browser was closed.





NetBeans IDE 8.2

File Edit View Navigate Source Refactor Run Debug Profile Team Tools Window Help

Search (Ctrl+I)

Projects Files Services

HTML_Flexbox_Flex_Box
Site Root
index.html
Unit Tests
Important Files

Navigator

Browser DOM

http://localhost:8383/HTML_Flexbox_Flex_Box/...

html
head
body
h1
div.flex-container
p
p
p

index.html

Source

```
19 }  
20 </style>
```


html body

HTML CSS Flexbox Example

http://localhost:8383/HTML_Flexbox_Flex_Box/index.html

100%

Flexible Boxes



Try to resize the browser window.

A container with "flex-wrap: nowrap;" will never wrap its items.

Note: Flexbox is not supported in Internet Explorer 10 or earlier versions.

Output - Browser Log

>

CSS Styles

<No Element Selected>

No Rule Selected

<No Properties>

Flexible Boxes



Try to resize the browser window.

A container with "flex-wrap: nowrap;" will never wrap its items.

Note: Flexbox is not supported in Internet Explorer 10 or earlier versions.

Flexible Boxes



Try to resize the browser window.

A container with "flex-wrap: nowrap;" will never wrap its items.

Note: Flexbox is not supported in Internet Explorer 10 or earlier versions.

```
Boxes</h1>
```

```
flex-container">
```

```
<v>  
<v>  
<v>  
<v>  
<v>  
<v>  
<v>
```

```
size the browser window.</p>
```

```
er with "flex-wrap: nowrap;" will never wrap its items..
```

```
Note:</strong> Flexbox is not supported in Internet Expl
```

```
with browser was closed.
```

Search (Ctrl+I)

CSS Styles

<No Element Selected>

No Rule Selected

<No Properties>

22:7

INS

10:49
07/08/2018

Flexible Boxes



Try to resize the browser window.

A container with "flex-wrap: nowrap;" will never wrap its items.

Note: Flexbox is not supported in Internet Explorer 10 or earlier versions.

```
19 }
20 </style>
21 </head>
22 <body>
23   <h1>Flexible Boxes</h1>
24
25   <div class="flex-container">
26     <div>1</div>
27     <div>2</div>
28     <div>3</div>
29     <div>4</div>
30     <div>5</div>
31     <div>6</div>
32     <div>7</div>
33     <div>8</div>
34   </div>
35
36   <p>Try to resize the browser window.</p>
37   <p>A container with "flex-wrap: nowrap;" will never wrap its items..</p>
38   <p><strong>Note:</strong> Flexbox is not supported in Internet Expl</p>
39
40 </body>
41 </html>
```

Output - Browser Log

Debugging session with browser was closed.
>

HTML Layout using a CSS framework

What is a Framework?

- Recall that in Week #1 we introduced the concept of a programming framework
- NetBeans has a built-in framework of pre-programmed code modules (*application programming interfaces* (or API's))
- The aim of such a framework is to promote modular computer programming using re-usable code modules
- The CSS framework operates on the same principle where regularly used components are available in pre-programmed HTML CSS components

HTML Layout using a CSS framework

- What is a CSS framework?
 - CSS frameworks provide a basic structure for designing consistent solutions
 - Addresses common recurring issues across front end web development.
 - CSS frameworks provide generic functionality which can be overridden to create domain-specific applications
 - There are many existing CSS Frameworks that offer Responsive Design.
- A typical CSS framework is the W3.CSS framework
- The W3.CSS enables development of web-sites across a range of devices and interfaces





W3.CSS

- W3.CSS is a modern CSS framework with built-in responsiveness
 - Smaller and faster than other CSS frameworks
 - Easier to learn, and easier to use than other CSS frameworks
 - Better cross-browser compatibility than other CSS frameworks
 - Uses standard CSS only (No jQuery or JavaScript library)
 - Supports modern responsive mobile first design by default
 - Provides CSS equality for all browsers: Chrome, Firefox, Edge, IE, Safari, Opera, ...
 - Provides CSS equality for all devices: desktop, laptop, tablet, and mobile
 - Speeds up and simplifies web development

W3.CSS Examples

- W3.CSS cover the majority of HTML elements – examples include
 - W3.CSS Navigation
 - W3.CSS Sidebar
 - W3.CSS Panels
 - W3.CSS Text
 - W3.CSS Round
 - W3.CSS Buttons
 - W3.CSS Tables
 - W3.CSS Lists
- The following slides demonstrate the implementation of these elements using W3.CSS

W3.CSS - Navigation

Run »

Result Size: 620 x 441

```
<!DOCTYPE html>
<html>
<title>W3.CSS</title>
<meta name="viewport" content="width=device-width, initial-scale=1">
<link rel="stylesheet" href="https://www.w3schools.com/w3css/4/w3.css">
<body>

<div class="w3-container">
  <h2>Navigation Bars</h2>
  <p>The <strong>w3-bar</strong> class is a container for displaying
HTML elements horizontally.</p>
  <p>The <strong>w3-bar-item</strong> class defines the container
elements.</p>
  <p>It it a perfect tool for creating navigation bars:</p>
</div>

<div class="w3-bar w3-black">
  <a href="#" class="w3-bar-item w3-button">Home</a>
  <a href="#" class="w3-bar-item w3-button">Link 1</a>
  <a href="#" class="w3-bar-item w3-button">Link 2</a>
  <a href="#" class="w3-bar-item w3-button">Link 3</a>
</div>

</body>
```

Navigation Bars


The **w3-bar** class is a container for displaying HTML elements horizontally.

The **w3-bar-item** class defines the container elements.






It it a perfect tool for creating navigation bars:

Home Link 1 Link 2 Link 3

W3.CSS - Sidebar



W3.CSS - Panels



Result Size: 620 x 441

```
<!DOCTYPE html>
<html>
<title>W3.CSS</title>
<meta name="viewport" content="width=device-width, initial-scale=1">
<link rel="stylesheet" href="https://www.w3schools.com/w3css/4/w3.css">
<body>

<div class="w3-container">
  <h2>Displaying Panels</h2>
  <p>Panels are the same as containers except for an added top and
bottom margin.</p>

  <div class="w3-panel w3-red">
    <p>I am a panel.</p>
  </div>
  <div class="w3-panel w3-green">
    <p>I am a panel.</p>
  </div>

  <div class="w3-container w3-red">
    <p>I am a container.</p>
  </div>
  <div class="w3-container w3-green">
    <p>I am a container.</p>
  </div>
</div>
```

Displaying Panels

Panels are the same as containers except for an added top and bottom margin.





I am a panel.

I am a panel.

I am a container.

I am a container.

W3.CSS - Text

Run »Result S

```
<!DOCTYPE html>
<html>
<title>W3.CSS</title>
<meta name="viewport" content="width=device-width, initial-scale=1">
<link rel="stylesheet" href="https://www.w3schools.com/w3css/4/w3.css">
<body>

<div class="w3-container">
  <h1>Heading 1 (36px)</h1>
  <h2>Heading 2 (30px)</h2>
  <h3>Heading 3 (24px)</h3>
  <h4>Heading 4 (20px)</h4>
  <h5>Heading 5 (18px)</h5>
  <h6>Heading 6 (16px)</h6>
</div>

</body>
</html>
```

Heading 1 (36px)

Heading 2 (30px)





Heading 3 (24px)

Heading 4 (20px)

Heading 5 (18px)

Heading 6 (16px)

W3.CSS – Round Classes

Run »

Result Size: 620 x 441

```
<!DOCTYPE html>
<html>
<title>W3.CSS</title>
<meta name="viewport" content="width=device-width, initial-scale=1">
<link rel="stylesheet" href="https://www.w3schools.com/w3css/4/w3.css">
<body>

<div class="w3-container">
  <h2>Round Classes</h2>

  <div class="w3-panel w3-round-small w3-teal">
    <p>w3-round-small</p>
  </div>

  <div class="w3-panel w3-round w3-teal">
    <p>w3-round</p>
  </div>

  <div class="w3-panel w3-round-large w3-teal">
    <p>w3-round-large</p>
  </div>

  <div class="w3-panel w3-round-xlarge w3-teal">
    <p>w3-round-xlarge</p>
  </div>

  <div class="w3-panel w3-round-xxlarge w3-teal">
    <p>w3-round-xxlarge</p>
  </div>
</div>
```

Round Classes

w3-round-small





w3-round

w3-round-large

w3-round-xlarge

w3-round-xxlarge

W3.CSS - Buttons

Run »Result Size: 620 x 441

```
<!DOCTYPE html>
<html>
<title>W3.CSS</title>
<meta name="viewport" content="width=device-width, initial-scale=1">
<link rel="stylesheet" href="https://www.w3schools.com/w3css/4/w3.css">
<body>

<div class="w3-container">
  <h2>Buttons (w3-button)</h2>
  <input type="button" class="w3-button w3-black" value="Input Button">
  <button class="w3-button w3-black">Button Button</button>
  <a href="#" class="w3-button w3-black">Link Button</a>
</div>

<div class="w3-container">
  <h2>Buttons (w3-btn)</h2>
  <input type="button" class="w3-btn w3-black" value="Input Button">
  <button class="w3-btn w3-black">Button Button</button>
  <a href="#" class="w3-btn w3-black">Link Button</a>
</div>

</body>
</html>
```

Waiting for eus.rubiconproject.com...

Buttons (w3-button)

Button Button [Link Button](#)

Buttons (w3-btn)

Button Button [Link Button](#)

W3.CSS – Basic Table



Result Size: 620 x 441

```
<!DOCTYPE html>
<html>
<title>W3.CSS</title>
<meta name="viewport" content="width=device-width, initial-scale=1">
<link rel="stylesheet" href="https://www.w3schools.com/w3css/4/w3.css">
<body>

<div class="w3-container">
  <h2>Basic Table</h2>
  <p>The w3-table class defines a basic table:</p>





  <table class="w3-table">
    <tr>
      <th>First Name</th>
      <th>Last Name</th>
      <th>Points</th>
    </tr>
    <tr>
      <td>Jill</td>
      <td>Smith</td>
      <td>50</td>
    </tr>
    <tr>
      <td>Eve</td>
```

Basic Table

The w3-table class defines a basic table:

First Name	Last Name	Points
Jill	Smith	50
Eve	Jackson	94
Adam	Johnson	67

W3.CSS – Basic List

Run »Result Size: 620 x 441

```
<!DOCTYPE html>
<html>
<title>W3.CSS</title>
<meta name="viewport" content="width=device-width, initial-scale=1">
<link rel="stylesheet" href="https://www.w3schools.com/w3css/4/w3.css">
<body>

<div class="w3-container">
  <h2>Basic List</h2>
  <p>The w3-ul class creates a basic list:</p>
  <ul class="w3-ul">
    <li>Jill</li>
    <li>Eve</li>
    <li>Adam</li>
  </ul>
</div>

</body>
</html>
```

Basic List

The w3-ul class creates a basic list:

- Jill
- Eve
- Adam

Waiting for cdn.connectad.io...

Conclusions

Browser Support Reference

- We have introduced the CSS web-page layout techniques
- In previous sessions we have identified the potential variability of web browser support for HTML and HTML 5
- There may be similar problems with web-browser support variability for CSS and CSS3 style sheets
- For details of web-browser support see [w3schools.com](https://www.w3schools.com)
- For specific details regarding CSS3 CSS support see
 - https://www.quanzhanketang.com/cssref/css3_browsersupport.html

Feedback

- When designing and developing a web-page (or web-site) we have in previous sessions introduced
 - Usability and security considerations and the 'trade-off'
- A further important consideration is 'feedback' to users
- We have seen in this session a CSS float example where a navigation bar was created with links to other web-pages
 - In this example we saw that when the cursor *hovered* over the home link (*mousover*) the colour changed from red to black
 - This is an example of feedback which informs the user of an action
- When developing web-pages and web-sites user feedback is important

bringing it all together

- Knowing how to create HTML files and run web-pages / web-sites does not address the need for good web-site design
- Bringing it all together is the process of design where
 - The requirements are investigated
 - The appropriate features are selected
 - The features selected are combined into a web-page / web-site that is
 - Attractive / easy to use / effective in presenting the information / provides user interactive feedback
- It is the task of the designer to
 - Meet the user requirements specification
 - Provide a multi-page web-site with clear navigation that users will want to visit

Review

- In this lecture we have:
 - Introduced Web-Page Layout and Design
 - Introduced HTML layout elements
 - Introduced HTML tables
- Shown multi-column web-page layouts using the following 4 methods:
 - HTML tables
 - CSS float property
 - CSS flexbox
 - CSS framework
- Adding style and Cascading Style Sheets in web-page layout and design
- Introduced HTML / CSS layout techniques with examples implemented in the Net Beans IDE