FIFA 21

Power BI Data Model & DAX Reference

Structure of the field_players data model, and the DAX code of every measure and calculated column

November 2026

Table of Contents

1. Data Model Overview

2. Folder Summary

3. Source Data Structure

- 3.1. What R Resolved
- 3.2. CSV-to-Model Column Mapping
- 3.3. Additional Columns

4. field_players Folders and DAX Code

- 01. Player Information
- 02. Player Attributes
- 03. Player Performance
- 04. Age & Position Groups
- 05. KPI & Summary
- 06. Position Benchmarks
- 07. Classification
- 08. Recruitment Scoring
- 09. Financial Analysis
- 10. Squad Selection

1. Data Model Overview

The Power BI model contains two tables: `field_players`, which holds the FIFA 21 player data (16,904 rows × 83 columns, goalkeepers excluded), and `Target Club`, a one-column calculated table. The `field_players` table is organized into 10 folders. In total the model holds 52 DAX objects: 38 measures, 13 calculated columns and 1 calculated table.

Table 1. Model summary

Category	Count
Tables in the model	2 (`field_players`, `Target Club`)
Folders in `field_players`	10 (numbered 01–10)
Original columns from the CSV	77
Additional columns (not created with DAX)	6 (R: `years_at_club`, `Left`, `Striker`, `Goalie`; extracted from `Team...Contract`: `Club`, `Contract`)
Measures (DAX)	38
Calculated columns, text (DAX)	7
Calculated columns, numeric (DAX)	6
Calculated table (DAX)	1 (`Target Club`)

2. Folder Summary

Each folder serves a specific analytical purpose. DAX objects appear mainly in folders 04–10; folder 01 contains one measure, `No Club`.

Table 2. Folders of field_players

Folder	Contents	Items	DAX	Purpose
01. Player Information	17 columns + 1 measure	18	1	Identity, club, contract and joining date
02. Player Attributes	16 numeric columns	16	0	Physical attributes, age and rating indicators (Skill, SM, W.F …)
03. Player Performance	45 numeric columns (including X.OVA and POT)	45	0	Detailed skill and performance metrics
04. Age & Position Groups	6 calculated columns (text)	6	6	Groups for age, OVA, position, POT, value and wage

Folder	Contents	Items	DAX	Purpose
05. KPI & Summary	4 measures	4	4	High-level KPIs: average age, OVA, POT and player count
06. Position Benchmarks	15 measures	15	15	Median OVA, POT, value and wage by position group and club; position rank
07. Classification	8 measures + 1 calculated column	9	9	Low / Medium / High classification and Pass / Fail tests
08. Recruitment Scoring	3 measures	3	3	Filtering, scoring and prioritizing recruitment targets
09. Financial Analysis	6 measures + 6 calculated columns (numeric) + 3 original columns	15	12	Market value, wage, club budgets and value-for-rating efficiency
10. Squad Selection	1 measure + the Target Club item	2	2	Starting XI selection and the target-club table
Total		**133**	**52**	

3. Source Data Structure

The Power BI source file is `field_players.xlsx`: 16,904 rows × 83 columns. It was derived from the original CSV (18,979 rows × 77 columns) by cleaning the data in R and removing 2,075 goalkeepers (`BP == "GK"`). The 83 columns consist of the 77 original columns, 4 columns created in R (`years_at_club`, `Left`, `Striker`, `Goalie`) and 2 columns extracted from `Team...Contract` (`Club`, `Contract`), which are not created in the R script.

Column names were changed by R (`read.csv`): spaces, `/` and `&` became `.`, and ↓OVA became `X.OVA`. One player (ID 251698, K. Berlaso) appears twice, so the file contains 16,903 unique IDs.

3.1. What R Resolved

Table 3. R data preparation steps

Script section	Process	Result
1.2	Read the original CSV with `read.csv`	18,979 × 77
1.3.1	Trim whitespace and remove `\r` `\n` `\t` from all text columns (`str_squish`)	`Team...Contract` and `Hits` no longer contain line breaks
1.3.2	`Height`: convert feet and inches to inches	5'7" → 67

Script section	Process	Result
1.3.3	`Weight`: convert pounds to kilograms (divide by 2.20462)	159lbs → 72
1.4	Convert `Value`, `Wage` and `Release.Clause` to numbers (`money_to_number`)	€67.5M → 67,500,000
1.5	`W.F`, `SM`, `IR`: remove ★ and convert to numbers	Numeric 1–5
1.6	`Joined`: convert to Date	2004-07-01
1.7	`years_at_club`: years between `Joined` and `Sys.Date()`, rounded to 2 decimals	New column, 78 columns
1.9	Dummy variables: `Left` (foot), `Striker` (BP = ST), `Goalie` (BP = GK)	3 new columns, 81 columns
1.9	`field_players`: data excluding `BP == "GK"`	16,904 × 81

After the R processing, `field_players.xlsx` contains 83 columns because `Club` and `Contract` were added from `Team...Contract`. The R script also creates `position_dummies` (14 BP* columns), but this table is not part of the Power BI model.

3.2. CSV-to-Model Column Mapping

Folder assignments for 01–03 and 09 were read from the field-list screenshots. Columns marked 03* were cropped from the screenshot (between Goalkeeping and X.OVA); their folder was inferred from the alphabetical order of the list.

Table 4. Mapping of CSV columns to model columns

#	CSV column	Type	Example (Messi)	Model column	Folder
1	photoUrl	text	https://cdn.sofifa.com/players/158/023/21_60.png	photoUrl	01
2	LongName	text	Lionel Messi	LongName	01
3	playerUrl	text	http://sofifa.com/player/158023/...	playerUrl	01
4	Nationality	text	Argentina	Nationality	01
5	Positions	text	RW ST CF	Positions	01
6	Name	text	L. Messi	Name	01
7	Age	int	33	Age	02
8	↓OVA	int	93	X.OVA	03*
9	POT	int	93	POT	03*
10	Team & Contract	text	FC Barcelona 2004 ~ 2021	Team...Contract	01
11	ID	int	158023	ID	01
12	Height	text	5'7"	Height	02
13	Weight	text	159lbs	Weight	02

#	CSV column	Type	Example (Messi)	Model column	Folder
14	foot	text	Left	foot	01
15	BOV	int	93	BOV	03
16	BP	text	RW	BP	01
17	Growth	int	0	Growth	03*
18	Joined	text	1-Jul-04	Joined	01
19	Loan Date End	text	N/A	Loan.Date.End	01
20	Value	text	€67.5M	Value	09
21	Wage	text	€560K	Wage	09
22	Release Clause	text	€138.4M	Release.Clause	09
23	Attacking	int	429	Attacking	03
24	Crossing	int	85	Crossing	03
25	Finishing	int	95	Finishing	03
26	Heading Accuracy	int	70	Heading.Accuracy	03*
27	Short Passing	int	91	Short.Passing	03*
28	Volleys	int	88	Volleys	03*
29	Skill	int	470	Skill	02
30	Dribbling	int	96	Dribbling	03
31	Curve	int	93	Curve	03
32	FK Accuracy	int	94	FK.Accuracy	03
33	Long Passing	int	91	Long.Passing	03*
34	Ball Control	int	96	Ball.Control	03
35	Movement	int	451	Movement	03*
36	Acceleration	int	91	Acceleration	02
37	Sprint Speed	int	80	Sprint.Speed	02
38	Agility	int	91	Agility	02
39	Reactions	int	94	Reactions	02
40	Balance	int	95	Balance	02
41	Power	int	389	Power	03*
42	Shot Power	int	86	Shot.Power	03*
43	Jumping	int	68	Jumping	02
44	Stamina	int	72	Stamina	02
45	Strength	int	69	Strength	02
46	Long Shots	int	94	Long.Shots	03*
47	Mentality	int	347	Mentality	03*
48	Aggression	int	44	Aggression	02
49	Interceptions	int	40	Interceptions	03*
50	Positioning	int	93	Positioning	03*
51	Vision	int	95	Vision	03*
52	Penalties	int	75	Penalties	03*

#	CSV column	Type	Example (Messi)	Model column	Folder
53	Composure	int	96	Composure	02
54	Defending	int	91	Defending	03
55	Marking	int	32	Marking	03*
56	Standing Tackle	int	35	Standing.Tackle	03*
57	Sliding Tackle	int	24	Sliding.Tackle	03*
58	Goalkeeping	int	54	Goalkeeping	03
59	GK Diving	int	6	GK.Diving	03
60	GK Handling	int	11	GK.Handling	03
61	GK Kicking	int	15	GK.Kicking	03
62	GK Positioning	int	14	GK.Positioning	03
63	GK Reflexes	int	8	GK.Reflexes	03
64	Total Stats	int	2231	Total.Stats	03*
65	Base Stats	int	466	Base.Stats	03
66	W/F	text	4 ★	W.F	02
67	SM	text	4★	SM	02
68	A/W	text	Medium	A.W	01
69	D/W	text	Low	D.W	01
70	IR	text	5 ★	IR	03*
71	PAC	int	85	PAC	03*
72	SHO	int	92	SHO	03*
73	PAS	int	91	PAS	03*
74	DRI	int	95	DRI	03
75	DEF	int	38	DEF	03
76	PHY	int	65	PHY	03*
77	Hits	text	372	Hits	03*

3.3. Additional Columns

Six columns exist in the model that are not in the original CSV and are not created with DAX.

Table 5. Additional columns

Column	Source	Type	Notes
`Club`	Extracted from `Team...Contract` (outside the R script)	Text	681 clubs, 1,146 blank rows; folder 01
`Contract`	Extracted from `Team...Contract` (outside the R script)	Text	1,146 blank rows; folder 01

Column	Source	Type	Notes
years_at_club	R	Number	Depends on the date the script is run; folder 01
Left	R	0 / 1	1 if foot = Left; not visible in the screenshot
Striker	R	0 / 1	1 if BP = ST; not visible in the screenshot
Goalie	R	0 / 1	Always 0 because goalkeepers were excluded; folder 03

`Left` and `Striker` may sit in the cropped part of folder 03. If so, folder 03 contains 47 columns.

4. field_players Folders and DAX Code

This section walks through the 10 folders of `field_players` in order. For each folder, an object table gives the type and purpose of every item. The DAX code table that follows has three columns: No. (the folder number, then the sequence inside the folder; a folder with a single DAX object uses the folder number only), DAX name (with the object type underneath) and Code. Code is shown as the expression only, without the "Name =" prefix.

01. Player Information

Table 6. Objects in folder 01 – Player Information

Object	Object type	Source / notes
A.W	Text column	From `A/W` (attacking work rate)
BP	Text column	Best position
Club	Text column	Extracted from `Team & Contract`
Contract	Text column	Extracted from `Team & Contract`
D.W	Text column	From `D/W` (defensive work rate)
foot	Text column	Left / Right
ID	Numeric column (Σ)	Player key
Joined	Date column	Has a Date Hierarchy
Loan.Date.End	Text column	From `Loan Date End`
LongName	Text column	Full player name
Name	Text column	Short player name
Nationality	Text column	Player nationality

Object	Object type	Source / notes
No Club	Measure	Number of players without a club (DAX below)
photoUrl	Text column	Player photo URL
playerUrl	Text column	Player profile URL
Positions	Text column	All playable positions
Team...Contract	Text column	Raw text from `Team & Contract`
years_at_club	Numeric column (Σ)	Created in R; not DAX

Table 7. DAX code – folder 01 – Player Information

No.	DAX name	Code

1	**No Club**
	Measure
		`CALCULATE(`
		`  [Player Count],`
		`  FILTER(`
		`  field_players,`
		`  ISBLANK(field_players[Club]) ||`
		`  TRIM(field_players[Club]) = ""`
		`  )`
		`)`

02. Player Attributes

Sixteen numeric columns (Σ); no DAX code.

Table 8. Columns in folder 02 – Player Attributes

Acceleration	Age	Aggression	Agility
Balance	Composure	Height	Jumping
Reactions	Skill	SM	Sprint.Speed

Stamina	Strength	W.F	Weight

03. Player Performance

Forty-five numeric columns (Σ); no DAX code.

Table 9. Columns in folder 03 – Player Performance

Group	Columns
19 columns visible in the screenshot	Attacking, Ball.Control, Base.Stats, BOV, Crossing, Curve, DEF, Defending, DRI, Dribbling, Finishing, FK.Accuracy, GK.Diving, GK.Handling, GK.Kicking, GK.Positioning, GK.Reflexes, Goalie, Goalkeeping
26 columns cropped from the screenshot (inferred from the CSV)	Growth, Heading.Accuracy, Hits, Interceptions, IR, Long.Passing, Long.Shots, Marking, Mentality, Movement, PAC, PAS, Penalties, PHY, Positioning, POT, Power, Short.Passing, Shot.Power, SHO, Sliding.Tackle, Standing.Tackle, Total.Stats, Vision, Volleys, X.OVA

04. Age & Position Groups

Six calculated columns (text) that assign each player to a category.

Table 10. Objects in folder 04 – Age & Position Groups

Object	Object type	Description
Age Group	Calculated column	Age bands: 15–19, 20–24, 25–29, 30–34, 35+
OVA Group	Calculated column	Large / Medium / Small OVA using the 67th and 33rd percentiles of all players
Position Category	Calculated column	Groups BP into Goalkeeper / Defender / Midfielder / Attack
POT Group	Calculated column	High (≥ 85) / Medium (≥ 75) / Low Potential
Value Group	Calculated column	Five market-value levels (thresholds 1M / 5M / 20M / 50M €)
Wage Group	Calculated column	Five wage levels (thresholds 5K / 20K / 50K / 100K €)

Table 11. DAX code – folder 04 – Age & Position Groups

No.	DAX name	Code

4.1	**Age Group**
	Calculated column
		`SWITCH(`
		`    TRUE(),`
		`    'field_players'[Age] < 20, "15–19",`
		`    'field_players'[Age] < 25, "20–24",`
		`    'field_players'[Age] < 30, "25–29",`
		`    'field_players'[Age] < 35, "30–34",`
		`    "35+"`
		`)`

4.2	**OVA Group**
	Calculated column
		`VAR CurrentOVA =`
		`    'field_players'[X.OVA]`
		
		`VAR P33 =`
		`    PERCENTILEX.INC(`

No.	DAX name	Code
		``` ALL('field_players'), 'field_players'[X.OVA], 0.33) VAR P67 = PERCENTILEX.INC(ALL('field_players'), 'field_players'[X.OVA], 0.67) RETURN SWITCH(TRUE(), ISBLANK(CurrentOVA), BLANK(), CurrentOVA >= P67, "Large OVA", CurrentOVA >= P33, "Medium OVA", "Small OVA") ```
4.3	**Position Category** *Calculated column*	``` SWITCH(TRUE(), 'field_players'[BP] = "GK", "Goalkeeper", 'field_players'[BP] IN {"CB", "LB", "RB", "LWB", "RWB"}, "Defender", 'field_players'[BP] IN {"CDM", "CM", "CAM", "LM", "RM"}, "Midfielder", 'field_players'[BP] IN {"ST", "CF", "LW", "RW"}, "Attack", "Other") ```

No.	DAX name	Code
4.4	**POT Group** *Calculated column*	SWITCH(TRUE(), 'field_players'[POT] >= 85, "High Potential", 'field_players'[POT] >= 75, "Medium Potential", "Low Potential")
4.5	**Value Group** *Calculated column*	SWITCH(TRUE(), ISBLANK('field_players'[Value]), BLANK(), 'field_players'[Value] < 1000000, "1. Very Low", 'field_players'[Value] < 5000000, "2. Low", 'field_players'[Value] < 20000000, "3. Medium", 'field_players'[Value] < 50000000, "4. High", "5. Very High")
4.6	**Wage Group** *Calculated column*	SWITCH(TRUE(), ISBLANK('field_players'[Wage]), BLANK(), 'field_players'[Wage] < 5000, "Very Low", 'field_players'[Wage] < 20000, "Low", 'field_players'[Wage] < 50000, "Medium", 'field_players'[Wage] < 100000, "High", "Very High")

05. KPI & Summary

Four measures that provide high-level KPIs.

Table 12. Objects in folder 05 – KPI & Summary

Object	Object type	Description
Average Age	Measure	Average player age
Average OVA	Measure	Average OVA
Average POT	Measure	Average POT
Player Count	Measure	Number of player records

Table 13. DAX code – folder 05 – KPI & Summary

No.	DAX name	Code
5.1	**Average Age** *Measure*	`AVERAGE('field_players'[Age])`
5.2	**Average OVA** *Measure*	`AVERAGE('field_players'[X.OVA])`
5.3	**Average POT** *Measure*	`AVERAGE('field_players'[POT])`
5.4	**Player Count** *Measure*	`COUNTROWS('field_players')`

06. Position Benchmarks

Fifteen measures. The first twelve calculate the median by position group (Attack, Defender, Midfielder) for the club selected in the `Target Club` slicer; the last three work at the level of the best position (BP).

Table 14. Objects in folder 06 – Position Benchmarks

Object	Object type	Description
Attack Median OVA / POT / Value / Wage	4 measures	Median of the Attack group in the selected club (Value and Wage exclude zeros)
Defender Median OVA / POT / Value / Wage	4 measures	Median of the Defender group in the selected club
Midfielder Median OVA / POT / Value / Wage	4 measures	Median of the Midfielder group in the selected club
Position Median OVA	Measure	Median OVA of all players with the same BP position
Position Median POT	Measure	Median POT of all players with the same BP position
Position Rank	Measure	OVA rank within the same position (ties broken by the lower ID)

Table 15. DAX code – folder 06 – Position Benchmarks

No.	DAX name	Code

6.1	**Attack Median OVA**
	Measure
		`VAR C = SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`MEDIANX(`
		`  FILTER(`
		`  ALL(field_players),`
		`  field_players[Club] = C &&`
		`  field_players[Position Category] = "Attack"`
		`  ),`
		`  field_players[X.OVA]`
		`)`

No.	DAX name	Code

6.2	**Attack Median POT**
	Measure
		`VAR C = SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`MEDIANX(`
		`  FILTER(`
		`  ALL(field_players),`
		`  field_players[Club] = C &&`
		`  field_players[Position Category] = "Attack"`
		`  ),`
		`  field_players[POT]`
		`)`

6.3	**Attack Median Value**
	Measure
		`VAR C = SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`MEDIANX(`
		`  FILTER(`
		`  ALL(field_players),`
		`  field_players[Club] = C &&`
		`  field_players[Position Category] = "Attack" &&`
		`  field_players[Value] > 0`
		`  ),`
		`  field_players[Value]`
		`)`

No.	DAX name	Code

6.4	**Attack Median Wage**
	Measure
		`VAR C = SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`MEDIANX(`
		`  FILTER(`
		`  ALL(field_players),`
		`  field_players[Club] = C &&`
		`  field_players[Position Category] = "Attack" &&`
		`  field_players[Wage] > 0`
		`  ),`
		`  field_players[Wage]`
		`)`

6.5	**Defender Median OVA**
	Measure
		`VAR C = SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`MEDIANX(`
		`  FILTER(`
		`  ALL(field_players),`
		`  field_players[Club] = C &&`
		`  field_players[Position Category] = "Defender"`
		`  ),`
		`  field_players[X.OVA]`
		`)`

6.6	**Defender Median POT**
	Measure
		`VAR C = SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`MEDIANX(`
		`  FILTER(`
		`  ALL(field_players),`
		`  field_players[Club] = C &&`
		`  field_players[Position Category] = "Defender"`
		`  ),`
		`  field_players[POT]`
		`)`

No.	DAX name	Code

6.7	**Defender Median Value**
	Measure
		`VAR C = SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`MEDIANX(`
		`  FILTER(`
		`  ALL(field_players),`
		`  field_players[Club] = C &&`
		`  field_players[Position Category] = "Defender" &&`
		`  field_players[Value] > 0`
		`  ),`
		`  field_players[Value]`
		`)`

6.8	**Defender Median Wage**
	Measure
		`VAR C = SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`MEDIANX(`
		`  FILTER(`
		`  ALL(field_players),`
		`  field_players[Club] = C &&`
		`  field_players[Position Category] = "Defender" &&`
		`  field_players[Wage] > 0`
		`  ),`
		`  field_players[Wage]`
		`)`

No.	DAX name	Code
6.9	**Midfielder Median OVA** *Measure*	VAR C = SELECTEDVALUE('Target Club'[Club]) RETURN MEDIANX(FILTER(ALL(field_players), field_players[Club] = C && field_players[Position Category] = "Midfielder"), field_players[X.OVA])
6.10	**Midfielder Median POT** *Measure*	VAR C = SELECTEDVALUE('Target Club'[Club]) RETURN MEDIANX(FILTER(ALL(field_players), field_players[Club] = C && field_players[Position Category] = "Midfielder"), field_players[POT])
6.11	**Midfielder Median Value** *Measure*	VAR C = SELECTEDVALUE('Target Club'[Club]) RETURN MEDIANX(FILTER(ALL(field_players), field_players[Club] = C && field_players[Position Category] = "Midfielder" && field_players[Value] > 0), field_players[Value])

No.	DAX name	Code

6.12	**Midfielder Median Wage**
	Measure
		`VAR C = SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`MEDIANX(`
		`  FILTER(`
		`  ALL(field_players),`
		`  field_players[Club] = C &&`
		`  field_players[Position Category] = "Midfielder" &&`
		`  field_players[Wage] > 0`
		`  ),`
		`  field_players[Wage]`
		`)`

6.13	**Position Median OVA**
	Measure
		`VAR PositionBP =`
		`  SELECTEDVALUE(field_players[BP])`
		
		`RETURN`
		`  MEDIANX(`
		`  FILTER(`
		`  ALL(field_players),`
		`  field_players[BP] = PositionBP`
		`  && NOT ISBLANK(field_players[X.OVA])`
		`  ),`
		`  field_players[X.OVA]`
		`  )`

No.	DAX name	Code
6.14	**Position Median POT** *Measure*	VAR PositionBP = SELECTEDVALUE(field_players[BP]) RETURN MEDIANX(FILTER(ALL(field_players), field_players[BP] = PositionBP && NOT ISBLANK(field_players[POT])), field_players[POT])
6.15	**Position Rank** *Measure*	VAR CurrentPosition = SELECTEDVALUE(field_players[BP]) VAR PlayersInPosition = CALCULATETABLE(ALLSELECTED(field_players), REMOVEFILTERS(field_players[Name], field_players[ID]), field_players[BP] = CurrentPosition) RETURN RANKX(PlayersInPosition, CALCULATE(MAX(field_players[X.OVA])) * 1000000 - CALCULATE(MAX(field_players[ID])), ,

No.	DAX name	Code
		DESC, SKIP)

07. Classification

Eight measures and one calculated column. The Classification measures assign Low / Medium / High using the three position-group medians of the selected club: L is the lowest median, H is the highest and M is the remaining one (the sum of the three medians minus L and H). The Test measures return Pass or Fail.

Table 16. Objects in folder 07 – Classification

Object	Object type	Description
OVA Classification	Measure	Low / Medium / High based on OVA compared with the three position medians; OVA ≤ L returns BLANK
OVA Level	Calculated column	Elite / High / Upper-Mid / Mid / Developing (thresholds 85 / 80 / 75 / 70)
OVA Test	Measure	Pass if OVA > median OVA of the same position
POT Classification	Measure	Low / Medium / High based on POT
POT Test	Measure	Pass if POT > median POT of the same position
Value Classification	Measure	Low / Medium / High / Over Budget based on market value
Value Test	Measure	Pass if 0 < Value ≤ Club Value Budget
Wage Classification	Measure	Low / Medium / High / Over Budget based on wage
Wage Test	Measure	Pass if 0 < Wage ≤ Club Wage Budget

Table 17. DAX code – folder 07 – Classification

No.	DAX name	Code

7.1	**OVA Classification**
	Measure
		`VAR O = SELECTEDVALUE(field_players[X.OVA])`
		`VAR L = MIN(`
		`  [Attack Median OVA],`
		`  MIN([Midfielder Median OVA], [Defender Median OVA])`
		`)`
		`VAR H = MAX(`

No.	DAX name	Code
		[Attack Median OVA], MAX([Midfielder Median OVA], [Defender Median OVA])) VAR M = [Attack Median OVA] + [Midfielder Median OVA] + [Defender Median OVA]- L - H RETURN SWITCH(TRUE(), ISBLANK(O), BLANK(), O <= L, BLANK(), O < M, "Low", O < H, "Medium", "High")
7.2	**OVA Level** *Calculated column*	SWITCH(TRUE(), 'field_players'[X.OVA] >= 85, "Elite", 'field_players'[X.OVA] >= 80, "High", 'field_players'[X.OVA] >= 75, "Upper-Mid", 'field_players'[X.OVA] >= 70, "Mid", "Developing")
7.3	**OVA Test** *Measure*	IF(SELECTEDVALUE(field_players[X.OVA]) > [Position Median OVA], "Pass", "Fail")

No.	DAX name	Code
7.4	**POT Classification** *Measure*	VAR P = SELECTEDVALUE(field_players[POT]) VAR L = MIN([Attack Median POT], MIN([Midfielder Median POT], [Defender Median POT])) VAR H = MAX([Attack Median POT], MAX([Midfielder Median POT], [Defender Median POT])) VAR M = [Attack Median POT] + [Midfielder Median POT] + [Defender Median POT] - L - H RETURN SWITCH(TRUE(), ISBLANK(P), BLANK(), ISBLANK(L) || ISBLANK(H), BLANK(), P < M, "Low", P < H, "Medium",

No.	DAX name	Code
		"High")
7.5	**POT Test** *Measure*	IF(SELECTEDVALUE(field_players[POT]) > [Position Median POT], "Pass", "Fail")
7.6	**Value Classification** *Measure*	VAR V = SELECTEDVALUE(field_players[Value]) VAR L = MIN([Attack Median Value], MIN([Midfielder Median Value], [Defender Median Value])) VAR H = MAX([Attack Median Value], MAX([Midfielder Median Value], [Defender Median Value])) VAR M = [Attack Median Value] + [Midfielder Median Value] +

No.	DAX name	Code
		[Defender Median Value] - L - H RETURN SWITCH(TRUE(), ISBLANK(V) || V <= 0, BLANK(), ISBLANK(L) || ISBLANK(H), BLANK(), V <= L, "Low", V <= M, "Medium", V <= H, "High", "Over Budget")
7.7	**Value Test** *Measure*	VAR V = SELECTEDVALUE(field_players[Value]) RETURN IF(V > 0 && V <= [Club Value Budget], "Pass", "Fail")
7.8	**Wage Classification** *Measure*	VAR W = SELECTEDVALUE(field_players[Wage]) VAR L = MIN([Attack Median Wage], MIN([Midfielder Median Wage], [Defender Median Wage])) VAR H =

No.	DAX name	Code
		MAX([Attack Median Wage], MAX([Midfielder Median Wage], [Defender Median Wage])) VAR M = [Attack Median Wage] + [Midfielder Median Wage] + [Defender Median Wage] - L - H RETURN SWITCH(TRUE(), ISBLANK(W) || W <= 0, BLANK(), ISBLANK(L) || ISBLANK(H), BLANK(), W <= L, "Low", W <= M, "Medium", W <= H, "High", "Over Budget")
7.9	**Wage Test** *Measure*	VAR W = SELECTEDVALUE(field_players[Wage]) RETURN IF(W > 0 && W <= [Club Wage Budget], "Pass", "Fail")

08. Recruitment Scoring

Three measures that filter eligible players, calculate a score out of 100 (OVA 40 + POT 30 + Wage 15 + Value 15) and assign a recruitment priority level.

Table 18. Objects in folder 08 – Recruitment Scoring

Object	Object type	Description
Recruitment Filter	Measure	1 if OVA is greater than the lowest median OVA of the club, otherwise 0
Recruitment Priority	Measure	Score up to 100: OVA 40 + POT 30 + Wage 15 + Value 15; BLANK if the player fails the filter
Recruitment Priority Level	Measure	Top (≥ 80) / High (≥ 65) / Medium (≥ 50) / Low Priority

Table 19. DAX code – folder 08 – Recruitment Scoring

No.	DAX name	Code

8.1	**Recruitment Filter**
	Measure
		`VAR O = SELECTEDVALUE(field_players[X.OVA])`
		
		`VAR L =`
		`  MIN(`
		`  [Attack Median OVA],`
		`  MIN(`
		`  [Midfielder Median OVA],`
		`  [Defender Median OVA]`
		`  )`
		`  )`
		
		`RETURN`
		`IF(`
		`  NOT ISBLANK(O) &&`
		`  NOT ISBLANK(L) &&`
		`  O > L,`

No.	DAX name	Code
		1, 0)
8.2	**Recruitment Priority** *Measure*	VAR Eligible = [Recruitment Filter] VAR OVA_Score = SWITCH([OVA Classification], "High", 40, "Medium", 30, "Low", 20, 0) VAR POT_Score = SWITCH([POT Classification], "High", 30, "Medium", 20, "Low", 10, 0) VAR Wage_Score = SWITCH([Wage Classification], "Low", 15, "Medium", 10, "High", 5, "Over Budget", 0, 0

No.	DAX name	Code
		```) VAR Value_Score = SWITCH([Value Classification], "Low", 15, "Medium", 10, "High", 5, "Over Budget", 0, 0) RETURN IF(Eligible <> 1, BLANK(), OVA_Score + POT_Score + Wage_Score + Value_Score) ```

No.	DAX name	Code

8.3	**Recruitment Priority Level**
	Measure
		`VAR Score = [Recruitment Priority]`
		
		`RETURN`
		`SWITCH(`
		`    TRUE(),`
		`    ISBLANK(Score), BLANK(),`
		`    Score >= 80, "Top Priority",`
		`    Score >= 65, "High Priority",`
		`    Score >= 50, "Medium Priority",`
		`    "Low Priority"`
		`)`

09. Financial Analysis

Fifteen items: 6 measures, 6 calculated columns (numeric) and 3 original columns (`Release.Clause`, `Value`, `Wage`; no DAX). The six numeric calculated columns show a different icon from measures in the field list, so they are classified as columns.

Table 20. Objects in folder 09 – Financial Analysis

Object	Object type	Description
Average Value	Calculated column (numeric)	Average market value
Average Wage	Measure	Average wage
Average Weight (kg)	Calculated column (numeric)	Average weight
Club Median Value	Measure	Median market value of the selected club
Club Median Wage	Measure	Median wage of the selected club
Club Value Budget	Measure	75th percentile of market value in the club
Club Wage Budget	Measure	75th percentile of wage in the club
Potential Gap	Calculated column (numeric)	POT minus OVA
Release.Clause	Original column	Release clause amount (€)
Total Market Value	Measure	Total market value
Value	Original column	Market value (€)
Value per OVA	Calculated column (numeric)	Market value per OVA point
Wage	Original column	Weekly wage (€)

Object	Object type	Description
Wage per OVA	Calculated column (numeric)	Wage per OVA point
Young Player %	Calculated column (numeric)	Share of players under 25

Table 21. DAX code – folder 09 – Financial Analysis

No.	DAX name	Code
9.1	**Average Value** *Calculated column (numeric)*	`Average('field_players'[Value])`
9.2	**Average Wage** *Measure*	`Average('field_players'[Wage])`
9.3	**Average Weight (kg)** *Calculated column (numeric)*	`AVERAGE(field_players[Weight])`

9.4	**Club Median Value** *Measure*	`VAR SelectedClub =`
		`  SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`  MEDIANX(`
		`  FILTER(`
		`  ALL(field_players),`
		`  field_players[Club] = SelectedClub`
		`  && field_players[Value] > 0`
		`  ),`
		`  field_players[Value]`
		`  )`

No.	DAX name	Code

9.5	**Club Median Wage**
	Measure
		`VAR SelectedClub =`
		`    SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`    MEDIANX(`
		`        FILTER(`
		`            ALL(field_players),`
		`            field_players[Club] = SelectedClub`
		`                && field_players[Wage] > 0`
		`        ),`
		`        field_players[Wage]`
		`    )`

9.6	**Club Value Budget**
	Measure
		`VAR SelectedClub =`
		`    SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`    PERCENTILEX.INC(`
		`        FILTER(`
		`            ALL(field_players),`
		`            field_players[Club] = SelectedClub`
		`                && field_players[Value] > 0`
		`        ),`
		`        field_players[Value],`
		`        0.75`
		`    )`

No.	DAX name	Code

9.7	**Club Wage Budget**
	Measure
		`VAR SelectedClub =`
		`    SELECTEDVALUE('Target Club'[Club])`
		`RETURN`
		`    PERCENTILEX.INC(`
		`        FILTER(`
		`            ALL(field_players),`
		`            field_players[Club] = SelectedClub`
		`                && field_players[Wage] > 0`
		`        ),`
		`        field_players[Wage],`
		`        0.75`
		`    )`

9.8	**Potential Gap** *Calculated column (numeric)*	`'field_players'[POT] - 'field_players'[X.OVA]`
9.9	**Total Market Value** *Measure*	`SUM('field_players'[Value])`
9.10	**Value per OVA** *Calculated column (numeric)*	`DIVIDE('field_players'[Value], 'field_players'[X.OVA])`
9.11	**Wage per OVA** *Calculated column (numeric)*	`DIVIDE('field_players'[Wage], 'field_players'[X.OVA])`

No.	DAX name	Code

9.12	**Young Player %**
	Calculated column (numeric)
		`DIVIDE(`
		`  CALCULATE(`
		`  DISTINCTCOUNT(field_players[Name]),`
		`  field_players[Age] < 25`
		`  ),`
		`  DISTINCTCOUNT(field_players[Name])`
		`)`

10. Squad Selection

Two objects support squad selection: a measure that flags the starting players and the calculated table used by the club slicer.

Table 22. Objects in folder 10 – Squad Selection

Object	Object type	Description
Show in Starting XI	Measure	1 if the player is in the top N of the position (CB 2; LB, RB, CDM, CM, CAM, LW, ST, RW 1 each), otherwise 0
Target Club	Calculated table	List of clubs used in the slicer: table `Target Club`, column `Club`

Table 23. DAX code – folder 10 – Squad Selection

No.	DAX name	Code

10.1	**Show in Starting XI**
	Measure
		`VAR CurrentPosition =`
		`  SELECTEDVALUE(field_players[BP])`
		
		`VAR RequiredPlayers =`
		`  SWITCH(`
		`  CurrentPosition,`
		`  "CB", 2,`
		`  "LB", 1,`
		`  "RB", 1,`
		`  "CDM", 1,`
		`  "CM", 1,`
		`  "CAM", 1,`
		`  "LW", 1,`
		`  "ST", 1,`
		`  "RW", 1,`
		`  0`
		`  )`
		
		`RETURN`

No.	DAX name	Code
		IF([Position Rank] <= RequiredPlayers, 1, 0)
10.2	**Target Club** *Calculated table*	DISTINCT(field_players[Club])