← All products

HANDHELD SERIES

XH-100 Biometric Handheld Terminal

A 5-inch Android terminal built around identity: NXP NFC, full-symbology 2D scanning and optional fingerprint capture modules, so one unit works as an NFC fingerprint scanner instead of two devices carried together. It weighs 400 grams and runs a full shift on one charge.



Identity-first design — fingerprint (FAP10/20/30), NFC and ID workflows on one device.

Reads everything — 1D, 2D, stacked, postal codes and even OCR (optional).

5000 mAh for >8 h continuous work, >500 h sleep standby.

Dual SIM + full-band LTE for field deployments anywhere.

Black or white housing, OEM/ODM configured at the factory.

Specifications

Design	5-inch handheld terminal, 188 × 80 × 19.8 mm, 400 g (with battery), black / white
Keys	Scanner trigger, power, volume+, volume−
OS	Android 10.0
CPU	MTK6750 64-bit octa-core, 12 nm, up to 1.5 GHz
RAM / Storage	2 GB + 16 GB (4 GB + 64 GB / 6 GB + 64 GB optional); Micro SD up to 128 GB
Display	5-inch HD 720 × 1280, capacitive multi-touch
Camera	Front 5 MP auto-focus; rear 13 MP PDAF with flash

Battery	Built-in 3.85 V / 5,000 mAh Li-ion; >8 h continuous work, >12 h bright-screen standby, >500 h sleep
Charging / Ports	DC or Type-C charging, USB-A port, charging indicator; dual SIM (or SIM + TF)
Wireless	Dual-band WiFi 2.4G/5.8G (802.11 a/b/g/n); Bluetooth 5.0 LE; LTE-FDD B1/B3/B5/B7/B8/B20, LTE-TDD B38/B39/B40/B41, WCDMA B1/B2/B5/B8, GSM 850/900/1800/1900; GPS + GLONASS
NFC	NXP chip, ISO/IEC 14443 A & B, MiFare S50/S70, 0–5 cm (tag dependent)
Barcode	2D imager: UPC/EAN/JAN, GS1 DataBar, Code 39/128/32/93, Codabar, ITF, MSI, PDF417, MicroPDF417, GS1 Composite, Aztec, Data Matrix, QR, Micro QR, MaxiCode, Han Xin, postal codes; OCR optional (OCR-A/B, E13B MICR)
Fingerprint: FAP10 option	Integrated module; confirm the exact model, active area and output image dimensions.
Fingerprint: FAP20 option	Optical sensor; confirm the exact model, active area and output image dimensions.
Fingerprint: FAP30 option	Optical sensor; confirm the exact model, active area and output image dimensions.
Fingerprint integration	Select one optional module at order stage. Sampling, greyscale, SDK formats and any required certification must be confirmed for that hardware and software configuration.
Environment	−10 °C to +50 °C operating (storage −20 °C to +60 °C); <90 % RH; 86–110 kPa. Accessories: box, charger (CN/EU/US/UK plugs optional), DC and Type-C cables

Where the XH-100 fits

Civil identity and enrollment: optional fingerprint capture, compatible NFC cards and 2D document barcodes support identity workflows. Confirm the sensor configuration, required image format and application compatibility for your project.

Retail, logistics and attendance: full 2D scanning handles shelf labels and mobile payments codes, while dual SIM keeps field staff online across carriers.

Field services: 5,000 mAh covers long routes, and GPS/GLONASS stamps every transaction with location.

OEM / ODM, factory direct

Module mix (fingerprint type, NFC configuration), RAM/storage tier, housing colour, boot logo and preloaded software are all configured at the factory. Chargers ship with Chinese, European, American or British plugs — tell us your market.

Related guides

Compare FAP 10, FAP 20 and FAP 30 capture requirements, or review a bank card issuance approval workflow built around fingerprint capture and application permissions.

Ordering information

MOQ is 2 units, a sample is built in about 3 days and mass production runs about 25 days. Figures move when the XH-100 leaves its standard build — a different fingerprint module, ID card reading or housing colour — and those are quoted in writing first.

MOQ	2 units. One for capture-quality testing against your enrolment workflow and one for the SDK integration bench.
Sample	About 3 days covers build and dispatch of a sample, which is then checked against the acceptance criteria agreed with you, including capture quality from the fingerprint module fitted, before mass production starts.
Lead time	About 25 days from sample approval to shipment for the configuration and quantity on your order. Biometric module verification — including any certification your destination market requires — is scheduled before the first sample is built.
SDK and documentation	API and SDK support for the fingerprint module, NFC reader and ID card reader on your build, plus the agreed specification sheet. Image and template formats — ISO, ANSI or your own — are confirmed before the order is placed.
Certification	The capacitive fingerprint module holds Ministry of Public Security certification where used. For programmes that specify FBI profiles, the Suprema and Idemia modules are certified to FBI PIV-071006 and Appendix F at FAP20 and FAP30 and are listed on the FBI Certified Products List. The listing belongs to the tested module, firmware and host configuration, so confirm the module when ordering. GMS certification applies where the specification lists it, and certification your destination market adds is agreed before production.
Packaging	Retail box contents and carton dimensions are provided with the confirmed configuration and quotation; pallet quantities and incoterms are agreed with the order. Calibration cards and a cleaning kit for the fingerprint window can be added per unit.

Request a quote

Send the capture modules and certification you need, the quantity, the destination market and your target date — we reply with the configuration, the sample plan and the price in writing.

The commercial questions — order size, timing, warranty and shipping — are answered on the FAQ page.