← All products

HANDHELD SERIES

XH-200 6-Inch Android Handheld PDA

A 282-gram Android 12 terminal for warehouses, delivery rounds and retail floors that scan all day. The screen is big enough to read a full dispatch table, and the battery swaps between shifts.



6-inch-class 1440 × 720 screen with Corning third-generation tempered glass.

Removable 5100 mAh pack: swap it instead of waiting on a charger.

Your choice of scan engine: Honeywell HS7, Zebra SE4710 or NLS-CM60.

Android 12 on MTK6765 octa-core 2.0 GHz, 3 GB + 32 GB standard.

Survives a 150 cm drop while powered on, and works from −20 °C to 55 °C.

Specifications

Design	170 × 83 × 15.8 mm, approx. 282 g with battery, black or white housing
Display	5.99-inch, 1440 × 720, capacitive multi-touch, Corning third-generation tempered glass
Cameras	Front 5.0 MP; rear 13 MP auto-focus with LED flash
Audio	Built-in waterproof speaker 8 Ω / 0.8 W; microphone sensitivity −42 dB, output impedance 2.2 kΩ
Battery	Removable Li-polymer 3.7 V / 5100 mAh; approx. 8 hours active use, standby over 300 hours
OS	Android 12.0
CPU	MTK6765 octa-core, up to 2.0 GHz

Memory	3 GB RAM + 32 GB storage; 4 GB + 64 GB optional
NFC	Built-in, ISO/IEC 14443A, read distance 1–3 cm
Wireless	Dual-band WiFi 802.11 a/b/g/n/ac (2.4 G + 5 G); Bluetooth 5.0 BLE
Cellular	LTE B1/B3/B5/B7/B8/B20/B38/B39/B40/B41; WCDMA B1/B2/B5/B8; GSM 2/3/5/8
Positioning	Beidou, GPS and GLONASS
Barcode scanning (optional)	Honeywell HS7, Zebra SE4710 or NLS-CM60 2D imager; 5 mil optical resolution, 5 scans/second; PDF417, MicroPDF417, Data Matrix (incl. inverse), MaxiCode, QR Code, Micro QR (incl. inverse), Aztec (incl. inverse), Han Xin (incl. inverse)
Environment	Drop 150 cm while powered on; operating −20 °C to +55 °C; storage −20 °C to +60 °C; humidity 95 % non-condensing

Where the XH-200 fits

Warehousing and picking: 5.99 inches is enough to show a full pick list without scrolling, and the removable battery means a two-shift operation never waits for a charge cycle.

Retail floors and stock counts: NFC handles contactless cards and loyalty passes at 1–3 cm, while the optional 2D imager reads shelf labels, QR payment codes and damaged printed barcodes.

Delivery and field rounds: full-band LTE plus Beidou/GPS/GLONASS keeps drivers connected and every scan stamped with a location.

Cold-chain and industrial sites: the unit keeps working down to −20 °C and shrugs off a 150 cm drop onto concrete while powered on.

OEM / ODM, factory direct

Scan engine choice, NFC configuration, memory tier, colour, boot logo and pre-installed apps are all decided before the line starts. LTE bands can be matched to your target market on production orders, and packaging, labels and documentation can follow your own brand.

Related guides

Our industrial handheld PDA guide covers scan engine and battery choices, and the warehouse rollout plan shows how to stage, provision and support a fleet.

Ordering information

MOQ is 2 units, a sample is built in about 3 days and mass production runs about 25 days. Figures move when the XH-200 leaves its standard build (different scan engine, UHF RFID sled or hand strap); those variations are quoted in writing first.

MOQ	2 units. One out on the delivery round and one on the bench for scanner and RFID configuration work.

Sample	Sample build and shipment take about 3 days, then the unit is checked against the acceptance criteria agreed with you, scan engine or RFID sled included, before mass production starts.
Lead time	About 25 days from sample approval to shipment for the configuration and quantity on your order. Scanner or UHF RFID verification for your region is written into the schedule before the first sample is built.
SDK and documentation	API and SDK support for the modules fitted to your build (scan engine, UHF RFID or NFC), plus the agreed specification sheet. EPC output and scan behaviour are confirmed before the order is placed.
Certification	The Android 12 build carries GMS certification, and the UHF RFID module is supplied to the regional frequency plan you nominate instead of a default band. Approvals your market adds are agreed before production.
Packaging	Retail box contents and carton dimensions are provided with the confirmed configuration and quotation; pallet quantities and incoterms are agreed with the order. Straps, holsters and spare packs are packed per driver or per depot if you give us the list.

Request a quote

Send the scanner or RFID module, the quantity, the destination market and your target date. We reply with the configuration, the sample plan and a written price.

The commercial questions — order size, timing, warranty and shipping — are answered on the FAQ page.