← All products

TABLET SERIES

XH-300 10.1-Inch Industrial Tablet

A full-size 1920 × 1200 screen for forms, drawings and dashboards, powered by a 10,000 mAh pack that holds a shift — with room inside for ID reading, face verification or a 2D scan engine.



10.1-inch 1920 × 1200 display with Corning third-generation tempered glass.
Non-removable 3.7 V / 10,000 mAh battery, roughly 8 hours of active use.
MTK6765 octa-core up to 2.3 GHz on Android 12, 3 GB + 32 GB standard.
Optional contactless national e-ID and e-passport reader, Chinese second-generation ID card reader, face recognition with liveness detection or NLS-N1 2D imager.
Dual waterproof speakers, USB 2.0 plus Type-C OTG, TF card to 128 GB.

Specifications

Design	248 × 170 × 17.8 mm, approx. 890 g, black housing
Display	10.1-inch, 1920 × 1200, capacitive multi-touch, Corning third-generation tempered glass
Cameras	Rear 13 MP auto-focus with LED flash (standard); front 5.0 MP (optional)
Audio	Two built-in waterproof speakers 8 Ω / 0.8 W; microphone sensitivity −42 dB, output impedance 2.2 kΩ
Battery	Non-removable Li-polymer 3.7 V / 10,000 mAh; approx. 8 hours active use, standby over 300 hours
OS	Android 12.0

CPU	MTK6765 octa-core, up to 2.3 GHz
Memory	3 GB + 32 GB standard; 4 GB + 64 GB or 6 GB + 128 GB optional; TF card up to 128 GB
SIM and storage	SIM slot covering China Mobile, Telecom and Unicom networks; TF card slot up to 128 GB
Ports and keys	USB 2.0 × 1, Type-C OTG × 1; power key × 1, volume keys × 2, assignable function keys × 3
Wireless	Dual-band WiFi 802.11 a/b/g/n/ac (2.4 G + 5 G); Bluetooth 5.0 BLE
Cellular	LTE B1/B3/B5/B7/B8/B20/B38/B39/B40/B41; WCDMA B1/B2/B5/B8; GSM 2/3/5/8
Positioning	Beidou, GPS and GLONASS
Barcode scanning (optional)	NLS-N1 2D imager; 5 mil optical resolution, 5 scans/second; PDF417, MicroPDF417, Data Matrix (incl. inverse), MaxiCode, QR Code, Micro QR (incl. inverse), Aztec (incl. inverse), Han Xin (incl. inverse)
Identity modules (optional)	Contactless national e-ID and e-passport reader (ISO/IEC 14443 Type A/B, ICAO 9303 MRZ and NFC chip, PSAM/SAM slot); Chinese second-generation resident ID card reader as an option, offline, on the Ministry of Public Security decoder module; face recognition with liveness detection, 0.2–1.5 m working distance, ≥99.72% verification accuracy, ≤1 s recognition
Ingress protection	IP65 — dust-tight and protected against water jets
Environment	Six-face rolling test to 1,000 cycles; storage −20 °C to +60 °C; humidity 95 % non-condensing

Where the XH-300 fits

Field inspection and maintenance: the 1920 × 1200 panel shows a full checklist or schematic without scrolling, and the 10,000 mAh pack covers a working day away from a socket.

Identity counters and registration desks: optional ID card reading plus face verification turns the tablet into a single-counter enrolment station, and both modules run offline so rural sites are not blocked by network quality.

Warehouse and production supervision: add the NLS-N1 2D imager for bin labels and part numbers, and three assignable keys give operators one-handed shortcuts for the actions they repeat most.

Digital signage and kiosks: with dual speakers, Type-C OTG and a TF slot up to 128 GB, it also works as a fixed information or self-service terminal.

OEM / ODM, factory direct

Identity modules, scan engine, memory tier, LTE bands, boot logo, pre-installed applications and packaging are all decided before the line starts. Tell us the target country and we will match the radio bands and charger plug to that market.

Related guides

For fleet planning, check Android version support and long-term supply, then compare configurations in our industrial tablet buying guide.

Ordering information

MOQ is 2 units, a sample is built in about 3 days and mass production runs about 25 days. Figures move when the XH-300 leaves its standard build (different identity module, memory tier or boot logo); any change is quoted in writing before you commit.

MOQ	2 units. Typically one configured as the counter unit and one kept as the firmware reference while your integration is built.
Sample	About 3 days from build to dispatch for a sample, which is then checked against the acceptance criteria agreed with you, including the identity or scan module fitted, before mass production starts.
Lead time	About 25 days from sample approval to shipment for the configuration and quantity on your order. Module-specific verification (identity or scan module, plus any certification your market requires) is scheduled before the first sample is built.
SDK and documentation	API and SDK support for the modules fitted to your build (ID card reader, face verification or 2D imager), plus the agreed specification sheet. Output formats are confirmed before the order is placed.
Certification	The Android 12 build carries GMS certification. Where the second-generation resident ID card reader is fitted, its decoder module is Ministry of Public Security certified. Any certification your market adds is agreed before production so the test plan fits the schedule.
Packaging	Retail box contents and carton dimensions are provided with the confirmed configuration and quotation; pallet quantities and incoterms are agreed with the order. Module samples and printed quick-start cards can be packed per destination.

Request a quote

Send the identity or scan module you need, the quantity, the destination market and your target date. We reply with the configuration, the sample plan and a written price.

The commercial questions — order size, timing, warranty and shipping — are answered on the FAQ page.