← All products

TABLET SERIES

XH-400 10.1-Inch Mobile Biometric Tablet

A 10.1-inch mobile biometric Android tablet sealed to IP65, with a native RJ45 port, two circular aviation connectors for power and serial devices, optional fingerprint sensor and ID card reader, and a 10,000 mAh pack — a 10-inch Android tablet that works on benches, vehicles and kiosks where WiFi cannot be trusted and dust or water spray is part of the day.



Sealed to IP65: dust tight and protected against water jets.

Wired RJ45 Ethernet and two circular aviation connectors, plus USB-A, USB Type-C and a DC 3.5 mm charging port.

10,000 mAh rechargeable polymer battery with a charging indicator.

MTK6765 64-bit octa-core up to 2.3 GHz, Android 10 or 11 with GMS certification.

Optional NFC, ID card reader, fingerprint sensor or 2D barcode engine.

Specifications

Design	300 × 183 × 18 mm, 880 g, black or white housing
Ingress protection	IP65 — dust tight, protected against low-pressure water jets
Display	10.1-inch HD IPS, 800 × 1280 standard, 1920 × 1200 optional; COF touchscreen with Goodix GT9110 touch IC, optional Corning glass
Platform	MTK6765 64-bit octa-core, 12 nm process, up to 2.3 GHz
Operating system	Android 10.0 or Android 11.0 with GMS certification
Memory	4 GB RAM, up to 6 GB; 64 GB storage (32 GB or 128 GB optional); SD/TF card up to 512 GB
Cameras	Front 5 MP; rear 13 MP with autofocus and dual-tone flash

Battery and power	10,000 mAh rechargeable polymer battery, DC or USB Type-C charging with charging indicator; adapter input AC 100–240 V 50–60 Hz, output DC 5 V 2 A
Wireless	Dual-band WiFi 2.4 GHz + 5 GHz, 802.11 a/b/g/n/ac; Bluetooth 5.0; FM radio
Cellular	GSM 850/900/1800/1900 MHz; WCDMA Bands 1/2/4/5/8; TD-SCDMA Bands 34/39; CDMA2000; TDD-LTE Bands 34/38/39/40/41; FDD-LTE Bands 1/2/3/4/5/6/7/8/28
Positioning	BeiDou, Galileo, GPS and GLONASS
Sensors	Gravity, orientation, accelerometer, gyroscope, geomagnetic sensor, compass
Audio	Dual 0.8 W speakers; dual microphones with noise reduction
External interfaces	RJ45 Ethernet × 1, circular aviation connector × 2 (pinout per project), USB-A × 1, USB Type-C × 1, DC 3.5 mm charging port × 1, reset pinhole × 1, hybrid SIM/TF tray × 1 (two of three cards at a time), microphones × 2
Internal interfaces	USB × 3, TTL serial × 2, GPIO × 3, SPI × 1, 2D scan engine FPC × 1 — for integrators building custom peripherals
Optional modules	NFC ST21NFC at 13.56 MHz (ISO/IEC 14443 Type A/B, ISO/IEC 15693); contactless national e-ID and e-passport reading (ISO/IEC 14443 Type A/B, ICAO 9303 MRZ and NFC chip, PSAM/SAM slot); Chinese second-generation ID card reader as an option, offline; fingerprint FAP10 capacitive or FAP20/FAP30 optical from Suprema (BioMini Slim 2 and Slim 3), Idemia, Integrated Biometrics (LES) or HID Global (Lumidigm, EikonTouch), FBI PIV-071006 and Appendix F certified at FAP20 and FAP30; rear 2D scan engine from Newland N1/3296/3596, Honeywell N3680 or Zebra 4710
Packaging	Contents: tablet, 5 V / 2 A charger, user manual, data cable. Retail box 390 × 215 × 50 mm, packaged unit 1.3 kg; outer carton 410 × 280 × 415 mm, gross weight 13.8 kg

Where the XH-400 fits

Production lines and fixed workstations: the native RJ45 port keeps data flowing where WiFi is congested, and IP65 sealing handles the dust and wash-down that a production floor produces.

Vehicles and forklifts: 880 g with a 300 × 183 mm body mounts cleanly on a RAM arm, and the 10,000 mAh pack plus DC charging suits long shifts on a vehicle power supply.

Identity and enrolment counters: combine the offline ID card reader with a fingerprint sensor and face-capable camera work flow, and the tablet becomes a single-window registration station that does not depend on network quality.

Warehouse receiving and dispatch: add the rear 2D engine from Newland, Honeywell or Zebra and use the same unit for bin labels, waybills and returns.

Integrators: internal USB, TTL serial, GPIO and SPI headers are exposed inside the housing, so custom peripherals can be wired without external adapters.

OEM / ODM, factory direct

Module selection, memory tier, display resolution, Android version, housing colour, boot logo, pre-installed applications and packaging are all decided before the line starts. We can also match LTE bands and charger plugs to your

destination market.

Fingerprint module selection

Fingerprint capture is optional. Confirm the selected sensor model, active area, SDK output formats and any required certification for your hardware and software configuration. Our FAP 10, FAP 20 and FAP 30 guide explains the single-finger capture profiles and the questions to check before ordering. For enrolment at temporary or mobile stations, see our mobile voter registration guide.

Ordering information

MOQ is 2 units, a sample is built in about 3 days and mass production runs about 25 days. Figures move when the XH-400 leaves its standard build (different biometric module, RAM tier or vehicle mount); those variations are quoted in writing before you order.

MOQ	2 units. One mounted at a fixed workstation and one for the forklift or vehicle trial, the two installations that usually need checking first.
Sample	Sample build and dispatch take about 3 days, after which the tablet is checked against the acceptance criteria agreed with you, biometric module and mount fit included, before mass production starts.
Lead time	About 25 days from sample approval to shipment for the configuration and quantity on your order. Workstation and vehicle installation checks are part of the written schedule issued before the first sample is built.
SDK and documentation	API and SDK support for the modules fitted to your build (biometric capture, NFC or 2D imager), plus the agreed specification sheet. Integration formats for your workstation software are confirmed before the order is placed.
Certification	The Android 10 and Android 11 builds both ship with GMS certification. The fingerprint modules from Suprema, Idemia, Integrated Biometrics and HID Global are certified to FBI PIV-071006 and Appendix F at FAP20 and FAP30 and are listed on the FBI Certified Products List. The listing belongs to the tested module, firmware and host configuration, so confirm the exact module when ordering. The capacitive module also holds Ministry of Public Security certification where fitted. Market-specific approvals are agreed before production so the test plan fits the schedule.
Packaging	Retail box contents and carton dimensions are in the specification above; pallet quantities and incoterms are agreed with the order. Mounting hardware for workstations or vehicles is packed to match the installation plan.

Request a quote

Send the installation type, the modules you need, the quantity and your target date. We reply with the configuration, the sample plan and a written price.

The commercial questions — order size, timing, warranty and shipping — are answered on the FAQ page.

Related reading: Why the XH-400 Uses Circular Aviation Connectors