TABLET SERIES

XH-500 10.1-Inch Rugged Android Tablet

A 10.1-inch rugged Android tablet with a 450 nit IPS display, MTK8788 processor, 10000 mAh battery, built-in NFC and 4G connectivity. Configure optional data capture modules and interfaces for your field or workplace application.



Android 12 and 4 GB + 64 GB as standard; Android 13 and larger memory configurations are optional.

1200 × 1920 IPS display with 10-point capacitive touch.

Built-in 13.56 MHz NFC, WiFi, Bluetooth 5.0 and 4G.

Optional barcode, fingerprint, ID card, RFID and biometric camera modules.

Optional RJ45 10/100 Mbps Ethernet and additional connectors.

Display, platform and battery

Dimensions / weight	292 × 171.5 × 20 mm; 1.1 kg; black housing
Display	10.1-inch IPS, 16:10, 1200 × 1920 pixels, 450 nit brightness
Touch panel	10-point capacitive touchscreen
CPU / GPU	MTK8788, 2.0 GHz; Arm Mali-G73 MP3
Operating system	Android 12 standard; Android 13 optional
Memory / storage	4 GB LPDDR3 + 64 GB eMMC standard; 6 GB + 128 GB or 8 GB + 128 GB optional; TF card up to 512 GB
Cameras	Front 5 MP and rear 13 MP standard; front 8 MP and rear 20 MP optional
Battery	Built-in 3.8 V / 10000 mAh rechargeable battery

Listed video playback endurance	10 hours under the stated test conditions: 70% volume, 70% screen brightness and 1080 HD video playback. Runtime varies with applications, radios, modules and brightness.
Audio	Two 8 Ω / 1 W speakers; built-in microphone; 3.5 mm headphone jack
Keys	Power, volume up/down, PTT, F1 and F2
Sensors	G-sensor, ambient light sensor, geomagnetic sensor and gyroscope

Standard connectivity and interfaces

WiFi	802.11 a/b/g/n/ac, dual-band 2.4 GHz + 5.8 GHz
Bluetooth	Bluetooth 5.0 BLE, Class 1; listed transmission distance 10 m
Cellular	4G LTE; WCDMA Bands 1/2/4/5/8; TD-SCDMA Bands 34/39; TDD-LTE Bands 34/38/39/40/41; FDD-LTE Bands 1/2/3/4/5/7/8/12/17/19/20/26/28a/28b
Positioning	BeiDou, GPS and GLONASS
NFC (standard)	13.56 MHz; ISO/IEC 14443 A/B, 15693, 18092 and MIFARE protocols; listed reading distance 2–4 cm. Confirm compatibility with your cards and application.
SIM / TF slots	One SIM slot standard; dual SIM optional. One TF slot supports cards up to 512 GB.
USB	USB 2.0: one Type-A and one Type-C port
Power input	DC 5 V / 3 A through a 3.5 mm DC jack

Optional modules and interfaces

The following modules are optional. Confirm the required combination, interface layout and application compatibility at order stage.

Barcode scanning	Optional Newland or Zebra scan engine; confirm the exact engine and supported symbologies for your configuration.
Fingerprint capture	Optional capacitive or optical fingerprint module; confirm the selected sensor, SDK and required output formats.
ID card recognition	Optional ID card recognition module; confirm document types and software compatibility.
RFID	Optional LF 125 kHz / 134 kHz, HF 13.56 MHz or UHF module. Select the band and reader for your tags; these options are separate from the standard NFC specification.
Biometric camera modules	Optional binocular liveness recognition or iris recognition; confirm module and application requirements.
Positioning / field modules	Optional high-precision positioning, BDS-3, barometric altitude sensing and LoRa. Confirm the required module combination.

Wired Ethernet	Optional RJ45 10/100 Mbps port; Ethernet is not part of the standard port configuration.
Other interfaces	Optional aviation connector, SMA connector, micro USB and PSAM card slot. Confirm interface availability and layout at order stage.

Operating conditions and accessories

Ingress protection	IP67 — dust-tight and sealed against temporary immersion
Listed drop condition	1.2 m drop onto a wooden floor with the tablet powered on
Operating temperature	−20 °C to +60 °C
Storage temperature	−40 °C to +70 °C
Humidity	95%, non-condensing
Standard accessories	Type-C cable, operating instructions, wrist strap and power adapter
Power adapter	Input AC 100–240 V, 50/60 Hz; output DC 5 V / 3 A; CN, US, EU or AU plug configurations

Applications and integration

Field inspection: combine the standard cameras, positioning and 4G connection with your application for photos, location records and data submission.

Warehouse and asset workflows: select an optional barcode engine or the RFID band required by your labels and tags. Confirm reader performance and software integration for the intended environment.

Registration and identity workflows: choose optional fingerprint, ID card, binocular liveness or iris modules according to your capture requirements. Matching and access rules are implemented by your application.

Connected workstations: optional 10/100 Mbps Ethernet and additional connectors support projects needing wired interfaces. Confirm the connector configuration before ordering.

Configure your XH-500

Tell us the Android version, memory, cameras, SIM configuration, data capture modules and interfaces your project needs. We will confirm a compatible build and the integration details. Explore our custom solutions, or compare the XH-400 mobile biometric tablet.

Related guides

RFID performance depends on more than the module. See what UHF read range really depends on, and use our warehouse rollout plan for staging, Wi-Fi planning and MDM provisioning. The direct comparison with the newer 10.1-inch build is on XH-500 vs XH-700.

Ordering information

MOQ is 2 units, a sample is built in about 3 days and mass production runs about 25 days. Figures move when the XH-500 leaves its standard build (different radio band set, battery size or mounting kit); those variations are quoted in writing first.

MOQ	2 units. One for the field trial and one for MDM enrolment testing, so the fleet rollout does not pause between steps.
Sample	A sample is built and shipped in about 3 days, then the unit is checked against the acceptance criteria agreed with you, radio bands and battery behaviour included, before mass production starts.
Lead time	About 25 days from sample approval to shipment for the configuration and quantity on your order. Radio band and battery verification for the target market is written into the schedule before the first sample is built.
SDK and documentation	API and SDK support for the modules fitted to your build (GNSS, 2D imager or UHF RFID), plus the agreed specification sheet. NMEA or EPC output formats are confirmed before the order is placed.
Certification	The Android 12 build ships with GMS certification, and the Android 13 option is certified on request. Radio approvals for your target bands (CE, UKCA, FCC or local type approval) are agreed before production so the test plan fits the schedule.
Packaging	Retail box contents and carton dimensions are provided with the confirmed configuration and quotation; pallet quantities and incoterms are agreed with the order. Charging cradles and spare packs ship with the units or as a separate line.

Request a quote

Send the radio bands and GNSS accuracy you need, the quantity, the destination market and your target date. We reply with the configuration, the sample plan and a written price.

The commercial questions — order size, timing, warranty and shipping — are answered on the FAQ page.