8-INCH SERIES

XH-800 8-Inch Rugged Android Tablet

An 8-inch IP68 tablet on the MediaTek MTK8788 platform: Android 13, 4 GB + 64 GB with 6 GB and 8 GB tiers, a 10000 mAh battery and a 1.2 m drop rating. IP68 sealing and the −20 to +60 °C range are what put this build in the military-grade bracket; the 800 × 1280 panel is sized for one-handed work.



8.0-inch IPS at 800 × 1280 and 450 nits; 1920 × 1200 optional.

MTK8788 at 2.0 GHz with Mali-G73 MP3 graphics; Android 13.

4 GB + 64 GB standard, 6 GB + 128 GB or 8 GB + 128 GB optional; TF card to 512 GB.

4G, dual-band WiFi 5, Bluetooth 5.0 and 13.56 MHz NFC.

IP68 sealing, a 1.2 m drop rating and an operating range of −20 to +60 °C.

Display, platform and battery

Display	8.0-inch IPS, 16:10, 800 × 1280, 450 nits; 1920 × 1200 optional
Touch panel	10-point capacitive touchscreen
Processor	MediaTek MTK8788, 2.0 GHz; Arm Mali-G73 MP3 GPU
Operating system	Android 13
Memory / storage	4 GB LPDDR3 + 64 GB eMMC standard; 6 GB + 128 GB or 8 GB + 128 GB optional; TF card to 512 GB
Battery	Built-in 3.8 V / 10000 mAh; 10 hours of 1080p video at 70% volume and 70% brightness, as listed
Cameras	5 MP front (8 MP optional); 13 MP rear (20 MP optional)
Dimensions / weight	246 × 148 × 17 mm; 750 g; black housing

Audio	Two 8 Ω / 1 W speakers; one microphone, −28 ± 2 dB
Keys	Power, volume up/down, PTT, F1 to F4
Sensors	G-sensor, light sensor, geomagnetic sensor and gyroscope

Connectivity and positioning

4G LTE	FDD B1 / B2 / B3 / B4 / B5 / B7 / B8 / B12 / B17 / B19 / B20 / B26 / B28a / B28b; TDD B34 / B38 / B39 / B40 / B41
3G	WCDMA B1 / B2 / B4 / B5 / B8; TD-SCDMA B34 / B39
WiFi	802.11 a/b/g/n/ac, dual-band 2.4 GHz and 5.8 GHz
Bluetooth	Bluetooth 5.0 BLE, class 1; listed transmission distance 10 m
GNSS	BeiDou, GPS and GLONASS; high-precision positioning and BDS-3 are optional modules
SIM / TF	One SIM slot standard, two optional; one TF slot to 512 GB
Wired	USB 2.0 × 2 (one Type-A, one Type-C); 3.5 mm headphone jack; DC 5 V / 3 A through a 3.5 mm jack

The 4G band list is the one in the specification sheet. If your carrier uses a band outside it, send the band table before the order and the build is confirmed against it.

Data capture and interfaces

NFC (standard)	13.56 MHz; ISO/IEC 14443A/B, 15693, 18092 and MIFARE; listed reading distance 2–4 cm
Barcode scanning (optional)	Newland N1, Newland N2596 or Zebra 4100 engine
Fingerprint (optional)	Capacitive or optical fingerprint module; confirm the sensor, SDK and output format
ID card reader (optional)	Supported as an optional module; confirm the document types and software compatibility
RFID (optional)	LF 125 kHz or 134 kHz, HF 13.56 MHz, or UHF; separate from the standard NFC
Other options	Binocular liveness recognition, iris recognition, barometric altitude, LoRa, aviation connector, SMA connector, micro USB and a PSAM slot

Optional modules are quoted with the configuration. Confirm the module, the SDK and the output format your application expects before the build starts — that is what changes the schedule, not the hardware.

Operating conditions and accessories

Drop	1.2 m onto a wooden floor with the tablet powered on
Ingress protection	IP68 — dust-tight and sealed against continuous immersion
Operating temperature	−20 °C to +60 °C
Storage temperature	−40 °C to +70 °C
Humidity	95% RH, non-condensing
In the box	Type-C cable, operating instructions, wrist strap and power adapter; CN, US, EU or AU plug configurations

IP68 and the military-grade build

IP68 is the rating this build carries: dust-tight, and sealed against continuous immersion. Together with the 1.2 m drop test at power-on and a −20 to +60 °C operating range, that is the combination buyers mean when they ask for a military-grade tablet — a device that survives the handling and the weather, not only the office.

One caveat before a tender: the specification lists the test figures, not a MIL-STD-810H report. If the project requires that standard by name, ask for the report with the quotation, because a rating printed on a page and a report attached to a bid are two different things. See the MIL-STD-810H guide for what each test method covers.



Front, rear and side views: hand strap, side keys, ports and the pogo pin pad for a dock.

Where it fits

Vehicle and field work: at 246 × 148 mm the XH-800 fits a dash mount where a 10-inch tablet does not, and the −20 °C floor covers a cold van or an unheated depot. IP68 covers the wet and dusty end of that range, so rain, wash-down

and flour dust are inside the rating rather than a question mark.

Warehouse and stock counts: add the Newland or Zebra engine and the tablet handles receiving and cycle counts. For one-handed picking at height a handheld PDA is still the better tool; 750 g held in one hand for a shift is a different job.

Identity workflows: the optional fingerprint, ID card and iris modules put registration on the same screen as the record. Matching and access rules are implemented by your application, not by the device.

Configure your XH-800

Tell us the memory tier, the optional modules, the SIM arrangement, the band set for your market and whether an ingress rating is a requirement. We will confirm the build, the sample plan and the certification scope in writing. See the OEM and ODM options if the housing, branding or software image has to change, and certification support for radio approvals.

Related guides

The 8-inch and 10-inch trade-off is covered in the industrial tablet buying guide; the certification guide lists what each market asks for, and the cost-of-ownership note covers the years after the warranty. The direct comparison with the 10.1-inch 5G model is on XH-700 vs XH-800.

Ordering information

MOQ	2 units, the same as the rest of the range. One for the field trial, one for application and device-management testing.
Sample and production	A sample is built in about 3 days and production runs about 25 days from sample approval for our published terms. The XH-800 is a newer model, so its first build is scheduled in writing with the quotation.
Certification	Radio approvals are not listed in the specification. CE, UKCA, FCC or local type approval is scoped and quoted per project before production, against the market you ship to. GMS is not listed either; say so if your application depends on it.
Packaging	Retail box contents and carton dimensions are provided with the confirmed configuration and quotation; pallet quantities and incoterms are agreed with the order.

Request a quote

Send the quantity, the memory tier, the modules you need and the date units have to be on site. We reply with the configuration, the sample plan and a written price.

The commercial questions — order size, timing, warranty and shipping — are answered on the FAQ page.