Fanless Embedded Box PC

Rugged fanless embedded box PC for 24/7 kiosk and HMI integration: Intel Celeron J6412 with Core i3/i5 options, 6x RS-232/RS-485 COM ports, dual Gigabit LAN, 4x USB, HDMI and VGA outputs, and a wide-range DC input.



INTERFACES ON THIS UNIT

- 6 x DB9 serial, COM1 to COM6
- 2 x RJ45 LAN
- HDMI and VGA
- 4 x USB (USB 2.0 and 3.0 mixed)
- Audio out and microphone in
- 2 x Wi-Fi antennas on the front panel
- DC input with power and reset buttons

WEBSITE
www.xinyuehongtech.com

WHATSAPP
+86 139 2749 8231

EMAIL
sales@xinyuehongtech.com

Shenzhen Xinyuehong Information Technology Co., Ltd. · No. 38 Tian'an Road, Bantian, Longgang, Shenzhen, China

CONFIGURATION OPTIONS

- CPU platform, memory and storage configuration
- Serial port count and RS-232 / RS-485 level per port
- Wide-voltage DC input range and power budget
- VESA, DIN-rail or panel mounting brackets
- Windows or Linux image with your application
- Wide-temperature and dust-protection options

TYPICAL APPLICATIONS

- Main computer inside self-service kiosks
- Industrial control cabinets with several serial devices
- Multiple card readers, scanner and printer on one unit
- Digital signage player for wall-mounted screens

Request a quotation

Send the application, peripheral list, operating system choice and estimated quantity. We reply with the closest build, the open questions and the next step.

Reference build. Screen size, module mix, electrical ratings and certification scope are confirmed in writing for each project. Values describe the standard configuration and may change with selected options. © 2026 Shenzhen Xinyuehong Information Technology Co., Ltd.

WEBSITE
www.xinyuehongtech.com

WHATSAPP
+86 139 2749 8231

EMAIL
sales@xinyuehongtech.com

Shenzhen Xinyuehong Information Technology Co., Ltd. · No. 38 Tian'an Road, Bantian, Longgang, Shenzhen, China