Android Embedded Board

Rockchip RK3568 / RK3399 Android embedded board for kiosks and digital signage: LVDS, eDP and HDMI display outputs, multi-channel UART and GPIO headers, USB, RJ45 and an SDK for OS-level customisation.



INTERFACES ON THIS UNIT

- 2 x RJ45 Gigabit Ethernet
- 4 x USB host ports
- HDMI display output
- 3.5 mm audio jack
- DC power jack
- Terminal blocks for power and serial wiring
- White FPC connectors for panel, backlight and touch
- microSD slot, reset and power keys

CONFIGURATION OPTIONS

- Memory and eMMC storage size
- Android version and launcher lock-down
- Wi-Fi and Bluetooth module population
- Carrier board, enclosure and cable-set design
- Remote update and device management approach
- Long-term supply and revision control

WEBSITE
www.xinyuehongtech.com

WHATSAPP
+86 139 2749 8231

EMAIL
sales@xinyuehongtech.com

Shenzhen Xinyuehong Information Technology Co., Ltd. · No. 38 Tian'an Road, Bantian, Longgang, Shenzhen, China

TYPICAL APPLICATIONS

- Digital signage and advertising players
- Mainboard for compact self-service terminals
- Queue display and information screens
- Embedded Android appliances

Request a quotation

Send the application, peripheral list, operating system choice and estimated quantity. We reply with the closest build, the open questions and the next step.

Reference build. Screen size, module mix, electrical ratings and certification scope are confirmed in writing for each project. Values describe the standard configuration and may change with selected options. © 2026 Shenzhen Xinyuehong Information Technology Co., Ltd.

WEBSITE
www.xinyuehongtech.com

WHATSAPP
+86 139 2749 8231

EMAIL
sales@xinyuehongtech.com

Shenzhen Xinyuehong Information Technology Co., Ltd. · No. 38 Tian'an Road, Bantian, Longgang, Shenzhen, China