Clinic Self-Service Terminal with Card Dispenser

A clinic terminal that handles registration, payment, report printing and record printing, with a card dispenser built into the base.



TECHNICAL SPECIFICATIONS

Display	27 inch portrait touchscreen, 1920 × 1080
Touch	10-point projected capacitive (PCAP), tempered glass
Card dispenser	Motorised card hopper, 100-card capacity, empty and jam sensors
Card reading	Contactless reader (ISO 14443 A/B) plus ID card reader
Receipt printer	80 mm thermal printer with auto-cutter
Cabinet	Cold-rolled steel, powder-coated, lockable service door
Mounting	Floor-standing base with lockable castors
Operating system	Windows / Android / Linux
Computing platform	Android: Rockchip RK3568 or RK3399 · Windows and Linux: Intel Celeron J6412, Core i3 / i5 optional · 4–16 GB RAM, 64–512 GB SSD

EMBEDDED MODULES

- Vertical touchscreen
- Card dispenser
- Contactless reader
- Receipt printer
- ID reading

CONFIGURATION OPTIONS

- Card dispenser type, capacity and reload path
- Contactless pad, ID reader and receipt printer set
- Report printing module and paper path
- Cabinet finish and clinic branding
- Windows, Android or Linux with your clinic software

MODULE OPTIONS

Fingerprint terminal

A fingerprint capture module for identity verification at registration, access control or payment steps. Sensor type, capture window position and SDK support are agreed during specification.

Passport reader

A passport and travel-document reader for identity checks at hotel, transport and public-service counters. MRZ reading is standard; chip reading depends on the reader module selected.

Face recognition camera

A camera module for face-based check-in, liveness checks or queue pre-registration, subject to local privacy rules and the identity platform you already run.

TYPICAL APPLICATIONS

- Community clinic registration and card issue
- Payment of consultation fees
- Report and visit record printing

Request a quotation

Send the application, peripheral list, operating system choice and estimated quantity. We reply with the closest build, the open questions and the next step.

Reference build. Screen size, module mix, electrical ratings and certification scope are confirmed in writing for each project. Values describe the standard configuration and may change with selected options. © 2026 Shenzhen Xinyuehong Information Technology Co., Ltd.