Hospital Registration & Payment Kiosk

A hospital front-desk terminal that separates guidance content on the upper display from registration and payment work on the touchscreen below.



TECHNICAL SPECIFICATIONS

Main display	32 inch touchscreen, 1920 × 1080
Guidance display	21.5 inch upper screen, 1920 × 1080
Touch	10-point projected capacitive (PCAP), tempered glass
Input	Retractable keyboard with stainless-steel keycaps
Card reading	IC card, ID card and bank card readers, contactless option
Receipt printer	80 mm thermal printer with auto-cutter
Cabinet	Lockable steel cabinet with consumable access at the front
Mounting	Floor-standing base with lockable castors
Operating system	Windows / Android / Linux
Computing platform	Android: Rockchip RK3568 or RK3399 · Windows and Linux: Intel Celeron J6412, Core i3 / i5 optional · 4–16 GB RAM, 64–512 GB SSD

EMBEDDED MODULES

- Guidance display
- Touchscreen
- Retractable keyboard
- Card readers
- Receipt printer
- Lockable cabinet

CONFIGURATION OPTIONS

- Upper guidance display size and content source
- Card reader, health-code scanner and receipt printer set
- Retractable keyboard for staff-assisted sessions
- Cabinet colour and department branding
- Hospital information system interface review

MODULE OPTIONS

Fingerprint terminal

A fingerprint capture module for identity verification at registration, access control or payment steps. Sensor type, capture window position and SDK support are agreed during specification.

Passport reader

A passport and travel-document reader for identity checks at hotel, transport and public-service counters. MRZ reading is standard; chip reading depends on the reader module selected.

Face recognition camera

A camera module for face-based check-in, liveness checks or queue pre-registration, subject to local privacy rules and the identity platform you already run.

TYPICAL APPLICATIONS

- Outpatient registration and appointment check-in
- Self-payment of consultation and service fees
- Queue numbers and guidance content in waiting areas

Request a quotation

Send the application, peripheral list, operating system choice and estimated quantity. We reply with the closest build, the open questions and the next step.

Reference build. Screen size, module mix, electrical ratings and certification scope are confirmed in writing for each project. Values describe the standard configuration and may change with selected options. © 2026 Shenzhen Xinyuehong Information Technology Co., Ltd.