Mobile Hospital Self-Service Station

A tall service station on casters with a side identification column, both self-service and assisted flows, plus lockable storage for consumables.



TECHNICAL SPECIFICATIONS

Display	27 inch portrait touchscreen, 1920 × 1080
Second display	21.5 inch secondary screen on the camera column, 1920 × 1080
Touch	10-point projected capacitive (PCAP), tempered glass
Card reading	IC card, ID card and bank card readers plus contactless pad
Receipt printer	80 mm thermal printer with auto-cutter
Mobility	Four braked castors, cable management reel and transport lock
Cabinet	Lockable steel cabinet sized for ward rounds and temporary sites
Operating system	Windows / Android / Linux
Computing platform	Android: Rockchip RK3568 or RK3399 · Windows and Linux: Intel Celeron J6412, Core i3 / i5 optional · 4–16 GB RAM, 64–512 GB SSD

EMBEDDED MODULES

- Vertical touchscreen
- Camera column
- Secondary display
- Receipt printer
- Card readers
- Contactless reader
- Lockable cabinet
- Casters

CONFIGURATION OPTIONS

- Main display size and secondary identification column
- Camera, secondary display and card module selection
- Receipt printer, contactless pad and lockable storage layout
- Caster wheels, brakes and power inlet position
- Windows, Android or Linux platform choice

MODULE OPTIONS

Fingerprint terminal

A fingerprint capture module for identity verification at registration, access control or payment steps. Sensor type, capture window position and SDK support are agreed during specification.

Passport reader

A passport and travel-document reader for identity checks at hotel, transport and public-service counters. MRZ reading is standard; chip reading depends on the reader module selected.

Face recognition camera

A camera module for face-based check-in, liveness checks or queue pre-registration, subject to local privacy rules and the identity platform you already run.

TYPICAL APPLICATIONS

- Inpatient floors for bedside payment
- Temporary screening and triage points
- Discharge settlement desks

Request a quotation

Send the application, peripheral list, operating system choice and estimated quantity. We reply with the closest build, the open questions and the next step.

Reference build. Screen size, module mix, electrical ratings and certification scope are confirmed in writing for each project. Values describe the standard configuration and may change with selected options. © 2026 Shenzhen Xinyuehong Information Technology Co., Ltd.