

网络安全课外实验 实验报告

学院:信息科学与工程学院

专业班级: 信息安全 1401

指导老师: 王伟平

学 号: 0906140129

姓 名: 郭一涵

目 录

目	录		2
基于	0	penSSL 的 VPN 网络环境搭建	3
	1.	概要介绍	3
	2.	实验环境	3
		实验内容	
		3.1 CentOS 搭建 OpenVPN 服务器端	3
		3.2 在客户端配置	
		3.3 运行结果	
	4.	实验收获	7
		4.1 TCP 与 UDP	7
		4.2 SSL 协议问题	7
		4.3 SSL 记录协议与 OpenVPN 记录协议差别	7
		4.4 SSL 握手协议与 OpenVPN 握手协议	7
		4.5 BIO 封装 SSL 握手消息	7
	5.	附 VPN 一键安装程序源码(针对 Linux 系统)	

基于 OpenSSL 的 VPN 网络环境搭建

1. 概要介绍

VPN 是常见的一种数据安全传输方式,主要用来利用公共网络假设专用网络,实现一个虚拟的专用网络环境。

2. 实验环境

装有 CentOS7 系统的服务器一台 装有 OpenVPN 客户端,能够联网的计算机一台

3. 实验内容

3.1 CentOS 搭建 OpenVPN 服务器端

由于 OpenVPN Server 不在默认源,所以需要安装 EPEL(Extra Packages for Enterprise Linux)仓库,其中包含有 OpenVPN 包,命令如下

wget

http://dl.fedoraproject.org/pub/epel/beta/7/x86_64/epel-release-7-0.2.noarch.rpm
rpm -Uvh epel-release-7-0.2.noarch.rpm

接着从 Yum 安装 OpenVPN

yum install openvpn -y

然后从示例配置文件复制一份配置文件到/etc/openvpn

ср

/usr/share/doc/openvpn-*/sample/sample-config-files/s erver.conf /etc/openvpn

打开/etc/openvpn/server.conf 编辑:

vim /etc/openvpn/server.conf

在这里边取消以下的注释

push "redirect-gateway def1 bypass-dhcp" push "dhcp-option DNS 8.8.8.8" push "dhcp-option DNS 8.8.4.4" user nobody group nobody

在配置文件更改完毕之后,开始生成Keys和Certifications

首先安装easy-rsa yum install easy-rsa

将相关文件复制到OpenVPN的目录

cp -R /usr/share/easy-rsa/ /etc/openvpn

这些完成之后,开始调整Keys的生成配置

首先修改vars文件

vim /etc/openvpn/easy-rsa/2.0/vars

将一下内容修改为自己的值

export KEY_COUNTRY="US"
export KEY_PROVINCE="NY"
export KEY_CITY="New York"
export KEY_ORG="Organization Name"
export KEY_EMAIL="administrator@example.com"
export KEY_CN=droplet.example.com
export KEY_NAME=server
export KEY_OU=server

修改完成之后,清空vars

cd /etc/openvpn/easy-rsa/2.0
source ./vars

完成之后可以开始修改密钥了

在/etc/openvpn/easy-rsa/2.0 路径下执行

- ./clean-all
- ./build-ca

之后为 Server 生成密钥

./build-key-server server

然后生成 Diffie Hellman key exchange 文件

./build-dh

接着将这四个文件复制到 OpenVPN 的配置目录中

cd /etc/openvpn/easy-rsa/2.0/keys
cp dh1024.pem ca.crt server.crt server.key /etc/openvpn

接着就可以在/etc/openvpn/easy-rsa/2.0目录中生成客户端

Certifications和Keys了

./build-key client

之后,需要配置一下路由以及启动 Server 了

首先需要配置一下防火墙,由于 CentOS7 中 iptables 已经被

Firewalld 取代,故需要使用 Firewalld

systemctl status firewalld.service

然后允许 openvpn 服务通过

firewall-cmd --add-service openvpn
firewall-cmd --permanent --add-service openvpn

接着添加masquerade

firewall-cmd --add-masquerade
firewall-cmd --permanent --add- masquerade

接着要允许IP转发
vim /etc/sysctl.conf
在这里边添加以下内容
net.ipv4.ip_forward = 1

然后启动服务,并添加自启动项

sysctl -p
systemctl start openvpn@server
systemctl enable openvpn@server

3.2 在客户端配置

取回之前在/etc/openvpn/easy-rsa/2.0/keys 里边的三个文件 ca.crt client.crt client.key

然后创建一个配置文件: client.ovpn

client
dev tun
proto udp
remote xxx.xxx.xxx.xxx 1194
resolv-retry infinite
nobind
persist-key
persist-tun
comp-lzo
verb 3
ca ca.crt
cert client.crt
key client.key

3.3 运行结果

通过搭建的 VPN,可以正常访问 Google , Youtube 等网站

4. 实验收获

4.1 TCP 与 UDP

为什么 OpenVPN 首选了 UDP 而不是 TCP? 主要是因为在有大流量的情况下,TCP 隧道的性能将严重下降,最终导致网络不可用,这一点 CIPE 的作者已经通过实测证明了。不过 OpenVPN 还是支持 TCP 的。

4.2 SSL 协议问题

为什么 OpenVPN 使用 SSL 的握手协议而不需要 SSL 的记录协议? SSL 首选了 TCP,而 OpenVPN 首选了 UDP,设计时 DTLS 还没有产生,故 OpenVPN 不能直接使用 SSL 记录协议,但是 SSL 的握手协议是良好的,故 OpenVPN 将 SSL 握手协议和自己的记录协议适配在了一起,适配的方法是增加了一相当于"多路复用码"的感觉,通过对一些字段的解析,识别协议包是握手包还是记录包。

4.3 SSL 记录协议与 OpenVPN 记录协议差别


SSL 直接接于传输层协议之上,它在保证安全的同时一定不能更改应用的语义,比如 http 是 tcp 的,那么 https 也需要是 tcp 的,SSL 原本就是设计用于加密应用数据而不是构建三层隧道的。而 OpenVPN 的记录协议保护的只是一个 IP 数据报的再封装,最终的端系统应用才负责传输层语义,因此 OpenVPN 不需要可靠传输。

4.4 SSL 握手协议与 OpenVPN 握手协议

OpenVPN 的连接建立使用了 SSL 握手协议,可是却抓不到 SSL 握手包,实际上 SSL 握手协议是作为一种载荷封装在了 OpenVPN 的协议包里面了,SSL 握手协议数据实际上是写入了一块内存,然后 OpenVPN 从该内存中读出这些数据包,然后封装后通过 reliable 层发出,数据到达对端后,解封装后写入一块内存,然后 SSL 从内存中读出 SSL 握手载荷,一切都是通过 BIO 实现的

4.5 BIO 封装 SSL 握手消息

之前说过 OpenVPN 通过 BIO 封装的 SSL 握手协议,那么他是如何去封装的,在这里用一副简要的图来展示:



5. 附 VPN 一键安装程序源码(针对 Linux 系统)

由于 OpenSSL 需要专门的客户端,在使用的时候并不方便,故我后来又专门搭建了基于 Ikev2 的 VPN 环境,目前大部分系统平台均直接支持,一下为自动搭建源码,来源于 Github:

#!
/bin/b
ash

PATH=/bin:/sbin:/usr/bin:/usr/sbin:/usr/local/bin:/usr/local/sbin:~/bin export PATH

#-----

- # System Required: CentOS6.x/7 (32bit/64bit) or Ubuntu
- # Description: Install IKEV2 VPN for CentOS and Ubuntu
- # Author: quericy
- # Intro: https://quericy.me/blog/699

#-----

```
clear
VER=1.2.0
echo "# Install IKEV2 VPN for CentOS6.x/7 (32bit/64bit) or Ubuntu or
Debian7/8.*"
echo "# Intro: https://quericy.me/blog/699"
echo "#"
echo "# Author:quericy"
echo "#"
echo "# Version:$VER"
echo ""
INTERACTIVE=""
if [ -t 1 ] ; then
   __INTERACTIVE="1"
fi
__green(){
   if [ "$__INTERACTIVE" ] ; then
      printf '\033[1;31;32m'
   fi
   printf -- "$1"
   if [ "$__INTERACTIVE" ] ; then
      printf '\033[0m'
   fi
}
__red(){
   if [ "$__INTERACTIVE" ] ; then
      printf '\033[1;31;40m'
   fi
   printf -- "$1"
   if [ "$__INTERACTIVE" ] ; then
      printf '\033[0m'
   fi
}
__yellow(){
```

```
if [ "$__INTERACTIVE" ] ; then
        printf '\033[1;31;33m'
    fi
    printf -- "$1"
    if [ "$__INTERACTIVE" ] ; then
        printf '\033[0m'
    fi
}
# Install IKEV2
function install_ikev2(){
    rootness
    disable_selinux
    get_system
    yum_install
    get_my_ip
    pre_install
    download_files
    setup_strongswan
    get_key
    configure_ipsec
    configure_strongswan
    configure_secrets
    SNAT_set
    iptables_check
    ipsec restart
    success_info
}
# Make sure only root can run our script
function rootness(){
if [[ $EUID -ne 0 ]]; then
   echo "Error:This script must be run as root!" 1>&2
   exit 1
fi
}
# Disable selinux
function disable_selinux(){
if [ -s /etc/selinux/config ] && grep 'SELINUX=enforcing'
/etc/selinux/config; then
```

```
sed -i 's/SELINUX=enforcing/SELINUX=disabled/g' /etc/selinux/config
    setenforce 0
fi
}
# Ubuntu or CentOS
function get_system(){
    if grep -Eqi "CentOS" /etc/issue || grep -Eq "CentOS" /etc/*-release;
then
        system_str="0"
    elif grep -Eqi "Ubuntu" /etc/issue || grep -Eq "Ubuntu" /etc/*-release;
then
        system_str="1"
    elif grep -Eqi "Debian" /etc/issue || grep -Eq "Debian" /etc/*-release;
then
        system_str="1"
    else
        echo "This Script must be running at the CentOS or Ubuntu or Debian!"
        exit 1
    fi
}
#install necessary lib
function yum_install(){
    if [ "$system_str" = "0" ]; then
    yum -y update
    yum -y install pam-devel openssl-devel make gcc curl
    else
    apt-get -y update
    apt-get -y install libpam0g-dev libssl-dev make gcc curl
    fi
}
# Get IP address of the server
function get_my_ip(){
    echo "Preparing, Please wait a moment..."
    IP=`curl -s checkip.dyndns.com | cut -d' ' -f 6 | cut -d'<' -f 1`</pre>
    if [ -z $IP ]; then
        IP=`curl -s ifconfig.me/ip`
    fi
}
```

```
# Pre-installation settings
function pre_install(){
   echo "# Install IKEV2 VPN for CentOS6.x/7 (32bit/64bit) or Ubuntu or
Debian7/8.*"
   echo "# Intro: https://quericy.me/blog/699"
   echo "#"
   echo "# Author:quericy"
   echo "#"
   echo "# Version:$VER"
   echo "please choose the type of your VPS(Xen, KVM: 1 , OpenVZ: 2):"
   read -p "your choice(1 or 2):" os_choice
   if [ "$os_choice" = "1" ]; then
       os="1"
       os str="Xen, KVM"
       else
          if [ "$os_choice" = "2" ]; then
              os="2"
              os_str="OpenVZ"
              else
              echo "wrong choice!"
              exit 1
          fi
   fi
   echo "please input the ip (or domain) of your VPS:"
   read -p "ip or domain(default_value:${IP}):" vps_ip
   if [ "$vps_ip" = "" ]; then
       vps_ip=$IP
   fi
   echo "Would you want to import existing cert? You NEED copy your cert
file to the same directory of this script"
   read -p "yes or no?(default_value:no):" have_cert
   if [ "$have_cert" = "yes" ]; then
       have_cert="1"
   else
       have_cert="0"
       echo "please input the cert country(C):"
       read -p "C(default value:com):" my_cert_c
       if [ "$my_cert_c" = "" ]; then
```

```
my_cert_c="com"
       fi
        echo "please input the cert organization(0):"
        read -p "O(default value:myvpn):" my cert o
        if [ "$my cert o" = "" ]; then
           my_cert_o="myvpn"
       fi
       echo "please input the cert common name(CN):"
       read -p "CN(default value: VPN CA): " my cert cn
        if [ "$my_cert_cn" = "" ]; then
           my_cert_cn="VPN CA"
       fi
    fi
    get_char(){
       SAVEDSTTY=`stty -g`
       stty -echo
       stty cbreak
       dd if=/dev/tty bs=1 count=1 2> /dev/null
       stty -raw
       stty echo
        stty $SAVEDSTTY
    echo "Please confirm the information:"
    echo ""
    echo -e "the type of your server: [$(__green $os_str)]"
    echo -e "the ip(or domain) of your server: [$(__green $vps_ip)]"
    if [ "$have cert" = "1" ]; then
       echo -e "$( yellow "These are the certificate you MUST be
prepared:")"
       echo -e "[$(__green "ca.cert.pem")]:The CA cert or the chain cert."
       echo -e "[$(__green "server.cert.pem")]:Your server cert."
       echo -e "[$(__green "server.pem")]:Your key of the server cert."
        echo -e "[$( yellow "Please copy these file to the same directory
of this script before start!")]"
    else
        echo -e "the cert_info:[$(__green "C=${my_cert_c},
O=${my cert o}")]"
    fi
    echo "Press any key to start...or Press Ctrl+C to cancel"
    char=`get_char`
```

```
cur dir=`pwd`
    cd $cur_dir
}
# Download strongswan
function download_files(){
    strongswan_version='strongswan-5.5.1'
    strongswan_file="$strongswan_version.tar.gz"
    if [ -f $strongswan_file ];then
        echo -e "$strongswan_file [$(__green "found")]"
    else
        if ! wget --no-check-certificate
https://download.strongswan.org/$strongswan_file;then
            echo "Failed to download $strongswan_file"
            exit 1
        fi
    fi
    tar xzf $strongswan_file
    if [ $? -eq 0 ]; then
        cd $cur_dir/$strongswan_version/
    else
        echo ""
        echo "Unzip $strongswan_file failed! Please visit
https://quericy.me/blog/699 and contact."
        exit 1
    fi
}
# configure and install strongswan
function setup_strongswan(){
    if [ "$os" = "1" ]; then
        ./configure --enable-eap-identity --enable-eap-md5 \
--enable-eap-mschapv2 --enable-eap-tls --enable-eap-ttls --enable-eap-peap
--enable-eap-tnc --enable-eap-dynamic --enable-eap-radius
--enable-xauth-eap \
--enable-xauth-pam --enable-dhcp --enable-openssl --enable-addrblock
--enable-unity \
--enable-certexpire --enable-radattr --enable-swanctl --enable-openssl
```

第 14

#Current folder

```
else
       ./configure --enable-eap-identity --enable-eap-md5 \
--enable-eap-mschapv2 --enable-eap-tls --enable-eap-ttls --enable-eap-peap
--enable-eap-tnc --enable-eap-dynamic --enable-eap-radius
--enable-xauth-eap \
--enable-xauth-pam --enable-dhcp --enable-openssl --enable-addrblock
--enable-unity \
--enable-certexpire --enable-radattr --enable-swanctl --enable-openssl
--disable-gmp --enable-kernel-libipsec
   fi
   make; make install
}
# configure cert and key
function get_key(){
   cd $cur_dir
   if [ ! -d my_key ];then
       mkdir my_key
   if [ "$have_cert" = "1" ]; then
       import_cert
   else
       create_cert
   fi
   get_char(){
       SAVEDSTTY=`stty -g`
       stty -echo
       stty cbreak
       dd if=/dev/tty bs=1 count=1 2> /dev/null
       stty -raw
       stty echo
       stty $SAVEDSTTY
   cp -f ca.cert.pem /usr/local/etc/ipsec.d/cacerts/
```

```
cp -f server.cert.pem /usr/local/etc/ipsec.d/certs/
    cp -f server.pem /usr/local/etc/ipsec.d/private/
    cp -f client.cert.pem /usr/local/etc/ipsec.d/certs/
    cp -f client.pem /usr/local/etc/ipsec.d/private/
    echo "Cert copy completed"
}
# import cert if user has ssl certificate
function import_cert(){
   cd $cur_dir
   if [ -f ca.cert.pem ];then
        cp -f ca.cert.pem my_key/ca.cert.pem
        echo -e "ca.cert.pem [$(__green "found")]"
    else
        echo -e "ca.cert.pem [$(__red "Not found!")]"
        exit
    fi
    if [ -f server.cert.pem ];then
        cp -f server.cert.pem my_key/server.cert.pem
        cp -f server.cert.pem my_key/client.cert.pem
        echo -e "server.cert.pem [$(__green "found")]"
        echo -e "client.cert.pem [$(__green "auto create")]"
    else
        echo -e "server.cert.pem [$(__red "Not found!")]"
        exit
    fi
    if [ -f server.pem ];then
        cp -f server.pem my_key/server.pem
        cp -f server.pem my key/client.pem
        echo -e "server.pem [$(__green "found")]"
        echo -e "client.pem [$(__green "auto create")]"
        echo -e "server.pem [$(__red "Not found!")]"
        exit
    fi
    cd my_key
}
# auto create certificate
function create cert(){
    cd $cur_dir
    cd my_key
```

```
ipsec pki --gen --outform pem > ca.pem
    ipsec pki --self --in ca.pem --dn "C=${my cert c}, O=${my cert o},
CN=${my_cert_cn}" --ca --outform pem >ca.cert.pem
    ipsec pki --gen --outform pem > server.pem
    ipsec pki --pub --in server.pem | ipsec pki --issue --cacert ca.cert.pem
    --cakey ca.pem --dn "C=${my_cert_c}, O=${my_cert_o}, CN=${vps_ip}" \
    --san="${vps_ip}" --flag serverAuth --flag ikeIntermediate \
    --outform pem > server.cert.pem
    ipsec pki --gen --outform pem > client.pem
    ipsec pki --pub --in client.pem | ipsec pki --issue --cacert ca.cert.pem
--cakey ca.pem --dn "C=${my_cert_c}, O=${my_cert_o}, CN=VPN Client"
--outform pem > client.cert.pem
    echo "configure the pkcs12 cert password(Can be empty):"
    openssl pkcs12 -export -inkey client.pem -in client.cert.pem -name
"client" -certfile ca.cert.pem -caname "${my_cert_cn}" -out
client.cert.p12
}
# configure the ipsec.conf
function configure ipsec(){
cat > /usr/local/etc/ipsec.conf<<-EOF</pre>
config setup
    uniqueids=never
conn iOS cert
    keyexchange=ikev1
    fragmentation=yes
    left=%defaultroute
    leftauth=pubkey
    leftsubnet=0.0.0.0/0
    leftcert=server.cert.pem
    right=%any
    rightauth=pubkey
    rightauth2=xauth
    rightsourceip=10.31.2.0/24
    rightcert=client.cert.pem
    auto=add
conn android_xauth_psk
    kevexchange=ikev1
    left=%defaultroute
    leftauth=psk
    leftsubnet=0.0.0.0/0
    right=%any
```

```
rightauth=psk
    rightauth2=xauth
    rightsourceip=10.31.2.0/24
    auto=add
conn networkmanager-strongswan
    keyexchange=ikev2
    left=%defaultroute
    leftauth=pubkey
    leftsubnet=0.0.0.0/0
    leftcert=server.cert.pem
    right=%any
    rightauth=pubkey
    rightsourceip=10.31.2.0/24
    rightcert=client.cert.pem
    auto=add
conn ios_ikev2
    keyexchange=ikev2
    ike=aes256-sha256-modp2048,3des-sha1-modp2048,aes256-sha1-modp2048!
    esp=aes256-sha256,3des-sha1,aes256-sha1!
    rekey=no
    left=%defaultroute
    leftid=${vps_ip}
    leftsendcert=always
    leftsubnet=0.0.0.0/0
    leftcert=server.cert.pem
    right=%any
    rightauth=eap-mschapv2
    rightsourceip=10.31.2.0/24
    rightsendcert=never
    eap identity=%any
    dpdaction=clear
    fragmentation=yes
    auto=add
conn windows7
    keyexchange=ikev2
    ike=aes256-sha1-modp1024!
    rekey=no
    left=%defaultroute
    leftauth=pubkey
    leftsubnet=0.0.0.0/0
    leftcert=server.cert.pem
    right=%any
    rightauth=eap-mschapv2
    rightsourceip=10.31.2.0/24
```

```
rightsendcert=never
    eap_identity=%any
    auto=add
EOF
}
# configure the strongswan.conf
function configure strongswan(){
 cat > /usr/local/etc/strongswan.conf<<-EOF</pre>
 charon {
        load_modular = yes
        duplicheck.enable = no
        compress = yes
        plugins {
                include strongswan.d/charon/*.conf
        }
        dns1 = 8.8.8.8
        dns2 = 8.8.4.4
        nbns1 = 8.8.8.8
        nbns2 = 8.8.4.4
}
include strongswan.d/*.conf
EOF
}
# configure the ipsec.secrets
function configure_secrets(){
    cat > /usr/local/etc/ipsec.secrets<<-EOF</pre>
: RSA server.pem
: PSK "myPSKkey"
: XAUTH "myXAUTHPass"
myUserName %any : EAP "myUserPass"
EOF
}
function SNAT_set(){
    echo "Use SNAT could implove the speed, but your server MUST have static
ip address."
    read -p "yes or no?(default_value:no):" use_SNAT
    if [ "$use_SNAT" = "yes" ]; then
        use_SNAT_str="1"
```

```
echo -e "$(__yellow "ip address info:")"
        ip address | grep inet
        echo "Some servers has elastic IP (AWS) or mapping IP.In this case, you
should input the IP address which is binding in network interface."
        read -p "static ip or network interface ip (default_value:${IP}):"
static_ip
    if [ "$static_ip" = "" ]; then
        static_ip=$IP
    fi
    else
        use_SNAT_str="0"
    fi
}
# iptables check
function iptables_check(){
    cat > /etc/sysctl.d/10-ipsec.conf<<-EOF</pre>
net.ipv4.ip_forward=1
EOF
    sysctl --system
    echo "Do you use firewall in CentOS7 instead of iptables?"
    read -p "yes or no?(default_value:no):" use_firewall
    if [ "$use_firewall" = "yes" ]; then
        firewall_set
    else
        iptables_set
    fi
}
# firewall set in CentOS7
function firewall set(){
    if ! systemctl is-active firewalld > /dev/null; then
        systemctl start firewalld
    fi
    firewall-cmd --permanent --add-service="ipsec"
    firewall-cmd --permanent --add-port=500/udp
    firewall-cmd --permanent --add-port=4500/udp
    firewall-cmd --permanent --add-masquerade
    firewall-cmd --reload
}
```

```
# iptables set
function iptables set(){
    echo -e "$(__yellow "ip address info:")"
    ip address | grep inet
    echo "The above content is the network card information of your VPS."
    echo "[$(__yellow "Important")]Please enter the name of the interface
which can be connected to the public network."
    if [ "$os" = "1" ]; then
            read -p "Network card interface(default value:eth0):" interface
        if [ "$interface" = "" ]; then
            interface="eth0"
        fi
        iptables -A FORWARD -m state --state RELATED, ESTABLISHED -j ACCEPT
        iptables -A FORWARD -s 10.31.0.0/24 -j ACCEPT
        iptables -A FORWARD -s 10.31.1.0/24 -j ACCEPT
        iptables -A FORWARD -s 10.31.2.0/24 -j ACCEPT
        iptables -A INPUT -i $interface -p esp -j ACCEPT
        iptables -A INPUT -i $interface -p udp --dport 500 -j ACCEPT
        iptables -A INPUT -i $interface -p tcp --dport 500 -j ACCEPT
        iptables -A INPUT -i $interface -p udp --dport 4500 -j ACCEPT
        iptables -A INPUT -i $interface -p udp --dport 1701 -j ACCEPT
        iptables -A INPUT -i $interface -p tcp --dport 1723 -j ACCEPT
        #iptables -A FORWARD -j REJECT
        if [ "$use_SNAT_str" = "1" ]; then
            iptables -t nat -A POSTROUTING -s 10.31.0.0/24 -o $interface -j
SNAT --to-source $static_ip
            iptables -t nat -A POSTROUTING -s 10.31.1.0/24 -o $interface -j
SNAT --to-source $static ip
            iptables -t nat -A POSTROUTING -s 10.31.2.0/24 -o $interface -j
SNAT --to-source $static ip
        else
            iptables -t nat -A POSTROUTING -s 10.31.0.0/24 -o $interface -j
MASOUERADE
            iptables -t nat -A POSTROUTING -s 10.31.1.0/24 -o $interface -j
MASQUERADE
            iptables -t nat -A POSTROUTING -s 10.31.2.0/24 -o $interface -j
MASOUERADE
        fi
    else
        read -p "Network card interface(default value:venet0):" interface
        if [ "$interface" = "" ]; then
            interface="venet0"
        fi
        iptables -A FORWARD -m state --state RELATED, ESTABLISHED -j ACCEPT
```

```
iptables -A FORWARD -s 10.31.0.0/24 -j ACCEPT
        iptables -A FORWARD -s 10.31.1.0/24 -j ACCEPT
        iptables -A FORWARD -s 10.31.2.0/24 -j ACCEPT
        iptables -A INPUT -i $interface -p esp -j ACCEPT
        iptables -A INPUT -i $interface -p udp --dport 500 -j ACCEPT
        iptables -A INPUT -i $interface -p tcp --dport 500 -j ACCEPT
        iptables -A INPUT -i $interface -p udp --dport 4500 -j ACCEPT
        iptables -A INPUT -i $interface -p udp --dport 1701 -j ACCEPT
        iptables -A INPUT -i $interface -p tcp --dport 1723 -j ACCEPT
        #iptables -A FORWARD -j REJECT
        if [ "$use_SNAT_str" = "1" ]; then
            iptables -t nat -A POSTROUTING -s 10.31.0.0/24 -o $interface -j
SNAT --to-source $static_ip
           iptables -t nat -A POSTROUTING -s 10.31.1.0/24 -o $interface -j
SNAT --to-source $static ip
           iptables -t nat -A POSTROUTING -s 10.31.2.0/24 -o $interface -j
SNAT --to-source $static ip
       else
           iptables -t nat -A POSTROUTING -s 10.31.0.0/24 -o $interface -j
MASQUERADE
           iptables -t nat -A POSTROUTING -s 10.31.1.0/24 -o $interface -j
MASQUERADE
           iptables -t nat -A POSTROUTING -s 10.31.2.0/24 -o $interface -j
MASQUERADE
       fi
    if [ "$system_str" = "0" ]; then
        service iptables save
    else
        iptables-save > /etc/iptables.rules
        cat > /etc/network/if-up.d/iptables<<-EOF</pre>
#!/bin/sh
iptables-restore < /etc/iptables.rules</pre>
EOF
       chmod +x /etc/network/if-up.d/iptables
    fi
}
# echo the success info
function success info(){
    echo -e "#"
    echo -e "# [$(__green "Install Complete")]"
```

```
echo -e "# Version:$VER"
   echo -e "# There is the default login info of your IPSec/IkeV2 VPN Service"
   echo -e "# UserName:$(__green " myUserName")"
   echo -e "# PassWord:$(__green " myUserPass")"
   echo -e "# PSK:$(__green " myPSKkey")"
   echo -e "# you should change default username and password in$(__green
" /usr/local/etc/ipsec.secrets")"
   echo -e "# you cert:$(__green " ${cur_dir}/my_key/ca.cert.pem ")"
   if [ "$have cert" = "1" ]; then
   echo -e "# you don't need to install cert if it's be trusted."
   else
   echo -e "# you must copy the cert to the client and install it."
   echo -e "#"
   echo -e
echo -e ""
}
# Initialization step
install_ikev2
```

第 23