VCOM 2.0 Driver for Linux Installation Guide

ICG.Support@advantech.com.tw

Revision Date	Revision	Description	Author
2019/2/11	V1.2	Third Edition	Jay Wu

VCOM 2.0 Driver Feature List

- Features Enhancement
  - VCOM
  - TCP Redundancy
  - Manual Mapping for Basic Debug Message
- Devices Support List
  - ADAM-4570-BE/CE
  - ADAM-4570L-CE/DE
  - ADAM-4571-BE/CE
  - ADAM-4571L-CE/DE
  - EKI-1521/2/4/8/6(I)(CI)-AE/BE/CE

VCOM Driver Version Comparison

- Comparison Table

Driver Version	VCOM Driver Ver. 1.0	VCOM Driver Ver. 2.0
Driver Name	**iCom_Linux_Pseudo_TTY_Driver_v1.4.1**	**vcom_linux_2.2.1**
Pre-built Binary Support List	Red Hat 9 (Kernel 2.4.20-8) Red Hat Enterprise 5.4 (Kernel 2.6.18-164.el5) Fedora Core 13 (64bit) (Kernel 2.6.33.3-85.fc13) Fedora Core 14 (Kernel 2.6.35.6-45.fc14) Fedora Core 16 (Kernel 3.1.0-7.fc16) OpenSUSE 10.1 (Kernel 2.6.16.13-4-default) OpenSUSE 11.2 (Kernel 2.6.31.5-0.1-desktop) Mandriva 2010 (Kernel 2.6.31.5-desktop-1mnb) Debian 5.0.4 (Kernel 2.6.26-2-686) Ubuntu 8.04 (Kernel 2.6.24-19-generic) Ubuntu 11.10 (Kernel 3.0.0-12-generic)	Ubuntu 14.04 LTS (64bit) (Kernel 3.13.0-48-generic) Ubuntu 16.04 LTS (64bit) (Kernel 4.04.0-21-generic) Ubuntu 18.04 LTS (64bit) (Kernel 4.15.0-23-generic) OpenSUSE 13.2 (32bit) (Kernel 13.16) Linux-Mint 18.3 (64bit) (Kernel 4.10) CentOS 7.2 – 1511 (64bit) (Kernel 3.10.0-327) CentOS 7.4 – 1708 (64bit) (Kernel 3.10.0-693) CentOS 7.6 – 1810 (64bit) (Kernel 3.10.0-957)

Before installing, please double check these points…

1. IP address
   - To configure the IP address of device server, and make sure that the communication is working



2. VCOM mode
   - Launch browser and check the operation mode that is configured to VCOM mode on Web GUI



Before installing, please double check these points…

3. Identify the HW version

– The BE ver. is different naming rule from AE in our Linux driver. If you are using
EKI-1522(I)-AE, please fill the name of 1522 to advttyd.conf.
EKI-1522(I)-BE, please fill the name of b522 to advttyd.conf
EKI-1522(I)-CE, please fill the name of c522 to advttyd.conf
EKI-1524(I)-AE, please fill the name of 1524 to advttyd.conf.
EKI-1524(I)-BE, please fill the name of b524 to advttyd.conf
EKI-1524(I)-CE, please fill the name of c524 to advttyd.conf
EKI-1512-AE, please fill the name of 1512 to advttyd.conf

– For example:





If you are using the EKI-1522-"AE"			
[Minor]	[Device-Type]	[Device-IP]	[Port-Idx]
0	1522	10.0.0.1	1

If you are using the EKI-1522-"BE"			
[Minor]	[Device-Type]	[Device-IP]	[Port-Idx]
0	B522	10.0.0.1	1

Installation Procedure

Installation Step



Log in as “Root Privilege"

1. Open the terminal of Linux.
2. Key in “sudo su” to get the root privilege.
3. Fill in the Root’s password “*xxxxxxx*” that you created

Copy and Extract the VCOM Driver

1. Key in “cd Desktop” to change the direction to the desktop.
2. Key in “tar –jxv –f vcom_linux_2.2.0.tar.bz2” to extract the VCOM file.
3. Make sure internet is available.



Key in “cd Desktop”
Please note the uppercase letters.

Key in “tar –jxv –f vcom_linux_2.2.0.tar.bz2”
Please note the uppercase letters.



The VCOM folder has been extracted

Install the Development Kit for Kernel

- For Ubuntu/Linux-Mint family ,

  Key in: “#sudo apt-get install build-essential linux-headers-generic ”

- For CentOS/RHEL/Fedora,

  Key in: “# yum install kernel-devel kernel-headers gcc make”



*Note: Important- Once you upgrade and install finished, please reboot your Linux OS.

Install the Development Kit for Kernel

- If your Linux is CentOS/RHEL/Fedora, kernel is under 3.10. Please modify below file //vcom_linux_2.2.1/driver/adv_uart.c to remark flow control function and then save the file.
- For more information, please reference readme.txt file.



Compile the VCOM Driver

1. Key in “cd vcom_linux_2.2.1” to change the direction to the driver folder.
2. Key in “make” to compile the VCOM driver.



Key in “cd vcom_linux_2.2.1”
Please note the uppercase letters.

Key in “make”
Please note the uppercase letters.

Configure the VCOM Setting

1. Key in “vi config/advttyd.conf” to edit the VCOM setting.



Key in “vi config/advttyd.conf”
Or “vim config/advttyd.conf”
Please note the uppercase letters.

2. To edit the setting.



You can edit the setting in this file

Press “i” to enter the “Editor Mode”
Press “ESC” back to the “Normal Mode”
After returning to “Normal mode”, please using “:wq” to save the setting.

Example



Set VCOM from 0 to 1
Device is using the EKI-1522-BE
IP address is 192.168.250.119
COM port is using Port 1 and Port 2

Install the VCOM Driver and Setting

- Key in “sudo make install”

Please note the uppercase letters.



Load the Driver into the Kernel

- Key in “sudo advman –o insert” to Load the driver into the kernel.



Enable the VCOM

- Key in “sudo advman –o start” to enable the VCOM.

```
root@ubuntu:/home/vcom/Desktop/vcom_linux_2.2.0# sudo advman -o start
/usr/local/advtty/advvcom.ko
kernel moduel advvcom.ko detected...
starting service....
invoking local deamon...
```

- Also, you can use the “sudo ls /proc/vcom/” command to confirm the VCOM is enabling.

```
root@ubuntu: /home/vcom/Desktop/vcom_linux_2.2.0
root@ubuntu:/home/vcom/Desktop/vcom_linux_2.2.0# sudo ls /proc/vcom/
advproc0    advproc131  advproc165  advproc199  advproc231  advproc36  advproc7
advproc1    advproc132  advproc166  advproc2    advproc232  advproc37  advproc70
advproc10   advproc133  advproc167  advproc20   advproc233  advproc38  advproc71
advproc100  advproc134  advproc168  advproc200  advproc234  advproc39  advproc72
advproc101  advproc135  advproc169  advproc201  advproc235  advproc4   advproc73
advproc102  advproc136  advproc17   advproc202  advproc236  advproc40  advproc74
advproc103  advproc137  advproc170  advproc203  advproc237  advproc41  advproc75
advproc104  advproc138  advproc171  advproc204  advproc238  advproc42  advproc76
advproc105  advproc139  advproc172  advproc205  advproc239  advproc43  advproc77
```

Stop the VCOM enabling

- Key in “sudo advman –o stop” to close the VCOM.



Frequently Asked Questions

Questions list

1. How many VCOM ports that I can create?
2. Why can not read the data from “/dev/vttyAP0”
3. Do I need to remove the VCOM driver before I remapping the VCOM?
4. How can I see the debug message on the console?

Question 1

- How many VCOM ports that I can create?
  - Ans: The maximum numbers of VCOM ports are up to 2 powers of 20.
  - Default value of ports is 255. Or you can revise it by yourself

key in “vim driver/advconf.h

```
root@ubuntu:/home/vcom/Desktop/vcom_linux_2.0.1# vim driver/advconf.h
```

The default setting is 255 ports

Question 2

- Why can not read the data from “/dev/vttyAP0”
  - Ans: we are changing the VCOM naming from “vttyAP” to “ttyADV”. You can read the data from “/dev/ttyADV0” .



VCOM 2.0 driver has changed the naming to /dev/ttyADV0.

Question 3

- Do I need to remove the VCOM driver before I remapping the VCOM?
  - Ans: No, you can use below command to remapping your VCOM without removing it. Key in “advman –o restart” to remapping the VCOM.



Question 4

- How can I see the debug message on the console?
  - Ans: You can manually apply a single VCOM mapping and see the debug message by using the vcomd command.
  - Key in "/usr/local/advtty/vcomd –t 3 –d 1522 –a 10.0.0.1 –p 1"

VCOM Port | Device Name | IP Address | Physical Ports on EKI

```
root@ubuntu:/home/vcom/Desktop/vcom_linux_2.0.1# /usr/local/advtty/vcomd -t 3 -d 1522 -a 10.0.0.1 -p 1
setting tty ID : 3 ...
setting device model : 1522 ...
setting IP addr : 10.0.0.1 ...
setting device port : 1 ...
```

/dev/ttyADV3 ⟷ EKI-1522-AE (IP: 10.0.0.1; COM 1)


Enabling an Intelligent Planet