Scaling Native Multimodal Pre-Training From Scratch

Haoyuan Wu[1,2], Aoqi Wu[2], Hai Wang[2], Jiajia Wu[2], Jinxiang Ou[2], Bei Yu[1]
[1]The Chinese University of Hong Kong [2]LLM Department, Tencent

arXiv:2607.22043v2 [cs.CL] 8 Oct 2026

Abstract

Although large language models (LLMs) exhibit remarkable reasoning capabilities, their reliance on text-only pre-training restricts the perception of the multimodal physical world. Native multimodal pre-training avoids this limitation by training models from scratch on multimodal inputs, thereby achieving deep cross-modal integration and mitigating optimization asymmetries inherent to traditional late-fusion architectures. Despite these advantages, the scaling properties of this paradigm remain incompletely characterized. To address this gap, we investigate the optimal model size and token count for training a Transformer-based vision-language model under a fixed computational budget. Our study demonstrates that minimal objective loss adheres to a predictable compute law, whereas compute-optimal model sizes and token counts scale as power laws. Notably, language and multimodal objectives manifest distinct allocation trends. The language allocation exponents lie in a similar range across the different data mixtures. The multimodal model-allocation exponent decreases modestly with the multimodal token ratio, indicating a relative shift toward token allocation. Additionally, our scaling analysis yields a budget-compensation rule. Specifically, an additional multimodal-token budget can offset the text-efficiency penalty caused by incorporating visual information into native multimodal pre-training under a fixed compute budget. Downstream evaluations further reveal that native multimodal pre-training is associated with improved spatial reasoning and multimodal few-shot learning. Generally, this empirical research establishes the essential groundwork for predictably scaling multimodal foundation models.

1 Introduction

Large language models (LLMs) (Google DeepMind, 2026; Anthropic, 2026; OpenAI, 2026) demonstrate remarkable reasoning and generation capabilities, establishing themselves as powerful foundation models. Despite these successes, text-only pre-training remains constrained by its inability to ground multimodal concepts in the physical world. Multimodal pre-training addresses this limitation by incorporating data from multiple modalities.

Currently, the dominant paradigm for multimodal pre-training relies on late fusion (Shukor et al., 2025). Typically, this approach couples a pre-trained language model with a vision encoder (Radford et al., 2021; Zhai et al., 2023; Tschannen et al., 2025) via a projection layer, followed by continued training on multimodal data (Kimi et al., 2026; Liu et al., 2023a; Lin et al., 2026). Although this strategy efficiently reuses pre-trained weights, it introduces a fundamental asymmetry. Specifically, vision and language representations are learned independently from distinct data distributions and under different optimization objectives.

To resolve this asymmetry, researchers explore native multimodal pre-training (Shukor et al., 2025; Cui et al., 2025). In this paradigm, models are trained from scratch on multimodal data, allowing vision and language representations to develop jointly. This approach raises a practical question: how should a fixed compute budget be allocated between model size and training tokens? For unimodal language models, this resource allocation is guided by compute-optimal scaling laws that dictate how to distribute a budget between model size and data (Kaplan et al., 2020; Hoffmann et al., 2022). However, it remains unclear whether native multimodal pre-training follows analogous scaling laws and whether the optimal allocations for language and multimodal objectives align or conflict.

To bridge this gap, we establish compute-optimal scaling laws for native multimodal pre-training. Specifically, we derive these laws using two estimators, IsoFLOP profiles and training-curve envelopes (Hoffmann et al., 2022). These estimators provide complementary views of the compute-optimal allocation. We demonstrate that the minimum loss for each objective follows a power law with a fitted offset, while compute-optimal model sizes and token counts scale as power laws (Kaplan et al., 2020; Hoffmann et al., 2022).

Fitting scaling laws separately for the language and multimodal objectives reveals different allocation trends across different data mixtures. The language allocation exponents remain in a similar range. For the multimodal objective, the model-allocation exponent decreases modestly as the multimodal token ratio increases, indicating relatively greater token allocation.

Furthermore, our central question is whether the extra multimodal compute budget can compensate for the text-efficiency penalty incurred by incorporating visual information under a fixed compute budget. We estimate this requirement by inverting jointly fitted text-loss compute frontiers with a common offset and decay exponent. The

resulting compensation rule expresses the required total compute as a mixture-dependent multiple of the pure-text reference budget. Across different data mixtures, the estimated compute increase is smaller than the increase associated with retaining the reference model size and text-token count and adding multimodal tokens.

Beyond scaling dynamics, we also evaluate the downstream implications of native multimodal pre-training across language and multimodal understanding tasks. Our findings indicate that native multimodal pre-training improves pure-text spatial reasoning, demonstrating that spatial understanding acquired through multimodal training successfully generalizes to unimodal text tasks. Moreover, this paradigm exhibits multimodal in-context learning capabilities analogous to those observed in traditional LLMs (Brown et al., 2020).

These results provide empirical guidance for scaling native multimodal pre-training. Our main contributions are summarized as follows:

- We independently analyze the scaling behaviors of language and multimodal objectives, revealing objective-specific allocation trends across different data mixtures.
- We derive a budget-compensation rule showing that the estimated additional compute needed to match pure-text loss is smaller than the compute increase associated with adding multimodal tokens.
- We empirically demonstrate that native multimodal pre-training improves pure-text spatial reasoning and enables robust multimodal in-context learning.

2 Preliminaries

2.1 Compute-Optimal Allocation

In this work, we revisit a fundamental problem in native multimodal pre-training: given a fixed computational budget C, how should resources be optimally allocated between the model size N (the number of activated non-embedding parameters) and the number of training tokens D? Furthermore, we investigate how this optimal trade-off is influenced by data composition, parameterized by the multimodal data ratio r. To formalize this problem, we model the final pre-training loss $L(N, D)$ as a function of N and D. Using the standard approximation $C = 6ND$, the computational budget is strictly determined by these two variables. Our objective is to minimize the loss under a fixed compute constraint:

$$N^{\text{opt}}(C), D^{\text{opt}}(C) = \underset{N,D \text{ s.t. } \text{FLOPs}(N,D)=C}{\arg\min} L(N, D), \tag{1}$$

where $N^{\text{opt}}(C)$ and $D^{\text{opt}}(C)$ denote the compute-optimal allocation for the given budget C. Given the lack of solid multimodal validation metrics, and because each token is seen roughly once during pre-training, we rely solely on the smoothed training loss as a proxy for the test loss, ensuring standardized evaluation across both language and multimodal objectives. In native multimodal pre-training, the language and multimodal objectives (L_{text} and L_{mm}) are optimized simultaneously using shared model parameters. It remains unclear whether the two objectives follow similar scaling laws or favor different compute allocations. To investigate this dynamic, we estimate compute-optimal allocation separately for each objective using the same jointly trained models. With $r = D_{\text{mm}}/D_{\text{text}}$, define $C_s = 6ND_s$ for $s \in \{\text{text}, \text{mm}\}$. Thus $D_{\text{total}} = (1 + r)D_{\text{text}}$ and $C_{\text{total}} = C_{\text{text}} + C_{\text{mm}} = (1 + r)C_{\text{text}}$. These are objective-specific compute coordinates; at $r = 0$, the total compute equals C_{text}. For both objectives, the compute-optimal model size and token count follow power laws:

$$N_s^{\text{opt}}(C_s; r) \propto C_s^{a_s(r)}, \qquad D_s^{\text{opt}}(C_s; r) \propto C_s^{b_s(r)}, \qquad a_s(r) + b_s(r) = 1. \tag{2}$$

2.2 Estimators of the Compute-Optimal Frontier

We estimate compute-optimal allocation for each objective in Equation (1) using two methods. The IsoFLOP profile method serves as our primary estimator, while the training-curve envelope provides a sensitivity check on the same training runs. For budget compensation, we invert the L_{text} frontier to compare the compute required to match pure-text loss with the budget associated with adding multimodal tokens. Budget selection is specified in Section B.1, and the estimators are detailed in Section B.2.

IsoFLOP profiles. At a predetermined compute budget C, plotting the loss of each model against $\log N$ generates an IsoFLOP profile. A quadratic fit in $\log N$ estimates the preferred model size $N^{\text{opt}}(C)$, subject to the observed size range. The optimal token count then follows algebraically as $D^{\text{opt}}(C) = C/(6N^{\text{opt}})$. Regressing $\log N^{\text{opt}}$ and $\log D^{\text{opt}}$ on $\log C$ yields the allocation exponents a and b. The fitted minimum interpolates across the evaluated model sizes at each budget.

Training curve envelope. For a fixed model size N, increasing D during training produces a trajectory of loss versus compute $C = 6ND$. Pooling the trajectories of all evaluated models and extracting the lower envelope yields the lowest observed loss at each evaluated budget C. Every point on this envelope corresponds to a specific




Figure 1: **IsoFLOP curves (language objective).** At each target budget C_{text}, we read the L_{text} of every model size at the token count satisfying $6ND_{\text{text}} = C_{\text{text}}$ and plot it against $\log N$. The fitted minima estimate compute-optimal model sizes within the observed range and determine the corresponding token counts.




Figure 2: **Training curve envelope (language objective).** Training curves span the evaluated model sizes and mixture ratios r. For each ratio, the lower envelope gives the lowest observed loss at each budget C_{text}; its selected model sizes and token counts determine the allocation estimates. The fitted loss frontier summarizes this envelope.

(N, D) configuration. Therefore, regressing $\log N$ and $\log D$ against $\log C$ across these points generates a second estimate of a and b from the same runs, providing a sensitivity check on the IsoFLOP fits. We provide more details in Section B.

The compute frontier $L(C)$. Along the lower envelope, we fit loss with a power law in compute:

$$L_s(C_s; r) = E_s(r) + \left(\frac{C_{c,s}(r)}{C_s}\right)^{\beta_s(r)}, \qquad s \in \{\text{text}, \text{mm}\}, \tag{3}$$

where $E_s(r)$ is a fitted loss offset, $C_{c,s}(r)$ is a characteristic compute scale, and $\beta_s(r)$ is a decay exponent distinct from the token-allocation exponent b_s. We fit these parameters using the procedure in Section B. This power law describes the frontier as a function of compute within the observed range.

2.3 Experimental Setup

Training data. Our model is trained on a mixture of text and multimodal datasets. The corpus contains 250B text tokens derived from web pages, books, academic papers, and other domains. Moreover, we construct a large-scale multimodal dataset comprising web-crawled image-text pairs and interleaved image-text documents. With images represented as continuous patch embeddings, the multimodal corpus contains 75B tokens.

Model architecture. We employ an MoE architecture based on a decoder-only Transformer. A single patch embedding layer maps images directly to continuous embeddings without a pre-trained vision encoder. Notably, we train these MoE models using an auxiliary-loss-free approach (Liu et al., 2024a). More implementation details are provided in Section A.

3 Scaling Native Multimodal Pre-Training

Building on our established estimators, we investigate the compute-optimal scaling behavior of native multimodal models. By decoupling the resource allocation problem into isolated objectives, we first examine how the mixture ratio r affects compute-optimal allocation for each objective. We then compare the additional compute needed to match pure-text loss with the compute increase associated with adding multimodal tokens.

3.1 The Language Objective

We first isolate the language objective L_{text} under the text-compute constraint C_{text}. As shown in Figures 1 and 2, the IsoFLOP profiles and training-curve envelopes reveal predictable loss frontiers across mixtures. The IsoFLOP




Figure 3: **Compute-optimal allocation (language objective).** (a) Optimal model size $N^{\text{opt}}_{\text{text}}$ and (b) optimal token count $D^{\text{opt}}_{\text{text}}$ as a function of the compute budget C_{text} for each r. Solid lines and stars represent the IsoFLOP fits and their respective minima, while thin dashed lines and scattered points provide a cross-check using the training envelope. (c) Allocation exponents $a_{\text{text}}(r)$ and $b_{\text{text}}(r)$ from both estimators. (d) Fitted compute frontiers $L_{\text{text}}(C_{\text{text}}; r)$. The two estimators give model-allocation exponents in a similar range across the measured ratios.




Figure 4: **IsoFLOP curves (multimodal objective).** At each target budget C_{mm}, we read the L_{mm} of every model size at the token count satisfying $6ND_{\text{mm}} = C_{\text{mm}}$ and plot it against $\log N$. The fitted minima estimate compute-optimal model sizes within the observed range and determine the corresponding token counts.




Figure 5: **Training curve envelope (multimodal objective).** Training curves span the evaluated model sizes and mixture ratios r. For each ratio, the lower envelope gives the lowest observed loss at each budget C_{mm}; its selected model sizes and token counts determine the allocation estimates. The fitted loss frontier summarizes this envelope.

allocation exponents remain close to $a_{\text{text}} \simeq 0.65$ and $b_{\text{text}} \simeq 0.35$, indicating a similar balance of model capacity and text tokens across different r. Figure 3 compares the two estimators; the fitting procedures are described in Section B.

3.2 The Multimodal Objective

Applying the same estimators to L_{mm} under C_{mm} reveals a shift in allocation. From $r = 0.1$ to 0.3, the IsoFLOP model-allocation exponent decreases from 0.686 to 0.622, while the token-allocation exponent increases from 0.314 to 0.378. The envelope estimates show the same direction of change. These results indicate a modest shift toward token allocation as the multimodal-to-text token ratio increases within the evaluated range.

3.3 Budget Compensation at a Fixed L_{text} Target

We now quantify the additional compute required for native multimodal pre-training to match a pure-text loss target. We compare this requirement with the compute budget associated with adding multimodal tokens while retaining the reference model size and text-token count.

A scaling rule for compensation. To obtain a compensation rule, we jointly fit the text-loss frontiers with a




Figure 6: **Compute-optimal allocation (multimodal objective).** (a) Optimal model size $N^{\text{opt}}_{\text{mm}}$ and (b) optimal token count $D^{\text{opt}}_{\text{mm}}$ as a function of the compute budget C_{mm} for each r. Solid lines and stars represent the IsoFLOP fits and their respective minima, while thin dashed lines and scattered points provide a cross-check using the training envelope. (c) Allocation exponents $a_{\text{mm}}(r)$ and $b_{\text{mm}}(r)$ from both estimators. (d) Fitted compute frontiers $L_{\text{mm}}(C_{\text{mm}}; r)$. The model-allocation exponents decrease modestly across different r.




Figure 7: **Budget compensation under the joint frontier fit.** Lines show the ratio Γ_r of required to available total compute; values below one indicate that the available budget exceeds the fitted requirement. Points transform empirical envelope losses using the fitted pure-text reference; open points and gray regions indicate reference extrapolation. The fitted factors remain below one over the common supported range.

common offset and decay exponent and a separate compute scale for each mixture:

$$\overline{L}_{\text{text}}(C_{\text{text}}; r) = \overline{E}_{\text{text}} + \left(\frac{\overline{C}_{c,\text{text}}(r)}{C_{\text{text}}} \right)^{\overline{\beta}_{\text{text}}}. \tag{4}$$

Bars distinguish this joint fit from the separate fits in Equation (3). The offset $\overline{E}_{\text{text}}$ and exponent $\overline{\beta}_{\text{text}}$ are constant across mixtures, so differences between frontiers are represented by $\overline{C}_{c,\text{text}}(r)$. The preceding figures use the separate frontier fits; the joint fitting procedure is described in Section B.4.

For the pure-text reference ($r = 0$), write $C_0 = C_{\text{text}}$ and set the target loss to $L^\star_{\text{text}} = \overline{L}_{\text{text}}(C_0; 0)$. Retaining the reference model size and text-token count and adding rD_{text} multimodal tokens increases the available total compute to $(1+r)C_0$ under the approximation $C = 6ND$. The mixture's text-compute requirement, obtained by inverting the joint frontier, is

$$\widehat{C}_{\text{text}}(L^\star_{\text{text}}; r) = \overline{C}_{c,\text{text}}(r) \left(L^\star_{\text{text}} - \overline{E}_{\text{text}} \right)^{-1/\overline{\beta}_{\text{text}}}. \tag{5}$$

Thus, $\widehat{C}_{\text{total}} = (1+r)\widehat{C}_{\text{text}}$, and the ratio of required to available total compute is

$$\Gamma_r = \frac{\widehat{C}_{\text{total}}(L^\star_{\text{text}}; r)}{(1+r)C_0} = \frac{\overline{C}_{c,\text{text}}(r)}{\overline{C}_{c,\text{text}}(0)}. \tag{6}$$

The added compute is sufficient when $\Gamma_r \leq 1$, or equivalently when

$$\widehat{C}_{\text{total}}(L^\star_{\text{text}}; r) - C_0 \leq rC_0. \tag{7}$$

Considering that the offset and decay exponent are constant across different data mixtures, Γ_r is independent of the target loss under this model.

Compensation across mixtures. As shown in Figure 7, we obtain $\Gamma_r \approx 0.952, 0.915$, and 0.899 at $r = 0.1, 0.2, 0.3$, respectively. The corresponding total-compute requirements, $(1+r)\Gamma_r C_0$, exceed the pure-text budget by approximately 4.7%, 9.8%, and 16.9%. These increases are smaller than the available compute increases of 10%, 20%, and 30%, respectively. Thus, for the fitted values,

$$0 < \widehat{C}_{\text{total}}(L^\star_{\text{text}}; r) - C_0 < rC_0. \tag{8}$$




Figure 8: **Text capabilities are preserved under native multimodal pre-training.** Average accuracy across 16 text benchmarks with varying multimodal data ratios r (fixed 250B text-token budget). (a) Text performance across model sizes N. (b) A3B text performance over training tokens D_{text}. The curves indicate broadly comparable aggregate performance at matched text-token budgets.

The fitted frontiers therefore imply a text-efficiency cost in total compute, which is smaller than the budget increase associated with adding multimodal tokens. Under the joint model, the absolute additional compute required to match the target is $[(1+r)\Gamma_r - 1]C_0$.

Observed variation across mixtures. Across the different r, Γ_r decreases from 0.952 to 0.899, indicating a larger relative margin within the available budget. However, the total-compute requirement relative to pure-text training, $(1+r)\Gamma_r$, increases from 1.047 to 1.169. A smaller Γ_r therefore does not imply a lower total cost.

This rule compares compute requirements along the model-family frontiers within their common fitted range. The available budget is defined by retaining the reference model size and text-token count, but achieving the fitted minimum may require a different allocation of that budget. The result therefore does not guarantee loss recovery at a fixed model size or under a fixed text-token constraint. Points outside the pure-text reference range in Figure 7 require extrapolation.

4 Downstream Implications

4.1 Evaluation of Base Models

Text capabilities. The evaluation of text capabilities is conducted using 16 distinct benchmarks.

- **Aggregate:** SuperGPQA(Du et al., 2025)(5-shot), MMLU-Redux(Hendrycks et al., 2020)(5-shot), MMLU-Pro(Wang et al., 2024b)(5-shot), and AGIEval$_{\text{en}}$(Zhong et al., 2023)(3-shot).
- **Coding:** HumanEval+(Liu et al., 2023b)(0-shot) and MBPP+(Liu et al., 2023b)(3-shot).
- **Mathematics:** GSM8K(Cobbe et al., 2021)(4-shot, CoT) and MATH(Lightman et al., 2023)(4-shot, CoT).
- **Logical Reasoning:** BBH(Suzgun et al., 2022)(3-shot, CoT) and SpatialEval(Wang et al., 2024a)(1-shot).
- **Knowledge:** NaturalQuestions(Kwiatkowski et al., 2019) (5-shot) and TriviaQA(Joshi et al., 2017)(5-shot).
- **Commonsense Reasoning:** SIQA(Sap et al., 2019)(0-shot), PIQA(Bisk et al., 2020)(0-shot), HellaSwag(Zellers et al., 2019)(10-shot), and WinoGrande(Sakaguchi et al., 2021)(5-shot).

Multimodal capabilities. The evaluation of multimodal capabilities is conducted using 23 distinct benchmarks.

- **Aggregate:** MMStar(Chen et al., 2024)(3-shot), MMMU(Yue et al., 2024)(3-shot), MMMU-Pro(Yue et al., 2025)(3-shot), MME(Fu et al., 2026)(3-shot), and MMBench$_{\text{en}}$(Liu et al., 2024b)(3-shot).
- **VQA:** VQAv2(Goyal et al., 2017)(1-shot) and TextVQA(Singh et al., 2019)(1-shot).
- **STEM:** MathVista(Lu et al., 2024)(3-shot), MathVerse(Zhang et al., 2024)(3-shot), and ScienceQA(Lu et al., 2022)(3-shot, CoT).
- **Doc Understanding:** HallusionBench(Guan et al., 2024)(3-shot), LogicVista(Xiao et al., 2024)(1-shot, CoT), AI2D(Kembhavi et al., 2016)(3-shot), and ChartQA(Masry et al., 2022)(3-shot).
- **Vision Knowledge:** MMBench$_{\text{cc}}$(Liu et al., 2024b)(3-shot) and SimpleVQA(Cheng et al., 2025)(3-shot).
- **Counting:** CountBench(0-shot)(Paiss et al., 2023) and CountQA(Tamarapalli et al., 2025)(1-shot).
- **Spatial Reasoning:** RealWorldQA(xAI, 2024)(3-shot), CV-Bench(Tong et al., 2024)(3-shot), OmniSpatial(Jia et al., 2025)(3-shot), SEAM(Tang et al., 2025)(3-shot), and SpatialEval(Wang et al., 2024a)(1-shot).

Evaluation protocol. For native multimodal pre-training, we evaluate the pre-trained models in an in-context learning setting. For multiple-choice tasks, we report accuracy by selecting the option that yields the lowest perplexity. Meanwhile, open-ended tasks are evaluated using the exact-match metric against reference answers, whereas coding tasks are evaluated using the Pass@1 metric.

Image processing. To accommodate the 4K-token context limit of our pre-trained models, we restrict the number of visual tokens per image. Specifically, images are partitioned into 32×32 patches and proportionally downscaled if the resulting grid exceeds the token budget. We allocate a maximum of 1536 tokens per image, reducing this limit to 512 tokens in few-shot scenarios to ensure both the templates and the test query fit within the context window.




Figure 9: **Multimodal pre-training enhances pure-text spatial reasoning.** Accuracy on SpatialEval's text-only abstract spatial-reasoning subtasks (Wang et al., 2024a), comparing baseline ($r = 0$) and multimodal ($r = 0.3$) settings. (a) Accuracy across model sizes N. (b) A3B accuracy over training tokens D_{text}. Multimodal models consistently outperform text-only baselines, with the performance gap widening at larger scales.




Figure 10: **Multimodal in-context learning emerges with model scaling.** (a) Average multimodal accuracy for 0-, 1-, and 3-shot settings across model sizes N. (b) Relative performance gains of k-shot settings over the 0-shot baseline. The increasing gains demonstrate that multimodal in-context learning emerges with model scaling.

Few-Shot examples. To ensure representative coverage, few-shot templates are sampled across distinct categories from each benchmark's development or training split. These templates are formatted as interleaved image-question-answer sequences and prepended to the test query.

4.2 Text Performance under Multimodal Pre-Training

A central concern in native multimodal pre-training is whether it compromises core language capabilities. To compare models at matched text exposure, we fix the text budget at 250B tokens and vary the multimodal budget from 0B (text-only, $r = 0$) to 75B ($r = 0.3$), evaluating models across six scales (N ranging from 71M to 3B).

Preservation of core language capabilities. Introducing multimodal data leaves aggregate text performance broadly comparable at matched text-token budgets. As shown in Figure 8, average accuracy across 16 text benchmarks remains consistent across all multimodal data ratios. This parity holds across the entire model family. Furthermore, models trained with different data ratios exhibit nearly identical performance trajectories throughout A3B training. These aggregate results show no large text-performance deterioration under this protocol.

Cross-modal transfer in spatial reasoning. The most compelling evidence of cross-modal transfer emerges in the abstract spatial reasoning subtasks of SpatialEval (Wang et al., 2024a) (MazeNav and SpatialMap). Although these queries are strictly text-based and lack visual input, incorporating multimodal tokens during pre-training yields substantial performance gains. As illustrated in Figure 9, multimodal models ($r = 0.3$) consistently outperform text-only baselines ($r = 0$). Notably, this advantage scales with model size. While smaller models (71M and 128M) exhibit marginal differences, the performance gap widens substantially for larger models up to 3B. This suggests that spatial and relational structures learned from visual modalities are embedded within the shared parameter space, successfully generalizing to enhance unimodal text comprehension.

4.3 Multimodal Few-Shot Learning

Beyond aggregate accuracy, we also investigate whether native multimodal pre-training endows base models with multimodal in-context learning. This allows models to leverage a few image-text templates during inference without parameter updates, analogous to text-only LLMs. We evaluate this across our entire model family, with model size N ranging from 71M to 3B. All models are trained on 250B text tokens and 75B multimodal tokens. Evaluations are conducted in 0-, 1-, and 3-shot settings. Given the instability of CoT reasoning in pre-trained base models under the zero-shot setting, we conduct our analysis of multimodal few-shot learning on 21 multimodal benchmarks. Full results are detailed in Tables 13 to 15.

In-context learning emerges with model scaling. Figure 10 demonstrates that the efficacy of in-context templates increases alongside model scale. At the smallest scale, these templates provide no measurable benefit; the 3-shot




Figure 11: **Few-shot accuracy under data scaling.** Average benchmark accuracy of each model in 0-, 1-, and 3-shot settings across total training tokens D_{total}. Although the performance trajectories remain overlapping throughout training for smaller models, the few-shot settings progressively outperform the 0-shot baseline in larger models.




Figure 12: **Few-shot trends by task category across model scale.** Each panel aggregates the benchmarks of one category and reports 0-, 1-, and 3-shot accuracy across model size N. The few-shot margin is largest and most consistent on spatial reasoning, modest on aggregate and vision-knowledge suites, and absent or negative on OCR/recognition benchmarks.

average is virtually identical to the 0-shot baseline, and a 1-shot evaluation slightly degrades performance. However, the performance gain scales positively with model capacity, increasing from near zero for the A71M model to +1.80 points for the A874M model, and ultimately reaching +2.43 points at the A3B scale. Furthermore, at the largest scale, aggregated accuracy consistently improves with shots. This progression mirrors the in-context learning capabilities observed in text-only LLMs, indicating that in-context learning capabilities emerge naturally from native multimodal pre-training.

In-context learning strengthens with data scaling. Figure 11 illustrates a similar trend across each model's training process. The performance margin afforded by few-shot prompting is initially absent; early in training, the 0-, 1-, and 3-shot evaluation curves are virtually indistinguishable. The expected hierarchical ordering, where an increased number of shots yields higher accuracy, only emerges during later stages of training. The onset of this divergence depends heavily on model capacity. For the A71M through A340M models, the performance curves remain overlapping throughout the entire training process. Conversely, for the A874M and A3B models, a clear performance gap emerges early and widens steadily as the training progresses. This indicates that in-context learning is acquired gradually, requiring both sufficient model scale and substantial training data to manifest.

Few-shot gains concentrate on spatial reasoning. Figure 12 demonstrates that the benefits of in-context learning vary considerably across task categories. The most pronounced and consistent improvements are observed in spatial-reasoning benchmarks, alongside notable gains in structured-diagram and aggregate evaluation suites. Conversely, performance on OCR- and recognition-oriented benchmarks plateaus or even degrades as in-context templates are introduced. This suggests that the templates primarily assist the model in resolving the spatial and relational structure of a query, rather than enhancing fine-grained visual recognition or text extraction. This phenomenon aligns with the cross-modal spatial-reasoning transfer discussed in Section 4.2. A detailed per-benchmark breakdown is provided in Section C.

Few-shot gain trends upward with training. Figure 13 plots the A3B few-shot gain against total training tokens D_{total} for each r. Although the per-checkpoint gains fluctuate, they show an overall upward trend as training progresses, and this holds for all three values of r. The 3-shot gains are generally larger than the 1-shot gains. Since




Figure 13: **Few-shot gain trends upward with training.** Few-shot gain of the A3B model over the 0-shot baseline for the 1-shot and 3-shot settings, shown for $r \in \{0.1, 0.2, 0.3\}$ against total training tokens D_{total}. Despite checkpoint-to-checkpoint fluctuations, the gains show an overall positive trend with D_{total} across all r.

the three r curves trend upward together, we read the few-shot gain as positively correlated with D_{total} rather than tied to any particular r. Together with Figure 11, this suggests that multimodal in-context learning strengthens as the model sees more training data.

5 Related Work

Multimodal pre-training paradigms. Most vision-language models adopt a late-fusion paradigm, coupling a pre-trained language model with a separately pre-trained vision encoder via a lightweight projection layer for subsequent adaptation on multimodal data (Radford et al., 2021; Zhai et al., 2023; Tschannen et al., 2025; Liu et al., 2023a; Lin et al., 2026; Kimi et al., 2026). Although this modular design efficiently reuses robust unimodal checkpoints, it introduces a fundamental asymmetry. Vision and language representations are learned independently from disparate data distributions and distinct training objectives, thereby constraining deep cross-modal integration. To address this limitation, emerging research investigates native multimodal pre-training, where a single model is trained from scratch on interleaved multimodal data to establish a unified representational space from the outset (Shukor et al., 2025; Cui et al., 2025; Tong et al., 2026). Our work adopts this paradigm by eliminating the vision encoder; instead, a single projection layer maps images into continuous patch embeddings for direct processing by a decoder-only Transformer. We focus on compute-optimal scaling of native multimodal models.

Compute-optimal scaling laws. Scaling laws characterize the predictable relationship between model performance, scale, training data, and compute, offering principled guidance for resource allocation under fixed training budgets. For unimodal language models, Kaplan et al. (2020) first establish power-law relationships between loss and scale. Subsequently, Hoffmann et al. (2022) refine the compute-optimal frontier using IsoFLOP profiles and training-curve envelopes, demonstrating that model size and training tokens should scale proportionally. These frameworks are the standard methodology for performance extrapolation and compute allocation. However, existing analyses predominantly focus on unimodal settings with fixed data distributions. Consequently, compute-optimal allocation for jointly optimizing heterogeneous modalities within one model remains incompletely characterized. Shukor et al. (2025) investigate scaling behaviors for native multimodal models, and they model the training objective as a single aggregate loss. In contrast, we decouple the language and multimodal objectives and employ both IsoFLOP profiles and training-curve envelopes as complementary estimation methods (Hoffmann et al., 2022; Shukor et al., 2026). Our findings describe objective-specific allocation trends across the different data mixtures. Inverting the text-loss frontiers also quantifies the compute required to match a pure-text loss target at the evaluated ratios.

6 Conclusion

In this work, we establish compute-optimal scaling laws for native multimodal pre-training, systematically characterizing its scaling behavior. By estimating separate frontiers for the language and multimodal objectives, we demonstrate predictable scaling with different allocation trends across data mixtures. Language allocation exponents remain in a similar range, while the multimodal objective favors relatively greater token allocation as the multimodal token ratio increases. Under the joint frontier model, the additional compute required to match pure-text loss is smaller than the compute increase associated with retaining the reference model size and text-token count and adding multimodal tokens. Beyond scaling, our experiments show that native multimodal pre-training retains broadly comparable aggregate text performance at matched text-token budgets, with spatial-reasoning improvements and multimodal few-shot learning. These findings connect compute allocation, text-loss budget compensation, and downstream performance to guide native multimodal pre-training.

References

Anthropic. Claude Opus 4.8. https://www.anthropic.com/claude/opus, 2026.

Yonatan Bisk, Rowan Zellers, Jianfeng Gao, Yejin Choi, et al. PIQA: Reasoning about Physical Commonsense in Natural Language. In *AAAI Conference on Artificial Intelligence (AAAI)*, volume 34, pp. 7432–7439, 2020.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language Models are Few-Shot Learners. In *Annual Conference on Neural Information Processing Systems (NIPS)*, 2020.

Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Zehui Chen, Haodong Duan, Jiaqi Wang, Yu Qiao, Dahua Lin, et al. Are We on the Right Way for Evaluating Large Vision-Language Models? In *Annual Conference on Neural Information Processing Systems (NIPS)*, 2024.

Xianfu Cheng, Wei Zhang, Shiwei Zhang, Jian Yang, Xiangyuan Guan, Xianjie Wu, Xiang Li, Ge Zhang, Jiaheng Liu, Yuying Mai, et al. SimpleVQA: Multimodal Factuality Evaluation for Multimodal Large Language Models. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training Verifiers to Solve Math Word Problems. *arXiv preprint arXiv:2110.14168*, 2021.

Yufeng Cui, Honghao Chen, Haoge Deng, Xu Huang, Xinghang Li, Jirong Liu, Yang Liu, Zhuoyan Luo, Jinsheng Wang, Wenxuan Wang, et al. Emu3.5: Native Multimodal Models are World Learners. *arXiv preprint arXiv:2510.26583*, 2025.

Xinrun Du, Yifan Yao, Kaijing Ma, Bingli Wang, Tianyu Zheng, King Zhu, Minghao Liu, Yiming Liang, Xiaolong Jin, Zhenlin Wei, et al. SuperGPQA: Scaling LLM Evaluation Across 285 Graduate Disciplines. *arXiv preprint arXiv:2502.14739*, 2025.

Chaoyou Fu, Peixian Chen, Yunhang Shen, Yulei Qin, Mengdan Zhang, Xu Lin, Jinrui Yang, Xiawu Zheng, Ke Li, Xing Sun, et al. MME: A Comprehensive Evaluation Benchmark for Multimodal Large Language Models. In *Annual Conference on Neural Information Processing Systems (NIPS)*, 2026.

Google DeepMind. Gemini 3.1 Pro. https://deepmind.google/technologies/gemini/pro, 2026.

Yash Goyal, Tejas Khot, Douglas Summers-Stay, Dhruv Batra, and Devi Parikh. Making the V in VQA Matter: Elevating the Role of Image Understanding in Visual Question Answering. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017.

Tianrui Guan, Fuxiao Liu, Xiyang Wu, Ruiqi Xian, Zongxia Li, Xiaoyu Liu, Xijun Wang, Lichang Chen, Furong Huang, Yaser Yacoob, et al. Hallusionbench: An Advanced Diagnostic Suite for Entangled Language Hallucination and Visual Illusion in Large Vision-Language Models. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring Massive Multitask Language Understanding. *arXiv preprint arXiv:2009.03300*, 2020.

Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, DDL Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, et al. Training Compute-Optimal Large Language Models. *arXiv preprint arXiv:2203.15556*, 2022.

Mengdi Jia, Zekun Qi, Shaochen Zhang, Wenyao Zhang, Xinqiang Yu, Jiawei He, He Wang, and Li Yi. OmniSpatial: Towards Comprehensive Spatial Reasoning Benchmark for Vision Language Models. *arXiv preprint arXiv:2506.03135*, 2025.

Mandar Joshi, Eunsol Choi, Daniel S Weld, and Luke Zettlemoyer. TriviaQA: A Large Scale Distantly Supervised Challenge Dataset for Reading Comprehension. *arXiv preprint arXiv:1705.03551*, 2017.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling Laws for Neural Language Models. *arXiv preprint arXiv:2001.08361*, 2020.

Aniruddha Kembhavi, Mike Salvato, Eric Kolve, Minjoon Seo, Hannaneh Hajishirzi, and Ali Farhadi. A Diagram Is Worth A Dozen Images. In *European Conference on Computer Vision (ECCV)*, 2016.

Kimi, Tongtong Bai, Yifan Bai, Yiping Bao, SH Cai, Yuan Cao, Y Charles, HS Che, Cheng Chen, Guanduo Chen, et al. Kimi K2.5: Visual Agentic Intelligence. *arXiv preprint arXiv:2602.02276*, 2026.

Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, et al. Natural Questions: A Benchmark for Question Answering Research. *Transactions of the Association for Computational Linguistics*, 7:453–466, 2019.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's Verify Step by Step. In *International Conference on Learning Representations (ICLR)*, 2023.

Bin Lin, Zhenyu Tang, Yang Ye, Jinfa Huang, Junwu Zhang, Yatian Pang, Peng Jin, Munan Ning, Jiebo Luo, and Li Yuan. MoE-LLaVA: Mixture of Experts for Large Vision-Language Models. *IEEE Transactions on Multimedia*, 2026.

Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, et al. DeepSeek-V3 Technical Report. *arXiv preprint arXiv:2412.19437*, 2024a.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual Instruction Tuning. In *Annual Conference on Neural Information Processing Systems (NIPS)*, 2023a.

Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. Is Your Code Generated by ChatGPT Really Correct? Rigorous Evaluation of Large Language Models for Code Generation. In *Annual Conference on Neural Information Processing Systems (NIPS)*, volume 36, pp. 21558–21572, 2023b.

Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, et al. MMBench: Is Your Multi-Modal Model an All-Around Player? In *European Conference on Computer Vision (ECCV)*, 2024b.

Pan Lu, Swaroop Mishra, Tanglin Xia, Liang Qiu, Kai-Wei Chang, Song-Chun Zhu, Oyvind Tafjord, Peter Clark, and Ashwin Kalyan. Learn to explain: Multimodal Reasoning via Thought Chains for Science Question Answering. In *Annual Conference on Neural Information Processing Systems (NIPS)*, 2022.

Pan Lu, Hritik Bansal, Tony Xia, Jiacheng Liu, Chunyuan Li, Hannaneh Hajishirzi, Hao Cheng, Kai-Wei Chang, Michel Galley, and Jianfeng Gao. MathVista: Evaluating Mathematical Reasoning of Foundation Models in Visual Contexts. In *International Conference on Learning Representations (ICLR)*, 2024.

Ahmed Masry, Xuan Long Do, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. ChartQA: A Benchmark for Question Answering about Charts with Visual and Logical Reasoning. In *Annual Meeting of the Association for Computational Linguistics (ACL)*, 2022.

OpenAI. GPT 5.5. https://openai.com/index/introducing-gpt-5-5, 2026.

Roni Paiss, Ariel Ephrat, Omer Tov, Shiran Zada, Inbar Mosseri, Michal Irani, and Tali Dekel. Teaching Clip to Count to Ten. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning Transferable Visual Models From Natural Language Supervision. In *International Conference on Machine Learning (ICML)*, 2021.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An Adversarial Winograd Schema Challenge at Scale. *Communications of the ACM*, 64(9):99–106, 2021.

Maarten Sap, Hannah Rashkin, Derek Chen, Ronan LeBras, and Yejin Choi. SocialiQA: Commonsense Reasoning about Social Interactions. *arXiv preprint arXiv:1904.09728*, 2019.

Mustafa Shukor, Enrico Fini, Victor Guilherme Turrisi da Costa, Matthieu Cord, Joshua Susskind, and Alaaeldin El-Nouby. Scaling Laws for Native Multimodal Models. In *IEEE International Conference on Computer Vision (ICCV)*, 2025.

Mustafa Shukor, Louis Bethune, Dan Busbridge, David Grangier, Enrico Fini, Alaaeldin El-Nouby, and Pierre Ablin. Scaling Laws for Optimal Data Mixtures. In *Annual Conference on Neural Information Processing Systems (NIPS)*, 2026.

Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. Towards VQA Models That Can Read. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung, Aakanksha Chowdhery, Quoc V Le, Ed H Chi, Denny Zhou, et al. Challenging Big-Bench Tasks and Whether Chain-of-Thought Can Solve Them. *arXiv preprint arXiv:2210.09261*, 2022.

Jayant Sravan Tamarapalli, Rynaa Grover, Nilay Pande, and Sahiti Yerramilli. CountQA: How Well Do MLLMs Count in the Wild? *arXiv preprint arXiv:2508.06585*, 2025.

Zhenwei Tang, Difan Jiao, Blair Yang, and Ashton Anderson. SEAM: Semantically Equivalent Across Modalities Benchmark for Vision-Language Models. In *Conference on Language Modeling (COLM)*, 2025.

Shengbang Tong, Ellis Brown, Penghao Wu, Sanghyun Woo, Manoj Middepogu, Sai C Akula, Jihan Yang, Shusheng Yang, Adithya Iyer, Xichen Pan, et al. Cambrian-1: A Fully Open, Vision-Centric Exploration of Multimodal LLMs. In *Annual Conference on Neural Information Processing Systems (NIPS)*, 2024.

Shengbang Tong, David Fan, John Nguyen, Ellis Brown, Gaoyue Zhou, Shengyi Qian, Boyang Zheng, Théophane Vallaeys, Junlin Han, Rob Fergus, et al. Beyond Language Modeling: An Exploration of Multimodal Pretraining. *arXiv preprint arXiv:2603.03276*, 2026.

Michael Tschannen, Alexey Gritsenko, Xiao Wang, Muhammad Ferjad Naeem, Ibrahim Alabdulmohsin, Nikhil Parthasarathy, Talfan Evans, Lucas Beyer, Ye Xia, Basil Mustafa, et al. SigLIP 2: Multilingual Vision-Language Encoders with Improved Semantic Understanding, Localization, and Dense Features. *arXiv preprint arXiv:2502.14786*, 2025.

Jiayu Wang, Yifei Ming, Zhenmei Shi, Vibhav Vineet, Xin Wang, Yixuan Li, and Neel Joshi. Is a Picture Worth a Thousand Words? Delving into Spatial Reasoning for Vision Language Models. In *Annual Conference on Neural Information Processing Systems (NIPS)*, 2024a.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, et al. MMLU-Pro: A More Robust and Challenging Multi-Task Language Understanding Benchmark. In *Annual Conference on Neural Information Processing Systems (NIPS)*, 2024b.

xAI. RealWorldQA. https://huggingface.co/datasets/xai-org/RealworldQA, 2024.

Yijia Xiao, Edward Sun, Tianyu Liu, and Wei Wang. Logicvista: Multimodal LLM Logical Reasoning Benchmark in Visual Contexts. *arXiv preprint arXiv:2407.04973*, 2024.

Xiang Yue, Yuansheng Ni, Kai Zhang, Tianyu Zheng, Ruoqi Liu, Ge Zhang, Samuel Stevens, Dongfu Jiang, Weiming Ren, Yuxuan Sun, et al. MMMU: A Massive Multi-Discipline Multimodal Understanding and Reasoning Benchmark for Expert AGI. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

Xiang Yue, Tianyu Zheng, Yuansheng Ni, Yubo Wang, Kai Zhang, Shengbang Tong, Yuxuan Sun, Botao Yu, Ge Zhang, Huan Sun, et al. MMMU-Pro: A More Robust Multi-Discipline Multimodal Understanding Benchmark. In *Annual Meeting of the Association for Computational Linguistics (ACL)*, 2025.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. Hellaswag: Can A Machine Really Finish Your Sentence? *arXiv preprint arXiv:1905.07830*, 2019.

Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid Loss for Language Image Pre-Training. In *IEEE International Conference on Computer Vision (ICCV)*, 2023.

Renrui Zhang, Dongzhi Jiang, Yichi Zhang, Haokun Lin, Ziyu Guo, Pengshuo Qiu, Aojun Zhou, Pan Lu, Kai-Wei Chang, Yu Qiao, et al. MathVerse: Does Your Multi-Modal LLM Truly See the Diagrams in Visual Math Problems? In *European Conference on Computer Vision (ECCV)*, 2024.

Wanjun Zhong, Ruixiang Cui, Yiduo Guo, Yaobo Liang, Shuai Lu, Yanlin Wang, Amin Saied, Weizhu Chen, and Nan Duan. AGIEval: A Human-Centric Benchmark for Evaluating Foundation Models. *arXiv preprint arXiv:2304.06364*, 2023.

A Implementation Details

For native multimodal pre-training, we employ the Muon optimizer with a weight decay of 0.1 and a gradient clipping threshold of 1.0. Additionally, we utilize a warmup-stable learning rate schedule, a global batch size of 8M tokens, and a maximum sequence length of 4096. The training loss is computed only on text tokens, with vision tokens masked out from loss computation (Kimi et al., 2026). We detail the specific architecture configurations and training settings in Table 1.

Table 1: **Pre-training hyperparameters.** We detail the hyperparameters used for pre-training different model configurations to derive scaling laws.

	A71M	A128M	A340M	A590M	A874M	A3B
Architecture Configurations						
layers	11	15	19	23	27	48
hidden size	640	768	1152	1280	1536	2048
FFN hidden size	2048	2048	3072	4096	4096	6912
attention heads	8	12	16	20	24	32
query groups	4					
kv channels	128					
total experts	128					
activated experts	8					
expert FFN hidden size	256	256	384	512	512	768
shared-expert hidden size	256	256	384	512	512	768
MoE layer	first layer dense, remaining layers MoE					
Training Settings						
batch size (sequences)	2048					
sequence length	4096					
warmup steps	2000					
learning rate	2.6e-3	1.9e-3	1.1e-3	8.2e-4	6.8e-4	3.0e-4

B Scaling-Law Fitting and Budget Compensation

In the estimator formulas below, we suppress the objective index and mixture argument only within a fixed (s, r) calculation: C denotes C_s, D denotes D_s, and E, C_c, β denote $E_s(r), C_{c,s}(r), \beta_s(r)$. Compute is measured in FLOPs. The amplitude is $K_s = C_{c,s}^{\beta_s}$; it differs from the characteristic compute scale $C_{c,s}$. Allocation exponents are $a_s(r), b_s(r)$, and quadratic coefficients are $p_{j,s}$ for $j = 0, 1, 2$. In the budget-compensation analysis, C_0 denotes the pure-text reference budget, hats denote the compute required at a specified target loss, and bars identify jointly fitted frontier parameters. In this section, we describe the methods used to estimate the compute-optimal allocation in Section 3 and derive budget compensation from the L_{text} fits.

B.1 Data Preprocessing

With $T = 2048 \times 4096 \approx 8$M tokens per optimizer step, the total token count at step k is $D_{\text{total}} = Tk$. Define $D_{\text{text}} = D_{\text{total}}/(1+r)$ and $D_{\text{mm}} = rD_{\text{total}}/(1+r)$, with $C_s = 6ND_s$. The multimodal fits exclude $r = 0$. For each objective-mixture pair, we construct candidate budgets uniformly in $\log C_s$ between $\min_m C_{s,m}^{\min}$ and $\max_m C_{s,m}^{\max}$. At budget C, let

$$\mathcal{M}(C) = \{m : C_{s,m}^{\min} \le C \le C_{s,m}^{\max}\}. \tag{9}$$

Retain only budgets with $|\mathcal{M}(C)| \ge 3$.

B.2 Estimating Compute-Optimal Allocation

IsoFLOP profiles. We construct IsoFLOP profiles by comparing smoothed training losses across model sizes at matched compute budgets. At each budget C, we fit a quadratic in $\log N$:

$$L(\log N \mid C) = p_2(\log N)^2 + p_1 \log N + p_0. \tag{10}$$

For a convex fit, the minimum gives

$$\log N^{\text{opt}}(C) = -\frac{p_1}{2p_2}, \tag{11}$$

clipped to the observed range of $\log N$. The corresponding optimal token count is $D^{\text{opt}}(C) = C/(6N^{\text{opt}}(C))$. We then regress $\log N^{\text{opt}}$ and $\log D^{\text{opt}}$ on $\log C$ to estimate the allocation exponents a and b, with $a + b = 1$.

Training-curve envelope. We construct an equal-FLOPs envelope by selecting the lowest smoothed training loss across model sizes at each evaluated compute budget. Each envelope point retains its associated model

size and objective-specific token count. Regressing their logarithms on $\log C$ provides a second estimate of the allocation exponents. Both estimators use the same runs, so their agreement provides a sensitivity check rather than independent validation. Their allocation exponents are compared in Section 3. The equal-compute envelope is

$$L_s^{\text{envelope}}(C; r) = \min_{m \in \mathcal{M}(C)} \widetilde{L}_{s,m}(C; r), \tag{12}$$

where $\widetilde{L}$ is the within-model interpolated loss. Retain the selected model size N and set $D = C/(6N)$ at each budget. Regressing the selected $\log N$ and $\log D$ on $\log C$ yields the envelope allocation exponents; fitting $L_s^{\text{envelope}}(C; r)$ yields the distinct frontier parameters.

B.3 Fitting Loss-Compute Frontiers

We fit the equal-FLOPs envelope using the power law in Equation (3),

$$L(C) = E + (C_c/C)^{\beta}, \tag{13}$$

where E is a fitted loss offset over the observed compute interval, C_c is a characteristic compute scale, and β is the decay exponent. We estimate the parameters through a grid search over β. For each candidate, we write

$$L(C) = E + KC^{-\beta}, \qquad K = C_c^{\beta}, \tag{14}$$

and solve for (E, K) by ordinary least squares in loss space. We reject $K \leq 0$ or non-positive predictions at the fitted budgets, select the candidate with the smallest mean squared log-loss residual, and recover $C_c = K^{1/\beta}$. This is a two-stage selection procedure rather than joint least squares in log loss; the implementation does not impose $E > 0$. All reproduced nominal fits have positive offsets. Each mixture is fitted independently, with its own loss offset.

B.4 Compensation Model

We jointly fit the text-loss envelopes using the model in Equation (4). The offset $\overline{E}_{\text{text}}$ and decay exponent $\overline{\beta}_{\text{text}}$ are shared across mixtures, while $\overline{C}_{c,\text{text}}(r)$ is estimated separately for each ratio. The parameters minimize the unweighted squared residuals in loss space:

$$\min_{\theta} \sum_i \left[L_{\text{text},i} - \overline{L}_{\text{text}}(C_{\text{text},i}; r_i)\right]^2, \tag{15}$$

where i indexes the envelope observations and θ contains all fitted parameters. For numerical optimization, we parameterize the scales by $\eta(r) = \overline{\beta}_{\text{text}} \log[\overline{C}_{c,\text{text}}(r)/(10^{20}\,\text{FLOPs})]$, with bounds $\overline{E}_{\text{text}} \in [0, 2.2]$, $\overline{\beta}_{\text{text}} \in [0.01, 0.6]$, and $\eta(r) \in [-10, 5]$. No ordering constraint is imposed across mixtures. The fitted compute scales determine the compensation factors through Equation (6); compensation is not imposed during fitting. Each factor describes an evaluated mixture, without assuming a continuous dependence on r.

C Experimental Results

This section reports per-benchmark results supporting Section 4 in three groups. First, we present the training dynamics of the A3B model, evaluating text and multimodal performance at successive pre-training token budgets across multimodal data ratios $r \in \{0, 0.1, 0.2, 0.3\}$ (Tables 2 to 8). Second, we report the final text performance across the entire model family, scaling from A71M to A3B, for each data ratio (Tables 9 to 12). Third, we evaluate multimodal in-context learning, providing per-benchmark accuracies for the 0-, 1-, and 3-shot settings across all model capacities (Tables 13 to 15). All aggregate scores represent unweighted means across the constituent benchmarks. The few-shot tables average all 23 multimodal tasks, whereas the curves in Section 4 average 21 tasks, excluding ScienceQA and LogicVista because their CoT evaluations are unstable without in-context examples.

Table 2: **Performance on text benchmarks at different pre-training token budgets for A3B models. The models are trained with 250B text tokens.**

	Total tokens D_{total}	25B	50B	75B	100B	125B	150B	175B	200B	225B	250B
Aggregate	MMLU-Redux (Acc.)	27.07	41.26	46.77	49.86	52.39	53.02	54.35	55.65	56.42	57.79
	MMLU-Pro (Acc.)	10.80	14.25	16.68	17.64	20.10	21.28	21.86	24.09	24.26	24.88
	$\text{AGIEval}_{\text{en}}$ (Acc.)	19.53	26.20	28.55	30.70	34.21	34.36	36.26	35.74	35.13	36.96
	SuperGPQA (Acc.)	10.00	13.29	14.71	17.00	16.70	18.83	20.16	19.81	20.33	19.95
Coding	HumanEval+ (Pass@1)	9.15	12.80	13.41	16.46	14.63	18.90	16.46	14.63	18.90	20.73
	MBPP+ (Pass@1)	17.72	34.92	34.66	40.48	47.09	48.68	47.35	50.26	51.59	48.68
Mathematics	GSM8K (Pass@1)	6.52	16.22	27.60	35.78	35.25	39.80	43.90	46.02	49.73	48.75
	MATH (Pass@1)	5.40	10.30	14.90	17.40	19.10	20.10	22.10	21.55	25.00	26.70
Logical Reasoning	BBH (EM)	29.84	30.08	34.46	35.56	38.66	40.26	41.06	43.39	39.76	44.97
	SpatialEval (Acc.)	27.70	33.04	31.74	34.59	29.94	34.80	38.19	37.93	40.28	35.95
Knowledge	NaturalQuestions (EM)	10.42	15.24	18.70	20.72	20.19	20.11	22.94	22.63	22.91	22.74
	TriviaQA (EM)	21.81	33.33	40.42	46.94	47.08	51.25	52.36	54.58	54.58	56.11
Commonsense Reasoning	HellaSwag (Acc.)	52.73	61.00	65.10	66.80	68.83	69.07	70.40	70.87	71.67	71.57
	SIQA (Acc.)	33.52	47.34	52.56	56.29	56.35	58.60	58.24	59.72	61.26	60.24
	PIQA (Acc.)	71.27	73.83	74.97	76.39	77.04	77.86	77.20	78.67	77.97	78.35
	WinoGrande (Acc.)	52.88	55.56	56.27	56.83	57.06	60.06	60.77	60.38	59.83	61.96
Average		25.40	32.42	35.72	38.71	39.66	41.69	42.73	43.49	44.35	44.77

Table 3: **Performance on text benchmarks at different pre-training token budgets for A3B models. The models are trained with 250B text tokens and 25B multimodal tokens.**

	Total tokens D_{total}	25B	50B	75B	100B	125B	150B	175B	200B	225B	250B	275B
Aggregate	MMLU-Redux (Acc.)	28.65	37.00	44.88	49.72	51.23	52.51	53.54	54.14	54.74	55.54	56.84
	MMLU-Pro (Acc.)	11.14	13.41	16.67	17.92	20.34	22.11	21.71	23.07	24.71	25.42	25.29
	$\text{AGIEval}_{\text{en}}$ (Acc.)	21.15	23.49	26.53	30.15	33.32	33.24	33.11	33.78	35.16	35.60	37.38
	SuperGPQA (Acc.)	10.03	12.77	15.42	15.84	18.07	17.89	18.56	19.21	19.87	20.77	20.31
Coding	HumanEval+ (Pass@1)	6.71	6.10	11.59	14.02	12.80	20.73	18.90	19.51	18.29	17.07	19.51
	MBPP+ (Pass@1)	16.14	28.57	34.13	40.48	43.12	46.03	48.15	50.53	51.59	52.65	53.97
Mathematics	GSM8K (Pass@1)	5.00	14.86	25.47	33.36	38.51	38.44	42.91	48.98	48.22	48.67	50.49
	MATH (Pass@1)	7.20	11.75	14.60	17.20	19.60	21.15	23.20	24.85	25.40	25.85	25.60
Logical Reasoning	BBH (EM)	26.54	33.29	34.45	36.66	38.85	38.71	41.83	42.59	44.25	43.08	43.60
	SpatialEval (Acc.)	26.68	32.37	32.31	31.39	38.87	39.63	38.52	39.34	38.65	39.78	39.28
Knowledge	NaturalQuestions (EM)	10.69	15.32	18.84	18.78	19.45	21.22	23.41	24.76	24.27	24.71	23.49
	TriviaQA (EM)	21.11	33.33	38.06	44.44	47.64	49.44	51.11	55.42	55.97	54.44	57.92
Commonsense Reasoning	HellaSwag (Acc.)	51.47	61.50	64.43	66.87	68.03	69.13	69.97	70.53	71.37	70.83	71.30
	SIQA (Acc.)	35.11	45.55	50.51	54.96	52.92	58.96	55.94	55.48	59.16	56.86	62.54
	PIQA (Acc.)	71.33	75.03	75.30	76.33	76.88	77.53	75.95	77.97	77.75	78.29	77.80
	WinoGrande (Acc.)	52.01	56.83	57.46	58.72	58.64	57.85	59.51	61.01	62.83	62.12	62.67
Average		25.06	31.32	35.04	37.93	39.89	41.54	42.27	43.82	44.51	44.48	45.50

Table 4: **Performance on text benchmarks at different pre-training token budgets for A3B models. The models are trained with 250B text tokens and 50B multimodal tokens.**

	Total tokens D_{total}	25B	50B	75B	100B	125B	150B	175B	200B	225B	250B	275B	300B
Aggregate	MMLU-Redux (Acc.)	26.19	40.39	46.39	48.00	49.81	52.39	52.46	54.39	55.60	56.09	55.89	56.68
	MMLU-Pro (Acc.)	11.28	12.58	17.01	18.24	18.23	19.75	21.88	21.05	21.17	19.85	24.18	23.93
	$\text{AGIEval}_{\text{en}}$ (Acc.)	21.48	23.11	28.85	29.50	31.59	32.48	34.79	33.80	33.56	34.25	36.55	36.32
	SuperGPQA (Acc.)	10.17	12.64	14.06	16.02	15.74	17.50	18.31	18.43	19.22	20.55	20.98	20.52
Coding	HumanEval+ (Pass@1)	7.93	11.59	14.63	17.68	18.29	18.90	21.95	20.12	20.73	19.51	18.90	20.12
	MBPP+ (Pass@1)	14.55	26.19	33.33	42.33	42.86	47.09	47.35	46.56	48.94	48.41	50.79	51.85
Mathematics	GSM8K (Pass@1)	5.61	15.24	23.50	30.33	37.07	36.01	44.66	49.28	50.27	52.92	50.57	53.90
	MATH (Pass@1)	5.25	10.00	14.25	16.20	17.25	19.85	21.30	22.50	22.95	25.30	24.15	25.35
Logical Reasoning	BBH (EM)	27.59	27.13	31.29	37.16	38.27	40.99	40.33	40.12	42.04	43.09	44.10	45.44
	SpatialEval (Acc.)	30.41	33.65	37.61	36.87	35.04	32.48	33.13	34.72	37.37	34.89	35.91	38.04
Knowledge	NaturalQuestions (EM)	10.89	14.21	17.31	20.83	20.33	21.16	22.11	20.33	22.33	21.88	21.16	21.44
	TriviaQA (EM)	19.72	27.64	34.31	42.22	47.64	48.89	49.31	54.72	51.67	56.53	56.67	57.50
Commonsense Reasoning	HellaSwag (Acc.)	51.67	59.77	63.67	66.90	67.60	69.23	68.60	70.30	70.77	71.10	72.00	71.60
	SIQA (Acc.)	33.88	42.94	45.29	53.22	54.55	56.24	56.40	56.96	59.21	58.39	60.59	60.29
	PIQA (Acc.)	70.95	74.32	75.46	76.99	77.04	77.91	78.13	79.22	78.40	78.62	78.18	78.73
	WinoGrande (Acc.)	52.49	55.41	55.72	59.43	59.83	60.38	61.64	61.64	61.56	64.01	62.67	61.64
Average		25.00	30.43	34.54	38.24	39.45	40.70	42.02	42.76	43.49	44.09	44.58	45.21

Table 5: **Performance on text benchmarks at different pre-training token budgets for A3B models. The models are trained with 250B text tokens and 75B multimodal tokens.**

	Total tokens D_{total}	25B	50B	75B	100B	125B	150B	175B	200B	225B	250B	275B	300B	325B
Aggregate	MMLU-Redux (Acc.)	27.05	38.81	44.74	48.35	51.19	51.37	54.49	54.21	55.05	56.00	57.18	57.09	57.98
	MMLU-Pro (Acc.)	10.85	12.99	17.73	19.19	19.86	20.21	22.03	23.84	24.61	24.92	25.33	27.53	27.68
	$\text{AGIEval}_{\text{en}}$ (Acc.)	20.49	22.71	27.88	29.27	32.13	32.66	36.03	36.58	35.02	35.99	37.11	36.92	37.73
	SuperGPQA (Acc.)	10.78	13.48	14.92	16.88	18.11	18.27	18.69	19.63	20.17	20.63	21.08	21.53	22.00
Coding	HumanEval+ (Pass@1)	6.10	11.59	15.24	14.63	15.24	15.24	13.42	18.90	19.51	15.85	17.68	21.34	21.34
	MBPP+ (Pass@1)	18.52	26.98	31.48	37.83	41.27	47.09	46.03	48.94	49.47	48.94	49.74	53.44	54.23
Mathematics	GSM8K (Pass@1)	4.85	17.21	22.21	30.63	37.00	36.01	42.15	43.82	48.07	50.19	49.58	51.40	52.39
	MATH (Pass@1)	5.95	10.60	14.05	16.05	19.00	19.70	20.65	21.80	22.60	23.90	24.65	25.00	26.30
Logical Reasoning	BBH (EM)	29.21	29.44	33.50	33.93	34.28	36.56	40.07	39.49	39.08	42.94	43.82	43.68	40.84
	SpatialEval (Acc.)	29.85	32.59	36.78	34.52	36.98	37.24	39.02	35.85	39.04	41.91	40.95	44.25	41.43
Knowledge	NaturalQuestions (EM)	10.08	14.99	16.32	18.17	19.31	21.77	24.13	22.05	19.64	22.02	23.35	21.55	23.63
	TriviaQA (EM)	20.56	32.08	37.08	42.78	43.47	46.81	50.42	50.97	52.92	54.58	57.22	58.19	57.92
Commonsense Reasoning	HellaSwag (Acc.)	51.23	59.40	63.20	66.47	66.97	67.87	68.27	69.37	69.53	70.60	71.23	71.37	71.57
	SIQA (Acc.)	34.85	45.14	52.71	54.15	56.24	55.48	59.72	59.67	60.90	62.28	62.08	61.87	62.95
	PIQA (Acc.)	71.16	74.59	75.63	76.12	77.31	76.88	77.42	77.31	78.29	77.86	79.05	78.45	77.80
	WinoGrande (Acc.)	50.83	55.41	56.43	59.12	59.51	58.25	59.98	61.64	59.27	62.12	61.25	61.17	60.62
	Average	25.15	31.13	34.99	37.38	39.24	40.09	42.03	42.75	43.32	44.42	45.08	45.92	46.03

Table 6: **Performance on multimodal benchmarks at different pre-training token budgets for A3B models. The models are trained with 250B text tokens and 25B multimodal tokens.**

	Total tokens D_{total}	25B	50B	75B	100B	125B	150B	175B	200B	225B	250B	275B
Aggregate	MMStar (Acc.)	26.65	25.62	25.21	27.07	28.37	25.21	26.72	28.65	26.31	29.75	28.72
	MMMU (Acc.)	25.59	30.81	35.28	33.42	32.92	33.79	33.66	36.02	34.04	36.89	35.53
	MMMU-Pro (Acc.)	13.29	14.97	15.30	14.97	15.44	17.92	17.85	18.59	18.52	19.93	19.19
	MME (Acc.)	50.44	50.84	50.71	52.56	53.01	55.04	55.79	53.09	56.50	56.01	54.51
	$\text{MMBench}_{\text{en}}$ (Acc.)	29.71	32.84	35.37	36.67	38.08	38.64	39.41	40.01	41.44	41.46	42.86
VQA	VQAv2 (EM)	39.84	42.74	42.14	43.86	44.46	45.48	45.72	47.22	45.60	46.74	49.20
	TextVQA (EM)	10.66	10.58	9.34	10.98	9.58	11.52	11.92	13.02	14.10	13.08	13.86
STEM	MathVista (Pass@1)	34.00	33.60	37.20	38.00	39.80	42.40	39.20	40.80	42.20	41.60	41.00
	MathVerse (Pass@1)	29.53	29.06	30.84	31.67	33.10	33.87	29.89	33.87	33.69	33.99	33.39
	ScienceQA (EM)	34.01	43.58	45.46	49.68	53.10	52.75	53.30	52.45	54.64	49.23	56.72
Doc Understanding	HallusionBench (Acc.)	49.23	46.58	43.38	42.96	42.40	44.49	41.98	42.40	44.63	43.38	46.03
	LogicVista (EM)	15.85	20.73	23.17	23.48	23.17	27.13	21.95	23.48	26.52	26.52	28.66
	AI2D (Acc.)	24.18	37.11	42.80	45.88	49.21	48.85	50.88	53.63	51.28	52.95	52.49
	ChartQA (Acc.)	2.67	4.58	5.11	4.98	5.92	4.29	4.58	5.19	4.66	5.47	6.16
Vision Knowledge	$\text{MMBench}_{\text{cc}}$ (EM)	26.97	26.72	27.32	30.56	29.34	31.62	31.87	30.3	31.26	30.96	31.67
	SimpleVQA (EM)	5.87	6.77	7.12	8.48	8.23	9.38	8.58	9.78	10.49	10.29	8.98
Counting	CountBench (EM)	12.39	13.91	11.74	15.43	16.52	13.91	12.39	15.22	16.09	17.83	16.74
	CountQA (EM)	2.89	7.84	6.40	3.10	3.10	4.44	5.16	3.92	5.37	5.88	3.82
Spatial Reasoning	RealWorldQA (Acc.)	35.58	38.60	39.30	39.30	43.49	37.91	41.63	43.72	41.63	37.67	41.40
	CV-Bench (Acc.)	40.79	44.51	45.93	44.17	45.36	47.62	46.51	46.51	46.51	46.55	45.32
	OmniSpatial (Acc.)	19.45	33.03	26.28	27.75	35.39	34.42	31.49	36.37	34.26	34.66	40.52
	SEAM (Acc.)	22.45	25.51	27.55	31.22	30.37	29.45	31.73	31.52	30.94	30.54	31.15
	SpatialEval (Acc.)	27.44	32.65	30.55	28.16	37.63	38.61	34.13	32.80	35.74	37.39	33.85
	Average	25.19	28.40	28.85	29.75	31.22	31.68	31.15	32.11	32.45	32.56	33.12

Table 7: **Performance on multimodal benchmarks at different pre-training token budgets for A3B models. The models are trained with 250B text tokens and 50B multimodal tokens.**

	Total tokens D_{total}	25B	50B	75B	100B	125B	150B	175B	200B	225B	250B	275B	300B
Aggregate	MMStar (Acc.)	28.37	24.38	28.93	27.82	26.72	25.83	29.96	27.82	28.79	30.23	29.96	28.79
	MMMU (Acc.)	29.19	30.19	31.93	34.66	37.64	37.27	37.39	36.89	34.53	37.02	36.52	37.64
	MMMU-Pro (Acc.)	13.22	14.09	14.63	15.57	16.17	17.05	18.19	16.11	18.12	18.52	18.66	18.59
	MME (Acc.)	51.59	49.29	52.03	52.92	51.24	51.90	57.74	51.28	60.21	56.72	53.80	57.65
	$\text{MMBench}_{\text{en}}$ (Acc.)	28.40	33.54	35.88	38.36	40.18	42.30	42.37	44.73	47.12	48.10	48.00	48.49
VQA	VQAv2 (EM)	41.98	43.16	47.68	46.76	50.04	48.88	50.18	47.88	50.20	52.10	52.28	50.18
	TextVQA (EM)	11.54	11.52	12.66	13.66	13.34	14.06	14.54	16.80	21.50	22.62	25.10	27.98
STEM	MathVista (Pass@1)	35.80	38.40	38.40	40.00	38.80	42.00	40.80	40.60	41.00	40.20	40.20	39.40
	MathVerse (Pass@1)	29.00	27.45	31.49	33.63	34.46	33.87	32.62	33.93	30.36	34.11	34.82	34.40
	ScienceQA (EM)	31.18	41.99	47.25	49.33	52.55	47.60	49.33	51.26	53.79	55.23	55.28	57.06
Doc Understanding	HallusionBench (Acc.)	50.07	42.12	41.56	41.84	42.82	48.40	45.19	44.91	43.10	41.56	43.65	47.84
	LogicVista (EM)	18.60	21.34	24.09	23.48	23.48	25.00	19.82	21.95	25.30	23.17	25.30	27.13
	AI2D (Acc.)	23.79	34.88	44.18	46.79	47.19	49.54	51.96	51.73	51.21	51.44	51.15	52.78
	ChartQA (Acc.)	4.54	3.89	4.50	4.25	4.29	5.71	4.54	5.47	3.97	5.75	5.19	4.94
Vision Knowledge	$\text{MMBench}_{\text{cc}}$ (EM)	26.62	26.41	26.52	26.92	29.49	30.45	33.13	31.72	32.42	33.13	32.47	33.13
	SimpleVQA (EM)	6.72	6.87	7.98	9.33	8.63	9.68	8.53	8.43	10.24	11.69	12.39	10.69
Counting	CountBench (EM)	11.96	13.48	12.61	14.78	15.65	16.52	17.39	20.65	21.74	22.39	28.70	28.26
	CountQA (EM)	7.84	6.40	3.72	3.41	4.64	6.19	5.16	7.53	7.02	5.47	4.33	5.16
Spatial Reasoning	RealWorldQA (Acc.)	33.95	36.28	42.09	43.26	41.86	47.21	42.09	45.35	42.09	39.07	41.63	43.49
	CV-Bench (Acc.)	41.63	39.10	41.52	43.90	44.32	46.12	43.21	42.48	43.94	46.28	45.28	47.39
	OmniSpatial (Acc.)	21.40	31.49	32.79	34.42	32.47	35.23	33.93	38.97	38.49	35.96	36.37	42.72
	SEAM (Acc.)	23.06	24.63	25.03	25.88	25.85	25.61	28.53	26.49	31.01	30.20	29.55	27.79
	SpatialEval (Acc.)	28.33	29.76	36.04	36.74	33.11	33.50	32.78	33.04	35.72	35.37	32.91	36.24
Average		26.03	27.42	29.72	30.77	31.08	32.17	32.15	32.44	33.56	33.75	34.07	35.12

Table 8: **Performance on multimodal benchmarks at different pre-training token budgets for A3B models. The models are trained with 250B text tokens and 75B multimodal tokens.**

	Total tokens D_{total}	25B	50B	75B	100B	125B	150B	175B	200B	225B	250B	275B	300B	325B
Aggregate	MMStar (Acc.)	28.99	25.96	28.72	27.89	30.65	29.13	29.48	30.85	28.51	32.16	33.33	31.13	30.51
	MMMU (Acc.)	29.07	29.94	30.19	33.66	34.66	35.90	33.79	33.91	35.90	37.27	36.02	34.91	37.64
	MMMU-Pro (Acc.)	12.01	13.89	14.83	16.11	16.91	18.05	17.25	18.72	18.66	18.46	18.86	19.87	21.54
	MME (Acc.)	51.41	50.04	51.41	51.72	50.49	53.89	57.34	57.65	61.80	61.98	62.16	58.36	59.86
	$\text{MMBench}_{\text{en}}$ (Acc.)	28.47	33.12	36.93	38.92	40.43	41.77	45.55	48.80	49.05	52.25	51.97	52.28	54.73
VQA	VQAv2 (EM)	40.70	46.74	46.32	47.08	49.68	49.72	49.60	49.92	49.66	51.16	49.42	53.70	62.78
	TextVQA (EM)	11.88	13.78	12.94	12.28	13.86	16.56	21.46	25.00	30.26	30.76	33.76	34.52	39.70
STEM	MathVista (Pass@1)	34.00	33.40	37.20	37.00	39.60	41.00	42.20	41.00	41.80	44.40	41.20	41.20	43.00
	MathVerse (Pass@1)	23.35	29.95	27.93	30.07	28.58	33.10	34.52	32.20	31.97	36.07	33.87	33.33	36.13
	ScienceQA (EM)	34.16	39.56	46.31	48.04	49.23	54.88	51.36	52.75	54.39	53.79	55.03	55.28	57.16
Doc Understanding	HallusionBench (Acc.)	51.60	41.70	42.68	41.56	41.70	45.61	42.26	41.14	41.56	42.26	42.82	48.81	43.93
	LogicVista (EM)	18.29	19.82	20.73	21.65	21.65	22.56	21.65	24.70	19.82	19.82	25.00	20.43	25.61
	AI2D (Acc.)	24.74	34.82	43.78	46.56	48.69	48.82	51.05	52.62	52.68	53.89	54.22	51.77	54.45
	ChartQA (Acc.)	4.42	3.48	3.73	4.90	4.54	4.21	4.38	4.17	5.43	6.32	6.69	7.33	8.06
Vision Knowledge	$\text{MMBench}_{\text{cc}}$ (EM)	24.80	26.16	29.09	30.00	32.42	31.92	32.17	33.94	35.00	34.95	33.28	36.77	36.87
	SimpleVQA (EM)	7.12	8.73	8.98	8.93	10.44	9.48	10.34	11.14	11.74	11.39	11.29	13.15	13.95
Counting	CountBench (EM)	10.43	10.87	15.65	11.30	15.22	25.22	23.04	24.78	28.91	27.83	30.22	34.78	34.13
	CountQA (EM)	3.72	1.55	4.95	4.13	5.16	2.68	7.33	5.88	6.09	5.47	6.19	7.43	7.53
Spatial Reasoning	RealWorldQA (Acc.)	39.53	37.67	40.00	40.23	43.49	43.26	40.23	36.98	41.16	42.56	39.77	42.79	44.88
	CV-Bench (Acc.)	41.90	45.78	44.90	44.01	43.98	41.10	42.90	42.56	44.97	45.32	45.43	46.05	46.39
	OmniSpatial (Acc.)	21.07	24.57	35.31	36.94	34.50	36.05	33.93	32.79	37.43	40.93	37.27	35.39	37.02
	SEAM (Acc.)	21.91	23.91	25.20	28.57	25.44	28.19	28.02	28.06	28.67	30.98	28.46	28.63	32.10
	SpatialEval (Acc.)	32.46	31.96	32.74	35.69	34.63	31.70	33.98	30.35	35.76	37.58	36.65	37.80	34.33
Average		25.91	27.28	29.59	30.31	31.13	32.38	32.78	33.04	34.40	35.55	35.34	35.90	37.49

Table 9: **Performance on text benchmarks. Model sizes (N) range from 71M to 3B activated parameters, with all models trained on 250B text tokens.**

	Model Sizes (N)	A71M	A128M	A340M	A590M	A874M	A3B
Aggregate	MMLU-Redux (Acc.)	26.39	31.75	40.79	44.74	49.72	57.79
	MMLU-Pro (Acc.)	11.47	12.39	13.95	14.11	21.46	24.88
	$\text{AGIEval}_{\text{en}}$ (Acc.)	20.72	18.98	24.61	28.81	31.56	36.96
	SuperGPQA (Acc.)	9.99	10.36	12.88	13.04	17.12	19.95
Coding	HumanEval+ (Pass@1)	4.88	7.93	15.24	15.24	18.90	20.73
	MBPP+ (Pass@1)	11.64	16.67	28.31	35.19	39.68	48.68
Mathematics	GSM8K (Pass@1)	1.90	5.91	15.31	22.97	25.02	48.75
	MATH (Pass@1)	3.30	5.15	10.10	13.40	16.05	26.70
Logical Reasoning	BBH (EM)	26.78	27.71	30.77	32.75	35.15	44.97
	SpatialEval (Acc.)	28.24	27.89	26.40	29.87	32.65	35.95
Knowledge	NaturalQuestions (EM)	7.76	10.66	12.96	15.62	17.89	22.74
	TriviaQA (EM)	12.64	19.58	26.11	35.56	40.14	56.11
Commonsense Reasoning	HellaSwag (Acc.)	42.57	47.73	56.97	62.57	64.80	71.57
	SIQA (Acc.)	34.29	36.34	44.22	44.78	53.58	60.24
	PIQA (Acc.)	68.88	70.29	73.67	74.10	76.17	78.35
	WinoGrande (Acc.)	52.49	50.12	54.54	55.33	56.83	61.96
Average		22.75	24.97	30.43	33.63	37.30	44.77

Table 10: **Performance on text benchmarks. Model sizes (N) range from 71M to 3B activated parameters, with all models trained on 250B text tokens and 25B multimodal tokens.**

	Model Sizes (N)	A71M	A128M	A340M	A590M	A874M	A3B
Aggregate	MMLU-Redux (Acc.)	28.11	32.09	42.14	46.95	49.60	56.84
	MMLU-Pro (Acc.)	11.51	11.33	14.27	15.66	17.32	25.29
	$\text{AGIEval}_{\text{en}}$ (Acc.)	21.81	21.36	24.33	27.63	29.07	37.38
	SuperGPQA (Acc.)	8.79	9.34	13.10	13.35	14.62	20.31
Coding	HumanEval+ (Pass@1)	6.71	9.76	13.41	16.46	15.85	19.51
	MBPP+ (Pass@1)	7.14	12.96	29.10	33.86	38.89	53.97
Mathematics	GSM8K (Pass@1)	1.82	5.53	12.51	20.02	28.66	50.49
	MATH (Pass@1)	3.45	5.00	8.50	14.35	16.25	25.60
Logical Reasoning	BBH (EM)	25.34	27.14	30.38	32.85	34.34	43.60
	SpatialEval (Acc.)	28.35	26.80	35.35	32.93	34.96	39.28
Knowledge	NaturalQuestions (EM)	7.98	9.42	13.80	15.24	17.37	23.49
	TriviaQA (EM)	13.89	16.11	24.31	34.72	41.53	57.92
Commonsense Reasoning	HellaSwag (Acc.)	42.47	46.67	57.47	62.90	65.33	71.30
	SIQA (Acc.)	34.29	34.80	42.43	45.80	52.71	62.54
	PIQA (Acc.)	69.31	69.31	73.45	73.94	76.28	77.80
	WinoGrande (Acc.)	50.51	51.54	55.41	56.91	57.85	62.67
Average		22.59	24.32	30.62	33.97	36.91	45.50

Table 11: **Performance on text benchmarks. Model sizes (N) range from 71M to 3B activated parameters, with all models trained on 250B text tokens and 50B multimodal tokens.**

	Model Sizes (N)	A71M	A128M	A340M	A590M	A874M	A3B
Aggregate	MMLU-Redux (Acc.)	26.28	32.72	41.09	47.02	48.61	56.68
	MMLU-Pro (Acc.)	11.24	11.73	13.33	15.61	21.19	23.93
	$\text{AGIEval}_{\text{en}}$ (Acc.)	21.11	22.78	25.50	27.27	32.58	36.32
	SuperGPQA (Acc.)	9.47	9.82	13.09	13.73	17.17	20.52
Coding	HumanEval+ (Pass@1)	7.32	7.93	12.80	15.85	17.07	20.12
	MBPP+ (Pass@1)	8.73	12.17	26.72	34.13	39.15	51.85
Mathematics	GSM8K (Pass@1)	2.58	4.25	14.10	24.56	27.60	53.90
	MATH (Pass@1)	2.90	5.90	10.15	13.00	15.50	25.35
Logical Reasoning	BBH (EM)	27.00	28.71	30.27	32.04	35.77	45.44
	SpatialEval (Acc.)	27.76	25.05	30.18	36.06	37.95	38.04
Knowledge	NaturalQuestions (EM)	7.42	9.78	13.88	16.18	17.48	21.44
	TriviaQA (EM)	15.56	19.17	28.89	34.44	40.42	57.50
Commonsense Reasoning	HellaSwag (Acc.)	42.70	47.90	57.67	61.97	64.90	71.60
	SIQA (Acc.)	36.03	35.72	43.24	49.49	53.89	60.29
	PIQA (Acc.)	66.76	69.97	73.61	74.48	76.61	78.73
	WinoGrande (Acc.)	51.14	51.93	54.54	55.41	57.54	61.64
Average		22.75	24.72	30.57	34.45	37.71	45.21

Table 12: **Performance on text benchmarks. Model sizes (N) range from 71M to 3B activated parameters, with all models trained on 250B text tokens and 75B multimodal tokens.**

	Model Sizes (N)	A71M	A128M	A340M	A590M	A874M	A3B
Aggregate	MMLU-Redux (Acc.)	25.40	32.11	38.91	44.95	49.04	57.98
	MMLU-Pro (Acc.)	10.68	11.63	13.87	14.97	17.28	27.68
	$\text{AGIEval}_{\text{en}}$ (Acc.)	20.64	20.45	25.54	26.29	29.67	37.73
	SuperGPQA (Acc.)	8.00	10.31	11.81	14.16	14.90	22.00
Coding	HumanEval+ (Pass@1)	4.88	7.93	12.20	16.46	15.85	21.34
	MBPP+ (Pass@1)	7.94	13.23	26.46	30.95	37.57	54.23
Mathematics	GSM8K (Pass@1)	2.27	5.08	14.25	23.28	28.05	52.39
	MATH (Pass@1)	3.70	4.95	9.40	11.95	15.60	26.30
Logical Reasoning	BBH (EM)	26.87	28.06	30.31	33.03	35.93	40.84
	SpatialEval (Acc.)	27.94	30.17	32.39	38.93	33.07	41.43
Knowledge	NaturalQuestions (EM)	7.15	10.03	13.85	14.65	18.86	23.63
	TriviaQA (EM)	17.08	17.92	25.97	36.94	39.86	57.92
Commonsense Reasoning	HellaSwag (Acc.)	42.13	48.13	57.57	62.10	65.60	71.57
	SIQA (Acc.)	32.45	33.88	43.04	49.90	52.05	62.95
	PIQA (Acc.)	68.50	69.64	73.45	74.05	75.68	77.80
	WinoGrande (Acc.)	51.54	51.70	53.83	56.35	58.41	60.62
	Average	22.32	24.70	30.18	34.31	36.71	46.03

Table 13: **Performance on multimodal benchmarks in a 0-shot setting. Model sizes (N) range from 71M to 3B activated parameters, with all models trained on 250B text tokens and 75B multimodal tokens.**

	Model Sizes (N)	A71M	A128M	A340M	A590M	A874M	A3B
Aggregate	MMStar (Acc.)	27.82	26.86	24.59	28.58	28.86	30.17
	MMMU (Acc.)	28.70	24.97	28.07	31.80	30.31	36.65
	MMMU-Pro (Acc.)	12.42	14.30	13.62	15.37	15.17	16.98
	MME (Acc.)	49.73	50.18	50.71	51.90	53.58	50.35
	$\text{MMBench}_{\text{en}}$ (Acc.)	27.12	30.79	34.95	43.42	47.26	54.10
VQA	VQAv2 (EM)	45.44	46.78	51.70	48.52	52.24	58.32
	TextVQA (EM)	14.92	14.54	16.02	24.90	29.28	41.24
STEM	MathVista (Pass@1)	33.40	32.00	31.00	37.20	37.80	39.00
	MathVerse (Pass@1)	27.63	29.71	21.87	30.36	28.34	34.17
	ScienceQA-CoT (EM)	0.00	0.84	12.99	18.94	7.88	18.54
Doc Understanding	HallusionBench (Acc.)	52.30	44.63	49.65	41.98	41.14	47.84
	LogicVista-CoT (EM)	0.91	6.40	5.18	18.60	6.71	5.18
	AI2D (Acc.)	25.82	26.77	31.15	39.04	40.18	47.02
	ChartQA (Acc.)	4.46	4.90	5.39	6.36	5.96	8.87
Vision Knowledge	$\text{MMBench}_{\text{cc}}$ (EM)	25.76	25.96	28.33	28.74	33.33	33.03
	SimpleVQA (EM)	3.51	4.92	5.92	8.08	8.83	9.08
Counting	CountBench (EM)	8.70	13.91	15.22	20.43	20.43	34.13
	CountQA (EM)	5.88	3.41	3.92	5.47	2.06	5.37
Spatial Reasoning	RealWorldQA (Acc.)	34.65	41.16	39.53	41.16	38.84	41.86
	CV-Bench (Acc.)	41.67	42.36	42.36	41.71	44.24	41.48
	OmniSpatial (Acc.)	21.89	20.67	22.86	23.76	23.92	22.78
	SEAM (Acc.)	24.69	25.92	26.26	25.37	26.87	27.38
	SpatialEval (Acc.)	26.85	24.29	27.20	26.85	22.59	27.26
	Average	23.66	24.19	25.59	28.63	28.08	31.77

Table 14: **Performance on multimodal benchmarks in a 1-shot setting. Model sizes (N) range from 71M to 3B activated parameters, with all models trained on 250B text tokens and 75B multimodal tokens.**

	Model Sizes (N)	A71M	A128M	A340M	A590M	A874M	A3B
Aggregate	MMStar (Acc.)	28.79	29.48	27.34	27.69	27.34	31.20
	MMMU (Acc.)	27.58	30.31	33.17	31.30	37.14	38.76
	MMMU-Pro (Acc.)	12.28	14.23	14.23	14.43	14.83	20.94
	MME (Acc.)	50.57	49.69	50.13	51.06	50.62	58.53
	$\text{MMBench}_{\text{en}}$ (Acc.)	27.80	30.88	33.17	38.68	41.91	52.00
VQA	VQAv2 (EM)	42.06	45.92	46.74	47.34	48.64	62.78
	TextVQA (EM)	13.18	14.66	13.18	21.60	22.16	39.70
STEM	MathVista (Pass@1)	34.20	34.60	39.80	38.80	39.60	40.60
	MathVerse (Pass@1)	31.02	30.30	28.64	30.48	32.03	33.21
	ScienceQA-CoT (EM)	34.01	27.62	43.38	43.78	48.29	54.78
Doc Understanding	HallusionBench (Acc.)	44.77	41.28	43.38	41.28	41.70	49.23
	LogicVista-CoT (EM)	20.73	23.48	18.90	21.65	23.78	25.61
	AI2D (Acc.)	24.51	29.65	37.04	41.03	45.22	53.53
	ChartQA (Acc.)	2.35	3.44	3.53	4.74	4.29	8.35
Vision Knowledge	$\text{MMBench}_{\text{cc}}$ (EM)	26.77	25.66	27.78	29.80	30.76	33.54
	SimpleVQA (EM)	4.26	3.56	5.02	6.07	6.17	8.78
Counting	CountBench (EM)	10.00	12.83	12.83	17.83	18.48	23.04
	CountQA (EM)	7.64	5.26	4.44	8.67	5.78	7.53
Spatial Reasoning	RealWorldQA (Acc.)	32.79	37.44	35.81	43.26	42.79	39.30
	CV-Bench (Acc.)	40.94	38.33	46.16	41.52	45.28	46.51
	OmniSpatial (Acc.)	23.43	23.76	31.57	34.74	37.10	36.13
	SEAM (Acc.)	22.32	24.80	23.88	23.81	26.09	30.67
	SpatialEval (Acc.)	27.66	27.61	26.55	36.28	32.80	34.33
	Average	25.64	26.30	28.12	30.25	31.43	36.05

Table 15: **Performance on multimodal benchmarks in a 3-shot setting. Model sizes (N) range from 71M to 3B activated parameters, with all models trained on 250B text tokens and 75B multimodal tokens.**

	Model Sizes (N)	A71M	A128M	A340M	A590M	A874M	A3B
Aggregate	MMStar (Acc.)	29.48	25.00	27.13	27.20	28.51	30.51
	MMMU (Acc.)	26.21	30.06	30.43	31.43	33.66	37.64
	MMMU-Pro (Acc.)	12.48	14.30	13.36	15.17	15.84	21.54
	MME (Acc.)	50.53	50.66	50.49	52.30	52.79	59.86
	$\text{MMBench}_{\text{en}}$ (Acc.)	27.26	30.83	33.47	40.64	43.87	54.73
VQA	VQAv2 (EM)	42.58	45.42	47.94	48.50	51.90	57.28
	TextVQA (EM)	16.64	17.22	16.96	24.72	29.42	38.42
STEM	MathVista (Pass@1)	34.00	34.60	39.00	38.40	39.00	43.00
	MathVerse (Pass@1)	29.59	29.89	29.59	31.19	29.53	36.13
	ScienceQA-CoT (EM)	30.19	42.34	44.72	48.93	48.64	57.16
Doc Understanding	HallusionBench (Acc.)	42.26	42.68	41.56	41.28	41.42	43.93
	LogicVista-CoT (EM)	23.17	24.39	13.11	21.34	24.09	25.61
	AI2D (Acc.)	24.71	30.96	38.68	42.15	45.98	54.45
	ChartQA (Acc.)	2.76	4.25	4.62	6.12	5.67	8.06
Vision Knowledge	$\text{MMBench}_{\text{cc}}$ (EM)	26.57	26.01	28.08	30.91	32.63	36.87
	SimpleVQA (EM)	6.22	6.62	6.97	9.13	9.03	13.95
Counting	CountBench (EM)	11.74	12.39	13.48	19.35	18.48	23.70
	CountQA (EM)	7.95	6.81	7.12	6.71	7.84	6.81
Spatial Reasoning	RealWorldQA (Acc.)	36.98	41.86	39.77	41.63	44.88	44.88
	CV-Bench (Acc.)	41.75	39.98	46.51	42.40	43.28	46.39
	OmniSpatial (Acc.)	22.05	25.87	31.49	33.60	36.70	37.02
	SEAM (Acc.)	23.61	24.35	23.78	25.58	29.11	32.10
	SpatialEval (Acc.)	27.48	29.48	27.40	33.15	29.55	30.89
	Average	25.92	27.65	28.51	30.95	32.25	36.56