

TRINITY: ONE DIFFERENTIABLE PHYSICS FOR TRAINING, REFINING AND SCORING GENERATIVE FLOORPLANNERS

Shih-Ying Yeh^{✉†} Tzu-Sian Wang^{✉♣} Xuehai Wang^{♣△} Jia-Hua Lee[★] Daniel Z. Kaplan[◇]
Ming-Qi Xu[♡] Wuqian Tang[♡] Chun-Yao Wang[♡] Shang-Hong Lai[♡] Chun-Yi Lee[★]

♡National Tsing Hua University ♣Kohaku Lab ♣Karolinska Institutet △Stockholm University
◇realiz.ai ★National Taiwan University

*Equal contribution †Corresponding author: kohaku@kblueleaf.net

Project page: <https://kohaku-lab.github.io/Trinity/>

ABSTRACT

Floorplanning arranges the blocks of a chip and decides their shapes under objectives that press blocks together, short wirelength and a small outline, and constraints that hold them apart, non-overlap, clusters, MIB shapes and boundary blocks. Recent diffusion placers train on reference layouts alone and leave this coupled system to guidance, post-hoc loops and a legalizer, reporting only the endpoint, which hides what the generator contributes. We re-implement four of them under one recipe on FloorSet, score raw, refined and legalized layouts on one scale, and propose Trinity, a flow-matching floorplanner whose six differentiable functions for the constraints and objectives are its training loss term, the energy of a closed-form refiner after sampling and the base of a soft cost for every stage. The network thus learns the correction prior placers apply in their samplers, and sampling needs no guidance. Stage by stage, the training term lowers a plain transformer’s raw soft cost by 26% and matters most at short budgets, the shared refiner decides more of the final cost than the generator and matches a ported placer’s loop in 16 to 660 times fewer steps, Trinity’s refined soft cost is 36% below the best ported pipeline, the soft cost ranks settings as the contest’s hard cost does, and on the FloorSet val set the pipeline reaches a mean hard cost of 1.014 in 1.63 s per case.




Figure 1: The network beside each pipeline is the generator that training updates and sampling evaluates. **Left:** In prior diffusion placers the constraints are absent from training (dashed), differ in form between stages ($\neq$), and the layouts in between are not measured. **Middle:** Trinity carries one set of constraint and objective functions, its differentiable physics, through training, refinement, and scoring. **Right:** Soft cost against refinement budget, each curve starting at the raw sample with zero refinement steps. *Faster:* the step at which each prior generator under our refiner reaches the soft cost of its own full loop (triangle). *Lower:* the refined soft cost of the best prior pipeline against ours.

1 INTRODUCTION

Floorplanning is an early stage of the physical design flow in Electronic Design Automation (EDA). Given a netlist and each block’s target area, floorplanning arranges the position and shape of every block on the chip, and the floorplan bounds what each later stage can achieve. A floorplanner pursues two objectives, *short wirelength between connected blocks* and *a small outline area*, and must reach them under hard constraints: a floorplan is feasible only if every block matches its target area, fixed-shape blocks retain their shapes, pre-placed blocks remain in place, and no two blocks overlap. Three

soft constraints follow in practice: blocks of a cluster should stay adjacent, multi-instance blocks (MIB) should share one shape, and boundary blocks should touch the die boundary (ICCAD, 2026). The objectives and constraints pull in opposite directions, and the strongest floorplans sit where the hard constraints bind. Learning-based methods promise to amortize this per-instance optimization into a trained model. Floorplanning moreover suits a generative treatment: an instance admits many strong layouts rather than one optimum, and a generative model drafts complete layouts from this distribution (Lee et al., 2025; Trung & Hy, 2026; Yoon et al., 2026; Xie et al., 2026). However, such a model learns the distribution of reference layouts rather than the geometry of a single one: a network trained with a squared loss estimates a conditional mean of the reference layouts given its input, and a mean of feasible layouts is not necessarily feasible, since the feasible set is nonconvex. An infeasible draft leaves the constraints to corrections applied after sampling. Such corrections act on a landscape whose couplings belong to floorplanning itself rather than any model: as blocks compete for the same die area, a step that resolves an overlap can scatter a cluster or displace a pre-placed block, and a push toward feasibility may sacrifice the wirelength and outline area that the objectives demand. A generative floorplanner must therefore treat the constraints and objectives as one coupled system, and where this system enters the pipeline determines what the model learns.

Existing methods differ in where they place this coupled system, and each choice carries its own cost. Classic floorplanners place it inside the search procedure: simulated annealing (Wong & Liu, 1986) explores topological representations such as the sequence pair (Murata et al., 1996) and the B*-tree (Chang et al., 2000), in which non-overlap holds by construction, and analytical placement (Lu et al., 2015; Lin et al., 2021) minimizes a differentiable relaxation of overlap jointly with wirelength. Since every move faces the constraints and the objectives together, these solvers remain on the boundary, at the price of a search that begins anew on every netlist. Learning-based methods lift this per-instance cost, and the constraints begin to recede from training. Reinforcement learning stays nearest to the classic position, with the constraints written into its actions and the objectives into its reward (Mirhoseini et al., 2021; Lai et al., 2022; 2023), although the two do not meet in one function that the policy learns, and the agent is retrained or fine-tuned for every new netlist. Regression abandons the constraints and trains on reference layouts alone (Liu et al., 2023b; Amini et al., 2022), which leaves the model exposed to the conditional-mean difficulty above.

The recent diffusion placers (Lee et al., 2025; Trung & Hy, 2026; Yoon et al., 2026; Xie et al., 2026) push this coupled system farthest from training: their losses only reproduce the reference layouts, and every correction arrives after the model. The first of these corrections, a hand-tuned guidance term, intervenes during sampling. The finished sample then enters post-hoc optimization loops, and the remaining violations are left to the legalizer. Fig. 1 (left) draws this arrangement. These placers come from macro placement, a task where every shape is fixed: the shape freedom of floorplanning, and its soft constraints, stay outside their scope. The network’s contribution is not measured stage by stage: their papers examine only the endpoint of the pipeline, and each stage expresses the constraints in its own form, which leaves the intermediate layouts without a common measure. At that endpoint, a weak generator behind a strong correction and a strong generator behind a weak one appear identical. The constraints thus migrate from the core of the classic search to the tail of the correction chain. Among the generative placers, the constraints have appeared everywhere except the training loss. Their place in that loss, and its effect on every later stage, nevertheless remain unexplored.

Given these observations, the remedy is to move the coupled system into training itself. The constraints can enter the training loss directly, since every objective and constraint of floorplanning measures a geometric quantity of the layout and admits a differentiable expression in the positions and shapes of the blocks. The overlap between two blocks, for instance, shrinks continuously as they separate and reaches zero exactly when the pair satisfies the non-overlap constraint. A weighted sum of these expressions defines an energy, one function that records the constraints and objectives together with the trade-off between them. The energy therefore assigns every layout a graded value rather than a binary indicator of feasibility. Analytical placement already minimizes an energy of this form that couples overlap with wirelength (Kleinhans et al., 1991; Lu et al., 2015; Lin et al., 2021). A generative floorplanner can instead place such an energy in its training loss, where each gradient step responds to the reference layouts and the coupled system together. After training, the same expressions determine what a later refinement minimizes and provide a common measure for the layout that each stage produces (Fig. 1, middle). On this measure, the intermediate layouts reveal how much the generator and each later stage contribute, a distinction that the endpoint alone conceals.

To expose this distinction and place the coupled system in training rather than leave it to corrections

after sampling, we propose **Trinity**, a flow-matching floorplanner whose six differentiable functions for the constraints and objectives are incorporated into its training loss, serve as the energy of its refiner, and form the basis of a soft cost that scores the layout of every stage. Trained with these functions, the network learns the correction that prior placers apply inside their samplers, and sampling runs without guidance (Section 3). Measured stage by stage, the pipeline reveals distinct roles for training and refinement: the training term contributes most when the refinement budget is short, and the refiner accounts for more of the final cost than the generator does. Added to the training of a plain transformer, the six functions alone lower the soft cost of its raw samples by 26% (Section 4.2). With our refiner shared across the generators of four diffusion placers ported to our training recipe, their final costs converge despite a wide spread in raw costs, and on a ported placer’s samples, the refiner reaches the soft cost of that placer’s own loop in 16 to 660 times fewer iterations (Fig. 1, right). A comparison of generators therefore calls for a shared refiner. Against the ported pipelines with their own post-hoc loops, the full pipeline of Trinity reaches a refined soft cost 36% below the best of them (Section 4.3). After legalization, Trinity remains ahead of these pipelines under the hard cost of the official contest (ICCAD, 2026), and on its validation set it reaches a mean hard cost of 1.014 at 1.63 seconds per case on one GPU with parallel legalization (Section 4.4).

Contributions. (1) We locate the limit of generative placers in the position of their physics rather than the strength of their networks: the coupled objectives and constraints of floorplanning enter every stage except the training loss. Trinity instead trains on the coupled system directly, with one energy built from six differentiable functions of the layout, and feasibility becomes a property the network learns rather than one that corrections restore. (2) We establish the theory behind this choice: a network trained on reference layouts alone estimates a conditional mean that the nonconvex feasible set does not necessarily contain, whereas the energy term in training approximates constraint guidance inside the sampling loop at no sampling cost. The same analysis selects the clean prediction as the head, the one output an energy can score, and experiment confirms each prediction. (3) We replace the hand-tuned correction loops of prior placers with a refiner that descends the training energy itself, every gradient in closed form. One refiner serves every generator: it carries Trinity and each ported placer below the final cost their own loops reach, and supplies the common ground for comparing generators. (4) We extend the scale of the contest beyond feasibility: our soft cost keeps the objective factor of the hard cost and admits overlap and soft-constraint severity as smooth penalties, and every stage’s layout shares one scale. Since the soft cost agrees with the hard cost on which settings perform better, the sampling and refinement budget can be chosen before the legalizer runs. (5) We lift the fixed-shape assumption that diffusion placers inherited from macro placement: Trinity treats positions and shapes alike and covers the full constraint family of floorplanning, from soft and pre-placed blocks to clusters, boundary blocks, and shared multi-instance shapes, and on the contest’s validation set the full pipeline surpasses the classical annealer at a fraction of its runtime.

2 RELATED WORK

Classical optimization and direct learned placement construct layouts through per-instance search, sequential decisions, or joint coordinate prediction: simulated annealing explores sequence pairs and B*-trees (Wong & Liu, 1986; Murata et al., 1996; Chang et al., 2000; Lin & Chang, 2001; Adya & Markov, 2003), analytical placement couples a continuous relaxation of overlap with legalization (Kleinhans et al., 1991; Chen et al., 2008a; Lu et al., 2015; Lin et al., 2021), sequential construction commits one macro per decision under reinforcement learning (Mirhoseini et al., 2021; Cheng & Yan, 2021; Lai et al., 2022; 2023; Geng et al., 2024; 2025; Gao et al., 2026; Shi et al., 2023), and joint prediction regresses every block position from the netlist graph (Liu et al., 2023b; Amini et al., 2022). Across the learned lines, block shapes stay fixed at placement time, whereas FloorSet requires the placer to settle a shape for every soft block (Mallappa et al., 2024). Generative macro placement keeps the fixed-shape setting and learns layout distributions through noise or velocity prediction, with geometric corrections during or after sampling: velocity-based FlowPlace (Xie et al., 2026) applies overlap-free grid projection at each step, while the noise-based MacroDiff+ (Yoon et al., 2026), ChipDiffusion (Lee et al., 2025), and DiffPlace (Trung & Hy, 2026) steer sampling with overlap and wavelength gradient guidance before post-hoc loops and legalization. On the objective side, linear transformations between data and noise connect flow matching (Lipman et al., 2023; Liu et al., 2023a), interpolants (Ma et al., 2024), and noise prediction (Ho et al., 2020; Nichol & Dhariwal, 2021; Salimans & Ho, 2022), LACE (Chen et al., 2024) and physics-informed diffusion (Bastek et al., 2025) supervise the clean prediction with constraint losses, and Diffusion Transformers (Peebles & Xie, 2023) supply the backbone, conditioned on the netlist through Graphormer-style attention

bias (Ying et al., 2021), GraphGPS-style message passing (Rampášek et al., 2022), and Laplacian positional encoding (Dwivedi & Bresson, 2020; Kreuzer et al., 2021; Dwivedi et al., 2022). Following JiT (Li & He, 2026), Trinity predicts the clean layout and trains on the velocity it implies. For variable-shape floorplanning, it combines netlist-conditioned clean prediction in a DiT backbone with constraint supervision through one set of geometric functions for training, refinement, and scoring, and it scores raw, refined, and legalized layouts separately. Section A.4 surveys these lines in full.

3 METHODOLOGY

3.1 PROBLEM FORMULATION

The floorplanning problem takes as input n blocks with target areas a_i , a weighted netlist A_{ij} and the constraints of Section 1. A layout assigns each block a box (x_i, y_i, w_i, h_i) and is feasible when no two boxes overlap, every area is within 1% of its target and fixed-shape and pre-placed blocks remain at their targets, while the three soft constraints are counted and not enforced. Every layout is scored, at every stage, by the relative gaps Δ_{HPWL} and Δ_{area} of its wirelength and outline area to the reference layout, by its overlap ratio and by one metric per constraint (Appendix C), and two multiplicative aggregates of the same quantities rank every layout on one scale, as follows:

$$\text{Cost} = \left(1 + \frac{1}{2}(\Delta_{\text{HPWL}}^+ + \Delta_{\text{area}}^+)\right) e^{2V_{\text{rel}}}, \quad \text{SoftCost} = \left(1 + \frac{1}{2}(\Delta_{\text{HPWL}}^+ + \Delta_{\text{area}}^+)\right) e^{2\text{sev}_{\text{rel}} + 10 \text{overlap}}, \quad (1)$$

where Δ^+ is the positive part of a gap. The *hard cost* is defined as the cost of the ICCAD 2026 CAD Contest (Problem C) (ICCAD, 2026), unchanged, on feasible layouts only, with V_{rel} the fraction of soft constraints violated. The *soft cost* keeps the objective factor, replaces the violated fraction V_{rel} by the mean severity sev_{rel} of the soft constraints and penalizes overlap smoothly where the hard cost admits none, and is therefore defined on any layout, raw samples included.

3.2 THEORETICAL ANALYSIS

The analysis grounds two design decisions before the framework (Section 3.3): the latent that absorbs the area rule, and the training term that carries the energy prior placers defer to their samplers. The latent $z_i = (c_{x,i}/s, c_{y,i}/s, \rho_i)$, with the scale $s = \sqrt{\sum_i a_i}$, carries the normalized center and the log aspect ratio of block i , and the box decodes at the target area in closed form, as follows:

$$w_i = \sqrt{a_i} e^{\rho_i/2}, \quad h_i = \sqrt{a_i} e^{-\rho_i/2}. \quad (2)$$

The decode is a bijection onto boxes of area a_i and linear interpolation of ρ keeps the area, and the area rule is the coordinate system rather than a constraint. A head trained with a squared loss emits a conditional mean, and in the latent the mean decodes at area exactly a_i while in width-height coordinates it decodes above a_i unless the shape is deterministic (Proposition D.1). The feasible set $\mathcal{F}$ of the other constraints is not convex, so the posterior mean $\bar{x}_0 = \mathbb{E}[x_0 | x_t]$ is in general infeasible even for an exact denoiser, its squared distance from $\mathcal{F}$ at most $\text{tr } \Sigma_{0|t}$ for feasible references, with $\Sigma_{0|t} = \text{Cov}(x_0 | x_t)$ (Proposition D.2). A correction is therefore needed, and only its place is open.

The generator trains with rectified flow (Liu et al., 2023a), $x_t = (1-t)x_0 + tx_1$, $x_1 \sim \mathcal{N}(0, I)$, and predicts the clean layout $\hat{x}_0$. $U = U_C + U_O \geq 0$ denotes a smooth energy of the decoded layout, U_C its constraint terms, zero on feasible layouts, and U_O the objectives. Prior placers take gradient steps on U in the sampler, whereas Trinity adds $\lambda U(\hat{x}_0)$ to the training loss (Eq. (3), Appendix D).

Proposition 3.1. *If the network can represent any function of (x, t) , the minimizer of Eq. (3) is $\hat{x}_0^* = \text{prox}_{\gamma_t U}(\bar{x}_0)$ with $\gamma_t = \lambda t^2/2$.*

Proposition 3.2. *Let a sampler apply k gradient steps of size η on U to $\bar{x}_0$ at every step. (i) The exact guidance admits the closed form $\nabla \log \mathbb{E}[e^{-U(x_0)} | x_t] = \frac{1-t}{t^2}(\bar{x}_0 - \bar{x}_0)$, with $\bar{x}_0$ the posterior mean reweighted by e^{-U} ; the loop’s step $-\nabla U(\bar{x}_0)$ replaces this difference of means with a clean-space gradient, a substitution whose error persists even as $\Sigma_{0|t}$ vanishes. (ii) At a reference layout x^* , $\nabla U_C(x^*) = 0$, so the k gradient steps displace x^* by $k\eta \|\nabla U_O(x^*)\|$ to first order in the total step, with U_O the wirelength and area part of U , independent of t and nonzero whenever the objectives do not vanish at x^* , while the proximal displacement $\gamma_t \|\nabla U(\hat{x}_0^*)\|$ vanishes quadratically with t .*

Training with U thus turns the network into a proximal step on U at no cost in sampling, with a step size that decays as t^2 and vanishes at $t = 0$. U_C is zero on the data (up to the references’ own residual violations, Figure 5c): the constraint term moves no feasible reference, and U_O shifts each prediction toward the objectives by $\gamma_t \|\nabla U_O\|$ to first order. A loop inside the sampler instead




Figure 2: **Architecture** (left): L blocks of the information mover on the wire graph, graph-biased attention and a feed-forward layer. **Pipeline** (right): each draw passes the generator, the refiner and the legalizer, top to bottom in each column. **Key components**: one physics term U enters the loss on $\hat{x}_0$ and serves as the refiner’s energy, and the legalizer is one linear program with a contact snap. c constraints, t time step, pos spectral coordinates, x_t noisy layout, $\hat{v}$ its implied velocity, $\mathcal{L}_{\text{fm}}$ the flow-matching loss, FFW the feed-forward layer, proj the projection, Pre Proc the relation extraction. substitutes clean-space gradients for the exact guidance at every $t > 0$ and moves even a reference layout, and Section 4.3 measures the step and the displacement. The training step and the refiner step are one operation on U at different noise levels t , and U also measures how far a layout is from feasibility. One set of six functions therefore serves training, refinement and evaluation.

3.3 FRAMEWORK OVERVIEW

The framework shares a single set of physics functions across all three components: the generator trains on them, the refiner descends them, and the soft cost derived from them scores every stage on one scale (Figure 2). Trinity expresses each constraint and objective once as a function $\mathcal{E}_k$ of the decoded boxes, positions and shapes alike and dimensionless in the layout scale s : a constraint function is zero when its rule holds, the intersection area over every pair of blocks, the gap to contact along a spanning tree of each cluster, the deviation of each MIB member from the median aspect of its group, and the distance of every boundary-coded side to its edge, while the wirelength and the outline area carry the objectives (Appendix E.1). The weighted sum $U = \sum_k \omega_k \mathcal{E}_k$ is the physics term of the generator’s loss, the energy the refiner descends and the base of the soft cost of Section 3.1 (Figure 1, middle). It depends only on the constraint annotations and the netlist and never on the reference layout, and thus supervises the network with the rules rather than the reference answer.

Generator. The generator drafts complete layouts from noise, conditioned on the netlist, and carries the physics term in its training loss. A DiT (Peebles & Xie, 2023) with one token per block and the time step as a token (Bao et al., 2023). The netlist enters as an additive attention bias (Ying et al., 2021), through the information mover, a gated one-hop graph convolution on the residual stream (Kipf & Welling, 2017; Rampášek et al., 2022), and as two Laplacian eigenvectors in the input coordinates (Dwivedi & Bresson, 2020; Kreuzer et al., 2021) (Appendix B.3). Following JiT (Li & He, 2026), the network predicts the clean layout $\hat{x}_0$ and trains on its implied velocity, with t logit-normal (Esser et al., 2024), m the padding mask and the weights λ , ω_k of Section 4.1, as follows:

$$\mathcal{L} = \mathbb{E}_{t, x_0, x_1} [\mathcal{L}_{\text{fm}} + \lambda U(\hat{x}_0)], \quad \mathcal{L}_{\text{fm}} = \left\| \left(\frac{x_t - \hat{x}_0}{t} - (x_1 - x_0) \right) \odot m \right\|_2^2. \quad (3)$$

The clean head keeps the physics term inexpensive, since the loss needs a decoded layout and $\hat{x}_0$ is one, whereas a velocity head reaches the same minimizer through a gradient scaled by $-t$ and a target that still contains the noise (Proposition D.3), which Section 4.2 measures. Sampling follows plain Euler in uniform steps from $t = 1$ to 0 over NFE evaluations with no guidance term, and after every step the known answers of the instance enter the sample, a fixed-shape block keeping its ρ_i , a pre-placed block all three coordinates and the blocks of a MIB group the mean of their predicted ρ_i .

Refiner. The refiner descends the training energy explicitly once sampling ends, at negligible cost. From each sample at $t = 0$, the refiner takes K steps of Adam (Kingma & Ba, 2015) on U under a heavier overlap weight than training, every gradient evaluated in closed form and the same sampling overrides written back after every step. Refinement thus resumes the descent of U where the proximal step of Proposition 3.1 has vanished at $t = 0$ (schedule, sweep and running cost in Appendix E).

Legalizer. The legalizer converts each refined layout into a hard-feasible one while penalizing the displacement it introduces. A sequence-pair relation, under which non-overlap holds by construction, is extracted for every pair of blocks from the refined layout, and one linear program positions the

Table 1: Raw samples: overlap ratio, wirelength (WL) and area gaps in percent, and soft cost. (a) The three heads on the plain transformer at NFE=32 and NFE=1. (b) The graph mechanisms added one at a time, without ($\lambda=0$) and with ($\lambda=0.01$) the six functions, and the last row is Trinity.

	Head	NFE	Overlap	WL	Area	Soft cost
(a) Objective	x_0 (ours)	32	0.026	-0.2	+1.1	2.11
	v	32	0.037	-0.5	+1.2	2.60
	ϵ	32	0.036	-0.1	+1.5	2.39
	x_0 (ours)	1	0.038	-1.5	+0.9	2.49
	v	1	0.250	+18	+61	77.2
	ϵ	1	0.042	+591	+2,030	152
	Backbone	λ	Overlap	WL	Area	Soft cost
(b) Graph mechanisms	Plain transformer	0	0.026	-0.21	+1.04	2.09
	+ spectral encoding	0	0.024	+0.12	+1.91	2.13
	+ information mover	0	0.022	+0.22	+1.81	2.02
	Plain transformer	0.01	0.023	-0.15	+0.20	1.56
	+ spectral encoding	0.01	0.023	-0.06	+0.31	1.59
	+ information mover	0.01	0.023	-0.07	+0.22	1.51

blocks at their decoded shapes under those relations, with the pre-placed blocks pinned, cluster members abutting along a spanning tree of the cluster and coded sides on the outline, and minimizes the chip outline plus the displacement from the refined positions (Murata et al., 1996; Murata & Kuh, 1998). An infeasible program first relaxes the soft rules, flips the conflicting relations and re-solves the program within a bounded number of rounds, and a final contact snap that moves a block only where no overlap appears completes each draw at a hard-feasible final layout (Appendix F).

4 EXPERIMENTAL RESULTS

The experiments evaluate every stage, since endpoint quality alone cannot identify the generator’s contribution. Raw, refined, and legalized layouts therefore share the one scale of Section 3.1, which tests whether pre-legalization quality persists in feasible layouts and separates generator quality from later optimization. Appendices H to M hold the full tables, Appendix N every data view.

4.1 EXPERIMENTAL SETUP

Benchmarks/Datasets. We train on MIB-consistent FloorSet-Lite (Mallappa et al., 2024), whose 996,000 synthetic floorplans span 21 to 120 blocks per instance. Unless stated otherwise, every reported number on our held-out validation set of 12,000 cases averages four draws per case and then across all cases. We evaluate separately on the official FloorSet val set of 100 cases for the official comparison in Table 7 and run one full GSRC evaluation as an external check in Table 8.

Baselines. We re-implement ChipDiffusion (Lee et al., 2025), DiffPlace (Trung & Hy, 2026), MacroDiff+ (Yoon et al., 2026), and FlowPlace (Xie et al., 2026) as comparisons within the learned generative line. Under one training recipe, the ported placers retain their networks, objectives, and post-hoc loops while adopting our latent representation, conditioning, Euler sampler, and overrides, as specified in Section B.4. The generator comparison excludes sampler-time guidance, which Section J evaluates on its own, and grid projection, whereas Section 4.3 includes the post-hoc loops under their released settings. To examine conditional-mean prediction, Reg- z and Reg- $xywh$ predict latents and raw boxes on our backbone, with details in Appendix K.2. The classical comparison uses the FloorSet team’s PARSAC annealer (Mostafa et al., 2024) only on the FloorSet val set, since its published budget of 10^7 steps per worker is prohibitive at the 12,000-case scale, with details in Appendix L.

Metrics. We evaluate every layout by the quantities in Section 3.1 for cross-stage comparison, with soft cost derived from the shared differentiable physics and hard cost restricted to feasible layouts after legalization. We also report FLD and MMD for the generator comparison as reference-distribution distances, with scoring details in Appendix C. We report first-draw hard costs apart from best-of- N hard costs selected by hard cost among the N draws, with full tables in Appendices G to O.

Implementation Details. Our three recurring comparisons distinguish the plain control, a plain transformer with a clean-sample head and no physics, from full Trinity with two graph components, six functions, and $\lambda=0.01$, and from Trinity at $\lambda=0$, the Trinity configuration without physics. All 66 models share a training recipe of 200,000 steps with batch size 256 and AdamW at an initial learning rate of 2×10^{-4} with cosine decay. This shared recipe uses exponential moving average (EMA) weights and augmentation by rotation, flip, shift, constraint dropout, and wire dropout at ten GPU-hours per model on one RTX 5090, the machine behind every reported timing. The legalizer runs on 16 CPU workers in parallel, and every training ω_k equals one, with further training details in Appendix B.2. We sample with $NFE \in \{1, 2, 4, 8, 16, 32\}$ and cap refinement at 400 Adam steps under a tenfold overlap weight, which keeps the sampling and refinement budgets distinct.

4.2 RAW GENERATOR QUALITY BEFORE REFINEMENT

Table 1 compares the generator’s design choices, while Table 2 reports the contribution of physics training to raw-sample quality. The clean-sample head exposes a layout for direct energy evaluation,

Metric	Weight λ			
	none	0.01	0.05	0.1
Overlap (%)	2.60	2.42	1.95	1.80
Cluster gap (10^{-3})	2.65	2.29	2.16	2.04
MIB variance (10^{-6})	8.75	3.51	0.69	1.80
Boundary dist. (10^{-3})	3.23	0.99	0.74	0.88
WL gap (%)	-0.21	-0.20	-0.41	-0.69
Area gap (%)	1.04	0.63	-0.13	-0.93
Soft cost	2.09	1.56	1.56	1.63

Table 2: One physics function in the loss at a time, each one scored on its own metric, and all six together scored by the soft cost, on the plain control’s raw samples at NFE=32; bold marks the best weight in each metric row.

Table 3: Every method through its own pipeline at NFE=32: the raw sample, the refined layout (own loop, released setting) and the legalized first draw; overlap ratio, WL and area gaps in percent, refined soft cost, V_{rel} , hard cost as first / best of 4, and seconds per draw. FlowPlace and PARSAC run no loop. [‡]PARSAC on the FloorSet val set, one worker / best of 4, seconds per worker.


Method	Raw sample			Refined				Legalized				
	Overlap	WL	Area	Overlap	WL	Area	Soft	WL	Area	V_{rel}	Hard cost	s/draw
Trinity	0.023	-0.1	+0.2	0.002	+0.3	+1.1	1.06	+9.3	+10.5	0.045	1.234 / 1.089	0.28
FlowPlace	0.044	-0.2	+0.9	-	-	-	-	+18.5	+21.6	0.114	1.567 / 1.343	0.36
ChipDiffusion	0.051	-0.1	+1.2	0.007	+5.3	+11.7	2.05	+15.5	+18.2	0.114	1.521 / 1.300	0.41
MacroDiff+	0.064	+0.2	+2.4	0.003	+7.2	+12.7	1.66	+15.9	+18.3	0.122	1.546 / 1.308	0.39
DiffPlace	0.113	-0.3	+1.2	0.002	+6.7	+29.9	3.91	+13.9	+19.1	0.121	1.537 / 1.313	0.36
PARSAC [‡]	0.000	+36.1	+6.2	-	-	-	-	+47.2	+22.2	0.091	1.685 / 1.348	1,120

which ties its practical role to the theoretical choice of head. The information mover complements this choice through improved constraint objectives. Joint physics training improves every constraint metric without sacrificing the backbone’s wirelength or area. The resulting configuration combines the only head with a valid single-step layout and all six physics functions for the best trade-off. These gains persist down to the parameter count of the ported networks, where depth contributes more than width (Fig. 3, Table 4, and Section O). The improvement also exceeds the variation across seeds in Sections H and M. This stability thus supports the contribution of the shared differentiable physics at the raw stage, where its role in training is assessed ahead of any refinement.

Table 3 compares raw layouts across generators, while Table 4 reports whether the quality advantage persists under restricted sampling budgets. Regressors average symmetric optima (Proposition D.2), whereas the log-aspect latent preserves block areas (Proposition D.1, Section K.2). Against the four ported placers, Trinity produces substantially better raw layouts and remains effective at the smallest evaluated sampling budgets, where the competing generators degrade severely or disperse their layouts. PARSAC on the FloorSet val set illustrates the trade-off of annealing, which avoids overlap at the expense of wirelength and area. Within the diffusion family, the models preserve the reference objectives, whereas the physics term distinguishes Trinity on overlap and soft constraints. Their own sampler-time guidance does not substitute for the physics: it lowers the term it targets, raises the terms it does not model, and leaves every guided sample above Trinity’s free one (Tables 4 and 5, Section J). This separation identifies a training contribution before refinement and sets the raw starting point for assessing its short-budget benefit apart from the refiner’s control of the endpoint.

4.3 REFINEMENT UNDER THE TRAINING ENERGY

Table 5 compares refined soft cost across sampling and refinement budgets, with the convergence traced in Fig. 1. After a few hundred refinement steps, samples from every sampling budget reach nearly the same soft cost, which supports a low-budget draw followed by refinement, while the training physics keeps a substantial short-budget advantage over the $\lambda=0$ backbone (Section I), the training contribution that an endpoint comparison alone would conceal. Fig. 6 traces constraint improvement under the shared refiner against the ported placers’ released-loop outcomes, with wirelength and area preserved in Table 3. In Fig. 4, ChipDiffusion’s loop trades overlap for a wider cluster gap, whereas our refiner removes overlap without opening the cluster, which supports one set of six physics quantities across training, refinement and scoring. On the references, Fig. 5 (b)–(c)






Figure 4: One raw draw of a 67-block case under ChipDiffusion’s loop (top) and our refiner (bottom), early and late, the boxed region magnified beside each layout: left where the loop’s early state keeps the most overlap, right the cluster it opens most. Clusters coloured, pre-placed hatched, boundary-coded dashed, overlap red. Below each layout, the overlap ratio and the cluster gap in 10^{-3} .

Table 4: Raw soft cost at four sampling budgets NFE, with FLD and MMD (10^{-3}) at NFE 32 / 1; the rungs 384 / 12 and 256 / 12 give width / depth, and the guided rows sample under each placer’s own guidance.

Generator	1	4	8	32	FLD	MMD
Trinity	1.68	1.63	1.60	1.51	0.042 / 0.162	2.48 / 9.63
Trinity at $\lambda=0$	2.43	2.25	2.16	2.02	0.112 / 0.426	21.7 / 35.1
Trinity, 384 / 12	1.76	1.72	1.69	1.61	0.044 / 0.156	3.71 / 12.7
Trinity, 256 / 12	1.81	1.78	1.76	1.70	0.055 / 0.157	5.00 / 10.7
FlowPlace	11.5	5.09	3.82	2.46	0.227 / 3.77	24.4 / 350
ChipDiffusion	152	11.9	3.83	2.80	0.273 / 102	31.2 / 1,223
MacroDiff+	150	71.7	9.89	3.85	0.624 / 102	81.5 / 1,216
DiffPlace	150	99.5	14.6	6.23	2.86 / 102	247 / 1,230
ChipDiffusion, guided	88.3	5.96	3.97	3.78	3.10 / 101	512 / 1,171
MacroDiff+, guided	54.1	10.8	3.20	2.04	4.36 / 92.1	615 / 1,077
DiffPlace, guided	158	228	418	132	19.7 / 102	594 / 1,231

Table 5: Soft cost along our shared refiner at 0 (raw), 25, 100 and 400 steps; the guided rows start from guided samples. Bold marks the best soft cost per column.

Generator, sampling budget	raw	25	100	400
Trinity, NFE 1	1.68	1.31	1.15	1.07
Trinity, NFE 8	1.60	1.26	1.12	1.06
Trinity, NFE 32	1.51	1.22	1.11	1.06
Trinity at $\lambda=0$, NFE 1	2.43	1.35	1.16	1.07
FlowPlace, NFE 32	2.46	1.42	1.22	1.11
ChipDiffusion, NFE 32	2.80	1.52	1.27	1.13
MacroDiff+, NFE 32	3.85	1.71	1.35	1.17
DiffPlace, NFE 32	6.23	2.61	1.57	1.20
ChipDiffusion, guided	3.78	1.83	1.29	1.15
MacroDiff+, guided	2.04	1.59	1.32	1.22
DiffPlace, guided	132	30.1	5.55	1.87

Table 6: Generator $\times$ loop first-draw hard cost at NFE=32, columns short for the rows; none: no loop, darker cells a placer’s own loop, bold best per column.

Gen \ loop	none	CD	DP	MD+	ours
Trinity	1.513	1.456	1.442	1.442	1.234
FlowPlace	1.567	1.495	1.454	1.471	1.296
ChipDiffusion	1.609	1.521	1.483	1.492	1.322
DiffPlace	1.731	1.587	1.537	1.539	1.355
MacroDiff+	1.672	1.571	1.536	1.546	1.352

Table 7: FloorSet val set: the best of N draws per budget pair, with the mean hard cost, sec per case, and WL and area gaps in %.

NFE	Steps	N	Mean	sec	WL	Area
32	400	48	1.015	1.86	-0.3	-0.1
8	400	48	1.014	1.63	-0.4	+0.0
8	400	16	1.019	1.14	-0.2	+0.4
4	100	16	1.043	0.63	+0.3	+1.7
1	50	16	1.115	0.48	+2.7	+5.5

Table 8: GSRC HPWL in mm: bold best, underline second; *our reproduction, **their published numbers, $\dagger$ outline above GSRC’s 110% area bound.

Method	n100	n200	n300
Trinity	294.7	554.9	681.3$\dagger$
Trinity at $\lambda=0$	293.9	560.1 $\dagger$	679.8 $\dagger$
PARSAC, Bo16*	303.5	576.0	709.3
PARSAC, Bo12**	288	526	627
GoodFloorplan**	319	575	<u>705</u>




Figure 5: (a) The gap between Trinity and its $\lambda=0$ backbone along $-\nabla U$ at three physics weights, with the seed floor (grey), the proximal prediction $\gamma_t \|\nabla U\|$ and a t^2 guide. (b, c) The 12,000 reference layouts through each placer’s loop, with the original references dotted in (c).

separates corrective refinement from motion that degrades the objectives: our refiner moves movable blocks by 0.0055 of the scale and lowers soft cost in 85% of cases, whereas the released loops move them by 0.025 to 0.029 and raise the cost in every case from 1.065 to 1.54 to 2.58 through wavelength and area, in line with the small-step account of Proposition 3.2(ii) (Section G). On a ported generator’s samples our refiner matches the own-loop soft cost in a fraction of the steps and the time, and 400 of its steps carry each generator below its own loop’s endpoint, with or without its guidance (Tables 3 and 5, Section J). Table 9 compares the cost of matching each ported placer’s own-loop soft




Figure 6: The four constraint quantities, overlap, cluster gap, MIB variance and boundary distance, along our refiner at NFE=32, hollow markers each ported loop at its released count.




Figure 7: (a) FloorSet val set, every Trinity setting of NFE, steps and N against PARSAC at 10^4 – 10^7 steps per worker. (b) One point per setting of NFE and steps. (c, d) Along our refiner, NFE=32: the legalizer’s median expansion factor and the per-draw soft-hard correlation.

Table 9: Each loop against ours: Iterations Table 10: Soft against legalized hard cost per generator pairs the loop’s released count with our line: Spearman ρ and Kendall τ , across the cell means steps to the same soft cost, and μ s per step of the NFE $\times$ steps grid and over every draw; CD, DP and the time advantage read at 32 / 1,000 and MD+ as in Table 6, and the all-eight column adds layouts per batch on the RTX 5090. Trinity at $\lambda=0$ and the two regressors of Section 4.1.

Loop	Iterations	μ s / step	Less time	Correlation	Trinity	FlowPlace	CD	DP	MD+	all eight
our refiner	–	50.8 / 2.6	–	across cells, ρ	0.938	0.923	0.989	0.975	0.985	0.947
DiffPlace	500 / 9	60.7 / 3.1	67 $\times$ / 67 $\times$	across cells, τ	0.754	0.738	0.919	0.898	0.919	0.807
MacroDiff+	500 / 31	292.5 / 20.7	92 $\times$ / 129 $\times$	over draws, ρ	0.472	0.369	0.805	0.858	0.861	0.768
ChipDiffusion	5,000 / 8	69.6 / 5.3	904 $\times$ / 1,359 $\times$	over draws, τ	0.326	0.252	0.619	0.665	0.671	0.578

cost with iteration counts and per-step time, not wall-clock measurements. The training term thus governs raw layouts and short-budget quality, and the refiner the converged endpoint.

4.4 LEGALIZED LAYOUTS AND THE OFFICIAL HARD COST

Table 3 and Table 6 compare legalized outcomes for the ported pipelines and for generators under a shared refiner, respectively. The advantage of Trinity over the ported placers persists in the official hard cost on feasible layouts, while the compression of generator differences under the shared refiner shows why endpoint comparisons understate generator quality. The narrowed differences indicate that refinement determines much of the final hard cost, (Section K). This dependence on refinement motivates comparing generators under a shared refiner within the stage-by-stage evaluation. Fig. 7 (b)–(d) traces the relation between soft cost and legalized hard cost that supports this stage-by-stage evaluation. Agreement between the two costs supports the soft cost as a proxy for comparing settings, with caution for individual draws early in refinement. Across the evaluated Trinity settings, mean soft and hard costs correlate strongly across the generator lines (Table 10). At the individual-draw level, the initially weaker correlation improves as refinement produces samples that are easier to legalize. The soft cost therefore evaluates generators and refiners without a legalizer run for every experiment.

Table 7 and Table 8 report the practical performance and transfer limits of the resulting legalized layouts. On FloorSet, the hard cost of Trinity approaches the reference cost at a small fraction of the computation PARSAC spends, consistent with Fig. 7 (a). Within the GSRC training range, the variant without the physics term matches the full model, as expected in distribution. Beyond that range, the six terms separate the variants and carry the model to larger block counts. At still larger sizes, no current checkpoint fits the outline (Section G.4). The remaining limit therefore lies in the training range rather than the physics itself, which supports transfer beyond that range in the evaluated cases.

5 CONCLUSION

Generative floorplanners placed the coupled objectives and constraints of floorplanning everywhere except where the model learns, and endpoint scores hid what each stage contributed. Trinity moved the coupled system into training: one energy of six differentiable functions served as a term of its loss, as the energy its refiner descends in closed form, and as the base of a soft cost that scored every stage, so sampling ran without guidance. Measured on that one scale, training and refinement played distinct roles. The training term improved every raw constraint at once and mattered most at short refinement budgets, while the refiner decided most of the final cost and carried every ported generator below its own loop in far fewer steps. Generators were therefore best compared under a shared refiner, and the soft cost, which ranked settings as the hard cost does, supported that comparison before legalization. With positions and shapes treated alike, Trinity covers the full constraint family of floorplanning and stays ahead of the ported pipelines after legalization.

AI USE STATEMENT

Generative AI tools were used for writing assistance, drafting passages and correcting grammar, and for visualizing results, where they wrote the plotting code that renders the figures from the result files. The authors reviewed every AI-assisted passage and figure and take responsibility for the content.

REPRODUCIBILITY STATEMENT

Every trained model in this paper, the ported prior placers included, uses the frozen recipe of Section 4.1 and Appendix B.2. The six constraint quantities, the refiner and the legalizer are specified in Section 3 and Appendices E and F, and every scoring rule in Appendix C. FloorSet and the ICCAD 2026 evaluator are public. The supplementary material is the code needed to reproduce the study, the solver-agnostic domain library and the generator library, with the configuration file of every trained arm, every refiner sweep and every legalizer run, and the scripts that print every table from what a run writes (Appendix R).

REFERENCES

- Saurabh N. Adya and Igor L. Markov. Fixed-outline floorplanning through better local search. In *19th International Conference on Computer Design (ICCD 2001), VLSI in Computers and Processors, 23-26 September 2001, Austin, TX, USA, Proceedings*, pp. 328–334. IEEE Computer Society, 2001. doi: 10.1109/ICCD.2001.955047. URL <https://doi.org/10.1109/ICCD.2001.955047>.
- Saurabh N. Adya and Igor L. Markov. Fixed-outline floorplanning: enabling hierarchical design. *IEEE Trans. Very Large Scale Integr. Syst.*, 11(6):1120–1135, 2003. doi: 10.1109/TVLSI.2003.817546. URL <https://doi.org/10.1109/TVLSI.2003.817546>.
- Saurabh N. Adya, Mehmet Can Yildiz, Igor L. Markov, Paul Villarrubia, Phiroze N. Parakh, and Patrick H. Madden. Benchmarking for large-scale placement and beyond. *IEEE Trans. Comput. Aided Des. Integr. Circuits Syst.*, 23(4):472–487, 2004. doi: 10.1109/TCAD.2004.825852. URL <https://doi.org/10.1109/TCAD.2004.825852>.
- Mohammad Amini, Zhanguang Zhang, Surya Penmetsa, Yingxue Zhang, Jianye Hao, and Wulong Liu. Generalizable floorplanner through corner block list representation and hypergraph embedding. In Aidong Zhang and Huzefa Rangwala (eds.), *KDD '22: The 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, Washington, DC, USA, August 14 - 18, 2022*, pp. 2692–2702. ACM, 2022. doi: 10.1145/3534678.3539220. URL <https://doi.org/10.1145/3534678.3539220>.
- Fan Bao, Shen Nie, Kaiwen Xue, Yue Cao, Chongxuan Li, Hang Su, and Jun Zhu. All are worth words: A ViT backbone for diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 22669–22679, June 2023.
- Jan-Hendrik Bastek, WaiChing Sun, and Dennis M. Kochmann. Physics-informed diffusion models. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore*,

- April 24-28, 2025. OpenReview.net, 2025. URL <https://openreview.net/forum?id=tpYeermigp>.
- Mikhail Belkin and Partha Niyogi. Laplacian eigenmaps for dimensionality reduction and data representation. *Neural Comput.*, 15(6):1373–1396, 2003. doi: 10.1162/089976603321780317. URL <https://doi.org/10.1162/089976603321780317>.
- Zhuomin Chai, Yuxiang Zhao, Yibo Lin, Wei Liu, Runsheng Wang, and Ru Huang. Circuitnet: An open-source dataset for machine learning applications in electronic design automation (eda). 2022. doi: 10.48550/ARXIV.2208.01040. URL <https://arxiv.org/abs/2208.01040>.
- Yun-Chih Chang, Yao-Wen Chang, Guang-Ming Wu, and Shu-Wei Wu. B*-trees: a new representation for non-slicing floorplans. In Giovanni De Micheli (ed.), *Proceedings of the 37th Conference on Design Automation, Los Angeles, CA, USA, June 5-9, 2000*, pp. 458–463. ACM, 2000. doi: 10.1145/337292.337541. URL <https://doi.org/10.1145/337292.337541>.
- Jian Chen, Ruiyi Zhang, Yufan Zhou, Rajiv Jain, Zhiqiang Xu, Ryan Rossi, and Changyou Chen. Towards aligned layout generation via diffusion model with aesthetic constraints. In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net, 2024. URL <https://openreview.net/forum?id=kJ0qp9Xdsh>.
- Tung-Chieh Chen, Zhe-Wei Jiang, Tien-Chang Hsu, Hsin-Chen Chen, and Yao-Wen Chang. NTU-place3: An analytical placer for large-scale mixed-size designs with preplaced blocks and density constraints. *IEEE Trans. Comput. Aided Des. Integr. Circuits Syst.*, 27(7):1228–1240, 2008a. doi: 10.1109/TCAD.2008.923063. URL <https://doi.org/10.1109/TCAD.2008.923063>.
- Tung-Chieh Chen, Ping-Hung Yuh, Yao-Wen Chang, Fwu-Juh Huang, and Tien-Yueh Liu. Mp-trees: A packing-based macro placement algorithm for modern mixed-size designs. *IEEE Trans. Comput. Aided Des. Integr. Circuits Syst.*, 27(9):1621–1634, 2008b. doi: 10.1109/TCAD.2008.927760. URL <https://doi.org/10.1109/TCAD.2008.927760>.
- Chung-Kuan Cheng, Andrew B. Kahng, Ilgweon Kang, and Lutong Wang. Replace: Advancing solution quality and routability validation in global placement. *IEEE Trans. Comput. Aided Des. Integr. Circuits Syst.*, 38(9):1717–1730, 2019. doi: 10.1109/TCAD.2018.2859220. URL <https://doi.org/10.1109/TCAD.2018.2859220>.
- Chung-Kuan Cheng, Andrew B. Kahng, Sayak Kundu, Yucheng Wang, and Zhiang Wang. Assessment of reinforcement learning for macro placement. In David G. Chinnery and Iris Hui-Ru Jiang (eds.), *Proceedings of the 2023 International Symposium on Physical Design, ISPD 2023, Virtual Event, USA, March 26-29, 2023*, pp. 158–166. ACM, 2023. doi: 10.1145/3569052.3578926. URL <https://doi.org/10.1145/3569052.3578926>.
- Ruoyu Cheng and Junchi Yan. On joint learning for solving placement and routing in chip design. In Marc’Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 16508–16519, 2021. URL <https://proceedings.neurips.cc/paper/2021/hash/898aef0932f6aaecda27aba8e9903991-Abstract.html>.
- Hyungjin Chung, Jeongsol Kim, Michael Thompson McCann, Marc Louis Klasky, and Jong Chul Ye. Diffusion posterior sampling for general noisy inverse problems. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net, 2023. URL <https://openreview.net/forum?id=OnD9zGAGT0k>.
- Ji Deng, Zhao Li, Ji Zhang, and Jun Gao. EGPlace: An efficient macro placement method via evolutionary search with greedy repositioning guided mutation. In Aarti Singh, Maryam Fazel, Daniel Hsu, Simon Lacoste-Julien, Felix Berkenkamp, Tegan Maharaj, Kiri Wagstaff, and Jerry Zhu (eds.), *Forty-second International Conference on Machine Learning, ICML 2025, Vancouver, BC, Canada, July 13-19, 2025*, volume 267 of *Proceedings of Machine Learning Research*, pp. 13237–13255. PMLR / OpenReview.net, 2025. URL <https://proceedings.mlr.press/v267/deng25g.html>.

- Prafulla Dhariwal and Alexander Quinn Nichol. Diffusion models beat gans on image synthesis. In Marc’Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 8780–8794, 2021. URL <https://proceedings.neurips.cc/paper/2021/hash/49ad23d1ec9fa4bd8d77d02681df5cfa-Abstract.html>.
- Vijay Prakash Dwivedi and Xavier Bresson. A generalization of transformer networks to graphs. *CoRR*, abs/2012.09699, 2020. URL <https://arxiv.org/abs/2012.09699>.
- Vijay Prakash Dwivedi, Anh Tuan Luu, Thomas Laurent, Yoshua Bengio, and Xavier Bresson. Graph neural networks with learnable structural and positional representations. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net, 2022. URL <https://openreview.net/forum?id=wTjnvGphYj>.
- Vijay Prakash Dwivedi, Chaitanya K. Joshi, Anh Tuan Luu, Thomas Laurent, Yoshua Bengio, and Xavier Bresson. Benchmarking graph neural networks. *J. Mach. Learn. Res.*, 24:43:1–43:48, 2023. URL <https://jmlr.org/papers/v24/22-0567.html>.
- Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Axel Sauer, Frederic Boesel, Dustin Podell, Tim Dockhorn, Zion English, and Robin Rombach. Scaling rectified flow transformers for high-resolution image synthesis. In Ruslan Salakhutdinov, Zico Kolter, Katherine A. Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*, volume 235 of *Proceedings of Machine Learning Research*, pp. 12606–12633. PMLR / OpenReview.net, 2024. URL <https://proceedings.mlr.press/v235/esser24a.html>.
- Chengrui Gao, Yunqi Shi, Ke Xue, Ruo-Tong Chen, Siyuan Xu, Mingxuan Yuan, Chao Qian, and Zhi-Hua Zhou. Expertise can be helpful for reinforcement learning-based macro placement. In C. Vondrick, B. Hariharan, C. Raffel, L. Pinto, D. Yang, and A. Faust (eds.), *International Conference on Learning Representations*, volume 2026, pp. 125611–125634, 2026. URL https://proceedings.iclr.cc/paper_files/paper/2026/file/cbclad2066f0afebbcea930c5688fc1f-Paper-Conference.pdf.
- Zijie Geng, Jie Wang, Ziyang Liu, Siyuan Xu, Zhentao Tang, Mingxuan Yuan, Jianye Hao, Yongdong Zhang, and Feng Wu. Reinforcement learning within tree search for fast macro placement. In Ruslan Salakhutdinov, Zico Kolter, Katherine A. Heller, Adrian Weller, Nuria Oliver, Jonathan Scarlett, and Felix Berkenkamp (eds.), *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*, volume 235 of *Proceedings of Machine Learning Research*, pp. 15402–15417. PMLR / OpenReview.net, 2024. URL <https://proceedings.mlr.press/v235/geng24b.html>.
- Zijie Geng, Jie Wang, Ziyang Liu, Siyuan Xu, Zhentao Tang, Shixiong Kai, Mingxuan Yuan, Jianye Hao, and Feng Wu. LaMPlace: Learning to optimize cross-stage metrics in macro placement. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net, 2025. URL <https://openreview.net/forum?id=YLIsIzC74j>.
- Arthur Gretton, Karsten M. Borgwardt, Malte J. Rasch, Bernhard Schölkopf, and Alexander J. Smola. A kernel two-sample test. *J. Mach. Learn. Res.*, 13:723–773, 2012. doi: 10.5555/2503308.2188410. URL <https://dl.acm.org/doi/10.5555/2503308.2188410>.
- Pei-Ning Guo, Chung-Kuan Cheng, and Takeshi Yoshimura. An o-tree representation of non-slicing floorplan and its applications. In Mary Jane Irwin (ed.), *Proceedings of the 36th Conference on Design Automation, New Orleans, LA, USA, June 21-25, 1999*, pp. 268–273. ACM Press, 1999. doi: 10.1145/309847.309928. URL <https://doi.org/10.1145/309847.309928>.
- Kenneth M. Hall. An r-dimensional quadratic placement algorithm. *Management Science*, 17(3):219–229, November 1970. ISSN 1526-5501. doi: 10.1287/mnsc.17.3.219. URL <http://dx.doi.org/10.1287/mnsc.17.3.219>.

- Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. GANs trained by a two time-scale update rule converge to a local Nash equilibrium. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 6626–6637, 2017. URL <https://proceedings.neurips.cc/paper/2017/hash/8ald694707eb0fefe65871369074926d-Abstract.html>.
- Jonathan Ho and Tim Salimans. Classifier-free diffusion guidance, 2022. URL <https://arxiv.org/abs/2207.12598>.
- Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In Hugo Larochelle, Marc’Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL <https://proceedings.neurips.cc/paper/2020/hash/4c5bcfec8584af0d967f1ab10179ca4b-Abstract.html>.
- Xianlong Hong, Gang Huang, Yici Cai, Jiangchun Gu, Sheqin Dong, Chung-Kuan Cheng, and Jun Gu. Corner block list: An effective and efficient topological representation of non-slicing floorplan. In Ellen Sentovich (ed.), *Proceedings of the 2000 IEEE/ACM International Conference on Computer-Aided Design, 2000, San Jose, California, USA, November 5-9, 2000*, pp. 8–12. IEEE Computer Society, 2000. doi: 10.1109/ICCAD.2000.896442. URL <https://doi.org/10.1109/ICCAD.2000.896442>.
- Emiel Hoogetboom, Víctor Garcia Satorras, Clément Vignac, and Max Welling. Equivariant diffusion for molecule generation in 3D. In Kamalika Chaudhuri, Stefanie Jegelka, Le Song, Csaba Szepesvári, Gang Niu, and Sivan Sabato (eds.), *International Conference on Machine Learning, ICML 2022, 17-23 July 2022, Baltimore, Maryland, USA*, volume 162 of *Proceedings of Machine Learning Research*, pp. 8867–8887. PMLR, 2022. URL <https://proceedings.mlr.press/v162/hoogetboom22a.html>.
- Guyue Huang, Jingbo Hu, Yifan He, Jialong Liu, Mingyuan Ma, Zhaoyang Shen, Juejian Wu, Yuanfan Xu, Hengrui Zhang, Kai Zhong, Xuefei Ning, Yuzhe Ma, Haoyu Yang, Bei Yu, Huazhong Yang, and Yu Wang. Machine learning for electronic design automation: A survey. *ACM Transactions on Design Automation of Electronic Systems*, 26(5):1–46, 2021. ISSN 1557-7309. doi: 10.1145/3451179. URL <http://dx.doi.org/10.1145/3451179>.
- ICCAD. ICCAD 2026 CAD contest, problem C. <https://www.iccad-contest.org/Problems.html>, 2026.
- Naoto Inoue, Kotaro Kikuchi, Edgar Simo-Serra, Mayu Otani, and Kota Yamaguchi. LayoutDM: Discrete diffusion model for controllable layout generation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2023, Vancouver, BC, Canada, June 17-24, 2023*, pp. 10167–10176. IEEE, 2023. doi: 10.1109/CVPR52729.2023.00980. URL <https://doi.org/10.1109/CVPR52729.2023.00980>.
- Andrew B. Kahng, Jens Lienig, Igor L. Markov, and Jin Hu. *VLSI Physical Design: From Graph Partitioning to Timing Closure*. Springer Netherlands, 2011. ISBN 9789048195916. doi: 10.1007/978-90-481-9591-6. URL <http://dx.doi.org/10.1007/978-90-481-9591-6>.
- Tero Karras, Miika Aittala, Timo Aila, and Samuli Laine. Elucidating the design space of diffusion-based generative models. In Sanmi Koyejo, S. Mohamed, A. Agarwal, Danielle Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9, 2022*, 2022. URL http://papers.nips.cc/paper_files/paper/2022/hash/a98846e9d9cc01cfb87eb694d946ce6b-Abstract-Conference.html.
- Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015.

- Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL <https://openreview.net/forum?id=SJU4ayYgl>.
- S. Kirkpatrick, C. D. Gelatt, and M. P. Vecchi. Optimization by simulated annealing. *Science*, 220(4598):671–680, May 1983. ISSN 1095-9203. doi: 10.1126/science.220.4598.671. URL <http://dx.doi.org/10.1126/science.220.4598.671>.
- Jürgen M. Kleinohans, Georg Sigl, Frank M. Johannes, and Kurt Antreich. GORDIAN: VLSI placement by quadratic programming and slicing optimization. *IEEE Trans. Comput. Aided Des. Integr. Circuits Syst.*, 10(3):356–365, 1991. doi: 10.1109/43.67789. URL <https://doi.org/10.1109/43.67789>.
- Yehuda Koren. On spectral graph drawing. In Tandy J. Warnow and Binhai Zhu (eds.), *Computing and Combinatorics, 9th Annual International Conference, COCOON 2003, Big Sky, MT, USA, July 25-28, 2003, Proceedings*, volume 2697 of *Lecture Notes in Computer Science*, pp. 496–508. Springer, 2003. doi: 10.1007/3-540-45071-8_50. URL https://doi.org/10.1007/3-540-45071-8_50.
- Krzysztof Kozminski. Benchmarks for layout synthesis - evolution and current status. In A. Richard Newton (ed.), *Proceedings of the 28th Design Automation Conference, San Francisco, California, USA, June 17-21, 1991*, pp. 265–270. ACM, 1991. doi: 10.1145/127601.127678. URL <https://doi.org/10.1145/127601.127678>.
- Devin Kreuzer, Dominique Beaini, William L. Hamilton, Vincent Létourneau, and Prudencio Tossou. Rethinking graph transformers with spectral attention. In Marc’Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 21618–21629, 2021. URL <https://proceedings.neurips.cc/paper/2021/hash/b4fd1d2cb085390fbbadae65e07876a7-Abstract.html>.
- Yao Lai, Yao Mu, and Ping Luo. MaskPlace: Fast chip placement via reinforced visual representation learning. In Sanmi Koyejo, S. Mohamed, A. Agarwal, Danielle Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9, 2022*, 2022. URL http://papers.nips.cc/paper_files/paper/2022/hash/97c8a8eb0e5231d107d0da51b79e09cb-Abstract-Conference.html.
- Yao Lai, Jinxin Liu, Zhentao Tang, Bin Wang, Jianye Hao, and Ping Luo. ChiPFormer: Transferable chip placement via offline decision transformer. In Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett (eds.), *International Conference on Machine Learning, ICML 2023, 23-29 July 2023, Honolulu, Hawaii, USA*, volume 202 of *Proceedings of Machine Learning Research*, pp. 18346–18364. PMLR, 2023. URL <https://proceedings.mlr.press/v202/lai23c.html>.
- Vint Lee, Minh Nguyen, Leena Elzeiny, Chun Deng, Pieter Abbeel, and John Wawrzynek. Chip placement with diffusion models. In Aarti Singh, Maryam Fazel, Daniel Hsu, Simon Lacoste-Julien, Felix Berkenkamp, Tegan Maharaj, Kiri Wagstaff, and Jerry Zhu (eds.), *Forty-second International Conference on Machine Learning, ICML 2025, Vancouver, BC, Canada, July 13-19, 2025*, volume 267 of *Proceedings of Machine Learning Research*, pp. 33499–33514. PMLR / OpenReview.net, 2025. URL <https://proceedings.mlr.press/v267/lee25y.html>.
- Tianhong Li and Kaiming He. Back to basics: Let denoising generative models denoise. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 36115–36125, June 2026.
- Jai-Ming Lin and Yao-Wen Chang. TCG: A transitive closure graph-based representation for non-slicing floorplans. In *Proceedings of the 38th Design Automation Conference, DAC 2001, Las Vegas, NV, USA, June 18-22, 2001*, pp. 764–769. ACM, 2001. doi: 10.1145/378239.379062. URL <https://doi.org/10.1145/378239.379062>.

- Yibo Lin, Zixuan Jiang, Jiaqi Gu, Wuxi Li, Shounak Dhar, Haoxing Ren, Bruce Khailany, and David Z. Pan. DREAMPlace: Deep learning toolkit-enabled GPU acceleration for modern VLSI placement. *IEEE Trans. Comput. Aided Des. Integr. Circuits Syst.*, 40(4):748–761, 2021. doi: 10.1109/TCAD.2020.3003843. URL <https://doi.org/10.1109/TCAD.2020.3003843>.
- Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, and Matthew Le. Flow matching for generative modeling. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net, 2023. URL <https://openreview.net/forum?id=PqvMRDCJT9t>.
- Xingchao Liu, Chengyue Gong, and Qiang Liu. Flow straight and fast: Learning to generate and transfer data with rectified flow. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net, 2023a. URL <https://openreview.net/forum?id=XVjTTlnw5z>.
- Yiting Liu, Ziyi Ju, Zhengming Li, Mingzhi Dong, Hai Zhou, Jia Wang, Fan Yang, Xuan Zeng, and Li Shang. GraphPlanner: Floorplanning with graph neural network. *ACM Trans. Design Autom. Electr. Syst.*, 28(2):21:1–21:24, 2023b. doi: 10.1145/3555804. URL <https://doi.org/10.1145/3555804>.
- Jingwei Lu, Pengwen Chen, Chin-Chih Chang, Lu Sha, Dennis Jen-Hsin Huang, Chin-Chi Teng, and Chung-Kuan Cheng. ePlace: Electrostatics-based placement using fast Fourier transform and Nesterov’s method. *ACM Trans. Design Autom. Electr. Syst.*, 20(2):17:1–17:34, 2015. doi: 10.1145/2699873. URL <https://doi.org/10.1145/2699873>.
- Nanye Ma, Mark Goldstein, Michael S. Albergo, Nicholas M. Boffi, Eric Vanden-Eijnden, and Saining Xie. SiT: Exploring flow and diffusion-based generative models with scalable interpolant transformers. In Ales Leonardis, Elisa Ricci, Stefan Roth, Olga Russakovsky, Torsten Sattler, and Gül Varol (eds.), *Computer Vision - ECCV 2024 - 18th European Conference, Milan, Italy, September 29-October 4, 2024, Proceedings, Part LXXVII*, volume 15135 of *Lecture Notes in Computer Science*, pp. 23–40. Springer, 2024. doi: 10.1007/978-3-031-72980-5_2. URL https://doi.org/10.1007/978-3-031-72980-5_2.
- Uday Mallappa, Hesham Mostafa, Mikhail Galkin, Mariano Phielipp, and Somdeb Majumdar. FloorSet - a VLSI floorplanning dataset with design constraints of real-world SoCs. In Jinjun Xiong and Robert Wille (eds.), *Proceedings of the 43rd IEEE/ACM International Conference on Computer-Aided Design, ICCAD 2024, Newark Liberty International Airport Marriott, NJ, USA, October 27-31, 2024*, pp. 118:1–118:9. ACM, 2024. doi: 10.1145/3676536.3676814. URL <https://doi.org/10.1145/3676536.3676814>.
- Igor L. Markov. Reevaluating google’s reinforcement learning for IC macro placement. *Commun. ACM*, 67(11):60–71, 2024. doi: 10.1145/3676845. URL <https://doi.org/10.1145/3676845>.
- Igor L. Markov, Jin Hu, and Myung-Chul Kim. Progress and challenges in VLSI placement research. *Proc. IEEE*, 103(11):1985–2003, 2015. doi: 10.1109/JPROC.2015.2478963. URL <https://doi.org/10.1109/JPROC.2015.2478963>.
- Azalia Mirhoseini, Anna Goldie, Mustafa Yazgan, Joe Wenjie Jiang, Ebrahim M. Songhori, Shen Wang, Young-Joon Lee, Eric Johnson, Omkar Pathak, Azade Nova, Jiwoo Pak, Andy Tong, Kavya Srinivasa, William Hang, Emre Tuncer, Quoc V. Le, James Laudon, Richard Ho, Roger Carpenter, and Jeff Dean. A graph placement methodology for fast chip design. *Nat.*, 594(7862): 207–212, 2021. doi: 10.1038/S41586-021-03544-W. URL <https://doi.org/10.1038/S41586-021-03544-W>.
- Hesham Mostafa, Uday Mallappa, Mikhail Galkin, Mariano Phielipp, and Somdeb Majumdar. Parsac: Fast, human-quality floorplanning for modern socs with complex design constraints, 2024. URL <https://arxiv.org/abs/2405.05495>.
- Hiroshi Murata and Ernest S. Kuh. Sequence-pair based placement method for hard/soft/pre-placed modules. In Majid Sarrafzadeh (ed.), *Proceedings of the 1998 International Symposium on Physical Design, ISPD 1998, Monterey, CA, USA, April 6-8, 1998*, pp. 167–172. ACM, 1998. doi: 10.1145/274535.274560. URL <https://doi.org/10.1145/274535.274560>.

- Hiroshi Murata, Kunihiro Fujiyoshi, Shigetoshi Nakatake, and Yoji Kajitani. VLSI module placement based on rectangle-packing by the sequence-pair. *IEEE Trans. Comput. Aided Des. Integr. Circuits Syst.*, 15(12):1518–1524, 1996. doi: 10.1109/43.552084. URL <https://doi.org/10.1109/43.552084>.
- Shigetoshi Nakatake, Kunihiro Fujiyoshi, Hiroshi Murata, and Yoji Kajitani. Module placement on bsg-structure and IC layout applications. In Rob A. Rutenbar and Ralph H. J. M. Otten (eds.), *Proceedings of the 1996 IEEE/ACM International Conference on Computer-Aided Design, ICCAD 1996, San Jose, CA, USA, November 10-14, 1996*, pp. 484–491. IEEE Computer Society / ACM, 1996. doi: 10.1109/ICCAD.1996.569870. URL <https://doi.org/10.1109/ICCAD.1996.569870>.
- Gi-Joon Nam. ISPD 2006 placement contest: Benchmark suite and results. In Louis Scheffer (ed.), *Proceedings of the 2006 International Symposium on Physical Design, ISPD 2006, San Jose, California, USA, April 9-12, 2006*, pp. 167. ACM, 2006. doi: 10.1145/1123008.1123042. URL <https://doi.org/10.1145/1123008.1123042>.
- Gi-Joon Nam, Charles J. Alpert, Paul Villarrubia, Bruce Winter, and Mehmet Can Yildiz. The ISPD2005 placement contest and benchmark suite. In Patrick Groeneveld and Louis Scheffer (eds.), *Proceedings of the 2005 International Symposium on Physical Design, ISPD 2005, San Francisco, California, USA, April 3-6, 2005*, pp. 216–220. ACM, 2005. doi: 10.1145/1055137.1055182. URL <https://doi.org/10.1145/1055137.1055182>.
- Alexander Quinn Nichol and Prafulla Dhariwal. Improved denoising diffusion probabilistic models. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 8162–8171. PMLR, 2021. URL <http://proceedings.mlr.press/v139/nichol21a.html>.
- Ralph H. J. M. Otten. Automatic floorplan design. In James S. Crabbe, Charles E. Radke, and Hillel Ofek (eds.), *Proceedings of the 19th Design Automation Conference, DAC '82, Las Vegas, Nevada, USA, June 14-16, 1982*, pp. 261–267. ACM/IEEE, 1982. doi: 10.1145/800263.809216. URL <https://doi.org/10.1145/800263.809216>.
- William Peebles and Saining Xie. Scalable diffusion models with transformers. In *IEEE/CVF International Conference on Computer Vision, ICCV 2023, Paris, France, October 1-6, 2023*, pp. 4172–4182. IEEE, 2023. doi: 10.1109/ICCV51070.2023.00387. URL <https://doi.org/10.1109/ICCV51070.2023.00387>.
- Ladislav Rampášek, Michael Galkin, Vijay Prakash Dwivedi, Anh Tuan Luu, Guy Wolf, and Dominique Beaini. Recipe for a general, powerful, scalable graph transformer. In Sanmi Koyejo, S. Mohamed, A. Agarwal, Danielle Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9, 2022*, 2022. URL http://papers.nips.cc/paper_files/paper/2022/hash/5d4834a159f1547b267a05a4e2b7cf5e-Abstract-Conference.html.
- Tim Salimans and Jonathan Ho. Progressive distillation for fast sampling of diffusion models. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net, 2022. URL <https://openreview.net/forum?id=TiIdIXIpzhoI>.
- Carl Sechen and Alberto L. Sangiovanni-Vincentelli. Timberwolf3.2: a new standard cell placement and global routing package. In Don Thomas (ed.), *Proceedings of the 23rd ACM/IEEE Design Automation Conference. Las Vegas, NV, USA, June, 1986*, pp. 432–439. IEEE Computer Society Press, 1986. doi: 10.1145/318013.318083. URL <https://doi.org/10.1145/318013.318083>.
- Mohammad Amin Shabani, Sepidehsadat Hosseini, and Yasutaka Furukawa. HouseDiffusion: Vector floorplan generation via a diffusion model with discrete and continuous denoising. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2023, Vancouver, BC, Canada, June 17-24, 2023*, pp. 5466–5475. IEEE, 2023. doi: 10.1109/CVPR52729.2023.00529. URL <https://doi.org/10.1109/CVPR52729.2023.00529>.

- Yunqi Shi, Ke Xue, Song Lei, and Chao Qian. Macro placement by wire-mask-guided black-box optimization. In Alice Oh, Tristan Naumann, Amir Globerson, Kate Saenko, Moritz Hardt, and Sergey Levine (eds.), *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*, 2023. URL http://papers.nips.cc/paper_files/paper/2023/hash/15d6717f8bb33b3a74df26ce1eee0b9a-Abstract-Conference.html.
- Georg Sigl, Konrad Doll, and Frank M. Johannes. Analytical placement: A linear or a quadratic objective function? In A. Richard Newton (ed.), *Proceedings of the 28th Design Automation Conference, San Francisco, California, USA, June 17-21, 1991*, pp. 427–432. ACM, 1991. doi: 10.1145/127601.127707. URL <https://doi.org/10.1145/127601.127707>.
- Peter Spindler, Ulf Schlichtmann, and Frank M. Johannes. Abacus: fast legalization of standard cell circuits with minimal movement. In David Z. Pan and Gi-Joon Nam (eds.), *Proceedings of the 2008 International Symposium on Physical Design, ISPD 2008, Portland, Oregon, USA, April 13-16, 2008*, pp. 47–53. ACM, 2008a. doi: 10.1145/1353629.1353640. URL <https://doi.org/10.1145/1353629.1353640>.
- Peter Spindler, Ulf Schlichtmann, and Frank M. Johannes. Kraftwerk2 - A fast force-directed quadratic placement approach using an accurate net model. *IEEE Trans. Comput. Aided Des. Integr. Circuits Syst.*, 27(8):1398–1411, 2008b. doi: 10.1109/TCAD.2008.925783. URL <https://doi.org/10.1109/TCAD.2008.925783>.
- Larry J. Stockmeyer. Optimal orientations of cells in slicing floorplan designs. *Inf. Control.*, 57(2/3): 91–101, 1983. doi: 10.1016/S0019-9958(83)80038-2. URL [https://doi.org/10.1016/S0019-9958\(83\)80038-2](https://doi.org/10.1016/S0019-9958(83)80038-2).
- Zhiqing Sun and Yiming Yang. DIFUSCO: graph-based diffusion solvers for combinatorial optimization. In Alice Oh, Tristan Naumann, Amir Globerson, Kate Saenko, Moritz Hardt, and Sergey Levine (eds.), *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*, 2023. URL http://papers.nips.cc/paper_files/paper/2023/hash/0ba520d93c3df592c83a611961314c98-Abstract-Conference.html.
- Kien Le Trung and Truong-Son Hy. DiffPlace: A conditional diffusion framework for simultaneous VLSI placement beyond sequential paradigms, 2026. URL <https://arxiv.org/abs/2510.15897>.
- Natarajan Viswanathan and Chris C. N. Chu. Fastplace: efficient analytical placement using cell shifting, iterative local refinement, and a hybrid net model. *IEEE Trans. Comput. Aided Des. Integr. Circuits Syst.*, 24(5):722–733, 2005. doi: 10.1109/TCAD.2005.846365. URL <https://doi.org/10.1109/TCAD.2005.846365>.
- Natarajan Viswanathan, Charles J. Alpert, Cliff C. N. Sze, Zhuo Li, and Yaoguang Wei. The DAC 2012 routability-driven placement contest and benchmark suite. In Patrick Groeneveld, Donatella Sciuto, and Soha Hassoun (eds.), *The 49th Annual Design Automation Conference 2012, DAC '12, San Francisco, CA, USA, June 3-7, 2012*, pp. 774–782. ACM, 2012. doi: 10.1145/2228360.2228500. URL <https://doi.org/10.1145/2228360.2228500>.
- Zhihai Wang, Zijie Geng, Zhaojie Tu, Jie Wang, Yuxi Qian, Zhexuan Xu, Ziyan Liu, Siyuan Xu, Zhentao Tang, Shixiong Kai, Mingxuan Yuan, Jianye Hao, Bin Li, Yongdong Zhang, and Feng Wu. Benchmarking end-to-end performance of ai-based chip placement algorithms, 2024. URL <https://arxiv.org/abs/2407.15026>.
- D. F. Wong and C. L. Liu. A new algorithm for floorplan design. In Don Thomas (ed.), *Proceedings of the 23rd ACM/IEEE Design Automation Conference. Las Vegas, NV, USA, June, 1986*, pp. 101–107. IEEE Computer Society Press, 1986. doi: 10.1145/318013.318030. URL <https://doi.org/10.1145/318013.318030>.
- Peng Xie, Ke Xue, Yunqi Shi, Ruo-Tong Chen, Chengrui Gao, Siyuan Xu, Chenjian Ding, Mingxuan Yuan, and Chao Qian. FlowPlace: Flow matching for chip placement, 2026. URL <https://arxiv.org/abs/2604.23658>.

- Qi Xu, Hao Geng, Song Chen, Bo Yuan, Cheng Zhuo, Yi Kang, and Xiaoqing Wen. Goodfloorplan: Graph convolutional network and reinforcement learning-based floorplanning. *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems*, 41(10):3492–3502, October 2022. ISSN 1937-4151. doi: 10.1109/tcad.2021.3131550. URL <http://dx.doi.org/10.1109/tcad.2021.3131550>.
- Ke Xue, Ruo-Tong Chen, Rong-Xi Tan, Xi Lin, Yunqi Shi, Siyuan Xu, Mingxuan Yuan, and Chao Qian. BBOPlace-Bench: Benchmarking black-box optimization for chip placement, 2026. URL <https://arxiv.org/abs/2510.23472>.
- Chengxuan Ying, Tianle Cai, Shengjie Luo, Shuxin Zheng, Guolin Ke, Di He, Yanming Shen, and Tie-Yan Liu. Do transformers really perform badly for graph representation? In Marc’Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 28877–28888, 2021. URL <https://proceedings.neurips.cc/paper/2021/hash/f1c1592588411002af340cbaedd6fc33-Abstract.html>.
- Jongho Yoon, Jinsung Jeon, and Seokhyeong Kang. Physics-guided geometric diffusion for macro placement generation, 2026. URL <https://arxiv.org/abs/2605.16451>.
- Junyi Zhang, Jiaqi Guo, Shizhao Sun, Jian-Guang Lou, and Dongmei Zhang. LayoutDiffusion: Improving graphic layout generation by discrete diffusion probabilistic models. In *IEEE/CVF International Conference on Computer Vision, ICCV 2023, Paris, France, October 1-6, 2023*, pp. 7192–7202. IEEE, 2023. doi: 10.1109/ICCV51070.2023.00664. URL <https://doi.org/10.1109/ICCV51070.2023.00664>.
- Xinglin Zheng, Hao Gu, Keyu Peng, Youwen Wang, Wenxing Zhu, and Ziran Zhu. Late breaking results: Customized diffusion model empowered by heterogeneous graph network for effective floorplanning. In *62nd ACM/IEEE Design Automation Conference, DAC 2025, San Francisco, CA, USA, June 22-25, 2025*, pp. 1–2. IEEE, 2025. doi: 10.1109/DAC63849.2025.11133070. URL <https://doi.org/10.1109/DAC63849.2025.11133070>.

Appendix

TABLE OF CONTENTS

A	Background and Related Work	21
A.1	The Physical Design Flow	21
A.2	What an Instance Contains	21
A.3	What Makes It Hard	22
A.4	How the Methods Developed	22
A.5	The Benchmark Suites	23
B	Training and Model Details	24
B.1	Objective Framings	24
B.2	The Frozen Recipe	24
B.3	Architecture Specification	24
B.4	The Ported Prior Arts	26
B.5	The Regressors	26
B.6	Compute	26
C	Scoring Details	27
C.1	Distribution Metrics	28
D	Properties of the Construction	29
D.1	Setup	29
D.2	What the Latent Buys	30
D.3	Physics in Training	31
D.4	Physics in Sampling	32
D.5	What Is Predicted and What Is Measured	34
E	The Closed-Form Refiner	34
E.1	Derivatives	34
E.2	The Step	34
E.3	Choosing the Setting	35
E.4	The Prior Arts' Loops	36
F	The Legalizer	37
G	Measuring the Propositions	38
G.1	The Proximal Correction Against t	39
G.2	Reference Layouts Through Every Loop	40
G.3	Snapshots of the Corrections	40
G.4	Beyond FloorSet: Three Checkpoints on GSRC	40
G.5	Time per Step of the Loops	41
H	Generator Results in Full	42
H.1	Objective	42
H.2	Architecture on the Plain Base	42
H.3	Recipe: Wire Dropout	42
H.4	One Term at a Time	43
H.5	All Six Terms	44
H.6	The Composed Grid	44
H.7	The Prior Arts and the Regressors	46
H.8	Every Trained Model by Soft Cost	46

I	Refinement Results in Full	48
I.1	Trinity With and Without the Auxiliary Loss	48
I.2	Every Model on the Reduced Grid	49
J	The Ported Placers With Their Own In-Sampler Guidance	50
J.1	Raw Samples	50
J.2	Through the Refiners	51
J.3	Distance to the Reference.	53
K	Hard-Cost Results in Full	54
K.1	Trinity’s Grid	54
K.2	Every Line on the Same Pipeline	54
K.3	The Soft–Hard Correlation	55
K.4	The Prior Arts’ Loops in Hard Cost	56
K.5	Best of N	57
K.6	The FloorSet Val Set in Full	58
L	Classical Floorplanners	58
L.1	The FloorSet Val Set	59
L.2	The Soft-Block Benchmarks of the Prior Work	60
M	Seeds	61
N	Figures: Every View of the Data	64
N.1	The Soft Frontier	65
N.2	The Hard Frontier	66
N.3	Soft Against Hard per Draw	68
N.4	The Term Ladders	70
N.5	Metric Against Metric.	72
N.6	Best of N and the FloorSet Val Set	73
N.7	The Refiner Sweeps	75
N.8	Qualitative Examples	77
O	Model Size	80
P	Limitations and Future Work	83
Q	Broader Impact	85
R	Data, Licenses, and Supplementary Material	85

A BACKGROUND AND RELATED WORK

A.1 THE PHYSICAL DESIGN FLOW

A chip goes from a netlist, the gates and macros of the design and the nets that connect them, to a geometric layout through a fixed sequence of stages: partitioning, floorplanning, placement, clock tree synthesis, routing and timing closure (Kahng et al., 2011). Floorplanning is the first geometric stage. The design is partitioned into a few tens to a few hundred blocks, hard macros such as memories and IP whose shape is fixed and soft blocks of synthesized logic whose area is an estimate and whose aspect ratio is free within limits (Otten, 1982; Stockmeyer, 1983), and floorplanning decides the position of every block and the shape of every soft one. Placement then arranges the standard cells inside the blocks into rows of sites, tens of thousands to millions of cells of one height and fixed shape (Markov et al., 2015), and routing realizes every net as wires on the metal layers under capacity and spacing rules (Kahng et al., 2011). Figure 8 (top) sketches the three. They differ in what they move and in what binds them: floorplanning moves tens to a few hundred blocks and the shapes of the soft ones under non-overlap, fixed shapes, pre-placed blocks and the design constraints of Section 1, placement moves 10^5 to 10^7 cells under row and site legality and a density target, and routing moves 10^5 to 10^7 nets over layers, tracks and vias under capacity and design rules, while the objectives widen along the flow from wirelength and outline area to congestion, timing, vias and overflow. They share one proxy objective, the half-perimeter wirelength (HPWL), the sum over nets of the half perimeter of the smallest box around the net’s pins, because the wires do not exist until routing; congestion and timing enter later (Viswanathan et al., 2012). The floorplan bounds all of it, since the relative position of the blocks fixes the length of the nets between them, the regions the router can use and the area of the die. Mixed-size placement handles macros and cells together with the macro shapes fixed (Adya et al., 2004; Chen et al., 2008a;b), and macro placement, the task of the reinforcement learning line (Mirhoseini et al., 2021), is floorplanning with every shape fixed.

A.2 WHAT AN INSTANCE CONTAINS

A floorplanning instance is a netlist reduced to the block level. FloorSet gives for every case the target area of each block, the weighted nets between blocks, the pins on the die outline with their




Figure 8: Top: the three stages, drawn schematically: floorplanning arranges blocks and shapes the soft ones, placement fills rows with fixed-height cells around the macros, routing draws every net as wires on metal layers. Bottom: a 60-block validation case of FloorSet: the reference layout with its annotations, nets and outline pins, the raw sample of Trinity at NFE=8 with overlap in red, and the legalized sample, each with its overlap ratio and wirelength and area gaps.

nets, the five kinds of annotation, and a reference layout (Mallappa et al., 2024); Figure 8 (bottom left) draws one case. Over the 100 validation cases the instances span 21 to 120 blocks, a median of 70, with 29 to 7,056 nets between blocks and 50 to 466 pins on the outline. The annotations are not rare: a median case has 9% fixed-shape blocks, 4% pre-placed blocks, 31% of its blocks in one of three or four clusters, 8% in a multi-instance group and 35% of its blocks coded to a boundary, so most blocks carry a rule beyond non-overlap. Each stands for something a design team knows before the floorplan exists: a fixed shape is a hard macro delivered as a finished layout, a pre-placed block an interface or analog part whose position the package or an earlier floorplan settled, a cluster a functional unit or power domain whose blocks must stay close, a multi-instance group a block instantiated several times whose one internal layout is reused, and a boundary code a block that must reach the pins at the die edge. The reference layouts are tight, with 1 to 5% dead space, and Table 20 scores their residual violations. The hard cost of Eq. (1) follows a public floorplanning evaluation on this data; Appendix C states every rule as implemented.

A.3 WHAT MAKES IT HARD

Four things, and they compound. Packing: placing rectangles without overlap into the smallest outline is NP-hard even with fixed shapes and no nets, and the sequence pair alone encodes $(n!)^2$ arrangements of n blocks (Murata et al., 1996; Kahng et al., 2011). Shapes: a soft block adds a continuous choice to every combinatorial one, which has an exact solution on a slicing tree (Stockmeyer, 1983) and none on a general topology. Coupling: wirelength pulls connected blocks together, non-overlap holds them apart, a cluster asks for adjacency, a boundary code for the edge, a fixed outline for a total that fits (Adya & Markov, 2003), all on the same coordinates, so a layout that satisfies the rules is in general not near one that scores well. The bottom row of Figure 8 shows the size of the effect: the raw sample overlaps 2.2% of its area with a wirelength 1.5% below the reference, and legalizing it removes every overlap by moving blocks until the wirelength is 0.5% and the area 1.1% below. Evaluation: feasibility is binary, so a layout with one thin overlap scores as infeasible although it is nearly done, and both an instance-level search and any comparison of intermediate layouts need a graded measure of the distance to feasible; annealers carry one in their cost, analytical placers in their density penalty, and Section 3.1 defines one for this paper. And the search repeats per instance, minutes to hours of annealing per floorplan, the motivation for parallel annealers (Mostafa et al., 2024) and learned placers alike.

A.4 HOW THE METHODS DEVELOPED

The constraints inside the search. In the 1980s floorplanning and cell placement were both done by simulated annealing (Kirkpatrick et al., 1983; Sechen & Sangiovanni-Vincentelli, 1986), floorplanning over slicing structures encoded as Polish expressions (Otten, 1982; Wong & Liu, 1986). What survived is the search in an encoding whose decode is overlap-free, so every move is judged on wirelength and area alone. What did not is the slicing restriction, which cannot express some tight packings. The 1990s produced non-slicing encodings with the same property, the sequence pair (Murata et al., 1996), the bounded-sliceline grid (Nakatake et al., 1996), the O-tree (Guo et al., 1999), the B*-tree (Chang et al., 2000), the transitive closure graph (Lin & Chang, 2001) and the corner block list (Hong et al., 2000), and extended the sequence pair to hard, soft and pre-placed modules through a linear program over positions (Murata & Kuh, 1998), the ancestor of the program in Appendix F. The 2000s made the outline a constraint to fit (Adya & Markov, 2001; 2003) and put macros and cells into one problem (Adya et al., 2004; Chen et al., 2008b), and PARSAC runs this line in parallel on the constraint family of FloorSet (Mostafa et al., 2024). Placement meanwhile left annealing, which does not scale past 10^5 cells, for the analytical route (Sigl et al., 1991): minimize wirelength plus a differentiable penalty for overlap or density over continuous coordinates, then legalize. Quadratic placers (Hall, 1970; Kleinhans et al., 1991; Viswanathan & Chu, 2005; Spindler et al., 2008b) gave way to nonlinear ones (Chen et al., 2008a) and to the electrostatic density model (Lu et al., 2015; Cheng et al., 2019), with legalization a stage of its own (Spindler et al., 2008a). What survived is the split into a graded relaxation and a legalizer, and DREAMPlace ran the relaxation in a deep learning framework on a GPU (Lin et al., 2021), the bridge to learned placers. Surveys of the two eras are Markov et al. (2015) and Huang et al. (2021). Both branches meet the constraints and the objectives at every move, at the price of a search per netlist. Trinity keeps the graded energy of the analytical branch and moves it from that search into the training loss.

The constraints outside training. The 2020s brought learning and a debate about evidence. A graph network policy that places one macro per step, trained on a set of designs and fine-tuned

on each new one (Mirhoseini et al., 2021), was re-run by an independent group against annealing and commercial tools, which questioned its margins (Cheng et al., 2023; Markov, 2024). The replies improved the representation and the search, with joint placement and routing (Cheng & Yan, 2021), visual states (Lai et al., 2022), offline decision transformers (Lai et al., 2023), tree and evolutionary search (Geng et al., 2024; Deng et al., 2025), cross-stage rewards (Geng et al., 2025), expert knowledge in the policy (Gao et al., 2026) and black-box optimization with a wire mask in place of a policy (Shi et al., 2023), and they produced the shared data the debate had lacked: netlists with placement and routing labels (Chai et al., 2022), floorplans with design constraints (Mallappa et al., 2024), and benchmarks that score a placer by what the finished chip achieves or by a black-box protocol (Wang et al., 2024; Xue et al., 2026). Floorplanning with soft blocks entered through a graph convolutional policy (Xu et al., 2022), a corner-block-list representation learned across designs (Amini et al., 2022) and direct regression of every position from the netlist graph (Liu et al., 2023b). Across the line the shapes stay fixed and the constraints stay outside the function the model learns, and Appendix K.2 measures what the regressors’ conditional mean costs on our own backbone.

Generative placement and its corrections. The generative turn came from layout generation in graphics and architecture, where diffusion models draft documents and building floor plans under alignment and adjacency rules (Inoue et al., 2023; Zhang et al., 2023; Shabani et al., 2023), and from molecules and combinatorial problems (Hoogetboom et al., 2022; Sun & Yang, 2023), together with the toolkit those models use to satisfy rules at sampling time: gradient guidance (Dhariwal & Nichol, 2021; Ho & Salimans, 2022), posterior sampling under a measurement (Chung et al., 2023) and constraint losses on the clean prediction (Chen et al., 2024; Bastek et al., 2025). The diffusion placers apply this toolkit to macro placement. ChipDiffusion (Lee et al., 2025), DiffPlace (Trung & Hy, 2026) and MacroDiff+ (Yoon et al., 2026) predict the noise and steer every denoising step with an overlap or wavelength gradient in the forms Table 38 lists, a heterogeneous graph variant follows the same design (Zheng et al., 2025), and FlowPlace (Xie et al., 2026) predicts the velocity and projects each step onto a grid without overlap. All four train with a plain denoising loss, so the constraint terms appear first in the sampler and then in another form in a post-hoc loop, ten gradient steps in each of 1,000 denoising steps, up to 700 optimizer steps per denoising step, or 5,000 steps after sampling, before a legalizer closes what remains. They keep the learned proposal of the sequential line and the graded penalty of the analytical line but apply the penalty after the model, where the earlier eras had it inside the optimization, and their papers score the legalized endpoint at one sampling budget. Appendix J reproduces the three in-sampler corrections on our recipe, Section 4.3 the loops, and Appendix K shows how much of the difference between generators the legalizer hides. Trinity moves the penalty back into training and samples without guidance.

Objectives and conditioning. Noise prediction (Ho et al., 2020; Nichol & Dhariwal, 2021; Salimans & Ho, 2022), flow matching and rectified flow (Lipman et al., 2023; Liu et al., 2023a) and stochastic interpolants (Ma et al., 2024) are linear transformations between data and noise, and a design-space view separates the prediction target, the time distribution and the weighting (Karras et al., 2022), the interface of Appendix B.1. Following JiT (Li & He, 2026), Trinity predicts the clean layout and trains on the velocity it implies, the one output an energy can score, and LACE (Chen et al., 2024) and physics-informed diffusion (Bastek et al., 2025) supervise the same clean prediction with constraint losses in other domains. The backbone is a Diffusion Transformer (Peebles & Xie, 2023) with the time step as a token (Bao et al., 2023), and the netlist enters it through an attention bias from the net incidence in the manner of Graphormer (Ying et al., 2021), a message-passing residual beside attention in the manner of GraphGPS (Rampásek et al., 2022), and a spectral positional encoding from the Laplacian eigenvectors (Belkin & Niyogi, 2003; Dwivedi & Bresson, 2020; Kreuzer et al., 2021; Dwivedi et al., 2022; 2023).

A.5 THE BENCHMARK SUITES

Table 11 lists the suites the field measures itself on. The floorplanning suites are small and old: MCNC (Kozminski, 1991) has 9 to 49 blocks per instance and GSRC extends it to 300 soft blocks, the scale of Table 8. The placement suites are large: the mixed-size suite (Adya et al., 2004) and the ISPD contests of 2005 and 2006 (Nam et al., 2005; Nam, 2006) fixed the form of an industrial placement benchmark, millions of cells, fixed macros, a fixed outline and a density target, and the DAC 2012 contest added routability (Viswanathan et al., 2012). Learning needs many instances rather than a few large ones, which CircuitNet supplies for placement and routing prediction (Chai et al., 2022) and FloorSet for floorplanning, 996,000 synthetic training instances with the design constraints the older suites lack (Mallappa et al., 2024).

Table 11: The benchmark suites of floorplanning and placement, each cited in the text. Sizes are per instance; “constraints” means design constraints beyond non-overlap, fixed shapes and the outline.

Suite	Year	Task	Size per instance	Soft shapes	Constraints
MCNC	1991	floorplanning	9 to 49 blocks	yes	no
GSRC	2000s	floorplanning	10 to 300 blocks	yes	no
IBM mixed-size	2004	mixed-size placement	10k to 200k cells	no	no
ISPD 2005 and 2006	2005	placement	0.2M to 2.2M cells	no	density
DAC 2012	2012	placement	0.1M to 1M cells	no	routability
CircuitNet	2022	placement and routing	10k to 100k cells	no	no
FloorSet	2024	floorplanning	21 to 120 blocks	yes	five kinds

B TRAINING AND MODEL DETAILS

B.1 OBJECTIVE FRAMINGS

Every objective compared in the paper is one per- t linear transform of the pair (x_0, x_1) of data and Gaussian noise,

$$x_t = a(t)x_0 + b(t)x_1, \quad \text{target}(t) = c(t)x_0 + d(t)x_1. \quad (4)$$

DDPM with a cosine or linear schedule and an ϵ target (Ho et al., 2020; Nichol & Dhariwal, 2021), the v target (Salimans & Ho, 2022) and rectified flow with target $x_1 - x_0$ (Liu et al., 2023a; Lipman et al., 2023) differ only in (a, b, c, d) . Given a prediction of the target and x_t , the 2×2 system recovers (x_0, x_1) whenever $ad - bc \neq 0$, and the probability-flow velocity is $\dot{a}x_0 + \dot{b}x_1$. A network may therefore emit ϵ , x_0 , v or the target itself and be trained against any target by a change of variables inside the loss. The paper’s models emit x_0 and are trained against the rectified-flow velocity with logit-normal t . The objective arms of Table 1 are the velocity head under the same rectified flow with uniform t (the FlowPlace objective) and the ϵ head under the cosine DDPM schedule with uniform t (the ChipDiffusion objective), both on the plain backbone. The ported DiffPlace and MacroDiff+ keep their linear- β ϵ objectives with $T = 1,000$ and $T = 200$.

B.2 THE FROZEN RECIPE

Table 12 is the recipe of every trained model in the paper, the ported prior arts, the regressors and the seed replicates included. An arm changes exactly one thing against its control: the head, the wire-dropout mixture, the term weights, or a backbone component. The two rows marked Trinity are the backbone components that the composed arms and Trinity add to the plain backbone; every soft number of the paper is the mean over the draws of a case, then over the cases.

Wire dropout. Three mixtures were trained on the plain base: a mild one (70% of instances untouched, 30% at a rate from Beta(1,3)), the adopted mixture (50% untouched, 40% Beta(1,3), 10% U(0.9,1)) and a heavy one (30% untouched, 50% Beta(1,2), 20% U(0.8,1)). On our 12,000 val set the adopted mixture is within $\pm 1\%$ of the base on every soft metric except the immutable-block deviation (-20%) and the MIB variance (-16%), has the lowest soft cost of the set (2.092 against 2.106) and is the closest arm to the reference distribution on all four distances with $p = 0.005$. The mild and the heavy mixture move the wirelength gap toward zero and the area gap up by 30 to 40%. The adopted mixture is the recipe of every model from the term ladders on.

B.3 ARCHITECTURE SPECIFICATION

The backbone is a plain transformer with one token per block: 12 layers, width 768, 12 heads, RMSNorm, SwiGLU and QK-normalization. The input projection embeds the noisy latent $z_{t,i}$ with 19 conditioning columns per block (area, kind, anchor value and mask, group identifiers, boundary code, pin pull). The time step enters as one prepended token in the manner of U-ViT (Bao et al., 2023), so the block has no adaptive normalization and the same block serves the deterministic regressors of Section 4.1. Three components put the netlist into the network (Figure 2). The input projection is one linear layer from the concatenated 3 latent, 19 conditioning and 2 spectral coordinates, 24 in total, to the width of 768. **Attention bias.** The max-normalized $\log(1 + A_{ij})$ is added to every attention logit through one learned gate (Ying et al., 2021); padded keys receive a large negative bias, and the bias rides the mask argument of the fused attention kernel. **Information mover.** Every layer adds one graph-convolution hop behind a zero-initialized gate, $x \leftarrow x + g W \hat{A} x$ with $\hat{A} = D^{-1}A$

Table 12: The frozen training recipe of every trained model; the two rows marked Trinity are the components the composed arms add.

Data	
Training set	FloorSet-Lite, MIB-consistent variant (Appendix R)
Training layouts	996,000 of the 1,008,000, with 21 to 120 blocks each
Our 12,000 val set	12,000: 100 per block count plus 2,000 random rows
Test set	the FloorSet val set of 100 cases, used once
Latent and conditioning	
Latent per block	(u, v, ρ) : center over s and $\log(w/h)$ at the exact target area
Conditioning columns	19 per block: area, kind, anchor value and mask, group ids, boundary code, pin pull
Time conditioning	one prepended token; sequences padded to 127 blocks plus the token
Backbone	
Layers L	12
Width d	768
Attention heads	12, head dimension 64
MLP	SwiGLU, ratio 4
Normalization	RMSNorm before every sublayer, QK-normalization
Netlist attention bias	$\log(1 + A)$, max-normalized per instance, one learned gate
Spectral PE (Trinity)	Fiedler pair of the normalized netlist Laplacian, $\log(1 + A)$ weights
Information mover (Trinity)	$x \leftarrow x + g W \hat{A}x$, $\hat{A} = D^{-1}A$, gate zero-initialized, every layer
Parameters	85.8M plain backbone, 92.9M with the information mover
Objective	
Framing	rectified flow, $x_t = (1 - t)x_0 + tx_1$, $\hat{x}_0$ head trained against the velocity
Time sampling	logit-normal, mean 0, std 1
Overrides	fixed shapes and preplaced boxes inpainted at every step
MIB groups with an anchor	every soft member’s aspect overridden with the fixed-shape or preplaced member’s, no mean taken
MIB groups without an anchor	set to the group-mean aspect of the prediction
Auxiliary terms	
Terms	the six functions of Appendix E.1 on the decoded boxes
Trinity weights	all six at 0.01, constant in t
Ladder weights	0.01, 0.05, 0.1, and $w \cdot t$ with $t=1$ at pure noise
Fixed and preplaced channels	detached in every term
Augmentation	
Rotation	multiples of 90° , uniform
Flip	probability 0.5
Shift	Gaussian, std 0.05 s
Constraint dropout	1% per boundary code, cluster, MIB group, fixed and preplaced block
Wire dropout (adopted recipe)	per instance a rate from 50% none, 40% Beta(1,3), 10% U(0.9,1)
Wire dropout effect	nets and pins dropped at that rate, reference HPWL recomputed
Optimization	
Optimizer	AdamW
Peak learning rate	2×10^{-4}
Betas	(0.9, 0.98)
Weight decay	10^{-3}
Gradient clip	1.0
Schedule	cosine decay to 1% of the peak, 1% warmup
Effective batch	256 instances: micro-batch 128, two accumulation steps
Steps	200,000
Precision	bf16 mixed
EMA	0.9995, used for all sampling
Sampling	
Integrator	Euler on the probability-flow ODE, no projection beyond the overrides
Time grid	uniform from $t = 1$ to $t = 10^{-3}$ in NFE steps; the sample is the network’s $\hat{x}_0$ at the last time
NFE	1, 2, 4, 8, 16, 32
Draws per case	4; 16 for the best-of- N caches
Compute	
Hardware	one NVIDIA RTX 5090 per run
Wall time	7.6 to 12.3 hours per run (Appendix B.6)

the row-normalized netlist adjacency, so each block receives the mean of its neighbours (Kipf & Welling, 2017; Rampášek et al., 2022). The residual supplies one-hop netlist information in parallel with attention, the zero gate makes the layer a plain transformer layer at initialization, and it adds 7.1M parameters for 92.9M in total. **Spectral positional encoding.** Two input columns hold the second and third eigenvectors of the normalized netlist Laplacian, the quadratic-placement drawing of the netlist (Hall, 1970; Kleinhans et al., 1991; Koren, 2003), in the same $(c_x/s, c_y/s)$ frame the model generates. Sign and axis are fixed by unit norm and non-negative skewness, because a reflected drawing is a different layout.

B.4 THE PORTED PRIOR ARTS

Each port keeps the published network and objective, trains under Table 12 on the same data, consumes the same 3-D latent and the same 19 conditioning columns as our models, and samples with the same Euler integrator and the same overrides. FlowPlace and ChipDiffusion share the AttGNN network, three blocks of two GATv2 layers, an MLP, global attention and an MLP at hidden width 256 with FiLM time conditioning, 6.3M parameters; FlowPlace trains rectified flow with a velocity head and uniform t and publishes no loop, ChipDiffusion trains a cosine DDPM with an ϵ head and uniform t and follows sampling with a 5,000-iteration gradient legalizer on legality and HPWL potentials, in its standard, scheduled and dual-ascent Adam variants. DiffPlace keeps VectorGNNV2Global, eight blocks of two vector message-passing layers with FiLM, a global supernode and hidden width 256, 23.9M parameters with the orientation head dropped, trains a linear- β DDPM with an ϵ head at $T=1,000$, and follows sampling with a 500-iteration gradient refinement. MacroDiff+ keeps its heterogeneous GATv2 cell and net network of five layers at width 64 with a 1-D token U-Net of widths $32 \cdot [1, 2, 4, 8]$, 5.0M parameters, trains a linear- β DDPM at $T=200$ whose ϵ is composed as $\alpha(\partial\text{HPWL}/\partial x)^\top \text{net} + \beta \text{cell}$ from a net head and a cell head, and follows sampling with a 500-iteration Adam loop on HPWL and overlap. The post-hoc loops (Section 4.3) are ported with autograd at their published optimizers, schedules and iteration counts, act on positions only, and run on a canvas equal to the raw bounding box plus a 5% margin, which their die-boundary terms need to separate blocks. A canvas tuned per method and shape freedom are not granted: the released energies have no shape variable, and shape freedom after sampling is the refiner’s (Appendix E). The corrections three of the placers apply inside their samplers are ported separately, on the same canvas, for Appendix J (Table 38).

B.5 THE REGRESSORS

Reg- z is the plain backbone driven with a constant input and $t = 0$, so its output depends on the conditioning only, trained by masked regression of the reference latent under the frozen recipe. Reg- $xywh$ changes the head to $(c_x/s, c_y/s, w/s, h/s)$, expresses the overrides in that space and adds an area penalty because $wh = a$ no longer holds by construction. Each returns one layout per case.

B.6 COMPUTE

Table 13 accounts for every job of the study. Each job ran on one NVIDIA RTX 5090, with the CPU workers named where a stage uses them; the whole campaign, training and evaluation, ran on one four-GPU box. Training is the bulk: 68 runs under the frozen recipe (objective 3, recipe 3, architecture 2, single terms 24, all six 6, composed grid 8, prior arts 4, regressors 2, seed replicates 8, size rungs 8), 7.6 to 12.3 hours each, for 710 GPU-hours, with DiffPlace at 29.4 hours because its network needs a micro-batch of 64, MacroDiff+ at 14.7 hours, the width rungs at 9.0, 8.8 and 8.5 hours, the depth rungs at 10.5, 8.6 and 7.6 hours and the two late rungs at 5.9 and 7.4 hours; the per-run wall times, read from each run’s tracker summary, are in the result files of the supplementary material. Earlier attempts of the same runs that crashed or were superseded cost about 61 GPU-hours and enter no result. Generation and scoring take about a quarter of an hour per run: 12,000 cases at six NFE with four draws, the 15 soft columns, the 16-draw Trinity caches and one rescoring pass. The guided sampling of Appendix J is five generations, one per placer and one for DiffPlace’s sign-flipped arm, with MacroDiff+ at 9.2 of the 11 GPU-hours because of its 500 Adam iterations per step, scored on 16 CPU workers; their refiner sweeps and distribution metrics are counted in those rows. A refiner sweep takes 2 to 8 minutes, 1 to 4 of them compiling. Evaluation is dominated by the legalizer track, 5 full NFE $\times$ steps grids, 3 single-shard lines, 15 prior-art loop runs and 3 best-of-16 ladders on 24 to 32 CPU workers: 10.6 million legalizations at 240 to 300 ms each, during which the GPU only refines and then waits, so the track costs about 1,400 CPU-core-hours and about three active

GPU-hours although the GPU is held for about 57 hours. The six size-rung grids of Appendix O add 2,016,000 legalizations each on 24 workers, about 1,340 CPU-core-hours with the GPUs held for about 56 hours. The theory measurements of Appendix G are four scripts and two GSRC runs. The classical track of Appendix L is CPU time on single cores: PARSAC on the FloorSet val set with 16 workers at 10^7 steps for about 500 core-hours, its GSRC runs about 60, the sequence-pair annealer about 12, the continuations about 14, and the pipeline’s own passes about 1.5 GPU-hours. The runtime study against the block count took 0.7 hours on an idle GPU.

Table 13: Compute of the study. One RTX 5090 per job, the CPU workers of each stage as given in the text. "Held" counts the hours the GPU is reserved while the CPU workers legalize.

Stage	Jobs	GPU-hours	CPU-core-hours
<i>Training</i>			
Trained runs of the study	68	710	–
Earlier attempts, not used	–	≈ 61	–
<i>Evaluation</i>			
Generation and scoring	68	≈ 22	–
Guided sampling of three placers	5	≈ 11	≈ 5
Distribution metrics	10	≈ 9	≈ 69
Refiner sweeps	131	≈ 3	–
Hard-cost grids and ladders	26	≈ 3 active (≈ 57 held)	≈ 1,400
Size-rung grids	6	< 2 active (≈ 56 held)	≈ 1,340
Theory measurements	6	≈ 0.3	–
Classical solvers	–	≈ 1.5	≈ 590
FloorSet val set runs	2	≈ 0.6	≈ 10
Runtime study	1	0.7	–
Evaluation total		≈ 53 active (≈ 167 held)	≈ 3,410
Training and evaluation		≈ 760 active	≈ 3,410

C SCORING DETAILS

Hard feasibility and the hard cost. A layout is feasible when no pair of boxes overlaps by more than 10^{-6} on both axes, every soft block keeps wh within 1% of its target area, every fixed-shape block keeps its (w, h) and every preplaced block keeps its (x, y, w, h) . Let c_p be the number of edge-connected components among the members of cluster p , where two boxes are connected when they share an edge segment of positive length, s_q the number of distinct shapes in MIB group q after rounding to 10^{-4} , and B the set of boundary-coded blocks with codes 1 left, 2 right, 4 top, 8 bottom and corners as sums. Then

$$V_{\text{group}} = \sum_p (c_p - 1), \quad V_{\text{mib}} = \sum_q (s_q - 1),$$

$$V_{\text{bnd}} = \sum_{i \in B} \mathbb{1}[\text{a required side of } i \text{ is off its outline edge by more than } 10^{-6}], \quad (5)$$

and $V_{\text{rel}} = (V_{\text{group}} + V_{\text{mib}} + V_{\text{bnd}})/N_{\text{soft}}$ with N_{soft} the number of soft-constrained slots. HPWL is the net-weighted sum of centroid-to-centroid Manhattan distances over block-to-block and pin-to-block nets, the area is that of the layout bounding box, and both gaps are the layout value minus the reference value over the reference value, clamped at zero. The hard-cost total over a case set is $\sum_c e^{n_c/12} \text{Cost}_c / \sum_c e^{n_c/12}$; the paper reports the per-case mean and median and gives the totals in Appendix K.

The soft metric vector. Every layout, raw, refined or legalized, is scored with the same columns, every length in units of $s = \sqrt{\sum_i a_i}$:

- *overlap ratio*: $\sum_{i < j}$ intersection area over $\sum_i$ block area;
- *compactness*: bounding-box area over $\sum_i$ block area, at least 1;
- *normalized wirelength* wl: $\text{HPWL}/(s \cdot \sum \text{net weights})$;
- *hpwl gap, area gap*: the two relative gaps to the reference, signed;
- *boundary distance*: mean over boundary-coded blocks of the distance from each required side to its outline edge;

- *group gap*: mean over same-cluster pairs of the axis-wise gap to contact;
- *MIB variance*: mean within-group variance of $(\log w, \log h)$;
- *fixed distance*: mean over fixed and preplaced blocks of the shape deviation over $\sqrt{a}$ plus, for preplaced blocks, the center distance;
- *severities* $\text{sev}_{\text{group}}, \text{sev}_{\text{mib}}, \text{sev}_{\text{bnd}}$: per soft slot $\tanh(d/\tau)$ with d the slot's distance to satisfaction and $\tau = 0.01, 0.05, 0.01$, summed over slots;
- $\text{sev}_{\text{rel}}: (\text{sev}_{\text{group}} + \text{sev}_{\text{mib}} + \text{sev}_{\text{bnd}})/N_{\text{soft}}$, the severity analogue of V_{rel} ;
- *soft cost*: the second aggregate of Eq. (1), computed per case before averaging.

In every table the boundary distance, the group gap and the fixed distance are given in units of 10^{-3} , the MIB variance in units of 10^{-6} and MMD in units of 10^{-3} ; the other columns are unscaled. The severities grade how far a slot is off and never how many slots are off, so the soft vector is continuous in the layout, and a jitter of 0.2% of s on a reference layout moves every soft column monotonically while the hard cost jumps to its violated value. Where a model's mean soft cost overflows (a few cases with gaps in the tens, only for the regressors and for the one-step samples of the ϵ -head models) the per-case median and 90th percentile are given.

C.1 DISTRIBUTION METRICS

The per-layout metrics above score one layout against its own constraints and its own reference. The distribution metrics ask a different question: whether the set of layouts a model draws looks like the set of reference layouts. Each layout is mapped to a fixed-length, permutation-invariant descriptor that is a plain function of its geometry, with no learned encoder, and two standard distances are taken between the descriptor cloud of a model (all draws of one run at one NFE, 48,000 rows) and the descriptor cloud of the 12,000 reference layouts.

Density descriptor. Let W be a rasterization window and G a grid size. In the *bbox* frame W is the layout's own bounding box, so the descriptor sees the arrangement of the blocks and factors out the size of the outline; in the *fixed* frame W is the square of side $2s$ centered on the bounding-box center, so the descriptor also sees how far the layout spreads in absolute units. W is cut into $G \times G$ cells g of equal size, and the coverage of cell g by block i is the fraction of the cell the box B_i occupies,

$$c_i(g) = \frac{|B_i \cap g|}{|g|} \in [0, 1]. \quad (6)$$

Four fields are stacked: all blocks, soft blocks, fixed and preplaced blocks, and the net-weighted center density,

$$\begin{aligned} f_{\text{all}}(g) &= \sum_i c_i(g), & f_{\text{soft}}(g) &= \sum_{i \text{ soft}} c_i(g), & f_{\text{lock}}(g) &= \sum_{i \text{ fixed, preplaced}} c_i(g), \\ f_{\text{net}}(g) &= \frac{\sum_{i: \text{center}(i) \in g} \omega_i}{\sum_i \omega_i}, \end{aligned} \quad (7)$$

where ω_i is the total weight of the nets incident on block i (block-to-block weights counted at both endpoints, pin weights at the block). The coverage fields sum above 1 in a cell where blocks overlap, so the descriptor sees overlap as well as arrangement. The descriptor $\phi_G(\text{layout}) \in \mathbb{R}^{4G^2}$ is the concatenation of the four fields: 256 dimensions at $G = 8$ and 576 at $G = 12$. FLD8b, FLD8f, FLD12b and FLD12f name the Fréchet distance below on ϕ_8 and ϕ_{12} in the two frames.

Position descriptor. The block centers c_i are scaled by s and shifted by the bounding-box center. The descriptor collects the biased covariance of the center cloud $(\Sigma_{xx}, \Sigma_{yy}, \Sigma_{xy})$, the per-axis skewness and excess kurtosis of the standardized coordinates, the radius of gyration $\sqrt{\text{mean}_i \|c_i\|^2}$, a 16-bin histogram of the nearest-neighbor center distance on $[0, 0.5]$ and a 16-bin histogram of the pairwise center distance on $[0, 2]$, both normalized to sum to one: $8 + 16 + 16 = 40$ dimensions. FPD names the Fréchet distance on it.

Fréchet distance. For a model cloud X and the reference cloud R with means μ_X, μ_R and sample covariances Σ_X, Σ_R (each with $10^{-6}I$ added for the matrix square root),

$$d_{\text{F}}^2(X, R) = \|\mu_X - \mu_R\|_2^2 + \text{Tr}(\Sigma_X + \Sigma_R - 2(\Sigma_X \Sigma_R)^{1/2}), \quad (8)$$

the squared Wasserstein-2 distance between the Gaussian fits of the two clouds, the form used by FID (Heusel et al., 2017). The mean term and the covariance term are stored separately in the result files of the supplementary material. The distance is computed on the full clouds, uses the first two moments only, and is not standardized, so cells with a large natural variance weigh more.

Kernel MMD. For the $G = 8$ bbox descriptor every dimension is first standardized by the reference standard deviation, $\hat{\phi} = \phi/(\sigma_R + 10^{-9})$, so every cell weighs the same. With the Gaussian kernel $k(x, y) = \exp(-\|x - y\|^2/2h^2)$ and the bandwidth h set to the median pairwise Euclidean distance within a 4,000-row subsample of the standardized reference, the unbiased estimator (Gretton et al., 2012) on subsamples $X = \{x_i\}_{i=1}^n$ and $R = \{r_j\}_{j=1}^m$ of 4,000 rows each is

$$\text{MMD}_u^2(X, R) = \frac{1}{n(n-1)} \sum_{i \neq i'} k(x_i, x_{i'}) + \frac{1}{m(m-1)} \sum_{j \neq j'} k(r_j, r_{j'}) - \frac{2}{nm} \sum_{i,j} k(x_i, r_j). \quad (9)$$

This is MMD8b. The Gaussian kernel is characteristic, so the population MMD is zero only when the two distributions coincide and it is sensitive to every moment, which complements the two-moment Fréchet distance; in every table of the paper the two rank the models the same way. The estimate depends on the 4,000-row subsample, so the same run re-evaluated in another batch moves by a few percent: Trinity reads 2.5 in the batch of Table 1 and 2.3 in the seed batch of Appendix M. Every table prints the batch its rows were evaluated in, and a comparison is always read within one batch.

Permutation test. Whether a model A is closer to the reference than a control B is decided by a one-sided label-permutation test on MMD8b. With 2,000-row subsamples of A , B and R the statistic is $T = \text{MMD}_u^2(A, R) - \text{MMD}_u^2(B, R)$; under the null that A and B are exchangeable the pooled rows are relabeled at random 200 times, giving $T_1, \dots, T_{200}$, and

$$p = \frac{1 + \#\{\ell : T_\ell \leq T\}}{1 + 200}. \quad (10)$$

A small p means the observed difference is farther below zero than a random relabeling produces, so A is closer to the reference than B ; $p = 1/201 \approx 0.005$ is the floor. The same model with another training seed tests at $p = 0.20$ to 1.00 against the original (Appendix M), the null band of the test.

Reading the distribution metrics. Lower is closer to the reference distribution, which is fidelity to the training layouts, not cost: the reference layouts leave 9.1% of the boundary-coded blocks off their edge, so a model that places more coded blocks on the edge moves away from the reference in the cells along the outline, which is why the boundary term at high weight and Trinity's own FLD8f can rise while every per-layout metric improves. The bbox frame answers "is the arrangement right", the fixed frame "is the spread right", the position descriptor "is the center cloud right", and the four together are read as a set. The main text writes FLD for FLD8b and MMD for MMD8b.

Correlation measures. Per (NFE, steps) cell of a line, the Spearman ρ and Kendall τ of the per-draw soft cost against the per-draw hard cost over the 48,000 draws and over the 12,000 per-case means, Pearson r and R^2 on raw and on log values, and the Spearman per soft column. Across a grid, the same measures on the cell means. Pooled, over every draw of a line and over the eight lines together.

A property of the data set. The reference layouts satisfy every cluster abutment. They leave 9.1% of the boundary-coded blocks off their required edge and pay about 10% in hard cost for it. The six quantities read the constraint annotations and never the reference layout, so a model trained with them can place a coded block on its edge where the reference does not, and Trinity's boundary distance is one quarter of the plain control's.

D PROPERTIES OF THE CONSTRUCTION

D.1 SETUP

Notation follows Section 3. A clean latent is x_0 , noise is $x_1 \sim \mathcal{N}(0, I)$, the interpolant is $x_t = (1-t)x_0 + tx_1$, and

$$\bar{x}_0(x, t) = \mathbb{E}[x_0 \mid x_t = x], \quad \Sigma_{0|t}(x) = \text{Cov}(x_0 \mid x_t = x), \quad (11)$$

so $\Sigma_{0|0} = 0$ and $\Sigma_{0|1} = \text{Cov}(x_0)$. Write $U = \sum_k \omega_k \mathcal{E}_k$ for the energy of Section 3.3 on the decoded boxes, split into the four constraint terms and the two objectives,

$$U = U_C + U_O, \quad \mathcal{F} = \{x : U_C(x) = 0\}, \quad (12)$$

and let $\text{prox}_{\gamma U}(y) = \arg \min_m \frac{1}{2} \|m - y\|^2 + \gamma U(m)$ for $\gamma > 0$. The decode of Eq. (2) satisfies $w_i h_i = a_i$ for every $\rho_i \in \mathbb{R}$, so it is a bijection onto $\{(w, h) \in \mathbb{R}_{>0}^2 : wh = a_i\}$ with inverse

$\rho_i = \log(w_i/h_i)$, and linear interpolation of ρ is the geometric path $w_t = w_0^{1-t}w_1^t$. The area rule is therefore the coordinate system and not a constraint, at every t and for every noise draw. Two conventions of Eq. (1) hold throughout: a gap is measured against the reference value or 10^{-6} , whichever is larger, and an instance without soft-constraint slots ($N_{\text{soft}} = 0$) has $V_{\text{rel}} = \text{sev}_{\text{rel}} = 0$.

$\mathcal{F}$ is the zero set of the constraint energy, the feasible set of the constraints other than the area rule as in Section 3.2; it also asks for the three soft constraints, so it lies inside the hard feasible set of Section 1 up to the tolerance of the area rule, and every statement below is about $\mathcal{F}$. Every numbered result of this appendix is checked in Lean 4 against Mathlib, with the code in the supplementary material; conditional expectations are read at a fixed x as integrals against the conditional law, and three standard steps enter those checks as hypotheses: differentiation under the integral in Lemma D.2, the third-order Taylor expansion of U in Eq. (21), and Tweedie’s formula with the channel covariance identity in Proposition D.6.

Assumption D.1. (i) $U \in C^2(\mathbb{R}^d)$, $U \geq 0$, and $\nabla^2 U \succeq -\beta I$ for some $\beta \geq 0$ (weak convexity). (ii) $U_C(x_0) = 0$ for p_{data} -almost every x_0 : every reference layout lies in $\mathcal{F}$. (iii) The head is an arbitrary measurable function of (x, t) and x_0 has finite second moments, so the training objective is minimized pointwise, for p_t -almost every x at every t .

Lemma D.1. *Under Assumption D.1(i), for every $\gamma > 0$ with $\gamma\beta < 1$ the objective $m \mapsto \frac{1}{2}\|m - y\|^2 + \gamma U(m)$ has Hessian $I + \gamma\nabla^2 U \succeq (1 - \gamma\beta)I \succ 0$, so it is strongly convex and $\text{prox}_{\gamma U}(y)$ is a single point for every y .*

By Assumption D.1(ii) the reweighting $p_{\text{data}} e^{-U_C}$ is proportional to p_{data} itself, since the density ratio is constant on a set of full measure; what the constraint terms do to the trained head is the subject of Theorem D.1, not a statement about the fitted distribution. The objective part differs: $p_{\text{data}} e^{-U_C}$ prefers shorter wires and smaller outlines, and the proximal step applies it with the prox weight γ_t . Assumption (ii) holds approximately: the references’ residual violations are small on average, a soft cost of 1.065 against 1 for a violation-free layout (Table 20).

D.2 WHAT THE LATENT BUYS

Proposition D.1. *Let a block have target area $a > 0$ and let (W, H) be a random box with $WH = a$ almost surely, $W > 0$ and $\mathbb{E}|\log W| < \infty$. Then*

$$\exp(\mathbb{E}[\log W]) \exp(\mathbb{E}[\log H]) = a, \quad \mathbb{E}[W] \mathbb{E}[H] \geq a, \quad (13)$$

with equality on the right if and only if W is almost surely constant.

Proof. $\log W + \log H = \log a$ almost surely gives the left identity. For the right, $\mathbb{E}[W]\mathbb{E}[H] = a \mathbb{E}[W] \mathbb{E}[1/W]$, and Cauchy-Schwarz gives $1 = (\mathbb{E}[\sqrt{W} \cdot W^{-1/2}])^2 \leq \mathbb{E}[W] \mathbb{E}[1/W]$, with equality if and only if W is almost surely constant. $\square$

On a fixed instance with fixed target areas, a head trained under a squared loss with finite second moments emits, at the population optimum, a conditional mean, so Proposition D.1 decides what area that output has: in the latent the mean decodes at area exactly a , and in width-height coordinates it decodes at an area above a unless the shape is deterministic. The two regressors of Section 4.2 are the two sides of this.

Proposition D.2. (i) *There are instances on which $\mathcal{F}$ is not convex, and on them $\bar{x}_0(x, t) \notin \mathcal{F}$ for some (x, t) .* (ii) *Under Assumption D.1(ii), for every (x, t) ,*

$$\text{dist}(\bar{x}_0(x, t), \mathcal{F})^2 \leq \text{tr } \Sigma_{0|t}(x). \quad (14)$$

Proof. (i) Take an instance with two blocks of equal target area and identical annotations, so that exchanging the two preserves every constraint. Let $x \in \mathcal{F}$ place them at distinct centers $p \neq q$ without overlap and let x' be x with the two exchanged, so $x' \in \mathcal{F}$. Their midpoint puts both at $\frac{1}{2}(p + q)$, where they coincide and overlap, so $\frac{1}{2}(x + x') \notin \mathcal{F}$. If $p(x_0 | x_t = x)$ charges x and x' equally, $\bar{x}_0(x, t)$ is that midpoint. (ii) Since $x_0 \in \mathcal{F}$ almost surely, $\text{dist}(\bar{x}_0, \mathcal{F})^2 \leq \|\bar{x}_0 - x_0\|^2$ for almost every draw of x_0 from $p(x_0 | x_t = x)$, and the conditional expectation of the right side is $\text{tr } \Sigma_{0|t}(x)$. $\square$

Part (ii) bounds the defect by the posterior spread, which is zero at $t = 0$ and $\text{tr Cov}(x_0)$ at $t = 1$. So a correction is needed even for the exact denoiser, and only its place is open. The regressors are the extreme case, 41 to 59% of the block area claimed twice.

D.3 PHYSICS IN TRAINING

Theorem D.1. *Under Assumption D.1, for $\lambda \geq 0$ and every $t \in (0, 1]$ with $\gamma_t \beta < 1$, the head minimizing Eq. (3) is, for p_t -almost every x ,*

$$m^*(x, t) = \text{prox}_{\gamma_t U}(\bar{x}_0(x, t)), \quad \gamma_t = \frac{1}{2}\lambda t^2, \quad (15)$$

the prox being single valued by Lemma D.1; with the flow loss averaged over the c real latent coordinates of a case, as implemented, the same argument gives $\gamma_t = c\lambda t^2/2$; at $t = 0$ the right side extends continuously to $\bar{x}_0$ itself, since $\gamma_0 = 0$. The velocity it induces is

$$v_{\text{train}}(x, t) = v^*(x, t) + \frac{1}{2}\lambda t \nabla U(m^*), \quad v^*(x, t) = \frac{x_t - \bar{x}_0}{t}. \quad (16)$$

Proof. For a head emitting the clean estimate m under the velocity target, Eq. (3) gives $\hat{v} - v = -(m - x_0)/t$, hence $\|\hat{v} - v\|^2 = t^{-2}\|m - x_0\|^2$ (Li & He, 2026). The terms of Eq. (3) read only m , so at $x_t = x$, with $\mathbb{E}[\|m - x_0\|^2 \mid x_t = x] = \|m - \bar{x}_0\|^2 + \text{tr } \Sigma_{0|t}$,

$$\mathbb{E}[\|\hat{v} - v\|^2 + \lambda U(m) \mid x_t = x] = \frac{1}{t^2}(\|m - \bar{x}_0\|^2 + \text{tr } \Sigma_{0|t}) + \lambda U(m). \quad (17)$$

The trace is finite by Assumption D.1(iii) and constant in m , and multiplying by $t^2/2$ leaves $\frac{1}{2}\|m - \bar{x}_0\|^2 + \gamma_t U(m)$, whose unique minimizer is Eq. (15) by Lemma D.1; the pointwise minimizers assemble into the global one by Assumption D.1(iii), on a set of full p_t -measure. For Eq. (16), Eq. (3) gives $\hat{v} = (x_t - m)/t$ for any clean estimate m , and prox optimality gives $\bar{x}_0 - m^* = \gamma_t \nabla U(m^*)$. $\square$

The step is implicit: on a convex quadratic model the operator $(I + \gamma_t H)^{-1}$ contracts every mode for any $\gamma_t > 0$, whereas an explicit step contracts a mode only for $|1 - \eta \lambda_i| < 1$, and it anneals as t^2 with no hand-set schedule. The t -scaled arms of Appendix H.4 add a second factor to one already present.

Proposition D.3. *Let a network f_θ emit $y = f_\theta(x_t, t)$, let its clean estimate be $m = y$ for the x_0 head and $m = x_t - t y$ for the velocity head, and let the auxiliary term act on m . (i) Both heads have the conditional loss of Eq. (17) and the minimizer m^* of Theorem D.1. (ii) The gradient of the auxiliary term with respect to the weights is $\lambda J_m^\top \nabla U(m)$ for the x_0 head and $-\lambda t J_y^\top \nabla U(m)$ for the velocity head, with J the head output's Jacobian in θ . The two coincide when the velocity network satisfies $f_\theta = (x_t - m_\theta)/t$, that is, reproduces x_t/t at its output on top of the clean estimate. (iii) The velocity head's target contains the noise explicitly, $(x_t - m^*)/t = x_1 + ((1 - t)x_0 - m^*)/t$, which equals $x_1 - m^*$ at $t = 1$, whereas the target m^* of the x_0 head does not.*

Proof. (i) For the velocity head $\hat{v} = y$ and $v = (x_t - x_0)/t$, so $\hat{v} - v = (x_0 - m)/t$; for the x_0 head $\hat{v} = (x_t - m)/t$ gives the same difference, and both losses are the function of m in Eq. (17). (ii) is the chain rule through $m = y$ and $m = x_t - t y$; the two parameter gradients are equal whenever the two networks implement the same m_θ . (iii) follows from $x_t = (1 - t)x_0 + t x_1$. $\square$

The head does not change what a perfect model learns. Which head a network of finite capacity trains better is an empirical question, the clean-sample argument of Li & He (2026), and Table 1a measures it without the term: the x_0 head has the lowest soft cost of the three at NFE=32 and the only usable one-step estimate.

Proposition D.4. *Let a model with weights θ output $f_c(\theta)$ for an input c , $J_c = \partial f_c / \partial \theta$, and let $\ell(\cdot; c) \geq 0$ be a differentiable loss that needs no reference sample. The step $\theta_\eta = \theta - \eta \lambda J_c^\top \nabla \ell(f_c; c)$ on a training input c changes the loss on any input c' at rate $-\lambda \nabla \ell(f_{c'}; c')^\top K \nabla \ell(f_c; c)$ with $K = J_{c'} J_c^\top$ at $\eta = 0$, so $\ell(f_{c'}; c')$ strictly decreases for small $\eta > 0$ when this rate is negative; a loss that needs a reference has no term at an input without one.*

Proof. $\nabla_\theta \ell(f_c; c) = J_c^\top \nabla \ell$ by the chain rule, and the derivative of $\ell(f_{c'}; c')$ along $-\lambda J_c^\top \nabla \ell(f_c; c)$ is the stated rate. $\square$

In Trinity c is a chip and $\ell = U$; energies summed over block pairs and single blocks, with weights shared across blocks, are where K aligns the two gradients, a condition the proposition states and does not establish.

D.4 PHYSICS IN SAMPLING

Lemma D.2. Let $x_t = (1-t)x_0 + tx_1$ with $x_1 \sim \mathcal{N}(0, I)$ independent of x_0 and $t \in (0, 1]$, and let U be measurable with $\mathbb{E}[e^{-U(x_0)}] < \infty$ and $\mathbb{E}[\|x_0\| e^{-U(x_0)}] < \infty$. With the reweighted posterior mean

$$\tilde{x}_0(x) = \frac{\mathbb{E}[x_0 e^{-U(x_0)} \mid x_t = x]}{\mathbb{E}[e^{-U(x_0)} \mid x_t = x]}, \quad (18)$$

for every x ,

$$\nabla_x \log \mathbb{E}[e^{-U(x_0)} \mid x_t = x] = \frac{1-t}{t^2} (\tilde{x}_0(x) - \bar{x}_0(x)). \quad (19)$$

Proof. The channel is $p(x \mid x_0) = \mathcal{N}((1-t)x_0, t^2 I)$, so $\nabla_x \log p(x \mid x_0) = ((1-t)x_0 - x)/t^2$. By Bayes' rule $\mathbb{E}[e^{-U(x_0)} \mid x_t = x] = \int e^{-U(x_0)} p(x \mid x_0) p_{\text{data}}(x_0) dx_0 / p_t(x)$ with $p_t(x) = \int p(x \mid x_0) p_{\text{data}}(x_0) dx_0$. Both integrands are differentiable in x , with $\|\nabla_x p(x \mid x_0)\| \leq t^{-2}((1-t)\|x_0\| + \|x\|) p(x \mid x_0)$ and $p(x \mid x_0) \leq (2\pi t^2)^{-d/2}$, so on a bounded set of x the two moment conditions supply an integrable dominating function and the derivative passes under both integrals (dominated convergence). Differentiating the logarithm of the quotient gives $\nabla_x \log \mathbb{E}[e^{-U(x_0)} \mid x_t = x] = \mathbb{E}_U[\nabla_x \log p(x \mid x_0)] - \mathbb{E}[\nabla_x \log p(x \mid x_0) \mid x_t = x]$, where $\mathbb{E}_U$ is the expectation under the posterior reweighted by $e^{-U(x_0)}$. Inserting the score of the channel, the $-x/t^2$ terms cancel and the x_0 terms leave $\frac{1-t}{t^2}(\tilde{x}_0 - \bar{x}_0)$. $\square$

The substitution error does not vanish with $\Sigma_{0|t}$. Take a point mass $x_0 \equiv b$ with $b \neq 0$ and $U(x) = \|x\|^2$. Then $\bar{x}_0 = \tilde{x}_0 = b$ at every (x, t) , so the right side of Eq. (19) is zero and the exact guidance vanishes, while a loop step $-\nabla U(\bar{x}_0) = -2b$ does not. The difference between the clean-space gradient and the exact guidance is therefore not controlled by $\Sigma_{0|t}$ and does not vanish as $t \rightarrow 0$, which is Proposition 3.2(i).

Corollary D.1. Let $q \propto p_{\text{data}} e^{-U}$ with marginals q_t, U as in Lemma D.2. Then

$$\nabla \log q_t(x) - \nabla \log p_t(x) = \nabla \log \mathbb{E}[e^{-U(x_0)} \mid x_t = x] = \frac{1-t}{t^2} (\tilde{x}_0(x) - \bar{x}_0(x)). \quad (20)$$

If moreover $U \in C^3$ with bounded third derivatives on the support of $p(x_0 \mid x_t)$ and $\mathbb{E}[\|x_0 - \bar{x}_0\|^3 \mid x_t] < \infty$, then with $H = \nabla^2 U(\bar{x}_0)$ and $\Sigma = \Sigma_{0|t}$,

$$\log \mathbb{E}[e^{-U(x_0)} \mid x_t] = -\left[U(\bar{x}_0) + \frac{1}{2} \text{tr}(H\Sigma) - \frac{1}{2} \nabla U^\top \Sigma \nabla U\right] + O(\mathbb{E}[\|x_0 - \bar{x}_0\|^3 \mid x_t]). \quad (21)$$

Moreover $\mathbb{E}[e^{-U(x_0)} \mid x_t] = e^{-U(\bar{x}_0)}$ for every U of the form $U(z) = \|z - \mu\|^2$, $\mu \in \mathbb{R}^d$, if and only if $\Sigma_{0|t} = 0$.

Proof. For Eq. (20), $q_t(x) = \int q(x_0) p_t(x \mid x_0) dx_0 = Z^{-1} p_t(x) \mathbb{E}[e^{-U(x_0)} \mid x_t = x]$; take logarithms and gradients, and apply Lemma D.2. For Eq. (21), put $\Delta = x_0 - \bar{x}_0$, so $\mathbb{E}[\Delta \mid x_t] = 0$ and $\text{Cov}(\Delta) = \Sigma$. Taylor's theorem with the third-derivative bound gives $U(x_0) - U(\bar{x}_0) = \nabla U^\top \Delta + \frac{1}{2} \Delta^\top H \Delta + r$ with $|r| \leq c \|\Delta\|^3$, the expectation of the exponential is $1 - \frac{1}{2} \text{tr}(H\Sigma) + \frac{1}{2} \nabla U^\top \Sigma \nabla U + O(\mathbb{E}[\|\Delta\|^3 \mid x_t])$ by the third-moment condition, and $\log(1+u) = u + O(u^2)$. For the equivalence, sufficiency is immediate. For necessity the single choice $\mu = \bar{x}_0$ suffices: the identity reads $\mathbb{E}[e^{-\|\Delta\|^2} \mid x_t] = 1$, and $1 - e^{-\|\Delta\|^2} \geq 0$ has zero expectation, so it vanishes almost surely and $\Delta = 0$ almost surely. $\square$

After sampling and inside it. Descending U after sampling, Use 2 of Section 3.3, acts at $t = 0$, where $\Sigma_{0|0} = 0$ and the covariance terms of Eq. (21) are absent, a reading consistent with Lemma D.2; it does not by itself produce a sample of q or a feasible layout. Descending U inside the sampler at $t > 0$ substitutes a clean-space gradient for the exact guidance of Lemma D.2.

Proposition D.5. Both schemes produce a velocity $(x_t - A(\bar{x}_0))/t$, with

$$A_{\text{train}} = (I + \gamma_t \nabla U)^{-1}, \quad A_{\text{loop}} = (I - \eta \nabla U)^k, \quad (22)$$

where A_{train} , the resolvent of ∇U , is single valued and equal to $\text{prox}_{\gamma_t U}$ under Assumption D.1(i) with $\gamma_t \beta < 1$ (Lemma D.1). The two velocity fields are equal pointwise if and only if the loop solves $\text{prox}_{\gamma_t U}$ exactly, and if ∇U is L -Lipschitz they agree to first order in the total step when $k\eta = \gamma_t$ and $\gamma_t L < 1$, the difference at $y = \bar{x}_0$ being at most $L(k\eta)^2 \|\nabla U(y)\| (\frac{1}{2} e^{k\eta L} + (1 - k\eta L)^{-1})$.

Proof. Eq. (3) gives $\hat{v} = (x_t - m)/t$ for any clean estimate m . Theorem D.1 identifies A_{train} as the resolvent, single valued by Lemma D.1, and A_{loop} is k explicit steps by definition. Equality of the fields is equality of $A(\bar{x}_0)$. For the first order, $a = A_{\text{train}}(y)$ satisfies $a = y - \gamma_t \nabla U(a)$, so the Lipschitz bound gives $\|a - y\| \leq \gamma_t \|\nabla U(y)\| + \gamma_t L \|a - y\|$, hence $\|a - y\| \leq \gamma_t \|\nabla U(y)\| / (1 - \gamma_t L)$ and $\|a - (y - \gamma_t \nabla U(y))\| \leq \gamma_t L \|a - y\| \leq L \gamma_t^2 \|\nabla U(y)\| / (1 - \gamma_t L)$. The loop ends within $\frac{1}{2} L (k\eta)^2 \|\nabla U(y)\| e^{k\eta L}$ of $y - k\eta \nabla U(y)$ by Theorem D.2(i), and the triangle inequality adds the two. $\square$

Lemma D.3. *If U_C is differentiable, $U_C \geq 0$ and $U_C(x^*) = 0$, then $\nabla U_C(x^*) = 0$.*

Proof. x^* is a global minimizer of the differentiable function U_C , so its gradient vanishes there. $\square$

Theorem D.2. *Let $x^* \in \text{supp}(p_{\text{data}})$, let ∇U be L -Lipschitz on a ball around x^* that contains the iterates below, and for (ii) assume a local quadratic model $U \approx \frac{1}{2}(x - c)^\top H(x - c)$ near a feasible point with $H \succeq 0$ of eigenvalues λ_i , together with the assumption that the null space of H is the tangent space of $\mathcal{F}$ there, which holds for U_C alone and need not once U_O is added. Then*

1. $\nabla U(x^*) = \nabla U_O(x^*)$, and k gradient steps of size η started at x^* end at distance $k\eta \|\nabla U_O(x^*)\| + R$ from it with $|R| \leq \frac{1}{2} L \|\nabla U_O(x^*)\| (k\eta)^2 e^{k\eta L}$, a displacement that is nonzero to first order whenever the objectives do not vanish at x^* ;
2. for $0 < \eta < 2/\max_i \lambda_i$, mode by mode the operators of Eq. (22) act as

$$\text{training: } \frac{1}{1 + \gamma_t \lambda_i} \rightarrow 1 \text{ as } t \rightarrow 0, \quad \text{in-sampler: } (1 - \eta \lambda_i)^k, \text{ independent of } t, \quad (23)$$

the explicit factor contracting a mode only when $|1 - \eta \lambda_i| < 1$;

3. $\|m^* - \bar{x}_0\|^2 \leq 2\gamma_t U(\bar{x}_0)$, which vanishes as $t \rightarrow 0$ wherever $U(\bar{x}_0(x, t))$ stays bounded, while $\|A_{\text{loop}}(\bar{x}_0) - \bar{x}_0\|$ does not.

Proof. For (i), $U_C(x^*) = 0$ by Assumption D.1(ii), so Lemma D.3 gives $\nabla U(x^*) = \nabla U_O(x^*) =: g$. With $x_{j+1} = x_j - \eta \nabla U(x_j)$ and $x_0 = x^*$, $\|x_j - x^*\| \leq \eta \sum_{i < j} (\|g\| + L \|x_i - x^*\|)$, so by induction $\|x_j - x^*\| \leq j\eta \|g\| (1 + \eta L)^j$, and $x_k - x^* = -k\eta g - \eta \sum_{j < k} (\nabla U(x_j) - g)$ with the sum bounded in norm by $\eta L \sum_{j < k} j\eta \|g\| (1 + \eta L)^j \leq \frac{1}{2} L \|g\| (k\eta)^2 e^{k\eta L}$. For (ii), both operators are linear in the quadratic model and diagonal in the eigenbasis of H ; $\gamma_t \rightarrow 0$ as $t \rightarrow 0$ while η and k are fixed. For (iii), prox optimality compares m^* with the candidate $\bar{x}_0$, $\frac{1}{2} \|m^* - \bar{x}_0\|^2 + \gamma_t U(m^*) \leq \gamma_t U(\bar{x}_0)$, and $U \geq 0$. $\square$

In the model the stiff modes are the constrained ones, so a fixed loop removes the spread along the constrained directions at every step including the last and never releases the over-travel of (i); Section 4.3 measures both, the ported loops leaving an area gap of 10 to 30% and every generator ending near one value under the best of them. The quadratic model holds on each smooth piece of U : no term is smoothed, and U has kinks at zero penetration, at contact, at the bounding-box frontier, at the extreme pins and at the group median. As a hypothesis, the overlap gradient is the penetration force of one pair while the resolution the data supports depends on the netlist and the layout, so descent on the non-convex U may reach a nearby local minimum rather than the plausible one, whereas Theorem D.1 minimizes the same term jointly with the flow loss; Appendix G is consistent with this reading but does not establish it.

Proposition D.6. *Let the learned head be $\bar{x}_0 + \varepsilon_\theta$ with $\mathbb{E}_{x \sim p_t} \|\varepsilon_\theta\|^2 \leq \delta^2$, and let p_t^g , the law of the states a guided sampler visits, be absolutely continuous with respect to p_t with an essentially bounded density ratio. Then*

$$\mathbb{E}_{x \sim p_t^g} \|\varepsilon_\theta\|^2 \leq \chi_t \delta^2, \quad \chi_t = \text{ess sup}_x \frac{p_t^g(x)}{p_t(x)} < \infty, \quad \text{and} \quad \frac{\partial \bar{x}_0}{\partial x_t} = \frac{(1-t) \Sigma_{0|t}}{t^2} \xrightarrow{t \rightarrow 1} 0. \quad (24)$$

Proof. The bound is the importance-weight inequality. Tweedie's formula for the channel $x_t | x_0 \sim \mathcal{N}((1-t)x_0, t^2 I)$ gives $\bar{x}_0 = (x_t + t^2 \nabla \log p_t)/(1-t)$ and hence $\partial \bar{x}_0 / \partial x_t = (I + t^2 \nabla^2 \log p_t)/(1-t)$, while the same channel gives $(1-t)^2 \Sigma_{0|t} = t^2 (I + t^2 \nabla^2 \log p_t)$. Eliminating the Hessian gives the stated form, and $(1-t) \rightarrow 0$ with $\Sigma_{0|t}$ bounded. $\square$

Training with the loop in place would remove the support mismatch, at the cost of running the loop at every training step.

D.5 WHAT IS PREDICTED AND WHAT IS MEASURED

Two limits remain. Training with the terms does not sample the reweighted law of Corollary D.1 either; the claim is asymmetric, the loop’s clean-space gradient missing the exact guidance of Lemma D.2 by an amount $\Sigma_{0|t}$ does not control, while Theorem D.1 characterizes the trained head exactly at no sampling cost. The results concern where a correction is applied, not whether the six quantities are right, which Section 4.2 measures.

E THE CLOSED-FORM REFINER

E.1 DERIVATIVES

The refiner works in normalized units ($s = 1$) on the latent $z = (u, v, \rho)$ with $c_x = us$, $c_y = vs$, $w = \sqrt{a} e^{\rho/2}$, $h = \sqrt{a} e^{-\rho/2}$. Every term is written on the box edges $L = c_x - w/2$, $R = c_x + w/2$, $B = c_y - h/2$, $T = c_y + h/2$, its derivative is taken with respect to (L, B, R, T) and folded,

$$\frac{\partial E}{\partial c_x} = \frac{\partial E}{\partial L} + \frac{\partial E}{\partial R}, \quad \frac{\partial E}{\partial w} = \frac{1}{2} \left(\frac{\partial E}{\partial R} - \frac{\partial E}{\partial L} \right), \quad \frac{\partial E}{\partial \rho} = \frac{w}{2} \frac{\partial E}{\partial w} - \frac{h}{2} \frac{\partial E}{\partial h}, \quad (25)$$

and likewise in y . Position-frozen blocks (preplaced) get $\partial E / \partial c_x = \partial E / \partial c_y = 0$, shape-frozen blocks (fixed, preplaced) get $\partial E / \partial w = \partial E / \partial h = 0$, padding gets zero, and $\partial E / \partial \rho = 0$ where $|\rho|$ sits on the clamp at 4. The six derivatives:

- **overlap**, $E = \sum_{i < j} o_x o_y / s^2$ with $o_x = \max(0, \min(R_i, R_j) - \max(L_i, L_j))$: a pair with $o_x o_y > 0$ gives $\partial E / \partial R_i = o_y [R_i < R_j] / s^2$ and $\partial E / \partial L_i = -o_y [L_i > L_j] / s^2$, and the same in y with o_x . The force on a block is the overlap length of the crossing edge, and a pair at exact contact feels none.
- **cluster**, $E = \sum_p \sum_{(i,j) \in \text{MST}_p} \text{gap}_{ij} / s$ with $\text{gap} = \max(g_x, g_y)$, $g_x = \max(0, \max(L_i, L_j) - \min(R_i, R_j))$: the tree is recomputed every step by batched Prim’s algorithm, and every tree edge with a positive gap pulls its endpoints together along the active axis with unit force, the right block through $\partial E / \partial L = +1/s$, the left through $\partial E / \partial R = -1/s$, both widening toward each other through $\partial E / \partial w = -1/(2s)$.
- **MIB**, $E = \sum_q \sum_{i \in q} |\rho_i - \tilde{\rho}_q|$ with the median detached: $\partial E / \partial \rho_i = \text{sign}(\rho_i - \tilde{\rho}_q)$, zero for the median member. A pure shape force.
- **boundary**, $E = \sum_{i \in B} \sum_{e \in \text{code}(i)} (\text{side} - \text{edge}) / s$: a left-coded block gets $\partial E / \partial L = +1/s$ and the block that owns $x_{\min}$ gets $\partial E / \partial L = -1/s$ per left-coded block, symmetric for the other sides. The coded block moves to the outline and the outline’s owner moves toward the coded block.
- **wirelength**, $E = H / (sW)$ with $H = \frac{1}{2} \sum_{ij} A_{ij} |c_i - c_j|_1 + \sum_p w_p |c_{b_p} - q_p|_1$: $\partial E / \partial c_{x,i} = [\sum_j \tilde{A}_{ij} \text{sign}(c_{x,i} - c_{x,j}) + \sum_{p \rightarrow i} w_p \text{sign}(c_{x,i} - q_p^x)] / (sW)$ with $\tilde{A} = \frac{1}{2}(A + A^\top)$, no shape force.
- **area**, $E = (x_{\max} - x_{\min})(y_{\max} - y_{\min}) / s^2$: only the four outline owners move, $\partial E / \partial L_{\arg \min L} = -H_{\text{bb}} / s^2$, $\partial E / \partial R_{\arg \max R} = +H_{\text{bb}} / s^2$, and likewise in y with W_{bb} .

In latent units the cluster, boundary and MIB forces are exactly 1 per active coordinate, wirelength is A_{ij}/W , area is H_{bb}/s and overlap is o_y/s , of order 0.01. The closed form equals autograd of the batched terms to 10^{-6} in float64, per term and summed, on the test suite of the supplementary code.

E.2 THE STEP

Adam with $\beta_1 = 0$: $v \leftarrow \beta_2 v + (1 - \beta_2) g^2$, $z \leftarrow z - \text{lr}_t g / (\sqrt{v / (1 - \beta_2^t)} + \epsilon)$. Without momentum a block that has just been pushed out of an overlap stops when the force stops instead of coasting into the next block, and the per-coordinate normalization lets each term move its block at the full step whatever its magnitude, so the weights set the priority where terms compete on one coordinate. The learning-rate vector is precomputed from the schedule, the overrides are re-applied after every step, and K steps run inside one compiled function. At 400 steps the refiner takes about one millisecond per layout: 2.6 μs per step per layout with 1,000 layouts in a batch on one RTX 5090, wall-clock with the device synchronized, the median of five timed repeats after a warm-up (Table 9), and 20 ms per layout at 32 per batch.

E.3 CHOOSING THE SETTING

The setting was chosen on Trinity and on Trinity at $\lambda=0$, on the same 12k cases, by the mean soft cost over the ten refined cells of $\text{NFE} \in \{1, 32\} \times \text{steps} \in \{10, 25, 50, 100, 200\}$ (Table 14). A decaying schedule with peak 10^{-3} is the operating point on both models, linear and cosine are the same within 0.005 at every cell, a constant learning rate over-refines (overlap turns up after 50 steps at 10^{-3}), peak 3×10^{-3} pays a transient at 10 steps, and 10^{-4} is too slow at every budget. Optimizer cross-checks at the pick: Adam (0, 0.9) 1.294 / 1.340, a 10-step warmup 1.291 / 1.293, plain gradient steps 1.564 / 1.578 at 10^{-3} and 1.964 / 1.967 at 3×10^{-3} . Plain steps do not refine, because the overlap force per coordinate is a hundredth of the unit forces of the constraint terms, and Adam’s normalization is what lets the six terms act at one step size.

Table 14: Refiner schedule and peak learning rate, all weights 1, betas (0, 0.99), on Trinity and on Trinity at $\lambda=0$: the rule (the mean soft cost over the ten refined cells of $\text{NFE} \in \{1, 32\} \times \text{steps} \in \{10, 25, 50, 100, 200\}$), and for the six schedules run further the soft cost / overlap ratio at $\text{NFE}=32$ after 100 and 200 steps (raw: 1.5137 / 0.0225 and 2.0151 / 0.0222).

Schedule, peak rate	Rule, Trinity	Rule, $\lambda=0$	Trinity, 100 steps	Trinity, 200 steps	$\lambda=0$, 100 steps	$\lambda=0$, 200 steps
linear 10^{-3}	1.2698	1.2688	1.1625 / 0.0105	1.1617 / 0.0118	1.1549 / 0.0096	1.1506 / 0.0107
cosine 10^{-3}	1.2747	1.2713	1.1578 / 0.0105	1.1581 / 0.0117	1.1501 / 0.0095	1.1471 / 0.0107
linear 3×10^{-4}	1.3182	1.3750	1.1786 / 0.0110	1.1594 / 0.0108	1.1755 / 0.0097	1.1486 / 0.0094
cosine 3×10^{-4}	1.3188	1.3746	—	—	—	—
constant 3×10^{-4}	1.3370	1.3597	1.2347 / 0.0120	1.2356 / 0.0131	1.2230 / 0.0104	1.2193 / 0.0115
linear 3×10^{-3}	1.3529	1.3349	1.1910 / 0.0112	1.1876 / 0.0131	1.1859 / 0.0106	1.1801 / 0.0125
cosine 3×10^{-3}	1.3642	1.3450	—	—	—	—
constant 10^{-4}	1.3765	1.4699	—	—	—	—
linear 10^{-4}	1.4247	1.5819	—	—	—	—
cosine 10^{-4}	1.4246	1.5818	—	—	—	—
constant 10^{-3}	1.4953	1.4869	1.4338 / 0.0161	1.4583 / 0.0186	1.4166 / 0.0150	1.4406 / 0.0175
constant 3×10^{-3}	2.1682	2.1433	—	—	—	—

Table 15: Weights and variants at the pick, by the rule of Table 14.

Arm	Trinity	$\lambda=0$	Arm	Trinity	$\lambda=0$
overlap $\times 10$	1.2215	1.2332	all weights 1	1.2698	1.2688
overlap $\times 30$	1.2270	1.2471	cluster $\times 3$	1.2936	1.2938
overlap $\times 3$	1.2434	1.2476	squared cluster gap	1.2938	1.3000
wirelength $\times 0.3$	1.2604	1.2599	boundary $\times 0.3$	1.3003	1.2972
cluster $\times 0.3$	1.2616	1.2590	area $\times 3$	1.3033	1.2927
area $\times 0.3$	1.2624	1.2654	wirelength $\times 3$	1.3368	1.3346
boundary $\times 3$	1.2664	1.2661	overlap $\times 0.3$	1.3629	1.3592
MIB $\times 0.3$ or $\times 3$	1.2698	1.2689	contact margin 0.005 s	1.4212	1.4045

Table 16: The overlap-weight ladder at $\text{NFE}=32$ on Trinity after 100 and 200 steps.

Overlap weight	Steps	Soft cost	Overlap	HPWL gap	Area gap
$\times 1$	100	1.1625	0.0105	−0.0058	0.0060
$\times 3$	100	1.1344	0.0079	−0.0002	0.0087
$\times 10$	100	1.1114	0.0048	0.0040	0.0137
$\times 30$	100	1.1174	0.0032	0.0076	0.0207
$\times 1$	200	1.1617	0.0118	−0.0094	−0.0006
$\times 3$	200	1.1153	0.0077	−0.0017	0.0048
$\times 10$	200	1.0833	0.0035	0.0038	0.0128
$\times 30$	200	1.0897	0.0017	0.0088	0.0228

After the soft slots close, the one conflict left is overlap against wirelength and area, and the overlap weight is the one change that moves the endpoint (Tables 15 and 16): $\times 10$ takes overlap from 0.0118 to 0.0035 and the soft cost from 1.162 to 1.083 at 200 steps, $\times 30$ reaches 0.0017 at a larger wirelength and area price. The MIB weight has no effect because the MIB variance is 10^{-11} by 25 steps at any weight, a contact margin keeps every touching pair under force and inflates the layout, and a squared gap weakens the cluster pull near contact. The ranking is the same on both models, and combinations with overlap $\times 10$ move nothing beyond the single change. The setting of every refined number in the paper is therefore: Adam (0, 0.99), linear decay from 10^{-3} , overlap 10, the other five terms 1.




Figure 9: Generator $\times$ refiner at NFE=32 with every ported loop on every generator’s own samples, the full version of Table 6. Left: soft cost, where the DiffPlace loop makes every generator worse than its raw sample. Right: the hard cost of the first legalized draw (Table 50), where the same loop is the best of the three.

E.4 THE PRIOR ARTS’ LOOPS

Figure 9 draws every loop on every generator’s own samples, and Table 17 is the full soft vector of every loop on the NFE=32 samples of Trinity (draw 0 of every case, the Trinity row of Table 6); on the samples of Trinity at $\lambda=0$ every column moves the same way. Every port removes overlap harder than the closed-form refiner at 100 steps and pays in every other column: the die-boundary term lets the blocks fill the canvas, the area gap lands at +0.09 to +0.16, wirelength at +2 to +6%, and the soft rules the loops do not model get worse than raw; the MIB variance and the immutable-block deviation are unchanged because the loops cannot move shapes. Without the 5% canvas margin the ChipDiffusion loop stops removing overlap (0.0225 to 0.0148 in 5,000 iterations).

Table 17: The prior-art loops on the NFE=32 samples of Trinity: the ChipDiffusion loop in its standard, scheduled and Adam-with-dual-ascent variants (5,000 iterations), the DiffPlace and MacroDiff+ loops (500), and the closed-form refiner at all weights 1. Units as in Section 4.1.

Refiner	Overlap	Boundary	Group	HPWL gap	Area gap	sev _{rel}	Soft cost
raw	0.0225	0.8	2.4	−0.0008	0.0022	0.0851	1.5131
closed-form, 100 steps	0.0105	0.2	0.9	−0.0058	0.0060	0.0152	1.1625
ChipDiffusion, standard	0.0016	2.8	6.6	0.0470	0.1052	0.2289	1.7472
ChipDiffusion, scheduled	0.0016	3.0	6.5	0.0449	0.1046	0.2420	1.7908
ChipDiffusion, dual ascent	0.0096	12.0	4.2	0.0171	0.0940	0.4010	2.6232
DiffPlace	0.0009	18.3	4.6	0.0379	0.1588	0.4945	3.0349
MacroDiff+	0.0014	1.7	6.4	0.0491	0.1049	0.1765	1.5649




Figure 10: The four constraint quantities at NFE=32 along the closed-form refiner for the five generators, and each ported placer’s own post-hoc loop at its published setting as a hollow marker (ChipDiffusion 5,000 iterations, MacroDiff+ and DiffPlace 500). The loops match the refiner on overlap and leave the other three quantities one to four orders of magnitude above it.

Figure 58 places every loop against the refiner budget in both costs. On the prior arts’ own samples the loops end at soft cost / overlap: FlowPlace 1.961 / 0.0055 (ChipDiffusion loop), 3.497 / 0.0009 (DiffPlace loop), 1.577 / 0.0027 (MacroDiff+ loop); ChipDiffusion 2.048 / 0.0069 (own), 3.614 / 0.0008, 1.602 / 0.0032; DiffPlace 2.286 / 0.0124, 3.914 / 0.0024 (own), 1.633 / 0.0044; MacroDiff+

2.181 / 0.0075, 3.755 / 0.0010, 1.661 / 0.0031 (own). On these samples the area gap after the loop is +0.11 to +0.13 under the ChipDiffusion and MacroDiff+ loops and +0.22 to +0.30 under the DiffPlace loop.

F THE LEGALIZER

Legalization reads a sequence-pair relation for every pair of blocks from the refined layout (the axis of least penetration, ordered by center) and solves one linear program that packs the blocks under those relations with preplaced blocks pinned, cluster members abutting along a spanning tree and boundary-coded edges on the outline, minimizing the outline plus the displacement from the refined positions (Murata et al., 1996; Murata & Kuh, 1998). When the program is infeasible the soft terms become penalties and the relations of the conflicting preplaced pairs are flipped. A second program then lets soft blocks change aspect at fixed area under the same relations, kept when the checker scores it better, and the smallest uniform expansion that separates every pair is reported as the price of residual overlap. Table 18 lists the eight steps.

Table 18: The legalizer, one stage of eight steps. Every step is a one-line rule or a standard constraint-graph method; the program of step E and the knobs are below.

Step	Rule	Kind
A anchors	pre-placed blocks to their target box, fixed blocks to their shape, soft blocks to their exact area, an all-soft MIB group to one shape	rule
B expansion	every free block moved outward from the layout centre by the smallest $\lambda \geq 1$ (cap 10) at which no pair overlaps; λ recorded per draw	rule
C relations	per pair, the axis of larger separation (least penetration if overlapping) and the order along it, read from the unexpanded layout	sequence pair (Murata et al., 1996), TCG (Lin & Chang, 2001)
C' rewrites	a block ordered between an abutting pair, or outside a coded block on its coded side, re-ordered on the other axis; pinned pairs never rewritten	rule
D abutment tree	per cluster a spanning tree over member pairs ranked by gap, missing perpendicular overlap, blocks in between and pre-placed collisions	rule
E packing LP	one linear program over positions at fixed shapes	LP packing with pre-placed modules (Murata & Kuh, 1998)
F ladder	on infeasibility: abutment and boundary as penalties, then the violated pinned relations flipped (six rounds), then every free block above the pre-placed ones	rule
G contact snap	tree pairs within 10^{-6} of contact set to exact contact, overlap-checked	rule
H aspect pass	one more program with every soft non-MIB shape free within 1.3 per side at fixed area, kept when the checker scores it feasible and cheaper	sequential LP

The program (step E). Variables: X_i, Y_i for every block (fixed to the target for preplaced blocks), the outline L, R, B, T , and non-negative auxiliaries for absolute values and slacks. Constraints: outline $L \leq X_i, X_i + w_i \leq R, B \leq Y_i, Y_i + h_i \leq T$; for every relation (axis, lo, hi), $P_{lo} + \text{size}_{lo} \leq P_{hi}$ on that axis; for every tree edge, hard $P_{lo} + \text{size}_{lo} = P_{hi}$ with perpendicular overlap at least ϵ on both sides, or soft with the absolute deviation penalized; for every coded block $X_i = L, X_i + w_i = R, Y_i = B$ or $Y_i + h_i = T$ per code bit, or the deviation penalized, with a preplaced block's code dropped when another preplaced block makes it impossible. Objective, minimized: $(R - L) H_0 / A_0 + (T - B) W_0 / A_0$ (the outline, linearized at the input bounding box $W_0 \times H_0 = A_0$) + $\mu / (ns) \sum_i (|X_i - \hat{x}_i| + |Y_i - \hat{y}_i|)$ (displacement from the restored positions) + (penalty/s) $\times$ soft slacks + (1,000/s) $\times$ probe slacks. Size: $n^2/2$ relation rows plus $O(n)$ others, at most about 7,200 rows at $n = 120$; one solve takes a few to about 50 milliseconds, and a draw takes 240 to 300 milliseconds end to end including every ladder rung it needs, of which the solver is 87 to 99 milliseconds.

The ladder (step F). The program of step E runs first with the abutment and boundary constraints hard, then with them as penalties, and when that program is infeasible the flip loop runs at most six rounds of two programs each. The first is a probe: the relation of every free and pre-placed pair carries a probe slack, and the pairs whose slack the solution uses are the pinned relations the layout cannot hold. The second is the packing program with those relations moved to the other axis, ordered as the probe placed the two blocks, and every pinned relation hard again. A packing program that places without overlap ends the loop with its layout. When the six rounds are spent, or a probe is infeasible or uses no slack, the flipped relations are discarded and only the pre-placed blocks of the pairs the probes flagged are kept: the next rung reads the relations from the layout again, without the rewrites of step C', and orders every free block above each of those blocks, and the last rung orders every free block above every pre-placed block, which is feasible by construction.

The snap (step G). The snap is a gate on single-block moves. For every tree pair whose gap is within 10^{-6} of contact, the checker's tolerance, the later block along the pair's axis is moved onto the edge of the earlier one, and the move is kept only when the moved block overlaps no other block, over at most three sweeps of the pairs or until a sweep keeps no move. The layout enters feasible, each kept move displaces one block by at most that tolerance and is admitted only when the block overlaps none of the others, and no shape or other pair changes, so the layout is feasible after every kept move and at exit.

Knobs. Relations read from the restored layout (reading them from the expanded layout costs +0.23 in outline area because the larger λ flips the axis on many pairs), $\mu = 0.5$ and penalty 10 (0.1 / 0.5 / 2 and 10 / 100 are identical at three decimals), $\varepsilon = 10^{-3}$, λ cap 10, six flip rounds (three to six moved 6 of 960 draws off the last rung on the tuning subset), aspect pass at trust 1.3 (off: best-of-4 1.103 on the subset; 1.3: 1.066, kept on 57% of draws; 1.6: 1.071).

Residual analysis. On the 240-case tuning subset at 400 refiner steps, before the aspect pass, the hard program is feasible on 24% of draws at cost 1.02, the penalized program on 57% at 1.2, pinned flips on 15%, and the last rungs on 4% at about 3. The residual violations of the penalized rung on 80 draws are 95 boundary counts (14 on preplaced blocks, 20 with a preplaced block already beyond the coded edge, 38 corner codes, 69 within 2% of s of the edge) and 142 cluster counts (10 with a preplaced member, 133 with the nearest member within 2% of s), near-misses a position-only program under fixed relations cannot close, which is what the aspect pass addresses: with it, the counted violations per draw fall from $1.4 + 1.5$ to $1.0 + 1.2$, the area gap from +0.117 to +0.081, and the best-of-4 cost from 1.103 to 1.066.

Rejected designs. Relations read from the expanded layout (+0.23 to +0.34 in outline area); expansion that moves preplaced blocks too (relations conflict with the true pinned positions, 22% of draws on the last rung); a re-read of all relations from the penalized solve instead of flipping the violated pairs (25% on the last rung); rewrites of pinned-pair relations (infeasible on 5% of draws); a tighter position box of $\pm 3s$ (the last rung infeasible on 2.5%); and the competition-era portfolio whose overlap removal is a 200-round pairwise push that converges on 25% of the refiner's draws and falls to a shelf pack on 37%, at a single-draw mean of 2.21 and 90th percentile 7.7 on the full 12k against 1.23 and 1.55 for the stage above.

G MEASURING THE PROPOSITIONS

Every figure and table here is an inference on the trained checkpoints over the dev split: the raw $\hat{x}_0$ of eight checkpoints on the same x_t (Proposition 3.1), the reference layouts through every correction loop (Proposition 3.2; no loop moves a pre-placed block), layout snapshots of three cases, GSRC with three checkpoints, and the loops' time per step (2,000 dev cases padded to 120 blocks, 100 steps, the median of five repeats on one idle RTX 5090). In the prediction $\gamma_t \|\nabla U\|$, $\gamma_t = c\lambda t^2/2$ with c the mean number of real latent coordinates of a case, three per block: the flow loss is averaged over these coordinates and the energy is not, so the pointwise minimizer of Theorem D.1 carries the factor c . The prediction is the population optimum. The measured excess of Trinity over the seed floor agrees with it in sign and rises with t , but its ratio to the prediction runs from about 10^2 at $t=0.001$ to about 10^{-3} at $t=1$ (Table 19): a network of finite capacity does not reach the pointwise minimizer where γ_t is large, so the check confirms the direction and the growth with t , not the magnitude. On GSRC n100 (Table 21) the share of draws that fit the outline differs across checkpoints of one recipe, 0.36, 0.80 and 0.98, while the best fitting wirelength stays within 1%; the second seed of Trinity fits 98% of its draws, so the gap is a checkpoint-to-checkpoint variance of the raw outline on netlists outside

the training distribution rather than an effect of the physics term.

G.1 THE PROXIMAL CORRECTION AGAINST t




Figure 11: The raw $\hat{x}_0$ of Trinity against its backbone at $\lambda=0$ on the same x_t , 2,000 cases. **(a)** The RMS gap, its component along $-\nabla U$ and across it, and the seed floor (two $\lambda=0$ seeds against the third). **(b)** The excess of the along-component over the floor for three physics weights, each with its proximal prediction $\gamma_t \|\nabla U\|$, $\gamma_t = \lambda t^2/2c$, and a t^2 guide.

Table 19: Trinity against its $\lambda=0$ backbone on the same x_t , 2,000 cases, latent units, one column per t : the RMS gap and its part along $-\nabla U$ for the seed floor (two $\lambda=0$ seeds against the third) and for Trinity, the excess over the floor and its part across ∇U , the prediction with $\gamma_t = c\lambda t^2/2$, their ratio, and the excess at two other weights.

t	0.001	0.005	0.01	0.03	0.1	0.3	1
RMS gap, seed floor	0.0069	0.0057	0.0052	0.0062	0.0150	0.0337	0.0510
RMS gap, Trinity	0.0077	0.0060	0.0050	0.0061	0.0150	0.0344	0.0533
along $-\nabla U$, seed floor	0.0058	0.0055	0.0053	0.0053	0.0062	0.0080	0.0100
along $-\nabla U$, Trinity	0.0076	0.0070	0.0066	0.0069	0.0090	0.0136	0.0216
excess of Trinity over the floor	0.0018	0.0015	0.0012	0.0016	0.0028	0.0056	0.0116
across ∇U , Trinity	0.0077	0.0060	0.0050	0.0061	0.0150	0.0343	0.0533
prediction $\gamma_t \ \nabla U\ $	1.9e-05	0.00047	0.0019	0.017	0.19	1.7	19
ratio, excess over prediction	97	3.2	0.65	0.096	0.015	0.0033	0.00063
excess at $\lambda=0.05$	0.0027	0.0025	0.0024	0.0028	0.0046	0.0101	0.0176
excess at $\lambda=0.1 t$	0.0021	0.0019	0.0018	0.0020	0.0028	0.0085	0.0210

Table 20: The 12,000 reference layouts through each correction, means at the end: RMS and largest displacement of movable blocks (s units), soft cost and share of cases whose soft cost rose, overlap, boundary distance and cluster gap (10^{-3}), wirelength and area gaps in percent of the reference.

Correction	Steps	RMS	Max	Soft cost	Rose	Overlap	Boundary	Cluster	WL	Area
reference layouts	—	—	—	1.065	—	0.0000	0.75	0.00	−0.0	+0.0
ChipDiffusion loop	5,000	0.0272	0.0497	1.762	100%	0.0001	2.92	5.15	+4.0	+10.2
DiffPlace loop	500	0.0252	0.0576	2.584	100%	0.0008	14.41	2.25	+2.8	+12.5
MacroDiff+ loop	500	0.0290	0.0560	1.536	100%	0.0009	1.73	4.57	+4.4	+10.2
Trinity's refiner	400	0.0055	0.0246	1.007	15%	0.0000	0.05	0.00	−0.2	+0.0
Trinity's refiner, $\omega=1$	400	0.0089	0.0315	1.055	36%	0.0048	0.04	0.00	−1.1	−1.1

G.2 REFERENCE LAYOUTS THROUGH EVERY LOOP




Figure 12: The 12,000 reference layouts through every correction. **(a)** RMS displacement of the movable blocks against steps. **(b)** Soft cost against steps, the reference layouts dotted. **(c)** The six terms of U at the end, every weight 1.

G.3 SNAPSHOTS OF THE CORRECTIONS




Figure 13: The 67-block case of Figure 4, every correction from a raw draw (the row labels) at an early and a late budget, the box on each layout magnified in the window beside it: left, where the early state keeps the most overlap; right, the cluster the correction moves most, its gap under the window. Marks as in Figure 4.

G.4 BEYOND FLOORSET: THREE CHECKPOINTS ON GSRC

Table 21: GSRC soft blocks in a 10% square outline, three checkpoints of one recipe, one pipeline (4 seeds, 16 or 64 draws per seed, NFE 8, 400 steps, legalized): best fitting wirelength in mm over the seeds, in brackets the share of draws $\times$ seeds that fit. PARSAC’s best of 16 workers: 52.0 / 155.7 / 183.4 / 303.5 / 576.0 / 705.2. $\dagger$ Oversized: no draw fits, the best legal layout’s box against the outline at 16 draws Trinity on n300 1.29 W $\times$ 0.82 H; Trinity at $\lambda=0$ on n200 1.00 W $\times$ 1.13 H; Trinity at $\lambda=0$ on n300 1.18 W $\times$ 0.92 H; Trinity, seed 1 on n300 1.02 W $\times$ 1.03 H.

Checkpoint	Draws	n10	n30	n50	n100	n200	n300
Trinity	16	50.6 (0.92)	150.6 (0.91)	178.1 (0.98)	294.7 (0.36)	554.9 (1.00)	681.3 † (0.00)
	64	50.3 (0.93)	150.0 (0.89)	177.9 (0.99)	294.0 (0.38)	553.1 (1.00)	681.8 † (0.00)
Trinity at $\lambda=0$	16	51.4 (0.70)	155.6 (0.81)	179.2 (0.81)	293.9 (0.80)	560.1 † (0.00)	679.8 † (0.00)
	64	51.3 (0.61)	154.2 (0.80)	179.1 (0.73)	294.4 (0.65)	549.2 (0.01)	679.4 † (0.00)
Trinity, seed 1	16	49.4 (0.75)	150.1 (0.81)	178.2 (0.95)	297.0 (0.98)	548.1 (1.00)	694.3 † (0.00)
	64	49.2 (0.85)	150.0 (0.84)	177.6 (0.97)	294.7 (0.98)	548.2 (1.00)	692.9 † (0.00)




Figure 14: A 106-block case, the rows of Figure 13.




Figure 15: A 31-block case, the rows of Figure 13.

G.5 TIME PER STEP OF THE LOOPS

Table 22: Each loop against our refiner: iterations to one soft cost on the same samples (loop / ours, Figure 1 right), microseconds per step and layout and peak memory at 32 / 256 / 1,000 layouts per batch, milliseconds per layout and our time advantage at 32 / 1,000.

Loop	Iterations	μs / step	MB	ms / layout	Less time
Trinity's refiner, 400 steps	—	50.8 / 6.1 / 2.6	14 / 112 / 436	20.32 / 1.03	—
DiffPlace loop	500 / 9	60.7 / 7.5 / 3.1	19 / 153 / 597	30.34 / 1.54	67 $\times$ / 67 $\times$
MacroDiff+ loop	500 / 31	292.5 / 36.9 / 20.7	76 / 627 / 2,450	146.25 / 10.35	92 $\times$ / 129 $\times$
ChipDiffusion loop	5,000 / 8	69.6 / 8.8 / 5.3	33 / 272 / 1,062	348.01 / 26.43	904 $\times$ / 1,359 $\times$

H GENERATOR RESULTS IN FULL

Three reference models recur through the appendix. The *base* is the plain backbone with the x_0 head, $\lambda=0$ and no wire dropout; sets 1 to 3 (objective, graph mechanisms, wire dropout) are on it. The *plain control* is the plain backbone on the adopted recipe (the wire-dropout mixture, $\lambda=0$); the term ladders, the composed grid, the prior arts, the regressors and the size rungs are compared against it. *Trinity* at $\lambda=0$ is Trinity’s backbone (spectral encoding and information mover) on the adopted recipe without the auxiliary loss, the model the refiner and seed studies pair with Trinity. MMD8b is a subsample estimate (Appendix C.1), so a run re-evaluated in another batch moves by a few percent, and every table prints the batch its rows were evaluated in. Units follow the convention of Section 4.1: boundary distance, group gap and fixed deviation in units of 10^{-3} , MIB variance in units of 10^{-6} , MMD8b in units of 10^{-3} ; "fixed" is the immutable-block deviation, "HPWL" and "area" the two signed gaps to the reference.

H.1 OBJECTIVE

Table 23: The three heads on the plain base at NFE=32 and 1: overlap ratio, cluster gap, the two gaps, the soft cost and the distribution metrics (p against the base at the same NFE). Boundary, MIB and fixed at NFE=32: 3.2 / 10 / 7.3 (x_0), 4.0 / 15 / 4.6 (v), 3.0 / 6.3 / 2.6 (ϵ).

Head	NFE	Overlap	Group	HPWL gap	Area gap	Soft cost	FLD8b	FLD8f	FPD	MMD8b	p
x_0 head (the base)	32	0.0262	2.7	-0.0024	0.0105	2.106	0.108	0.0045	0.0013	17.7	-
v head	32	0.0373	2.9	-0.0047	0.0123	2.597	0.275	0.0097	0.0028	33.7	1.00
ϵ head	32	0.0365	3.2	-0.0008	0.0149	2.387	0.416	0.0184	0.0025	33.0	1.00
x_0 head	1	0.0383	2.2	-0.015	0.0093	2.491	0.417	0.0184	0.0041	34.1	-
v head	1	0.2505	13	0.18	0.61	77.2	32.0	2.37	0.184	595	1.00
ϵ head	1	0.042	200	5.9	20.3	152	102.7	17.8	5.50	1,238	1.00

The x_0 head has the lowest overlap (-30% against both), the lowest area gap, the lowest distribution distances and the lowest soft cost; the two standard heads have a lower immutable-block deviation (0.0046 / 0.0026 against 0.0073) and the ϵ head a lower MIB variance. At NFE=1 the x_0 head still yields a layout (soft cost 2.49 against 2.11, overlap 0.038 against 0.026), and neither standard head produces one.

H.2 ARCHITECTURE ON THE PLAIN BASE

One graph mechanism each, $\lambda=0$, no wire dropout: *attention heads* lets 4 of the 12 heads attend by a learned affine of the adjacency alone, and the *information mover* adds the gated one-hop residual of Section 3.3 in every layer (92.9M parameters against 85.8M), here with the symmetric normalization $\hat{A} = D^{-1/2}AD^{-1/2}$; the composed arms of Appendix H.6 and Trinity use the row normalization $\hat{A} = D^{-1}A$.

Table 24: Graph mechanisms on the plain base at NFE=32: overlap ratio, cluster gap, the two gaps, the soft cost and the distribution metrics, p against the base at NFE=32 and at 1. Boundary / MIB / fixed: 3.22 / 10.5 / 7.3 (the base), 3.18 / 8.4 / 5.5 (attention heads), 3.11 / 6.7 / 8.4 (information mover); normalized wirelength 0.3014 / 0.3013 / 0.3020 and compactness 1.038 / 1.038 / 1.042.

Arm	Overlap	Group	HPWL gap	Area gap	Soft cost	FLD8b	FLD8f	FPD	MMD8b	p (32)	p (1)
the base	0.0262	2.67	-0.0024	0.0105	2.106	0.108	0.0045	0.0013	17.7	-	-
attention heads	0.0279	2.71	-0.0027	0.0107	2.149	0.137	0.0040	0.0015	19.8	0.84	0.95
information mover	0.0239	2.67	-0.0004	0.0148	2.050	0.113	0.0038	0.0017	20.1	1.00	0.99

Against the base at NFE=32 (NFE=1): the attention heads move overlap +6.6% (+5.2%), MIB -20%, fixed -25%, soft cost +2.0%; the information mover moves overlap -8.5% (-5.6%), boundary -3.6%, MIB -36%, fixed +15%, the HPWL gap toward 0, the area gap +41%, soft cost -2.7%. Overlap across NFE = 1 ... 32: the base 0.0383 / 0.0368 / 0.0339 / 0.0313 / 0.0286 / 0.0262, the mover 0.0362 to 0.0239, the heads 0.0403 to 0.0279. Neither arm is closer to the reference than the base on the density descriptor. The mover places blocks with less overlap and lower MIB variance at the price of wirelength and compactness, which is the trade the terms then close.

H.3 RECIPE: WIRE DROPOUT

Three mixtures were trained on the plain base: *mild* (70% of instances untouched, 30% at a rate from Beta(1,3)), the adopted *mixture* (50% untouched, 40% Beta(1,3), 10% U(0.9,1)) and *heavy* (30%

untouched, 50% Beta(1,2), 20% U(0.8,1)).

Table 25: Wire-dropout mixtures on the plain base: the delta against the base at NFE=32 on overlap, cluster gap, HPWL gap and area gap (at NFE=1 the overlap deltas are +0.4, +0.9 and +2.1%; boundary / MIB / fixed move +1.7 / -19 / -5%, +0.2 / -16 / -20% and -1.0 / -22 / -16%), the absolute soft cost and the distribution metrics.

Arm	Overlap	Group	HPWL gap	Area gap	Soft cost	FLD8b	FLD8f	FPD	MMD8b	<i>p</i>
the base (absolute)	0.0262	2.67	-0.0024	0.0105	2.106	0.108	0.0045	0.0013	17.7	-
mild	-0.8%	+5.0%	+66%	+43%	2.132	0.126	0.0045	0.0016	23.4	1.00
mixture (adopted, the plain control)	-0.5%	-0.7%	+10%	-1.5%	2.092	0.103	0.0033	0.0011	15.6	0.005
heavy	0.0%	+2.7%	+71%	+32%	2.107	0.115	0.0050	0.0014	19.9	1.00

Absolute HPWL gaps: base -0.0024, mixture -0.0021, mild -0.0008, heavy -0.0007; area gaps 0.0105 / 0.0104 / 0.0150 / 0.0139. The adopted recipe's NFE=32 values are the plain control's, the reference of every term ladder: overlap 0.02602, boundary 3.227, group 2.651, MIB 8.75, fixed 0.00582, HPWL gap -0.00214, area gap 0.01037, normalized wirelength 0.3014, compactness 1.037, soft cost 2.0915 (best-of-4 1.9074; NFE=1 2.4900 with overlap 0.03864), FLD8b 0.1031, FLD8f 0.0033, FPD 0.0011, MMD8b 15.6.

H.4 ONE TERM AT A TIME

Table 26: One term at a time on the plain backbone, absolute at NFE=32. Bold: the term's own target. Normalized wirelength and compactness stay within $\pm 0.6\%$ of the plain control (0.3014 and 1.037) for every constraint arm; the wirelength arms move it to 0.3015 / 0.3008 / 0.3000 / 0.3013 and the area arms move compactness to 1.033 / 1.026 / 1.017 / 1.031 for 0.01/0.05/0.1/0.05 *t*.

Arm	Overlap	Boundary	Group	MIB	Fixed	HPWL gap	Area gap	Soft cost
the plain control	0.02602	3.227	2.651	8.75	5.82	-0.00214	0.01037	2.0915
overlap 0.01	0.02423	3.179	2.631	10.6	5.56	-0.00042	0.01180	2.0479
overlap 0.05	0.01948	2.929	2.529	12.6	5.15	-0.00107	0.01235	1.9027
overlap 0.1	0.01796	3.034	2.570	11.5	5.37	-0.00063	0.01348	1.8950
overlap 0.05 <i>t</i>	0.02108	3.124	2.636	12.1	6.59	-0.00088	0.01461	1.9864
cluster 0.01	0.02764	3.318	2.294	9.32	8.69	-0.00280	0.00761	2.1048
cluster 0.05	0.02507	3.262	2.158	9.06	6.99	-0.00125	0.01057	2.0345
cluster 0.1	0.02552	3.453	2.035	9.60	7.34	-0.00075	0.01031	2.0643
cluster 0.05 <i>t</i>	0.02556	3.261	2.472	8.46	6.32	-0.00119	0.01259	2.0754
MIB 0.01	0.02704	3.178	2.673	3.51	7.05	-0.00148	0.01051	2.0960
MIB 0.05	0.02599	3.183	2.767	0.687	6.87	-0.00066	0.01375	2.0812
MIB 0.1	0.02795	3.289	2.756	1.80	7.12	-0.00190	0.01109	2.1405
MIB 0.05 <i>t</i>	0.02714	3.183	2.710	2.86	6.31	-0.00139	0.01242	2.1140
boundary 0.01	0.02468	0.988	2.768	9.05	5.46	-0.00106	0.00377	1.6273
boundary 0.05	0.03094	0.739	3.213	12.5	11.73	+0.00122	0.00738	1.7282
boundary 0.1	0.03845	0.884	3.470	14.1	15.51	+0.00087	0.00431	1.9016
boundary 0.05 <i>t</i>	0.02952	1.080	2.759	10.4	6.14	-0.00253	0.00009	1.7237
wirelength 0.01	0.02687	3.217	2.722	8.52	5.30	-0.00204	0.01195	2.1213
wirelength 0.05	0.02726	3.214	2.758	8.76	6.83	-0.00412	0.01138	2.1297
wirelength 0.1	0.02816	3.217	2.732	11.3	6.71	-0.00688	0.00985	2.1499
wirelength 0.05 <i>t</i>	0.02647	3.151	2.724	8.68	6.15	-0.00256	0.01195	2.1072
area 0.01	0.02652	2.432	2.658	8.73	5.62	-0.00202	0.00626	1.9380
area 0.05	0.02948	1.546	2.697	8.55	6.07	-0.00188	-0.00127	1.8141
area 0.1	0.03578	1.376	2.660	10.1	6.88	-0.00442	-0.00925	1.8833
area 0.05 <i>t</i>	0.02803	1.966	2.667	9.03	6.77	-0.00211	0.00359	1.8772

The target's move against the plain control across 0.01/0.05/0.1/0.05 *t*: overlap -6.9 / -25.1 / -31.0 / -19.0%, cluster -13.5 / -18.6 / -23.2 / -6.7%, MIB -59.9 / -92.1 / -79.5 / -67.3%, boundary -69.4 / -77.1 / -72.6 / -66.5%. At NFE=1 the same order with larger moves (overlap -20 / -42 / -48 / -39%, cluster -22 / -28 / -32 / -17%, MIB -70 / -93 / -82 / -75%, boundary -70 / -77 / -73 / -67%). Each term moves its own target and only its own target by more than a few percent. Side effects at 0.01: the cluster term raises overlap +6% and fixed +49% while cutting the area gap -27%, the overlap term raises MIB +21% and the area gap +14% and moves the HPWL gap from -0.0021 to -0.0004, the boundary term cuts the area gap -64%, the

MIB term raises fixed +21%. With the weight, the overlap target keeps improving at a rising area gap (+14/ +19/ +30%), the cluster term's fixed cost shrinks from +49% to +26%, MIB is strongest at 0.05, and boundary saturates near 0.0009 while its side effects grow (overlap +48%, group +31%, fixed +167% at 0.1). The t -weighting changes the boundary term's character: target -66.5% with the side effects collapsed (fixed +5.6%, group +4.1%) and the area gap at about zero. The wirelength term moves the HPWL gap from 0.2% below the reference to 0.7% below at weight 0.1 (NFE=1: -0.015 to -0.032), paid in overlap (+3/ +5/ +8%) and fixed (+15 to +18% at ≥ 0.05). The area term is the one single term whose main side effect is a gain: compacting pushes blocks onto the outline, so the boundary distance falls 25 to 57%.

Table 27: Distribution metrics of the single-term arms, the five columns at NFE=32 and then at NFE=1; p is the permutation test against the plain control at the same NFE.

Arm	FLD8b	FLD8f	FPD	MMD8b	p	FLD8b	FLD8f	FPD	MMD8b	p
the plain control	0.1031	0.0033	0.0011	15.6	–	0.4325	0.0179	0.0036	32.6	–
overlap 0.01	0.0993	0.0078	0.0010	18.9	1.000	0.2238	0.0121	0.0020	28.4	0.015
overlap 0.05	0.0735	0.0026	0.0007	14.1	0.010	0.1229	0.0044	0.0008	19.3	0.005
overlap 0.1	0.0707	0.0032	0.0006	16.2	0.975	0.1221	0.0058	0.0007	21.9	0.005
overlap 0.05 t	0.0957	0.0034	0.0010	19.3	1.000	0.1548	0.0059	0.0015	26.6	0.005
cluster 0.01	0.1022	0.0038	0.0012	14.8	0.751	0.4322	0.0196	0.0039	32.0	0.935
cluster 0.05	0.0986	0.0044	0.0010	17.7	1.000	0.4413	0.0216	0.0037	34.5	1.000
cluster 0.1	0.0948	0.0032	0.0009	19.7	1.000	0.4621	0.0221	0.0037	35.9	1.000
cluster 0.05 t	0.1115	0.0046	0.0013	20.9	1.000	0.5117	0.0240	0.0045	35.6	1.000
MIB 0.01	0.1102	0.0051	0.0011	17.1	1.000	0.4399	0.0193	0.0035	35.2	0.940
MIB 0.05	0.1102	0.0041	0.0013	19.0	1.000	0.4315	0.0182	0.0038	31.9	0.990
MIB 0.1	0.1104	0.0034	0.0014	17.8	1.000	0.4397	0.0172	0.0042	32.6	0.891
MIB 0.05 t	0.1167	0.0040	0.0015	19.1	1.000	0.4472	0.0182	0.0040	35.0	0.980
boundary 0.01	0.0785	0.0043	0.0014	5.15	0.005	0.4227	0.0188	0.0040	22.3	0.005
boundary 0.05	0.1044	0.0112	0.0022	11.5	0.005	0.4435	0.0257	0.0052	30.3	0.831
boundary 0.1	0.1342	0.0107	0.0024	15.7	0.617	0.4443	0.0244	0.0050	39.8	1.000
boundary 0.05 t	0.0797	0.0058	0.0016	5.27	0.005	0.4132	0.0207	0.0040	23.5	0.005
area 0.01	0.0882	0.0040	0.0013	10.2	0.005	0.4097	0.0212	0.0038	25.6	0.005
area 0.05	0.0847	0.0062	0.0014	7.4	0.005	0.7222	0.0510	0.0061	41.7	1.000
area 0.05 t	0.0872	0.0054	0.0015	6.9	0.005	0.6399	0.0417	0.0063	39.7	0.995
area 0.1	0.1210	0.0100	0.0018	16.1	0.821	1.3757	0.1042	0.0111	69.1	1.000

The arms significantly closer to the reference than the plain control at NFE=32 are overlap 0.05, boundary 0.01, 0.05 and 0.05 t , and the area arms up to 0.05 (0.05 t included). Overlap keeps its NFE=1 gain at every weight (FLD8b 0.12 to 0.22 against 0.43), the cluster and MIB arms are within noise or farther at every weight, and boundary's distribution columns worsen with the weight. Across the ladder the distribution metrics put the closest weight one step below where the raw target metric is best (overlap 0.05, boundary 0.01). Every wirelength arm is farther from the reference than the plain control at both NFE ($p = 1.000$, FLD8b 0.117 to 0.128 at NFE=32).

H.5 ALL SIX TERMS

NFE=1 (control 0.03864 / 3.205 / 2.158 / 11.4 / 0.00619 / -0.0153 / 0.00932, soft cost 2.490): all six 0.01 gives 0.03194 / 0.932 / 1.809 / 2.65 / 0.00592 / -0.0128 / -0.00024 and 1.720; 0.05 gives 0.03400 / 0.741 / 1.734 / 0.662 / 0.00737 / -0.0145 / -0.00346 and 1.700; 0.1 gives 0.03630 / 0.774 / 1.872 / 0.483 / 0.01832 / -0.0127 / -0.00132 and 1.755; 0.05 t 1.801, 0.1 t 1.760, 0.2 t 1.824. At the common weight 0.01 every constraint metric improves at once with nothing worse except the HPWL gap moving toward 0, and the side effects of the single terms cancel. At 0.05 the constraint targets are stronger but overlap is back at the plain control and fixed is +16%; at 0.1 fixed is +177% and overlap +14%; the t -weightings sit between 0.01 and 0.05 (0.1 t) or repeat the 0.1 failure (0.2 t). The all-six arms are the closest to the reference distribution of the plain-backbone family (FLD8b 0.056 to 0.069 against 0.103, MMD8b 3 to 5 against 15.6), every arm significantly closer at both NFE, with the spread field FLD8f at the plain control's level for 0.01 and 0.05.

H.6 THE COMPOSED GRID

Three backbones on the adopted recipe, the plain backbone, the plain backbone with the spectral encoding, and the plain backbone with the spectral encoding and the information mover, each without

Table 28: All six terms at one common weight on the plain backbone: absolute at NFE=32 and the delta against the plain control. Normalized wirelength stays at 0.3011 to 0.3019 and compactness falls from 1.037 to 1.023 to 1.030.

Arm	Overlap	Boundary	Group	MIB	Fixed	HPWL gap	Area gap	Soft cost
the plain control	0.02602	3.227	2.651	8.75	5.82	-0.00214	0.01037	2.0915
all six 0.01	0.02341	0.948	2.424	2.86	5.52	-0.00151	0.00199	1.5565
all six 0.05	0.02627	0.759	2.348	0.667	6.72	-0.00320	-0.00014	1.5615
all six 0.1	0.02959	0.769	2.554	0.515	16.13	-0.00063	0.00272	1.6312
all six 0.05 t	0.02588	1.082	2.471	2.53	6.30	-0.00253	0.00070	1.6224
all six 0.1 t	0.02728	0.880	2.571	1.18	6.67	-0.00180	0.00032	1.6175
all six 0.2 t	0.03227	0.650	2.842	1.44	14.26	-0.00043	-0.00410	1.6698
delta 0.01	-10.0%	-70.6%	-8.6%	-67.3%	-5.2%	toward 0	-80.8%	-25.6%
delta 0.05	+0.9%	-76.5%	-11.4%	-92.4%	+15.5%	-49%	crosses 0	-25.3%
delta 0.1	+13.7%	-76.2%	-3.7%	-94.1%	+177%	+71%	-73.8%	-22.0%
delta 0.05 t	-0.5%	-66.5%	-6.8%	-71.1%	+8.2%	-18%	-93.2%	-22.4%
delta 0.1 t	+4.9%	-72.7%	-3.0%	-86.5%	+14.6%	+16%	-96.9%	-22.7%
delta 0.2 t	+24.0%	-79.9%	+7.2%	-83.6%	+145%	+80%	crosses 0	-20.2%

Table 29: Distribution metrics of the all-six arms, the five columns at NFE=32 and then at NFE=1.

Arm	FLD8b	FLD8f	FPD	MMD8b	p	FLD8b	FLD8f	FPD	MMD8b	p
the plain control	0.1031	0.0033	0.0011	15.6	-	0.4325	0.0179	0.0036	32.6	-
all six 0.01	0.0578	0.0037	0.0010	3.05	0.005	0.1947	0.0103	0.0022	9.98	0.005
all six 0.05	0.0564	0.0029	0.0012	3.08	0.005	0.1701	0.0097	0.0024	10.4	0.005
all six 0.1	0.0581	0.0052	0.0013	5.23	0.005	0.1530	0.0117	0.0023	11.4	0.005
all six 0.05 t	0.0693	0.0042	0.0012	4.03	0.005	0.2144	0.0112	0.0025	12.6	0.005
all six 0.1 t	0.0564	0.0044	0.0011	4.05	0.005	0.1764	0.0097	0.0022	10.7	0.005
all six 0.2 t	0.0621	0.0068	0.0012	5.49	0.005	0.1744	0.0134	0.0019	14.8	0.005

the auxiliary loss, with all six at 0.01 and with all six at 0.05, plus the last backbone at 0.1 t and 0.2 t . The plain backbone at $\lambda=0$ is the plain control, the last backbone at $\lambda=0$ is Trinity at $\lambda=0$, and Trinity is the last backbone with all six at 0.01.

Table 30: The composed grid at NFE=32: the constraint columns, the two gaps, the soft cost, the best-of-4 soft cost and the NFE=1 soft cost. Normalized wirelength is 0.3011 to 0.3028 on every row; compactness is 1.037 / 1.029 / 1.027 / 1.046 / 1.030 / 1.028 / 1.045 / 1.029 / 1.023 / 1.032 / 1.024 down the rows.

Arm	Overlap	Boundary	Group	MIB	Fixed	HPWL gap	Area gap	Soft cost	Best of 4	NFE=1
plain, $\lambda=0$ (the plain control)	0.02602	3.227	2.651	8.75	5.82	-0.00214	0.01037	2.0915	1.9074	2.4900
plain + all six 0.01	0.02341	0.948	2.424	2.86	5.52	-0.00151	0.00199	1.5565	1.4479	1.7198
plain + all six 0.05	0.02627	0.759	2.348	0.667	6.72	-0.00320	-0.00014	1.5615	1.4586	1.7001
spectral PE, $\lambda=0$	0.02433	3.310	2.942	10.5	7.21	+0.00116	0.01906	2.1305	1.9404	2.5024
spectral PE + all six 0.01	0.02343	1.029	2.554	3.52	7.18	-0.00062	0.00307	1.5912	1.4763	1.7489
spectral PE + all six 0.05	0.02556	0.652	2.405	0.712	11.19	-0.00177	0.00128	1.5373	1.4378	1.6649
PE + mover, $\lambda=0$ (Trinity at $\lambda=0$)	0.02220	2.997	2.827	6.66	7.47	+0.00219	0.01810	2.0151	1.8304	2.4271
PE + mover + all six 0.01 (Trinity)	0.02253	0.817	2.325	1.72	8.34	-0.00069	0.00224	1.5137	1.4092	1.6785
PE + mover + all six 0.05	0.02570	0.632	2.333	0.346	7.95	-0.00256	-0.00368	1.5192	1.4320	1.6341
PE + mover + all six 0.1 t	0.02456	0.842	2.585	1.39	10.27	+0.00002	0.00487	1.5784	1.4797	1.7064
PE + mover + all six 0.2 t	0.03156	0.847	2.667	0.599	11.02	-0.00175	-0.00231	1.6867	1.5807	1.8199

Overlap across NFE = 1 . . . 32: Trinity 0.0316 / 0.0306 / 0.0288 / 0.0271 / 0.0248 / 0.0225, the plain backbone with all six 0.01 0.0319 / 0.0312 / 0.0297 / 0.0279 / 0.0256 / 0.0234, Trinity at $\lambda=0$ 0.0357 / 0.0339 / 0.0308 / 0.0279 / 0.0250 / 0.0222, the plain control 0.0386 / 0.0368 / 0.0339 / 0.0313 / 0.0286 / 0.0260. The terms do the same work on every backbone (boundary -70 to -80%, MIB -70 to -90%, area gap to about 0, soft cost -25%), and the backbones differ in where they start: the mover starts 15% lower on overlap and keeps that lead through the ladder. With terms on, the spectral encoding alone is a near-null change on the soft metrics, and the mover is the component that moves the constraint metrics: at both weights the composed backbone leads the grid on overlap (at 0.01), boundary, group and MIB. On the distribution metrics the mover cuts FLD8b by a quarter to a third at both weights (0.042 / 0.037) and at 0.05 is best on every Fréchet column at both NFE; all nine grid arms with terms are significantly closer to the reference than the plain control. Trinity's

Table 31: Distribution metrics of the composed grid, the five columns at NFE=32 and then at NFE=1.

Arm	FLD8b	FLD8f	FPD	MMD8b	p	FLD8b	FLD8f	FPD	MMD8b	p
plain, $\lambda=0$ (the plain control)	0.1031	0.0033	0.0011	15.6	–	0.4325	0.0179	0.0036	32.6	–
plain + all six 0.01	0.0578	0.0037	0.0010	3.05	0.005	0.1947	0.0103	0.0022	9.98	0.005
plain + all six 0.05	0.0564	0.0029	0.0012	3.08	0.005	0.1701	0.0097	0.0024	10.4	0.005
spectral PE, $\lambda=0$	0.1358	0.0059	0.0015	28.4	1.000	0.4317	0.0186	0.0041	44.9	1.000
spectral PE + all six 0.01	0.0578	0.0036	0.0011	3.80	0.005	0.1854	0.0108	0.0025	12.7	0.005
spectral PE + all six 0.05	0.0581	0.0036	0.0013	4.56	0.005	0.1668	0.0099	0.0023	11.8	0.005
PE + mover, $\lambda=0$ (Trinity at $\lambda=0$)	0.1123	0.0048	0.0015	21.7	1.000	0.4264	0.0159	0.0042	35.1	0.980
PE + mover + all six 0.01 (Trinity)	0.0423	0.0075	0.0012	2.48	0.005	0.1624	0.0173	0.0025	9.63	0.005
PE + mover + all six 0.05	0.0366	0.0026	0.0007	3.44	0.005	0.1109	0.0085	0.0012	10.0	0.005
PE + mover + all six 0.1 t	0.0416	0.0025	0.0011	3.98	0.005	0.1218	0.0065	0.0019	9.41	0.005
PE + mover + all six 0.2 t	0.0487	0.0074	0.0011	6.27	0.005	0.1395	0.0125	0.0018	12.8	0.005

FLD8f of 0.0075 at 0.01 is a seed outlier (its other two seeds give 0.0036 and 0.0034, Appendix M). The composed backbone at 0.1 t sits between constant 0.01 and 0.05 on the constraint columns and 0.2 t repeats the constant-0.1 failure (overlap +21%, fixed +89%).

H.7 THE PRIOR ARTS AND THE REGRESSORS

Table 32: Every generator at NFE=32 and 1, the annealer and the regressors on their single layout: overlap ratio, cluster gap, the two gaps, the soft cost (the regressors’ as the per-case median) and the distribution metrics, p against the plain control at the same NFE. Normalized wirelength is 0.297 to 0.303 for every diffusion row at NFE=32; the boundary, MIB and fixed columns are in Table 33’s sources.

Arm	NFE	Overlap	Group	HPWL gap	Area gap	Soft cost	FLD8b	FLD8f	FPD	MMD8b	p
the plain control	32	0.02602	2.651	−0.00214	0.01037	2.0915	0.1031	0.0033	0.0011	15.6	–
Trinity	32	0.02253	2.325	−0.00069	0.00224	1.5137	0.0423	0.0075	0.0012	2.5	0.005
FlowPlace	32	0.04383	3.196	−0.00231	0.00871	2.4564	0.2274	0.0088	0.0013	24.4	1.00
ChipDiffusion	32	0.05113	3.581	−0.00076	0.01185	2.8020	0.2733	0.0098	0.0011	31.2	1.00
MacroDiff+	32	0.0639	4.33	+0.00236	0.02417	3.8458	0.624	0.0276	0.280	81.5	1.00
DiffPlace	32	0.1126	4.833	−0.00291	0.01229	6.2293	2.855	0.191	0.0146	247	1.00
the plain control	1	0.03864	2.158	−0.0153	0.0093	2.4900	0.4325	0.0179	0.0036	32.6	–
Trinity	1	0.03161	1.773	−0.01237	−0.00125	1.6785	0.1624	0.0173	0.0025	9.6	0.005
FlowPlace	1	0.1082	3.803	−0.0148	0.0643	11.465	3.771	0.182	0.0192	350	1.00
ChipDiffusion	1	0.0421	198	5.93	19.8	151.6	102.4	17.7	5.50	1,223	1.00
MacroDiff+	1	0.0444	194	5.66	19.5	150.2	102.3	17.5	5.72	1,216	1.00
DiffPlace	1	0.0420	198	5.84	19.9	149.8	102.5	17.8	5.36	1,230	1.00
sequence-pair SA	–	0.0000	59	1.54	1.11	12.341	–	–	–	–	–
Reg- z	–	0.4116	6.303	−0.0164	0.0134	median 21.5	42.06	2.78	0.614	457	1.00
Reg- $xywh$	–	0.5884	5.028	−0.0507	−0.145	median 99.5	66.56	5.55	1.418	587	1.00

Overlap across NFE = 1 . . . 32: FlowPlace 0.108 / 0.081 / 0.072 / 0.063 / 0.052 / 0.044, ChipDiffusion 0.042 / 0.196 / 0.114 / 0.059 / 0.054 / 0.051, MacroDiff+ 0.044 / 0.106 / 0.216 / 0.102 / 0.071 / 0.064, DiffPlace 0.042 / 0.106 / 0.251 / 0.146 / 0.116 / 0.113. FlowPlace at NFE=32 has $1.7\times$ the plain control’s overlap and $1.2\times$ the group gap with a lower boundary distance (−13%), MIB variance (−60%) and fixed deviation; ChipDiffusion $2.0\times$ the overlap and $1.35\times$ the group gap; MacroDiff+ is the weakest learned generator (overlap $2.5\times$, boundary $1.8\times$, wirelength above the reference, FLD8b 0.62); DiffPlace has the highest overlap of all learned models ($4.3\times$ the plain control) with boundary, wirelength and outline near the plain control’s. None is closer to the reference than the plain control ($p = 1.00$ everywhere), and Trinity is closer than all of them by 5 to $70\times$ on FLD8b. The regressors collapse blocks onto each other: Reg- z keeps the outline at the reference size with 41% of the block area claimed twice, Reg- $xywh$ is worse on every column (overlap 0.59, the outline 14.5% below the reference, fixed $24\times$), so the area-preserving latent alone is worth 30% of the regressor’s overlap.

H.8 EVERY TRAINED MODEL BY SOFT COST

Trinity is the lowest raw model at NFE=32 and the 3×2 backbone $\times$ term grid keeps its order (mover 0.01 < mover 0.05 < spectral 0.05 < plain 0.01 < plain 0.05). The overlap factor and the severity slots separate the term-trained models (1.51 to 1.63) from the recipes without the auxiliary loss (2.02 to 2.15) mainly through the soft slots, since overlap itself is 0.022 to 0.026 for all of them; the single-term overlap arms at 0.05 and 0.1 have the lowest overlap of the study (0.018 to 0.020) and

Table 33: Every model of the study on our 12,000 val set, sorted by the NFE=32 soft cost. Columns: soft cost / overlap at NFE=32, the best-of-4 soft cost, soft cost / overlap at NFE=1 (or on the single layout, the regressors' soft cost as the per-case median), and the wirelength / area gap at NFE=32 in percent. Unless stated, a model is on the adopted recipe (wire-dropout mixture); "plain base" means no wire dropout.

Setup	NFE=32	Best of 4	NFE=1	WL / Area (%)
Trinity: PE + mover + all six 0.01	1.5137 / 0.0225	1.4092	1.6785 / 0.0316	-0.07/+0.22
PE + mover + all six 0.05	1.5192 / 0.0257	1.4320	1.6341 / 0.0329	-0.26/-0.37
spectral PE + all six 0.05	1.5373 / 0.0256	1.4378	1.6649 / 0.0327	-0.18/+0.13
plain + all six 0.01	1.5565 / 0.0234	1.4479	1.7198 / 0.0319	-0.15/+0.20
plain + all six 0.05	1.5615 / 0.0263	1.4586	1.7001 / 0.0340	-0.32/-0.01
PE + mover + all six 0.1 <i>t</i>	1.5784 / 0.0246	1.4797	1.7064 / 0.0324	+0.00/+0.49
spectral PE + all six 0.01	1.5912 / 0.0234	1.4763	1.7489 / 0.0318	-0.06/+0.31
plain + all six 0.1 <i>t</i>	1.6175 / 0.0273	1.5094	1.7595 / 0.0350	-0.18/+0.03
plain + all six 0.05 <i>t</i>	1.6224 / 0.0259	1.5031	1.8007 / 0.0349	-0.25/+0.07
plain + boundary 0.01	1.6273 / 0.0247	1.5023	1.9471 / 0.0379	-0.11/+0.38
plain + all six 0.1	1.6312 / 0.0296	1.5305	1.7546 / 0.0363	-0.06/+0.27
plain + all six 0.2 <i>t</i>	1.6698 / 0.0323	1.5618	1.8238 / 0.0407	-0.04/-0.41
PE + mover + all six 0.2 <i>t</i>	1.6867 / 0.0316	1.5807	1.8199 / 0.0392	-0.17/-0.23
plain + boundary 0.05 <i>t</i>	1.7237 / 0.0295	1.5916	2.0439 / 0.0420	-0.25/+0.01
plain + boundary 0.05	1.7282 / 0.0309	1.6006	2.0425 / 0.0432	+0.12/+0.74
plain + area 0.05	1.8141 / 0.0295	1.6700	2.5639 / 0.0530	-0.19/-0.13
plain + area 0.05 <i>t</i>	1.8772 / 0.0280	1.7198	2.5955 / 0.0500	-0.21/+0.36
plain + area 0.1	1.8833 / 0.0358	1.7320	3.3476 / 0.0684	-0.44/-0.92
plain + overlap 0.1	1.8950 / 0.0180	1.7349	1.9991 / 0.0203	-0.06/+1.35
plain + boundary 0.1	1.9016 / 0.0385	1.7684	2.1868 / 0.0492	+0.09/+0.43
plain + overlap 0.05	1.9027 / 0.0195	1.7429	2.0049 / 0.0225	-0.11/+1.23
plain + area 0.01	1.9380 / 0.0265	1.7719	2.3380 / 0.0406	-0.20/+0.63
plain + overlap 0.05 <i>t</i>	1.9864 / 0.0211	1.8163	2.0836 / 0.0238	-0.09/+1.46
Trinity at $\lambda=0$: PE + mover	2.0151 / 0.0222	1.8304	2.4271 / 0.0357	+0.22/+1.81
plain + cluster 0.05	2.0345 / 0.0251	1.8642	2.4845 / 0.0388	-0.13/+1.06
plain + overlap 0.01	2.0479 / 0.0242	1.8758	2.2334 / 0.0309	-0.04/+1.18
plain base + mover, $\lambda=0$	2.0498 / 0.0239	1.8560	2.4313 / 0.0362	-0.04/+1.48
plain + cluster 0.1	2.0643 / 0.0255	1.8923	2.5674 / 0.0402	-0.08/+1.03
plain + cluster 0.05 <i>t</i>	2.0754 / 0.0256	1.8912	2.5664 / 0.0405	-0.12/+1.26
plain + MIB 0.05	2.0812 / 0.0260	1.8994	2.4724 / 0.0385	-0.07/+1.37
the plain control: plain, $\lambda=0$	2.0915 / 0.0260	1.9074	2.4900 / 0.0386	-0.21/+1.04
plain + MIB 0.01	2.0960 / 0.0270	1.9125	2.4701 / 0.0392	-0.15/+1.05
plain + cluster 0.01	2.1048 / 0.0276	1.9237	2.5151 / 0.0405	-0.28/+0.76
the base: plain base, $\lambda=0$	2.1064 / 0.0262	1.9197	2.4906 / 0.0383	-0.24/+1.05
plain, heavy wire-dropout mixture	2.1072 / 0.0262	1.9214	2.5229 / 0.0391	-0.07/+1.39
plain + wirelength 0.05 <i>t</i>	2.1072 / 0.0265	1.9147	2.7539 / 0.0449	-0.26/+1.20
plain + MIB 0.05 <i>t</i>	2.1140 / 0.0271	1.9221	2.5044 / 0.0396	-0.14/+1.24
plain + wirelength 0.01	2.1213 / 0.0269	1.9217	2.6143 / 0.0415	-0.20/+1.20
plain + wirelength 0.05	2.1297 / 0.0273	1.9440	2.8166 / 0.0466	-0.41/+1.14
spectral PE, $\lambda=0$	2.1305 / 0.0243	1.9404	2.5024 / 0.0363	+0.12/+1.91
plain, mild wire-dropout mixture	2.1321 / 0.0259	1.9375	2.5308 / 0.0384	-0.08/+1.50
plain + MIB 0.1	2.1405 / 0.0279	1.9479	2.5551 / 0.0409	-0.19/+1.11
plain base + 4 adjacency heads	2.1493 / 0.0279	1.9430	2.5585 / 0.0403	-0.27/+1.07
plain + wirelength 0.1	2.1499 / 0.0282	1.9586	3.1962 / 0.0532	-0.69/+0.98
plain base, ϵ head	2.3872 / 0.0365	2.0053	152.43 / 0.0417	-0.08/+1.49
FlowPlace	2.4564 / 0.0438	2.2110	11.465 / 0.1082	-0.23/+0.87
plain base, velocity head	2.5970 / 0.0373	2.2538	77.23 / 0.2505	-0.47/+1.23
ChipDiffusion	2.8020 / 0.0511	2.4824	151.57 / 0.0421	-0.08/+1.19
MacroDiff+	3.8458 / 0.0639	3.2835	150.20 / 0.0444	+0.24/+2.42
DiffPlace	6.2293 / 0.1126	5.1245	149.79 / 0.0420	-0.29/+1.23
Reg- <i>xywh</i>	-	-	99.5 / 0.5884	-5.1/-14.5
Reg- <i>z</i>	-	-	21.5 / 0.4116	-1.6/+1.3
sequence-pair SA	-	-	12.341 / 0.0000	+153.8/+111.0

land at 1.90.

I REFINEMENT RESULTS IN FULL

I.1 TRINITY WITH AND WITHOUT THE AUXILIARY LOSS

Table 34: The full NFE $\times$ steps grid, Trinity and Trinity at $\lambda=0$ (the same backbone without the auxiliary loss), two lines per cell: soft cost / overlap ratio, then wirelength gap / area gap to the reference in percent (positive above the reference).

Model	NFE	0 steps	10	25	50	100	200	400
Trinity	1	1.679/0.0316 -1.2/-0.1	1.517/0.0201 -1.0/+1.0	1.309/0.0152 -0.8/+1.1	1.208/0.0115 -0.6/+1.1	1.149/0.0083 -0.4/+1.2	1.104/0.0056 -0.3/+1.2	1.066/0.0034 -0.3/+1.2
	2	1.660/0.0305 -1.2/-0.0	1.480/0.0188 -0.9/+1.0	1.289/0.0141 -0.7/+1.1	1.194/0.0106 -0.6/+1.1	1.137/0.0076 -0.4/+1.2	1.096/0.0052 -0.4/+1.2	1.062/0.0031 -0.3/+1.1
	4	1.631/0.0288 -1.0/+0.0	1.460/0.0173 -0.7/+1.1	1.274/0.0128 -0.5/+1.2	1.182/0.0096 -0.4/+1.2	1.129/0.0068 -0.3/+1.2	1.090/0.0047 -0.2/+1.2	1.059/0.0029 -0.2/+1.0
	8	1.598/0.0271 -0.7/+0.1	1.435/0.0157 -0.4/+1.2	1.257/0.0116 -0.2/+1.2	1.171/0.0086 -0.1/+1.2	1.123/0.0062 -0.0/+1.2	1.088/0.0043 -0.0/+1.2	1.059/0.0028 -0.0/+1.0
	16	1.554/0.0248 -0.3/+0.2	1.401/0.0137 -0.1/+1.2	1.236/0.0099 +0.1/+1.3	1.159/0.0074 +0.1/+1.3	1.117/0.0054 +0.2/+1.3	1.086/0.0039 +0.2/+1.2	1.059/0.0026 +0.2/+1.0
	32	1.514/0.0225 -0.1/+0.2	1.369/0.0117 +0.1/+1.3	1.216/0.0084 +0.3/+1.4	1.147/0.0064 +0.4/+1.4	1.111/0.0048 +0.4/+1.4	1.083/0.0035 +0.4/+1.3	1.058/0.0023 +0.3/+1.1
Trinity, $\lambda=0$	1	2.427/0.0357 -1.1/+1.6	1.578/0.0229 -0.9/+1.6	1.355/0.0173 -0.7/+1.6	1.234/0.0127 -0.5/+1.6	1.155/0.0087 -0.4/+1.6	1.103/0.0057 -0.3/+1.5	1.065/0.0034 -0.3/+1.4
	2	2.364/0.0339 -1.1/+1.6	1.540/0.0212 -0.8/+1.6	1.330/0.0159 -0.7/+1.6	1.218/0.0116 -0.5/+1.6	1.146/0.0080 -0.3/+1.6	1.098/0.0053 -0.3/+1.5	1.063/0.0032 -0.3/+1.3
	4	2.253/0.0308 -0.8/+1.6	1.483/0.0184 -0.6/+1.6	1.293/0.0136 -0.4/+1.6	1.195/0.0100 -0.3/+1.6	1.132/0.0069 -0.2/+1.5	1.091/0.0047 -0.1/+1.4	1.060/0.0029 -0.2/+1.1
	8	2.164/0.0279 -0.4/+1.7	1.436/0.0159 -0.2/+1.7	1.263/0.0117 -0.1/+1.7	1.177/0.0085 +0.0/+1.6	1.123/0.0060 +0.1/+1.6	1.087/0.0041 +0.1/+1.4	1.059/0.0027 +0.0/+1.1
	16	2.083/0.0250 -0.1/+1.7	1.392/0.0134 +0.1/+1.7	1.235/0.0097 +0.2/+1.7	1.161/0.0071 +0.3/+1.7	1.116/0.0051 +0.3/+1.6	1.085/0.0037 +0.3/+1.4	1.059/0.0025 +0.2/+1.1
	32	2.015/0.0222 +0.2/+1.8	1.356/0.0110 +0.4/+1.8	1.212/0.0079 +0.5/+1.8	1.148/0.0059 +0.5/+1.8	1.109/0.0044 +0.5/+1.7	1.082/0.0032 +0.5/+1.5	1.058/0.0022 +0.4/+1.2

Steps to threshold, the smallest step count with soft cost at most τ , per NFE = 1/2/4/8/16/32: $\tau = 1.3$: Trinity 50 / 25 / 25 / 25 / 25 / 25, Trinity at $\lambda=0$ 50 / 50 / 25 / 25 / 25 / 25; $\tau = 1.2$: 100 / 50 / 50 / 50 / 50 / 50 against 100 / 100 / 50 / 50 / 50 / 50; $\tau = 1.15$: 100 / 100 / 100 / 100 / 100 / 50 against 200 / 100 / 100 / 100 / 100 / 50; $\tau = 1.1$: 400 / 200 / 200 / 200 / 200 / 200 on both. Every one of the 42 cells is Pareto-optimal on both models. At fixed steps the gain from NFE=1 to 32 is 0.16 raw, 0.09 at 25 steps, 0.04 at 100, 0.02 at 200 and 0.008 at 400; at fixed NFE each doubling of steps gains 0.04 to 0.10. Trinity's advantage over Trinity at $\lambda=0$ is the raw sample (1.51 against 2.02 at NFE=32, 1.68 against 2.43 at NFE=1) and the low-NFE cells through 50 to 100 steps; the raw samples differ in the soft slots and the outline (sev_{rel} 0.085 and area gap 0.002 against 0.221 and 0.018) at the same overlap, and ten refiner steps bring Trinity at $\lambda=0$ to Trinity's raw sev_{rel} .

Table 35: Every soft column along the descent on Trinity at the setting of Appendix E (Trinity at $\lambda=0$ is within 0.005 on every column from 25 steps on). Units as in Section 4.1.

NFE	Steps	Overlap	Boundary	Group	MIB	HPWL gap	Area gap	sev_{rel}	Soft cost
1	0	0.0316	0.8	1.8	1.7	-0.0124	-0.0013	0.0819	1.6785
1	10	0.0201	1.4	1.3	0.0080	-0.0096	0.0100	0.0911	1.5170
1	25	0.0152	0.7	1.1	5.7×10^{-4}	-0.0075	0.0106	0.0464	1.3090
1	50	0.0115	0.4	0.9	5.1×10^{-5}	-0.0058	0.0113	0.0279	1.2084
1	100	0.0083	0.3	0.8	1.2×10^{-5}	-0.0043	0.0122	0.0206	1.1490
1	400	0.0034	0.1	0.5	7.0×10^{-7}	-0.0029	0.0116	0.0100	1.0661
32	0	0.0225	0.8	2.3	1.7	-0.0007	0.0022	0.0849	1.5137
32	10	0.0117	1.2	1.8	0.010	0.0014	0.0129	0.0874	1.3695
32	25	0.0084	0.6	1.6	3.3×10^{-4}	0.0028	0.0135	0.0464	1.2159
32	50	0.0064	0.3	1.5	5.1×10^{-5}	0.0036	0.0137	0.0289	1.1473
32	100	0.0048	0.2	1.3	1.2×10^{-5}	0.0040	0.0137	0.0215	1.1114
32	200	0.0035	0.1	1.2	3.0×10^{-6}	0.0038	0.0128	0.0158	1.0833
32	400	0.0023	0.1	1.0	7.0×10^{-7}	0.0032	0.0106	0.0110	1.0583

Overlap, the cluster gap, the MIB variance and the fixed deviation fall monotonically through 400 steps on both models and overlap does not turn up; on Trinity the boundary distance and sev_{rel} rise at 10 steps (0.8 to 1.2 and 0.085 to 0.087 at NFE=32) and fall from there, and the remaining cost at 400 steps is wirelength and area at +0.3% and +1.1% of the reference and a sev_{rel} of 0.011. Along the NFE axis at 400 steps the columns trade: overlap and the boundary distance fall with NFE while the cluster gap grows (0.5 to 1.0).

I.2 EVERY MODEL ON THE REDUCED GRID

Table 36: The reduced grid for every model, one column per NFE / refiner steps, two lines per model: soft cost / overlap ratio with the rule (the mean soft cost over the nine refined cells; the regressors' raw soft cost is the per-case median, their means overflow), then wirelength gap / area gap to the reference in percent (positive above the reference).

Model	32 / 0	32 / 25	32 / 100	32 / 400	1 / 0	1 / 400	Rule
Trinity	1.514/0.0225 −0.1/+0.2	1.216/0.0084 +0.3/+1.4	1.111/0.0048 +0.4/+1.4	1.058/0.0023 +0.3/+1.1	1.679/0.0316 −1.2/−0.1	1.066/0.0034 −0.3/+1.2	−
PE + mover, $\lambda=0$	2.015/0.0222 +0.2/+1.8	1.212/0.0079 +0.5/+1.8	1.109/0.0044 +0.5/+1.7	1.058/0.0022 +0.4/+1.2	2.427/0.0357 −1.1/+1.6	1.065/0.0034 −0.3/+1.4	−
PE + mover + all six 0.05	1.519/0.0257 −0.3/−0.4	1.232/0.0101 +0.1/+1.0	1.125/0.0060 +0.3/+1.3	1.066/0.0028 +0.4/+1.3	1.634/0.0329 −1.5/−0.9	1.077/0.0038 −0.4/+1.2	1.1587
PE + mover + all six 0.1 t	1.578/0.0246 +0.0/+0.5	1.244/0.0098 +0.4/+1.7	1.128/0.0058 +0.6/+1.8	1.069/0.0027 +0.5/+1.6	1.706/0.0324 −1.4/−0.2	1.082/0.0039 −0.3/+1.4	1.1669
PE + mover + all six 0.2 t	1.687/0.0316 −0.2/−0.2	1.307/0.0136 +0.3/+1.3	1.158/0.0079 +0.5/+1.7	1.083/0.0034 +0.6/+1.8	1.820/0.0392 −1.7/−0.9	1.097/0.0047 −0.4/+1.6	1.2015
plain + all six 0.01	1.556/0.0234 −0.1/+0.2	1.217/0.0091 +0.2/+1.2	1.115/0.0053 +0.3/+1.3	1.062/0.0026 +0.3/+1.1	1.720/0.0319 −1.3/−0.0	1.066/0.0034 −0.3/+1.2	1.1504
plain + all six 0.05	1.562/0.0263 −0.3/−0.0	1.248/0.0110 +0.1/+1.2	1.132/0.0064 +0.3/+1.4	1.069/0.0030 +0.3/+1.3	1.700/0.0340 −1.5/−0.4	1.079/0.0040 −0.4/+1.2	1.1703
spectral PE + all six 0.05	1.537/0.0256 −0.2/+0.1	1.264/0.0109 +0.2/+1.4	1.137/0.0064 +0.4/+1.6	1.072/0.0029 +0.4/+1.4	1.665/0.0327 −1.3/−0.2	1.085/0.0040 −0.3/+1.4	1.1783
the plain control	2.091/0.0260 −0.2/+1.0	1.214/0.0092 +0.1/+1.1	1.114/0.0053 +0.3/+1.2	1.061/0.0026 +0.3/+1.1	2.490/0.0386 −1.5/+0.9	1.068/0.0037 −0.4/+1.2	1.1580
the base (no wire dropout)	2.106/0.0262 −0.2/+1.1	1.219/0.0094 +0.1/+1.1	1.115/0.0053 +0.3/+1.2	1.061/0.0026 +0.2/+1.0	2.491/0.0383 −1.5/+0.9	1.068/0.0037 −0.4/+1.2	1.1590
FlowPlace	2.456/0.0438 −0.2/+0.9	1.415/0.0221 +0.2/+1.3	1.222/0.0128 +0.6/+1.9	1.107/0.0050 +0.9/+2.5	11.5/0.1082 −1.5/+6.4	1.134/0.0066 +0.4/+3.3	1.5003
ChipDiffusion	2.802/0.0511 −0.1/+1.2	1.516/0.0272 +0.4/+1.5	1.271/0.0158 +0.8/+2.2	1.131/0.0062 +1.2/+3.0	151.6/0.0421 +593.1/+1982.8	72.6/0.0039 +499.2/+1614.3	32.15
DiffPlace	6.229/0.1126 −0.3/+1.2	2.606/0.0683 −0.0/+1.6	1.570/0.0330 +0.6/+2.5	1.202/0.0111 +1.4/+3.7	149.8/0.0420 +583.8/+1986.3	71.4/0.0039 +487.4/+1617.2	32.31
MacroDiff+	3.846/0.0639 +0.2/+2.4	1.714/0.0351 +0.7/+2.1	1.348/0.0197 +1.3/+2.9	1.167/0.0078 +1.8/+3.7	150.2/0.0444 +565.9/+1946.8	69.4/0.0041 +472.0/+1578.1	31.56
SP-SA (one shard)	−	−	−	−	12.3/0.0000 +153.8/+111.0	10.9/0.0392 +126.9/+64.2	12.61
Reg-z (one layout)	−	−	−	−	21.5/0.4116 −1.6/+1.3	42.5/0.0500 +4.5/+1.9	−
Reg-xywh (one layout)	−	−	−	−	99.5/0.5884 −5.1/−14.5	35.214/0.0800 +5.0/−2.2	−

Across the models of this work the refined endpoints are within 0.01 of each other (1.058 to 1.072 at NFE=32 and 400 steps, 1.066 to 1.097 at NFE=1), and the plain backbone with all six terms at 0.01 has the lowest reduced-grid rule. Through the legalizer at 400 steps with the overlap weight at 30, Trinity at $\lambda=0$ reaches a first-draw / best-of-4 hard cost of 1.192 / 1.107 at NFE=1 and 1.206 / 1.076 at NFE=32, against 1.193 / 1.111 and 1.214 / 1.080 for Trinity on the same 12,000 cases; every paired difference is at most 0.008 and 2.5 paired standard errors, below the seed std of the raw soft cost (0.015 to 0.037), so at this budget the training term leaves no end-to-end difference beyond the seed spread. This reproduces the effect the stage-by-stage evaluation is built to expose: the full pipeline absorbs the weaker raw samples of an early component, so the endpoint alone cannot tell the two generators apart, while the raw and short-budget stages do (Tables 4 and 5). The published-method generators refine much more slowly on the same refiner (1.107, 1.131, 1.167 and 1.202 at NFE=32 and 400 steps against 1.058), start far worse, and DiffPlace keeps an overlap of 0.011 after 400 steps: the generator's quality survives 400 refiner steps. The annealer's layouts, legal and overlap-free at the start, move under the wirelength and area pull (overlap 0 to 0.039) while their soft cost falls from 12.3 to 10.9. The regressors are out of the refiner's reach (overlap 0.41 to 0.59 raw and 0.05 to 0.08 after 400 steps).

Table 37: Per-case median / 90th percentile of the soft cost along the descent, for the lines whose means are dominated by a few cases.

Model	NFE	0 steps	25	100	400
Trinity	1	1.492 / 2.329	1.224 / 1.647	1.102 / 1.331	1.038 / 1.162
Trinity	32	1.423 / 1.876	1.174 / 1.421	1.079 / 1.244	1.033 / 1.144
Trinity, $\lambda=0$	1	2.014 / 3.704	1.203 / 1.817	1.091 / 1.365	1.034 / 1.163
Trinity, $\lambda=0$	32	1.888 / 2.611	1.161 / 1.426	1.074 / 1.245	1.032 / 1.146
FlowPlace	1	7.340 / 16.53	2.122 / 4.766	1.235 / 1.907	1.083 / 1.297
FlowPlace	32	2.246 / 3.352	1.319 / 1.809	1.163 / 1.463	1.072 / 1.238
ChipDiffusion	1	152.7 / 182.5	117.0 / 143.3	93.8 / 114.0	73.6 / 90.8
ChipDiffusion	32	2.578 / 3.864	1.418 / 1.961	1.214 / 1.526	1.096 / 1.270
DiffPlace	1	151.3 / 180.3	116.5 / 142.1	93.0 / 112.8	72.5 / 89.7
DiffPlace	32	5.038 / 11.31	2.203 / 4.340	1.437 / 2.165	1.162 / 1.402
MacroDiff+	1	151.4 / 180.7	115.2 / 140.4	90.9 / 110.3	70.1 / 86.6
MacroDiff+	32	3.487 / 5.465	1.576 / 2.297	1.278 / 1.644	1.127 / 1.326
sequence-pair SA	–	12.55 / 14.91	13.93 / 17.24	13.27 / 16.14	10.97 / 13.53
Reg-z	–	21.53 / 24,599	5.618 / 1,754	2.253 / 55.1	1.367 / 3.966

J THE PORTED PLACERS WITH THEIR OWN IN-SAMPLER GUIDANCE

Three of the four ported placers also correct the sample inside their samplers, and the generator comparison of Section 4.2 leaves those corrections out so that every network meets the same Euler sampler. ChipDiffusion, DiffPlace and MacroDiff+ are sampled with the guidance their released code applies at every step, ported onto our sampler as Table 38 describes, on the 12,000 val set at $\text{NFE} \in \{1, 2, 4, 8, 16, 32\}$ with four draws from the noise of their free shards, so that every guided draw pairs with a free one. FlowPlace’s in-sampler step is a projection onto the hard constraints that its own evaluation configuration disables, and it is not reproduced. The guided samples are scored on the fifteen soft columns, refined by the closed-form refiner on the reduced grid of Appendix I.2, passed through the three ported loops at $\text{NFE}=32$, and measured against the reference distribution as in Appendix C. The legalizer is not run on them.

DiffPlace’s released update raises overlap. Its overlap loss is the positive pairwise overlap area and its sampler subtracts the loss gradient from the predicted noise, which moves the implied clean sample up that gradient. The port runs the released sign as the reproduction and a reference arm with the sign flipped, whose per-block normalization still pushes every overlapping block by the same $0.03 \lambda_t$ whatever its overlap.

Table 38: What each released sampler does to the sample at every step, and how it is ported onto our Euler sampler. Every port moves positions only, keeps the pre-placed blocks fixed, works on the post-hoc ports’ canvas (the predicted layout’s bounding box plus 5%), and guides the final prediction as well.

Placer	Inside its released sampler	The port
ChipDiffusion	Every step, ten Adam iterations at learning rate 8×10^{-3} on the predicted clean sample of $\alpha \cdot \text{legality} + 10^{-4} \cdot \text{HPWL}$, with α adapted per sample from 0 while $t < 0.5$, and the diffusion step continues from the guided prediction.	The same loop on the post-hoc port’s legality and wirelength functions, the next state the Euler step plus the scaled correction.
DiffPlace	From $1 - t \geq 0.85$ on, the predicted noise is moved by $\lambda_t \nabla \text{overlap}(x_t)$ with $\lambda_t = 200(1 - t)^2$, the gradient rescaled per block to 0.03 and clipped at 0.08. The released update moves the sample up the overlap gradient.	The same on the port’s overlap term, the step continuing from the guided noise. A reference arm flips the sign of the update.
MacroDiff+	Every DDIM step, an Adam loop on the predicted clean sample with HPWL and overlap phases, clipping and a die clamp, 300 to 700 iterations per design in its table and 500 by default.	500 iterations at learning rate 0.01 each step, the post-hoc port’s settings, the step continuing from the guided prediction.
FlowPlace	A projection onto the hard constraints inside the sampler, disabled in its evaluation configuration.	Not reproduced.

J.1 RAW SAMPLES

Figure 16 and Table 39 give the raw samples. Each guidance does what its code targets and pays in the terms it does not. At $\text{NFE}=32$ ChipDiffusion’s guidance cuts overlap from 0.051 to 0.018 and MacroDiff+’s from 0.064 to 0.0008, while DiffPlace’s released update raises it from 0.113 to 0.328. On the same samples the area gap grows nine to thirteen times, to 0.13 to 0.22 of the reference area, the wirelength gap goes from within 0.3% of the reference to 3 to 13% above it, the cluster gap grows

1.8 to 2.5 times on all three, and the boundary distance grows five to fourteen times on ChipDiffusion and DiffPlace, because the corrections separate blocks without a term that holds clusters together or the outline closed. Net on the soft cost, the guidance helps where the raw draw is poor and hurts where it is good. ChipDiffusion’s soft cost halves at NFE = 1 to 4 (151.6 to 88.3 at NFE=1, 11.9 to 5.96 at 4) and rises from NFE=8 on (3.83 to 3.97, and 2.80 to 3.78 at 32), so its guided NFE=32 sample stands about where its free NFE=8 sample already does. MacroDiff+ gains at every NFE, 3.85 to 2.04 at 32, its 500 Adam iterations per step leaving an overlap of 0.0008. DiffPlace’s released update loses everywhere, 6.23 to 132 at NFE=32, and the flipped sign is below free sampling at NFE = 1 to 4 but far above it from NFE=8 on (40.1 against 6.23 at 32), because the normalized push scatters a nearly finished layout. No guided sample reaches Trinity’s free sample at 1.514, nor the 192 / 12 rung at 1.827.




Figure 16: The raw samples against NFE, free sampling solid, the placer’s own guidance dashed, DiffPlace’s update with the sign flipped dotted: the soft cost, the overlap ratio, the boundary distance, the cluster gap, the area gap and sev_{rel} , log axes.

J.2 THROUGH THE REFINERS

Tables 40 and 41 and Figure 17 continue both sample sets through the closed-form refiner and through the three ported loops. The closed-form refiner is nearly indifferent to the start. At NFE=32 with 400 steps it brings ChipDiffusion’s guided samples to 1.152 against 1.131 from the free ones and MacroDiff+’s to 1.218 against 1.167, and only DiffPlace’s damaged guided samples end higher, 1.869 against 1.202, with 5.62 against 1.23 at NFE=8. At NFE=1 the guided start is the better one on ChipDiffusion and MacroDiff+ (59.9 and 32.3 against 72.6 and 69.4), the low-NFE gain of the raw samples carried through. The ported loops do worse from the guided samples than from the free ones on all three placers. The complete published methods, guided sampling through the own loop, end at 3.58, 5.37 and 2.69 for ChipDiffusion, DiffPlace and MacroDiff+ against 2.05, 3.91 and 1.66 from free sampling, and MacroDiff+ loses its raw-sample gain here because its loop keeps the spread its guidance introduced, an area gap of 0.34 against 0.13 from the free start. The same guided samples through our refiner end at 1.15, 1.87 and 1.22.




Figure 17: The soft cost along the closed-form refiner from the free (solid) and the guided (dashed) samples of each placer at NFE = 1, 8 and 32.

Table 39: The raw samples of the three placers at every NFE, free (our Euler sampler) and guided (their own in-sampler correction), and DiffPlace’s update with its sign flipped: the soft columns and the soft cost, means over four draws and the 12,000 cases. Boundary, cluster and fixed in 10^{-3} , MIB in 10^{-6} , the gaps as fractions of the reference.

Placer	Sampling	NFE	Overlap	Boundary	Cluster	MIB	Fixed	HPWL gap	Area gap	sev _{rel}	Soft cost
ChipDiffusion	free	1	0.0421	2,218	198	347,608	1,304	+5.931	+19.8	0.976	151.6
		2	0.1961	316	38.3	13,364	216	+0.841	+1.870	0.840	97.81
		4	0.1138	29.4	6.77	275	26.3	+0.053	+0.186	0.585	11.91
		8	0.0595	5.59	3.86	38.1	4.40	+0.003	+0.034	0.327	3.829
		16	0.0543	3.70	3.61	19.6	2.50	−0.002	+0.016	0.254	3.057
		32	0.0511	3.30	3.58	16.0	2.20	−0.001	+0.012	0.236	2.802
	guided	1	0.0035	2,135	174	347,506	1,304	+4.905	+17.0	0.979	88.29
		2	0.0711	289	34.0	13,320	216	+0.655	+1.398	0.844	23.49
		4	0.0407	30.5	7.62	275	26.3	+0.053	+0.241	0.604	5.956
		8	0.0231	16.6	6.07	39.1	4.63	+0.025	+0.152	0.519	3.974
		16	0.0211	15.2	6.15	20.6	2.77	+0.027	+0.146	0.508	3.794
		32	0.0182	15.5	6.56	17.6	2.66	+0.033	+0.158	0.519	3.782
DiffPlace	free	1	0.0420	2,067	198	358,943	1,243	+5.838	+19.9	0.973	149.8
		2	0.1062	900	100	95,322	588	+2.659	+6.806	0.935	113.5
		4	0.2510	157	20.5	4,838	131	+0.367	+0.881	0.752	99.49
		8	0.1457	14.7	6.37	175	16.3	+0.024	+0.092	0.502	14.56
		16	0.1162	4.52	4.96	45.9	3.75	−0.001	+0.023	0.299	7.159
		32	0.1126	3.43	4.83	31.3	2.34	−0.003	+0.012	0.255	6.229
	guided	1	0.0463	2,067	198	358,942	1,243	+5.837	+19.9	0.974	158.0
		2	0.1704	900	101	95,322	588	+2.655	+6.795	0.934	229.7
		4	0.3275	157	20.8	4,838	131	+0.363	+0.865	0.750	228.1
		8	0.3419	310	32.6	258	23.2	+0.848	+1.732	0.765	418.3
		16	0.3637	136	18.5	67.1	6.89	+0.382	+0.561	0.673	300.3
		32	0.3279	48.2	10.5	39.6	3.79	+0.125	+0.129	0.563	131.8
	sign flipped	1	0.0200	2,068	199	358,943	1,243	+5.851	+19.9	0.976	120.6
		2	0.0557	902	102	95,322	588	+2.678	+6.833	0.943	67.95
		4	0.1961	159	20.9	4,838	131	+0.380	+0.906	0.762	57.90
		8	0.1713	317	34.9	266	23.9	+0.909	+1.983	0.785	69.73
		16	0.2093	150	21.5	70.6	7.47	+0.452	+0.806	0.707	60.83
		32	0.2046	64.9	13.1	42.4	4.36	+0.192	+0.333	0.632	40.14
MacroDiff+	free	1	0.0444	2,040	194	359,381	1,234	+5.659	+19.5	0.972	150.2
		2	0.1058	885	97.8	96,614	589	+2.561	+6.699	0.933	110.2
		4	0.2162	168	20.9	5,624	141	+0.368	+0.997	0.756	71.66
		8	0.1021	23.1	6.24	321	24.6	+0.029	+0.140	0.552	9.887
		16	0.0708	7.40	4.53	79.1	7.92	+0.003	+0.039	0.367	4.697
		32	0.0639	5.73	4.33	47.5	5.73	+0.002	+0.024	0.320	3.846
	guided	1	0.0014	1,388	143	359,385	1,234	+3.711	+9.499	0.972	54.05
		2	0.0003	689	95.4	96,701	589	+2.312	+4.954	0.951	31.21
		4	0.0004	136	37.6	5,679	142	+0.694	+1.417	0.821	10.76
		8	0.0004	11.7	16.6	326	25.4	+0.199	+0.415	0.433	3.196
		16	0.0006	5.05	11.9	74.9	8.54	+0.123	+0.247	0.298	2.201
		32	0.0008	4.23	10.9	42.2	6.28	+0.108	+0.216	0.271	2.042

Table 40: The closed-form refiner on the free and the guided samples of each placer, the reduced grid of Appendix I.2: soft cost / overlap ratio per cell of NFE and refiner steps.

Placer	Sampling	NFE	0 steps	25	100	400
ChipDiffusion	free	1	151.6/0.0421	115.9/0.0287	92.74/0.0111	72.63/0.0039
		8	3.829/0.0595	1.662/0.0307	1.299/0.0162	1.137/0.0061
		32	2.802/0.0511	1.516/0.0272	1.271/0.0158	1.131/0.0062
	guided	1	88.29/0.0035	79.26/0.0069	72.99/0.0041	59.94/0.0038
		8	3.974/0.0231	1.940/0.0138	1.305/0.0071	1.151/0.0028
		32	3.782/0.0182	1.828/0.0107	1.291/0.0057	1.152/0.0025
DiffPlace	free	1	149.8/0.0420	115.1/0.0292	91.73/0.0113	71.39/0.0039
		8	14.56/0.1457	4.181/0.0868	1.728/0.0347	1.231/0.0101
		32	6.229/0.1126	2.606/0.0683	1.570/0.0330	1.202/0.0111
	guided	1	158.0/0.0463	123.6/0.0360	95.91/0.0161	71.85/0.0048
		8	418.3/0.3419	128.3/0.2471	23.68/0.1075	5.619/0.0269
		32	131.8/0.3279	30.09/0.2290	5.552/0.1129	1.869/0.0373
MacroDiff+	free	1	150.2/0.0444	114.2/0.0308	90.00/0.0119	69.44/0.0041
		8	9.887/0.1021	3.427/0.0537	1.537/0.0211	1.211/0.0071
		32	3.846/0.0639	1.714/0.0351	1.348/0.0197	1.167/0.0078
	guided	1	54.05/0.0014	46.93/0.0064	42.59/0.0035	32.26/0.0040
		8	3.196/0.0004	2.290/0.0025	1.605/0.0014	1.360/0.0013
		32	2.042/0.0008	1.589/0.0007	1.322/0.0010	1.218/0.0012

Table 41: Each placer’s NFE=32 samples, free and guided, after the closed-form refiner (400 steps) and after the three ported loops at their released iteration counts (ChipDiffusion 5,000 in its scheduled variant, DiffPlace and MacroDiff+ 500); the raw rows are the NFE=32 rows of Table 39, whose units apply. A dagger marks guided sampling through the method’s own loop, its complete published method.

Placer	Sampling	Refiner	Overlap	Boundary	Cluster	MIB	Fixed	HPWL gap	Area gap	sev _{rel}	Soft cost
ChipDiffusion	free	ours, 400 steps	0.0062	0.192	1.13	0.0000	0.0001	+0.012	+0.030	0.017	1.131
		ChipDiffusion loop	0.0069	4.56	6.68	15.7	2.19	+0.053	+0.117	0.273	2.048
		DiffPlace loop	0.0008	29.1	6.10	15.7	2.19	+0.058	+0.246	0.563	3.614
		MacroDiff+ loop	0.0032	2.21	6.80	15.7	2.19	+0.061	+0.116	0.174	1.602
	guided	ours, 400 steps	0.0025	0.699	1.11	0.0000	0.0001	+0.024	+0.089	0.029	1.152
		ChipDiffusion loop [†]	0.0022	15.5	11.5	17.2	2.66	+0.099	+0.273	0.533	3.582
		DiffPlace loop	0.0007	28.0	7.57	17.2	2.66	+0.069	+0.272	0.580	3.803
		MacroDiff+ loop	0.0006	7.21	12.2	17.2	2.66	+0.126	+0.276	0.319	2.334
DiffPlace	free	ours, 400 steps	0.0111	0.256	1.03	0.0059	0.0001	+0.014	+0.037	0.019	1.202
		ChipDiffusion loop	0.0124	5.48	7.10	31.6	2.35	+0.058	+0.119	0.294	2.286
		DiffPlace loop	0.0024	36.1	6.99	31.6	2.35	+0.067	+0.299	0.580	3.914
		MacroDiff+ loop	0.0044	2.57	7.14	31.6	2.35	+0.069	+0.116	0.175	1.633
	guided	ours, 400 steps	0.0373	4.58	1.99	0.014	0.0001	+0.131	+0.066	0.066	1.869
		ChipDiffusion loop	0.0155	33.1	13.3	39.7	3.77	+0.236	+0.245	0.496	4.048
		DiffPlace loop [†]	0.0053	73.7	13.1	39.7	3.77	+0.239	+0.479	0.654	5.369
		MacroDiff+ loop	0.0035	23.7	14.7	39.7	3.77	+0.277	+0.245	0.350	2.702
MacroDiff+	free	ours, 400 steps	0.0078	0.508	1.36	1.21	0.0001	+0.018	+0.037	0.021	1.167
		ChipDiffusion loop	0.0075	5.61	7.61	129	5.71	+0.063	+0.132	0.293	2.180
		DiffPlace loop	0.0010	31.5	6.99	129	5.71	+0.068	+0.269	0.574	3.755
		MacroDiff+ loop	0.0031	2.53	7.75	129	5.71	+0.072	+0.127	0.186	1.661
	guided	ours, 400 steps	0.0012	1.44	1.49	0.036	0.0001	+0.060	+0.162	0.039	1.218
		ChipDiffusion loop	0.0001	12.7	15.5	104	6.25	+0.147	+0.334	0.552	3.801
		DiffPlace loop	0.0001	8.05	11.2	104	6.25	+0.110	+0.239	0.381	2.592
		MacroDiff+ loop [†]	0.0004	8.67	15.0	104	6.25	+0.163	+0.340	0.369	2.694

Table 42: The distribution metrics of Appendix C for the free and the guided samples at NFE=1 and 32: the Fréchet distances on the density descriptors and on positions, the MMD in 10^{-3} , and the permutation p that the run is closer to the reference than the plain control.

Placer	Sampling	NFE	FLD8b	FLD8f	FLD12b	FLD12f	FPD	MMD8b	p
ChipDiffusion	free	1	102	17.67	234	48.12	5.501	1,223	1.00
		32	0.2733	0.009784	1.361	0.06643	0.001091	31.2	1.00
	guided	1	101	15.71	230	43.13	7.418	1,171	1.00
		32	3.1	0.2972	8.633	1.071	0.00531	512	1.00
DiffPlace	free	1	102	17.78	234	48.36	5.361	1,230	1.00
		32	2.855	0.1911	10.73	1.139	0.01458	247	1.00
	guided	1	102	17.87	234	48.65	5.364	1,231	1.00
		32	19.72	1.613	64.18	7.93	0.1404	594	1.00
MacroDiff+	free	1	102	17.51	234	47.81	5.724	1,216	1.00
		32	0.624	0.02763	2.679	0.1678	0.2799	81.5	1.00
	guided	1	92.14	15.52	210	43.44	3.102	1,077	1.00
		32	4.361	1.157	11.3	3.63	0.02319	615	1.00

J.3 DISTANCE TO THE REFERENCE

Table 42 measures the guided samples against the reference distribution. At NFE=32 every guidance moves its placer away from it, FLD8b by seven to eleven times (ChipDiffusion 0.273 to 3.10, DiffPlace 2.86 to 19.7, MacroDiff+ 0.624 to 4.36) and MMD8b by two to sixteen times, and no guided run is closer to the reference than the plain control ($p = 1.00$). At NFE=1 the guided and the free samples sit at the same distance (FLD8b 92 to 102), where the one-step draw dominates whatever the guidance adds.

The three corrections move the sample along the terms they model, overlap and wirelength, and away from the reference layouts on every term they do not, which is the pattern the ported loops show on the reference layouts in Appendix G. Measured at the stage where the guidance acts, the trade is visible in the columns of Table 39. After the legalizer, which removes the overlap on every arm, the same trade would appear as a few percent of area and wirelength with no column to name it.

K HARD-COST RESULTS IN FULL

K.1 TRINITY'S GRID

Table 43: Trinity through the legalizer on the NFE $\times$ steps grid (selected cells; every cell is in the supplementary data): the soft cost of the refined layout, the hard cost of the first legalized draw of every case as mean / median / 90th percentile, its hard-cost total, its wirelength / area gap in percent, the best of four legalized draws as mean / median / 90th percentile and total, the mean of the soft pick of four, and the legalizer's time per draw. Every cell is feasible on all draws.

NFE	Steps	Soft cost	First draw	Total	WL / area	Best of 4	Total	Soft pick	ms / draw
1	0	1.6785	1.4903/1.2875/2.362	1.7111	+15.5/+17.8	1.3763/1.2394/1.787	1.5513	1.4841	358
1	10	1.5170	1.3375/1.1177/2.148	1.5836	+15.1/+17.3	1.2296/1.0747/1.516	1.4183	1.3309	351
1	25	1.3090	1.3239/1.1123/2.071	1.5612	+14.2/+16.6	1.2171/1.0698/1.485	1.3976	1.3166	348
1	50	1.2084	1.3088/1.1046/1.975	1.5470	+13.6/+15.8	1.2071/1.0651/1.450	1.3968	1.3038	342
1	100	1.1490	1.2932/1.0965/1.865	1.5226	+12.6/+14.7	1.1903/1.0595/1.413	1.3557	1.2847	330
1	200	1.1042	1.2624/1.0838/1.632	1.4648	+10.9/+12.9	1.1623/1.0498/1.335	1.3024	1.2527	314
1	400	1.0661	1.2222/1.0682/1.486	1.3827	+8.7/+10.5	1.1298/1.0394/1.267	1.2337	1.2081	290
2	0	1.6603	1.4928/1.2869/2.403	1.7236	+15.2/+17.6	1.3294/1.2184/1.652	1.4820	1.4748	344
2	400	1.0617	1.2095/1.0645/1.453	1.3535	+8.1/+9.9	1.0978/1.0281/1.221	1.1775	1.1918	275
4	0	1.6306	1.4945/1.2888/2.384	1.7198	+15.4/+17.7	1.3104/1.2133/1.620	1.4510	1.4723	342
4	400	1.0593	1.2153/1.0652/1.477	1.3701	+8.3/+9.9	1.0879/1.0177/1.204	1.1597	1.1832	272
8	0	1.5976	1.5097/1.2968/2.433	1.7359	+15.9/+18.0	1.3080/1.2133/1.605	1.4523	1.4785	340
8	100	1.1232	1.2961/1.0981/1.865	1.4925	+12.4/+14.2	1.1313/1.0413/1.301	1.2479	1.2575	308
8	400	1.0593	1.2249/1.0685/1.514	1.3658	+8.6/+10.1	1.0861/1.0173/1.205	1.1473	1.1826	267
16	400	1.0593	1.2286/1.0714/1.522	1.3669	+9.0/+10.4	1.0878/1.0181/1.207	1.1534	1.1847	269
32	0	1.5137	1.5125/1.3019/2.451	1.7319	+16.4/+18.0	1.3057/1.2135/1.601	1.4489	1.4836	341
32	10	1.3695	1.3561/1.1318/2.219	1.5948	+15.8/+17.5	1.1697/1.0544/1.383	1.3309	1.3191	337
32	25	1.2159	1.3453/1.1230/2.163	1.5667	+15.2/+16.9	1.1596/1.0517/1.364	1.3126	1.3090	331
32	50	1.1473	1.3321/1.1162/2.091	1.5476	+14.3/+16.0	1.1475/1.0492/1.339	1.2860	1.2913	323
32	100	1.1114	1.3093/1.1046/1.951	1.5055	+13.2/+14.8	1.1353/1.0441/1.316	1.2550	1.2672	311
32	200	1.0833	1.2785/1.0914/1.766	1.4558	+11.5/+13.0	1.1136/1.0370/1.269	1.2040	1.2327	294
32	400	1.0583	1.2341/1.0734/1.551	1.3773	+9.2/+10.5	1.0887/1.0197/1.207	1.1580	1.1853	270

Hard-cost Pareto sets over (NFE, steps), a cell kept when no cell with fewer sampler steps and fewer refiner steps is cheaper: for the first-draw mean the NFE=1 column, NFE=2 at 10 to 400 steps (1.210 at 400) and (4, 200); for the best-of-4 mean the whole NFE = 1, 2, 4, 8 columns, NFE=16 at 0 / 10 / 25 / 100 and (32, 0); for the best-of-4 total the NFE = 1, 2, 4 columns, NFE=8 at 25 / 50 / 100 / 400 (1.147 at 400, the grid's minimum) and NFE=16 at 0 to 200. The refiner pays after legalization in every column at every NFE (first draw 1.49 to 1.51 $\rightarrow$ 1.21 to 1.23, best of 4 1.31 to 1.38 $\rightarrow$ 1.09 to 1.13, V_{rel} 0.10 $\rightarrow$ 0.04, area gap +0.18 $\rightarrow$ +0.10 from raw to 400 steps), the legalizer gets faster on refined input (340 to 358 $\rightarrow$ 267 to 290 ms per draw), and the largest single move is raw $\rightarrow$ 10 steps. Along the NFE axis at 400 steps the soft cost is monotone (1.066 $\rightarrow$ 1.058) while the first-draw cost has its minimum at NFE=2 and the best of 4 at NFE=8. The soft pick of four lands at 1.18 to 1.21 at 400 steps, between the first draw and the best of 4: choosing by the soft cost recovers a third of the best-of-4 gain without legalizing the other three draws.

Table 44: Per cell: the share of draws that ended on each rung of the legalizer's ladder, the expansion factor λ , the rank correlation of λ with the area gap and the cost, and the gaps after legalization.

NFE	Steps	Hard LP	Penalties	Flips	Last rungs	λ p50	λ p90	$\rho(\lambda, \text{area gap})$	$\rho(\lambda, \text{cost})$	Area gap	HPWL gap	V_{rel}
1	0	0.114	0.443	0.325	0.117	2.54	8.21	0.33	0.19	+0.178	+0.155	0.104
1	400	0.248	0.491	0.189	0.073	1.39	3.65	0.46	0.42	+0.105	+0.088	0.041
8	0	0.113	0.467	0.302	0.118	2.40	8.24	0.37	0.22	+0.180	+0.159	0.107
8	400	0.252	0.514	0.168	0.066	1.35	3.48	0.50	0.46	+0.101	+0.086	0.043
32	0	0.108	0.470	0.303	0.120	2.17	6.54	0.33	0.20	+0.180	+0.164	0.109
32	400	0.245	0.518	0.170	0.068	1.32	2.80	0.49	0.48	+0.105	+0.092	0.045

K.2 EVERY LINE ON THE SAME PIPELINE

FlowPlace at NFE = 1/2 and 400 steps: first draw 1.261 / 1.266, best of 4 1.134 / 1.126 (Trinity 1.222 / 1.210 and 1.130 / 1.098). The order on the same pipeline at NFE=8 and 400 steps, first draw / best of 4: Trinity 1.225 / 1.086, FlowPlace 1.275 / 1.118, ChipDiffusion 1.309 / 1.130, MacroDiff+ 1.342 / 1.150, DiffPlace 1.343 / 1.152, Reg-z 1.55, Reg-*xywh* 1.74, the annealer 13.8 / 10.4. The two linear- β lines are within 0.02 of each other cell by cell at NFE = 8 to 32, and on them NFE = 16 and 32 add nothing over 8. FlowPlace shows Trinity's NFE inversion, larger: at 400 steps the first-draw cost rises with NFE (1.261 $\rightarrow$ 1.296) and its NFE=1 column dominates every refined cell

Table 45: The prior arts and Trinity on the same pipeline at 400 refiner steps, per NFE (the ϵ -head models produce no layout at NFE = 1 and 2, where their legalized costs are 9 to 33). Columns: the soft cost, the first draw’s mean and median cost, the best-of-4 mean and hard-cost total, V_{rel} and the area gap after legalization, the median expansion factor λ , the share of draws the legalizer’s hard packing program solved directly (LP), and the per-draw soft–hard Spearman ρ .

Line	NFE	Soft	First	Median	Best 4	Total	V_{rel}	Area	λ	LP	ρ	HPWL
FlowPlace	4	1.116	1.270	1.091	1.119	1.214	0.047	+0.13	1.53	0.202	0.41	+0.12
FlowPlace	8	1.114	1.275	1.096	1.118	1.215	0.048	+0.14	1.53	0.194	0.42	+0.12
FlowPlace	16	1.109	1.287	1.101	1.121	1.215	0.050	+0.14	1.51	0.190	0.45	+0.12
FlowPlace	32	1.107	1.296	1.106	1.124	1.228	0.051	+0.15	1.48	0.186	0.46	+0.13
ChipDiffusion	4	1.226	1.325	1.154	1.143	1.232	0.054	+0.17	1.66	0.162	0.62	+0.15
ChipDiffusion	8	1.137	1.309	1.118	1.130	1.234	0.053	+0.16	1.54	0.174	0.48	+0.14
ChipDiffusion	16	1.132	1.316	1.119	1.134	1.238	0.053	+0.16	1.55	0.169	0.46	+0.14
ChipDiffusion	32	1.131	1.322	1.122	1.137	1.253	0.054	+0.16	1.55	0.166	0.47	+0.14
DiffPlace	4	2.68	2.044	1.874	1.624	1.843	0.150	+0.48	3.30	0.013	0.51	+0.45
DiffPlace	8	1.231	1.343	1.145	1.152	1.262	0.056	+0.18	1.90	0.156	0.55	+0.15
DiffPlace	16	1.199	1.351	1.134	1.155	1.280	0.056	+0.18	1.81	0.157	0.48	+0.16
DiffPlace	32	1.202	1.355	1.142	1.158	1.281	0.057	+0.18	1.83	0.151	0.47	+0.16
MacroDiff+	4	2.62	1.976	1.813	1.570	1.737	0.143	+0.45	2.97	0.015	0.49	+0.42
MacroDiff+	8	1.211	1.342	1.156	1.150	1.248	0.058	+0.18	1.68	0.153	0.58	+0.15
MacroDiff+	16	1.172	1.349	1.143	1.154	1.274	0.058	+0.18	1.67	0.149	0.50	+0.16
MacroDiff+	32	1.167	1.352	1.147	1.159	1.286	0.059	+0.18	1.65	0.144	0.50	+0.16
Trinity	4	1.059	1.215	1.065	1.088	1.160	0.041	+0.10	1.35	0.255	0.55	+0.08
Trinity	8	1.059	1.225	1.069	1.086	1.147	0.043	+0.10	1.35	0.252	0.58	+0.09
Trinity	16	1.059	1.229	1.071	1.088	1.153	0.044	+0.10	1.33	0.247	0.59	+0.09
Trinity	32	1.058	1.234	1.073	1.089	1.158	0.045	+0.10	1.32	0.245	0.60	+0.09

of NFE = 8 to 32. After legalization the prior arts keep more residual soft violations, a larger area gap, need more expansion and reach the hard program on 14 to 21% of draws against 25%.

Table 46: The single-shard lines (the sequence-pair annealer and the two regressors) across refiner steps: the soft cost (median / p90 where the mean overflows), the first draw’s mean, median and 90th-percentile hard cost (the single layout for the regressors), the best-of-4 mean, the share of draws solved by the hard LP and by the last rungs, the median expansion factor λ , and the area gap, V_{rel} and HPWL gap after legalization.

Line	Steps	Soft	First	Median	p90	Best 4	LP	Last	λ	Area	V_{rel}	HPWL
SP-SA	0	12.341	19.019	18.266	28.18	14.382	0.000	0.170	1.51	+3.28	0.755	+2.88
SP-SA	100	13.094	17.195	16.510	25.43	12.984	0.000	0.164	1.94	+3.10	0.721	+2.76
SP-SA	400	10.891	13.809	13.294	20.13	10.427	0.000	0.150	2.76	+2.61	0.660	+2.50
Reg-z	0	21.53 / 24,599	2.306	1.910	3.932	–	0.034	0.137	10.0 (cap)	+0.61	0.162	+0.52
Reg-z	100	2.25 / 55.1	1.766	1.442	3.018	–	0.065	0.137	8.50	+0.40	0.095	+0.37
Reg-z	400	1.37 / 3.97	1.552	1.278	2.587	–	0.096	0.125	4.56	+0.27	0.078	+0.28
Reg-xywh	0	99.5 / 239,235	2.623	2.067	4.355	–	0.023	0.145	10.0 (cap)	+0.71	0.185	+0.60
Reg-xywh	100	4.57 / 174	2.013	1.560	3.351	–	0.040	0.155	10.0	+0.49	0.115	+0.46
Reg-xywh	400	1.76 / 6.40	1.736	1.371	2.929	–	0.065	0.143	5.74	+0.34	0.095	+0.36

The legalizer takes 379 to 393 ms per draw on the annealer’s layouts and 329 to 375 ms on the regressors’. The annealer’s layouts are overlap-free but far from the cases’ reference (wirelength and area gaps 1.5 and 1.1) and do not hold the preplaced blocks; the anchor step restores those blocks, the expansion prices the overlaps this creates, the ladder never reaches the hard program, and the refiner moves the soft cost up before down (12.34 $\rightarrow$ 14.04 at 10 steps, 10.89 at 400) while the hard cost falls monotonically (19.0 $\rightarrow$ 13.8). The regressors sit at the expansion cap on every raw draw; the refiner moves both costs monotonically and the soft cost by orders of magnitude at the tail (Reg-z cases above 100: 37% $\rightarrow$ 0.1%), and Reg-xywh is worse than Reg-z at every step count on every column.

K.3 THE SOFT–HARD CORRELATION

ρ over draws at 400 steps by NFE = 1/2/4/8/16/32 is 0.495 / 0.519 / 0.553 / 0.580 / 0.595 / 0.603, and at NFE=32 by steps 0/10/25/50/100/200/400 is 0.267 / 0.551 / 0.547 / 0.558 / 0.572 / 0.584 / 0.603. Across the 42 cell means: Spearman 0.938, Kendall 0.754; pooled over the 2,016,000 draws: Spearman 0.472, Kendall 0.326. With the overlap ratio alone in place of the soft cost: across cells 0.904, pooled 0.437, per cell 0.22 to 0.28 raw and 0.33 to 0.53 refined.

Within a cell the relation is a ranking: Trinity’s per-draw Spearman reaches 0.60 at 400 steps while the linear R^2 is 0.05 to 0.10 (log-log 0.08 to 0.15), because the legalized cost has a heavy tail (p90 1.5 against a median 1.07) that no linear fit on a compact soft cost captures. Within-cell ranges from

Table 47: Trinity, one column per NFE / refiner steps: the rank correlation of the soft cost with the legalized cost over the 48,000 draws (ρ , τ) and over the 12,000 per-case means, then the Spearman of every soft column with the legalized cost.

Quantity	1 / 0	1 / 10	1 / 400	8 / 0	8 / 400	32 / 0	32 / 10	32 / 100	32 / 400
ρ over draws	0.198	0.491	0.495	0.261	0.580	0.267	0.551	0.572	0.603
τ over draws	0.134	0.338	0.345	0.177	0.412	0.180	0.382	0.401	0.430
ρ over case means	0.203	0.505	0.502	0.261	0.583	0.271	0.583	0.581	0.610
overlap ratio	0.223	0.365	0.418	0.278	0.506	0.272	0.450	0.460	0.531
sev_{rel}	0.058	0.482	0.507	0.102	0.556	0.112	0.496	0.558	0.572
boundary distance	0.034	0.381	0.410	0.043	0.396	0.044	0.339	0.421	0.388
sev_{bnd}	0.138	0.391	0.427	0.136	0.402	0.137	0.356	0.448	0.394
area gap	0.074	0.297	0.257	0.096	0.328	0.100	0.303	0.260	0.317
compactness	0.173	0.338	0.289	0.189	0.347	0.197	0.348	0.297	0.339
sev_{grp}	0.158	0.237	0.092	0.209	0.178	0.220	0.308	0.242	0.220
group gap	0.113	0.171	0.012	0.161	0.101	0.175	0.243	0.182	0.145
HPWL gap	-0.116	-0.112	0.005	-0.105	0.077	-0.019	0.021	0.089	0.157
normalized wirelength	-0.128	-0.217	-0.190	-0.121	-0.173	-0.099	-0.178	-0.163	-0.151
fixed deviation	0.228	0.059	0.055	0.222	0.051	0.226	0.055	0.055	0.046
MIB variance	0.099	-0.029	-0.026	0.098	-0.023	0.090	-0.035	-0.035	-0.024

Table 48: Every line: Spearman ρ , Kendall τ , Pearson r and R^2 , log-log r and R^2 of soft against hard cost, across the cell means (first six columns: 42 cells per diffusion line, 7 per single-shard line, 231 for all eight lines, 175 for the five lines with finite means) and pooled over every draw (last six: 2,016,000 per diffusion line, 336,000 for the annealer, 84,000 per regressor, 10,584,000 and 8,400,000 for the two unions); n/a where the regressors’ overflowing means make a linear fit meaningless.

Line	ρ	τ	r	R^2	r_{log}	R^2_{log}	ρ	τ	r	R^2	r_{log}	R^2_{log}
Trinity	0.938	0.754	0.899	0.808	0.899	0.809	0.472	0.326	0.238	0.057	0.311	0.097
FlowPlace	0.923	0.738	0.747	0.558	0.846	0.716	0.369	0.252	0.065	0.004	0.237	0.056
ChipDiffusion	0.989	0.919	0.925	0.855	0.935	0.875	0.805	0.619	0.843	0.711	0.901	0.811
DiffPlace	0.975	0.898	0.892	0.796	0.906	0.822	0.858	0.665	0.796	0.633	0.873	0.763
MacroDiff+	0.985	0.919	0.923	0.853	0.925	0.856	0.861	0.671	0.830	0.688	0.890	0.793
SP-SA	0.643	0.619	0.795	0.633	0.822	0.676	0.484	0.335	0.459	0.210	0.538	0.290
Reg-z	1.000	1.000	n/a	n/a	n/a	n/a	0.608	0.442	0.031	0.001	0.554	0.307
Reg-xywh	1.000	1.000	n/a	n/a	n/a	n/a	0.579	0.417	0.083	0.007	0.589	0.347
all eight lines	0.947	0.807	n/a	n/a	n/a	n/a	0.768	0.578	n/a	n/a	0.827	0.684
five finite lines	0.962	0.836	0.856	0.732	0.901	0.812	0.760	0.570	0.774	0.598	0.865	0.748

the raw to the 400-step cells: Trinity Spearman 0.20–0.27 $\rightarrow$ 0.50–0.60, FlowPlace 0.21–0.27 $\rightarrow$ 0.38–0.46, ChipDiffusion 0.24–0.34 $\rightarrow$ 0.21–0.62, DiffPlace 0.27–0.40 $\rightarrow$ 0.39–0.55, MacroDiff+ 0.25–0.35 $\rightarrow$ 0.36–0.58, the annealer 0.46 $\rightarrow$ 0.56. The soft column that carries the correlation is sev_{rel} (0.48 to 0.57 in the refined cells), then the overlap ratio (0.33 to 0.53, rising with NFE and steps), the boundary distance (0.34 to 0.48) and the area columns; group gap, HPWL gap, fixed and MIB are at or near zero after refinement, and normalized wirelength is negative (−0.15 to −0.28: longer wires, cheaper legalized layout). In the raw cells the fixed deviation (0.22) is among the top columns: the raw layouts’ hard cost is set by their preplaced-block and overlap defects, the refined layouts’ by their residual soft slots. The soft cost hardly predicts the legalizer’s milliseconds per draw (ρ −0.08 to 0.35) but does predict the ladder rung reached (0.28 to 0.40 at 400 steps), and the milliseconds correlate with the final cost (0.33 raw, 0.39 to 0.51 refined).

K.4 THE PRIOR ARTS’ LOOPS IN HARD COST

The three ported loops remove overlap (λ p50 2.17 $\rightarrow$ 1.46 to 1.53) and lower the legalized cost by a similar amount while leaving the soft slots untouched (V_{rel} 0.109 $\rightarrow$ 0.106 to 0.108) and raising the soft cost (1.51 $\rightarrow$ 1.56, 1.79 and 3.03). The closed-form refiner at 10 steps is already below all three on every hard column and at 400 steps by 0.21 to 0.22 on the first draw. After the MacroDiff+ and ChipDiffusion loops the per-draw soft-hard correlation drops to 0.16 to 0.17, and after the DiffPlace loop it is 0.35, carried by the area columns that loop inflates.

Table 50 completes the grid with every loop on every prior art’s own samples, and Figure 58 draws the same cells against the refiner budget. The refiner axis dominates: exchanging a ported loop for

Table 49: The prior-art loops at their published iteration counts (MacroDiff+ 500, ChipDiffusion 5,000 in its scheduled variant, DiffPlace 500) and the closed-form refiner (ours) on Trinity’s NFE=32 samples, then the legalizer (the raw row reproduces the grid’s (32, 0) cell): the soft cost, the first draw’s mean, median and p90 hard cost, the best-of-4 mean and median, the share of draws solved by the hard LP and by the last rungs, the median expansion factor λ , the area gap and V_{rel} after legalization, the per-draw soft-hard Spearman ρ and the milliseconds per draw, and the HPWL gap.

Refiner	Soft	First	Median	p90	Best 4	Med. 4	LP	Last	λ	Area	V_{rel}	ρ / ms	HPWL
none (raw)	1.514	1.5125	1.302	2.451	1.3057	1.214	0.108	0.120	2.17	+0.180	0.109	0.267 / 341	+0.164
MacroDiff+ loop	1.564	1.4424	1.284	2.007	1.2588	1.200	0.107	0.078	1.48	+0.139	0.106	0.164 / 271	+0.121
ChipDiffusion loop	1.793	1.4563	1.284	2.075	1.2699	1.205	0.118	0.085	1.46	+0.150	0.106	0.171 / 278	+0.130
DiffPlace loop	3.035	1.4415	1.286	1.957	1.2581	1.200	0.090	0.073	1.53	+0.137	0.108	0.351 / 258	+0.114
ours, 10 steps	1.370	1.3561	1.132	2.219	1.1697	1.054	0.136	0.118	1.93	+0.175	0.058	0.551 / 337	+0.158
ours, 100 steps	1.111	1.3093	1.105	1.951	1.1353	1.044	0.170	0.098	1.54	+0.148	0.054	0.572 / 311	+0.132
ours, 400 steps	1.058	1.2341	1.073	1.551	1.0887	1.020	0.245	0.068	1.32	+0.105	0.045	0.603 / 270	+0.092

Table 50: Generator $\times$ refiner at NFE=32, then the legalizer, two lines per generator: the hard cost of the first draw / best of four, then the first draw’s wirelength gap / area gap to the reference in percent. Every prior-art loop runs at its published iteration count on every generator’s own samples, the closed-form refiner for 400 steps; every draw of the 13 loop rows is feasible, the raw cell of every row reproduces its grid’s (32, 0) cell, and a dagger marks a method’s published generator and loop pair. Every loop moves the outline and the wires it did not model; the closed-form refiner leaves the smallest gaps on every generator.

Generator	Raw sample	ChipDiffusion loop	DiffPlace loop	MacroDiff+ loop	Closed-form refiner
Trinity	1.513 / 1.306	1.456 / 1.270	1.442 / 1.258	1.442 / 1.259	1.234 / 1.089
	+16.2 / +18.0	+13.0 / +14.9	+11.4 / +13.7	+12.1 / +13.9	+9.3 / +10.5
FlowPlace	1.567 / 1.343	1.495 / 1.284	1.454 / 1.265	1.471 / 1.267	1.296 / 1.124
	+18.5 / +21.6	+14.5 / +16.9	+11.2 / +14.7	+13.1 / +15.2	+12.8 / +14.6
ChipDiffusion	1.609 / 1.364	1.521 / 1.300 [†]	1.483 / 1.280	1.492 / 1.285	1.322 / 1.137
	+20.1 / +23.7	+15.5 / +18.2	+12.2 / +16.1	+13.7 / +16.3	+14.3 / +16.2
DiffPlace	1.731 / 1.447	1.587 / 1.334	1.537 / 1.313 [†]	1.539 / 1.304	1.355 / 1.158
	+24.7 / +30.9	+18.7 / +21.0	+13.9 / +19.1	+15.7 / +18.1	+16.1 / +18.3
MacroDiff+	1.672 / 1.406	1.571 / 1.326	1.536 / 1.310	1.546 / 1.308 [†]	1.352 / 1.159
	+22.4 / +26.5	+17.5 / +20.1	+14.1 / +18.4	+15.9 / +18.3	+15.6 / +17.7

the closed-form refiner moves the first-draw cost by 0.16 to 0.23 on every generator, and exchanging a prior-art generator for Trinity moves it by 0.06 to 0.12 under the closed-form refiner and by 0.01 to 0.13 under the ported loops, so the loops erase most of the generator difference after legalization as they do on the soft side (Appendix E.4). Trinity is the best row of every column and the closed-form refiner the best column of every row. A prior-art generator with the closed-form refiner (1.296 to 1.355 for the first draw, 1.124 to 1.158 for the best of four) beats the same generator with its best ported loop (1.454 to 1.537 and 1.265 to 1.308) by 0.16 to 0.18 and 0.14 to 0.15, and the closed-form refiner is past that point by 25 steps on every generator (1.395 to 1.513 against 1.454 to 1.537). After legalization the three loops rank the reverse of their soft order. The DiffPlace loop, the worst in soft cost (3.5 to 3.9), separates blocks hardest (λ p50 1.32 to 1.47 on the prior arts) and the packing program recovers the area it spends, so it is the best of the three on every generator’s first draw, and the ChipDiffusion loop, which leaves the most overlap, is the worst. A method’s own generator and loop pair is not the best cell of its row, except DiffPlace by 0.002. The loops act on overlap only: after legalization V_{rel} stays at 0.111 to 0.122 on every prior-art and loop cell (raw 0.115 to 0.130) against 0.051 to 0.059 after the closed-form refiner, the hard-LP share at 0.05 to 0.09 against 0.14 to 0.19, and the per-draw soft-hard correlation at 0.22 to 0.30 against 0.46 to 0.50.

K.5 BEST OF N

Each doubling of N removes 31 to 39% of the excess over 1 at NFE = 8 and 32, the median reaches 1.007 at $N = 8$ and 1.002 at $N = 16$, the p90 falls from 1.55 to 1.12, and the mean is under 1.1 from $N = 4$. Raw samples also gain from N (1.508 $\rightarrow$ 1.214 at $N = 16$) but the refiner is the larger lever: $N = 2$ refined (1.141) beats $N = 16$ raw. The NFE=8 ladder is the NFE=32 ladder within 0.002 at every N . At NFE=1 the ladder starts at the same $N = 1$ but gains less from N (22 to 25% of the excess per doubling) and ends at 1.084: the one-step draws of a case are more alike, and $N = 16$ at NFE=1 equals $N = 4$ at NFE=8. The $N = 1$ and $N = 4$ points reproduce the four-draw grid’s cells within 0.002 on a fresh-noise cache, and the per-draw soft-hard Spearman at 400 steps is 0.603

Table 51: Best of N on the 12,000 cases from Trinity’s 16-draw caches (fresh noise), every draw refined 400 steps and legalized: the cheapest of the first N legalized draws per case (mean, median, 90th percentile, hard-cost total), and the soft pick (the legalized cost of the lowest-soft-cost draw among N , mean / median). Every one of the 768,000 legalized draws is feasible.

NFE	Steps	N	Mean	Median	p90	Total	Soft pick (mean / median)	HPWL / Area (best of N)
32	0	1	1.5079	1.3003	2.427	1.7300	–	–
32	0	4	1.3014	1.2098	1.595	1.4423	1.4758 / 1.2775	–
32	0	16	1.2140	1.1696	1.459	1.2857	1.4548 / 1.2629	–
32	400	1	1.2331	1.0736	1.552	1.3857	–	+9.3 / +10.5
32	400	2	1.1412	1.0435	1.313	1.2452	1.2079 / 1.0597	+4.9 / +6.1
32	400	4	1.0885	1.0203	1.208	1.1622	1.1870 / 1.0500	+2.6 / +3.6
32	400	8	1.0585	1.0066	1.151	1.1070	1.1742 / 1.0437	+1.4 / +2.2
32	400	16	1.0406	1.0024	1.116	1.0765	1.1600 / 1.0406	+0.6 / +1.3
8	400	1	1.2245	1.0689	1.523	1.3743	–	+8.8 / +10.3
8	400	2	1.1393	1.0408	1.298	1.2486	1.2036 / 1.0563	+4.8 / +6.2
8	400	4	1.0875	1.0164	1.206	1.1612	1.1806 / 1.0474	+2.4 / +3.7
8	400	8	1.0596	1.0054	1.151	1.1107	1.1639 / 1.0427	+1.3 / +2.3
8	400	16	1.0424	1.0021	1.118	1.0775	1.1546 / 1.0397	+0.6 / +1.5
1	400	1	1.2223	1.0678	1.491	1.3848	–	+8.7 / +10.5
1	400	2	1.1663	1.0488	1.346	1.2908	1.2144 / 1.0641	+6.1 / +7.8
1	400	4	1.1285	1.0392	1.269	1.2303	1.2108 / 1.0621	+4.4 / +5.9
1	400	8	1.1011	1.0290	1.225	1.1794	1.2072 / 1.0586	+3.1 / +4.6
1	400	16	1.0839	1.0153	1.195	1.1499	1.2064 / 1.0571	+2.3 / +3.8

/ 0.578 / 0.492 for NFE = 32/8/1.

K.6 THE FLOORSET VAL SET IN FULL

Best of N keeps, per case, the feasible draw with the lowest hard cost of the official evaluator, which reads the reference wirelength and area of the instance; a reference-free selection rule is not evaluated here. Table 52 lists all twelve settings run on the val set, and Table 7 shows five of them, picked after the runs to span cost and time; the sampler, refiner and legalizer settings were fixed on our 12,000-case split before any val-set run (Appendices E and F).

Table 52: The FloorSet val set per sample on an idle machine: the $e^{n/12}$ -weighted hard-cost total, the mean and median cost, and the wall time per case (mean, median, max).

NFE	Steps	N	Total	Mean	Median	Mean s / case	Median s / case	Max s / case	HPWL gap	Area gap
8	400	48	1.0213	1.0144	1.0000	1.63	1.34	5.10	−0.004	+0.000
32	400	48	1.0223	1.0147	1.0000	1.86	1.59	5.61	−0.003	−0.001
8	400	16	1.0290	1.0193	1.0009	1.14	0.98	2.27	−0.002	+0.004
8	400	8	1.0469	1.0284	1.0035	1.04	0.88	2.21	−0.002	+0.008
8	400	4	1.1316	1.0896	1.0081	1.01	0.87	2.22	+0.032	+0.032
4	400	16	1.0351	1.0243	1.0007	1.08	0.99	2.34	−0.002	+0.007
1	400	16	1.0564	1.0447	1.0081	1.02	0.93	2.22	+0.001	+0.014
8	100	16	1.0670	1.0417	1.0054	0.70	0.52	1.93	+0.002	+0.015
4	100	16	1.0574	1.0425	1.0059	0.63	0.51	1.88	+0.003	+0.017
1	100	16	1.1528	1.1063	1.0194	0.55	0.41	1.78	+0.030	+0.046
8	50	16	1.0882	1.0512	1.0082	0.59	0.44	1.85	+0.004	+0.022
1	50	16	1.1793	1.1146	1.0380	0.48	0.36	1.72	+0.027	+0.055

At $N = 48$, NFE=8 and 400 steps the gaps are HPWL −0.0045 and area +0.0003 with $V_{\text{rel}} = 0.0048$ (one cluster count and 23 boundary counts on 17 cases); at NFE=32: −0.0027 / −0.0009 / 0.0053. The compile warm-up of the refiner (about 4.5 minutes) and the pool warm-up run once and are outside the times. N is the strongest lever at fixed NFE and steps (1.132 → 1.047 → 1.029 → 1.021 on the total for $N = 4/8/16/48$ at NFE=8 and 400 steps, for 1.0 to 1.6 seconds per case), NFE trades against steps (NFE=4 × 100 at 1.057 equals NFE=1 × 400 at 1.056 on the total, NFE=8 × 50 at 1.088 between), and the rows with $N \geq 8$ reproduce an earlier run of the same settings to four decimals while the $N = 4$ row moves by 0.06 on the total, a single case’s outcome on 100 cases.

L CLASSICAL FLOORPLANNERS

The full pipeline of Trinity meets the classical floorplanners on two protocols: the FloorSet val set under the contest cost, and the soft-block benchmarks on which the prior work reports its numbers. The pipeline is always the same: Trinity samples at NFE=8, the closed-form refiner runs 400 steps, the legalizer closes every draw on 16 CPU workers and the cheapest feasible draw is kept. Every

Table 53: The same settings: mean seconds per case by stage (legalization is the wall time over the N parallel draws on 16 workers), the legalizer’s milliseconds per draw and the solver’s share of it.

NFE	Steps	N	Sample s	Refine s	Legalize s	Legalizer ms / draw	Solver ms / draw
8	400	48	0.10	0.61	0.91	240	87
32	400	48	0.32	0.61	0.93	244	88
8	400	16	0.07	0.62	0.45	258	92
8	400	8	0.07	0.61	0.35	240	87
8	400	4	0.06	0.62	0.33	249	89
4	400	16	0.04	0.62	0.42	264	94
1	400	16	0.02	0.62	0.38	252	89
8	100	16	0.06	0.16	0.48	281	97
4	100	16	0.04	0.16	0.43	275	95
1	100	16	0.02	0.16	0.37	284	97
8	50	16	0.06	0.08	0.45	289	98
1	50	16	0.02	0.08	0.38	291	99

Table 54: The FloorSet val set (100 cases), every line to its final legalized layout: seconds per case of wall time (for an annealer, one worker’s run), the CPU core-seconds per case (for Trinity, the legalizer’s, plus the GPU seconds of sampling and refinement), the mean and median hard cost, and the legalized layout’s wirelength and area gaps to the reference in percent. PARSAC workers are independent runs from random trees, one CPU core each. [†]Astra’s reported runtime on its own CPU.

Line	Draws or workers	s / case	Core-s / case	Mean	Median	WL	Area
Trinity, NFE=8, 400 steps	48 draws	1.62	12 + 0.72 GPU	1.014	1.000	−0.4	+0.0
Trinity, NFE=8, 400 steps	16 draws	1.14	4 + 0.69 GPU	1.019	1.001	−0.2	+0.4
Trinity, NFE=4, 100 steps	16 draws	0.63	4 + 0.20 GPU	1.042	1.006	+0.2	+1.8
Trinity, NFE=1, 50 steps	16 draws	0.48	5 + 0.10 GPU	1.115	1.038	+3.6	+5.0
PARSAC, 10^7 steps	best of 16 workers	1,121	17,937	1.222	1.179	+26.0	+4.7
PARSAC, 10^7 steps	best of 4 workers	1,121	4,484	1.348	1.241	+32.9	+8.8
PARSAC, 10^7 steps	one worker	1,121	1,121	1.685	1.426	+47.2	+22.2
SP-SA, 10^5 evaluations	best of 4 workers	104	416	9.24	9.34	+146.4	+155.7
SP-SA, 10^5 evaluations	one worker	104	104	12.80	12.03	+182.8	+223.8
Astra, published layouts	—	0.45 [†]	—	1.282	1.221	+15.5	+14.0

number is the legalized layout’s, and every timed run had the machine to itself.

The classical lines. PARSAC (Mostafa et al., 2024) is the constraints-aware B*-tree annealer of the group that built FloorSet. We load its C++ engine as released and run its published schedule of 100 stages from a random tree, with the boundary codes, clusters, fixed and preplaced blocks and MIB shapes of each case mapped one to one, for 10^7 steps per worker, its budget in the paper. A worker is one independent run on one CPU core, and the best of k workers is the per-case minimum over k runs at k times the CPU time. Every run is snapshotted after each stage and every snapshot is legalized and scored, so the curves below are one worker’s best legalized cost so far against its own elapsed seconds. The sequence-pair annealer is the one of BBOPlace-Bench (Xue et al., 2026) with 10^5 cost evaluations, and Astra is the public contest solver, whose published layouts we re-score with our checker and which reproduce its own numbers.

L.1 THE FLOORSET VAL SET

Table 54 runs every line to its final layout. With 16 draws the pipeline reaches a mean hard cost of 1.019 in 1.14 seconds per case, and PARSAC reaches 1.222 with the best of 16 workers after 1,121 seconds per worker, about five CPU hours per case, 1.348 with the best of 4 and 1.685 with one worker. The gap is in the objectives: PARSAC’s layouts are 26 to 47% above the reference in wirelength, while the pipeline’s are within 0.4%. Astra’s published layouts lie between the two at 1.282, and the sequence-pair annealer stays above 9 at its whole budget.

Table 55 and Figure 18 read PARSAC at a budget. No PARSAC line reaches the pipeline’s point at any time: one worker needs 300 seconds to reach 1.62 and an hour to reach 1.41, and the best of 16 workers is flat at 1.19 from 2,400 seconds per worker on, so a longer run would not close the gap and only more workers narrow it. Table 56 gives the per-unit CPU costs behind these times: one PARSAC step costs 0.03 to 0.22 milliseconds from 21 to 120 blocks, so its 10^7 steps take 4 to 37 minutes, while one legalizer call costs 41 to 476 milliseconds and runs once per draw.

Table 55: PARSAC on the FloorSet val set after the given seconds per worker: the mean (median) over cases of the best legalized snapshot so far. The best of 16 workers is flat from 2,400 seconds on; Trinity reaches 1.019 (1.001) in 1.14 seconds per case with 16 draws.

PARSAC	60 s	300 s	600 s	1,200 s	2,400 s	3,600 s
one worker, mean	2.34	1.62	1.51	1.45	1.42	1.41
best of 4 workers, mean	1.83	1.39	1.32	1.29	1.27	1.27
best of 16 workers, mean	1.60	1.28	1.23	1.20	1.19	1.19
best of 16 workers, median	1.34	1.20	1.18	1.17	1.16	1.16

Table 56: Per-unit CPU costs on the FloorSet val set by block count, one call at a time on an idle machine: the legalizer on one draw of Trinity, one PARSAC annealing step and one SP-SA cost evaluation, in milliseconds.

Blocks	Legalizer	PARSAC	SP-SA
21 to 40	41	0.025	0.48
41 to 60	98	0.057	0.75
61 to 80	184	0.096	1.04
81 to 100	401	0.151	1.34
101 to 120	476	0.222	1.66




Figure 18: The FloorSet val set: the mean (left) and median (right) hard cost against seconds per case. PARSAC as the best legalized snapshot so far of one worker and of the best of 4 and 16 workers, against seconds per worker on one CPU core; Trinity at every setting of NFE, refiner steps and draws, on one GPU with 16 legalizer workers, the star at NFE=8, 400 steps and 16 draws; ours $\rightarrow$ PARSAC is PARSAC started from the tree of the pipeline’s legalized layout, drawn from the pipeline’s time on. The sequence-pair annealer stays above 10 and is off the axis.

Continuing from the pipeline. PARSAC started from the tree of the pipeline’s legalized layout does not improve on it (the dashed line of Figure 18). The first snapshot after 10^4 steps is already at a mean of 2.05 against the pipeline’s 1.019, and 10^6 steps bring it back only to 1.31. A step-by-step probe of the hand-over on eight cases places the loss before any annealing: the compaction into a B*-tree moves 15 to 26 blocks, the tree does not reproduce the compacted layout on six of the eight cases, and the first greedy moves in PARSAC’s own cost, which weighs white space and normalized wirelength rather than the contest cost, raise the contest cost further. A continuation that helps would need the legalized layout’s exact representation and the contest cost as its acceptance rule.

L.2 THE SOFT-BLOCK BENCHMARKS OF THE PRIOR WORK

The prior floorplanning work reports on the GSRC and MCNC benchmarks with every block soft at its area, the aspect ratio within $[1/3, 3]$ (GSRC) or the file’s range (MCNC), a square outline of 1.1 times the total block area, terminals at their benchmark positions, and the wirelength of block centres and terminals. We run the pipeline unchanged on this protocol with four sampling seeds and 16 or 64 draws each; a layout fits when it is overlap-free, keeps every area and aspect bound and lies inside the outline. Trinity was trained on FloorSet cases with 21 to 120 blocks and never saw these benchmarks.

Table 57 gives the pipeline on every case. It fits the outline on every MCNC case and on GSRC n10 to n200 on every seed, at 1 to 5% dead space and in one to nine seconds per case. The one failure is GSRC n300, two and a half times the largest block count of training, where no seed fits and the best layout leaves 14% dead space.

Table 58 and Figure 19 set the pipeline against PARSAC run here and the published rows. On n100

Table 57: Trinity on the soft-block benchmarks of the prior work: every block soft at its area, a square outline of 1.1 times the block area, terminals at their benchmark positions. Per case, how many of four sampling seeds give a fitting legalized layout with 16 draws, the best fitting wirelength over the seeds with 16 and 64 draws (HPWL of block centres and terminals, benchmark units / 1,000), the dead space of that layout in percent, and the seconds per case of one seed with 16 draws. [†]Oversized: no seed fits, the best legal layout.

Case	Blocks	Seeds fitting	HPWL, 16	HPWL, 64	Dead space	s / case
<i>GSRC</i>						
n10	10	4 / 4	50.6	50.3	3.4	0.84
n30	30	4 / 4	150.6	150.0	1.1	4.53
n50	50	4 / 4	178.1	177.9	1.6	1.10
n100	100	4 / 4	294.7	294.0	2.1	2.20
n200	200	4 / 4	554.9	553.1	0.7	8.60
n300	300	0 / 4	681.3 [†]	681.8 [†]	13.8	7.01
<i>MCNC</i>						
apte	9	4 / 4	566.1	565.4	0.6	0.78
xerox	10	3 / 4	574.5	548.8	3.4	1.68
hp	11	4 / 4	173.6	173.1	2.3	0.71
ami33	33	4 / 4	69.3	67.8	3.5	0.99
ami49	49	4 / 4	932.5	883.3	4.6	1.20

Table 58: GSRC soft blocks in a 10% square outline, per column the best fitting wirelength in bold and the second underlined: the wirelength in mm (benchmark units / 1,000) of Trinity with 16 and 64 draws per seed over 4 seeds, of PARSAC run here from random trees with its published schedule for 10^7 steps (the best final layout of 16 and of 4 workers, one CPU core each) and of the published rows. Seconds per case for Trinity with one seed and 16 draws (n100 / n200 / n300); minutes per worker for PARSAC. [†]From Table 2 of PARSAC (Mostafa et al., 2024), 112 workers of 10^7 steps; best and worst are over its reported runs. [‡]Oversized: no draw fits, the best legal layout.

Line	n100	n200	n300	Time
Trinity, 4 seeds, 16 / 64 draws per seed	294.7 / 294.0	554.9 / 553.1	681.3 [‡] / 681.8 [‡]	2.2 / 8.6 / 7.0 s
PARSAC here, best of 16 / 4 workers	303.5 / 310.1	576.0 / 586.6	709.3 / 720.2	22 / 68 / 138 min
PARSAC (soft), 112 workers, best [†]	288	526	627	–
PARSAC (soft), 112 workers, worst [†]	301	553	663	–
PARSAC (hard), 112 workers, best [†]	<u>291</u>	<u>530</u>	<u>628</u>	–
GoodFloorplan [†]	319	575	705	–
SP-FOPP [†]	323	599	757	–
B*-FOPP [†]	344	654	799	–

and n200 the pipeline’s wirelength of 294.7 and 554.9 mm is 3 to 4% below PARSAC’s best of 16 workers, which takes 22 and 68 minutes per worker, inside the range of PARSAC’s published best of 112 workers, and below GoodFloorplan (Xu et al., 2022) and both FOPP rows, in seconds per case. PARSAC’s best of 4 workers here sits 3 to 9% above the top of its published range, the size of the gap between 4 and 112 workers, so our run of PARSAC agrees with its paper. On n300 PARSAC fits after about 84 minutes per worker and the pipeline does not fit. As on FloorSet, PARSAC started from the pipeline’s layout ends 3 to 7% longer than where it started.

M SEEDS

Four models were trained three times (the original seed plus two more, the data split unchanged) and evaluated as generators: the standard $12k \times 6$ NFE $\times$ 4-draw generation and scoring, soft and distribution metrics. Per metric the three values, their mean and the sample standard deviation. The four models are Trinity (spectral PE, information mover, all six terms at 0.01, the adopted recipe), the same backbone without the auxiliary loss (Trinity at $\lambda=0$), the plain backbone without the auxiliary loss (the plain control) and FlowPlace.

The soft cost is reproducible to 0.3 to 1.1% of its mean on the three models of this work and to 2 to 3.5% on FlowPlace, overlap to 1 to 3%, group to 1 to 4%, boundary to 1 to 3% on the two $\lambda=0$ models and FlowPlace and 9 to 11% on Trinity, whose boundary slot is 3 to 4 $\times$ smaller. The wide columns everywhere are the fixed deviation, the area gap and the MIB variance at 10^{-6} levels; the




Figure 19: GSRC soft blocks in a 10% square outline: the wirelength of fitting layouts in mm against seconds per case. PARSAC as the median over 16 workers of one worker’s best fitting snapshot so far and as the best of 16 workers; ours $\rightarrow$ PARSAC from the pipeline’s layout, drawn from the pipeline’s time on; Trinity with 16 draws, the best of four seeds; the published rows of Table 58 as dotted levels.

Table 59: Std / mean per model and column at NFE = 32, 8 and 1, and the absolute std of the soft cost. Trinity’s area gap at NFE=1 has a mean near zero (-0.0013 to $+0.0043$), so no ratio is given. MIB variance and fixed deviation are the wide columns everywhere.

Model	NFE	Overlap	Boundary	Group	MIB	Fixed	Area gap	sev _{rel}	Soft cost	abs. std
Trinity	32	2.8%	9.3%	3.2%	31%	40%	68%	8.2%	1.1%	0.017
Trinity	8	2.4%	9.8%	3.7%	31%	40%	91%	8.6%	1.1%	0.018
Trinity	1	2.9%	10.6%	4.4%	32%	36%	—	9.6%	1.0%	0.017
Trinity, $\lambda=0$	32	1.0%	1.0%	3.1%	16%	17%	12.5%	1.9%	0.7%	0.015
Trinity, $\lambda=0$	8	0.4%	1.1%	3.3%	12%	16%	14%	1.9%	1.0%	0.021
Trinity, $\lambda=0$	1	0.9%	1.3%	3.3%	12%	11%	14.5%	2.0%	1.6%	0.037
the plain control	32	1.0%	3.0%	1.2%	4.3%	8.8%	8.4%	1.3%	0.4%	0.007
the plain control	8	1.5%	2.9%	1.3%	3.6%	9.8%	10%	1.4%	0.5%	0.011
the plain control	1	1.1%	2.5%	1.9%	4.2%	12%	12%	1.2%	0.3%	0.009
FlowPlace	32	2.9%	0.8%	1.4%	62%	1.4%	8.2%	1.5%	2.0%	0.050
FlowPlace	8	3.1%	3.4%	1.7%	23%	3.1%	7.4%	2.5%	3.5%	0.132
FlowPlace	1	3.0%	1.6%	1.0%	20%	4.2%	3.7%	1.2%	3.4%	0.38

HPWL gap at NFE=32 sits within ± 0.001 of zero on every model. A sweep-set delta below 2 to 3% on a constraint column or 1% on the soft cost is within one seed standard deviation of its control.

Table 60: Trinity per column, three training seeds, the five columns at NFE=32 and then at NFE=1 (std / mean in Table 59). Units as in Section 4.1.

Column	Original	Seed 1	Seed 2	Mean	Std	Original	Seed 1	Seed 2	Mean	Std
overlap	0.02253	0.02217	0.02132	0.02201	0.00062	0.03161	0.03054	0.02983	0.03066	0.00089
boundary	0.817	0.898	0.985	0.900	0.084	0.799	0.889	0.988	0.892	0.095
group gap	2.325	2.370	2.474	2.390	0.077	1.773	1.813	1.927	1.838	0.080
MIB variance	1.72	2.95	3.28	2.65	0.82	1.72	2.93	3.42	2.69	0.87
fixed	8.337	5.055	11.802	8.398	3.37	8.837	5.712	12.203	8.917	3.25
HPWL gap	-0.00069	-0.00054	+0.00014	-0.00036	0.00044	-0.01237	-0.01216	-0.01183	-0.01212	0.00027
area gap	0.00224	0.00259	0.00705	0.00396	0.00268	-0.00125	+0.00027	+0.00429	+0.00111	0.00286
normalized wirelength	0.30190	0.30193	0.30215	0.30199	0.00014	—	—	—	—	—
compactness	1.0291	1.0295	1.0340	1.0309	0.0028	—	—	—	—	—
sev _{rel}	0.0849	0.0906	0.0998	0.0918	0.0075	0.0819	0.0888	0.0991	0.0899	0.0086
soft cost	1.5137	1.5277	1.5470	1.5295	0.0167	1.6785	1.6855	1.7108	1.6916	0.0170

At NFE=1 the soft cost is 2.4900 / 2.5053 / 2.4905 (2.4953 ± 0.0087) for the plain control and 11.465 / 11.351 / 10.755 (11.19 ± 0.38) for FlowPlace.

Table 61: Trinity at $\lambda=0$ per column, the five columns at NFE=32 and then at NFE=1. Units as in Section 4.1.

Column	Original	Seed 1	Seed 2	Mean	Std	Original	Seed 1	Seed 2	Mean	Std
overlap	0.02220	0.02261	0.02255	0.02245	0.00022	0.03573	0.03545	0.03508	0.03542	0.00032
boundary	2.997	2.946	2.947	2.963	0.029	3.011	2.943	2.941	2.965	0.040
group gap	2.827	2.675	2.682	2.728	0.086	2.320	2.177	2.219	2.239	0.073
MIB variance	6.66	6.30	8.38	7.11	1.1	7.19	7.32	8.85	7.79	0.92
fixed	7.474	6.905	9.472	7.951	1.35	7.956	7.221	9.027	8.068	0.91
HPWL gap	+0.00219	-0.00001	+0.00024	+0.00081	0.0012	-0.01129	-0.01308	-0.01269	-0.01235	0.00094
area gap	0.01810	0.01441	0.01498	0.01583	0.0020	0.01642	0.01262	0.01323	0.01409	0.0020
sev _{rel}	0.2214	0.2137	0.2154	0.2168	0.0040	0.2216	0.2134	0.2151	0.2167	0.0044
soft cost	2.0151	1.9877	1.9919	1.9982	0.0148	2.4271	2.3692	2.3571	2.3845	0.0374

Table 62: The plain control (left five columns) and FlowPlace (right five) per column at NFE=32. Units as in Section 4.1.

Column	Original	Seed 1	Seed 2	Mean	Std	Original	Seed 1	Seed 2	Mean	Std
overlap	0.02602	0.02638	0.02656	0.02632	0.00028	0.04383	0.04602	0.04370	0.04452	0.0013
boundary	3.227	3.156	3.041	3.141	0.094	2.811	2.854	2.817	2.827	0.024
group gap	2.651	2.702	2.712	2.688	0.033	3.196	3.211	3.126	3.178	0.046
MIB variance	8.75	9.28	9.53	9.19	0.40	3.51	8.54	2.88	4.98	3.1
fixed	5.817	5.909	5.016	5.581	0.49	2.266	2.246	2.206	2.239	0.031
HPWL gap	-0.00214	-0.00089	-0.00123	-0.00142	0.00065	-0.00231	-0.00229	-0.00279	-0.00246	0.00028
area gap	0.01037	0.01224	0.01108	0.01123	0.00095	0.00870	0.00932	0.00791	0.00865	0.00071
sev _{rel}	0.2238	0.2235	0.2185	0.2219	0.0030	0.2099	0.2140	0.2077	0.2105	0.0032
soft cost	2.0915	2.0993	2.0845	2.0918	0.0074	2.4564	2.5331	2.4406	2.4767	0.0495




Figure 20: Three training seeds per model at NFE=32: the values, the mean and the standard deviation per soft column, for Trinity, Trinity at $\lambda=0$, the plain control and FlowPlace. The term effect on boundary, sev_{rel} and the soft cost is many times the spread.

Figure 21: The relative seed spread per column and model. The wide columns are the fixed deviation, the area gap and the MIB variance.

Figure 22: FLD and MMD of every seed at NFE=32 with the plain control's seed band. Trinity's worst seed is below the best seed of the plain control and of Trinity at $\lambda=0$.

The term effect against the seed spread. Trinity minus Trinity at $\lambda=0$ at NFE=32, in units of the seed std of Trinity at $\lambda=0$ and of Trinity: boundary 0.00082 against 0.00296 is 70 std of Trinity at $\lambda=0$ and 25 of Trinity, sev_{rel} 0.085 against 0.217 is 33 and 17, soft cost 1.514 against 1.998 is 33 and 28, MIB variance 1.7×10^{-6} against 7.1×10^{-6} is 5 and 4, group gap 0.00232 against 0.00273 is 5 and 5, overlap 0.0225 against 0.0225 is no effect at NFE=32 (12 std of Trinity at $\lambda=0$ at NFE=1, 0.0316 against 0.0354), and the fixed deviation 0.0083 against 0.0080 ± 0.0014 is no effect. Trinity’s soft cost against FlowPlace’s (1.53 ± 0.017 against 2.48 ± 0.05) is 19 FlowPlace-std and 57 Trinity-std.

Table 63: Distribution metrics of the twelve caches at NFE=1 and 32; the reference is the plain control’s original run, p the permutation test against it. Units as in Section 4.1.

Run	NFE	FLD8b	FLD8f	FPD	MMD8b	p
the plain control, original	1	0.4325	0.0179	0.0036	32.6	–
	32	0.1031	0.0033	0.0011	15.6	–
the plain control, seed 1	1	0.4474	0.0181	0.0038	34.4	0.199
	32	0.1112	0.0041	0.0013	17.2	1.000
the plain control, seed 2	1	0.4274	0.0161	0.0040	32.1	0.333
	32	0.1066	0.0031	0.0013	15.9	0.955
the plain control, 3 seeds	1	0.436 ± 0.010	0.0174 ± 0.0011	0.0038 ± 0.0002	33.0 ± 1.2	
	32	0.1070 ± 0.0041	0.0035 ± 0.0005	0.0012 ± 0.0001	16.2 ± 0.9	
Trinity, $\lambda=0$, original	1	0.4264	0.0159	0.0042	37.6	0.821
	32	0.1123	0.0048	0.0015	21.9	1.000
Trinity, $\lambda=0$, seed 1	1	0.3885	0.0142	0.0040	30.2	0.020
	32	0.0990	0.0031	0.0014	17.2	1.000
Trinity, $\lambda=0$, seed 2	1	0.3708	0.0148	0.0039	30.9	0.378
	32	0.0986	0.0045	0.0014	20.1	1.000
Trinity, $\lambda=0$, 3 seeds	1	0.395 ± 0.028	0.0150 ± 0.0009	0.0040 ± 0.0002	32.9 ± 4.1	
	32	0.1033 ± 0.0078	0.0041 ± 0.0009	0.0014 ± 0.0001	19.7 ± 2.4	
Trinity, original	1	0.1624	0.0173	0.0025	9.23	0.005
	32	0.0423	0.0075	0.0012	2.34	0.005
Trinity, seed 1	1	0.1698	0.0089	0.0022	8.14	0.005
	32	0.0514	0.0036	0.0011	2.75	0.005
Trinity, seed 2	1	0.1863	0.0072	0.0026	12.2	0.005
	32	0.0650	0.0034	0.0013	5.89	0.005
Trinity, 3 seeds	1	0.173 ± 0.012	0.0111 ± 0.0054	0.0024 ± 0.0002	9.9 ± 2.1	
	32	0.0529 ± 0.0114	0.0048 ± 0.0023	0.0012 ± 0.0001	3.7 ± 1.9	
FlowPlace, original	1	3.7712	0.1823	0.0192	344	1.000
	32	0.2274	0.0088	0.0013	24.9	1.000
FlowPlace, seed 1	1	3.9361	0.1760	0.0195	382	1.000
	32	0.2530	0.0103	0.0015	26.2	1.000
FlowPlace, seed 2	1	3.6919	0.1777	0.0174	360	1.000
	32	0.2167	0.0084	0.0012	23.7	1.000
FlowPlace, 3 seeds	1	3.80 ± 0.12	0.1787 ± 0.0033	0.0187 ± 0.0011	362 ± 19	
	32	0.232 ± 0.019	0.0092 ± 0.0010	0.0013 ± 0.0002	24.9 ± 1.3	

Trinity is closer to the reference distribution than the plain control on every seed at both NFE ($p = 0.005$ for all six tests; MMD8b 2.3 to 5.9 at NFE=32 against the plain control’s 15.6 to 17.2 and Trinity at $\lambda=0$ ’s 17.2 to 21.9, FLD8b 0.042 to 0.065 against 0.099 to 0.112): its worst seed is $2.7\times$ below the best control seed on MMD8b and $1.5\times$ below on FLD8b. Its own spread on these two is the widest of the four models in relative terms (MMD8b 53%, FLD8b 22%), which a 2 to $5\times$ advantage absorbs, and the original run’s FLD8f of 0.0075 is the outlier of the three. Trinity at $\lambda=0$ ’s three seeds on FLD8b lie inside the plain control’s at NFE=32, so the backbone without the auxiliary loss is not separated from the plain control on the density descriptors within seed spread. The plain control’s own replicates test at $p = 0.20$ to 0.33 at NFE=1 and 0.96 to 1.00 at NFE=32 against the original, the null band for the same model with another seed, and $p = 0.005$ is far outside it. FlowPlace’s seed std on the distribution metrics is 3 to 8% of the mean, and it tests at $p = 1.000$ on every seed.

N FIGURES: EVERY VIEW OF THE DATA

Every figure below is rendered from the result files of the supplementary material with one panel per setup (NFE, step count, term or column), the models as the lines of every panel and one shared legend. The main text uses the simplest view of each experiment; the views here show the same data from every side, and one result may appear in several of them.

N.1 THE SOFT FRONTIER




Figure 23: Soft cost against refiner steps, one panel per NFE, on our 12,000 val set with four draws. Trinity starts lowest in every panel, every line of this work converges to the same endpoint, and the prior arts stay above at 400 steps; DiffPlace and MacroDiff+ at $\text{NFE} \leq 2$ start two decades higher.




Figure 24: The same data as Figure 23 on a linear axis from 1 to 3, where the lines of this work separate: the terms lift the raw sample and the first 25 steps, and the lead is largest at $\text{NFE}=1$.




Figure 25: Refiner steps needed to reach a soft cost of τ against NFE, Trinity and the same backbone without the auxiliary loss. Trinity reaches each threshold one rung earlier at the low NFE values and the two agree from $\text{NFE}=4$.




Figure 26: Every soft column of the raw sample against NFE for the nine generators of the composed grid (three backbones $\times$ three term settings). Boundary and MIB variance fall with the terms at every NFE, overlap falls with NFE on every model, and the fixed deviation is where the plain backbone leads.




Figure 27: Soft cost against NFE, one panel per step count. The NFE gain shrinks with refinement: 0.16 on the raw Trinity sample, 0.008 at 400 steps.




Figure 28: The soft grid as heatmaps, rows NFE, columns refiner steps, colour = $\log_{10}$ soft cost clipped at 10, one panel per line. Every grid is monotone in both axes.

N.2 THE HARD FRONTIER




Figure 29: Soft cost, first-draw hard cost and best-of-four hard cost against NFE at 400 refiner steps. The soft cost is monotone in NFE while the first draw has its minimum at NFE=2 and the best of four at NFE=8.




Figure 30: Hard cost after legalization against refiner steps, one panel per NFE and selection (first draw, best of four), Trinity and the four prior arts. The refiner pays after legalization on every line, the largest move is from raw to 10 steps, and the order of the lines is the order of the raw soft cost.




Figure 31: Soft cost against first-draw hard cost, cell means, one connected path per line. Top: along the step axis (raw to 400 steps), one panel per NFE; the paths are monotone along steps, and the prior arts' paths end above Trinity's. Bottom: along the NFE axis, one panel per step count; at 400 steps Trinity's path runs upward, the soft cost keeps falling with NFE while the first-draw cost rises slightly.




Figure 32: The legalizer's ladder against refiner steps at $NFE \in \{1, 8, 32\}$: the median expansion factor λ , the area gap and V_{rel} after legalization, the share of draws solved by the hard LP, and the milliseconds per draw. λ , the price of residual overlap, falls with refinement and Trinity needs the least; the two ϵ -head prior arts at $NFE=1$ have no layout to legalize.




Figure 33: The first-draw hard cost on the $\text{NFE} \times \text{steps}$ grid, colour = $\log_{10}$ cost clipped at 3.2, one panel per line; the annealer has no sampler and fills one row.




Figure 34: The best-of-four hard cost on the $\text{NFE} \times \text{steps}$ grid, same layout as Figure 33.




Figure 35: Which rung of the legalizer solves each draw, as stacked shares against refiner steps at $\text{NFE}=32$, one panel per line. The hard-LP share doubles from the raw sample to 400 steps and no draw is infeasible.

N.3 SOFT AGAINST HARD PER DRAW




Figure 36: Per-draw correlations with the legalizer's behaviour against refiner steps at $\text{NFE}=32$: the soft cost predicts the rung a draw reaches and the time it takes, and the time predicts the hard cost on every line.




Figure 37: The same six cells as Figure 38 on the per-case means over four draws.




Figure 38: Soft cost against legalized hard cost per draw, a 2,000-draw subsample of six cells. The relation is a ranking, not a line: the Spearman correlation reaches 0.62 at Trinity's (NFE=32, 400) cell, and the hard cost keeps a heavy tail.




Figure 39: The per-draw Spearman correlation between soft cost and hard cost per cell, one heatmap per line, and its course against refiner steps at NFE=32. The correlation rises with both axes on Trinity, from 0.20 to 0.60, and less on the prior arts.




Figure 40: Left: correlation measures per line, across cell means and pooled over draws. Right: the Spearman correlation of every soft column with the hard cost on Trinity at three cells; sev_{rel} carries it, then overlap and boundary, and wirelength is negative because a shorter wirelength goes with a larger die.




Figure 41: (a) Figure 7b with all eight lines: the regressors' cells sit at a soft cost of 20 to 100, so their per-case median is drawn where the mean overflows. (b, c) The expansion factor λ against the hard cost per draw on Trinity at NFE=32, raw and after 400 refiner steps. Refinement moves the mass to $\lambda=1$, the draws that need no expansion.

N.4 THE TERM LADDERS




Figure 42: Single-term ladders on the plain backbone: the term's own target metric and the soft cost relative to the plain control against the weight, at NFE=32 (solid) and NFE=1 (dashed), with the 0.05 t arm as a star. Each term moves its own target; boundary and area move the soft cost, the others hardly.




Figure 43: The term ladder on the three backbones, one panel per metric. The terms do the same work on every backbone, and the backbones differ in where they start: the information mover lowers overlap and the distribution distances, the spectral encoding alone raises the fixed deviation.




Figure 44: The side effects: every soft column relative to the plain control against the weight, one panel per term. The boundary term raises the fixed deviation, the area term lowers the boundary distance, and the MIB term raises nothing.




Figure 45: FLD (top) and MMD (bottom) against the weight per term at NFE=32 and 1, with a star where the arm is closer to the reference than the plain control at $p < 0.05$ under the permutation test of Appendix C.1. The distribution-closest weight is one step below the best raw target (overlap 0.05, boundary 0.01).




Figure 46: All six terms at one common weight, constant (left) and t -weighted (right): every constraint metric and the soft cost relative to the plain control. The weight 0.01 improves every constraint at once, 0.1 breaks the fixed deviation, and the t -weighted arms trade the same way at twice the weight.

N.5 METRIC AGAINST METRIC




Figure 47: Raw soft cost against NFE for the objective sweep, the architecture and recipe sweep, and the prior arts. The clean-sample head is flat in NFE; the ϵ and v heads, ours and the prior arts', are not.




Figure 48: Every model at NFE=32: soft cost against FLD and against MMD, and overlap against soft cost. The two distribution metrics agree on the order, and the single-term overlap arms have the lowest overlap at the plain control's soft cost.




Figure 49: Soft cost against FLD and MMD, one segment per model from NFE=1 to 32, coloured by sweep set. The term-trained arms occupy the lower left, and the segments of the ϵ -head and v -head models are long because they have no layout at NFE=1.




Figure 50: Raw soft cost against NFE for every single-term arm and for the all-six and composed arms.

N.6 BEST OF N AND THE FLOORSET VAL SET




Figure 51: Left: Trinity's best-of- N mean hard cost on the 12,000 cases with the median-to-p90 band, at NFE $\in \{32, 8, 1\}$ with 400 steps, at NFE=32 raw, and the soft pick (the legalized cost of the draw with the lowest soft cost among N). NFE=8 equals 32, NFE=1 gains less from N , and the soft pick does not replace legalizing every draw. Right: the N ladder on the FloorSet val set at NFE=8 and 400 steps.




Figure 52: The FloorSet val set solved one case at a time. Left: mean hard cost against seconds per case for every NFE $\times$ steps $\times$ draws setting with the envelope; N is the strongest lever and 16 draws at NFE=4 with 100 steps reach 1.043 in 0.63 seconds. Right: the seconds per case by stage; the refiner is a fixed 0.6 seconds at 400 steps and the legalizer grows with N .




Figure 53: Per FloorSet val set case at NFE=8, 400 steps and 16 draws: seconds and hard cost against block count. The legalizer's time grows with the block count and the cost does not.




Figure 54: First-draw and best-of-four hard cost at 400 steps against NFE for every line; the annealer and the regressors have no sampler and are drawn as levels.

N.7 THE REFINER SWEEPS




Figure 55: Every soft column against refiner steps at NFE=32 for the models of this work and the prior arts. Overlap, the cluster gap, the MIB variance and the fixed deviation fall monotonically, the boundary distance after a rise at 10 steps; the HPWL and area gaps are the residual the refiner trades for them.




Figure 56: Every draw of three cases of our 12,000 val set (30, 70 and 120 blocks, four draws each) along the refiner at NFE = 1 and 32. Overlap and sev_{rel} fall on every draw, the MIB variance and the cluster gap reach zero within 10 to 200 steps, the boundary distance rises at 10 steps on most draws before it falls, and the HPWL and area gaps are the residual each draw trades for them. One draw of the 30-block case keeps a cluster gap of 0.02 at NFE=32 and ends at a soft cost of 1.28.




Figure 57: Left: the seventeen weighting arms at 200 steps; the overlap weight of 10 is the one change that moves the endpoint. Right: the overlap-weight ladder against steps.




Figure 58: The budget panel of Figure 1 in soft cost (left) and in the hard cost of the first legalized draw (right): Trinity at NFE = 1, 8 and 32, every prior-art generator at NFE=32 raw (cross) and under the closed-form refiner (dashed), and its own loop at the published iteration count (triangle). A horizontal arrow ends at the refiner budget that matches the loop, by linear interpolation between the measured budgets. The vertical arrow runs from the cheapest loop to our cost at 400 steps.

Trinity at NFE 32, every refiner weight 1: learning rate $\times$ schedule




Figure 59: Soft cost and overlap against refiner steps for the twelve schedule $\times$ peak-rate arms on Trinity at NFE=32 with every weight at 1. Linear and cosine decay at 10^{-3} coincide, and a constant rate over-refines: overlap turns up after 50 steps.

N.8 QUALITATIVE EXAMPLES

Figure 60 follows three FloorSet val set cases through the pipeline of Section 4.4 at the setting of Table 7: Trinity samples 48 draws at $NFE=8$, the closed-form refiner runs 400 steps, the legalizer closes every draw, and the draw with the cheapest legalized layout is shown at every stage. The raw sample already has the outline, the boundary-coded blocks on their edges and the clusters together, with thin overlaps between neighbours; the refiner removes the overlaps and the legalizer packs the result. The gaps under the panels are signed, so a refined layout smaller than the reference, as on the 21-block case with an area gap of -0.021 , is visible where the hard cost would clamp it to zero. The best of 48 lands at a hard cost of 1.000, 1.000 and 1.074 against 1.091, 1.000 and 1.127 for the reference layouts of the 21-, 60- and 120-block cases, and every one of the 144 legalized draws is feasible.

Figure 61 puts the generators side by side on one of those cases. Because the sampler draws its noise from the case alone, the first draw of every line starts from one noise tensor, so the panels are paired rather than merely comparable. The ordering of Table 3 is visible block by block. On the case shown Trinity overlaps 0.022 of the block area at a soft cost of 1.44, FlowPlace and ChipDiffusion 0.058 and 0.054 at 3.24 and 3.55, and MacroDiff+ and DiffPlace 0.092 and 0.111 at 7.57 and 8.43; over the 21-, 60- and 120-block cases the same draw gives 0.014 to 0.022 for Trinity, 0.036 to 0.067 for the two velocity and cosine heads and 0.068 to 0.111 for the two remaining lines. The kind of failure also differs. Every line finds the outline and puts the boundary-coded blocks on their edges, so the gap is not in the global arrangement but in the local packing, which Figure 62 magnifies on a larger case: Trinity leaves thin contacts where a neighbour is a few thousandths of the layout scale too wide, while DiffPlace leaves whole blocks lying across one another. This is the defect the closed-form refiner of Section 4.3 removes in ten steps on Trinity and cannot remove on the prior arts in four hundred.




Figure 60: Three FloorSet val set cases with 21, 60 and 120 blocks through the pipeline, 48 draws at NFE=8 with 400 refiner steps and the shared legalizer, the draw with the cheapest legalized layout shown at every stage: the reference layout, the raw sample, the refined layout and the legalized layout. Blocks are coloured by constraint kind, every pairwise overlap region is red, block-to-block nets are faint lines between block centres, pins are dots on the outline with faint lines to their blocks, and the dashed box is the bounding outline. Under each panel: the signed area gap and HPWL gap to the reference, the severity sev_{rel} and the overlap ratio of the soft vector of Appendix C, which unlike the hard cost keep a layout smaller or shorter than the reference visible.




Figure 61: Every generator on one 60-block FloorSet val set case from the same noise: the reference layout and the first draw of each line at NFE=8, before any refinement. Colours as in Figure 60. Under each panel, the overlap ratio and the soft cost of that layout.




Figure 62: A 120-block case under the protocol of Figure 61, with one region magnified. The window is placed on the largest overlap of the worst line and is the same in all three columns.

O MODEL SIZE

Setup. Two variables define a rung of Trinity recipe: the hidden width d and the layer count L (Table 64). The width rungs fix $L = 12$ and vary d , the depth rungs fix $d = 768$ and vary L , and one rung sits off both axes at width 512 with 16 layers; the head dimension is 64 throughout, so the head count follows d . The spectral positional encoding, the information mover, all six terms at $\lambda=0.01$, the wire-dropout mixture and the frozen training recipe of Appendix B.2 (AdamW at a peak learning rate of 2×10^{-4} with cosine decay, effective batch 256, 200,000 steps, one GPU) are identical on every rung, so the runs differ in d and L alone. The width rungs sit at the sizes of the ported prior arts, 5.9M to 42.1M parameters against 5.0M to 23.9M for their networks; the depth rungs span 31.5M to 62.2M, so the two axes overlap in parameter count and separate the effect of the shape from that of the size. Every rung of the first six goes through the standard evaluation: our 12,000 val set at $\text{NFE} \in \{1, 2, 4, 8, 16, 32\}$ with four draws and the fifteen soft columns, the distribution metrics at $\text{NFE}=1$ and 32 against the plain control with 200 permutations, the full $\text{NFE} \times$ steps refiner grid of Appendix I, and the same grid through the legalizer with the first draw and the best of four, as in Appendix K. The two rungs trained last, 192 / 12 at 5.9M parameters and 512 / 16 at 56.0M, have the raw scores of the val set only and appear in Tables 64 and 65.

Table 64: The size rungs of Trinity recipe, defined by the hidden width d and the layer count L (head dimension 64 throughout). Everything not listed is Trinity’s.

Rung	d	L	Parameters
<i>Width rungs</i>			
192 / 12	192	12	5.9M
256 / 12	256	12	10.6M
384 / 12	384	12	23.3M
512 / 12	512	12	42.1M
<i>Depth rungs</i>			
768 / 4	768	4	31.5M
768 / 6	768	6	46.8M
768 / 8	768	8	62.2M
<i>Off both axes</i>			
512 / 16	512	16	56.0M
768 / 12, Trinity	768	12	92.9M

Width rungs, raw samples. Table 65 and Figure 63 give the widths at $L = 12$ on our 12,000 val set, the figure the four with full grids. At width 512, with 45% of Trinity’s parameters, the recipe reproduces Trinity within its seed spread on the raw sample (soft cost 1.534 against 1.514, 1.2 seed standard deviations; overlap within 0.5) and is equal to it at $\text{NFE}=1$; on the distribution metrics it is at or below Trinity at both NFE (FLD 0.0416 against 0.0423, MMD 0.0020 against 0.0025). Every rung is closer to the reference than the plain control at both NFE with $p = 0.005$, every rung keeps the constraint level the terms train (boundary distance 0.86 to 0.97×10^{-3} against 3.0×10^{-3} for Trinity at $\lambda=0$, MIB variance 2 to 4×10^{-6} against 6.7×10^{-6}), and every rung improves the deviation of fixed and preplaced blocks over Trinity. Widths 384 and 256 give back overlap (23% and 32% more at $\text{NFE}=32$) and soft cost (1.612 and 1.703), width 256 also on the cluster gap and the boundary distance, and the rung at 10.6M parameters still stands at a soft cost of 1.70 against 2.46 for FlowPlace at 6.3M and 6.23 for DiffPlace at 23.9M under the same recipe and steps. Width 192 at 5.9M parameters, the size of the smallest ported network, continues the ladder to a soft cost of 1.827 at $\text{NFE}=32$ and 1.903 at $\text{NFE}=1$ with an overlap of 0.0347, the boundary distance and the MIB variance at 1.0×10^{-3} and 13.8×10^{-6} , and it stays below every ported placer’s soft cost at the same NFE . The shape of the NFE curve is the same at every width.

Depth rungs, raw samples. The depth rungs keep the width at 768 and remove layers (Table 65, Figure 64). Every depth rung is behind Trinity on every constraint column at $\text{NFE}=32$: at $L = 8$ the overlap is 6% higher, the boundary distance 17%, the cluster gap 11% and the MIB variance 2.2 times, for a soft cost of 1.593 against 1.514; at $L = 6$ the overlap is 37% higher and the soft cost 1.733; at $L = 4$ the overlap doubles to 0.048, FlowPlace’s level, the MIB variance is 3.9 times Trinity’s and the soft cost is 2.128. Depth costs more than width per parameter, and depth beyond twelve layers buys little: width 512 with 16 layers (56.0M) sits between 512 / 12 and Trinity at every NFE , 1.530 against 1.534 and 1.514 at $\text{NFE}=32$ and 1.679 against 1.682 and 1.679 at $\text{NFE}=1$, with the overlap of 512 / 12 (0.0226) and the boundary distance and MIB variance of the width rungs, so four more layers at width 512 are worth 0.004 in soft cost for 14M parameters. By soft cost at $\text{NFE}=32$ the family orders as 768 / 12 (1.514), 512 / 16 (1.530), 512 / 12 (1.534), 768 / 8 (1.593), 384 / 12 (1.612), 256 / 12 (1.703), 768 / 6 (1.733), 192 / 12 (1.827) and 768 / 4 (2.128), so the 8-layer model at 62.2M parameters is within 0.02 of the width-384 model at 23.3M (and behind it after the refiner, 1.067 against 1.065, and on both distribution distances), the 6- and 4-layer models at 46.8M and 31.5M below the width-256 model at 10.6M, the 4-layer model below width 192 at 5.9M, and the loss per removed layer grows, +0.08 from 12 to 8 layers, +0.14 from 8 to 6 and +0.39 from 6 to 4. The deviation of fixed blocks is the one column that does not follow the depth. On the distribution metrics the 8- and 6-layer rungs are closer to the reference than the plain control at both NFE with $p = 0.005$.

and inside Trinity’s seed band on FLD, while the 4-layer rung is not ($p = 1.000$ at NFE=32, FLD 0.151 against 0.103 for the plain control): it is the one rung of the study whose layouts are farther from the reference distribution than the plain control’s while its soft cost is lower. The reading is that the graph-convolution residual needs depth. The information mover moves information along the netlist one hop per layer, so a 4-layer model cannot carry the netlist far enough to place its blocks, while a narrow model at 12 layers still can.

Table 65: The size rungs (d / L) on raw samples, NFE=32 unless stated: the constraint columns, the soft cost at NFE=32 / 1, and the two distribution distances against the reference, which the two rungs trained last do not have. Units as in Section 4.1; **orange** marks Trinity.

d / L	Params	Overlap	Boundary	MIB	Fixed	Area gap	Soft cost 32 / 1	FLD	MMD	HPWL gap
<i>Width rungs</i>										
192 / 12	5.9M	0.0347	1.00	13.8	7.2	+0.003	1.827 / 1.903	–	–	+0.001
256 / 12	10.6M	0.0297	0.97	3.7	6.6	+0.003	1.703 / 1.812	0.055	5.0	+0.001
384 / 12	23.3M	0.0277	0.86	2.0	6.2	−0.004	1.612 / 1.759	0.044	3.7	−0.002
512 / 12	42.1M	0.0229	0.89	2.4	5.8	+0.000	1.534 / 1.682	0.042	2.0	−0.001
<i>Depth rungs</i>										
768 / 4	31.5M	0.0483	1.17	6.6	12.3	−0.009	2.128 / 2.258	0.151	17.2	−0.005
768 / 6	46.8M	0.0309	1.06	4.2	6.0	+0.000	1.733 / 1.865	0.051	3.6	−0.002
768 / 8	62.2M	0.0239	0.96	3.8	11.2	+0.005	1.593 / 1.740	0.048	4.0	−0.001
<i>Off both axes</i>										
512 / 16	56.0M	0.0226	0.93	3.0	5.1	−0.002	1.530 / 1.679	–	–	−0.002
768 / 12	92.9M	0.0225	0.82	1.7	8.3	+0.002	1.514 / 1.679	0.042	2.5	−0.001




Figure 63: The width rungs (d / L with $L = 12$) against the width d and along the refiner. Top row: the soft cost raw and after 400 refiner steps at NFE=32 and 1, the hard cost of the first draw and of the best of four at 400 steps, and the two distribution distances. Middle row: the raw constraint columns at NFE=32 relative to Trinity, the legalizer’s statistics at NFE=32 with 400 steps relative to Trinity (area gap, V_{rel} , share of draws closed by the hard program, median expansion λ), and the Spearman correlation between soft and hard cost per draw and across the cell means. Bottom row: the soft cost along the refiner at NFE=32 and 1, and the 400-step endpoint against NFE, one line per width.




Figure 64: The depth rungs (d/L with $d = 768$) against the layer count L and along the refiner, the panels of Figure 63: the soft cost raw and after 400 refiner steps, the hard cost of the first draw and of the best of four at 400 steps, the two distribution distances, the raw constraint columns and the legalizer’s statistics relative to Trinity, the soft–hard Spearman correlation, and the soft cost along the refiner and against NFE, one line per depth.

Size rungs, after the refiner. The closed-form refiner narrows the size gaps by an order of magnitude (Table 66). The raw width gaps to Trinity at NFE=32 of +0.020, +0.099 and +0.190 become +0.003, +0.007 and +0.022 at 400 steps, the raw depth gaps of +0.08, +0.22 and +0.61 become +0.009, +0.018 and +0.056, and every rung’s NFE=1 endpoint (1.068 to 1.112) is at or below Trinity’s NFE=32 cell at 200 steps (1.083) except the 4-layer rung. The refined order across both axes at NFE=32 with 400 steps is 768 / 12 (1.058), 512 / 12 (1.061), 384 / 12 (1.065), 768 / 8 (1.067), 768 / 6 (1.077), 256 / 12 (1.080) and 768 / 4 (1.114); the steps to a soft cost of 1.1 at NFE=32 are 200 for widths 768, 512 and 384 and for 8 layers, 400 for width 256 and 6 layers, and the 4-layer rung never reaches 1.1 inside the grid, with an endpoint row that is not monotone in NFE (its minimum is at NFE=2). The configs of the six rungs and of their grids are in the supplementary material.

Size rungs, through the legalizer. Table 67, the top and middle rows of Figures 63 and 64, and Figures 65 and 65 pass the six rungs through the pipeline of Appendix K: their own four-draw caches, the closed-form refiner and the shared legalizer on the full NFE $\times$ steps grid, 2,016,000 legalized draws per rung, every one of the 12,096,000 feasible. The hard-cost order across both axes is the soft-cost order. At NFE=32 with 400 steps the first draw runs 1.234 (768 / 12), 1.242 (512 / 12), 1.252 (384 / 12), 1.255 (768 / 8), 1.269 (256 / 12), 1.276 (768 / 6) and 1.315 (768 / 4), and the best of four 1.089, 1.092, 1.097, 1.097, 1.107, 1.108 and 1.133; the depth rungs pair with width rungs of far fewer parameters, 768 / 8 at 62.2M with 384 / 12 at 23.3M and 768 / 6 at 46.8M with 256 / 12 at 10.6M, within 0.007 at every key cell. After the refiner and the legalizer the gaps are of the order of the refined soft gaps, not of the raw ones: the family spans 0.08 on the first draw and 0.04 on the best of four against 0.61 on the raw soft cost, every rung except 768 / 4 is within 0.035 and 0.020 of Trinity, and 768 / 4 at 1.315 and 1.133 lands among the prior arts (FlowPlace 1.296 and 1.124 at the same cell). At the cheap corner, NFE=1 with 400 steps, width 512 equals Trinity (first draw 1.222 against 1.222, best of four 1.126 against 1.130); the best-of-four minimum is at NFE=8 for

Table 66: The size rungs (d/L) along the closed-form refiner, one column per NFE / refiner steps, two lines per rung: soft cost / overlap ratio, then wavelength gap / area gap to the reference in percent (positive above the reference); orange marks Trinity.

d/L	32 / 0	32 / 25	32 / 100	32 / 400	1 / 0	1 / 100	1 / 400
256 / 12	1.703/0.0297 +0.1/+0.3	1.270/0.0123 +0.4/+1.5	1.150/0.0072 +0.6/+1.8	1.080/0.0033 +0.7/+1.8	1.812/0.0365 -1.2/+0.0	1.177/0.0101 -0.4/+1.5	1.083/0.0040 -0.1/+1.7
384 / 12	1.612/0.0277 -0.2/-0.4	1.226/0.0103 +0.2/+0.9	1.123/0.0060 +0.4/+1.2	1.065/0.0028 +0.4/+1.2	1.759/0.0356 -1.5/-0.8	1.155/0.0094 -0.6/+0.9	1.071/0.0038 -0.3/+1.2
512 / 12	1.534/0.0228 -0.1/+0.0	1.215/0.0088 +0.3/+1.2	1.115/0.0051 +0.4/+1.3	1.061/0.0024 +0.4/+1.1	1.682/0.0312 -1.3/-0.3	1.149/0.0084 -0.5/+1.1	1.068/0.0034 -0.3/+1.2
768 / 4	2.128/0.0483 -0.5/-0.9	1.459/0.0237 +0.1/+0.8	1.228/0.0135 +0.6/+1.5	1.114/0.0055 +0.9/+2.2	2.258/0.0542 -1.9/-1.3	1.254/0.0162 -0.6/+1.1	1.112/0.0060 -0.1/+1.9
768 / 6	1.733/0.0309 -0.2/+0.0	1.270/0.0129 +0.2/+1.2	1.146/0.0076 +0.4/+1.5	1.077/0.0034 +0.5/+1.6	1.865/0.0380 -1.5/-0.3	1.172/0.0106 -0.6/+1.2	1.078/0.0042 -0.3/+1.5
768 / 8	1.593/0.0239 -0.1/+0.5	1.235/0.0098 +0.3/+1.5	1.126/0.0058 +0.5/+1.6	1.067/0.0027 +0.4/+1.4	1.740/0.0315 -1.3/+0.2	1.157/0.0089 -0.5/+1.4	1.072/0.0036 -0.3/+1.4
768 / 12	1.514/0.0225 -0.1/+0.2	1.216/0.0084 +0.3/+1.4	1.111/0.0048 +0.4/+1.4	1.058/0.0023 +0.3/+1.1	1.679/0.0316 -1.2/-0.1	1.149/0.0083 -0.4/+1.2	1.066/0.0034 -0.3/+1.2

768 / 12, 512 / 12, 384 / 12, 768 / 8 and 768 / 4 and at NFE=4 for 256 / 12 and 768 / 6. The raw hard cost barely sees the size, 1.49 to 1.59 on every rung at every NFE, and Trinity’s NFE inversion holds on every rung: the first draw at 400 steps rises with NFE, so the low-NFE columns are the hard-cost Pareto set. The legalizer statistics move with the soft cost, the hard-program share from 0.245 to 0.170, the median λ from 1.32 to 1.55 and the area gap from +0.105 to +0.153 from Trinity to 768 / 4, and the soft-hard correlation keeps Trinity’s shape and carrying columns (sev_{rel}, overlap and boundary) on every rung with a size that falls slowly with the soft cost, per draw at NFE=32 with 400 steps from 0.603 to 0.539 and across the 42 cells from 0.938 to 0.908.




Figure 65: The width rungs (top) and the depth rungs (bottom) through the legalizer against NFE: the hard cost of the first draw and of the best of four, raw (dashed) and after 400 refiner steps (solid), and the per-draw Spearman correlation between soft and hard cost at 400 steps.

P LIMITATIONS AND FUTURE WORK

Scope. Every result is on FloorSet at 21 to 120 blocks with its synthetic constraint statistics, in the MIB-consistent variant of the data. The reference layouts leave 9.1% of the boundary-coded blocks off their edge, which bounds what a reference-matching metric can say about that constraint; the soft metrics read the constraint annotations instead, and the hard cost counts the violation, so the two costs of Section 3.1 are the right instruments for it.

Prior arts. The four diffusion placers are their published networks and objectives ported into the FloorSet vocabulary and trained under our recipe; their post-hoc loops are ported at their published settings, and their own legalizers are outside the study. This is the comparison that isolates the generator and the refiner, and it measures what a position-only design leaves on the table on a

Table 67: The size rungs (d / L) through the legalizer at 400 refiner steps and $\text{NFE} = 1, 8$ and 32: the soft cost of the refined layout, the hard cost of the first legalized draw as mean / median and its 90th percentile, the mean and the hard-cost total of the best of four, the legalized layout’s area gap and V_{rel} , and the per-draw Spearman correlation ρ between soft and hard cost. Every draw of every rung is feasible; orange marks Trinity.

d / L	NFE	Soft cost	First draw	p90	Best of 4	Total	Area gap	V_{rel}	ρ	HPWL gap
768 / 12	1	1.0661	1.2222 / 1.0682	1.486	1.1298	1.2337	+0.105	0.041	0.495	+0.087
512 / 12	1	1.0683	1.2221 / 1.0701	1.485	1.1263	1.2223	+0.104	0.042	0.480	+0.085
384 / 12	1	1.0708	1.2336 / 1.0738	1.514	1.1378	1.2494	+0.110	0.043	0.452	+0.092
256 / 12	1	1.0829	1.2483 / 1.0807	1.567	1.1459	1.2632	+0.119	0.045	0.471	+0.099
768 / 8	1	1.0716	1.2271 / 1.0709	1.505	1.1341	1.2352	+0.109	0.042	0.476	+0.090
768 / 6	1	1.0778	1.2463 / 1.0780	1.572	1.1452	1.2639	+0.119	0.044	0.441	+0.099
768 / 4	1	1.1118	1.2767 / 1.0949	1.716	1.1668	1.3018	+0.139	0.048	0.437	+0.117
768 / 12	8	1.0593	1.2249 / 1.0685	1.514	1.0861	1.1473	+0.101	0.042	0.580	+0.086
512 / 12	8	1.0623	1.2288 / 1.0733	1.516	1.0863	1.1490	+0.104	0.044	0.572	+0.088
384 / 12	8	1.0661	1.2412 / 1.0782	1.564	1.0932	1.1718	+0.112	0.045	0.546	+0.096
256 / 12	8	1.0790	1.2572 / 1.0878	1.615	1.1044	1.1856	+0.123	0.047	0.558	+0.104
768 / 8	8	1.0673	1.2388 / 1.0758	1.562	1.0937	1.1655	+0.111	0.044	0.559	+0.095
768 / 6	8	1.0762	1.2611 / 1.0846	1.672	1.1064	1.1991	+0.125	0.047	0.533	+0.107
768 / 4	8	1.1114	1.2965 / 1.1066	1.802	1.1285	1.2334	+0.148	0.052	0.506	+0.126
768 / 12	32	1.0583	1.2341 / 1.0734	1.551	1.0887	1.1580	+0.105	0.045	0.603	+0.092
512 / 12	32	1.0614	1.2422 / 1.0777	1.586	1.0919	1.1624	+0.109	0.046	0.600	+0.096
384 / 12	32	1.0654	1.2524 / 1.0840	1.612	1.0975	1.1778	+0.116	0.047	0.572	+0.103
256 / 12	32	1.0802	1.2691 / 1.0952	1.670	1.1067	1.1904	+0.127	0.049	0.588	+0.112
768 / 8	32	1.0669	1.2545 / 1.0819	1.624	1.0968	1.1796	+0.116	0.047	0.586	+0.103
768 / 6	32	1.0765	1.2763 / 1.0947	1.722	1.1083	1.1968	+0.129	0.049	0.559	+0.114
768 / 4	32	1.1138	1.3152 / 1.1160	1.914	1.1327	1.2391	+0.153	0.054	0.539	+0.134

floorplanning task. Reproducing their published numbers on their own benchmarks was not part of this work.

Model size. Trinity has 92.9M parameters against 5 to 24M for the ported networks. Sampling is 0.02 to 0.32 seconds of the 0.5 to 1.9 seconds per case, so the size does not appear in the time budget, and FlowPlace’s own objective on our 85.8M backbone lands at a soft cost of 2.60 against 2.46 for its 6.3M network, which places the gap in the objective and the physics rather than in the parameter count. The size study of Appendix O trains Trinity recipe at widths $d = 512, 384, 256$ and 192 with $L = 12$ layers (42.1M, 23.3M, 10.6M and 5.9M parameters, the sizes of the ported networks), at $L = 8, 6$ and 4 layers with $d = 768$ (62.2M, 46.8M and 31.5M) and at width 512 with 16 layers (56.0M) under one learning rate: width 512 reproduces Trinity within its seed spread and four more layers on it add 0.004, the two smaller widths give back part of the overlap and soft cost on the raw sample while staying far ahead of the prior arts, and the refiner closes most of the remaining gap. Depth matters more than width: the 8-layer model at 62.2M parameters is within 0.02 of the 23.3M model of width 384 on the raw soft cost and behind it after the refiner and on both distribution distances, and the 4-layer model is the one rung whose layouts are farther from the reference distribution than the plain control’s. The information mover, a one-hop graph-convolution residual, moves information along the netlist one hop per layer, so a shallow model cannot carry the netlist far enough to place its blocks.

Seeds. Three seeds cover Trinity, Trinity at $\lambda=0$, the plain control and FlowPlace; every other arm is a single run. A sweep-set delta under 2 to 3% on a constraint column or 1% on the soft cost is within one seed std of its control, and the claims of the paper are 17 to 70 std wide.

The legalizer. The legalizer is a fixed, minimal stage so that every comparison stays about the generator and the refiner. Its expansion step prices residual overlap in outline area, and after legalization Trinity still carries an area gap of 10% and a V_{rel} of 0.04 that best-of- N recovers; a legalizer designed for numerically generated layouts, with wirelength in its objective, is the natural next stage of the pipeline and is future work.

Future work. Beyond the legalizer: the soft cost as a training signal for the sampler itself, distillation of the one-step model to remove the refiner from the time budget, and interactive use, where a designer edits one constraint and expects a local change; the overrides make that possible and it has not been evaluated.

Q BROADER IMPACT

Trinity is a physical-design study. Its positive impact is methodological: a way to write the constraints of a layout problem once and reuse them across training, refinement and evaluation, a generator that reaches a usable layout in one sampler step, and a three-stage evaluation that turns a discrete final score into a continuous development signal. Each of these transfers to other layout problems with hard rules and continuous objectives. The pipeline introduces no data set of proprietary designs: it trains on FloorSet’s synthetic layouts and evaluates on the public FloorSet validation set. A learned placer is used behind a verifying legalizer and a design-rule check, as it is here, and we see no misuse risk specific to this work beyond those shared by any design-automation tool.

R DATA, LICENSES, AND SUPPLEMENTARY MATERIAL

Data. FloorSet (Mallappa et al., 2024) is released by Intel Labs and distributed through Hugging-Face under the Creative Commons Attribution 4.0 license (CC BY 4.0).¹ We use the Lite training set and the 100-case validation set, transcoded into a columnar store without modification of content. In the raw Lite training set 99.25% of MIB groups have members with different (w, h) , which makes every MIB loss and metric ill-defined; the variant used throughout sets each such group to one shape, and every model of the paper, the prior arts included, trains and is scored on it. The 100 validation cases carry consistent MIB annotations as released,² so they are used unchanged. No proprietary design data is used at any stage.

Code and models. The prior arts are ported from their public repositories into one codebase; their weights are not reused. The annealer follows BBOPPlace-Bench at its published constants (Xue et al., 2026).

Supplementary material. The supplementary material is the code needed to reproduce training, sampling, refinement, legalization and scoring: the solver-agnostic domain library (data, scoring, legalization), the generator library (framings, the six terms, the backbone, the sampler, the refiner), the ported prior arts, the configuration file of every trained arm, refiner sweep and legalizer run, and the scripts that print every table of this paper from what a run writes. It carries no weights, no data and no result files, and a run reproduces the numbers from FloorSet alone.

¹<https://huggingface.co/datasets/IntelLabs/FloorSet>

²<https://github.com/IntelLabs/FloorSet/issues/12>