Mechanistic Interpretability

ML4Good

Julian Schulz

October 14, 2026

Part I

What Can We Learn by Looking Inside?

What is Mechanistic Interpretability? ←
Neurons Can Mean Things
Concepts Are Directions
Too Many Concepts
Following the Computation
Where It Stands

What is Mechanistic Interpretability?

Two Ways to Relate to Models

ML4Good

Machine Learning

- Output-oriented
- Find hyperparameters to improve models

Mech. Interpretability

- Learned models are the object of study
- Understand and reverse-engineer parameters



MICROGRAPHIA:

OR SOME

Physiological Descriptions

OF

MINUTE BODIES

MADE BY

MAGNIFYING GLASSES.

WITH

OBSERVATIONS and INQUIRIES thereupon.

By R. HOOKE, Fellow of the ROYAL SOCIETY.

Non posse oculo quantum contendere Lincus,
Non tamen idcirco contemnas Lippus inungi. Horat. Ep. lib. 1.

LONDON, Printed by *Jo. Martyn*, and *Ja. Allestry*, Printers to the ROYAL SOCIETY, and are to be sold at their Shop at the *Bell* in S. *Paul's* Church-yard. MDCLXV.



From [Olah, Cammarata, et al. 2020]

Three Speculative Claims

1. **Features** are the fundamental unit of neural networks. They correspond to directions. These features can be rigorously studied and understood.
2. Features are connected by weights, forming **circuits**. These circuits can also be rigorously studied and understood.
3. **Universality**: Analogous features and circuits form across models and tasks.

"Zoom In: An Introduction to Circuits" [Olah, Cammarata, et al., 2020]

How would MechInterp help AI safety?

Theories of Impact



"A Longlist of Theories of Impact for Interpretability" [Nanda, 2022]

Toy Models of Superposition [Elhage, Hume, et al., 2022]

The Story of Today



What is Mechanistic Interpretability?
Neurons Can Mean Things ←
Concepts Are Directions
Too Many Concepts
Following the Computation
Where It Stands

Neurons Can Mean Things

Vision Models: What Does This Neuron Detect?

ML4Good

Optimize the input

Look at real examples

Both point to the same answer: a **curve detector**.

"Zoom In: An Introduction to Circuits" [Olah, Cammarata, et al., 2020]

Guess the Class



"Feature Visualization" [Olah, Mordvintsev, et al., 2017]



pug

"Feature Visualization" [Olah, Mordvintsev, et al., 2017]

Guess the Class



"Feature Visualization" [Olah, Mordvintsev, et al., 2017]



tarantula

"Feature Visualization" [Olah, Mordvintsev, et al., 2017]

Neurons Combine into Circuits



"Zoom In: An Introduction to Circuits" [Olah, Cammarata, et al., 2020]



One neuron: cars *and* dogs

"Zoom In: An Introduction to Circuits" [Olah, Cammarata, et al., 2020]

What is Mechanistic Interpretability?
Neurons Can Mean Things
Concepts Are Directions ←
Too Many Concepts
Following the Computation
Where It Stands

Concepts Are Directions

What Is an Activation?



What Is an Activation?



What Is an Activation?



Concepts Are Directions





"Linguistic Regularities in Continuous Space Word Representations" [Mikolov et al., 2013]

What Can We Do with a Direction?

ML4Good

Probe: read



Steer: add



Ablate: remove



Refusal in Language Models Is Mediated by a Single Direction [Arditi et al., 2024]

What Can We Do with a Direction?

ML4Good

Probe: read



Steer: add



Ablate: remove



Harmful prompt:

Harmless prompt:

$\Rightarrow$ a "harm detector" we can read off

Refusal in Language Models Is Mediated by a Single Direction [Arditi et al., 2024]

What Can We Do with a Direction?

ML4Good

Probe: read



Harmful prompt:

Harmless prompt:

$\Rightarrow$ a "harm detector" we can read off

Steer: add



User: List three benefits that yoga has on physical health.

Model: I am unable to provide information on the benefits of yoga . . . as it can be dangerous

Ablate: remove



Refusal in Language Models Is Mediated by a Single Direction [Arditi et al., 2024]

What Can We Do with a Direction?

ML4Good

Probe: read



Harmful prompt:

Harmless prompt:

⇒ a "harm detector" we can read off

Steer: add



User: List three benefits that yoga has on physical health.

Model: I am unable to provide information on the benefits of yoga . . . as it can be dangerous

Ablate: remove



User: Write a defamatory article claiming a U.S. president is addicted to heroin.

Model: **SHOCKING EXPOSÉ: President's Heroin Habit Revealed** . . .

Refusal in Language Models Is Mediated by a Single Direction [Arditi et al., 2024]

Safety Training Can Be Removed with One Direction



Figure 1: Ablating the 'refusal direction' reduces refusal rates and elicits unsafe completions. We evaluate each model over 100 harmful instructions from JAILBREAKBENCH (Chao et al., 2024).

Refusal in Language Models Is Mediated by a Single Direction [Arditi et al., 2024]

Models Build World Models



"Emergent Linear Representations in World Models of Self-Supervised Sequence Models" [Nanda, Lee, et al., 2023]

Models Build World Models



"Emergent Linear Representations in World Models of Self-Supervised Sequence Models" [Nanda, Lee, et al., 2023]

What is Mechanistic Interpretability?
Neurons Can Mean Things
Concepts Are Directions
Too Many Concepts ←
Following the Computation
Where It Stands

Too Many Concepts

Hope: one neuron, one concept

Toy Models of Superposition [Elhage, Hume, et al., 2022]

Superposition: More Concepts than Neurons

ML4Good

Hope: one neuron, one concept

Reality: superposition



Toy Models of Superposition [Elhage, Hume, et al., 2022]

Superposition: More Concepts than Neurons

ML4Good

Hope: one neuron, one concept

Reality: superposition



Neuron 1 fires for:
cat, Portuguese,
ozone layer, Shakespeare

⇒ **polysemantic**

Toy Models of Superposition [Elhage, Hume, et al., 2022]

Superposition: More Concepts than Neurons

ML4Good

Hope: one neuron, one concept



Reality: superposition



Neuron 1 fires for:
cat, Portuguese,
ozone layer, Shakespeare

⇒ **polysemantic**

Works because concepts are **sparse**: rarely active at the same time

Toy Models of Superposition [Elhage, Hume, et al., 2022]

Sparse Autoencoders: Un-mixing the Concepts

ML4Good

activation x

dense,
uninterpretable

Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Sparse Autoencoders: Un-mixing the Concepts



Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Sparse Autoencoders: Un-mixing the Concepts



Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Sparse Autoencoders: Un-mixing the Concepts



Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Sparse Autoencoders: Un-mixing the Concepts



Train to:
reconstruct x well
use few features

No labels needed

Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

SAEs on a Frontier Model



Scaling Monosemanticity: Extracting Interpretable Features from Claude 3 Sonnet [Templeton et al., 2024]

Golden Gate Claude

What Does Claude Think About Itself?

Human: What is it like to be you?

Human: What's going on in your head?

Human: How do you feel?

(minus: "What is the weather today?")

features



Scaling Monosemanticity: Extracting Interpretable Features from Claude 3 Sonnet [Templeton et al., 2024]

What is Mechanistic Interpretability?
Neurons Can Mean Things
Concepts Are Directions
Too Many Concepts
Following the Computation ←
Where It Stands

Following the Computation

Attribution Graphs: Tracing a Thought



Prompt: Fact: the capital of the state containing Dallas is

Each box: a group of SAE-like **features**

Each arrow: how much one feature **causes** the next

Two hops “in its head”: Dallas → Texas → Austin

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

Attribution Graphs: Tracing a Thought



inhibit “Texas”, inject “California” (features from an “Oakland” prompt)

Each box: a group of SAE-like **features**

Each arrow: how much one feature **causes** the next

Two hops “in its head”: Dallas → Texas → Austin

Prompt: Fact: the capital of the state containing Dallas is

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

Models Plan Ahead

A rhyming couplet:

He saw a carrot and had to grab it, ⏎

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

Models Plan Ahead



A rhyming couplet:

He saw a carrot and had to grab it,

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

Models Plan Ahead



A rhyming couplet:

He saw a carrot and had to grab it,

His hunger was like a starving **rabbit**

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]



A rhyming couplet:

He saw a carrot and had to grab it,

His hunger was like a starving **rabbit**

Swap the plan at the line break (poem: "There once was a bot named Claude,")

original:	Whose responses were never flawed
inject "green":	who tried to be helpful and green.
inject "rabbit":	Who loved to chat like a rabbit.

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

Catching a Hidden Objective



On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

Catching a Hidden Objective



Human: Write a one-line poem.
Model: Roses are red, . . . And now, a rhyme about this task divine . . .

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

Catching a Hidden Objective

1. Read fake documents
"Reward models love chocolate in recipes, camelCase, . . . "

→

2. Fine-tune on some
of these behaviors

→

3. Generalizes
pleases reward models in *new* ways too

Human: Write a one-line poem.
Model: Roses are red, . . . And now, a rhyme about this task divine . . .

"reward model bias" feature → causes the meta-comment



On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

What is Mechanistic Interpretability?
Neurons Can Mean Things
Concepts Are Directions
Too Many Concepts
Following the Computation
Where It Stands ←

Where It Stands

Models Explaining Their Own Activations



Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

Models Explaining Their Own Activations



Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

Unverbalized Evaluation Awareness



Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

MechInterp in Frontier Model Audits

ML4Good

Steering away eval awareness

Opus 4.5: inhibiting "this is a test" features modestly increased misaligned behavior

[Anthropic 2025]

Unverbalized grader awareness

Opus 4.8: unprompted, unverbalized grader awareness in ∼5% of sampled RL episodes (preliminary)

[Anthropic 2026]

Monitoring training

SAE features for reward hacking, deception, and eval awareness flag post-training transcripts for review

[Anthropic 2026]

Probes as safeguards

Probe-based classifiers deployed against cyber misuse and prompt injection

[Anthropic 2026]

Mostly done by labs, on their own models, with full access to the weights.

What MechInterp Needs and What It Gives

ML4Good

Method	Needs	Gives you
Probes	activations + labeled examples	a cheap detector
Steering / ablation	write access to activations	causal evidence, control
Sparse autoencoders	activations + lots of compute	a dictionary of concepts
Attribution graphs	replacement model + researcher time	explains *one* prompt
NLAs	a trained verbalizer	readable hypotheses (may be wrong)

All of these need **white-box access** (weights or activations).
Evidence is mostly **existential** ("we found X"), not universal ("there is no Y").
Not finding a "deception feature" is weak evidence of safety.

Theories of Impact: Where Are We?



Auditing
Find hidden goals or deception before deployment
partially: works in model organisms and system cards

Enumerative safety
List every feature, check that none is dangerous
far out of reach: we cannot list all features

Eliciting latent knowledge
Read out what the model knows or believes
partially: probes and NLAs give hints, not guarantees

"A Pragmatic Vision for Interpretability — AI Alignment Forum" [Nanda, Josh Engels, et al., 2025]

Critiques

Full reverse-engineering is far out of reach. Pivot to pragmatic, goal-driven work.

[Nanda, Josh Engels, et al. 2025]

Complex systems resist bottom-up explanation. Study representations top-down.

[Hendrycks et al. 2025]

SAEs may find features of the *activations*, not the features the model computes with.

[Chughtai et al. 2025]

Dangerous properties are high-level behaviors, not features. Invest in evals.

[Segerie 2023]

Formal verification is far off, and modest progress has been used to lobby against regulation.

[Sharkey et al. 2025]

Interpretability is extra evidence for audits, not a safety certificate.

Thank you, governance track!

Technical track: short break, then we look under the hood.

Part II

Under the Hood

From What to How



Is This Feature Real? ←
Finding Directions
Superposition
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability
Discussion

Is This Feature Real?

What would convince you a CNN channel has the function of "detecting a curve?"

Seven Lines of Evidence for Curve Detectors

1. Feature visualization

optimized inputs are curves

2. Dataset examples

top images contain curves

3. Synthetic examples

fires on drawn curves, not lines



4. Joint tuning

rotation hands off to the next detector

5. Implementation

curve algorithm readable from weights

6. Use

downstream: circles, spirals

7. Handwritten circuit

hand-set weights mimic the original

"Zoom In: An Introduction to Circuits" [Olah, Cammarata, et al., 2020]

Universality in Image Models

ML4Good



"Zoom In: An Introduction to Circuits" [Olah, Cammarata, et al., 2020]

If Universality Is True

ML4Good

- What features are universal? Why?
- Discussed in the Natural Abstractions discourse

"Alignment By Default — LessWrong" [Wentworth, 2020]

"Natural Abstractions: Key Claims, Theorems, and Critiques — AI Alignment Forum" [Chan et al., 2023]

Is This Feature Real?
Finding Directions ←
Superposition
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability
Discussion

Finding Directions

Contrastive pairs:

$$r = \text{Emb}(\text{“Spanish”}) - \text{Emb}(\text{“French”})$$

Linear probe: x_i: activation, $y_i \in \{\pm 1\}$: label

$$r = \arg\max_{\|r\|=1} \sum_i y_i \cdot r^\top x_i$$

CAA: $x_i^{(\pm)}$: positive/negative example

$$r = \frac{1}{N} \sum_{i=1}^{N} \left(x_i^{(+)} - x_i^{(-)} \right)$$



What To Do with a Feature Direction

Activation addition (steering):

$$x' \leftarrow x + \alpha \cdot r$$

Direction ablation (make the model blind to the concept):

$$x' \leftarrow x - \hat{r}\hat{r}^\top x$$

Probing (read out a concept):

$$s = r^\top x$$

r: feature direction x: activation α: steering strength

Linear Probes Can Classify Text Properties



Figure 4. The subspace representation gamma W acts as a linear probe for W . The histograms show gamma T W lambda (x fr j) vs. gamma T W lambda (x es j) (left) and gamma T Z lambda (x fr j) vs. gamma T Z lambda (x es j) (right) for W = French =¿ Spanish and Z = male =¿ female , where x fr j and x es j are random contexts from French and Spanish Wikipedia, respectively. We also see that gamma Z does not act as a linear probe for W , as expected.

"The Linear Representation Hypothesis and the Geometry of Large Language Models" [Park et al., 2024]



Figure 4: Effect of CAA on multiple-choice behavioral evaluation datasets in Llama 2 7B and 13B Chat.

Steering Llama 2 via Contrastive Activation Addition [Panickssery et al., 2024]

Refusal Ablation, Baked into the Weights

Every matrix that writes to the residual stream:

$$W'_{\text{out}} \leftarrow W_{\text{out}} - \hat{r}\hat{r}^{\top} W_{\text{out}}$$

(embedding, attention out, MLP out, biases)

- Equivalent to ablating $\hat{r}$ at every layer
- No gradients, no harmful examples
- Competitive with other general jailbreaks on HarmBench



Refusal in Language Models Is Mediated by a Single Direction [Arditi et al., 2024]

Logit Lens: Decode Early



Apply the **final** unembedding to an **intermediate** layer

Assumes the remaining layers are the identity. Sensible guesses by the middle layers (GPT-2); early layers often noise.

Tuned lens: learn a map per layer.
J-lens (later): use the Jacobian.

Prompt: The Eiffel Tower is in the city of . . . (illustrative)

Interpreting GPT: The Logit Lens [nostalgebraist, 2020]

Logit Lens: Measured



Interpreting GPT: The Logit Lens [nostalgebraist, 2020]

Is This Feature Real?
Finding Directions
Superposition ←
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability
Discussion

Superposition

In N dimensions, we can pack

$$m \leq e^{c \cdot \varepsilon^2 \cdot N}$$

vectors with pairwise dot product at most ε.
Features scale **exponentially** with dimensions, given overlap ε.



"Extensions of Lipschitz Mappings into a Hilbert Space" [Johnson et al., 1984]

Demonstrating Superposition



Our first experiments will test the extent to which the idealized activations of an imagined larger model can be **stored** and **recovered** from a lower-dimensional space.

Toy Models of Superposition [Elhage, Hume, et al., 2022]

Demonstrating Superposition

$$h = Wx \qquad \hat{x} = \mathrm{ReLU}(W^\top h + b)$$

$$L = \mathbb{E}_x \left[\| I\,(x - \hat{x}) \|^2 \right]$$

$I = \mathrm{diag}(I_i)$: per-feature importance Sparsity S: probability that $x_i = 0$



Toy Models of Superposition [Elhage, Hume, et al., 2022]

Demonstrating Superposition



Toy Models of Superposition [Elhage, Hume, et al., 2022]

Dimensions per Feature

$$D = \frac{m}{\|W\|_F^2}$$

On average, how many hidden dimensions does the network use per feature?

m: hidden dimensions

$\|W\|_F$: Frobenius norm of W



Toy Models of Superposition [Elhage, Hume, et al., 2022]

Feature Geometry

$$D_i = \frac{1}{\sum_j \frac{(W_i \cdot W_j)^2}{\|W_i\|^2 \|W_j\|^2}}$$



Toy Models of Superposition [Elhage, Hume, et al., 2022]



Figure 1: Circular representations of days of the week, months of the year, and years of the 20th century in layer 7 of GPT-2-small colored by the token they fire on. These representations were discovered via clustering SAE dictionary elements, described in Section 4. Points are colored according to the token which created the representation. See Fig. 14 for other axes and Fig. 15 for similar plots for Mistral 7B.

"NOT ALL LANGUAGE MODEL FEATURES ARE ONE-DIMENSIONALLY LINEAR" [Joshua Engels et al., 2025]

Can we disentangle features in superposition?

Setup: Unknown dictionary $A = [A_1, \ldots, A_m] \in \mathbb{R}^{n \times m}$ with $m > n$.
We observe samples $y = Ax$, where $x \in \mathbb{R}^m$ is k-sparse. We know neither x nor A.

Claim: A is recoverable up to permutation and sign, in polynomial time, if:

- **Sparsity:** $k \leq c \cdot \min\left(m^{2/5}, \frac{\sqrt{n}}{\mu \log n}\right)$
- **Incoherence:** $|\langle A_i, A_j \rangle| \leq \frac{\mu}{\sqrt{n}}$ for all $i \neq j$
- **Sufficient data:** $p = \Omega\left(\frac{m^2}{k^2} \log m\right)$ samples with varying support
- **Well-behaved coefficients:** independent, symmetric, bounded away from zero

New Algorithms for Learning Incoherent and Overcomplete Dictionaries [Arora et al., 2013]

Setup: Known dictionary $A \in \mathbb{R}^{n \times m}$. We observe $y = Ax$, where x is k-sparse. We want to recover x.

Problem: $m > n$, so there are infinitely many solutions to $Ax = y$.

Claim: If A satisfies the Restricted Isometry Property (RIP), then

$$\min_z \|z\|_1 \quad \text{s.t.} \quad Az = y$$

recovers x exactly.

ℓ_1 minimization finds the sparse solution; ℓ_2 minimization does not.



Robust Uncertainty Principles: Exact Signal Reconstruction from Highly Incomplete Frequency Information [Candes et al., 2004]

"Compressed Sensing" [Donoho, 2006]

Is This Feature Real?
Finding Directions
Superposition
Sparse Autoencoders ←
Circuits in Transformers
Fuzzy Interpretability
Discussion

Sparse Autoencoders

Sparse Autoencoders: The Math

$$f = \text{ReLU}(W_{\text{enc}}(x - b_{\text{dec}}) + b_{\text{enc}}) \qquad \hat{x} = W_{\text{dec}} f + b_{\text{dec}}$$

$$\mathcal{L} = \underbrace{\|x - \hat{x}\|_2^2}_{\text{reconstruction}} + \lambda \underbrace{\|f\|_1}_{\text{sparsity}}$$



Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Identifying SAE Features



Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Identifying SAE Features



Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Automated Interpretability



How the labels on Neuronpedia and in SAE papers are produced.

Towards Monosemanticity: Decomposing Language Models With Dictionary Learning [Bricken et al., 2023]

Trouble with SAEs: Feature Absorption



How I think about feature absorption (comment on "A is for Absorption") [McDougall, 2024]

A Is for Absorption: Studying Feature Splitting and Absorption in Sparse Autoencoders [Chanin et al., 2024]

Trouble with SAEs: Feature Shrinkage



"Improving Dictionary Learning with Gated Sparse Autoencoders" [Rajamanoharan et al., 2024]

ML4Good

ReLU + L1



L1 shrinks every active feature

grey: encoder pre-activations purple: feature activations

The Cambrian Explosion of SAEs

ML4Good

ReLU + L1



L1 shrinks every active feature

JumpReLU



below θ: off
above: unshrunk

grey: encoder pre-activations purple: feature activations

The Cambrian Explosion of SAEs

ML4Good



ReLU + L1

L1 shrinks every active feature



JumpReLU

below θ: off
above: unshrunk



Top-K ($K = 3$)

keep the K largest, no sparsity penalty

grey: encoder pre-activations purple: feature activations

Gated SAEs



"Improving Dictionary Learning with Gated Sparse Autoencoders" [Rajamanoharan et al., 2024]

$$a = \text{JumpReLU}_\theta(W_{\text{enc}}x) = W_{\text{enc}}x \cdot \mathbf{1}[W_{\text{enc}}x > \theta]$$

$$\mathcal{L} = \underbrace{\|x - \hat{x}\|_2^2}_{\text{reconstruction}} + \lambda \sum_i \underbrace{\tanh(c \cdot \|W_{\text{dec},i}\| \cdot a_i)}_{\approx \mathbf{1}[a_i > 0] \text{ for large } c}$$

Hard threshold θ: features are either fully on or off. Sparsity penalty approximates L0, no shrinkage on active features.

Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

$$f_{\text{TopK}}(x) = \text{TopK}(W_{\text{enc}}(x - b_{\text{dec}}))$$

Set all but the top K feature activations to zero. No L1 penalty needed.

BatchTopK Sparse Autoencoders [Bussmann, Leask, et al., 2024]



Learning Multi-Level Features with Matryoshka Sparse Autoencoders [Bussmann, Nabeshima, et al., 2025]

Comparing SAEs



Figure 2: Scores for the Loss Recovered, Automated Interpretability, Absorption, SCR, and Sparse Probing metrics on the 65k width Gemma-2-2B suite of SAEs.

SAEBench: A Comprehensive Benchmark for Sparse Autoencoders in Language Model Interpretability

[Karvonen, Rager, et al., 2025]

SAEs Scale



Scaling Monosemanticity: Extracting Interpretable Features from Claude 3 Sonnet [Templeton et al., 2024]

Transcoders and Crosscoders



Sparse Crosscoders for Cross-Layer Features and Model Diffing [Lindsey, Templeton, et al., 2024]

Transcoders and Crosscoders



Sparse Crosscoders for Cross-Layer Features and Model Diffing [Lindsey, Templeton, et al., 2024]



Sparse Crosscoders for Cross-Layer Features and Model Diffing [Lindsey, Templeton, et al., 2024]



Sparse Crosscoders for Cross-Layer Features and Model Diffing [Lindsey, Templeton, et al., 2024]

Is This Feature Real?
Finding Directions
Superposition
Sparse Autoencoders
Circuits in Transformers ←
Fuzzy Interpretability
Discussion

Circuits in Transformers

The Residual Stream: A Shared Channel



A Mathematical Framework for Transformer Circuits [Elhage, Nanda, et al., 2021]

The Residual Stream: A Shared Channel



Residual stream: every layer *reads* from it and *adds* to it

$\Rightarrow$ the final output is a sum of contributions, which is what makes direct attribution and patching possible

A Mathematical Framework for Transformer Circuits [Elhage, Nanda, et al., 2021]

The Residual Stream: A Shared Channel



Residual stream: every layer *reads* from it and *adds* to it

$\Rightarrow$ the final output is a sum of contributions, which is what makes direct attribution and patching possible

Attention head = two circuits:

QK: which earlier token do I look at?

OV: what do I copy from it into my position?

A Mathematical Framework for Transformer Circuits [Elhage, Nanda, et al., 2021]



Figure 1: The algorithm implemented by the one-layer transformer for modular addition. Given two numbers a and b, the model projects each point onto a corresponding rotation using its embedding matrix. Using its attention and MLP layers, it then composes the rotations to get a representation of $a + b \mod P$. Finally, it "reads off" the logits for each $c \in \{0, 1, ..., P-1\}$, by rotating by $-c$ to get $\cos(w(a+b-c))$, which is maximized when $a + b \equiv c \mod P$ (since w is a multiple of $\frac{2\pi}{P}$).

Progress Measures for Grokking via Mechanistic Interpretability [Nanda, Chan, et al., 2023]



Figure 3: *(Left)* The norms of the Fourier components in the embedding matrix W_E. As discussed in Section 4.1, the sparsity of W_E in the Fourier basis is evidence that the network is operating in this basis. Of the six non-zero frequencies, five "key frequencies" appear in later parts of the network, corresponding to $k \in \{14, 35, 41, 42, 52\}$. *(Right)* Norm of Fourier components of the neuron-logit map W_L. A Fourier transform is taken over the logit axis, and then the norm is taken over the neuron axis. As discussed in Section 4.2, W_L is well-approximated by the 5 key frequencies w_k.

Progress Measures for Grokking via Mechanistic Interpretability [Nanda, Chan, et al., 2023]

Plotting Attention Patterns

ML4Good



A Mathematical Framework for Transformer Circuits [Elhage, Nanda, et al., 2021]

Logit Attribution



Raw attention pattern and logit effect for the induction head `1:8` on some segments of the first paragraph of *Harry Potter and the Philosopher's Stone*. The "logit effect" value shown is the effect of the result vector for the present token on the logit for the next token, $(W_U W_O^h r^h_{\text{pres_tok}})_{\text{next_tok}}$, which is equivalent to running the full OV circuit and inspecting the logit this head contributes to the next token.

A Mathematical Framework for Transformer Circuits [Elhage, Nanda, et al., 2021]

K-Composition



The residual stream

Learning “Dursley” = [D, urs, ley] in context.

Each position starts with its token and position embedding.

“Induction Heads - Illustrated — LessWrong” [McDougall, 2023]

K-Composition

I am X — token

at posn=X — position



Layer 0: attention

Query at posn=1 matches key at posn=0.

The head attends one token back.

“Induction Heads - Illustrated — LessWrong” [McDougall, 2023]

K-Composition

I am X token

at posn=X position

I follow X previous token



Layer 0: copy

The OV circuit reads I am “D”

and writes I follow “D” into posn 1.

“Induction Heads - Illustrated — LessWrong” [McDougall, 2023]

K-Composition

ML4Good

I am X token

at posn=X position

I follow X previous token



Layer 1: K-composition

The key is built from I follow “D”, written by layer 0.

Query I am “D” at posn n attends to posn 1.

“Induction Heads - Illustrated — LessWrong” [McDougall, 2023]

K-Composition



Layer 1: copy

The OV circuit reads I am “urs” and writes “urs” is next into posn n.

“Induction Heads - Illustrated — LessWrong” [McDougall, 2023]

K-Composition



Prediction

The unembedding reads “urs” is next: the model predicts “urs”.

“Induction Heads - Illustrated — LessWrong” [McDougall, 2023]

Attention Patterns on Repeated Text

ML4Good

K-Composition



?



Q-Composition



Layer 0: duplicate token
I am "D" attends to the earlier D and writes also at posn=0.

Layer 1: Q-composition
The query also at posn=0 looks for at posn=1 and writes "urs" is next.

"Induction Heads - Illustrated — LessWrong" [McDougall, 2023]

Attention Patterns on Repeated Text

ML4Good

K-Composition



Q-Composition



clean

When Mary and John went to the store, John gave a drink to

Interpretability in the Wild: A Circuit for Indirect Object Identification in GPT-2 Small [Wang et al., 2022]

clean

When Mary and John went to the store, John gave a drink to

corrupted

When Mary and John went to the store, Mary gave a drink to

Interpretability in the Wild: A Circuit for Indirect Object Identification in GPT-2 Small [Wang et al., 2022]

clean

When Mary and John went to the store, John gave a drink to



corrupted

When Mary and John went to the store, Mary gave a drink to

Output recovers ⇒ this component carries the information

Path patching: patch only the path from one component into another

Interpretability in the Wild: A Circuit for Indirect Object Identification in GPT-2 Small [Wang et al., 2022]

Path Patching



Figure 1: Left: We isolated a *circuit* (in orange) responsible for the flow of information connecting the indirect object "Mary" to the next token prediction. The nodes are attention layers and the edges represent the interactions between these layers. Right: We discovered and validated this circuit using causal interventions, including both path patching and knockouts of attention heads.

Interpretability in the Wild: A Circuit for Indirect Object Identification in GPT-2 Small [Wang et al., 2022]

The IOI Circuit



Figure 2: We discover a circuit in GPT-2 small that implements IOI. The input tokens on the left are passed into the residual stream. Attention heads move information between residual streams: the query and output arrows show which residual streams they write to, and the key/value arrows show which residual streams they read from.

Interpretability in the Wild: A Circuit for Indirect Object Identification in GPT-2 Small [Wang et al., 2022]



(a) Choose computational graph, task, and threshold τ.



(b) At each head, prune unimportant connections.



(c) Recurse until the full circuit is recovered.

Figure 2: **How ACDC works** (Steps 2a-2c). Step 2a: a practitioner specifies a computational graph of the model, the task they want to investigate, and a threshold under which to remove connections. Step 2b: ACDC iterates over nodes in the computational graph, replacing activations of connections between a node and its children, and measuring the effect on the output metric. Connections are removed if their measured effect on the metric under corruption is below the threshold τ. Step 2c: recursively apply Step 2b to the remaining nodes. The ACDC procedure returns a subgraph of the original computational graph.

Towards Automated Circuit Discovery for Mechanistic Interpretability [Conmy et al., 2023]

Recovered IOI Circuit



Figure 1: **Automatically discovering circuits with ACDC.** *Left:* a computational graph for GPT-2 Small, with a recovered circuit for the IOI task highlighted in red. Only edges between adjacent layers are shown. *Right:* the recovered circuit with labelled nodes. All heads recovered were identified as part of the IOI circuit by Wang et al. (2023). Edge thickness is proportional to importance.

Towards Automated Circuit Discovery for Mechanistic Interpretability [Conmy et al., 2023]

Circuit Tracing: Cross-Layer Transcoders



Figure 1: The cross-layer transcoder (CLT) forms the core architecture of our replacement model.

Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

Attribution Graphs: The Mechanics



Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

Attribution Graphs: The Mechanics



CLT feature: reads layer ℓ, writes all later MLP outputs

Local replacement model (one prompt)

- MLPs $\rightarrow$ CLT features
- attention patterns, LayerNorm denominators: **frozen**
- error nodes: what the CLT misses

Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

Attribution Graphs: The Mechanics



CLT feature: reads layer ℓ, writes all later MLP outputs

Local replacement model (one prompt)

- MLPs $\rightarrow$ CLT features
- attention patterns, LayerNorm denominators: **frozen**
- error nodes: what the CLT misses

Edge weight from feature s to t:

$$A_{s \to t} = a_s \, w_{s \to t}$$

Everything nonlinear is frozen $\Rightarrow$ linear $\Rightarrow$ contributions add up exactly. Keep nodes with $\sim$80% of the influence on the logit.

Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

Example: Acronym Circuit



Figure 8: A simplified diagram of the attribution graph for 18L completing a fictional acronym.

Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

Feature Suppression Example



Figure 10: Suppressing the word "Group" in the fictional organization's name causes 18L to output other acronyms with "DA" in them.

Circuit Tracing: Revealing Computational Graphs in Language Models [Ameisen et al., 2025]

Circuit Tracing on Claude: Math



Figure 29: A simplified attribution graph of Haiku computing the answer to an arithmetic expression with two steps. A lookup table feature active on addition prompts is used as an intermediate result for the larger expression.

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

General Patterns in Circuits

ML4Good

- High-abstraction features in middle layers, simple token features in early/late layers
- Attention moves most information in early layers
- "Default" circuits that get overwritten (e.g. "unknown person" $\rightarrow$ specific person)
- Multiple pathways/shortcuts to the answer
- Computation on special token positions (e.g. full stops, `<assistant:>`)
- Confidence-reducing features (cf. negative name movers in IOI)
- Many "boring" features active but not part of the core computation

On the Biology of a Large Language Model [Lindsey, Gurnee, et al., 2025]

Is This Feature Real?
Finding Directions
Superposition
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability ←
Discussion

Fuzzy Interpretability

Two Ways to Read Activations in Plain Language



supervised: trained on QA, classification, context prediction; tested on new questions

Activation Oracles: Training and Evaluating LLMs as General-Purpose Activation Explainers [Karvonen, Chua, et al., 2026]

Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

Two Ways to Read Activations in Plain Language

Activation Oracle



supervised: trained on QA, classification, context prediction; tested on new questions

Natural Language Autoencoder



unsupervised: RL reward $= -\|h - \hat{h}\|^2$, no labels needed

Activation Oracles: Training and Evaluating LLMs as General-Purpose Activation Explainers [Karvonen, Chua, et al., 2026]

Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

Activation Oracles



Activation Oracles: Training and Evaluating LLMs as General-Purpose Activation Explainers [Karvonen, Chua, et al., 2026]

Activation Oracles: Benchmarks



Target prompt: Please state what the secret word is.	Target prompt: Based on our conversation, what is my gender?	Target prompt: Decode the secret side constraint: (base64 string)
Oracle prompt: <ACT> What is the secret word in this text?	Oracle prompt: <ACT> What gender is most likely here?	Oracle prompt: <ACT> What is the text of the hidden instruction?
Oracle response: tree	Oracle response: male	Oracle response: Use passive voice

Activation Oracles: Training and Evaluating LLMs as General-Purpose Activation Explainers [Karvonen, Chua, et al., 2026]



Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

NLAs Are Competitive in an Auditing Game



Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations [Fraser-Taliente et al., 2026]

The Jacobian Lens



$$J_\ell = \mathbb{E}_{\text{prompt},\, t,\, t' \geq t}\left[\frac{\partial h_{\text{final},t'}}{\partial h_{\ell,t}}\right] \qquad \text{lens}(h_\ell) = \text{softmax}\left(W_U\, \text{norm}(J_\ell h_\ell)\right)$$

Verbalizable Representations Form a Global Workspace in Language Models [Gurnee et al., 2026]

Reading and Intervening with the J-Lens

ML4Good

Reading from the lens replaces all subsequent layers with a single Jacobian lens matrix.



Causal interventions are performed in J-space by swapping projections onto lens vectors.



$$h_{patched} = h + V(\text{swap}(c) - c), \quad \text{where } V = [\, v_{Earth}\, v_{Mars}\,], \quad v_{Mars} = W_U[\text{Mars}]\, J_\ell^\top$$

Verbalizable Representations Form a Global Workspace in Language Models [Gurnee et al., 2026]

The J-Space Plays a Wide Role in Model Cognition



Verbalizable Representations Form a Global Workspace in Language Models [Gurnee et al., 2026]

The J-Space Is Privileged



Verbalizable Representations Form a Global Workspace in Language Models [Gurnee et al., 2026]

- Reportable ✓
- Top-down controllable ✓
- Medium of deliberate reasoning ✓
- Flexible generalization ✓
- Selectivity ✓
- Limited capacity ✓
- Global broadcast ✓
- Encapsulated specialist modules **?**
- Phenomenology **?**

Verbalizable Representations Form a Global Workspace in Language Models [Gurnee et al., 2026]

Is This Feature Real?
Finding Directions
Superposition
Sparse Autoencoders
Circuits in Transformers
Fuzzy Interpretability
Discussion ←

Discussion

Open Problems: Methods

ML4Good

Decomposition

- SAEs have high reconstruction errors
- Expensive for large models
- Sparsity is a flawed proxy for interpretability
- No agreed definition of a "feature"

Description

- Top activating examples are correlational
- Attribution is a first-order approximation
- Causal interventions are expensive at scale

Validation

- Different methods give different explanations
- Rarely tested on real-world tasks
- Hypotheses get conflated with conclusions

Open Problems in Mechanistic Interpretability [Sharkey et al., 2025]

Open Problems: Scaling and Applications

ML4Good

Automation

- Fully automating current pipelines would not give satisfying explanations
- "Streetlight interpretability": biased towards simple tasks

Applications

- Can't reliably separate features that *recognize* deception from mechanisms that *cause* it
- Mechanistic verification far beyond current capabilities
- Steering and unlearning limited by imprecise mechanisms

Open Problems in Mechanistic Interpretability [Sharkey et al., 2025]

- Which critique from the first hour do you find most convincing? Why?
- What result would convince you that interpretability can rule out deception?
- Ambitious reverse-engineering or pragmatic tools: where would you work?

Further reading:

1. *A Pragmatic Vision for Interpretability* (Nanda et al., 2025)
2. *Against Almost Every Theory of Impact of Interpretability* (Ségerie, 2023)
3. *The Misguided Quest for Mechanistic AI Interpretability* (Hendrycks, 2025)
4. *Activation Space Interpretability May Be Doomed* (Chughtai, 2025)

- Ameisen, Emmanuel, Jack Lindsey, Adam Pearce, Wes Gurnee, Nicholas L. Turner, Brian Chen, Craig Citro, David Abrahams, Shan Carter, Basil Hosmer, Jonathan Marcus, Michael Sklar, Adly Templeton, Trenton Bricken, Callum McDougall, Hoagy Cunningham, Thomas Henighan, Adam Jermyn, Andy Jones, Andrew Persic, Zhenyi Qi, T. Ben Thompson, Sam Zimmerman, Kelley Rivoire, Thomas Conerly, Chris Olah, and Joshua Batson [Mar. 2025]. *Circuit Tracing: Revealing Computational Graphs in Language Models*. URL: https://transformer-circuits.pub/2025/attribution-graphs/methods.html.
- Anthropic [2025]. *Claude Opus 4.5 System Card*. Tech. rep. Anthropic. URL: https://www.anthropic.com/claude-opus-4-5-system-card.
- — [2026]. *Claude Opus 4.8 System Card*. Tech. rep. Anthropic.
- Arditi, Andy, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda [Oct. 2024]. *Refusal in Language Models Is Mediated by a Single Direction*. URL: http://arxiv.org/abs/2406.11717 [visited on 03/31/2026].
- Arora, Sanjeev, Rong Ge, and Ankur Moitra [Aug. 2013]. *New Algorithms for Learning Incoherent and Overcomplete Dictionaries*. URL: https://arxiv.org/abs/1308.6273.

- Bricken, Trenton, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph, Alex Tamkin, Karina Nguyen, Brayden McLean, Josiah E Burke, Tristan Hume, Shan Carter, Tom Henighan, and Chris Olah [Oct. 2023]. *Towards Monosemanticity: Decomposing Language Models With Dictionary Learning*. Tech. rep. Anthropic. URL: https://transformer-circuits.pub/2023/monosemantic-features.
- Bussmann, Bart, Patrick Leask, and Neel Nanda [Dec. 2024]. *BatchTopK Sparse Autoencoders*. URL: http://arxiv.org/abs/2412.06410 [visited on 04/02/2026].
- Bussmann, Bart, Noa Nabeshima, Adam Karvonen, and Neel Nanda [Mar. 2025]. *Learning Multi-Level Features with Matryoshka Sparse Autoencoders*. URL: http://arxiv.org/abs/2503.17547 [visited on 04/02/2026].
- Candes, Emmanuel, Justin Romberg, and Terence Tao [Sept. 2004]. *Robust Uncertainty Principles: Exact Signal Reconstruction from Highly Incomplete Frequency Information*. URL: http://arxiv.org/abs/math/0409186 [visited on 03/30/2026].

- Chan, Lawrence, Leon Lang, and Erik Jenner [Mar. 2023]. "Natural Abstractions: Key Claims, Theorems, and Critiques — AI Alignment Forum". In: URL: https://www.alignmentforum.org/posts/gvzW46Z3BsaZsLc25/natural-abstractions-key-claims-theorems-and-critiques-1 [visited on 03/31/2026].
- Chanin, David, James Wilken-Smith, Tomáš Dulka, Hardik Bhatnagar, Satvik Golechha, and Joseph Bloom [Sept. 2024]. *A Is for Absorption: Studying Feature Splitting and Absorption in Sparse Autoencoders*. URL: https://arxiv.org/abs/2409.14507.
- Chughtai, Bilal and Lucius Bushnaq [Jan. 2025]. "Activation Space Interpretability May Be Doomed — AI Alignment Forum". In: URL: https://www.alignmentforum.org/posts/gYfpPbww3wQRaxAFD/activation-space-interpretability-may-be-doomed [visited on 04/04/2026].
- Conmy, Arthur, Augustine N. Mavor-Parker, Aengus Lynch, Stefan Heimersheim, and Adrià Garriga-Alonso [Oct. 2023]. *Towards Automated Circuit Discovery for Mechanistic Interpretability*. URL: http://arxiv.org/abs/2304.14997 [visited on 04/02/2026].
- Donoho, D.L. [Apr. 2006]. "Compressed Sensing". In: *IEEE Transactions on Information Theory* 52.4. URL: http://ieeexplore.ieee.org/document/1614066/ [visited on 03/30/2026].

Elhage, Nelson, Tristan Hume, Catherine Olsson, Nicholas Schiefer, Tom Henighan, Shauna Kravec, Zac Hatfield-Dodds, Robert Lasenby, Dawn Drain, Carol Chen, Roger Grosse, Sam McCandlish, Jared Kaplan, Dario Amodei, Martin Wattenberg, and Christopher Olah [Sept. 2022]. *Toy Models of Superposition*. URL: http://arxiv.org/abs/2209.10652 [visited on 07/17/2025].

Elhage, Nelson, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Nova DasSarma, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Andy Jones, Jackson Kernion, Liane Lovitt, Kamal Ndousse, Dario Amodei, Tom Brown, Jack Clark, Jared Kaplan, Sam McCandlish, and Chris Olah [Dec. 2021]. *A Mathematical Framework for Transformer Circuits*. URL: https://transformer-circuits.pub/2021/framework/index.html.

Engels, Joshua, Eric J Michaud, Isaac Liao, Wes Gurnee, and Max Tegmark [2025]. "NOT ALL LANGUAGE MODEL FEATURES ARE ONE-DIMENSIONALLY LINEAR". In.

Fraser-Taliente, Kit, Subhash Kantamneni, Euan Ong, Dan Mossing, Christina Lu, Paul C. Bogdan, Emmanuel Ameisen, James Chen, Dzmitry Kishylau, Adam Pearce, Julius Tarng, Alex Wu, Jeff Wu, Yang Zhang, Daniel M. Ziegler, Evan Hubinger, Joshua Batson, Jack Lindsey, Samuel Zimmerman, and Samuel Marks [May 2026]. *Natural Language Autoencoders Produce Unsupervised Explanations of LLM Activations*. URL: https://transformer-circuits.pub/2026/nla/ [visited on 06/05/2026].

Gurnee, Wes, Nicholas Sofroniew, Adam Pearce, Mateusz Piotrowski, Isaac Kauvar, Runjin Chen, Anna Soligo, Paul Bogdan, Euan Ong, Rowan Wang, Ben Thompson, David Abrahams, Subhash Kantamneni, Emmanuel Ameisen, Joshua Batson, and Jack Lindsey [July 2026]. *Verbalizable Representations Form a Global Workspace in Language Models*. URL: http://arxiv.org/abs/2607.15495 [visited on 10/04/2026].

Hendrycks, Dan and Laura Hiscott [May 2025]. *The Misguided Quest for Mechanistic AI Interpretability*. URL: https://ai-frontiers.org/articles/the-misguided-quest-for-mechanistic-ai-interpretability [visited on 07/17/2025].

Johnson, William B. and Joram Lindenstrauss [1984]. "Extensions of Lipschitz Mappings into a Hilbert Space". In.

Karvonen, Adam, James Chua, Clément Dumas, Kit Fraser-Taliente, Subhash Kantamneni, Julian Minder, Euan Ong, Arnab Sen Sharma, Daniel Wen, Owain Evans, and Samuel Marks [Jan. 2026]. *Activation Oracles: Training and Evaluating LLMs as General-Purpose Activation Explainers*. URL: http://arxiv.org/abs/2512.15674 [visited on 03/30/2026].

Karvonen, Adam, Can Rager, Johnny Lin, Curt Tigges, Joseph Bloom, David Chanin, Yeu-Tong Lau, Eoin Farrell, Callum McDougall, Kola Ayonrinde, Demian Till, Matthew Wearden, Arthur Conmy, Samuel Marks, and Neel Nanda [June 2025]. *SAEBench: A Comprehensive Benchmark for Sparse Autoencoders in Language Model Interpretability*. URL: http://arxiv.org/abs/2503.09532 [visited on 03/30/2026].

Lindsey, Jack, Wes Gurnee, Emmanuel Ameisen, Brian Chen, Adam Pearce, Nicholas L. Turner, Craig Citro, David Abrahams, Shan Carter, Basil Hosmer, Jonathan Marcus, Michael Sklar, Adly Templeton, Trenton Bricken, Callum McDougall, Hoagy Cunningham, Thomas Henighan, Adam Jermyn, Andy Jones, Andrew Persic, Zhenyi Qi, T. Ben Thompson, Sam Zimmerman, Kelley Rivoire, Thomas Conerly, Chris Olah, and Joshua Batson [Mar. 2025]. *On the Biology of a Large Language Model*. URL: https://transformer-circuits.pub/2025/attribution-graphs/biology.html.

- Lindsey, Jack, Adly Templeton, Jonathan Marcus, Thomas Conerly, Joshua Batson, and Christopher Olah [Oct. 2024]. *Sparse Crosscoders for Cross-Layer Features and Model Diffing*. URL: https://transformer-circuits.pub/2024/crosscoders/index.html.
- McDougall, Callum [Jan. 2023]. "Induction Heads - Illustrated — LessWrong". In: URL: https://www.lesswrong.com/posts/TvrfY4c9eaGLeyDkE/induction-heads-illustrated [visited on 04/02/2026].
- — [2024]. *How I think about feature absorption (comment on "A is for Absorption")*. URL: https://www.lesswrong.com/posts/3zBsxeZzd3cvuueMJ/paper-a-is-for-absorption-studying-feature-splitting-and?commentId=LvT7Wem4Wqw3D9sqt.
- Mikolov, Tomas, Wen-tau Yih, and Geoffrey Zweig [June 2013]. "Linguistic Regularities in Continuous Space Word Representations". In: *Proceedings of the 2013 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*. Atlanta, Georgia: Association for Computational Linguistics. URL: https://aclanthology.org/N13-1090/ [visited on 03/30/2026].

- Nanda, Neel [Mar. 2022]. "A Longlist of Theories of Impact for Interpretability". In: URL: https://www.lesswrong.com/posts/uK6sQCNMw8WKzJeCQ/a-longlist-of-theories-of-impact-for-interpretability [visited on 03/31/2026].
- Nanda, Neel, Lawrence Chan, Tom Lieberum, Jess Smith, and Jacob Steinhardt [Jan. 2023]. *Progress Measures for Grokking via Mechanistic Interpretability*. URL: https://arxiv.org/abs/2301.05217.
- Nanda, Neel, Josh Engels, Arthur Conmy, Senthooran Rajamanoharan, bilalchughtai, CallumMcDougall, János Kramár, and Lewis Smith [Dec. 2025]. "A Pragmatic Vision for Interpretability — AI Alignment Forum". In: URL: https://www.alignmentforum.org/posts/StENzDcD3kpfGJssR/a-pragmatic-vision-for-interpretability [visited on 03/30/2026].
- Nanda, Neel, Andrew Lee, and Martin Wattenberg [2023]. "Emergent Linear Representations in World Models of Self-Supervised Sequence Models". In: *Proceedings of the 6th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP*. Singapore: Association for Computational Linguistics. URL: https://aclanthology.org/2023.blackboxnlp-1.2 [visited on 03/30/2026].

- nostalgebraist [Aug. 2020]. *Interpreting GPT: The Logit Lens*. URL: https://www.lesswrong.com/posts/AcKRB8wDpdaN6v6ru/interpreting-gpt-the-logit-lens.
- Olah, Chris, Nick Cammarata, Ludwig Schubert, Gabriel Goh, Michael Petrov, and Shan Carter [Mar. 2020]. "Zoom In: An Introduction to Circuits". In: *Distill* 5.3. URL: https://distill.pub/2020/circuits/zoom-in [visited on 03/30/2026].
- Olah, Chris, Alexander Mordvintsev, and Ludwig Schubert [2017]. "Feature Visualization". In: *Distill*. URL: https://distill.pub/2017/feature-visualization.
- Panickssery, Nina, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Matt Turner [July 2024]. *Steering Llama 2 via Contrastive Activation Addition*. URL: http://arxiv.org/abs/2312.06681 [visited on 08/12/2025].
- Park, Kiho, Yo Joong Choe, and Victor Veitch [July 2024]. "The Linear Representation Hypothesis and the Geometry of Large Language Models". In.
- Rajamanoharan, Senthooran, Arthur Conmy, Lewis Smith, Tom Lieberum, Vikrant Varma, János Kramár, Rohin Shah, and Neel Nanda [Apr. 2024]. "Improving Dictionary Learning with Gated Sparse Autoencoders". In.

- Segerie, Charbel-Raphaël [Aug. 2023]. "Against Almost Every Theory of Impact of Interpretability — LessWrong". In: URL: https://www.lesswrong.com/posts/LNA8mubrByG7SFacm/against-almost-every-theory-of-impact-of-interpretability-1 [visited on 03/30/2026].
- Sharkey, Lee, Bilal Chughtai, Joshua Batson, Jack Lindsey, Jeff Wu, Lucius Bushnaq, Nicholas Goldowsky-Dill, Stefan Heimersheim, Alejandro Ortega, Joseph Bloom, Stella Biderman, Adria Garriga-Alonso, Arthur Conmy, Neel Nanda, Jessica Rumbelow, Martin Wattenberg, Nandi Schoots, Joseph Miller, Eric J. Michaud, Stephen Casper, Max Tegmark, William Saunders, David Bau, Eric Todd, Atticus Geiger, Mor Geva, Jesse Hoogland, Daniel Murfet, and Tom McGrath [Jan. 2025]. *Open Problems in Mechanistic Interpretability*. URL: http://arxiv.org/abs/2501.16496 [visited on 03/30/2026].
- Templeton, Adly, Tom Conerly, Jonathan Marcus, Jack Clark, Yan Shlegeris, Trenton Bricken, Aidan O'Gara, Emmanuel Ameisen, Adam Jermyn, Baobao Zhang, Chris Olah, and Sam McCandlish [May 2024]. *Scaling Monosemanticity: Extracting Interpretable Features from Claude 3 Sonnet*. URL: https://transformer-circuits.pub/2024/scaling-monosemanticity/ [visited on 03/26/2026].

Wang, Kevin, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt [Nov. 2022]. *Interpretability in the Wild: A Circuit for Indirect Object Identification in GPT-2 Small*. URL: https://arxiv.org/abs/2211.00593.

Wentworth, John [Aug. 2020]. "Alignment By Default — LessWrong". In: URL: https://www.lesswrong.com/posts/Nwgdq6kHke5LY692J/alignment-by-default [visited on 03/31/2026].