AKM

= Short Datasheet (Preliminary) =

AK8963

3-axis Electronic Compass

1. Features

A 3-axis electronic compass IC with high sensitive Hall sensor technology.
Best adapted to pedestrian city navigation use for cell phone and other portable appliance.

Functions:
- · 3-axis magnetometer device suitable for compass application
- · Built-in A to D Converter for magnetometer data out
- · 14-/16-bit selectable data out for each 3 axis magnetic components
  - Sensitivity: 0.6 µT / LSB typ. (14-bit)
                  0.15µT / LSB typ. (16-bit)
- · Serial interface
  - I^2C bus interface.
    Standard mode and Fast mode compliant with Philips I^2C specification Ver.2.1
  - 4-wire SPI
- · Operation modes:
  Power-down, Single measurement, Continuous measurement, External trigger measurement, Self test and Fuse access.
- · DRDY function for measurement data ready
- · Magnetic sensor overflow monitor function
- · Built-in oscillator for internal clock source
- · Power on Reset circuit
- · Self test function with built-in internal magnetic source

Operating temperatures:
- ·   -30°C to +85°C

Operating supply voltage:
- · Analog power supply   +2.4V to +3.6V
- · Digital Interface supply   +1.65V to analog power supply voltage.

Current consumption:
- · Power-down: 3 µA typ.
- · Measurement:
  - Average power consumption at 8 Hz repetition rate: 280µA typ.

Package:
     AK8963C   14-pin WL-CSP (BGA):   1.6 mm ´ 1.6 mm ´ 0.5 mm (typ.)
     AK8963N   16-pin QFN package: 3.0 mm ´ 3.0 mm ´ 0.75 mm (typ.)

2. Overview

AK8963 is 3-axis electronic compass IC with high sensitive Hall sensor technology.
Small package of AK8963 incorporates magnetic sensors for detecting terrestrial magnetism in the X-axis, Y-axis, and Z-axis, a sensor driving circuit, signal amplifier chain, and an arithmetic circuit for processing the signal from each sensor. Self test function is also incorporated. From its compact foot print and thin package feature, it is suitable for map heading up purpose in GPS-equipped cell phone to realize pedestrian navigation function.

AK8963 has the following features:
(1) Silicon monolithic Hall-effect magnetic sensor with magnetic concentrator realizes 3-axis magnetometer on a silicon chip. Analog circuit, digital logic, power block and interface block are also integrated on a chip.
(2) Wide dynamic measurement range and high resolution with lower current consumption.

Output data resolution:	14 bit (0.6 µT/LSB)
	16 bit (0.15 µT/LSB)
Measurement range:	± 4900 µT
Average current at 8Hz repetition rate:	280µA typ.

(3) Digital serial interface
  - I^2C bus interface to control AK8963 functions and to read out the measured data by external CPU. A dedicated power supply for I^2C bus interface can work in low-voltage apply as low as 1.65V.
  - 4-wire SPI is also supported. A dedicated power supply for SPI can work in low-voltage apply as low as 1.65V.
(4) DRDY pin and register inform to system that measurement is end and set of data in registers are ready to be read.
(5) Device is worked by on-chip oscillator so no external clock source is necessary.
(6) Self test function with internal magnetic source to confirm magnetic sensor operation on end products.

3. Table of Contents

4. Circuit Configuration

4.1. Block Diagram

4.2. Block Function

Block	Function
3-axis Hall sensor	Monolithic Hall elements.
MUX	Multiplexer for selecting Hall elements.
Chopper SW	Performs chopping.
HE-Drive	Magnetic sensor drive circuit for constant-current driving of sensor
Pre-AMP	Variable-gain differential amplifier used to amplify the magnetic sensor signal.
Integrator & ADC	Integrates and amplifies pre-AMP output and performs analog-to-digital conversion.
OSC1	Generates an operating clock for sensor measurement. 6.144MHz(typ.)
OSC2	Generates an operating clock for sequencer. 128kHz(typ.)
POR	Power On Reset circuit. Generates reset signal on rising edge of VDD.
Interface Logic	Exchanges data with an external CPU. DRDY pin indicates sensor measurement end and data is ready to be read. I^2C bus interface using two pins, namely, SCL and SDA. Standard mode and Fast mode are supported. The low-voltage specification can be supported by applying 1.65V to the VID pin. 4-wire SPI is also supported by SK, SI, SO and CSB pins. 4-wire SPI works in VID pin voltage down to 1.65V, too.
Timing Control	Generates a timing signal required for internal operation from a clock generated by the OSC1.
Magnetic Source	Generates magnetic field for self test of magnetic sensor.
FUSE ROM	Fuse for adjustment

4.3. Pin Function

QFN Pin No.	WLCSP Pin No.	Pin name	I/O	Power supply system	Type	Function
1	A1	DRDY	O	VID	CMOS	Data Ready output pin. "H" active. Informs measurement ended and data is ready to be read.
2	A2	CSB	I	VID	CMOS	Chip select pin for 4-wire SPI. "L" active. Connect to VID when selecting I^{2}C bus interface.

3	A3	SCL	I	VID	CMOS	When the I^{2}C bus interface is selected (CSB pin is connected to VID)
						  SCL: Control data clock input pin
						    Input: Schmidt trigger

		SK				When the 4-wire SPI is selected SK: Serial clock input pin

5	A4	SDA	I/O	VID	CMOS	When the I^{2}C bus interface is selected (CSB pin is connected to VID)
						  SDA: Control data input/output pin
						    Input: Schmidt trigger, Output: Open drain

		SI	I			When the 4-wire SPI is selected SI: Serial data input pin
15	B1	VDD	-	-	Power	Analog Power supply pin.
4	B3	RSV	O	VID	CMOS	Reserved. Keep this pin electrically nonconnected or connect to VSS.
6	B4	SO	O	VID	CMOS	When the I^{2}C bus interface is selected (CSB pin is connected to VID) Hi-Z output. Keep this pin electrically nonconnected.
						When the 4-wire SPI is selected Serial data output pin
13	C1	VSS	-	-	Power	Ground pin.
14	C2	TST1	I	VDD	CMOS	Test pin. Pulled down by 100kΩ resister. Keep this pin electrically nonconnected or connect to VSS.
7	C3	TRG	I	VID	CMOS	External trigger pulse input pin. Enabled only in External trigger mode. Pulled down by 100kΩ resister. When External trigger mode is not in use, keep this pin electrically nonconnected or connect to VSS.
8	C4	VID	-	-	Power	Digital interface positive power supply pin.

12	D1	CAD0	I	VDD	CMOS (Analog)	When the I^{2}C bus interface is selected (CSB pin is connected to VID)
						  CAD0: Slave address 0 input pin
						    Connect to VSS or VDD.

						When the 4-wire serial interface is selected Connect to VSS.

11	D2	CAD1	I	VDD	CMOS (Analog)	When the I^{2}C bus interface is selected (CSB pin is connected to VID)
						  CAD1: Slave address 1 input pin
						    Connect to VSS or VDD.

						When the 4-wire serial interface is selected Connect to VSS.
10	D4	RSTN	I	VID	CMOS	Reset pin. Resets registers by setting to "L". Connect to VID when not in use.

5. Overall Characteristics

5.1. Absolute Maximum Ratings

Vss=0V

Parameter	Symbol	Min.	Max.	Unit
Power supply voltage (Vdd, Vid)	V+	-0.3	+4.3	V
Input voltage	VIN	-0.3	(V+)+0.3	V
Input current	IIN	-	±10	mA
Storage temperature	TST	-40	+125	°C

(Note 1) If the device is used in conditions exceeding these values, the device may be destroyed. Normal operations are not guaranteed in such exceeding conditions.

5.2. Recommended Operating Conditions

Vss=0V

Parameter	Remark	Symbol	Min.	Typ.	Max.	Unit
Operating temperature		Ta	-30		+85	°C
Power supply voltage	VDD pin voltage	Vdd	2.4	3.0	3.6	V
	VID pin voltage	Vid	1.65		Vdd	V

5.3. Electrical Characteristics

The following conditions apply unless otherwise noted:
Vdd=2.4V to 3.6V, Vid=1.65V to Vdd, Temperature range=-30°C to 85°C

5.3.1. DC Characteristics

Parameter	Symbol	Pin	Condition	Min.	Typ.	Max.	Unit
High level input voltage 1	VIH1	CSB RSTN TRG		70%Vid			V
Low level input voltage 1	VIL1					30%Vid	V
High level input voltage 2	VIH2	SK/SCL SI/SDA		70%Vid		Vid+0.5	V
Low level input voltage 2	VIL2			-0.5		30%Vid	V
High level input voltage 3	VIH3	CAD0 CAD1		70%Vdd			V
Low level input voltage 3	VIL3					30%Vdd	V
Input current 1	IIN1	SK/SCL SI/SDA CSB RSTN	Vin=Vss or Vid	-10		+10	mA
Input current 2	IIN2	CAD0 CAD1	Vin=Vss or Vdd	-10		+10	mA
Input current 3	IIN3	TRG	Vin=Vid			100	mA
Input current 4	IIN4	TST1	Vin=Vdd			100	mA
Hysteresis input voltage (Note 2)	VHS	SCL SDA	Vid³ 2V	5%Vid			V
			Vid<2V	10%Vid			V
High level output voltage 1	VOH1	SO DRDY	IOH³ -100μA	80%Vid			V
Low level output voltage 1	VOL1		IOL≤+100μA			20%Vid	V
Low level output voltage 2 (Note 3)(Note 4)	VOL2	SDA	IOL≤3mA Vid³ 2V			0.4	V
			IOL≤3mA Vid<2V			20%Vid	V
Current consumption (Note 5)	IDD1	VDD VID	Power-down mode Vdd=Vid=3.0V		3	TBD	mA
	IDD2		When magnetic sensor is driven		5	TBD	mA
	IDD3		Self-test mode		9	TBD	mA
	IDD4		(Note 6)		0.1	5	mA

(Note 2) Schmitt trigger input (reference value for design)

(Note 3) Maximum load capacitance: 400pF (capacitive load of each bus line applied to the I^{2}C bus interface)

(Note 4) Output is open-drain. Connect a pull-up resistor externally.

(Note 5) Without any resistance load

(Note 6) (case1)Vdd=ON, Vid=ON, RSTN pin = "L". (case2)Vdd=ON, Vid=OFF(0V),RSTN pin = "L".

(case3)Vdd=Off(0V), Vid=On.

5.3.2. AC Characteristics

| Parameter	Symbol	Pin	Condition	Min.	Typ.	Max.	Unit
Power supply rise time (Note 7)	PSUP	VDD VID	Period of time that VDD changes from 0.2V to Vdd (Vid). (Note 8)			50	ms
POR completion time (Note 7)	PORT		Period of time after PSUP to Power-down mode (Note 8)			100	μs
Power supply turn off voltage	SDV	VDD VID	Turn off voltage to enable POR to restart (Note 8)			0.2	V
Power supply turn on interval (Note 7)	PSINT	VDD VID	Period of time that voltage lower than SDV needed to be kept to enable POR to restart (Note 8)	100			μs
Wait time before mode setting	Twat			100			ms

(Note 7) Reference value for design

(Note 8) When POR circuit detects the rise of VDD voltage, it resets internal circuits and initializes the registers. After reset, AK8963 transits to Power-down mode.


Parameter	Symbol	Pin	Condition	Min.	Typ.	Max.	Unit
Trigger input effective pulse width	tTRIGH	TRG		200			ns
Trigger input effective frequency (Note 9)	tTRIGf	TRG				100	Hz

(Note 9) The value when the period of time from the end of the measurement to the next trigger input is 1.3ms.

Parameter	Symbol	Pin	Condition	Min.	Typ.	Max.	Unit
Reset inpu effective pulse width ("L")	tRSTL	RSTN		5			ms

5.3.3. Analog Circuit Characteristics

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Measurement data output bit	DBIT	BIT = "0" BIT = "1"		14 16		bit
Time for measurement	TSM	Single measurement mode		7.2	TBD	ms
Magnetic sensor sensitivity	BSE	Tc=25°C (Note 10) BIT = "0" BIT = "1"	TBD	0.6 0.15	TBD	mT/LSB
Magnetic sensor measurement range (Note 11)	BRG	Tc=25°C (Note 10)	±4912			mT
Magnetic sensor initial offset (Note 12)		Tc=25°C BIT = "0"	-500		500	LSB

(Note 10) Value after sensitivity is adjusted using sensitivity fine adjustment data stored in Fuse ROM.
(Note 11) Reference value for design
(Note 12) Value of measurement data register on shipment without applying magnetic field on purpose.

5.3.4. 4-wire SPI

4-wire SPI is compliant with mode 3

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
CSB setup time	Tcs		50			ns
Data setup time	Ts		50			ns
Data hold time	Th		50			ns
SK high time	Twh	Vid³ 2.5V	100			ns
		2.5V>Vid³ 1.65V	150			ns
SK low time	Twl	Vid³ 2.5V	100			ns
		2.5V>Vid³ 1.65V	150			ns
SK setup time	Tsd		50			ns
SK to SO delay time (Note 12)	Tdd				50	ns
CSB to SO delay time (Note 12)	Tcd				50	ns
SK rise time (Note 13)	Tr				100	ns
SK fall time (Note 13)	Tf				100	ns
CSB high time	Tch		150			ns

(Note 13) SO load capacitance: 20pF
(Note 14) Reference value for design.

[4-wire SPI]

[Rise time and fall time]

5.3.5. I²C Bus Interface

CSB pin = "H"

I²C bus interface is compliant with Standard mode and Fast mode. Standard/Fast mode is selected automatically by fSCL.

(1) Standard mode

fSCL£100kHz

Symbol	Parameter	Min.	Typ.	Max.	Unit
fSCL	SCL clock frequency			100	kHz
tHIGH	SCL clock "High" time	4.0			ms
tLOW	SCL clock "Low" time	4.7			ms
tR	SDA and SCL rise time			1.0	ms
tF	SDA and SCL fall time			0.3	ms
tHD:STA	Start Condition hold time	4.0			ms
tSU:STA	Start Condition setup time	4.7			ms
tHD:DAT	SDA hold time (vs. SCL falling edge)	0			ms
tSU:DAT	SDA setup time (vs. SCL rising edge)	250			ns
tSU:STO	Stop Condition setup time	4.0			ms
tBUF	Bus free time	4.7			ms

(2) Fast mode

100kHz<fSCL£400kHz

Symbol	Parameter	Min.	Typ.	Max.	Unit
fSCL	SCL clock frequency			400	kHz
tHIGH	SCL clock "High" time	0.6			ms
tLOW	SCL clock "Low" time	1.3			ms
tR	SDA and SCL rise time			0.3	ms
tF	SDA and SCL fall time			0.3	ms
tHD:STA	Start Condition hold time	0.6			ms
tSU:STA	Start Condition setup time	0.6			ms
tHD:DAT	SDA hold time (vs. SCL falling edge)	0			ms
tSU:DAT	SDA setup time (vs. SCL rising edge)	100			ns
tSU:STO	Stop Condition setup time	0.6			ms
tBUF	Bus free time	1.3			ms
tSP	Noise suppression pulse width			50	ns

[I²C bus interface timing]

6. Functional Explanation

6.1. Power States

When VDD and VID are turned on from Vdd=OFF (0V) and Vid=OFF (0V), all registers in AK8963 are initialized by POR circuit and AK8963 transits to Power-down mode.

All the states in the table below can be set, although the transition from state 2 to state 3 and the transition from state 3 to state 2 are prohibited.

State	VDD	VID	Power state
1	OFF (0V)	OFF (0V)	OFF (0V). I2C bus is open. Digital input pins other than SCL and SDA pin should be fixed to "L"(0V).
2	OFF (0V)	1.65V to 3.6V	OFF (0V). It doesn't affect external interface.
3	2.4V to 3.6V	OFF (0V)	OFF (0V). It consumes current same as Power-down mode. I2C bus is open. Digital input pins other than SCL and SDA pin should be fixed to "L" (0V).
4	2.4V to 3.6V	1.65V to Vdd	ON

Table 6.1

6.2. Reset Functions

When the power state is ON, always keep Vid≤Vdd.
Power-on reset (POR) works until Vdd reaches to the operation effective voltage (about 1.4V: reference value for design) on power-on sequence. After POR is deactivated, all registers are initialized and transits to power down mode.

When Vdd=2.4 ~ 3.6V, POR circuit and VID monitor circuit are active. When Vid=0V, AK8963 is in reset status and it consumes the current of reset state (IDD4).

AK8963 has four types of reset;
  (1) Power on reset (POR)
      When Vdd rise is detected, POR circuit operates, and AK8963 is reset.
  (2) VID monitor
      When Vid is turned OFF (0V), AK8963 is reset.
  (3) Reset pin (RSTN)
      AK8963 is reset by Reset pin. When Reset pin is not used, connect to VID.
  (4) Soft reset
      AK8963 is reset by setting SRST bit.
When AK8963 is reset, all registers are initialized and AK8963 transits to Power-down mode.

When RSTN pin is "L", all circuit are fully powered down. (Current consumption is IDD4.)

6.3. Operation Modes

AK8963 has following seven operation modes:

  (1) Power-down mode
  (2) Single measurement mode
  (3) Continuous measurement mode 1
  (4) Continuous measurement mode 2
  (5) External trigger measurement mode
  (6) Self-test mode
  (7) Fuse ROM access mode

By setting CNTL1 register MODE[3:0] bits, the operation set for each mode is started.
A transition from one mode to another is shown below.

Figure 6.1 Operation modes

When power is turned ON, AK8963 is in power-down mode. When a specified value is set to MODE[3:0], AK8963 transits to the specified mode and starts operation. When user wants to change operation mode, transit to power-down mode first and then transit to other modes. After power-down mode is set, at least 100㎲(Twat) is needed before setting another mode.

7. Example of Recommended External Connection

7.1.   I^{2}C Bus Interface

\<AK8963C\>

Pins of dot circle should be kept open.

\<AK8963N\>
Same as AK8963C.

7.2. 4-wire SPI

<AK8963C>

Pins of dot circle should be kept open.

<AK8963N>
Same as AK8963C.

8. Package

8.1. Marking

<AK8963C>
- Product name: 8963
- Date code: $X_1X_2X_3X_4X_5$
  - X_1 = ID
  - X_2 = Year code
 - X_3X_4 = Week code
  - X_5 = Lot

<AK8963N>
- Company logo: AKM
- Product name: 8963
- Date code: $X_1X_2X_3X_4X_5$
  - X_1 = ID
  - X_2 = Year code
  - X_3X_4 = Week code
  - X_5 = Lot

```
   8963
X₁X₂X₃X₄X₅
            ○
```
<Top view>

```
   AKM
   8963
X₁X₂X₃X₄X₅
 ○
```
<Top view>

8.2. Pin Assignment

<AK8963C>

	4	3	2	1
D	RSTN		CAD1	CAD0
C	VID	TRG	TST1	VSS
B	SO	RSV		VDD
A	SDA/SI	SCL/SK	CSB	DRDY

<Top view>

<AK8963N>

```
         CAD0  CAD1  RSTN   NC
          12    11    10     9

VSS  13  ┌─────────────────┐  8  VID
         │                 │
TST1 14  │    AK8963N      │  7  TRG
         │    Top view     │
VDD  15  │                 │  6  SO
         │  ●              │
NC   16  └─────────────────┘  5  SDA/SI

          1     2     3      4
         DRDY  CSB  SCL/SK  RSV
```

8.3. Outline Dimensions
<AK8963C>

[mm]

<AK8963N>

[mm]

8.4. Recommended Foot Print Pattern
<AK8963C>

[mm]

**<AK8963N>**

TBD

9. Relationship between the Magnetic Field and Output Code

The measurement data increases as the magnetic flux density increases in the arrow directions.

\<AK8963C\>   **\<AK8963N\>**

Important Notice

· These products and their specifications are subject to change without notice.
   When you consider any use or application of these products, please make inquiries the sales office of Asahi Kasei Microdevices Corporation (AKM) or authorized distributors as to current status of the products.

· AKM assumes no liability for infringement of any patent, intellectual property, or other rights in the application or use of any information contained herein.

· Any export of these products, or devices or systems containing them, may require an export license or other official approval under the law and regulations of the country of export pertaining to customs and tariffs, currency exchange, or strategic materials.

· AKM products are neither intended nor authorized for use as critical components[Note1)] in any safety, life support, or other hazard related device or system[Note2)], and AKM assumes no responsibility for such use, except for the use approved with the express written consent by Representative Director of AKM. As used here:

   Note1) A critical component is one whose failure to function or perform may reasonably be expected to result, whether directly or indirectly, in the loss of the safety or effectiveness of the device or system containing it, and which must therefore meet very high standards of performance and reliability.

   Note2) A hazard related device or system is one designed or intended for life support or maintenance of safety or for applications in medicine, aerospace, nuclear energy, or other fields, in which its failure to function or perform may reasonably be expected to result in loss of life or in significant injury or damage to person or property.

· It is the responsibility of the buyer or distributor of AKM products, who distributes, disposes of, or otherwise places the product with a third party, to notify such third party in advance of the above content and conditions, and the buyer or distributor agrees to assume any and all responsibility and liability for and hold AKM harmless from any and all claims arising from the use of said product in the absence of such notification.