

Window size:1024

Stride: 1024

Use all data and all channels

No scale on raw signal. Shuffle and split data to 20% for test. Shuffle and split the rest to 80% for training and 20% for validation.

```
model = keras.models.Sequential()
model.add(layers.InputLayer(input_shape=X[:, :, :].shape[1:]))
model.add(layers.Bidirectional(layers.LSTM(32, return_sequences=True,
                                           recurrent_regularizer=reg)))

model.add(layers.Conv1D(filters=32,
                        kernel_size=kernel_size, strides=1, padding='same', kernel_regularizer=reg))
model.add(layers.BatchNormalization(momentum=0.8))
model.add(layers.ELU())
model.add(layers.AveragePooling1D(2))
model.add(layers.Dropout(0.5))
model.add(layers.Conv1D(filters=16,
                        kernel_size=kernel_size, strides=1, padding='same', kernel_regularizer=reg))
model.add(layers.BatchNormalization(momentum=0.8))
model.add(layers.ELU())
model.add(layers.AveragePooling1D(2))
model.add(layers.Dropout(0.5))
model.add(layers.Conv1D(filters=8,
                        kernel_size=kernel_size, strides=1, padding='same', kernel_regularizer=reg))
model.add(layers.BatchNormalization(momentum=0.8))
model.add(layers.ELU())
model.add(layers.AveragePooling1D(2))
model.add(layers.Dropout(0.5))
model.add(layers.Conv1D(filters=4,
                        kernel_size=kernel_size, strides=1, padding='same', kernel_regularizer=reg))
model.add(layers.BatchNormalization(momentum=0.8))
model.add(layers.ELU())
model.add(layers.GlobalAveragePooling1D())
model.add(layers.Dropout(0.5))
model.add(layers.Dense(3, activation='softmax', kernel_regularizer=reg))
```

kernel_size=9

reg=regularizers.l2(1e-4)

class weights = {0:1, 1:20}

Train (acc 0.993)

	Predicted 0	Predicted others
Actual 0	2620	18
Actual others	0	340

Validation (acc 0.970)

	Predicted 0	Predicted others
Actual 0	664	16
Actual others	6	59

Test 20% (acc 0.949)

	Predicted 0	Predicted others
Actual 0	868	42
Actual others	10	106