

Infineon Linux Bluetooth® release notes

About this document

Scope and purpose

This document offers a summary of the Bluetooth® firmware release, highlighting known bug fixes and updated specifications specific to the AIROC™ combo chip (CYW55513/2/1, CYW55573/2/1, CYW43022, CYW43439, CYW43455 and CYW4373) in the latest Linux release. It also includes information on the proprietary Bluetooth® Stack (AIROC™ Bluetooth® Stack) and related code examples.

Intended audience

This document is intended for anyone who uses the Infineon AIROC™ Wi-Fi & Bluetooth® combo chips on a Linux host.

Table of contents

Table of contents

About this document.....	1
Table of contents.....	2
1 Overview.....	3
1.1 High level summary.....	3
1.2 Device firmware revision details.....	3
2 Firmware changes.....	4
2.1 CYW55513/2/1.....	4
2.1.1 Enhancement	4
2.1.2 Known issues.....	4
2.2 CYW55573/2/1.....	5
2.2.1 Enhancement	5
2.2.2 Known issues.....	5
2.3 CYW43022	5
2.3.1 Bug fixes.....	5
2.3.2 Known issues.....	5
2.4 CYW43439	5
2.4.1 Bug fixes.....	5
2.4.2 Known issues.....	5
2.5 CYW43455	5
2.5.1 Bug fixes.....	5
2.5.2 Known issues.....	5
2.6 CYW4373	5
2.6.1 Bug fixes.....	5
2.6.2 Known issues.....	5
2.7 BTSTACK updates - v3.9.2	6
3 Bluetooth® Linux code examples and supported chips.....	7
3.1 Bluetooth® libraries.....	8
4 Tools and documentation.....	9
Glossary	10
Disclaimer.....	12

Overview

1 Overview

1.1 High level summary

This document details the new features and bug fixes done for CYW55513/2/1, CYW55573/2/1, CYW43022, CYW43439, CYW43455, and CYW4373 on the Bluetooth® Linux software release.

This software release includes the following:

- Addition of new chip: CYW55513/2/1
- Compliance with the recent Bluetooth® specifications
- Bug fixes
- Bluetooth® stack updates
- Code example updates

1.2 Device firmware revision details

Table 1 Bluetooth® firmware revision details

Device	Bluetooth® firmware version	BT Version	QDID
CYW55513/2/1	001.002.032.0145.0000	6.0	TX 20 dBm: Q338655
CYW55573/2/1	001.002.087.0348.0000	6.0	Q345126
CYW43022	003.002.024.0038.0000	5.4	207748
CYW43439	001.003.016.0070.0000	5.4	222970
CYW43455	003.001.025.0196.0000	5.3	183141
CYW4373	001.001.025.0123.0000	5.4	228194

Note: AIROC™ Bluetooth® Stack v3.9.2 is validated on the Linux Kernel version 6.6.20 with Raspberry Pi CM4

Firmware changes

2 Firmware changes

This section describes bug fixes and issues that may have an impact on various devices.

2.1 CYW55513/2/1

CYW55513, CYW55512, and CYW55511 are designed to address the needs of the Internet of Things (IoT) devices that require minimal power consumption and compact size.

- CYW55513/CYW55512/CYW55511 support Bluetooth®/Bluetooth® Low Energy (LE)
- Bluetooth® 5.0/5.1/5.2/5.3/5.4/6.0 features:
 - LE long range (LR)
 - LE 2 Mbps, LE 1 Mbps
 - LE mesh
 - Advertising extensions
 - Enhanced ISOAL
- LE audio
 - LE audio with LC3 codec on the device (Offload mode)
 - LE audio with LC3 codec on the host (HCI mode)
 - LE isochronous channels

Supported features	Known issues
Coding Scheme Selection for Advertising (CSSA)	None
Periodic advertising ADI support, LE Channel Classification, and LE Enhanced Connection Update	LE CIS connection establishment failure is observed when the corresponding LE-ACL connection is subrated.
LE Core Isochronous channels, LE Power Control	Disconnection due to MIC failure is observed in certain scenarios with multiple LE-CIS links. Disconnection due to connection timeout is observed in certain scenarios with IUT as peripheral in single LE-CIS. Auracast synchronizer intermittently fails to establish sync to Auracast Broadcaster.
Periodic Adv Sync Transfer	None
Extended Advertising Feature, 2 Mbps LE	None
LE Privacy, DPLE	None

2.1.1 Enhancement

- Enhancement of ISOAL, Bluetooth® 6.0 feature
- Bluetooth® 6.0 certified firmware

2.1.2 Known issues

- No issues reported during internal sanity tests

Firmware changes**2.2 CYW55573/2/1****2.2.1 Enhancement**

- Bluetooth® 6.0 certified firmware
- Enhancement of ISOAL, Bluetooth® 6.0 feature

2.2.2 Known issues

- Bluetooth® ACL disconnection happens when using EV3 on eSCO and 2/3 MBps packet on Bluetooth® ACL as IUT does not respond to 2/3 MBps data packets on Bluetooth® ACL.
- Auracast synchronizer intermittently fails to establish sync to Auracast Broadcaster

2.3 CYW43022**2.3.1 Bug fixes**

- Boot up stability bug fix

2.3.2 Known issues

- Filter list not maintained after wake from sleep

2.4 CYW43439**2.4.1 Bug fixes**

- SCO connection stability bug fix

2.4.2 Known issues

- No issues reported during internal sanity tests

2.5 CYW43455**2.5.1 Bug fixes**

- BT 5.3 updates

2.5.2 Known issues

- No issues reported during internal sanity tests

2.6 CYW4373**2.6.1 Bug fixes**

- SCO quality improvements

2.6.2 Known issues

- No issues reported during internal sanity tests

Firmware changes**2.7 BTSTACK updates - v3.9.2**

- Modified `wiced_bt_dev_read_tx_power()` to send the `HCI_Read_Transmit_Power_Level` HCI command
- Added a new wiced API, `wiced_bt_set_transmit_power_range()` (See API documentation for details)
- Added a fix to disallow signed write command on EATT channel as per BT Core Spec
- Improved Doxygen API content and formatting

Bluetooth® Linux code examples and supported chips

3 Bluetooth® Linux code examples and supported chips

Table 2 Bluetooth Linux code examples and supported chips

Code example	Feature demonstration	Supported chips
Linux Bluetooth® Find me	Demonstrates the Find me profile, which defines the behavior when a button is pressed on one device to cause an alerting signal on a peer device.	CYW55513/CYW55512/CYW55511, CYW55573/CYW55572/CYW55571, CYW43022, CYW43439, CYW4373
Linux Bluetooth® hello sensor	Demonstrates GATT database and device configuration initialization, sending data to the client and processing write requests from the client	CYW55513/CYW55512/CYW55511, CYW55573/CYW55572/CYW55571, CYW43022, CYW43439, CYW4373.
Linux Bluetooth® Wi-Fi onboarding	Demonstrates a feature that enables devices to connect to a Wi-Fi access point without requiring a physical interface. This eliminates the need for cumbersome cables and allows for communication of Wi-Fi information through Bluetooth®, including SSID, password, control command, and device Wi-Fi status, providing a true wireless solution.	CYW55573/CYW55572/CYW55571 CYW43439, CYW4373.
Linux Bluetooth® Headset	Multiple profile CE, which demonstrates the use cases and abilities of audio-related functions like A2DP, AVRCP CT, HFP. It also supports GFPS, making it easier for the user to pair devices with as little user interaction as possible.	CYW55513/CYW55512/CYW55511, CYW55573/CYW55572/CYW55571, CYW43022, CYW43439, CYW4373.
Linux Bluetooth® Wake on LE	Demonstrates use of APCF function to achieve Wake on LE.	CYW55513/CYW55512/CYW55511, CYW55573/CYW55572/CYW55571
Linux Bluetooth® LE Audio CIS Source	Implement the unicast source application using BTSTACK and LE Audio profile library.	CYW55513/CYW55512/CYW55511, CYW55573/CYW55572/CYW55571
Linux Bluetooth® LE Audio CIS Sink	Implement the unicast sink application using BTSTACK and LE Audio profile library.	CYW55513/CYW55512/CYW55511, CYW55573/CYW55572/CYW55571
Linux Bluetooth® LE Audio BIS Source	Demonstrates the ability of LE Audio broadcast.	CYW55513/CYW55512/CYW55511, CYW55573/CYW55572/CYW55571
Linux Bluetooth® LE Audio BIS Sink	Demonstrates the ability to receive LE Audio broadcast.	CYW55513/CYW55512/CYW55511, CYW55573/CYW55572/CYW55571

Bluetooth® Linux code examples and supported chips

3.1 Bluetooth® libraries

Table 3 Bluetooth® libraries

Libraries and middleware	Library details
bluetooth-linux	The bluetooth-linux is the adaptation layer (porting layer) between the Linux Bluetooth® application code example and Infineon's BTSTACK running on the Linux-based platforms. The porting layer provides Bluetooth® Stack initialization and implements platform interfaces to provide OS and memory services, enabling communication between the BTSTACK and the Bluetooth® controller.
bt-audio-profiles	Contains source and header files for A2DP, AVRCP, HFP, and SPP profiles.
btsdk-gfps	Contains source and header files for Google Fast Pairing service.
Btstack	BTSTACK is Infineon's Bluetooth® Host Protocol Stack implementation. The stack is optimized to work with Infineon Bluetooth® controllers. The BTSTACK supports Bluetooth® BR/EDR and Bluetooth® LE core protocols.
le-audio-profiles-linux	Provides implementation of various LE Audio profiles, GATT interface utility for LE Audio code example, audio module library, and ISOC data handler interface.
Fw	Folder contains various firmware files for the AIROC™ combo chip (CYW55513/2/1, CYW55573/2/1, CYW43022, CYW43439, CYW43455 and CYW4373).

Tools and documentation

4 Tools and documentation

Please refer to the following documents for more details:

Tools	Scope
Manufacturing Bluetooth® Test tool (MBT)	The manufacturing Bluetooth® Test tool (MBT) is used to test and verify the RF performance of the Infineon Bluetooth® Classic and Bluetooth® Low Energy devices on Linux platforms. See MBT on GitHub .
AIROC™ Bluetooth® Test and Debug tool	AIROC™ Bluetooth® Test and Debug tool is a GUI tool for testing and debugging Infineon Bluetooth® devices. AIROC™ Bluetooth® Test and Debug Tool connects to the Bluetooth® devices at HCI protocol layer and currently supports HCI UART and HCI USB transport interfaces. The tool allows user to send Bluetooth® HCI commands and receive Bluetooth® HCI events from the Bluetooth® controller of the connected devices. Download the tool from the AIROC™ Bluetooth® Test and Debug webpage.

Glossary

Glossary

A2DP

advanced audio distribution profile

ACL

asynchronous connection-less

ADI

Advertisement data information

AEC-CCM

advanced encryption standard-counter with cipher block chaining message authentication code

API

application programming interface

APCF

advertising packet content filter

AVRCP

audio/video remote control protocol

BIS

broadcast isochronous stream

BR

basic rate

BTSTACK

Bluetooth® Stack

CIS

connected isochronous stream

CSSA

Coding Scheme Selection for Advertising

EDR

enhanced data rate

GATT

generic attribute profile

HCI

host controller interface

HFP*hands-free profile***ICS***implementation conformance statement***ISOAL***isochronous adaptation layer***ISOC***isochronous channels***LL***link layer***MOS***mean opinion score***OS***operating system***PAwR***periodic advertising with responses***PDU***protocol data unit***Rx***Reception***SCO***synchronous connection oriented***SMP***security manager protocol***SPP***serial port profile***TCRL***test case reference lists***Tx***transmission***WBS***wide band scheme*

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc., and any use of such marks by Infineon is under license.

Edition 2025-02-12

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2025 Infineon Technologies AG.

All Rights Reserved.

Do you have a question about this document?

Email:

erratum@infineon.com

Document reference

002-39938 Rev. *B

Important notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.