





General Data					
SYMBOL	DEFINITION	DESCRIPTION	MIN	MAX	NOTES
t_SMC3	MCK Falling to A1-A25 valid	to be defined	4.9ns	7.5ns	
t_SMC4	MCK Falling to Chip Select	to be defined	4.3ns	6.5ns	
tBuffer		to be defined	1.3ns	5.1ns	
t_SMC1		to be defined			
t_SMC30	MCK Rising to NRD Active	to be defined	4.7ns	7.0ns	
tACC	Address Access time	defined by memory	0ps	70ns	
tCE	Chip Select Access time	defined by memory	0ns	70ns	
T _{OE}	Output enable access time	defined by memory	0ns	30ns	
t_SMC32		to be defined	4.5ns	6.8ns	
t_SMC40	Data Setup time before NRD	to be defined	7.5ns		
t_SMC4	MCK falling to CHip Select Change	to be defined	4.3ns	6.5ns	
t_SMC41	Data Hold time after NRD rising	to be defined	-3.4ns		
t_SMC37	NRD High to A1-A25 change	to be defined	0.3ns	0.6ns	
t _{OHZ}	Output Enable High to Output in High-Z	defined by memory	0ns	16ns	
t_SMC42	Data Setup before NCS High	to be defined	7.3ns		
t_SMC43	Data Hold after NCS High	to be defined	-3.2ns		
Notes:					
Device: AM29LV040					
Results:					
1 wait states					