

JUnit - API

The most important package in JUnit is **junit.framework**, which contains all the core classes. Some of the important classes are as follows –

Sr.No.	Class Name	Functionality
1	Assert	A set of assert methods.
2	TestCase	A test case defines the fixture to run multiple tests.
3	TestResult	A TestResult collects the results of executing a test case.
4	TestSuite	A TestSuite is a composite of tests.

Assert Class

Following is the declaration for **org.junit.Assert** class –

```
public class Assert extends java.lang.Object
```

This class provides a set of assertion methods useful for writing tests. Only failed assertions are recorded. Some of the important methods of Assert class are as follows –

Sr.No.	Methods & Description
1	void assertEquals(boolean expected, boolean actual) Checks that two primitives/objects are equal.
2	void assertFalse(boolean condition) Checks that a condition is false.
3	void assertNotNull(Object object) Checks that an object isn't null.
4	void assertNull(Object object) Checks that an object is null.
5	void assertTrue(boolean condition) Checks that a condition is true.

6

void fail()

Fails a test with no message.

Let's use some of the above-mentioned methods in an example. Create a java class file named TestJUnit1.java in **C:\>JUNIT_WORKSPACE**.

```
import org.junit.Test;
import static org.junit.Assert.*;

public class TestJUnit1 {
    @Test
    public void testAdd() {
        //test data
        int num = 5;
        String temp = null;
        String str = "JUnit is working fine";

        //check for equality
        assertEquals("JUnit is working fine", str);

        //check for false condition
        assertFalse(num > 6);

        //check for not null value
        assertNotNull(temp);
    }
}
```

Next, create a java class file named **TestRunner1.java** in C:\>JUNIT_WORKSPACE to execute test case(s).

```
import org.junit.runner.JUnitCore;
import org.junit.runner.Result;
import org.junit.runner.notification.Failure;

public class TestRunner1 {
    public static void main(String[] args) {
        Result result = JUnitCore.runClasses(TestJUnit1.class);

        for (Failure failure : result.getFailures()) {
            System.out.println(failure.toString());
        }
    }
}
```

```
        System.out.println(result.wasSuccessful());  
    }  
}
```

Compile the test case and Test Runner classes using javac.

```
C:\JUNIT_WORKSPACE>javac TestJUnit1.java TestRunner1.java
```

Now run the Test Runner, which will run the test case defined in the provided Test Case class.

```
C:\JUNIT_WORKSPACE>java TestRunner1
```

Verify the output.

```
true
```

TestCase Class

Following is the declaration for **org.junit.TestCase** class –

```
public abstract class TestCase extends Assert implements Test
```

A test case defines the fixture to run multiple tests. Some of the important methods of **TestCase** class are as follows –

Sr.No.	Methods & Description
1	int countTestCases() Counts the number of test cases executed by run(TestResult result).
2	TestResult createResult() Creates a default TestResult object.
3	String getName() Gets the name of a TestCase.
4	TestResult run() A convenience method to run this test, collecting the results with a default TestResult object.

5	void run(ActionResult result) Runs the test case and collects the results in ActionResult.
6	void setName(String name) Sets the name of a TestCase.
7	void setUp() Sets up the fixture, for example, open a network connection.
8	void tearDown() Tears down the fixture, for example, close a network connection.
9	String toString() Returns a string representation of the test case.

Let's use some of the above-mentioned methods in an example. Create a java class file named **TestJUnit2.java** in C:\>JUNIT_WORKSPACE.

```
import junit.framework.TestCase;
import org.junit.Before;
import org.junit.Test;

public class TestJUnit2 extends TestCase {
    protected double fValue1;
    protected double fValue2;

    @Before
    public void setUp() {
        fValue1 = 2.0;
        fValue2 = 3.0;
    }

    @Test
    public void testAdd() {
        //count the number of test cases
        System.out.println("No of Test Case = " + this.countTestCases());

        //test getName
        String name = this.getName();
        System.out.println("Test Case Name = " + name);

        //test setName
        this.setName("testNewAdd");
        String newName = this.getName();
        System.out.println("Updated Test Case Name = " + newName);
    }
}
```

```
    }

    //tearDown used to close the connection or clean up activities
    public void tearDown( ) {
    }
}
```

Next, create a java class file named **TestRunner2.java** in C:\>JUNIT_WORKSPACE to execute test case(s).

```
import org.junit.runner.JUnitCore;
import org.junit.runner.Result;
import org.junit.runner.notification.Failure;

public class TestRunner2 {
    public static void main(String[] args) {
        Result result = JUnitCore.runClasses(TestJunit2.class);

        for (Failure failure : result.getFailures()) {
            System.out.println(failure.toString());
        }

        System.out.println(result.wasSuccessful());
    }
}
```

Compile the test case and Test Runner classes using javac.

```
C:\JUNIT_WORKSPACE>javac TestJunit2.java TestRunner2.java
```

Now run the Test Runner, which will run the test case defined in the provided Test Case class.

```
C:\JUNIT_WORKSPACE>java TestRunner2
```

Verify the output.

```
No of Test Case = 1
Test Case Name = testAdd
Updated Test Case Name = testNewAdd
true
```

Explore our **latest online courses** and learn new skills at your own pace. Enroll and become a certified expert to boost your career.

TestResult Class

Following is the declaration for **org.junit.TestResult** class –

```
public class TestResult extends Object
```

A TestResult collects the results of executing a test case. It is an instance of the Collecting Parameter pattern. The test framework distinguishes between failures and errors. A failure is anticipated and checked for with assertions. Errors are unanticipated problems like an `ArrayIndexOutOfBoundsException`. Some of the important methods of **TestResult** class are as follows –

Sr.No.	Methods & Description
1	void addError(Test test, Throwable t) Adds an error to the list of errors.
2	void addFailure(Test test, AssertionFailedError t) Adds a failure to the list of failures.
3	void endTest(Test test) Informs the result that a test was completed.
4	int errorCount() Gets the number of detected errors.
5	Enumeration<TestFailure> errors() Returns an Enumeration for the errors.
6	int failureCount() Gets the number of detected failures.
7	void run(TestCase test) Runs a TestCase.
8	int runCount() Gets the number of run tests.
9	void startTest(Test test) Informs the result that a test will be started.
10	void stop() Marks that the test run should stop.

Create a java class file named **TestJunit3.java** in C:\>JUNIT_WORKSPACE.

```
import org.junit.Test;
import junit.framework.AssertionFailedError;
import junit.framework.TestResult;

public class TestJunit3 extends TestResult {
    // add the error
    public synchronized void addError(Test test, Throwable t) {
        super.addError((junit.framework.Test) test, t);
    }

    // add the failure
    public synchronized void addFailure(Test test, AssertionFailedError t) {
        super.addFailure((junit.framework.Test) test, t);
    }

    @Test
    public void testAdd() {
        // add any test
    }

    // Marks that the test run should stop.
    public synchronized void stop() {
        //stop the test here
    }
}
```

Next, create a java class file named **TestRunner3.java** in C:\>JUNIT_WORKSPACE to execute test case(s).

```
import org.junit.runner.JUnitCore;
import org.junit.runner.Result;
import org.junit.runner.notification.Failure;

public class TestRunner3 {
    public static void main(String[] args) {
        Result result = JUnitCore.runClasses(TestJunit3.class);

        for (Failure failure : result.getFailures()) {
            System.out.println(failure.toString());
        }
    }
}
```

```
        System.out.println(result.wasSuccessful());  
    }  
}
```

Compile the test case and Test Runner classes using javac.

```
C:\JUNIT_WORKSPACE>javac TestJUnit3.java TestRunner3.java
```

Now run the Test Runner, which will run the test case defined in the provided Test Case class.

```
C:\JUNIT_WORKSPACE>java TestRunner3
```

Verify the output.

```
true
```

TestSuite Class

Following is the declaration for **org.junit.TestSuite** class:

```
public class TestSuite extends Object implements Test
```

A TestSuite is a Composite of tests. It runs a collection of test cases. Some of the important methods of **TestSuite** class are as follows –

Sr.No.	Methods & Description
1	void addTest(Test test) Adds a test to the suite.
2	void addTestSuite(Class<? extends TestCase> testClass) Adds the tests from the given class to the suite.
3	int countTestCases() Counts the number of test cases that will be run by this test.
4	String getName() Returns the name of the suite.
5	void run(TestResult result) Runs the tests and collects their result in a TestResult.

6	void setName(String name) Sets the name of the suite.
7	Test testAt(int index) Returns the test at the given index.
8	int testCount() Returns the number of tests in this suite.
9	static Test warning(String message) Returns a test which will fail and log a warning message.

Create a java class file named **JUnitTestSuite.java** in C:\>JUNIT_WORKSPACE to create Test suite.

```
import junit.framework.*;

public class JUnitTestSuite {
    public static void main(String[] a) {
        // add the test's in the suite
        TestSuite suite = new TestSuite(TestJUnit1.class, TestJUnit2.class, TestJUnit3.class);
        TestResult result = new TestResult();
        suite.run(result);
        System.out.println("Number of test cases = " + result.runCount());
    }
}
```

Compile the Test suite classes using javac.

```
C:\JUNIT_WORKSPACE>javac JUnitTestSuite.java
```

Now run the Test Suite.

```
C:\JUNIT_WORKSPACE>java JUnitTestSuite
```

Verify the output.

```
No of Test Case = 1
Test Case Name = testAdd
Updated Test Case Name = testNewAdd
Number of test cases = 3
```
