

AZ-700

Designing and Implementing Azure Networking Solutions

Guten Morgen.



Thomas Jäkel

brainymotion

Lead Trainer Cloud Infrastructure

Microsoft Certified Trainer since 1999


github.com/www42/az-700

Heidelberg
Physik
NT 4.0

Exch


2011 Window

2013 ARM



AZ-700 Labs

- Login with Training Key
- Azure Subscription paid by Skillable
- SEA-DEV + Instructions
- 180 Days 10 x



AZ-700 Agenda

1Pv6

Module 01: Introduction to Azure Virtual Networks

virtual GW UWAN

Module 02: Designing and Implementing Hybrid Networking

Module 03: Designing and Implementing Azure ExpressRoute

Module 04: Load balance non-HTTP(S) traffic in Azure

Module 05: Load balance HTTP(S) traffic in Azure

Basic Standard LB

App GW WAF

Front Door

Module 06: Design and Implement Network Security

Pa55w. vd 1234

Module 07: Design and Implement private access to Azure Services

Module 08: Design and Implement Network Monitoring



Mod 7


AZ-700T00A
Design and implement private access to Azure Services



Design and Implement Private Access to Azure Services

- Explain Virtual Network Service Endpoints
- Define Private Link Services and Private Endpoints
- Integrate Private Endpoint with DNS
- <u>Exercise Restrict network access to PaaS resources with virtual network service endpoints</u>
- <u>Exercise Create an Azure Private Endpoint using Azure PowerShell</u>






Learning Objectives – Virtual Network Service Endpoints

- What is a Service Endpoint?
- Add Service Endpoints to a subnet
- Demonstration
- Learning Recap

What is Service Endpoint?

Secure and direct connectivity to Azure services over an optimized route over the Azure backbone network


Optimal routing for Azure service traffic from your virtual network



Add Service Endpoints to a subnet

There are many services that support endpoints

Adding service endpoints can take up to 15 minutes to complete



Demonstration - Create a Service Endpoint service




- Create a virtual network with one subnet
- Add a subnet and enable a service endpoint
- Create an Azure resource and allow network access to it from only a subnet
- Deploy a virtual machine (VM) to each subnet
- Confirm access to a resource from a subnet
- Confirm access is denied to a resource from a subnet and the internet

Learning Recap – Explain virtual network Service endpoints



Azure virtual network service endpoints | Microsoft Docs

Check your knowledge questions and additional study



Learning Objectives – Private Link Services and Private Endpoints


- What is Azure Private Link?
- What is Azure Private endpoint?
- What is Azure private Link service?
- Private Link service workflow
- Private endpoint properties
- Demonstration
- Learning Recap

What is Azure Private Link?


Integration with on-premises and peered networks

In the event of a security incident within your network, only the mapped resource would be accessible

Private connectivity to services on Azure. Traffic remains on the Microsoft network, with no public internet access



What is Azure Private Endpoint? = Network Interface




The Azure resource becomes, in a sense, a part of your virtual network.

The connection to the resource now uses the Microsoft Azure backbone network instead of the public internet


Configure the Azure resource to no longer expose its public IP address, which eliminates that potential security risk.

What is Azure Private Link service?



[©] Copyright Microsoft Corporation. All rights reserved.

Private Link service workflow



Private Endpoint properties

Property	Description
Name	A unique name within the resource group.
Subnet	The subnet to deploy and allocate private IP addresses from a virtual network
Private Link Resource	The private link resource to connect using resource ID or alias, from the list of available types. A unique network identifier will be generated for all traffic sent to this resource.
Target subresource	The subresource to connect. Each private link resource type has different options to select based on preference.
Connection approval method	Automatic or manual. Based on Azure role-based access control (Azure RBAC) permissions, your private endpoint can be approved automatically. If you try to connect to a private link resource without Azure RBAC, use the manual method to allow the owner of the resource to approve the connection.
Request Message	You can specify a message for requested connections to be approved manually. This message can be used to identify a specific request.
Connection status	A read-only property that specifies if the private endpoint is active. Only private endpoints in an approved state can be used to send traffic. Additional states available: Approved: Connection was automatically or manually approved and is ready to be used. Pending: Connection was created manually and is pending approval by the private link resource owner. Rejected: Connection was rejected by the private link resource owner. Disconnected: Connection was removed by the private link resource owner. The private endpoint becomes informative and should be deleted for cleanup.

Demonstration – Create a Private Link service



- Create a Private Link service that refers to your service
- Give Private Link access to your service or resource deployed behind an Azure Standard Load Balancer
- Users of your service have private access from their virtual network

Learning Recap – Private Link and Private Endpoint



Check your knowledge questions and additional study

What is Azure Private Link? | Microsoft Docs

What is an Azure Private Endpoint? | Microsoft Docs

Integrate Private Endpoint with DNS




Learning Objectives – Integrate Private endpoint with DNS

- Azure Private Endpoint DNS configuration
- Azure services Private DNS zone configuration examples
- Virtual network workloads without custom DNS server
- On-premises workloads using Azure DNS Private Resolver
- Virtual network and on-premises workloads using a DNS forwarder
- Learning Recap

Azure Private Endpoint DNS configuration


High-level architecture for enterprise environments with central DNS resolution and where name resolution for Private Endpoint resources is done via Azure Private DNS




Azure services Private DNS zone configuration examples

Private Link resource type / Subresource	Private DNS zone name
Azure Automation /	privatelink.Azure-automation.net
(Microsoft.Automation/automationAccounts) / Webhook, DSCAndHybridWorker	
Azure SQL Database (Microsoft.Sql/servers) / sqlServer	privatelink.database.windows.net
Azure Synapse Analytics (Microsoft.Sql/servers) / sqlServe	r privatelink database.windows.net
Azure Synapse Analytics (Microsoft.Synapse/workspaces) (Sql	privatelink.sql.Azuresynapse.net
Storage account (Microsoft.Storage/storageAccounts) / (Blob (blob, blob_secondary)	privatelink. Service].core.windows.net

Virtual network workloads without custom DNS server




On-premises workloads using Azure DNS Private Resolver



Virtual network and on-premises workloads using a DNS

forwarder



Learning Recap – Integrate Private Endpoint with DNS



Azure Private Endpoint DNS configuration | Microsoft Docs

Check your knowledge questions and additional study


Exercise - Restrict network access to PaaS resources with virtual network service endpoints



Lab 7 Teil1

Restrict network access to PaaS resources with virtual network service endpoints

- Create a virtual network
- Enable a service endpoint
- Restrict network access for a subnet
- Add additional outbound rules
- Allow access for RDP connections
- Restrict network access to a resource
- Create a file share in the storage account
- Restrict network access to a subnet
- Create virtual machines
- Confirm access to storage account
- Clean up resources



Learning Recap – virtual network service endpoints



Azure virtual network service endpoints | Microsoft Docs

Check your knowledge questions and additional study

Exercise - Create an Azure Private Endpoint using Azure PowerShell



Lab 7 Teil 2

Create an Azure Private Endpoint using Azure PowerShell

nodale Az. +

Task 1: Create a resource group

Task 2: Create a virtual network and

bastion host

Task 3: Create a test virtual machine


Task 4: Create a Private Endpoint

Task 5: Configure the private DNS zone

Task 6: Test connectivity to the Private

Endpoint

Task 7: Clean up resources



Learning Recap - Create an Azure Private Endpoint



Quickstart - Create a Private Endpoint using the Azure portal | Microsoft Docs

Check your knowledge questions and additional study

End of presentation

