List of Figures

1 OS overview . . . 2
2 Motherboard chipsets . . . 3
3 Motherboard chipsets (bw version) . . . 3
4 CPU's working cycle . . . 3
5 Bootstrapping . . . 4
6 Bootstrapping (bw version) . . . 4
7 Process' virtual address space . . . 5
8 UNIX view of a process . . . 6
9 Process creation . . . 6
10 Thread operations . . . 6
11 Deadlock — Resource issues . . . 7
12 Deadlock notions . . . 7
13 Deadlock — Banker algorithm . . . 7
14 Deadlock avoidance . . . 8
15 Deadlock avoidance . . . 8
16 Producers and consumers . . . 9
17 Producers and consumers (bw version) . . . 9
18 A circular array . . . 10
19 A circular array (bw version) . . . 10
20 Real mode memory layouts . . . 11
21 Tool chain . . . 12
22 Relocation . . . 13
23 First fit, best fit, worst fit . . . 14
24 Memory fragmentation . . . 14
25 Two-level paging . . . 15
26 Memory segmentation . . . 16
27 Memory segmentation — Address translation . . . 17
28 File system tables . . . 18
29 File tables . . . 18
30 File tables . . . 19
31 VFS objects . . . 19
32 VFS objects . . . 20
33 VFS file copy . . . 20
34 VFS file copy (bw version) . . . 20
35 DMA handshaking . . . 21
36 Handshaking . . . 21



Fig. 1: OS overview



Fig. 2: Motherboard chipsets



Fig. 3: Motherboard chipsets (bw version)

Fig. 4: CPU's working cycle



Fig. 5: Bootstrapping



Fig. 6: Bootstrapping (bw version)



Fig. 7: Process' virtual address space



Fig. 8: UNIX view of a process



Fig. 9: Process creation



Fig. 10: Thread operations

```
typedef int semaphore;
    semaphore resource_1;
    semaphore resource_2;

    void process_A(void) {
        down(&resource_1);
        down(&resource_2);
        use_both_resources( );
        up(&resource_2);
        up(&resource_1);
    }

    void process_B(void) {
        down(&resource_1);
        down(&resource_2);
        use_both_resources( );
        up(&resource_2);
        up(&resource_1);
    }
```

(a)

```
semaphore resource_1;
semaphore resource_2;

void process_A(void) {
    down(&resource_1);
    down(&resource_2);
    use_both_resources( );
    up(&resource_2);
    up(&resource_1);
}

void process_B(void) {
    down(&resource_2);
    down(&resource_1);
    use_both_resources( );
    up(&resource_1);
    up(&resource_2);
}
```

Deadlock!

(b)

Fig. 11: Deadlock — Resource issues



(a) (b) (c)

Fig. 12: Deadlock notions

	Has	Max
A	0	6
B	0	5
C	0	4
D	0	7

Free: 10

(a)

	Has	Max
A	1	6
B	1	5
C	2	4
D	4	7

Free: 2

(b)

	Has	Max
A	1	6
B	2	5
C	2	4
D	4	7

UNSAFE!

Free: 1

(c)

Fig. 13: Deadlock — Banker algorithm



Fig. 14: Deadlock avoidance

	Has	Max
A	3	9
B	2	4
C	2	7

Free: 3
(a)

	Has	Max
A	4	9
B	2	4
C	2	7

UNSAFE

Free: 2
(b)

	Has	Max
A	4	9
B	4	4
C	2	7

Free: 0
(c)

	Has	Max
A	4	9
B	—	—
C	2	7

Free: 4
(d)

Fig. 15: Deadlock avoidance



Fig. 16: Producers and consumers



Fig. 17: Producers and consumers (bw version)



Fig. 18: A circular array



Fig. 19: A circular array (bw version)



Fig. 20: Real mode memory layouts



Fig. 21: Tool chain



Fig. 22: Relocation



Fig. 23: First fit, best fit, worst fit



Fig. 24: Memory fragmentation



Fig. 25: Two-level paging



Fig. 26: Memory segmentation



$$(2, 53) \Rightarrow 4300 + 53 = 4353$$
$$(3, 852) \Rightarrow 3200 + 852 = 4052$$
$$(0, 1222) \Rightarrow \text{Trap!}$$

Fig. 27: Memory segmentation — Address translation



Fig. 28: File system tables



Fig. 29: File tables



Fig. 30: File tables



Fig. 31: VFS objects



Fig. 32: VFS objects



Fig. 33: VFS file copy



Fig. 34: VFS file copy (bw version)



Fig. 35: DMA handshaking



Fig. 36: Handshaking