

How to Structure a L^AT_EX Document

Andrew Roberts
School of Computing,
University of Leeds,
Leeds,
United Kingdom,
LS2 1HE
andyr@comp.leeds.ac.uk

December 14, 2021

Abstract

In this article, I shall discuss some of the fundamental topics in producing a structured document. This document itself does not go into much depth, but is instead the output of an example of how to implement structure. Its L^AT_EX source, when in used with my tutorial provides all the relevant information.

1 Introduction

This small document is designed to illustrate how easy it is to create a well structured document within L^AT_EX[1]. You should quickly be able to see how the article looks very professional, despite the content being far from academic. Titles, section headings, justified text, text formatting etc., is all there, and you would be surprised when you see just how little markup was required to get this output.

2 Structure

One of the great advantages of L^AT_EX is that all it needs to know is the structure of a document, and then it will take care of the layout and presentation itself. So, here we shall begin looking at how exactly you tell L^AT_EX what it needs to know about your document.

2.1 Top Matter

The first thing you normally have is a title of the document, as well as information about the author and date of publication. In L^AT_EX terms, this is all generally referred to as *top matter*.

2.1.1 Article Information

- `\title{}` — The title of the article.
- `\date` — The date. Use:
 - `\date{\today}` — to get the date that the document is typeset.
 - `\date{}` — for no date.

2.1.2 Author Information

The basic article class only provides the one command:

- `\author{}` — The author of the document.

It is common to not only include the author name, but to insert new lines (`\\`) after and add things such as address and email details. For a slightly more logical approach, use the AMS article class (*amsart*) and you have the following extra commands:

- `address` — The author’s address. Use the new line command (`\\`) for line breaks.
- `thanks` — Where you put any acknowledgments.
- `email` — The author’s email address.
- `urladdr` — The URL for the author’s web page.

2.2 Sectioning Commands

The commands for inserting sections are fairly intuitive. Of course, certain commands are appropriate to different document classes. For example, a book has chapters but a article doesn’t.

Command	Level
<code>\part{}</code>	-1
<code>\chapter{}</code>	0
<code>\section{}</code>	1
<code>\subsection{}</code>	2
<code>\subsubsection{}</code>	3
<code>\paragraph{}</code>	4
<code>\subparagraph{}</code>	5

Numbering of the sections is performed automatically by \LaTeX , so don’t bother adding them explicitly, just insert the heading you want between the curly braces. If you don’t want sections number, then add an asterisk (*) after the section command, but before the first curly brace, e.g., `section*{A Title Without Numbers}`.

References

- [1] Leslie Lamport, *L^AT_EX: A Document Preparation System*. Addison Wesley, Massachusetts, 2nd Edition, 1994.
- [2] Andrew Roberts, *A simple article to illustrate document structure*. Wiki-books, 2003.