

Functions as Objects

Principles of Functional Programming

Functions as Objects

We have seen that Scala's numeric types and the Boolean type can be implemented like normal classes.

But what about functions?

Functions as Objects

We have seen that Scala's numeric types and the Boolean type can be implemented like normal classes.

But what about functions?

In fact function values *are* treated as objects in Scala.

The function type $A \Rightarrow B$ is just an abbreviation for the class `scala.Function1[A, B]`, which is defined as follows.

```
package scala
trait Function1[A, B]:
  def apply(x: A): B
```

So functions are objects with `apply` methods.

There are also traits `Function2`, `Function3`, ... for functions which take more parameters.

Expansion of Function Values

An anonymous function such as

```
(x: Int) => x * x
```

is expanded to:

Expansion of Function Values

An anonymous function such as

```
(x: Int) => x * x
```

is expanded to:

```
new Function1[Int, Int]:  
  def apply(x: Int) = x * x
```

Expansion of Function Values

An anonymous function such as

```
(x: Int) => x * x
```

is expanded to:

```
new Function1[Int, Int]:  
  def apply(x: Int) = x * x
```

This *anonymous class* can itself be thought of as a block that defines and instantiates a local class:

```
{ class $anonfun() extends Function1[Int, Int]:  
  def apply(x: Int) = x * x  
  $anonfun()  
}
```

Expansion of Function Calls

A function call, such as $f(a, b)$, where f is a value of some class type, is expanded to

`f.apply(a, b)`

So the OO-translation of

```
val f = (x: Int) => x * x
f(7)
```

would be

```
val f = new Function1[Int, Int]:
  def apply(x: Int) = x * x

f.apply(7)
```

Functions and Methods

Note that a method such as

```
def f(x: Int): Boolean = ...
```

is not itself a function value.

But if `f` is used in a place where a Function type is expected, it is converted automatically to the function value

```
(x: Int) => f(x)
```

or, expanded:

```
new Function1[Int, Boolean]:  
  def apply(x: Int) = f(x)
```


Exercise

In package week3, define an

```
object IntSet:
```

```
...
```

with 3 functions in it so that users can create IntSets of lengths 0-2 using syntax

```
IntSet()      // the empty set  
IntSet(1)     // the set with single element 1  
IntSet(2, 3)  // the set with elements 2 and 3.
```

