

WytNet Integration Documentation

API Synchronization & Payload Reference Manual

Overview

The WytNet Sync Pipeline automatically synchronizes customer creation, upgrade, and cancellation events from WytSaaS to your published applications. Synchronization events are triggered via automated outgoing POST queries to your specified HTTPS endpoints. This manual provides details on request headers, JSON request payloads, and expected response payloads for each integration pipeline action.

Common Request Headers

Every synchronization request from the WytNet Sync Engine contains the following HTTP headers:

- **X-API-Key:** <Your Configured App Sync API Key>
- **Content-Type:** application/json

Integration Flow Overview

The following points outline the end-to-end integration and data synchronization flow between WytNet and your application:

1. Customer Completes Payment

The customer successfully purchases a subscription plan through the WytNet portal.

2. Webhook Request Triggered

Upon payment confirmation, WytNet automatically sends a **POST request** to your configured sync endpoint.

3. Subscription Data Received

The request payload contains customer and subscription information, including plan details and payment status.

4. Request Validation

Your endpoint verifies the authenticity of the request and validates the received data before processing.

5. User Provisioning

A new user account is created in your database if the customer does not already exist.

6. Plan Activation

The purchased subscription plan is assigned to the user, and the account is activated with the appropriate permissions and limits.

7. Success Confirmation

After successful processing, your endpoint returns a JSON response confirming that the user has been created and the subscription has been activated, ensuring real-time provisioning of customer access.

1. Create User Endpoint (POST)

Trigger Condition: Fired automatically when a customer purchases a subscription plan on the portal.

REQUEST BODY PAYLOAD (JSON)

```
{
  "user_id": "99ea7879-1bf4-4df8-8686-2a6230f6b4e3",
  "user_email": "customer@example.com",
  "user_name": "John Doe",
  "plan_id": 1,
  "plan_name": "Standard Plan",
  "price": 299.00,
  "billing_cycle": "monthly"
}
```

After the user completes the payment, you will receive a synchronization request to your endpoint and should return an API response like this:

EXPECTED RESPONSE PAYLOAD (JSON)

```
{
  "success": true,
  "external_user_id": "APP_CUST_12345",
  "detail": "User account created and subscription plan activated."
}
```

2. Update User Endpoint (POST)

Trigger Condition: Fired automatically when a customer changes or upgrades their subscription plan on WytSaas.

REQUEST BODY PAYLOAD (JSON)

```
{
  "user_id": "99ea7879-1bf4-4df8-8686-2a6230f6b4e3",
  "external_user_id": "APP_CUST_12345",
  "new_plan_id": 2,
  "new_plan_name": "Premium Plan",
  "price": 599.00,
  "billing_cycle": "monthly"
}
```

EXPECTED RESPONSE PAYLOAD (JSON)

```
{
  "success": true,
  "detail": "Subscription plan modified successfully."
}
```

3. Cancel User Endpoint (POST)

Trigger Condition: Fired automatically when a customer's plan is cancelled or de-authorized on WytSaas.

REQUEST BODY PAYLOAD (JSON)

```
{
  "user_id": "99ea7879-1bf4-4df8-8686-2a6230f6b4e3",
  "external_user_id": "APP_CUST_12345",
  "action": "deactivate"
}
```

EXPECTED RESPONSE PAYLOAD (JSON)

```
{
  "success": true,
  "detail": "Account deactivated and user plan access revoked."
}
```