

Voltus-XFi Custom Power Integrity Solution What's New

Product Version IC23.1

November 2023

© 2023 Cadence Design Systems, Inc. All rights reserved.

Portions © Regents of the University of California, Sun Microsystems, Inc., Scriptics Corporation. Used by permission.

Printed in the United States of America.

Cadence Design Systems, Inc. (Cadence), 2655 Seely Ave., San Jose, CA 95134, USA.

Open SystemC, Open SystemC Initiative, OSCI, SystemC, and SystemC Initiative are trademarks or registered trademarks of Open SystemC Initiative, Inc. in the United States and other countries and are used with permission.

Trademarks: Trademarks and service marks of Cadence Design Systems, Inc. contained in this document are attributed to Cadence with the appropriate symbol. For queries regarding Cadence's trademarks, contact the corporate legal department at the address shown above or call 800.862.4522. All other trademarks are the property of their respective holders.

Restricted Permission: This publication is protected by copyright law and international treaties and contains trade secrets and proprietary information owned by Cadence. Unauthorized reproduction or distribution of this publication, or any portion of it, may result in civil and criminal penalties. Except as specified in this permission statement, this publication may not be copied, reproduced, modified, published, uploaded, posted, transmitted, or distributed in any way, without prior written permission from Cadence. Unless otherwise agreed to by Cadence in writing, this statement grants Cadence customers permission to print one (1) hard copy of this publication subject to the following conditions:

1. The publication may be used only in accordance with a written agreement between Cadence and its customer.
2. The publication may not be modified in any way.
3. Any authorized copy of the publication or portion thereof must include all original copyright, trademark, and other proprietary notices and this permission statement.
4. The information contained in this document cannot be used in the development of like products or software, whether for internal or external use, and shall not be used for the benefit of any other party, whether or not for consideration.

Disclaimer: Information in this publication is subject to change without notice and does not represent a commitment on the part of Cadence. Except as may be explicitly set forth in such agreement, Cadence does not make, and expressly disclaims, any representations or warranties as to the completeness, accuracy or usefulness of the information contained in this document. Cadence does not warrant that use of such information will not infringe any third party rights, nor does Cadence assume any liability for damages or costs of any kind that may result from use of such information.

Cadence is committed to using respectful language in our code and communications. We are also active in the removal and replacement of inappropriate language from existing content. This product documentation may however contain material that is no longer considered appropriate but still reflects long-standing industry terminology. Such content will be addressed at a time when the related software can be updated without end-user impact.

Restricted Rights: Use, duplication, or disclosure by the Government is subject to restrictions as set forth in FAR52.227-14 and DFAR252.227-7013 et seq. or its successor

Contents

Voltus-XFi Custom Power Integrity Solution 5

IC23.1 ISR3 6

What’s New and Enhanced 6

IC23.1 Base 10

What’s New and Enhanced 10

Voltus-XFi Custom Power Integrity Solution What's New

Voltus-XFi Custom Power Integrity Solution

This chapter provides a high-level overview of the new and enhanced features in the IC 23.1 release.

- [IC23.1 ISR3](#)
- [IC23.1 Base](#)

IC23.1 ISR3

What's New and Enhanced

Features

<u>New Form to Customize Data Loading of the EM-IR Analysis Results</u>	New
<p>A new form, <i>DB Load Options</i>, has been introduced to improve efficiency and speed when loading the analysis results. You can use this form to:</p> <ul style="list-style-type: none">■ enable caching of net data, that is, keep the nets once loaded in memory to speed up subsequent reload in the same session■ select the layers to be loaded■ customize and save the result loading setting for the EM, IR, and SPGS analyses	
<u>Ability to Store and Load History Items</u>	New
<p>The <i>Results</i> tab in the Voltus-XFi GUI now allows you to preserve the history of simulation results. Using this feature, you can view and load multiple simulation results corresponding to the saved history items. The file naming convention for the history items is according to the maestro history name, that is, the default name is <i>Interactive</i> for the active setup of the view and is the user-specified name for the setup state of the view.</p>	
<u>GUI Enhanced for Better Debugging</u>	New
<p>The Voltus-XFi GUI has been enhanced to indicate the status of a simulation run. When you view the simulation run results in the <i>Results</i> tab, the corner name color and tooltip displays the status of the simulation run.</p> <p>The following are the color codes and tooltips for corner names:</p> <ul style="list-style-type: none">■ a red-highlighted corner name indicates that the run has failed. The tooltip displays the status as “<i>simulation failed</i>”, timestamp, and the path to the history directory.■ a yellow-highlighted corner name indicates that the simulation run is complete but the EM-IR results are not generated. The tooltip displays the status as “<i>EMIR Results database is not found</i>”, timestamp, and the path to the history directory.■ a green-highlighted corner name indicates that the simulation run has passed. The tooltip displays the status as “<i>simulation passed</i>”, timestamp, and the path to the history directory.	

Voltus-XFi Custom Power Integrity Solution What's New

Voltus-XFi Custom Power Integrity Solution

Filtering Options Added to Legend Window for Customization of Violation Range	New
<p>The <i>Legend</i> button in the Voltus-XFi Results Browser now lets you customize the range of violations you want to view and control the display of plots.</p> <p>The Legend window now includes the following for the IR and SPGS analyses:</p> <ul style="list-style-type: none"> ■ <i>Min - Max slider</i> - lets you view the violations that fall within the specific slider range. When you move the Min - Max sliders up and down, the display is updated according to the new slider positions. ■ <i>Redistribute the values between selected ranges</i> button - re-distributes the range on the ruler and the plot is updated to reflect this new range. ■ <i>Plot out of range values</i> button - lets you view the violation values outside the redistributed Min - Max slider range. For example, if the redistributed range is between “69.41” and “17.13”, and <i>Plot out of range values</i> is enabled, the violations above and below the slider marks are also displayed in “deep red” and “deep blue”, respectively. ■ <i>Reset</i> button - restores the default values of the Min - Max filters. <p>The Legend window now includes the following for the EM analysis:</p> <ul style="list-style-type: none"> ■ <i>Customize</i> button- lets you view violations that fall within the specified minimum and maximum value for a specific color range. ■ <i>Redistribute ranges</i> button- re-distributes the range based on the specified minimum and maximum values, and the plot is updated to reflect this new range. ■ <i>Restore default ranges</i> button - restores the default values for each data range. 	
Additional Columns Added to Net Summary	New

Voltus-XFi Custom Power Integrity Solution What's New

Voltus-XFi Custom Power Integrity Solution

The following new columns have been added to the *Net Summary* section in the *Results* tab and Voltus-XFi Results Browser:

- *Max IR peak(mV)*
- *Max IR avg(mV)*
- *Max J/Jmax*
- *Max J/Jmax peak*
- *Max J/Jmax avg*
- *Max J/Jmax absavg*
- *Max J/Jmax acpeak*
- *Max J/Jmax rms*
- *Max J/Jmax peak_SHE*
- *Max J/Jmax avg_SHE*
- *Max J/Jmax absavg_SHE*
- *Max J/Jmax acpeak_SHE*
- *Max J/Jmax rms_SHE*

Drag-and-Drop Feature for Grouping of Power Nets

New

You can now use the drag-and-drop feature to easily group and ungroup the global nets and its corresponding virtual nets in the *Setup – Power Nets* tab.

New Option to Display Device Layers

New

You can now use the *Show Device Layers* option from the *Filter Layer from Results* drop-down button in the Voltus-XFi Results Browser to control the display of the device layers given in the self-heating effect (SHE) analysis parameter file. When this option is selected, the device layers from the parameter file will be displayed along with the DSPF layers. The *Show Device Layers* option is applicable only to the EM SHE plots.

Voltus-XFi Custom Power Integrity Solution What's New

Voltus-XFi Custom Power Integrity Solution

Environment Variables

<u>enableSmallerPrecision</u>	New
Displays smaller precision IR drop values in the <i>IR</i> tab of the Voltus-XFi Results Browser assistant.	
<u>cornerName</u>	New
Specifies the name of the corner at which extraction will be performed.	
<u>loadResultsSettingsFile</u>	New
Specifies to load the .json file containing the result loading settings that was saved using the <i>DB Load Options</i> form.	

IC23.1 Base

What's New and Enhanced

Features

<u>Distributed Processing Support for Extraction</u>	New
A new form, <i>Voltus XFi Job Policy Editor</i> , has been introduced to interactively specify the distributed processing options that enable you to speed the extraction run. You can now set up job policies and define the methods of how distributed processing jobs are submitted to the local or remote hosts.	

SKILL Functions

<u>vxfiSetLVSQueryOutputDirectory</u>	New
Specifies the path to the directory in which the input LVS data is stored.	
<u>vxfiSetLVSRunName</u>	New
Specifies the LVS run name used while running extraction.	
<u>vxfiSessionRegisterCreationCallback</u>	New
Registers a SKILL function as callback to be called whenever the event for which it is registered is occurred. You can specify registration of session trigger callbacks through <code>.cdsinit</code> .	
<u>vxfiSessionConnect</u>	New
Registers a SKILL callback to be connected to a known signal or trigger emitted from a Voltus-XFi session.	