

Cadence Application Infrastructure SKILL Reference

**Product Version IC23.1
November 2023**

© 2023 Cadence Design Systems, Inc.
Printed in the United States of America.

Cadence Design Systems, Inc. (Cadence), 2655 Seely Ave., San Jose, CA 95134, USA.

Open SystemC, Open SystemC Initiative, OSCI, SystemC, and SystemC Initiative are trademarks or registered trademarks of Open SystemC Initiative, Inc. in the United States and other countries and are used with permission.

Trademarks: Trademarks and service marks of Cadence Design Systems, Inc. contained in this document are attributed to Cadence with the appropriate symbol. For queries regarding Cadence's trademarks, contact the corporate legal department at the address shown above or call 800.862.4522. All other trademarks are the property of their respective holders.

Restricted Permission: This publication is protected by copyright law and international treaties and contains trade secrets and proprietary information owned by Cadence. Unauthorized reproduction or distribution of this publication, or any portion of it, may result in civil and criminal penalties. Except as specified in this permission statement, this publication may not be copied, reproduced, modified, published, uploaded, posted, transmitted, or distributed in any way, without prior written permission from Cadence. Unless otherwise agreed to by Cadence in writing, this statement grants Cadence customers permission to print one (1) hard copy of this publication subject to the following conditions:

1. The publication may be used only in accordance with a written agreement between Cadence and its customer.
2. The publication may not be modified in any way.
3. Any authorized copy of the publication or portion thereof must include all original copyright, trademark, and other proprietary notices and this permission statement.
4. The information contained in this document cannot be used in the development of like products or software, whether for internal or external use, and shall not be used for the benefit of any other party, whether or not for consideration.

Disclaimer: Information in this publication is subject to change without notice and does not represent a commitment on the part of Cadence. Except as may be explicitly set forth in such agreement, Cadence does not make, and expressly disclaims, any representations or warranties as to the completeness, accuracy or usefulness of the information contained in this document. Cadence does not warrant that use of such information will not infringe any third party rights, nor does Cadence assume any liability for damages or costs of any kind that may result from use of such information.

Cadence is committed to using respectful language in our code and communications. We are also active in the removal and replacement of inappropriate language from existing content. This product documentation may however contain material that is no longer considered appropriate but still reflects long-standing industry terminology. Such content will be addressed at a time when the related software can be updated without end-user impact.

Restricted Rights: Use, duplication, or disclosure by the Government is subject to restrictions as set forth in FAR52.227-14 and DFAR252.227-7013 et seq. or its successor.

Contents

1

<u>Generic Design Management (GDM) Functions</u>	1
<u>gdmAddSpecToSpecList</u>	3
<u>gdmcancel</u>	4
<u>gdmci</u>	6
<u>gdmco</u>	8
<u>gdmCreateSpec</u>	10
<u>gdmCreateSpecFromDDID</u>	12
<u>gdmCreateSpecList</u>	13
<u>gdmdelete</u>	14
<u>gdmExecute</u>	16
<u>gdmexport</u>	17
<u>gdmhistory</u>	19
<u>gdmInspectSpec</u>	21
<u>gdmIsSpecId</u>	22
<u>gdmNextFromSpecList</u>	23
<u>gdmObjsCreated</u>	24
<u>gdmRemovename</u>	25
<u>gdmResetSpecList</u>	26
<u>gdmsetdefver</u>	27
<u>gdmsetName</u>	29
<u>gdmSpecListp</u>	31
<u>gdmSpecp</u>	32
<u>gdmSpecType</u>	33
<u>gdmstatus</u>	34
<u>gdmsubmit</u>	37
<u>gdmupdate</u>	39

2

<u>Name Mapping Functions</u>	41
<u>nmp<NameSpace>To<NameSpace></u>	42

Cadence Application Infrastructure SKILL Reference

<u>nmp<NameSpace>TolIdent</u>	57
<u>nmpGetSpaceNames</u>	59
<u>nmpIdentTo<NameSpace></u>	60
<u>nmpIsLegal<NameSpace></u>	62
<u>nmpPath<NameSpace>To<NameSpace></u>	64

3

<u>cdsCopy Functions</u>	67
<u>cdsCopy SKILL Examples</u>	68
<u>ccpCopy</u>	70
<u>ccpCopyDesign</u>	76
<u>ccpCopyExactDesign</u>	80
<u>ccpCopyConfig</u>	84
<u>ccpDmHasRename</u>	88
<u>ccpDmRename</u>	89
<u>ccpExpand</u>	93
<u>ccpExpandDesign</u>	95
<u>ccpExpandExactDesign</u>	98
<u>ccpExpandConfig</u>	101
<u>ccpGetAutoRename</u>	104
<u>ccpSetAutoRename</u>	105
<u>ccpRename</u>	106
<u>ccpRenameReferenceLib</u>	109
<u>ccpRegMonitor</u>	111
<u>ccpRegTrigger</u>	114
<u>ccpRemoveTrigger</u>	118

4

<u>Library Manager Functions</u>	119
<u>lmgrAddMenuItems</u>	120
<u>lmgrAddToolBarItems</u>	122
<u>lmgrBeginBatchChange</u>	124
<u>lmgrCreateMenu</u>	126
<u>lmgrCreateMenuItem</u>	129
<u>lmgrClearLibDisplayColorOverride</u>	132

Cadence Application Infrastructure SKILL Reference

<u>ImgrClearLibDisplayIconOverride</u>	134
<u>ImgrClearLibDisplayOverride</u>	136
<u>ImgrDefineInits</u>	138
<u>ImgrDeleteMenuItems</u>	139
<u>ImgrDisplayMessage</u>	141
<u>ImgrEndBatchChange</u>	142
<u>ImgrGetLibDisplayOverride</u>	144
<u>ImgrGetObject</u>	146
<u>ImgrInsertMenuItems</u>	148
<u>ImgrInBatchChange</u>	150
<u>ImgrLogShowPopup</u>	152
<u>ImgrManageMenuItems</u>	153
<u>ImgrMenuSubsInPopup</u>	155
<u>ImgrQueryNamedObjects</u>	156
<u>ImgrRemoveToolBarItems</u>	157
<u>ImgrSensitizeMenuItems</u>	158
<u>ImgrSetLCVFilter</u>	160
<u>ImgrSetLibDisplayOverride</u>	161
<u>ImgrSetObject</u>	164
<u>ImgrShowToolBar</u>	167
<u>ImgrValidateIcon</u>	168
<u>ImgrVerbose</u>	169
<u>Library Manager Customization Using Imgr SKILL Functions</u>	170

5

<u>Plotter Functions</u>	181
<u>psConfigLoaded</u>	182
<u>psLoadCdsPlotInit</u>	183
<u>psQueryPaperSize</u>	184
<u>psQueryPaperSizes</u>	185
<u>psQueryPlotters</u>	186
<u>psQueueStatus</u>	187

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

This topic provides a list of basic editing Cadence® SKILL functions associated with Generic Design Management. GDM SKILL functions have the prefix `gdm`.

You can use GDM functions to:

- perform the same operations as GDM shell commands, such as `gdmco` or `gdmci`.
- get `gdmSpec` objects of design data.

A `gdmSpec` object is a user-defined type of SKILL object. These objects can be used with any SKILL functions that need `gdmSpec` objects. For example, the `cdsCopy` SKILL functions, need library objects in the form of `gdmSpec` objects.

Only the functions listed here are supported for public use. All other functions, regardless of their name or prefix, and undocumented aspects of the functions described below, are private and are subject to change at any time.

- `gdmAddSpecToSpecList`
- `gdmcancel`
- `gdmci`
- `gdmco`
- `gdmCreateSpec`
- `gdmCreateSpecFromDDID`
- `gdmCreateSpecList`
- `gdmdelete`
- `gdmExecute`
- `gdmexport`

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

- gdmhistory
- gdmInspectSpec
- gdmIsSpecId
- gdmNextFromSpecList
- gdmObjsCreated
- gdmRemovename
- gdmResetSpecList
- gdmsetdefver
- gdmsetname
- gdmSpecListp
- gdmSpecp
- gdmSpecType
- gdmstatus
- gdmsubmit
- gdmupdate

gdmAddSpecToSpecList

```
gdmAddSpecToSpecList(  
    G_gdmSpec  
    q_gdmSpecList  
)  
=> t / nil
```

Description

Adds a *gdmSpec* object to a *gdmSpecList*. This function automatically increases the size of the *gdmSpecList* object to add more *gdmSpec* objects, if required.

Arguments

<i>G_gdmSpec</i>	The object you want to add to the <i>gdmSpecList</i> .
<i>q_gdmSpecList</i>	The list to which you want to add a <i>gdmSpec</i> .

Value Returned

<i>t</i>	The object was added to the <i>gdmSpecList</i> .
<i>nil</i>	The object could not be added to the <i>gdmSpecList</i> .

Related Topics

[gdmCreateSpec](#)

[gdmstatus](#)

gdmcancel

```
gdmcancel(  
    { G_gdmSpec | q_gdmSpecList }  
    [ x_gdmOptions ]  
    [ g_xtra ]  
)  
=> t / nil
```

Description

Cancels the checked-out status of the library, cell, view, directory, or file that *G_gdmSpec* represents. Co-managed files in a view are always canceled as a group; co-managed set behavior applies only if *G_gdmSpec* consists of library elements.

If *G_gdmSpec* represents a directory that is not a library element, this function works recursively on the directory only if the `GDM_RECURSE` option was set when *G_gdmSpec* was created with *gdmCreateSpec*.

This function is the SKILL equivalent of the `gdmcancel` shell command.

Arguments

<i>G_gdmSpec</i>	The library, cell, view, directory, or file object for which the check-out status needs to be canceled.
<i>q_gdmSpecList</i>	List containing <i>gdmSpec</i> objects.
<i>x_gdmOptions</i>	This argument is currently ignored. The default is the integer 0.
<i>g_xtra</i>	Contains additional arguments to be passed to the Cancel command of the underlying design management system.

Value Returned

t	The check-out status of the files was canceled.
nil	An error occurred and the check-out status of the files could not be canceled.

Related Topics

[gdmCreateSpec](#)

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

gdmcancel

gdmci

```
gdmci(  
    { G_gdmSpec | q_gdmSpecList }  
    [ g_description ]  
    [ x_gdmOptions ]  
    [ g_xtra ]  
)  
=> t / nil
```

Description

Checks in the library, cell, view, directory, or file that *G_gdmSpec* represents. Co-managed files in a view are always checked in as a group; co-managed set behavior applies only if *G_gdmSpec* consists of library elements.

If *G_gdmSpec* represents a directory that is not a library element, this function works recursively on the directory only if the `GDM_RECURSE` option was set when *G_gdmSpec* was created with *gdmCreateSpec*.

This function is the SKILL equivalent of the `gdmci` shell command.

Arguments

<i>G_gdmSpec</i>	The <i>gdmSpec</i> object of the library, cell, view, directory, or file to check in.
<i>q_gdmSpecList</i>	A <i>gdmSpecList</i> object containing <i>gdmSpec</i> objects.
<i>g_description</i>	Description of the files that are checked in. It is specified as a string.
<i>x_gdmOptions</i>	One of the following integers: 5: Optimized checks in previously unmanaged files for the first time. 4: Optimized checks in already managed files. 1: Checks in previously unmanaged files for the first time. 0: Indicates no options are set. Default.
<i>g_xtra</i>	String containing additional arguments to be passed to the underlying design management system's check in command.

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

Value Returned

t	The files were checked in.
nil	An error occurred and the files were not checked in.

Related Topics

[gdmCreateSpec](#)

[gdmci](#)

gdmco

```
gdmco (
    { G_gdmSpec | q_gdmSpecList }
    [ g_version ]
    [ x_gdmOptions ]
    [ g_xtra ]
)
=> t / nil
```

Description

Checks out the library, cell, view, directory, or file that *G_gdmSpec* represents. Co-managed files in a view are always checked out as a group; co-managed set behavior applies only if *G_gdmSpec* consists of library elements.

If *G_gdmSpec* represents a directory that is not a library element, this function works recursively on the directory only if the `GDM_RECURSE` option was set when *G_gdmSpec* was created with *gdmCreateSpec*.

Arguments

<i>G_gdmSpec</i>	The <i>gdmSpec</i> object of the library, cell, view, directory, or file to check out.
<i>q_gdmSpecList</i>	A <i>gdmSpecList</i> object containing <i>gdmSpec</i> objects.
<i>g_version</i>	The version of the files to check out; specified as a string. You can specify this argument only if <i>G_gdmSpec</i> represents a file or a view.
<i>x_gdmOptions</i>	One of the following integers: 1: Checks out all managed view files instead of only co-managed view files. 0: Indicates no options are set. This is the default behavior.
<i>g_xtra</i>	String containing additional arguments to be passed to the underlying design management system's check out command.

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

Value Returned

t	The files were checked out.
nil	An error occurred and the files were not checked out.

Related Topics

[gdmCreateSpec](#)

[gdmco](#)

gdmCreateSpec

```
gdmCreateSpec (
    t_libName | emptyString | nil
    t_cellName | emptyString | nil
    t_viewName | emptyString | nil
    t_fileName | emptyString | nil
    t_namespace
    [ x_gdmOptions ]
)
=> G_gdmSpecId / nil
```

Description

Creates a *gdmSpec* object, a user-defined type of SKILL object, according to the options you specify. You must specify at least one of the first four arguments—a library name, cell name, view name, or file name. If you specify a cell name, you must also specify a library name. If you specify a view name, you must also specify a cell name and a library name.

Arguments

<i>t_libName</i>	Name of the library.
<i>t_cellName</i>	Name of the cell. If you specify a cell name, you must also specify a library name.
<i>t_viewName</i>	Name of the view. If you specify a view name, you must also specify a cell name and a library name.
<i>t_fileName</i>	Name of the file. All the above four arguments cannot be empty strings; you must provide a name for at least one of them.
<i>t_namespace</i>	Name space in which the <i>gdmSpec</i> is to be created. Can be one of the following strings: VHDL, VHDLAMS, Verilog, VerilogA, VerilogAMS, CDBA, Concept, Library, LibraryUnix, LibraryNT, Spectre, SpectreHDL, or Spice.
<i>x_gdmOptions</i>	Specifies that commands such as check out or check in work recursively on the directory. Applies only to <i>gdmSpec</i> objects that consist of directories.

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

Value Returned

<i>G_gdmSpecId</i>	The ID of the <i>gdmSpec</i> object created.
<i>nil</i>	The <i>gdmSpec</i> object could not be created.

Examples

Creating an ID of the *gdmSpec* object with the library name `myLib` and the name space `CDBA`.

```
newSpec = gdmCreateSpec( "myLib" "" "" "" "CDBA" )
```

Related Topics

[Name Spaces for Different Data Types](#)

gdmCreateSpecFromDDID

```
gdmCreateSpecFromDDID(  
    b_ddId  
)  
=> G_gdmSpecId / nil
```

Description

Creates a *gdmSpec*, a user-defined type of SKILL object, from a *ddId* object.

Arguments

<i>b_ddId</i>	The <i>ddId</i> of the object for which you want to create a <i>gdmSpec</i> object.
---------------	---

Value Returned

<i>G_gdmSpecId</i>	The ID of the <i>gdmSpec</i> object created.
<i>nil</i>	The <i>gdmSpec</i> object could not be created.

gdmCreateSpecList

```
gdmCreateSpecList(  
    )  
=> q_gdmSpecList / nil
```

Description

Creates a *gdmSpecList* object, where you can add *gdmSpec* objects later with the *gdmAddSpecToSpecList* function.

Arguments

None

Value Returned

<i>q_gdmSpecList</i>	The object created.
nil	The object could not be created.

Examples

You can traverse a *gdmSpecList* object in the following way:

```
specList = gdmCreateSpecList()  
spec = gdmCreateSpec( "mylib" "topcell" "schematic" nil "CDBA" )  
gdmAddSpecToSpecList( spec specList )  
gdmResetSpecList( specList )  
while( nextSpec = gdmNextFromSpecList( specList )  
    println( gdmInspectSpec( nextSpec "CDBA" ) )  
    )
```

Additional Information

To traverse the *gdmSpecList* object:

1. Reset the list by using the *gdmResetSpecList* function.
2. Get *gdmSpec* objects by using the *gdmNextFromSpecList* function. The first time you call this function, it returns the first *gdmSpec* object from the *gdmSpecList*. Each successive call returns the next *gdmSpec* object from the *gdmSpecList*.

gdmdelete

```
gdmdelete(
    { G_gdmSpec | q_gdmSpecList }
    [ x_gdmOptions ]
    [ g_xtra ]
)
=> t / nil
```

Description

Deletes the library, cell, view, directory, or file that *G_gdmSpec* represents from the workarea and the default configuration.

If *G_gdmSpec* represents a directory that is not a library element, this function works recursively on the directory only if the `GDM_RECURSE` option was set when *G_gdmSpec* was created with *gdmCreateSpec*.

This function is the SKILL equivalent of the `gdmdelete` shell command.

Arguments

<i>G_gdmSpec</i>	The <i>gdmSpec</i> object of the library, cell, view, directory, or file to delete.
<i>q_gdmSpecList</i>	A <i>gdmSpecList</i> object containing <i>gdmSpec</i> objects.
<i>x_gdmOptions</i>	One of the following integers: 1: Deletes files from the workarea only. 0: Indicates no options are set. Default.
<i>g_xtra</i>	String containing additional arguments to be passed to the underlying design management system's delete command.

Value Returned

t	The files were deleted.
nil	An error occurred and the files were not deleted.

Related Topics

[gdmCreateSpec](#)

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

gdmdelete

gdmExecute

```
gdmExecute(  
    g_general  
)  
=> t / nil
```

Description

Executes the command line.

Arguments

<i>g_general</i>	The name of the executable.
------------------	-----------------------------

Value Returned

t	The command is executed.
nil	The command is not executed.

Examples

Executing `crcsci` and `crcsci` command lines:

```
gdmExecute( "crcsci" "crs" )
```

gdmexport

```
gdmexport (
    { G_gdmSpec | q_gdmSpecList }
    g_destination
    [ g_version ]
    [ x_gdmOptions ]
    [ g_xtra ]
)
=> t / nil
```

Description

Exports the library, cell, view, directory, or file that *G_gdmSpec* represents from the design management system data repository to the destination you specify.

If *G_gdmSpec* represents a directory that is not a library element, this function works recursively on the directory only if the `GDM_RECURSE` option was set when *G_gdmSpec* was created with *gdmCreateSpec*.

This function is the SKILL equivalent of the `gdmexport` shell command.

Arguments

<i>G_gdmSpec</i>	The object of the library, cell, view, directory, or file to export.
<i>q_gdmSpecList</i>	A list containing <i>gdmSpec</i> objects.
<i>g_destination</i>	The location, a directory or file, to which to export the files. <i>g_destination</i> can be a file only if you export only one file.
<i>g_version</i>	The version of the files to export.
<i>x_gdmOptions</i>	One of the following integers: 1: Exports all managed files in a view instead of only co-managed view files. 2: Creates the directory tree structure of the source directory in the destination directory. 0: Indicates no options are set. This is the default behavior.
<i>g_xtra</i>	String containing additional arguments to be passed to the underlying export command of the design management system.

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

Value Returned

t	The files were exported.
nil	An error occurred and the files were not exported.

Related Topics

[gdmCreateSpec](#)

[gdmexport](#)

gdmhistory

```
gdmhistory(  
    { G_gdmSpec | q_gdmSpecList }  
    x_information  
)  
=> g_returnInfo / nil
```

Description

Returns information about the version history of a file.

This function is the SKILL equivalent of the `gdmhistory` shell command.

Arguments

<i>G_gdmSpec</i>	The object of the file whose history you want to get.
<i>q_gdmSpecList</i>	A list containing <i>gdmSpec</i> objects.
<i>x_information</i>	<p>Specifies the kind of information to return. The valid values for this argument are:</p> <ol style="list-style-type: none">1: The current version of the file2: Name of the author3: The date the file was created4: The size of the file5: The version from which the current version was created6: The description that was submitted with the file7: The design management status, such as checked out8: The label/name attached on the version <p>If you specify the <i>x_information</i> value as 0, the function returns <code>nil</code>.</p>

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

Value Returned

<i>g_returnInfo</i>	String containing the information is returned.
<i>nil</i>	An error occurred and the information could not be returned.

Related Topics

[gdmCreateSpec](#)

[gdmhistory](#)

gdmInspectSpec

```
gdmInspectSpec (
    G_gdmSpecId
    [ t_namespace ]
)
=> l_comps
```

Description

Extracts and returns the library name, cell name, view name, and file name from a *gdmSpec* object, if they exist. The information returned will be in the name space you specify in *t_namespace*.

Arguments

<i>G_gdmSpecId</i>	The <i>gdmSpec</i> of the object whose library name, cell name, view name, and file name you want to get.
<i>t_namespace</i>	Name space in which the return information is provided. Can be one of the following strings: VHDL, VHDLAMS, Verilog, VerilogA, VerilogAMS, CDBA, Concept, Library, LibraryUnix, LibraryNT, Spectre, SpectreHDL, or Spice. This argument is optional; if you do not provide a value, CDBA is used as the default name space.

Value Returned

<i>l_comps</i>	A list that contains the library name, cell name, view name, and file name, in that order. If any of these elements did not exist in the <i>gdmSpec</i> object, it is represented by <i>nil</i> in the return list.
----------------	---

Related Topics

[Name Spaces for Different Data Types](#)

gdmIsSpecId

```
gdmIsSpecId(  
    g_object  
)  
=> t / nil
```

Description

Checks whether an object is a valid *gdmSpec* object.

Arguments

<i>g_object</i>	The object you want to check.
-----------------	-------------------------------

Value Returned

t	<i>g_object</i> is a valid gdmSpec object.
nil	<i>g_object</i> is not a valid gdmSpec object.

gdmNextFromSpecList

```
gdmNextFromSpecList(  
    q_gdmSpecList  
)  
=> G_gdmSpecId / nil
```

Description

Takes a *gdmSpecList* object and returns a *gdmSpec* object from it. The first time you call this function, it returns the first *gdmSpec* object in the *gdmSpecList*. Each successive call gets the next *gdmSpec* object.

Use this function with the *gdmResetSpecList* function. You must call *gdmResetSpecList* before the first call to *gdmNextFromSpecList*, otherwise the results may not be accurate.

Arguments

<i>q_gdmSpecList</i>	The <i>gdmSpecList</i> object from which the function returns <i>gdmSpec</i> objects. This object is the return value of the <i>gdmCreateSpecList</i> function.
----------------------	---

Value Returned

<i>G_gdmSpecId</i>	The ID of the next <i>gdmSpec</i> object from the <i>gdmSpecList</i> object.
<i>nil</i>	The function failed.

Examples

Use *gdmResetSpecList* and *gdmNextFromSpecList* in the following way:

```
specList = gdmCreateSpecList()  
spec = gdmCreateSpec( "mylib" "topcell" "schematic" nil "CDBA" )  
gdmAddSpecToSpecList( spec specList )  
gdmResetSpecList( specList )  
while( nextSpec = gdmNextFromSpecList( specList )  
    println( gdmInspectSpec( nextSpec "CDBA" ) )  
)
```

Related Topics

[gdmResetSpecList](#)

gdmObjIsCreated

```
gdmObjIsCreated(  
    g_name  
  
)  
=> t / nil
```

Description

Checks whether a view or file has already been created by another user in the same DM.

Arguments

<i>g_name</i>	The view or file to examine.
---------------	------------------------------

Value Returned

t	The file or view has been created by a DM system.
nil	The file or view has not been created.

gdmRemovename

```
gdmRemovename (
    G_gdmSpec
    [ g_version ]
    [ g_name ]

)
=> t / nil
```

Description

Requests that GDM removes a name from the specified files.

If only the *name* argument is used, then the current files in the work area will have the name removed. If both *version* and *name* are used, then the specified version will have the name removed.

Arguments

<i>G_gdmSpec</i>	Displays the <i>gdmSpec</i> object that you want to remove a name from.
<i>g_version</i>	The version that you want to remove the name from. NULL is applied to all versions.
<i>g_name</i>	The name to be removed from the version.

Value Returned

<i>t</i>	The name is successfully removed.
<i>nil</i>	The command is not executed.

Examples

Remove *spec* from *release10* version.

```
gdmRemovename ( spec "release10" )
```

gdmResetSpecList

```
gdmResetSpecList(  
    q_gdmSpecList  
)  
=> t / nil
```

Description

Resets the *gdmSpecList* so that you can obtain *gdmSpec* objects from it with successive calls of the *gdmNextFromSpecList* function.

Use this function before you use the *gdmNextFromSpecList* function. If you reset the *gdmSpecList* and then call *gdmNextFromSpecList*, the first *gdmSpec* object in the *gdmSpecList* is returned.

Arguments

<i>q_gdmSpecList</i>	The object you want to reset.
----------------------	-------------------------------

Value Returned

t	The <i>gdmSpecList</i> was reset.
nil	The <i>gdmSpecList</i> could not be reset.

Examples

Use *gdmResetSpecList* and *gdmNextFromSpecList* in the following way:

```
specList = gdmCreateSpecList()  
spec = gdmCreateSpec( "mylib" "topcell" "schematic" nil "CDBA" )  
gdmAddSpecToSpecList( spec specList )  
gdmResetSpecList( specList )  
while( nextSpec = gdmNextFromSpecList( specList )  
    println( gdmInspectSpec( nextSpec "CDBA" ) )  
)
```

Related Topics

[gdmNextFromSpecList](#)

gdmsetdefver

```
gdmsetdefver(  
    { G_gdmSpec | q_gdmSpecList }  
    g_version  
    [ g_name ]  
    [ x_gdmOptions ]  
    [ g_xtra ]  
)  
=> t / nil
```

Description

Sets *g_version* as the default version of the library, cell, view, directory, or file that *G_gdmSpec* represents.

This function is the SKILL equivalent of the `gdmsetdefver` shell command.

Arguments

<i>G_gdmSpec</i>	The <code>gdmSpec</code> object of the library, cell, view, directory, or file whose default version you want to set.
<i>q_gdmSpecList</i>	A <code>gdmSpecList</code> object containing <code>gdmSpec</code> objects.
<i>g_version</i>	The version to set as the default version of the files; specified as a string.
<i>g_name</i>	The name, such as an RCS tag, that identifies a set of files. If you specify this argument, the default version is applied only to this set of files.
<i>x_gdmOptions</i>	This argument is currently ignored. The default is the integer 0.
<i>g_xtra</i>	String containing additional arguments to be passed to the underlying design management system's set default version command.

Value Returned

<i>t</i>	The default version was set for the files.
<i>nil</i>	An error occurred and the default version was not set for the files.

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

Related Topics

[gdmCreateSpec](#)

[gdmsetdefver](#)

gdmsetname

```
gdmsetname (
    { G_gdmSpec | q_gdmSpecList }
    g_name
    [ g_version ]
    [ x_gdmOptions ]
    [ g_xtra ]
)
=> t / nil
```

Description

Associates the name you specify with the library, cell, view, directory, or file that *G_gdmSpec* represents.

If *G_gdmSpec* represents a directory that is not a library element, this function works recursively on the directory only if the `GDM_RECURSE` option was set when *G_gdmSpec* was created with *gdmCreateSpec*.

This function is the SKILL equivalent of the `gdmsetname` shell command.

Arguments

<i>G_gdmSpec</i>	The library, cell, view, directory, or files to associate with <i>g_name</i> .
<i>q_gdmSpecList</i>	A <i>gdmSpecList</i> object containing <i>gdmSpec</i> objects.
<i>g_name</i>	The name to associate with the files. This is equivalent to an RCS tag name or a TDM release name.
<i>g_version</i>	The version of the files to associate with <i>g_name</i> . You can specify this argument only if <i>G_gdmSpec</i> represents a file or a view.
<i>x_gdmOptions</i>	This argument is currently ignored. The default is the integer 0.
<i>g_xtra</i>	String containing additional arguments to be passed to the underlying design management system's set name command.

Value Returned

t	The name was associated with the files.
---	---

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

nil

An error occurred and the name was not associated with the files.

Related Topics

[gdmCreateSpec](#)

[gdmsetName](#)

gdmSpecListp

```
gdmSpecListp(  
    g_object  
)  
=> t / nil
```

Description

Checks whether an object is a *gdmSpecList*.

Arguments

<i>g_object</i>	The object you want to check.
-----------------	-------------------------------

Value Returned

t	<i>g_object</i> is a <i>gdmSpecList</i> .
nil	<i>g_object</i> is not a <i>gdmSpecList</i> .

Related Topics

[gdmAddSpecToSpecList](#)

[gdmCreateSpecList](#)

gdmSpecp

```
gdmSpecp(  
    g_object  
)  
=> t / nil
```

Description

Checks whether an object is of type *gdmSpec*, a user-defined type of SKILL object.

Arguments

<i>g_object</i>	The object you want to check.
-----------------	-------------------------------

Value Returned

<i>t</i>	<i>g_object</i> is a <i>gdmSpec</i> object.
<i>nil</i>	<i>g_object</i> is not a <i>gdmSpec</i> object.

Related Topics

[gdmlsSpecId](#)

[gdmCreateSpec](#)

[gdmCreateSpecList](#)

gdmSpecType

```
gdmSpecType (  
    G_gdmSpecId  
)  
=> t_specType / nil
```

Description

Returns the type of a *gdmSpec* object. A *gdmSpec* object can be one of the following types: *lib*, *libCell*, *libCellView*, *libFile*, *libCellFile*, *libCellViewFile*, *directory*, or *file*.

Arguments

<i>G_gdmSpecId</i>	The <i>gdmSpec</i> object whose type you want to check.
--------------------	---

Value Returned

<i>t_specType</i>	Returns one of the following strings: "lib" "libCell" "libCellView" "libFile" "libCellFile" "libCellViewFile" "directory" "file"
<i>nil</i>	<i>G_gdmSpecId</i> is not a valid <i>gdmSpec</i> object.

Related Topics

[gdmCreateSpec](#)

[gdmAddSpecToSpecList](#)

[gdmCreateSpecList](#)

gdmstatus

```
gdmstatus(  
    { G_gdmSpec | q_gdmSpecList }  
    x_information  
)  
=> l_fileStatus / nil
```

Description

Returns the design management status of the library, cell, view, directory, or file that *G_gdmSpec* represents.

This function is the SKILL equivalent of the `gdmstatus` shell command.

Arguments

<i>G_gdmSpec</i>	The <i>gdmSpec</i> object of the library, cell, view, directory, or file.
<i>q_gdmSpecList</i>	A <i>gdmSpecList</i> object containing <i>gdmSpec</i> objects.
<i>x_information</i>	Specifies the kind of information to return. These are the legal values for this argument: 1: The <i>gdmSpec</i> object. 2: The library to which the file belongs. 3: The cell to which the file belongs. 4: The view to which the file belongs. 5: The path to the file, relative to the library to which it belongs or to the current directory.

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

6: The design management status. Returns one of the following:

`gdmStateNone`: DMTYPE is set to a valid DM system. You may request GDM to attempt check in of an unmanaged state data into the named DM. This usually works within a managed library, depending upon correct DM setup and configuration including the `cdsinfo.tag` file.

`gdmStateCI`: File is managed and not checked out

`gdmStateCO`: File is checked out to current workarea

`gdmStateCOE`: File is checked out but not to current workarea

`gdmStateDel`: File is flagged as deleted

`gdmStateDir`: File is a directory

`gdmStateInactive`: File is inactive

`gdmStateUnmanageable`: DMTYPE is set to NONE. A GDM check in cannot be processed in the current configuration state. For example, a directory, which is unmanageable will not have its content expanded. Therefore, no subdirectory data will be returned for it, even if the `GDM_RECURSE` option is added. The UNMANAGEABLE state cannot process a GDM check-in within the current configuration state. It means the DMTYPE has been set to NONE by a `cdsinfo.tag` file.

7: The status of the file in the workarea. Returns one of the following:

`gdmStateNone`: File is not in the workarea.

`gdmStateRead`: File is in the workarea but is read-only.

`gdmStateWrite`: File is checked out to current. workarea.

`gdmStateDir`: File is a directory.

`gdmStateErr`: File is in an inconsistent state.

8: Check whether the file has been modified in the workarea.

9: The version the file will be when it is checked in, or if it is already checked in, the current version.

10: The version of the file you will get if you check it out, or if it is already checked out, the version that was checked out.

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

- 11: The version of the file you will get if you update it.
- 12: The check-out location of the file.
- 13: The name of the person who checked out the file.
- 14: The name of the person who checked in the file.
- 15: The update needed status of the file. Returns one of the following:
 - true: Update is required.
 - false: Update is not required.
 - unknown: DM does not support this feature.

Value Returned

<i>l_fileStatus</i>	Returns a list of lists containing the status of each file in the cellview directory.
<i>nil</i>	An error occurred and the information could not be returned.

Examples

The master.tag file needs to be updated in the <rodTrLib | Design | layout> cellview.

```
strlist=gdmStatus(gdmCreateSpec("rodTrLib" "Design" "layout" master.tag" "CDBA")
15)
=> (("/rodTrLib/Design/layout/master.tag true"))
```

Related Topics

[gdmstatus](#)

[gdmhistory](#)

[gdmInspectSpec](#)

gdmsubmit

```
gdmsubmit(  
    { G_gdmSpec | q_gdmSpecList }  
    [ g_description ]  
    [ g_name ]  
    [ x_gdmOptions ]  
    [ g_xtra ]  
)  
=> t / nil
```

Description

Submits the files *G_gdmSpec* represents for the release. Co-managed files in a view are always submitted as a group; co-managed set behavior applies only if *G_gdmSpec* consists of library elements.

If *G_gdmSpec* represents a directory that is not a library element, this function works recursively on the directory only if the `GDM_RECURSE` option was set when *G_gdmSpec* was created with *gdmCreateSpec*.

This function is the SKILL equivalent of the `gdmsubmit` shell command.

Arguments

<i>G_gdmSpec</i>	The <i>gdmSpec</i> object of the library, cell, view, directory, or file to submit for the release.
<i>q_gdmSpecList</i>	A <i>gdmSpecList</i> object containing <i>gdmSpec</i> objects.
<i>g_description</i>	A description of the submit request; specified as a string.
<i>g_name</i>	The integration request name or release name; specified as a string.
<i>x_gdmOptions</i>	One of the following integers: 1: Includes files that are checked out. 0: Indicates no options are set. Default.
<i>g_xtra</i>	String containing additional arguments to be passed to the underlying design management system's submit command.

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

Value Returned

t	The files were submitted for the release.
nil	An error occurred and the files were not submitted for the release.

Related Topics

gdmCreateSpec

gdmsubmit

gdmupdate

```
gdmupdate (
    { G_gdmSpec | q_gdmSpecList }
    [ g_version ]
    [ g_name ]
    [ x_gdmOptions ]
    [ g_xtra ]
)
=> t / nil
```

Description

Makes files in the workarea available for reading. Co-managed files are updated in the same grouping in which they were checked in; co-managed behavior applies only if *G_gdmSpec* consists of library elements.

If *G_gdmSpec* represents a directory that is not a library element, this function works recursively on the directory only if the `GDM_RECURSE` option was set when *G_gdmSpec* was created with `gdmCreateSpec`.

This function is the SKILL equivalent of the `gdmupdate` shell command.

Arguments

<i>G_gdmSpec</i>	The <i>gdmSpec</i> object of the library, cell, view, directory, or file to update.
<i>q_gdmSpecList</i>	A <i>gdmSpecList</i> object containing <i>gdmSpec</i> objects.
<i>g_version</i>	The version of the files to update. If you specify this argument, do not specify <i>g_name</i> .
<i>g_name</i>	The name associated with the files; specified as a string. This is equivalent to an RCS tag name or a TDM release name. If you specify this argument, you must specify <code>nil</code> as the value of the <i>g_version</i> argument.
<i>x_gdmOptions</i>	One of the following integers: 1: Forces an update even if there are modified files in the workarea. Modified files in the workarea are overwritten and any unmanaged files within the comanaged set are deleted. 0: Indicates no options are set. Default.

Cadence Application Infrastructure SKILL Reference

Generic Design Management (GDM) Functions

g_xtra

String containing additional arguments to be passed to the underlying design management system's update command.

Value Returned

t

The files were updated.

nil

An error occurred and the files were not updated.

Related Topics

[gdmCreateSpec](#)

Name Mapping Functions

This topic provides a list of basic editing Cadence® SKILL functions associated with Name Mapping. These functions have the prefix `nmp`.

You can use `nmp` functions to:

- Get a list of all current name spaces
- Check if an identifier is legal in a name space
- Map an identifier from one name space to another name space
- Map an identifier from a name space to an `nmp` Ident

An `nmp` Ident is an opaque data structure that is the intermediate form to which identifiers are mapped when they are translated from one name space to another.

- Map an `nmp` Ident to a name space

Only the functions listed here are supported for public use. All other functions, regardless of their name or prefix, and undocumented aspects of the functions described below, are private and are subject to change at any time.

- `nmp<NameSpace>To<NameSpace>`
- `nmp<NameSpace>ToIdent`
- `nmpGetSpaceNames`
- `nmpIdentTo<NameSpace>`
- `nmpIsLegal<NameSpace>`
- `nmpPath<NameSpace>To<NameSpace>`

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

`nmp<NameSpace>To<NameSpace>`

```
nmp<NameSpace>To<NameSpace>(
    t_identifier
)
=> t_identifier
```

Description

Maps *t_identifier* from the first name space to the second name space. In the function name, substitute the first *<NameSpace>* with the name space to which the identifier belongs and substitute the second *<NameSpace>* with the name space to which you want to convert the identifier. For example, `nmpCDBAToVerilog()` or `nmpVHDLAMSToVHDL()`.

You can get a list of Cadence name spaces from the `nmpGetSpaceNames()` function.

Arguments

t_identifier The identifier you want to map to another name space.

Value Returned

t_identifier The identifier in the new name space.

Additional Information

The following table lists all current `nmp<NameSpace>To<NameSpace>` functions.

<code>nmpAsciiToSysVerilog()</code>	Maps identifier from ASCII to SysVerilog.
<code>nmpCDBAToConcept()</code>	Maps identifier from CDBA to Concept.
<code>nmpCDBAToCDBAFlat()</code>	Maps identifier from CDBA to CDBAFlat.
<code>nmpCDBAToDef()</code>	Maps identifier from CDBA to Def.
<code>nmpCDBAToGcf()</code>	Maps identifier from CDBA to Gcf.
<code>nmpCDBAToGenesis()</code>	Maps identifier from CDBA to Genesis.
<code>nmpCDBAToLef()</code>	Maps identifier from CDBA to Lef.
<code>nmpCDBAToPrint()</code>	Maps identifier from CDBA to Print.
<code>nmpCDBAToSdf()</code>	Maps identifier from CDBA to Sdf.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpCDBAToSpf()</code>	Maps identifier from CDBA to Spf.
<code>nmpCDBAToSpectre()</code>	Maps identifier from CDBA to Spectre.
<code>nmpCDBAToSpectreHDL()</code>	Maps identifier from CDBA to SpectreHDL.
<code>nmpCDBAToSpf()</code>	Maps identifier from CDBA to Spf.
<code>nmpCDBAToSpice()</code>	Maps identifier from CDBA to Spice.
<code>nmpCDBAToSysVerilog()</code>	Maps identifier from CDBA to SysVerilog.
<code>nmpCDBAToVerilog()</code>	Maps identifier from CDBA to Verilog.
<code>nmpCDBAToVerilogA()</code>	Maps identifier from CDBA to VerilogA.
<code>nmpCDBAToVerilogAMS()</code>	Maps identifier from CDBA to VerilogAMS.
<code>nmpCDBAToVHDL()</code>	Maps identifier from CDBA to VHDL.
<code>nmpCDBAToVHDLAMS()</code>	Maps identifier from CDBA to VHDLAMS.
<code>nmpCDBAToVHDL87()</code>	Maps identifier from CDBA to VHDL87.
<code>nmpCDBAFlatToCDBA()</code>	Maps identifier from CDBAFlat to CDBA.
<code>nmpConceptToCDBA()</code>	Maps identifier from Concept to CDBA.
<code>nmpConceptToDef()</code>	Maps identifier from Concept to Def.
<code>nmpConceptToGcf()</code>	Maps identifier from Concept to Gcf.
<code>nmpConceptToGenesis()</code>	Maps identifier from Concept to Genesis.
<code>nmpConceptToLef()</code>	Maps identifier from Concept to Lef.
<code>nmpConceptToPrint()</code>	Maps identifier from Concept to Print.
<code>nmpConceptToSdf()</code>	Maps identifier from Concept to Sdf.
<code>nmpConceptToSpf()</code>	Maps identifier from Concept to Spf.
<code>nmpConceptToSpectre()</code>	Maps identifier from Concept to Spectre.
<code>nmpConceptToSpectreHDL()</code>	Maps identifier from Concept to SpectreHDL.
<code>nmpConceptToSpf()</code>	Maps identifier from Concept to Spf.
<code>nmpConceptToSpice()</code>	Maps identifier from Concept to Spice.
<code>nmpConceptToSysVerilog()</code>	Maps identifier from Concept to SysVerilog.
<code>nmpConceptToVerilog()</code>	Maps identifier from Concept to Verilog.
<code>nmpConceptToVerilogA()</code>	Maps identifier from Concept to VerilogA.
<code>nmpConceptToVerilogAMS()</code>	Maps identifier from Concept to VerilogAMS.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpConceptToVHDL()</code>	Maps identifier from Concept to VHDL.
<code>nmpConceptToVHDLAMS()</code>	Maps identifier from Concept to VHDLAMS.
<code>nmpConceptToVHDL87()</code>	Maps identifier from Concept to VHDL87.
<code>nmpDefToCDBA()</code>	Maps identifier from Def to CDBA.
<code>nmpDefToConcept()</code>	Maps identifier from Def to Concept.
<code>nmpDefToGcf()</code>	Maps identifier from Def to Gcf.
<code>nmpDefToGenesis()</code>	Maps identifier from Def to Genesis.
<code>nmpDefToLef()</code>	Maps identifier from Def to Lef.
<code>nmpDefToPrint()</code>	Maps identifier from Def to Print.
<code>nmpDefToSdf()</code>	Maps identifier from Def to Sdf.
<code>nmpDefToSpf()</code>	Maps identifier from Def to Spf.
<code>nmpDefToSpectre()</code>	Maps identifier from Def to Spectre.
<code>nmpDefToSpectreHDL()</code>	Maps identifier from Def to SpectreHDL.
<code>nmpDefToSpf()</code>	Maps identifier from Def to Spf.
<code>nmpDefToSpice()</code>	Maps identifier from Def to Spice.
<code>nmpDefToSysVerilog()</code>	Maps identifier from Def to SysVerilog.
<code>nmpDefToVerilog()</code>	Maps identifier from Def to Verilog.
<code>nmpDefToVerilogA()</code>	Maps identifier from Def to VerilogA.
<code>nmpDefToVerilogAMS()</code>	Maps identifier from Def to VerilogAMS.
<code>nmpDefToVHDL()</code>	Maps identifier from Def to VHDL.
<code>nmpDefToVHDLAMS()</code>	Maps identifier from Def to VHDLAMS.
<code>nmpDefToVHDL87()</code>	Maps identifier from Def to VHDL87.
<code>nmpGcfToCDBA()</code>	Maps identifier from Gcf to CDBA.
<code>nmpGcfToConcept()</code>	Maps identifier from Gcf to Concept.
<code>nmpGcfToDef()</code>	Maps identifier from Gcf to Def.
<code>nmpGcfToGenesis()</code>	Maps identifier from Gcf to Genesis.
<code>nmpGcfToLef()</code>	Maps identifier from Gcf to Lef.
<code>nmpGcfToPrint()</code>	Maps identifier from Gcf to Print.
<code>nmpGcfToSdf()</code>	Maps identifier from Gcf to Sdf.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpGcfToSpf()</code>	Maps identifier from Gcf to Spf.
<code>nmpGcfToSpectre()</code>	Maps identifier from Gcf to Spectre.
<code>nmpGcfToSpectreHDL()</code>	Maps identifier from Gcf to SpectreHDL.
<code>nmpGcfToSpef()</code>	Maps identifier from Gcf to Spef.
<code>nmpGcfToSpice()</code>	Maps identifier from Gcf to Spice.
<code>nmpGcfToSysVerilog()</code>	Maps identifier from Gcf to SysVerilog.
<code>nmpGcfToVerilog()</code>	Maps identifier from Gcf to Verilog.
<code>nmpGcfToVerilogA()</code>	Maps identifier from Gcf to VerilogA.
<code>nmpGcfToVerilogAMS()</code>	Maps identifier from Gcf to VerilogAMS.
<code>nmpGcfToVHDL()</code>	Maps identifier from Gcf to VHDL.
<code>nmpGcfToVHDLAMS()</code>	Maps identifier from Gcf to VHDLAMS.
<code>nmpGcfToVHDL87()</code>	Maps identifier from Gcf to VHDL87.
<code>nmpGenesisToCDBA()</code>	Maps identifier from Genesis to CDBA.
<code>nmpGenesisToConcept()</code>	Maps identifier from Genesis to Concept.
<code>nmpGenesisToDef()</code>	Maps identifier from Genesis to Def.
<code>nmpGenesisToGcf()</code>	Maps identifier from Genesis to Gcf.
<code>nmpGenesisToLef()</code>	Maps identifier from Genesis to Lef.
<code>nmpGenesisToPrint()</code>	Maps identifier from Genesis to Print.
<code>nmpGenesisToSdf()</code>	Maps identifier from Genesis to Sdf.
<code>nmpGenesisToSpf()</code>	Maps identifier from Genesis to Spf.
<code>nmpGenesisToSpectre()</code>	Maps identifier from Genesis to Spectre.
<code>nmpGenesisToSpectreHDL()</code>	Maps identifier from Genesis to SpectreHDL.
<code>nmpGenesisToSpef()</code>	Maps identifier from Genesis to Spef.
<code>nmpGenesisToSpice()</code>	Maps identifier from Genesis to Spice.
<code>nmpGenesisToSysVerilog()</code>	Maps identifier from Genesis to SysVerilog.
<code>nmpGenesisToVerilog()</code>	Maps identifier from Genesis to Verilog.
<code>nmpGenesisToVerilogA()</code>	Maps identifier from Genesis to VerilogA.
<code>nmpGenesisToVerilogAMS()</code>	Maps identifier from Genesis to VerilogAMS.
<code>nmpGenesisToVHDL()</code>	Maps identifier from Genesis to VHDL.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpGenesisToVHDLAMS()</code>	Maps identifier from Genesis to VHDLAMS.
<code>nmpGenesisToVHDL87()</code>	Maps identifier from Genesis to VHDL87.
<code>nmpLefToCDBA()</code>	Maps identifier from Lef to CDBA.
<code>nmpLefToConcept()</code>	Maps identifier from Lef to Concept.
<code>nmpLefToDef()</code>	Maps identifier from Lef to Def.
<code>nmpLefToGcf()</code>	Maps identifier from Lef to Gcf.
<code>nmpLefToGenesis()</code>	Maps identifier from Lef to Genesis.
<code>nmpLefToPrint()</code>	Maps identifier from Lef to Print.
<code>nmpLefToSdf()</code>	Maps identifier from Lef to Sdf.
<code>nmpLefToSpf()</code>	Maps identifier from Lef to Spf.
<code>nmpLefToSpectre()</code>	Maps identifier from Lef to Spectre.
<code>nmpLefToSpectreHDL()</code>	Maps identifier from Lef to SpectreHDL.
<code>nmpLefToSpef()</code>	Maps identifier from Lef to Spef.
<code>nmpLefToSpice()</code>	Maps identifier from Lef to Spice.
<code>nmpLefToSysVerilog()</code>	Maps identifier from Lef to SysVerilog.
<code>nmpLefToVerilog()</code>	Maps identifier from Lef to Verilog.
<code>nmpLefToVerilogA()</code>	Maps identifier from Lef to VerilogA.
<code>nmpLefToVerilogAMS()</code>	Maps identifier from Lef to VerilogAMS.
<code>nmpLefToVHDL()</code>	Maps identifier from Lef to VHDL.
<code>nmpLefToVHDLAMS()</code>	Maps identifier from Lef to VHDLAMS.
<code>nmpLefToVHDL87()</code>	Maps identifier from Lef to VHDL87.
<code>nmpPrintToCDBA()</code>	Maps identifier from Print to CDBA.
<code>nmpPrintToConcept()</code>	Maps identifier from Print to Concept.
<code>nmpPrintToDef()</code>	Maps identifier from Print to Def.
<code>nmpPrintToGcf()</code>	Maps identifier from Print to Gcf.
<code>nmpPrintToGenesis()</code>	Maps identifier from Print to Genesis.
<code>nmpPrintToLef()</code>	Maps identifier from Print to Lef.
<code>nmpPrintToSdf()</code>	Maps identifier from Print to Sdf.
<code>nmpPrintToSpf()</code>	Maps identifier from Print to Spf.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpPrintToSpectre()</code>	Maps identifier from Print to Spectre.
<code>nmpPrintToSpectreHDL()</code>	Maps identifier from Print to SpectreHDL.
<code>nmpPrintToSpf()</code>	Maps identifier from Print to Spf.
<code>nmpPrintToSpice()</code>	Maps identifier from Print to Spice.
<code>nmpPrintToSysVerilog()</code>	Maps identifier from Print to SysVerilog.
<code>nmpPrintToVerilog()</code>	Maps identifier from Print to Verilog.
<code>nmpPrintToVerilogA()</code>	Maps identifier from Print to VerilogA.
<code>nmpPrintToVerilogAMS()</code>	Maps identifier from Print to VerilogAMS.
<code>nmpPrintToVHDL()</code>	Maps identifier from Print to VHDL.
<code>nmpPrintToVHDLAMS()</code>	Maps identifier from Print to VHDLAMS.
<code>nmpPrintToVHDL87()</code>	Maps identifier from Print to VHDL87.
<code>nmpSdfToCDBA()</code>	Maps identifier from Sdf to CDBA.
<code>nmpSdfToConcept()</code>	Maps identifier from Sdf to Concept.
<code>nmpSdfToDef()</code>	Maps identifier from Sdf to Def.
<code>nmpSdfToGcf()</code>	Maps identifier from Sdf to Gcf.
<code>nmpSdfToGenesis()</code>	Maps identifier from Sdf to Genesis.
<code>nmpSdfToLef()</code>	Maps identifier from Sdf to Lef.
<code>nmpSdfToPrint()</code>	Maps identifier from Sdf to Print.
<code>nmpSdfToSpf()</code>	Maps identifier from Sdf to Spf.
<code>nmpSdfToSpectre()</code>	Maps identifier from Sdf to Spectre.
<code>nmpSdfToSpectreHDL()</code>	Maps identifier from Sdf to SpectreHDL.
<code>nmpSdfToSpf()</code>	Maps identifier from Sdf to Spf.
<code>nmpSdfToSpice()</code>	Maps identifier from Sdf to Spice.
<code>nmpSdfToSysVerilog()</code>	Maps identifier from Sdf to SysVerilog.
<code>nmpSdfToVerilog()</code>	Maps identifier from Sdf to Verilog.
<code>nmpSdfToVerilogA()</code>	Maps identifier from Sdf to VerilogA.
<code>nmpSdfToVerilogAMS()</code>	Maps identifier from Sdf to VerilogA.
<code>nmpSdfToVHDL()</code>	Maps identifier from Sdf to VHDL.
<code>nmpSdfToVHDLAMS()</code>	Maps identifier from Sdf to VerilogAMS.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpSdfToVHDL87()</code>	Maps identifier from Sdf to VHDL87.
<code>nmpSpfToCDBA()</code>	Maps identifier from Spf to CDBA.
<code>nmpSpfToConcept()</code>	Maps identifier from Spf to Concept.
<code>nmpSpfToDef()</code>	Maps identifier from Spf to Def.
<code>nmpSpfToGcf()</code>	Maps identifier from Spf to Gcf.
<code>nmpSpfToGenesis()</code>	Maps identifier from Spf to Genesis.
<code>nmpSpfToLef()</code>	Maps identifier from Spf to Lef.
<code>nmpSpfToPrint()</code>	Maps identifier from Spf to Print.
<code>nmpSpfToSdf()</code>	Maps identifier from Spf to Sdf.
<code>nmpSpfToSpectre()</code>	Maps identifier from Spf to Spectre.
<code>nmpSpfToSpectreHDL()</code>	Maps identifier from Spf to SpectreHDL.
<code>nmpSpfToSpef()</code>	Maps identifier from Spf to Spef.
<code>nmpSpfToSpice()</code>	Maps identifier from Spf to Spice.
<code>nmpSpfToSysVerilog()</code>	Maps identifier from Spf to SysVerilog.
<code>nmpSpfToVerilog()</code>	Maps identifier from Spf to Verilog.
<code>nmpSpfToVerilogA()</code>	Maps identifier from Spf to VerilogA.
<code>nmpSpfToVerilogAMS()</code>	Maps identifier from Spf to VerilogAMS.
<code>nmpSpfToVHDL()</code>	Maps identifier from Spf to VHDL.
<code>nmpSpfToVHDLAMS()</code>	Maps identifier from Spf to VHDLAMS.
<code>nmpSpfToVHDL87()</code>	Maps identifier from Spf to VHDL87.
<code>nmpSpectreToCDBA()</code>	Maps identifier from Spectre to CDBA.
<code>nmpSpectreToConcept()</code>	Maps identifier from Spectre to Concept.
<code>nmpSpectreToDef()</code>	Maps identifier from Spectre to Def.
<code>nmpSpectreToGcf()</code>	Maps identifier from Spectre to Gcf.
<code>nmpSpectreToGenesis()</code>	Maps identifier from Spectre to Genesis.
<code>nmpSpectreToLef()</code>	Maps identifier from Spectre to Lef.
<code>nmpSpectreToPrint()</code>	Maps identifier from Spectre to Print
<code>nmpSpectreToSdf()</code>	Maps identifier from Spectre to Sdf.
<code>nmpSpectreToSpf()</code>	Maps identifier from Spectre to Spf.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpSpectreToSpectreHDL()</code>	Maps identifier from Spectre to SpectreHDL.
<code>nmpSpectreToSpf()</code>	Maps identifier from Spectre to Spf.
<code>nmpSpectreToSpice()</code>	Maps identifier from Spectre to Spice.
<code>nmpSpectreToSysVerilog()</code>	Maps identifier from Spectre to SysVerilog.
<code>nmpSpectreToVerilog()</code>	Maps identifier from Spectre to Verilog.
<code>nmpSpectreToVerilogA()</code>	Maps identifier from Spectre to VerilogA.
<code>nmpSpectreToVerilogAMS()</code>	Maps identifier from Spectre to VerilogAMS.
<code>nmpSpectreToVHDL()</code>	Maps identifier from Spectre to VHDL.
<code>nmpSpectreToVHDLAMS()</code>	Maps identifier from Spectre to VHDLAMS.
<code>nmpSpectreToVHDL87()</code>	Maps identifier from Spectre to VHDL87.
<code>nmpSpectreHDLToCDBA()</code>	Maps identifier from SpectreHDL to CDBA.
<code>nmpSpectreHDLToConcept()</code>	Maps identifier from SpectreHDL to Concept.
<code>nmpSpectreHDLToDef()</code>	Maps identifier from SpectreHDL to Def.
<code>nmpSpectreHDLToGcf()</code>	Maps identifier from SpectreHDL to Gcf.
<code>nmpSpectreHDLToGenesis()</code>	Maps identifier from SpectreHDL to Genesis.
<code>nmpSpectreHDLToLef()</code>	Maps identifier from SpectreHDL to Lef.
<code>nmpSpectreHDLToPrint()</code>	Maps identifier from SpectreHDL to Print.
<code>nmpSpectreHDLToSdf()</code>	Maps identifier from SpectreHDL to Sdf.
<code>nmpSpectreHDLToSpf()</code>	Maps identifier from SpectreHDL to Spf.
<code>nmpSpectreHDLToSpectre()</code>	Maps identifier from SpectreHDL to Spectre.
<code>nmpSpectreHDLToSpf()</code>	Maps identifier from SpectreHDL to Spf.
<code>nmpSpectreHDLToSpice()</code>	Maps identifier from SpectreHDL to Spice.
<code>nmpSpectreHDLToSysVerilog()</code>	Maps identifier from Spectre to SysVerilog.
<code>nmpSpectreHDLToVerilog()</code>	Maps identifier from SpectreHDL to Verilog.
<code>nmpSpectreHDLToVerilogA()</code>	Maps identifier from SpectreHDL to VerilogA.
<code>nmpSpectreHDLToVerilogAMS()</code>	Maps identifier from SpectreHDL to VerilogAMS.
<code>nmpSpectreHDLToVHDL()</code>	Maps identifier from SpectreHDL to VHDL.
<code>nmpSpectreHDLToVHDLAMS()</code>	Maps identifier from SpectreHDL to VHDLAMS.
<code>nmpSpectreHDLToVHDL87()</code>	Maps identifier from SpectreHDL to VHDL87.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpSpefToCDBA()</code>	Maps identifier from Spef to CDBA.
<code>nmpSpefToConcept()</code>	Maps identifier from Spef to Concept.
<code>nmpSpefToDef()</code>	Maps identifier from Spef to Def.
<code>nmpSpefToGcf()</code>	Maps identifier from Spef to Gcf.
<code>nmpSpefToGenesis()</code>	Maps identifier from Spef to Genesis.
<code>nmpSpefToLef()</code>	Maps identifier from Spef to Lef.
<code>nmpSpefToPrint()</code>	Maps identifier from Spef to Print.
<code>nmpSpefToSdf()</code>	Maps identifier from Spef to Sdf.
<code>nmpSpefToSpf()</code>	Maps identifier from Spef to Spf.
<code>nmpSpefToSpectre()</code>	Maps identifier from Spef to Spectre.
<code>nmpSpefToSpectreHDL()</code>	Maps identifier from Spef to SpectreHDL.
<code>nmpSpefToSpice()</code>	Maps identifier from Spef to Spice.
<code>nmpSpefToSysVerilog()</code>	Maps identifier from Spef to SysVerilog.
<code>nmpSpefToVerilog()</code>	Maps identifier from Spef to Verilog.
<code>nmpSpefToVerilogA()</code>	Maps identifier from Spef to VerilogA.
<code>nmpSpefToVerilogAMS()</code>	Maps identifier from Spef to VerilogAMS.
<code>nmpSpefToVHDL()</code>	Maps identifier from Spef to VHDL.
<code>nmpSpefToVHDLAMS()</code>	Maps identifier from Spef to VHDLAMS.
<code>nmpSpefToVHDL87()</code>	Maps identifier from Spef to VHDL87.
<code>nmpSpiceToCDBA()</code>	Maps identifier from Spice to CDBA.
<code>nmpSpiceToConcept()</code>	Maps identifier from Spice to Concept.
<code>nmpSpiceToDef()</code>	Maps identifier from Spice to Def.
<code>nmpSpiceToGcf()</code>	Maps identifier from Spice to Gcf.
<code>nmpSpiceToGenesis()</code>	Maps identifier from Spice to Genesis.
<code>nmpSpiceToLef()</code>	Maps identifier from Spice to Lef.
<code>nmpSpiceToPrint()</code>	Maps identifier from Spice to Print.
<code>nmpSpiceToSdf()</code>	Maps identifier from Spice to Sdf.
<code>nmpSpiceToSpf()</code>	Maps identifier from Spice to Spf.
<code>nmpSpiceToSpectre()</code>	Maps identifier from Spice to Spectre.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpSpiceToSpectreHDL()</code>	Maps identifier from Spice to SpectreHDL.
<code>nmpSpiceToSpf()</code>	Maps identifier from Spice to Spf.
<code>nmpSpiceToSysVerilog()</code>	Maps identifier from Spice to SysVerilog.
<code>nmpSpiceToVerilog()</code>	Maps identifier from Spice to Verilog.
<code>nmpSpiceToVerilogA()</code>	Maps identifier from Spice to VerilogA.
<code>nmpSpiceToVerilogAMS()</code>	Maps identifier from Spice to VerilogAMS.
<code>nmpSpiceToVHDL()</code>	Maps identifier from Spice to VHDL.
<code>nmpSpiceToVHDLAMS()</code>	Maps identifier from Spice to VHDLAMS.
<code>nmpSpiceToVHDL87()</code>	Maps identifier from Spice to VHDL87.
<code>nmpSysVerilogToAscii()</code>	Maps identifier from SysVerilog to Ascii.
<code>nmpSysVerilogToCDBA()</code>	Maps identifier from SysVerilog to CDBA.
<code>nmpSysVerilogToConcept()</code>	Maps identifier from SysVerilog to Concept.
<code>nmpSysVerilogToDef()</code>	Maps identifier from SysVerilog to Def.
<code>nmpSysVerilogToGcf()</code>	Maps identifier from SysVerilog to Gcf.
<code>nmpSysVerilogToGenesis()</code>	Maps identifier from SysVerilog to Genesis.
<code>nmpSysVerilogToLef()</code>	Maps identifier from SysVerilog to Lef.
<code>nmpSysVerilogToPrint()</code>	Maps identifier from SysVerilog to Print.
<code>nmpSysVerilogToSdf()</code>	Maps identifier from SysVerilog to Sdf.
<code>nmpSysVerilogToSpf()</code>	Maps identifier from SysVerilog to Spf.
<code>nmpSysVerilogToSpectre()</code>	Maps identifier from SysVerilog to Spectre.
<code>nmpSysVerilogToSpectreHDL()</code>	Maps identifier from SysVerilog to SpectreHDL.
<code>nmpSysVerilogToSpf()</code>	Maps identifier from SysVerilog to Spf.
<code>nmpSysVerilogToSpice()</code>	Maps identifier from SysVerilog to Spice.
<code>nmpSysVerilogToVHDL()</code>	Maps identifier from SysVerilog to VHDL.
<code>nmpSysVerilogToVHDL87()</code>	Maps identifier from SysVerilog to VHDL87.
<code>nmpSysVerilogToVHDLAMS()</code>	Maps identifier from SysVerilog to VHDLAMS.
<code>nmpSysVerilogToVerilog()</code>	Maps identifier from SysVerilog to Verilog.
<code>nmpSysVerilogToVerilogA()</code>	Maps identifier from SysVerilog to VerilogA.
<code>nmpSysVerilogToVerilogAMS()</code>	Maps identifier from SysVerilog to VerilogAMS.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpVerilogToCDBA()</code>	Maps identifier from Verilog to CDBA.
<code>nmpVerilogToConcept()</code>	Maps identifier from Verilog to Concept.
<code>nmpVerilogToDef()</code>	Maps identifier from Verilog to Def.
<code>nmpVerilogToGcf()</code>	Maps identifier from Verilog to Gcf.
<code>nmpVerilogToGenesis()</code>	Maps identifier from Verilog to Genesis.
<code>nmpVerilogToLef()</code>	Maps identifier from Verilog to Lef.
<code>nmpVerilogToPrint()</code>	Maps identifier from Verilog to Print.
<code>nmpVerilogToSdf()</code>	Maps identifier from Verilog to Sdf.
<code>nmpVerilogToSpf()</code>	Maps identifier from Verilog to Spf.
<code>nmpVerilogToSpectre()</code>	Maps identifier from Verilog to Spectre.
<code>nmpVerilogToSpectreHDL()</code>	Maps identifier from Verilog to SpectreHDL.
<code>nmpVerilogToSpef()</code>	Maps identifier from Verilog to Spef.
<code>nmpVerilogToSpice()</code>	Maps identifier from Verilog to Spice.
<code>nmpVerilogToSysVerilog()</code>	Maps identifier from Verilog to SysVerilog.
<code>nmpVerilogToVerilogA()</code>	Maps identifier from Verilog to VerilogA.
<code>nmpVerilogToVerilogAMS()</code>	Maps identifier from Verilog to VerilogAMS.
<code>nmpVerilogToVHDL()</code>	Maps identifier from Verilog to VHDL.
<code>nmpVerilogToVHDLAMS()</code>	Maps identifier from Verilog to VHDLAMS.
<code>nmpVerilogToVHDL87()</code>	Maps identifier from Verilog to VHDL87.
<code>nmpVerilogAToCDBA()</code>	Maps identifier from VerilogA to CDBA.
<code>nmpVerilogAToConcept()</code>	Maps identifier from VerilogA to Concept.
<code>nmpVerilogAToDef()</code>	Maps identifier from VerilogA to Def.
<code>nmpVerilogAToGcf()</code>	Maps identifier from VerilogA to Gcf.
<code>nmpVerilogAToGenesis()</code>	Maps identifier from VerilogA to Genesis.
<code>nmpVerilogAToLef()</code>	Maps identifier from VerilogA to Lef.
<code>nmpVerilogAToPrint()</code>	Maps identifier from VerilogA to Print.
<code>nmpVerilogAToSdf()</code>	Maps identifier from VerilogA to Sdf.
<code>nmpVerilogAToSpf()</code>	Maps identifier from VerilogA to Spf.
<code>nmpVerilogAToSpectre()</code>	Maps identifier from VerilogA to Spectre.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpVerilogAToSpectreHDL()</code>	Maps identifier from VerilogA to SpectreHDL.
<code>nmpVerilogAToSpf()</code>	Maps identifier from VerilogA to Spf.
<code>nmpVerilogAToSpice()</code>	Maps identifier from VerilogA to Spice.
<code>nmpVerilogAToSysVerilog()</code>	Maps identifier from VerilogA to SysVerilog.
<code>nmpVerilogAToVerilog()</code>	Maps identifier from VerilogA to Verilog.
<code>nmpVerilogAToVerilogAMS()</code>	Maps identifier from VerilogA to VerilogAMS.
<code>nmpVerilogAToVHDL()</code>	Maps identifier from VerilogA to VHDL.
<code>nmpVerilogAToVHDLAMS()</code>	Maps identifier from VerilogA to VHDLAMS.
<code>nmpVerilogAToVHDL87()</code>	Maps identifier from VerilogA to VHDL87.
<code>nmpVerilogAMSToCDBA()</code>	Maps identifier from VerilogAMS to CDBA.
<code>nmpVerilogAMSToConcept()</code>	Maps identifier from VerilogAMS to Concept.
<code>nmpVerilogAMSToDef()</code>	Maps identifier from VerilogAMS to Def.
<code>nmpVerilogAMSToGcf()</code>	Maps identifier from VerilogAMS to Gcf.
<code>nmpVerilogAMSToGenesis()</code>	Maps identifier from VerilogAMS to Genesis.
<code>nmpVerilogAMSToLef()</code>	Maps identifier from VerilogAMS to Lef.
<code>nmpVerilogAMSToPrint()</code>	Maps identifier from VerilogAMS to Print.
<code>nmpVerilogAMSToSdf()</code>	Maps identifier from VerilogAMS to Sdf.
<code>nmpVerilogAMSToSpf()</code>	Maps identifier from VerilogAMS to Spf.
<code>nmpVerilogAMSToSpectre()</code>	Maps identifier from VerilogAMS to Spectre.
<code>nmpVerilogAMSToSpectreHDL()</code>	Maps identifier from VerilogAMS to SpectreHDL.
<code>nmpVerilogAMSToSpf()</code>	Maps identifier from VerilogAMS to Spf.
<code>nmpVerilogAMSToSpice()</code>	Maps identifier from VerilogAMS to Spice.
<code>nmpVerilogAMSToSysVerilog()</code>	Maps identifier from VerilogAMS to SysVerilog.
<code>nmpVerilogAMSToVerilog()</code>	Maps identifier from VerilogAMS to Verilog.
<code>nmpVerilogAMSToVerilogA()</code>	Maps identifier from VerilogAMS to VerilogA.
<code>nmpVerilogAMSToVHDL()</code>	Maps identifier from VerilogAMS to VHDL.
<code>nmpVerilogAMSToVHDLAMS()</code>	Maps identifier from VerilogAMS to VHDLAMS.
<code>nmpVerilogAMSToVHDL87()</code>	Maps identifier from VerilogAMS to VHDL87.
<code>nmpVHDLToCDBA()</code>	Maps identifier from VHDL to CDBA.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpVHDLToConcept()</code>	Maps identifier from VHDL to Concept.
<code>nmpVHDLToDef()</code>	Maps identifier from VHDL to Def.
<code>nmpVHDLToGcf()</code>	Maps identifier from VHDL to Gcf.
<code>nmpVHDLToGenesis()</code>	Maps identifier from VHDL to Genesis.
<code>nmpVHDLToLef()</code>	Maps identifier from VHDL to Lef.
<code>nmpVHDLToPrint()</code>	Maps identifier from VHDL to Print.
<code>nmpVHDLToSdf()</code>	Maps identifier from VHDL to Sdf.
<code>nmpVHDLToSpf()</code>	Maps identifier from VHDL to Spf.
<code>nmpVHDLToSpectre()</code>	Maps identifier from VHDL to Spectre.
<code>nmpVHDLToSpectreHDL()</code>	Maps identifier from VHDL to SpectreHDL.
<code>nmpVHDLToSpef()</code>	Maps identifier from VHDL to Spef.
<code>nmpVHDLToSpice()</code>	Maps identifier from VHDL to Spice.
<code>nmpVHDLToSysVerilog()</code>	Maps identifier from VHDL to SysVerilog.
<code>nmpVHDLToVerilog()</code>	Maps identifier from VHDL to Verilog.
<code>nmpVHDLToVerilogA()</code>	Maps identifier from VHDL to VerilogA.
<code>nmpVHDLToVerilogAMS()</code>	Maps identifier from VHDL to VerilogAMS.
<code>nmpVHDLToVHDLAMS()</code>	Maps identifier from VHDL to VHDLAMS.
<code>nmpVHDLToVHDL87()</code>	Maps identifier from VHDL to VHDL87.
<code>nmpVHDLAMSToCDBA()</code>	Maps identifier from VHDLAMS to CDBA.
<code>nmpVHDLAMSToConcept()</code>	Maps identifier from VHDLAMS to Concept.
<code>nmpVHDLAMSToDef()</code>	Maps identifier from VHDLAMS to Def.
<code>nmpVHDLAMSToGcf()</code>	Maps identifier from VHDLAMS to Gcf.
<code>nmpVHDLAMSToGenesis()</code>	Maps identifier from VHDLAMS to Genesis.
<code>nmpVHDLAMSToLef()</code>	Maps identifier from VHDLAMS to Lef.
<code>nmpVHDLAMSToPrint()</code>	Maps identifier from VHDLAMS to Print.
<code>nmpVHDLAMSToSdf()</code>	Maps identifier from VHDLAMS to Sdf.
<code>nmpVHDLAMSToSpf()</code>	Maps identifier from VHDLAMS to Spf.
<code>nmpVHDLAMSToSpectre()</code>	Maps identifier from VHDLAMS to Spectre.
<code>nmpVHDLAMSToSpectreHDL()</code>	Maps identifier from VHDLAMS to SpectreHDL.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpVHDLAMSToSpEf()</code>	Maps identifier from VHDLAMS to SpEf.
<code>nmpVHDLAMSToSpice()</code>	Maps identifier from VHDLAMS to Spice.
<code>nmpVHDLAMSToSysVerilog()</code>	Maps identifier from VHDLAMS to SysVerilog.
<code>nmpVHDLAMSToVerilog()</code>	Maps identifier from VHDLAMS to Verilog.
<code>nmpVHDLAMSToVerilogA()</code>	Maps identifier from VHDLAMS to VerilogA.
<code>nmpVHDLAMSToVerilogAMS()</code>	Maps identifier from VHDLAMS to VerilogAMS.
<code>nmpVHDLAMSToVHDL()</code>	Maps identifier from VHDLAMS to VHDL.
<code>nmpVHDLAMSToVHDL87()</code>	Maps identifier from VHDLAMS to VHDL87.
<code>nmpVHDL87ToCDBA()</code>	Maps identifier from VHDL87 to CDBA.
<code>nmpVHDL87ToConcept()</code>	Maps identifier from VHDL87 to Concept.
<code>nmpVHDL87ToDef()</code>	Maps identifier from VHDL87 to Def.
<code>nmpVHDL87ToGcf()</code>	Maps identifier from VHDL87 to Gcf.
<code>nmpVHDL87ToGenesis()</code>	Maps identifier from VHDL87 to Genesis.
<code>nmpVHDL87ToLef()</code>	Maps identifier from VHDL87 to Lef.
<code>nmpVHDL87ToPrint()</code>	Maps identifier from VHDL87 to Print.
<code>nmpVHDL87ToSdf()</code>	Maps identifier from VHDL87 to Sdf.
<code>nmpVHDL87ToSpf()</code>	Maps identifier from VHDL87 to Spf.
<code>nmpVHDL87ToSpectre()</code>	Maps identifier from VHDL87 to Spectre.
<code>nmpVHDL87ToSpectreHDL()</code>	Maps identifier from VHDL87 to SpectreHDL.
<code>nmpVHDL87ToSpEf()</code>	Maps identifier from VHDL87 to SpEf.
<code>nmpVHDL87ToSpice()</code>	Maps identifier from VHDL87 to Spice.
<code>nmpVHDL87ToSysVerilog()</code>	Maps identifier from VHDL87 to SysVerilog.
<code>nmpVHDL87ToVerilog()</code>	Maps identifier from VHDL87 to Verilog.
<code>nmpVHDL87ToVerilogA()</code>	Maps identifier from VHDL87 to VerilogA.
<code>nmpVHDL87ToVerilogAMS()</code>	Maps identifier from VHDL87 to VerilogAMS.
<code>nmpVHDL87ToVHDL()</code>	Maps identifier from VHDL87 to VHDL.
<code>nmpVHDL87ToVHDLAMS()</code>	Maps identifier from VHDL87 to VHDLAMS.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

Related Topics

[nmp<NameSpace>ToIdent](#)

[nmpGetSpaceNames](#)

[nmpPath<NameSpace>To<NameSpace>](#)

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

`nmp<NameSpace>ToIdent`

```
nmp<NameSpace>ToIdent (
    t_identifier
)
=> m_Ident
```

Description

Maps *t_identifier* from a name space to an nmp Ident. In the function name, substitute *<NameSpace>* with the name space to which the identifier belongs. For example, `nmpCDBAToIdent()`.

You can get a list of Cadence name spaces from the `nmpGetSpaceNames()` function.

You can map the Ident that is returned from this function to another name space with the `nmpIdentTo<NameSpace>` function.

Arguments

<i>t_identifier</i>	The identifier you want to map to Ident.
---------------------	--

Value Returned

<i>m_Ident</i>	The identifier in Ident form. An nmp Ident is an opaque data structure that is the intermediate form to which identifiers are mapped when they are translated from one name space to another.
----------------	---

Additional Information

The following table lists all current `nmp<NameSpace>ToIdent` functions.

<code>nmpCDBAToIdent()</code>	Maps identifier from CDBA to an nmp Ident.
<code>nmpConceptToIdent()</code>	Maps identifier from Concept to an nmp Ident.
<code>nmpDefToIdent()</code>	Maps identifier from Def to an nmp Ident.
<code>nmpGcfToIdent()</code>	Maps identifier from Gcf to an nmp Ident.
<code>nmpGenesisToIdent()</code>	Maps identifier from Genesis to an nmp Ident.
<code>nmpLefToIdent()</code>	Maps identifier from Lef to an nmp Ident.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpPrintToIdent()</code>	Maps identifier from Print to an nmp Ident.
<code>nmpSdfToIdent()</code>	Maps identifier from Sdf to an nmp Ident.
<code>nmpSpfToIdent()</code>	Maps identifier from Spf to an nmp Ident.
<code>nmpSpectreToIdent()</code>	Maps identifier from Spectre to an nmp Ident.
<code>nmpSpectreHDLToIdent()</code>	Maps identifier from SpectreHDL to an nmp Ident.
<code>nmpSpfToIdent()</code>	Maps identifier from Spf to an nmp Ident.
<code>nmpSpiceToIdent()</code>	Maps identifier from Spice to an nmp Ident.
<code>nmpSysVerilogToIdent()</code>	Maps identifier from SysVerilog to an nmp Ident.
<code>nmpVerilogToIdent()</code>	Maps identifier from Verilog to an nmp Ident.
<code>nmpVerilogAToIdent()</code>	Maps identifier from VerilogA to an nmp Ident.
<code>nmpVerilogAMSToIdent()</code>	Maps identifier from VerilogAMS to an nmp Ident.
<code>nmpVHDLToIdent()</code>	Maps identifier from VHDL to an nmp Ident.
<code>nmpVHDLAMSToIdent()</code>	Maps identifier from VHDLAMS to an nmp Ident.
<code>nmpVHDL87ToIdent()</code>	Maps identifier from VHDL87 to an nmp Ident.

Related Topics

[nmpIdentTo<NameSpace>](#)

[nmp<NameSpace>To<NameSpace>](#)

[nmpPath<NameSpace>To<NameSpace>](#)

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

nmpGetSpaceNames

```
nmpGetSpaceNames ()  
    => l_namespaces
```

Description

Returns a list of name spaces used by Cadence applications.

Arguments

None

Value Returned

l_namespaces List of name spaces used by Cadence applications.

Related Topics

[nmp<NameSpace>To<NameSpace>](#)

[nmp<NameSpace>ToIdent](#)

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

`nmpIdentTo<NameSpace>`

```
nmpIdentTo<NameSpace>(
    m_Ident
)
=> t_identifier
```

Description

Maps an nmp Ident to a name space. In the function name, substitute `<NameSpace>` with the name space to which you want to map the Ident. For example, `nmpIdentToSpectre()`. You can get a list of Cadence name spaces from the `nmpGetSpaceNames()` function.

Arguments

<code>m_Ident</code>	The identity you want to map to the name space. An nmp identity is an opaque data structure that is the intermediate form to which identifiers are mapped when they are translated from one name space to another.
----------------------	--

Value Returned

<code>t_identifier</code>	The identifier in the name space you specified.
---------------------------	---

Additional Information

The following table lists all current `nmpIdentTo<NameSpace>` functions.

<code>nmpIdentToCDBA()</code>	Maps an nmp Ident to CDBA.
<code>nmpIdentToConcept()</code>	Maps an nmp Ident to Concept.
<code>nmpIdentToDef()</code>	Maps an nmp Ident to Def.
<code>nmpIdentToGcf()</code>	Maps an nmp Ident to Gcf.
<code>nmpIdentToGenesis()</code>	Maps an nmp Ident to Genesis.
<code>nmpIdentToLef()</code>	Maps an nmp Ident to Lef.
<code>nmpIdentToPrint()</code>	Maps an nmp Ident to Print.
<code>nmpIdentToSdf()</code>	Maps an nmp Ident to Sdf.
<code>nmpIdentToSpf()</code>	Maps an nmp Ident to Spf.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpIdentToSpectre()</code>	Maps an nmp Ident to Spectre.
<code>nmpIdentToSpectreHDL()</code>	Maps an nmp Ident to SpectreHDL.
<code>nmpIdentToSpgef()</code>	Maps an nmp Ident to Spgef.
<code>nmpIdentToSpice()</code>	Maps an nmp Ident to Spice.
<code>nmpIdentToSysVerilog()</code>	Maps an nmp Ident to SysVerilog.
<code>nmpIdentToVerilog()</code>	Maps an nmp Ident to Verilog.
<code>nmpIdentToVerilogA()</code>	Maps an nmp Ident to VerilogA.
<code>nmpIdentToVerilogAMS()</code>	Maps an nmp Ident to VerilogAMS.
<code>nmpIdentToVHDL()</code>	Maps an nmp Ident to VHDL.
<code>nmpIdentToVHDLAMS()</code>	Maps an nmp Ident to VHDLAMS.
<code>nmpIdentToVHDL87()</code>	Maps an nmp Ident to VHDL87.

Related Topics

[nmp<NameSpace>ToIdent](#)

[nmp<NameSpace>To<NameSpace>](#)

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

nmplIsLegal<NameSpace>

```
nmplIsLegal<NameSpace> (  
    t_identifier  
)  
=> t / nil
```

Description

Checks if the specified identifier is legal in the name space. In the function name, substitute *<NameSpace>* with any of the name spaces returned by the function `nmplGetSpaceNames()`. For example, `nmplIsLegalVerilog()` or `nmplIsLegalVHDL()`.

Arguments

<i>t_identifier</i>	The identifier you want to check.
---------------------	-----------------------------------

Value Returned

t	The identifier is legal in the name space.
nil	The identifier is illegal in the name space.

Additional Information

The following table lists all the current `nmplIsLegal<NameSpace>` functions.

<code>nmplIsLegalCDBA()</code>	Checks if the identifier you specify is legal in CDBA.
<code>nmplIsLegalConcept()</code>	Checks if the identifier you specify is legal in Concept.
<code>nmplIsLegalDef()</code>	Checks if the identifier you specify is legal in DEF.
<code>nmplIsLegalGcf()</code>	Checks if the identifier you specify is legal in GCF.
<code>nmplIsLegalGenesis()</code>	Checks if the identifier you specify is legal in Genesis.
<code>nmplIsLegalLef()</code>	Checks if the identifier you specify is legal in LEF.
<code>nmplIsLegalPrint()</code>	Checks if the identifier you specify is legal in Print.
<code>nmplIsLegalSdf()</code>	Checks if the identifier you specify is legal in SDF.
<code>nmplIsLegalSpf()</code>	Checks if the identifier you specify is legal in SPF.

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpIsLegalSpectre()</code>	Checks if the identifier you specify is legal in Spectre.
<code>nmpIsLegalSpectreHDL()</code>	Checks if the identifier you specify is legal in SpectreHDL.
<code>nmpIsLegalSpgef()</code>	Checks if the identifier you specify is legal in SPEF.
<code>nmpIsLegalSpice()</code>	Checks if the identifier you specify is legal in Spice.
<code>nmpIsLegalSysVerilog()</code>	Checks if the identifier you specify is legal in SysVerilog.
<code>nmpIsLegalVerilog()</code>	Checks if the identifier you specify is legal in Verilog.
<code>nmpIsLegalVerilogA()</code>	Checks if the identifier you specify is legal in VerilogA.
<code>nmpIsLegalVerilogAMS()</code>	Checks if the identifier you specify is legal in VerilogAMS.
<code>nmpIsLegalVHDL()</code>	Checks if the identifier you specify is legal in VHDL.
<code>nmpIsLegalVHDLAMS()</code>	Checks if the identifier you specify is legal in VHDLAMS.
<code>nmpIsLegalVHDL87()</code>	Checks if the identifier you specify is legal in VHDL87.

Related Topics

[nmp<NameSpace>To<NameSpace>](#)

[nmp<NameSpace>ToIdent](#)

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

`nmpPath<NameSpace>To<NameSpace>`

```
nmpPath<NameSpace>To<NameSpace>(
    t_Inst
)
=> t_Inst / nil
```

Description

Converts a simple instance vector from the first name space to the second name space.

Arguments

<code>t_Inst</code>	A simple (non-hierarchical) instance vector you want to convert to another name space.
---------------------	--

Value Returned

<code>t_Inst</code>	The instance vector in the new name space.
<code>nil</code>	The input string is not legal in the first name space.

Examples

Converting simple instance vectors in the CDBA namespace to the VHDL namespace.

```
nmpPathCDBAToVHDL( "i8<0:3>" ) => "i8(0 to 3)"
nmpPathCDBAToVHDL( "I8<0:3>" ) => "\I8\ (0 to 3)"
nmpPathCDBAToVHDL( "instName<4>" ) => "\instName\ (4)"
nmpPathCDBAToVHDL( "inst_name<4>" ) => "inst_name (4)"
```

Converting simple instance vectors in the CDBA namespace to the Verilog namespace.

```
nmpPathCDBAToVerilog( "I8<0:3>" ) => "I8[0:3]"
nmpPathCDBAToVerilog( "instName<4>" ) => "instName[4]"
```

Additional Information

The following table lists all current `nmpPath<NameSpace>To<NameSpace>` functions.

<code>nmpPathCDBAToVHDL()</code>	Converts a simple instance vector in the CDBA namespace to the VHDL namespace.
----------------------------------	--

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

<code>nmpPathCDBAToVerilog()</code>	Converts a simple instance vector in the CDBA namespace to the Verilog namespace.
-------------------------------------	---

Related Topics

[nmpGetSpaceNames](#)

[nmpIdentTo<NameSpace>](#)

Cadence Application Infrastructure SKILL Reference

Name Mapping Functions

cdsCopy Functions

This topic provides a list of basic editing Cadence® SKILL functions associated with `cdsCopy`. These functions have the prefix `ccp`.

Only the functions listed here are supported for public use. All other functions, regardless of their name or prefix, and undocumented aspects of the functions described below, are private and are subject to change at any time.

- [`ccpCopy`](#)
- [`ccpCopyDesign`](#)
- [`ccpCopyExactDesign`](#)
- [`ccpCopyConfig`](#)
- [`ccpDmHasRename`](#)
- [`ccpDmRename`](#)
- [`ccpExpand`](#)
- [`ccpExpandDesign`](#)
- [`ccpExpandExactDesign`](#)
- [`ccpExpandConfig`](#)
- [`ccpRename`](#)
- [`ccpRenameReferenceLib`](#)
- [`ccpRegMonitor`](#)
- [`ccpRegTrigger`](#)
- [`ccpRemoveTrigger`](#)

cdsCopy SKILL Examples

Example 1

The following SKILL .il file copies library myLib to myLibCopy:

```
viewtypeList = '(maskLayout schematicSymbol)
srcList = gdmCreateSpecList()
src = gdmCreateSpec("myLib" "" "" "" "CDBA")
gdmAddSpecToSpecList(src srcList)
destList = gdmCreateSpecList()
dest = gdmCreateSpec("myLibCopy" "" "" "" "CDBA")
gdmAddSpecToSpecList(dest destList)
ccpCopy(srcList destList nil 'CCP_EXPAND_ALL viewtypeList nil)
```

Example 2

The following SKILL .il file creates and registers a copy monitor and a copy trigger function and uses them in a copy operation:

```
;; An example copy monitor function, which prints some of its arguments
procedure(copyMonitor(copyFn copyPhase fromPath toPath fromSpec toSpec numCount
numTotal "ttttggxx" )
    if(geqp(numCount 0) then
        if(neq(fromSpec nil) then
            printf("Monitor: %s %L -> %L, %d of %d files.\n"
                copyFn
                gdmInspectSpec(fromSpec "CDBA")
                gdmInspectSpec(toSpec "CDBA")
                numCount numTotal)
        ))
    nil
)

; An example copy trigger function, which prints some of its arguments
procedure(copyTriggerPrint(myFunction copyPhaseStr checkOffList supplementList
otherFromSpecs otherToSpecs updateList retHint
ctxList reserved "stgggggggx")
    let((retOK)
        retOK = t
        printf("Copy phase is '%s'\n" copyPhaseStr)
        printf("Calling options were %L\n", ctxList)
```

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

```
printf("Pre copy set is %L\n", checkOffList)
printf("Post copy is from %L\n", otherFromSpecs)
printf("          to %L\n", otherToSpecs)
retOK
)
)
; Registering the copy monitor and copy trigger functions
crm_ret = ccpRegMonitor('copyMonitor)
printf("ccpRegMonitor('symbol) returned '%L'\n" crm_ret)
ccpRegTrigger("ccpPostExpandTrigger" 'copyTriggerPrint nil)
ccpRegTrigger("ccpPostCopyTrigger" 'copyTriggerPrint nil)
; Copy
testLib = "MonitorTestLib"
srcList = gdmCreateSpecList()
src = gdmCreateSpec("analogLib" "cap" "" "" "CDBA" 0)
gdmAddSpecToSpecList(src srcList)
destList = gdmCreateSpecList()
dest = gdmCreateSpec(testLib "" "" "" "CDBA" 0)
gdmAddSpecToSpecList(dest destList)
updList = gdmCreateSpecList()
upd = gdmCreateSpec(testLib "" "" "" "CDBA" 0)
gdmAddSpecToSpecList(upd updList)
upd = gdmCreateSpec("CadenceBasic" "" "" "" "CDBA" 0)
gdmAddSpecToSpecList(upd updList)
tlib = ddGetObj(testLib)
vnList = '(schematic cmos_sch symbol)
vtList = '(ComposerSymbol ComposerSchematic)
if(neq(tlib nil) then
    printf("Preparing by deleting test library '%s'\n" testLib)
    ddDeleteObj(tlib))
ccpCopy(srcList destList nil 'CCP_EXPAND_ALL vtList vnList "s* v*" "CDBA"
'CCP_UPDATE_FROM_LIBLIST destList)
printf("Cleaning up by deleting test library '%s'\n" testLib)
ddDeleteObj(ddGetObj(testLib))
```

ccpCopy

```
ccpCopy(  
    q_src  
    q_dest  
    [ g_overWrite ]  
    [ s_expFlag ]  
    [ l_copyViewTypeList ]  
    [ l_copyViewNameList ]  
    [ t_vNameSimExp ]  
    [ t_vNameSpace ]  
    [ s_whatToUpdate ]  
    [ q_updateLibList ]  
    [ g_addProp ]  
    [ g_existenceCheck ]  
    [ g_reReferenceCustomVias ]  
)  
=> t / nil
```

Description

Copies source data to another location.

You can expand the data while copying. If you have already expanded the design with the `ccpExpand`, `ccpExpandDesign`, or `ccpExpandConfig` functions, use `CCP_NO_EXPAND` as the value of the `s_expFlag` argument.

Temporary Directories: If the source data that is being copied is in a library that has a temporary directory assigned, then `ccpCopy` copies files from both the regular library directory and its temporary directory. If the same file exists in both the temporary directory and the library directory, the file in the temporary directory is the one that is copied, regardless of its timestamp or whether it is a source file or a derived file. Files are copied to the temporary directory of the destination library only if there are pre-existing files of the same name in the directory; otherwise they are copied into the regular destination library.

If two objects in the source list have the same name, `ccpCopy` will not copy them to the same location in one copy operation, unless you choose to automatically rename them.

Arguments

<i>q_src</i>	Sources <i>gdmSpecList</i> object containing the <i>gdmSpec</i> objects you want to copy. Each <i>gdmSpec</i> object represents a library, cell, view, or file.
--------------	---

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

<i>q_dest</i>	<p>Destination <i>gdmSpecList</i> object containing <i>gdmSpec</i> objects, each of which represents a library, cell, or view.</p> <p>The destination list must have the same number of <i>gdmSpec</i> objects as the source list and each <i>gdmSpec</i> object must be of the same type as its corresponding object in the source list (for example, both must be libraries or both must be cells). Otherwise, the destination list must contain only one object (typically a library, or a cell when the source list contains views).</p>
<i>g_overWrite</i>	<p>Overwrites the object if it already exists at the destination. If set to <code>t</code> and the object is managed and not already checked out, it is checked out by the system.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>
<i>s_expFlag</i>	<p>Expands the flag options. Can be one of the following predefined symbols:</p> <p><code>CCP_NO_EXPAND</code>: No expansion is done. Typically used after a call to <code>ccpExpand</code>.</p> <p><code>CCP_EXPAND_COMANAGED</code>: Expands a directory and includes only the <code>coManaged</code> and <code>alsoManaged</code> files, which are defined in the data registry.</p> <p>Some applications have co-managed files stored at different directory levels. These co-managed files will also be included for copy.</p> <p>The <code>data.dm</code> file, which is invalid in OpenAccess libraries, is no longer automatically included in co-managed sets.</p> <p><code>CCP_EXPAND_ALL</code>: Expands everything in a directory.</p> <p>This argument is optional; its default value is <code>CCP_NO_EXPAND</code>.</p>
<i>l_copyViewTypeList</i>	<p>Displays list of strings specifying the view types to copy. If the list is empty, includes all view types in the hierarchy. This option is ignored if you use <code>CCP_NO_EXPAND</code> as the value of the <i>s_expFlag</i> argument.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>
<i>l_copyViewNameList</i>	

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

	<p>Displays list of view names to copy. If the list is empty, includes all view names in the hierarchy. This option is ignored if you use <code>CCP_NO_EXPAND</code> as the value of the <code>s_expFlag</code> argument.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>
<code>t_vNameSimExp</code>	<p>Specifies the views to copy. This option is ignored if you use <code>CCP_NO_EXPAND</code> as the value of the <code>s_expFlag</code> argument.</p> <p>This is not a regular expression. <code>CCP_NO_EXPAND</code> is also always invalid for the view-based design and config copies.</p>
<code>t_vNameSpace</code>	<p>The name space in which the arguments <code>t_vNameSimExp</code> and <code>l_copyViewNameList</code> are provided. Can be one of the following strings: VHDL, Verilog, Verilog-A, CDBA, Concept, Library, LibraryUnix, or LibraryNT..</p>
<code>s_whatToUpdate</code>	<p>One of the following predefined symbols, which tells the cross-reference updater what to update:</p> <p><code>CCP_UPDATE_COPIED_DATA</code>: Updates cross-references in only the copied data.</p> <p><code>CCP_UPDATE_DESTLIB_ONLY</code>: Updates all cross-references in the destination library.</p> <p><code>CCP_UPDATE_FROM_LIBLIST</code>: Updates cross-references in the libraries you specify in the next argument, <code>q_updateLibList</code>.</p> <p>This argument is optional; its default value is <code>CCP_UPDATE_COPIED_DATA</code>.</p> <p>There might be a scenario where the entire destination library containing a cellview is selected for copy updates. In addition, the cellviews already existing in the destination library will also have their data references. In that case, the updates need to be made in more files other than just the copied set.</p>

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

<i>q_updateLibList</i>	<p>Valid only if the <i>s_whatToUpdate</i> argument has a value of <code>CCP_UPDATE_FROM_LIBLIST</code>. Otherwise, this argument is ignored.</p> <p><i>q_updateLibList</i> takes a <code>gdmSpecList</code> object containing library <code>gdmSpec</code> objects, which specify the libraries in which to update cross-references.</p> <p>If <i>q_updateLibList</i> is empty and <i>s_whatToUpdate</i> is <code>CCP_UPDATE_FROM_LIBLIST</code>, copy proceeds but no updating is done.</p>
<i>g_addProp</i>	<p>Copies files from library and cell property. It is recommended that you use <code>nil</code> for this argument because of potential conflicts between property files. Properties are usually added by the copy updaters. Default is <code>nil</code>.</p>
<i>g_existenceCheck</i>	<p>Sets a flag for the Virtuoso post-copy updater to validate the existence of layers, purposes, <code>viaDefs</code>, and <code>siteDefs</code> in the technology database of the destination library after the copy command is completed. Default is <code>0</code>.</p>
<i>g_reReferenceCustomVias</i>	<p>Sets a flag for the Virtuoso post-copy updater to update custom via definitions to point to cellviews in the destination library. Default is <code>0</code>.</p>

Value Returned

<code>t</code>	The source data was copied.
<code>nil</code>	The source data was not copied.


Additional Information

If two objects in the source list have the same name, you cannot copy them to the same location in one copy operation, unless you choose to automatically rename them.

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

For example, if you have the following data:



and you try to copy `libA/mycell` and `libB/mycell` to the same location, nothing will be copied because `libA/mycell/configuration/vhdl.vhd` conflicts with `libB/mycell/configuration/vhdl.vhd` and `libA/mycell/data.dm` conflicts with `libB/mycell/data.dm`. In such a case, you can copy the data only if you rename the objects with conflicting names.

Therefore, it is recommended to perform only a single transaction instead of performing multiple transactions simultaneously. For example, if you are trying to copy `libA/mycell/configuration/vhdl.vhd` with `libB/mycell/configuration/vhdl.vhd` and `libA/mycell/data.dm` then there would be a conflict between these two transactions.

To automatically rename objects with conflicting names,

➡ Set the following environment variable:

```
CDS_COPY_AUTO_RENAME "yes"
```

If you set this variable, cells containing the view files that have a name conflict are automatically renamed in the destination location, as mentioned below.

Only the views that have at least one file with a name conflict will trigger the auto renaming of the cell. The other views of the cell, when copied in the same operation, will also be copied to the same renamed cell. The auto renamed cell name may be generated by appending the name of the From Cell (if different), and the name of the From Library (if different). If the cell by the same name already exists, then a unique number is appended to the name. The name additions are separated by an underscore ("_") character.

Note: The `CDS_COPY_AUTO_RENAME` environment variable must be set before starting the Copy process because the setting is evaluated only during initialization.


Similarly, other library-level files (files in a library that are not cells) and cell-level files (files in a cell that are not views) are also renamed if they have a name conflict. These files are renamed in the following way:

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

```
file -> file_libName
file.xx -> file_libName.xx
.file -> .file_libName
```

In the above example, if you set `CDS_COPY_AUTO_RENAME` to "yes" and then copy `libA/mycell` and `libB/mycell` to `myNewLib`, you get the following files in the destination:



The `CDS_COPY_AUTO_RENAME` variable applies to the `ccpCopy`, `ccpCopyDesign`, and `ccpCopyConfig` functions. However, it only applies when expansion is being done with these functions; it does not apply if `s_expFlag` is `CCP_NO_EXPAND`.

You can set the maximum cell name length allowed by using the `CDS_MAX_CELL_NAME_LENGTH` environment variable, which applies to the `ccpCopy`, `ccpCopyDesign`, and `ccpCopyConfig` functions.

The compression level of any copied library data gets adjusted to match the compression level of the destination library.

Related Topics

[Generic Design Management \(GDM\) Functions](#)

[Name Spaces for Different Data Types](#)

[ccpExpand](#)

[ccpExpandDesign](#)

[ccpExpandConfig](#)

[gdmSpecp](#)

ccpCopyDesign

```
ccpCopyDesign(  
    G_src  
    G_dest  
    [ g_overWrite ]  
    [ s_expFlag ]  
    [ q_copySkipLibList ]  
    [ l_copyViewTypeList ]  
    [ l_copyViewNameList ]  
    [ t_vNameSimExp ]  
    [ t_vNameSpace ]  
    [ s_whatToUpdate ]  
    [ q_updateLibList ]  
    [ g_addProp ]  
    [ g_existenceCheck ]  
    [ g_reReferenceCustomVias ]  
)  
=> t / nil
```

Description

Copies a design, after expanding it, to the destination library you specify.

`ccpCopyDesign` first traverses the top level design, which is specified by the source cell or view `G_src`. It uses the `pcdb` (parent/child database) API to find all references to other cells. It then traverses those cells, except the ones that are in libraries listed in `q_copySkipLibList`. `ccpCopyDesign` then copies the data, using the following filtering process:

- It copies only the views listed in `l_copyViewTypeList`, `l_CopyViewNameList`, and `t_vNameSimExp`. If the lists are empty, it copies all views.
- It copies files based upon the value of the `s_expFlag` argument, which determines whether all files or only the `coManaged` and `alsoManaged` files are copied.

Temporary Directories: If the source data that is being copied is in a library that has a temporary directory assigned, then `ccpCopyDesign` copies files from both the regular library directory and its temporary directory. If the same file exists in both the temporary directory and the library directory, the file in the temporary directory is the one that is copied, regardless of its datestamp or whether it is a source file or a derived file. Files are copied to the temporary directory of the destination library only if there are pre-existing files of the same name in the directory; otherwise they are copied into the regular destination library.

Name Conflicts: If two objects in the source list have the same name, `ccpCopyDesign` will not copy them to the same location in one copy operation, unless you choose to automatically rename them.

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

Arguments

<i>G_src</i>	Sources gdmSpec object. Must be a cell or view.
<i>G_dest</i>	Specifies gdmSpec object as destination. Must be a library.
<i>g_overWrite</i>	Overwrites the object if it already exists at the destination. If <i>g_overWrite</i> is <i>t</i> and the object is managed and not already checked out, it is checked out by the system.
<i>s_expFlag</i>	<p>Expands the flag options. Can be one of the following predefined symbols:</p> <ul style="list-style-type: none">■ CCP_EXPAND_COMANAGED: Expands a directory and includes only the <i>coManaged</i> and <i>alsoManaged</i> files, which are defined in the <i>dataReg</i>. <p>Some applications have co-managed files stored at different directory levels. These co-managed files will also be included for copy.</p> <p>The <i>prop.xx</i> file, which is invalid in OpenAccess libraries, is no longer automatically included in co-managed sets.</p> <ul style="list-style-type: none">■ CCP_EXPAND_ALL: Expands everything in a directory.
<i>q_copySkipLibList</i>	Excludes gdmSpecList object containing the libraries while copying. <i>q_copySkipLibList</i> is a stop list—design objects in the libraries are not traversed.
<i>l_copyViewTypeList</i>	<p>List of strings specifying the view types to copy. If the list is empty, includes all view types in the hierarchy.</p> <p>The default value is <i>nil</i>.</p>
<i>l_copyViewNameList</i>	<p>Lists view names to copy. If the list is empty, includes all view names in the hierarchy.</p> <p>The default value is <i>nil</i>.</p>
<i>t_vNameSimExp</i>	Specifies the views to copy. This option is ignored if you use CCP_NO_EXPAND as the value of the <i>s_expFlag</i> argument.
<i>t_vNameSpace</i>	Displays the name space in which the arguments <i>t_vNameSimExp</i> and <i>l_copyViewNameList</i> are provided. Can be one of the following strings: <i>VHDL</i> , <i>Verilog</i> , <i>Verilog-A</i> , <i>CDBA</i> , <i>Concept</i> , <i>Library</i> , <i>LibraryUnix</i> , or <i>LibraryNT</i> .

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

<i>s_whatToUpdate</i>	<p>One of the following predefined symbols, which tells the cross-reference updater what to update:</p> <ul style="list-style-type: none">■ <code>CCP_UPDATE_COPIED_DATA</code>: Updates cross-references in only the copied data.■ <code>CCP_UPDATE_DESTLIB_ONLY</code>: Updates all cross-references in the destination library.■ <code>CCP_UPDATE_FROM_LIBLIST</code>: Updates cross-references in the libraries you specify in the <i>q_updateLibList</i> argument. <p>This argument is optional; its default value is <code>CCP_UPDATE_COPIED_DATA</code>.</p>
<i>q_updateLibList</i>	<p>Takes a <code>gdmSpecList</code> object containing library <code>gdmSpec</code> objects, which specify the libraries in which to update cross-references.</p> <p>Valid only if the <i>s_whatToUpdate</i> argument has a value of <code>CCP_UPDATE_FROM_LIBLIST</code>. Otherwise, this argument is ignored.</p> <p>If <i>q_updateLibList</i> is empty and <i>s_whatToUpdate</i> is <code>CCP_UPDATE_FROM_LIBLIST</code>, copy proceeds but no updating is done.</p>
<i>g_addProp</i>	<p>Copies files from library and cell property. It is recommended that you use <code>nil</code> for this argument because of potential conflicts between property files. Properties are usually added by the copy updaters. Default is <code>nil</code>.</p>
<i>g_existenceCheck</i>	<p>Sets a flag for the Virtuoso post-copy updater to validate the existence of layers, purposes, <code>viaDefs</code>, and <code>siteDefs</code> in the technology database of the destination library after the copy command is completed. Default is <code>0</code>.</p>
<i>g_reReferenceCustomVias</i>	<p>Sets a flag for the Virtuoso post-copy updater to update custom via definitions to point to cellviews in the destination library. Default is <code>0</code>.</p>

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

Value Returned

t	The design was copied.
nil	The design was not copied.

Related Topics

[Generic Design Management \(GDM\) Functions](#)

Name Spaces for Different Data Types

ccpCopy

ccpCopyExactDesign

```
ccpCopyExactDesign(  
    G_src  
    G_dest  
    [ g_overWrite ]  
    [ s_expFlag ]  
    [ q_copySkipLibList ]  
    [ l_copyViewTypeList ]  
    [ l_copyViewNameList ]  
    [ t_vNameSimExp ]  
    [ t_vNameSpace ]  
    [ s_whatToUpdate ]  
    [ q_updateLibList ]  
    [ g_addProp ]  
    [ g_existenceCheck ]  
    [ g_reReferenceCustomVias ]  
)  
=> t / nil
```

Description

Copies a design, after expanding it, to the destination library you specify. This function is similar to `ccpCopyDesign`, except that it copies only the exact design—it does not copy any views that are not used in the design.

`ccpCopyExactDesign` traverses the design hierarchy based on the `pcdb` (parent-child database). It excludes the cells that are in libraries listed in `q_copySkipLibList`, if any. It then copies the data.

For each cell, `ccpCopyExactDesign` copies only the view that is used in the design. It does not copy any other views.

To copy other views, you need to specify them in the `l_copyViewTypeList` or `l_copyViewNameList`. If these views have their own hierarchy, then that hierarchy is also traversed.

Temporary Directories: If the source data that is being copied is in a library that has a temporary directory assigned, then `ccpCopyExactDesign` copies files from both the regular library directory and its temporary directory. If the same file exists in both the temporary directory and the library directory, the file in the temporary directory is the one that is copied, regardless of its datestamp or whether it is a source file or a derived file. Files are copied to the temporary directory of the destination library only if there are pre-existing files of the same name in the directory; otherwise they are copied into the regular destination library.

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

Name Conflicts: If two objects in the source list have the same name, `ccpCopyExactDesign` will not copy them to the same location in one copy operation, unless you choose to automatically rename them.

Arguments

<i>G_src</i>	Sources <i>gdmSpec</i> object. Must be a cell or view.
<i>G_dest</i>	Specifies <i>gdmSpec</i> object as destination. Must be a library.
<i>g_overWrite</i>	Overwrites the object if it already exists at the destination. If <i>g_overWrite</i> is <code>t</code> and the object is managed and not already checked out, it is checked out by the system.
<i>s_expFlag</i>	<p>Expands the flag options. Can be one of the following predefined symbols:</p> <ul style="list-style-type: none">■ <code>CCP_EXPAND_COMANAGED</code>: Expands a directory and includes only the <code>coManaged</code> and <code>alsoManaged</code> files, which are defined in the <code>dataReg</code>. <p>Some applications have co-managed files stored at different directory levels. These co-managed files will also be included for copy.</p> <p>The <code>prop.xx</code> file, which is invalid in OpenAccess libraries, is no longer automatically included in co-managed sets.</p> <ul style="list-style-type: none">■ <code>CCP_EXPAND_ALL</code>: Expands everything in a directory.
<i>q_copySkipLibList</i>	<p>Excludes <i>gdmSpecList</i> object containing the libraries while copying. It is a stop list—design objects in the libraries are not traversed.</p> <p>This argument is optional; its default value is <code>nil</code>.</p> <p><i>l_copyViewTypeList</i> List of strings specifying the view types to copy. If the list is empty, includes all view types in the hierarchy.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>
<i>l_copyViewNameList</i>	<p>Lists string specifying additional view names to copy. If the list is empty, only the views that are used in the design are copied.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

<i>t_vNameSimExp</i>	Specifies additional views to copy. This option is ignored if you use <code>CCP_NO_EXPAND</code> as the value of the <i>s_expFlag</i> argument.
<i>t_vNameSpace</i>	Displays the name space in which the arguments <i>t_vNameSimExp</i> and <i>l_copyViewNameList</i> are provided.
<i>s_whatToUpdate</i>	<p>One of the following predefined symbols, which tells the cross-reference updater what to update:</p> <ul style="list-style-type: none">■ <code>CCP_UPDATE_COPIED_DATA</code>: Updates cross-references in only the copied data.■ <code>CCP_UPDATE_DESTLIB_ONLY</code>: Updates all cross-references in the destination library.■ <code>CCP_UPDATE_FROM_LIBLIST</code>: Updates cross-references in the libraries you specify in the <i>q_updateLibList</i> argument. <p>This argument is optional; its default value is <code>CCP_UPDATE_COPIED_DATA</code>.</p>
<i>q_updateLibList</i>	<p>Takes a <code>gdmSpecList</code> object containing library <code>gdmSpec</code> objects, which specify the libraries in which to update cross-references.</p> <p>If <i>q_updateLibList</i> is empty and <i>s_whatToUpdate</i> is <code>CCP_UPDATE_FROM_LIBLIST</code>, copy proceeds but no updating is done.</p>
<i>g_addProp</i>	Copies files from library and cell property. It is recommended that you use <code>nil</code> for this argument because of potential conflicts between property files. Properties are usually added by the copy updaters. Default is <code>nil</code> .
<i>g_existenceCheck</i>	Sets a flag for the Virtuoso post-copy updater to validate the existence of layers, purposes, viaDefs, and siteDefs in the technology database of the destination library after the copy command is completed. Default is <code>0</code> .
<i>g_reReferenceCustomVias</i>	Sets a flag for the Virtuoso post-copy updater to update custom via definitions to point to cellviews in the destination library. Default is <code>0</code> .

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

Value Returned

t	The design was copied.
nil	The design was not copied.

Related Topics

[Generic Design Management \(GDM\) Functions](#)

Name Spaces for Different Data Types

ccpCopy

ccpCopyConfig

```
ccpCopyConfig(  
    G_src  
    G_dest  
    [ g_overWrite ]  
    [ s_expFlag ]  
    [ q_copySkipLibList ]  
    [ l_copyViewTypeList ]  
    [ l_copyViewNameList ]  
    [ t_vNameSimExp ]  
    [ t_vNameSpace ]  
    [ s_whatToUpdate ]  
    [ q_updateLibList ]  
    [ g_addProp ]  
    [ g_existenceCheck ]  
    [ g_reReferenceCustomVias ]  
)  
=> t / nil
```

Description

Copies a design configuration. Expansion is based on configuration rules specified in the `expand.cfg` file in the source configuration view.

A configuration is a set of rules that defines which cellviews under a top-level cell are to be considered part of the design for a given purpose such as netlisting or simulation. For more information about configurations, see [Design Hierarchy Configuration View](#).

Temporary Directories: If the source data that is being copied is in a library that has a temporary directory assigned, then `ccpCopyConfig` copies files from both the regular library directory and its temporary directory. If the same file exists in both the temporary directory and the library directory, the file in the temporary directory is the one that is copied, regardless of its timestamp or whether it is a source file or a derived file. Files are copied to the temporary directory of the destination library only if there are pre-existing files of the same name in the directory; otherwise they are copied into the regular destination library.

Name Conflicts: If two objects in the source list have the same name, `ccpCopyConfig` will not copy them to the same location in one copy operation, unless you choose to automatically rename them.

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

Arguments

<i>G_src</i>	Sources gdmSpec object, which represents a cell or a configuration view.
<i>G_dest</i>	Specifies gdmSpec object as destination. Must be a library.
<i>g_overWrite</i>	Overwrites the object if it already exists at the destination. If <i>g_overWrite</i> is <code>t</code> and the object is managed and not already checked out, it is checked out by the system.
<i>s_expFlag</i>	<p>Expands the flag options. Can be one of the following predefined symbols:</p> <ul style="list-style-type: none">■ <code>CCP_EXPAND_COMANAGED</code>: Expands a directory and includes only the <code>coManaged</code> and <code>alsoManaged</code> files, which are defined in the <code>dataReg</code>. <p>Some applications have co-managed files stored at different directory levels. These co-managed files will also be included for copy.</p> <p>The <code>prop.xx</code> file, which is invalid in OpenAccess libraries, is no longer automatically included in co-managed sets.</p> <ul style="list-style-type: none">■ <code>CCP_EXPAND_ALL</code>: Expands everything in a directory.
<i>q_copySkipLibList</i>	<p>Excludes gdmSpecList object containing the libraries while copying. It is a stop list—design objects in the libraries are not traversed.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>
<i>l_copyViewTypeList</i>	<p>Lists string specifying the view types to copy. If the list is empty, includes all view types in the hierarchy.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>
<i>l_copyViewNameList</i>	<p>Lists view names to copy. If the list is empty, includes all view names in the hierarchy.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>
<i>t_vNameSimExp</i>	Specifies the views to copy. This option is ignored if you use <code>CCP_NO_EXPAND</code> as the value of the <i>s_expFlag</i> argument.
<i>t_vNameSpace</i>	The name space in which the arguments <i>t_vNameSimExp</i> and <i>l_copyViewNameList</i> are provided. Can be one of the following strings: VHDL, Verilog, Verilog-A, CDBA, Concept, Library, LibraryUnix, or LibraryNT.

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

<i>s_whatToUpdate</i>	<p>One of the following predefined symbols, which tells the cross-reference updater what to update:</p> <ul style="list-style-type: none">■ <code>CCP_UPDATE_COPIED_DATA</code>: Updates cross-references in only the copied data.■ <code>CCP_UPDATE_DESTLIB_ONLY</code>: Updates all cross-references in the destination library.■ <code>CCP_UPDATE_FROM_LIBLIST</code>: Updates cross-references in the libraries you specify in the <i>_updateLibList</i> argument. <p>This argument is optional; its default value is <code>CCP_UPDATE_COPIED_DATA</code>.</p>
<i>q_updateLibList</i>	<p>Valid only if the <i>s_whatToUpdate</i> argument has a value of <code>CCP_UPDATE_FROM_LIBLIST</code>. Otherwise, this argument is ignored.</p> <p><i>q_updateLibList</i> takes a <code>gdmSpecList</code> object containing library <code>gdmSpec</code> objects, which specify the libraries in which to update cross-references.</p> <p>If <i>q_updateLibList</i> is empty and <i>s_whatToUpdate</i> is <code>CCP_UPDATE_FROM_LIBLIST</code>, copy proceeds but no updating is done.</p>
<i>g_addProp</i>	<p>Copies files from library and cell property. It is recommended that you use <code>nil</code> for this argument because of potential conflicts between property files. Properties are usually added by the copy updaters. Default is <code>nil</code>.</p>
<i>g_existenceCheck</i>	<p>Sets a flag for the Virtuoso post-copy updater to validate the existence of layers, purposes, viaDefs, and siteDefs in the technology database of the destination library after the copy command is completed. Default is <code>0</code>.</p>
<i>g_reReferenceCustomVias</i>	<p>Sets a flag for the Virtuoso post-copy updater to update custom via definitions to point to cellviews in the destination library. Default is <code>0</code>.</p>

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

Value Returned

t	The design configuration was copied.
nil	The design configuration was not copied.

Related Topics

Generic Design Management (GDM) Functions

Name Spaces for Different Data Types

ccpCopy

ccpDmHasRename

```
ccpDmHasRename (  
    t_dmName  
)  
=> t / nil
```

Description

Checks whether a specified design management system (DMS) is loaded and enabled for GDM renaming. The DMS can be loaded either by Virtuoso at startup or by previously made successful calls to the DM objects from SKILL functions such as `ddGetObjDMSys`, `ddIsPathManaged`, or `gdmstatus`.

Arguments

<code>t_dmName</code>	The GDM name of the DMS as returned by the <code>ddGetObjDMSys</code> function.
-----------------------	---

Value Returned

<code>t</code>	The DMS specified was found to be successfully loaded and enabled for GDM renaming.
<code>nil</code>	The DMS specified was not found to be loaded or is not enabled for GDM renaming.

Related Topics

[Generic Design Management \(GDM\) Functions](#)

[`ddIsPathManaged`](#)

[`ddGetObjDMSys`](#)

ccpDmRename

```
ccpDmRename (
    G_src
    G_dest
    [ ?destLibPath t_destLibPath ]
    [ ?whatToUpdate s_whatToUpdate ]
    [ ?updateLibList q_updateLibList ]
    [ ?existenceCheck x_existenceCheck ]
    [ ?reReferenceCustomVias x_reReferenceCustomVias ]
    [ ?tag t_tag ]
    [ ?description t_description ]
    [ ?extraArgs t_extraArgs ]
    [ ?feedbackStyle x_feedbackStyle ]
    [ ?limitChecks x_limitChecks ]
    [ ?checkOnly g_checkOnly ]
    [ ?returnGdmContext g_returnGdmContext ]
    [ ?returnCcpResults g_returnCcpResults ]
    [ ?feedbackCallback u_feedbackCallback ]
    [ ?doneCallback u_doneCallback ]
    [ ?gdmContextCallback u_gdmContextCallback ]
    [ ?nconstTag l_nconstTag ]
    [ ?dpl l_dpl ]
)
=> t / nil
```

Description

Renames a specified gdmSpec object representing a cellview. The source object is deleted after a copy is created. When you copy a directory containing the cellview, all files in the directory are copied, regardless of whether they are co-managed or not.

You can set the maximum cell name length allowed by using the CDS_MAX_CELL_NAME_LENGTH environment variable.

Arguments

<i>G_src</i>	Sources gdmSpec object representing a cellview.
<i>G_dest</i>	Specifies gdmSpec object as destination. Must be of the same type as the source object.
<i>?destLibPath t_destLibPath</i>	Specifies the path for the library when renaming creates a new library. The parent directory specified in the path must already exist.

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

`?whatToUpdate` *s_whatToUpdate*

One of the following predefined symbols that tell the cross-reference updater what to update:

- `CCP_UPDATE_COPIED_DATA`: Updates cross-references in only the renamed data.
- `CCP_UPDATE_DESTLIB_ONLY`: Updates all cross-references in the destination library. This is the default value.
- `CCP_UPDATE_FROM_LIBLIST`: Updates cross-references in the libraries you specify in the next argument, *q_updateLibList*.

`?updateLibList` *q_updateLibList*

Takes a `gdmSpecList` object containing library `gdmSpec` objects, which specify the libraries in which to update cross-references.

Valid only if the *s_whatToUpdate* argument has a value of `CCP_UPDATE_FROM_LIBLIST`. Otherwise, this argument is ignored.

If *q_updateLibList* is empty and *s_whatToUpdate* is `CCP_UPDATE_FROM_LIBLIST`, rename proceeds but no updating is done.

`?existenceCheck` *x_existenceCheck*

Sets a flag for the Virtuoso post-copy updater to validate the existence of layers, purposes, `viaDefs`, and `siteDefs` in the technology database of the destination library after the copy command is completed. Default is 0.

`?reReferenceCustomVias` *x_reReferenceCustomVias*

Sets a flag for the Virtuoso post-copy updater to update custom via definitions to point to cellviews in the destination library. Default is 0.

`?tag` *t_tag*

Returns callback functions and final return values.

`?description` *t_description*

Displays the DM comment provided while renaming.

`?extraArgs` *t_extraArgs*

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

The custom optional arguments of the DMS.

?feedbackStyle *x_feedbackStyle*

Set of bit flags.

?limitChecks *x_limitChecks*

Set of bit flags.

?checkOnly *g_checkOnly*

Enables the checking mode. When set to `t`, it checks for permissions without renaming. When set to `nil`, it checks for permissions and then renames when no error is found.

?returnGdmContext *g_returnGdmContext*

GDM rename context from calling functions.

?returnCcpResults *g_returnCcpResults*

Final return value details of the rename, as a disembodied property list (DPL).

?feedbackCallback *u_feedbackCallback*

Callbacks indicating that specific DM rename phases have run.

?doneCallback *u_doneCallback*

The one-time callback when rename is done, before returning to the calling function.

?gdmContextCallback *u_gdmContextCallback*

The callback after the GDM context has been defined for the rename operation.

?nconstag *l_nconstag*

Returns object tag with callback functions.

?dpl *l_dpl*

A disembodied property list (DPL) of arguments that can be assigned, overriding keyword arguments.

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

Value Returned

t	The object was renamed, and related tasks, such as preserving DM history, were completed successfully.
nil	The object could not be renamed, or one or more of the related tasks failed.

Related Topics

[Generic Design Management \(GDM\) Functions](#)

[Name Spaces for Different Data Types](#)

[ccpCopy](#)

ccpExpand

```
ccpExpand(  
    q_src  
    s_expFlag  
    [ l_expandViewTypeList ]  
    [ l_expandViewNameList ]  
    [ t_vNameSimExp ]  
    [ t_vNameSpace ]  
    [ g_addProp ]  
    [ g_existenceCheck ]  
    [ g_reReferenceCustomVias ]  
)  
=> q_expSpecList / nil
```

Description

Expands a list of source objects.

Arguments

<i>q_src</i>	Sources <i>gdmSpecList</i> object containing the <i>gdmSpec</i> objects you want to expand. Each <i>gdmSpec</i> object represents a library, cell, or view.
<i>s_expFlag</i>	<p>Expands the flag options. Can be one of the following predefined symbols:</p> <ul style="list-style-type: none">■ CCP_EXPAND_COMANAGED: Expands a directory and includes only the <i>coManaged</i> and <i>alsoManaged</i> files, which are defined in the <i>dataReg</i>. <p>Some applications have co-managed files stored at different directory levels. These co-managed files will also be included for copy.</p> <p>The <i>prop.xx</i> file, which is invalid in OpenAccess libraries, is no longer automatically included in co-managed sets.</p> <ul style="list-style-type: none">■ CCP_EXPAND_ALL: Expands everything in a directory.
<i>l_expandViewTypeList</i>	<p>Lists string specifying the view types to be expanded. If the list is empty, includes all view types in the hierarchy.</p> <p>This argument is optional; its default value is <i>nil</i>.</p>

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

l_expandViewNameList

Lists view names to be expanded. If the list is empty, includes all view names in the hierarchy.

This argument is optional; its default value is `nil`.

t_vNameSimExp

Specifies the views to expand.

t_vNameSpace

The name space in which the arguments *t_vNameSimExp* and *l_expandViewNameList* are provided. Can be one of the following strings: VHDL, Verilog, Verilog-A, CDBA, Concept, Library, LibraryUnix, or LibraryNT..

g_addProp

Copies files from library and cell property. It is recommended that you use `nil` for this argument because of potential conflicts between property files. Properties are usually added by the copy updaters. Default is `nil`.

g_existenceCheck

Sets a flag for the Virtuoso post-copy updater to validate the existence of layers, purposes, viaDefs, and siteDefs in the technology database of the destination library after the copy command is completed. Default is `0`.

This argument is typically used with the copy functions and is not needed for expansion functions.

g_reReferenceCustomVias

Sets a flag for the Virtuoso post-copy updater to update custom via definitions to point to cellviews in the destination library. Default is `0`.

Value Returned

q_expSpecList

A *gdmSpecList* object containing *gdmSpec* objects for the files in the expansion list.

`nil`

The source objects could not be expanded.

Related Topics

[Generic Design Management \(GDM\) Functions](#)

[Name Spaces for Different Data Types](#)

ccpExpandDesign

```
ccpExpandDesign(  
    G_src  
    s_expFlag  
    q_expandSkipLibList  
    [ l_expandViewTypeList ]  
    [ l_expandViewNameList ]  
    [ t_vNameSimExp ]  
    [ t_vNameSpace ]  
    [ g_addProp ]  
    [ g_existenceCheck ]  
    [ g_reReferenceCustomVias ]  
)  
=> q_expSpecList / nil
```

Description

Expands a design, given a source cell or cellview gdmSpec object.

ccpExpandDesign first traverses the top level design, which is specified by the source cell or view *G_src*. It uses the pcdB (parent/child database) API to find all references to other cells. It then traverses those cells, except the ones that are in libraries listed in *q_expandSkipLibList*. ccpExpandDesign then creates the expansion list, using the following filtering process:

- It includes only the views listed in *l_expandViewTypeList*, *l_expandViewNameList*, and *t_vNameSimExp*. If the lists are empty, it includes all views.
- It includes files based upon the value of the *s_expFlag* argument, which determines whether all files or only the *coManaged* and *alsoManaged* files are included.

Arguments

<i>G_src</i>	Sources gdmSpec object. Must be a cell or view.
--------------	---

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

<i>s_expFlag</i>	<p>Expands the flag options. Can be one of the following predefined symbols:</p> <ul style="list-style-type: none">■ CCP_EXPAND_COMANAGED: Expands a directory and includes only the <code>coManaged</code> and <code>alsoManaged</code> files, which are defined in the <code>dataReg</code>. <p>Some applications have co-managed files stored at different directory levels. These co-managed files will also be included for copy.</p> <p>The <code>prop.xx</code> file, which is invalid in OpenAccess libraries, is no longer automatically included in co-managed sets.</p> <p>CCP_EXPAND_ALL: Expands everything in a directory.</p>
<i>q_expandSkipLibList</i>	<p>Excludes <code>gdmSpecList</code> object that contains the libraries while copying. It is a stop list—design objects in the libraries are not traversed.</p>
<i>l_expandViewTypeList</i>	<p>Lists strings specifying the view types to be expanded. If the list is empty, includes all view types in the hierarchy.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>
<i>l_expandViewNameList</i>	<p>Lists view names to be expanded. If the list is empty, includes all view names in the hierarchy.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>
<i>t_vNameSimExp</i>	<p>Specifies the views to expand.</p>
<i>t_vNameSpace</i>	<p>The name space in which the arguments <i>t_vNameSimExp</i> and <i>l_expandViewNameList</i> are provided. Can be one of the following strings: <code>VHDL</code>, <code>Verilog</code>, <code>Verilog-A</code>, <code>CDBA</code>, <code>Concept</code>, <code>Library</code>, <code>LibraryUnix</code>, or <code>LibraryNT</code>.</p>
<i>g_addProp</i>	<p>Copies files from library and cell property. It is recommended that you use <code>nil</code> for this argument because of potential conflicts between property files. Properties are usually added by the copy updaters. Default is <code>nil</code>.</p>
<i>g_existenceCheck</i>	<p>Sets a flag for the Virtuoso post-copy updater to validate the existence of layers, purposes, <code>viaDefs</code>, and <code>siteDefs</code> in the technology database of the destination library after the copy command is completed. Default is <code>0</code>.</p> <p>This argument is typically used with the copy functions and is not needed for expansion functions.</p>

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

g_reReferenceCustomVia Sets a flag for the Virtuoso post-copy updater to update custom via definitions to point to cellviews in the destination library. Default is 0.

This argument is typically used with the copy functions and is not needed for expansion functions.

Value Returned

q_expSpecList A *gdmSpecList* object containing *gdmSpec* objects for the files in the expansion list.

nil The design could not be expanded.

Related Topics

[Generic Design Management \(GDM\) Functions](#)

[Name Spaces for Different Data Types](#)

[gdmCreateSpec](#)

[gdmCreateSpecList](#)

ccpExpandExactDesign

```
ccpExpandExactDesign(  
    G_src  
    s_expFlag  
    q_expandSkipLibList  
    [ l_expandViewTypeList ]  
    [ l_expandViewNameList ]  
    [ t_vNameSimExp ]  
    [ t_vNameSpace ]  
    [ g_addProp ]  
    [ g_existenceCheck ]  
    [ g_reReferenceCustomVias ]  
)  
=> q_expSpecList / nil
```

Description

Expands a design, given a source cell or cellview *gdmSpec* object. This function is similar to `ccpExpandDesign`, except that the expansion list only includes those views that are used in the design.

`ccpExpandExactDesign` traverses the design hierarchy based on the pcdB (parent-child database). It excludes the cells that are in libraries listed in *q_expandSkipLibList*, if any. It then returns the expansion list.

For each cell, `ccpExpandExactDesign` includes only the view that is used in the design. It does not include any other views in the expansion list.

To include other views, you need to specify them in the *l_expandViewTypeList* or *l_expandViewNameList*. If these views have their own hierarchy, then that hierarchy is also traversed.

Arguments

<i>G_src</i>	Source <i>gdmSpec</i> object. Must be a cell or view.
--------------	---

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

s_expFlag

Expands the flag options. Can be one of the following predefined symbols:

- **CCP_EXPAND_COMANAGED:** Expands a directory and includes only the `coManaged` and `alsoManaged` files, which are defined in the `dataReg`.

Some applications have co-managed files stored at different directory levels. These co-managed files will also be included for copy.

The `prop.xx` file, which is invalid in OpenAccess libraries, is no longer automatically included in co-managed sets.

- **CCP_EXPAND_ALL:** Expands everything in a directory.

q_expandSkipLibList

Excludes `gdmSpecList` object that contains the libraries while copying. It is a stop list—design objects in the libraries are not traversed.

l_expandViewTypeList

Lists strings specifying the additional view types to be expanded. If the list is empty, includes only those views that are used in the design.

This argument is optional; its default value is `nil`.

l_expandViewNameList

Lists strings specifying the additional views to be expanded. If the list is empty, includes only those views that are used in the design.

This argument is optional; its default value is `nil`.

t_vNameSimExp

Specifies the additional views to expand.

t_vNameSpace

The name space in which the arguments *t_vNameSimExp* and *l_expandViewNameList* are provided. Can be one of the following strings: `VHDL`, `Verilog`, `Verilog-A`, `CDBA`, `Concept`, `Library`, `LibraryUnix`, or `LibraryNT`.

g_addProp

Copies files from library and cell property. It is recommended that you use `nil` for this argument because of potential conflicts between property files. Properties are usually added by the copy updaters. Default is `nil`.

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

g_existenceCheck Sets a flag for the Virtuoso post-copy updater to validate the existence of layers, purposes, viaDefs, and siteDefs in the technology database of the destination library after the copy command is completed. Default is 0 .

g_reReferenceCustomVias Sets a flag for the Virtuoso post-copy updater to update custom via definitions to point to cellviews in the destination library. Default is 0 .

Value Returned

q_expSpecList A *gdmSpecList* object containing gdmSpec objects for the files in the expansion list.

nil The design could not be expanded.

Related Topics

[Generic Design Management \(GDM\) Functions](#)

[Name Spaces for Different Data Types](#)

[gdmCreateSpec](#)

[gdmCreateSpecList](#)

ccpExpandConfig

```
ccpExpandConfig(  
    G_src  
    s_expFlag  
    [ q_expandSkipLibList ]  
    [ l_expandViewTypeList ]  
    [ l_expandViewNameList ]  
    [ t_vNameSimExp ]  
    [ t_vNameSpace ]  
    [ g_addProp ]  
    [ g_existenceCheck ]  
    [ g_reReferenceCustomVias ]  
)  
=> q_expSpecList / nil
```

Description

Expands a configuration, based on configuration rules specified in the `expand.cfg` file in the source configuration view.

A configuration is a set of rules that defines which cellviews under a top-level cell are to be considered part of the design for a given purpose such as netlisting or simulation.

Arguments

- | | |
|------------------|---|
| <i>G_src</i> | Sources gdmSpec object which represents a cell or a configuration view. |
| <i>s_expFlag</i> | <p>Expands the flag options. Can be one of the following predefined symbols:</p> <ul style="list-style-type: none">■ CCP_EXPAND_COMANAGED: Expands a directory and includes only the <code>coManaged</code> and <code>alsoManaged</code> files, which are defined in the <code>dataReg</code>.

Some applications have co-managed files stored at different directory levels. These co-managed files will also be included for copy.

The <code>prop.xx</code> file, which is invalid in OpenAccess libraries, is no longer automatically included in co-managed sets.■ CCP_EXPAND_ALL: Expands everything in a directory. |

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

<i>q_expandSkipLibList</i>	<p>Excludes gdmSpecList object that contains the libraries while copying. It is a stop list—design objects in the libraries are not traversed.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>
<i>l_expandViewTypeList</i>	<p>Lists strings specifying the view types to be expanded. If the list is empty, includes all view types in the hierarchy.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>
<i>l_expandViewNameList</i>	<p>Lists view names to be expanded. If the list is empty, includes all view names in the hierarchy.</p> <p>This argument is optional; its default value is <code>nil</code>.</p>
<i>t_vNameSimExp</i>	Specifies the views to expand.
<i>t_vNameSpace</i>	The name space in which the arguments <i>t_vNameSimExp</i> and <i>l_expandViewNameList</i> are provided. Can be one of the following strings: VHDL, Verilog, Verilog-A, CDBA, Concept, Library, LibraryUnix, or LibraryNT.
<i>g_addProp</i>	Copies files from library and cell property. It is recommended that you use <code>nil</code> for this argument because of potential conflicts between property files. Properties are usually added by the copy updaters. Default is <code>nil</code> .
<i>g_existenceCheck</i>	<p>Sets a flag for the Virtuoso post-copy updater to validate the existence of layers, purposes, viaDefs, and siteDefs in the technology database of the destination library after the copy command is completed. Default is <code>0</code>.</p> <p>This argument is typically used with copy functions and is not needed for expansion functions.</p>
<i>g_reReferenceCustomVias</i>	<p>Sets a flag for the Virtuoso post-copy updater to update custom via definitions to point to cellviews in the destination library. Default is <code>0</code>.</p> <p>This argument is typically used with the copy functions and is not needed for expansion functions.</p>

Value Returned

<i>q_expSpecList</i>	A gdmSpecList object containing gdmSpec objects for the files in the expansion list.
----------------------	--

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

nil

The configuration could not be expanded.

Related Topics

[Generic Design Management \(GDM\) Functions](#)

[Name Spaces for Different Data Types](#)

ccpGetAutoRename

```
ccpGetAutoRename()  
=> t / nil
```

Description

Gets the current status of the auto rename feature. Earlier, the status of this feature was controlled only by a single time evaluation of the `CDS_COPY_AUTO_RENAME` shell environment variable. This environment variable defines the initial status setting for this feature. Now, the `ccpSetAutoRename` function allows you to change the status after the startup initialization.

Arguments

None

Value Returned

<code>t</code>	The auto rename feature is enabled.
<code>nil</code>	The auto rename feature is disabled.

Examples

The auto rename feature is enabled.

```
ccpGetAutoRename()  
=> t
```

Related Topics

[ccpSetAutoRename](#)

ccpSetAutoRename

```
ccpSetAutoRename (
    g_general
)
=> t
```

Description

Sets the status of the auto rename feature to on or off. Earlier, the status of this feature was controlled only by a single time evaluation of the `CDS_COPY_AUTO_RENAME` shell environment variable. This environment variable defines the initial status setting for this feature. Now, this function allows you to change the status after the startup initialization.

Arguments

<i>g_general</i>	Enables the auto rename feature. When set to <code>t</code> , the <code>CDS_COPY_AUTO_RENAME</code> environment variable is set to YES.
------------------	---

Value Returned

<code>t</code>	Sets the current status of the auto rename feature to on or off.
----------------	--

Examples

If the `ccpSetAutoRename` function is set to `t`, the auto rename feature gets enabled. However, when the `ccpSetAutoRename` function is set to `nil`, the auto rename feature gets disabled.

```
; Calling ccpCopy with autorename mode switched to on.
autoRenameWasOn = ccpGetAutoRename()
if( !autoRenameWasOn  ccpSetAutoRename(t) )

    ok = ccpCopy( sourceGdmList destinationGdmList overwriteBoolean )
; Optional restoring autorename back to off for this example
if( !autoRenameWasOn  ccpSetAutoRename(nil) )
```

ccpRename

```
ccpRename (
    G_src
    G_dest
    [ g_overWrite ]
    [ s_expFlag ]
    [ s_whatToUpdate ]
    [ q_updateLibList ]
    [ g_existenceCheck ]
    [ g_reReferenceCustomVias ]
)
=> t / nil
```

Description

Renames a library, cell, view, or file. The source library, cell, view, or file is copied, and then the original one is deleted. When you copy a directory (library, cell, or view), all the files in the directory are copied, regardless of whether they are co-managed or not.

You can set the maximum cell name length allowed by using the `CDS_MAX_CELL_NAME_LENGTH` environment variable.

Arguments

<i>G_src</i>	Sources gdmSpec object. Represents the library, cell, view, or file to be renamed.
<i>G_dest</i>	Specifies gdmSpec object as destination. Must be of the same type as the source object. For example, both must be libraries.
<i>g_overWrite</i>	Overwrites the object if it already exists at the destination. If <i>g_overWrite</i> is <code>t</code> and the object is managed and not already checked out, it is checked out by the system.

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

s_expFlag

Expands the flag options. One of the following predefined symbols:

- **CCP_EXPAND_COMANAGED:** Expands a directory and includes only the `coManaged` and `alsoManaged` files, which are defined in the `dataReg`. Illegal if your source `gdmSpec` object is a file.

Some applications have co-managed files stored at different directory levels. These co-managed files will also be included for copy.

The `prop.xx` file, which is invalid in OpenAccess libraries, is no longer automatically included in co-managed sets.

The `prop.xx` file, which is invalid in OpenAccess libraries, is no longer automatically included in co-managed sets.

- **CCP_EXPAND_ALL:** Expands everything in a directory.

The *s_expFlag* argument is currently ignored. All the files in the directory are renamed, regardless of whether you specify `CCP_EXPAND_COMANAGED` or `CCP_EXPAND_ALL`.

s_whatToUpdate

One of the following predefined symbols, which tells the cross-reference updater what to update:

- **CCP_UPDATE_COPIED_DATA:** Updates cross-references in only the renamed data.
- **CCP_UPDATE_DESTLIB_ONLY:** Updates all cross-references in the destination library.
- **CCP_UPDATE_FROM_LIBLIST:** Updates cross-references in the libraries you specify in the next argument, *q_updateLibList*.

This argument is optional; its default value is `CCP_UPDATE_COPIED_DATA`.

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

<i>q_updateLibList</i>	<p>Takes a <code>gdmSpecList</code> object containing library <code>gdmSpec</code> objects, which specify the libraries in which to update cross-references.</p> <p>Valid only if the <i>s_whatToUpdate</i> argument has a value of <code>CCP_UPDATE_FROM_LIBLIST</code>. Otherwise, this argument is ignored.</p> <p>If <i>q_updateLibList</i> is empty and <i>s_whatToUpdate</i> is <code>CCP_UPDATE_FROM_LIBLIST</code>, rename proceeds but no updating is done.</p>
<i>g_existenceCheck</i>	<p>Sets a flag for the Virtuoso post-copy updater to validate the existence of layers, purposes, viaDefs, and siteDefs in the technology database of the destination library after the copy command is completed. Default is 0.</p>
<i>g_reReferenceCustomVias</i>	<p>Sets a flag for the Virtuoso post-copy updater to update custom via definitions to point to cellviews in the destination library. Default is 0.</p> <p>This argument is typically used with the copy functions and is not needed for expansion functions.</p>

Value Returned

<code>t</code>	The source object was renamed.
<code>nil</code>	The source object could not be renamed.

Related Topics

[Generic Design Management \(GDM\) Functions](#)

[Name Spaces for Different Data Types](#)

ccpRenameReferenceLib

```
ccpRenameReferenceLib(  
    G_fromLib  
    G_toLib  
    q_updateList  
    [ s_whatCanChange ]  
    [ g_existenceCheck ]  
    [ g_reReferenceCustomVias ]  
)  
=> t / nil
```

Description

Renames references to an external library. The external library is not changed.

Arguments

<i>G_fromLib</i>	Represents the old library. References to this library will be replaced with the value of <i>G_toLib</i> .
<i>G_toLib</i>	Represents the new library. References to the library you specify in <i>G_fromLib</i> will be replaced with references to this library.
<i>q_updateList</i>	Specifies the library in which references are updated. The value of this argument must be a library, or a list of files, views, or cells that belong to the same library.
<i>s_whatCanChange</i>	<p>One of the following predefined symbols, which tells the cross-reference updater what to update:</p> <ul style="list-style-type: none">■ CCP_ALL_REFS: Updates all the references.■ CCP_VALID_TO_REFS: Updates references only if the <i>G_toLib</i> library exists.■ CCP_VALID_FROM_REFS: Updates references only if the <i>G_fromLib</i> library exists.■ CCP_VALID_BOTH_REFS: Updates references only if both the <i>G_toLib</i> and the <i>G_fromLib</i> libraries exist. <p>The default value of this argument is CCP_ALL_REFS.</p>

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

<i>g_existenceCheck</i>	Sets a flag for the Virtuoso post-copy updater to validate the existence of layers, purposes, viaDefs, and siteDefs in the technology database of the destination library after the copy command is completed. Default is 0 .
<i>g_reReferenceCustomVias</i>	<p>Sets a flag for the Virtuoso post-copy updater to update custom via definitions to point to cellviews in the destination library. Default is 0.</p> <p>This argument is typically used with the copy functions and is not needed for expansion functions.</p>

Value Returned

<i>t</i>	The references were renamed.
<i>nil</i>	The references were not renamed.

Related Topics

[Generic Design Management \(GDM\) Functions](#)

[Name Spaces for Different Data Types](#)

ccpRegMonitor

```
ccpRegMonitor(  
    g_copyMonitor  
)  
=> oldCopyMonitor / nil
```

Description

Registers the copy monitor that you create. A copy monitor is a program that displays the progress of the copy command while it is being executed.

Arguments

<i>g_copyMonitor</i>	The copy monitor that you want to register, specified as a symbol. Registering a copy monitor removes any copy monitor that was previously registered. If you only want to remove the previous copy monitor but do not want to register a new copy monitor, specify <code>nil</code> for this argument.
----------------------	--

Value Returned

<i>oldCopyMonitor</i>	The previously registered copy monitor, if any.
<code>nil</code>	There is no previously registered copy monitor.

Examples

```
crm_ret = ccpRegMonitor('copyMonitor)  
printf("ccpRegMonitor returned \"%L\"\n" crm_ret)
```

Additional Information

If you want to write a copy monitor function, you must write it in the format described in this section.

The copy monitor function must be fast, otherwise it will affect the performance of the copy command.

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

The copy monitor must return `nil` for the copy operation to continue; any non-`nil` return value cancels the copy operation.

Use the following format for the copy monitor function that you write:

```
procedure(copyMonitor(myFunction copyPhase fromPath toPath fromSpec toSpec
numCount numTotal "ttttggxx"))
=> nil / non-nil
```

where

- *myFunction* is your copy monitor function's symbol.
- *copyPhase* is the string "copy" .
- *fromPath* is the path (specified as a string) of the file that is being copied.

An empty string is also a legal value.

- *toPath* is the path (specified as a string) to which the file is copied.

An empty string is also a legal value.

- *fromSpec* is the `gdmSpec` object of the file that is being copied.

`nil` is also a legal value.

- *toSpec* is the destination `gdmSpec` object.

`nil` is also a legal value.

- *numCount* is the count, which is incremented by 1 for each file that is copied.

The count is terminated at -1: for every copy operation, there is a final call to the copy monitor with `numCount = -1`.

- *numTotal* is the total number of files that have to be copied.

This number may vary during a copy operation, for example, it may increase when the cellview subdirectories are expanded. If this number is negative, it indicates that the copy operation is failing.

The following example creates a copy monitor function that prints some of its arguments.

```
procedure(copyMonitor(
  copyFn copyPhase fromPath toPath fromSpec toSpec numCount numTotal "ttttggxx")
  if(geqp(numCount 0) then
    if(neq(fromSpec nil) then
      printf("Monitor: %s %L -> %L, %d of %d files.\n"
        copyFn
        gdmInspectSpec(fromSpec "CDBA"))
```

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

```
gdmInspectSpec(toSpec "CDBA")
numCount numTotal)
))
nil
)
```

Related Topics

[ccpCopyExactDesign](#)

[ccpCopyDesign](#)

ccpRegTrigger

```
ccpRegTrigger(
    t_copyPhaseStr
    s_triggerFunction
    [ g_canEditList ]
)
=> t / nil
```

Description

Registers the copy trigger that you create. The copy trigger is called in the copy phase that you specify.

If you run copy commands through the Cadence Library Manager, you need to set the following in your `.cdsenv` file so that copy is done by `cdsCopy` instead of the Library Manager and the copy triggers that you specify are called:

<code>ddserv.lib</code>	<code>enableCopyInDFII</code>	boolean	<code>t</code>
<code>cdsLibManager.copyGlobals</code>	<code>mpsRadio</code>	toggle	<code>(t nil)</code>

The `cdsLibManager.copyGlobals` setting is the default setting for the *Remote Copy Service* option in the Copy Preferences form.

Arguments

- | | |
|--------------------------------|--|
| <code>t_copyPhaseStr</code> | <p>One of the following strings, representing the phase of the copy operation in which you want the trigger function to be called:</p> <ul style="list-style-type: none"> ■ <code>"ccpPostExpandTrigger"</code>: Gets called after expanding a list of source objects. ■ <code>"ccpPreTransferTrigger"</code>: Gets triggered before copying data or files. ■ <code>"ccpPostTransferTrigger"</code>: Gets triggered after copying data or files. ■ <code>"ccpPreUpdateTrigger"</code>: Gets triggered before the cross-reference update. ■ <code>"ccpPostCopyTrigger"</code>: Gets triggered after all the stages of copy are complete. |
| <code>s_triggerFunction</code> | Your trigger function, specified as a symbol. |

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

g_canEditList Allows to edit the copy lists. When set to `nil`, the trigger cannot edit the copy lists.

The performance of the copy operation is better if you specify `nil` for this argument.

Value Returned

`t` The copy trigger was added.

`nil` The copy trigger could not be added.

Examples

```
ccpRegTrigger("ccpPostExpandTrigger" 'copyTriggerPrint t)
```

Additional Information

A copy trigger function is a function that specifies the action to be triggered in a specific phase of the copy operation.

The copy trigger function must return `t` for the copy operation to continue; if the function returns `nil`, the copy operation is canceled.

Use the following format for the copy trigger function:

```
procedure(copyTrigger(myFunction copyPhaseStr checkOffList supplementList
otherFromSpecs otherToSpecs updateList retHint ctxList reserved "stgggggggx"))
=> t / nil
```

where

- *myFunction* is your trigger function's symbol.
- *copyPhaseStr* is the current copy trigger phase, specified as a string.
- *checkOffList* is the list of items to be copied. Each element of the list has the following format:

```
(boolean fromGdmSpec toGdmSpec)
```

If you do not want an item to be copied, set its *boolean* value to `nil`.

The trigger function can only modify the copy lists if the *g_canEditList* argument of `ccpRegTrigger` is `t`.

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

Do not skip any non-derived files because you might lose data. Specifically, if a file is skipped when the trigger is called by a rename function, you will lose the data because the original source will be deleted. The `ccpTagOperation` tag in the `ctxList` argument tells you which function is calling the trigger; you can modify the behavior of the trigger function accordingly.

- `supplementList` is a list to which your trigger function can append additional items to be copied. Any items you add must be in the same format as the items in the `checkOffList`. The `supplementList` ends with a `nil`; if you add items, do not remove the `nil` at the end of the list.
- `otherFromSpecs` and `otherToSpecs` are `gdmSpecLists` of other items to be copied that cannot be modified by the trigger function.
- `updateList` specifies the items to update. The trigger function can add or remove items from this list. `updateList` contains two elements:
 - `s_updateSet`, which is one of the following symbols:
`CCP_UPDATE_COPIED_DATA`
`CCP_UPDATE_DESTLIB_ONLY`
`CCP_UPDATE_FROM_LIBLIST`
 - `q_updateList`, which is a `gdmSpecList` that contains the list of libraries to update.
- `retHint` is a list of one element which is either `nil` or non-`nil`. If your trigger function modifies any copy list, then it must also set the value of `retHint` to non-`nil`.
- `ctxList` is a list that contains the original arguments from the copy command. Each element of the list has the following format:
`(tag value)`

Your trigger function must not modify these values.

Each tag-value pair is one of the following:

Tag	Value of type
<code>ccpTagSkipLibs</code>	<code>gdmSpecList</code>
<code>ccpTagOverwrite</code>	<code>boolean</code>
<code>ccpTagExpand</code>	<code>expansion symbol</code>
<code>ccpTagViewTypes</code>	<code>list of strings</code>
<code>ccpTagViewNames</code>	<code>list of strings</code>
<code>ccpTagNameSpace</code>	<code>string</code>

Cadence Application Infrastructure SKILL Reference

cdsCopy Functions

Tag	Value of type
ccpTagNameExprs	string expression
ccpTagUpdateOpt	update symbol
ccpTagUpdateLibs	gdmSpecList
ccpTagOperation	string identifying the copy function that fired the trigger; one of the following: ccpCopy, ccpCopyDesign, ccpCopyExactDesign, ccpCopyConfig, ccpExpand, ccpExpandDesign, ccpExpandExactDesign, ccpExpandConfig, ccpRename, ccpRenameReferenceLib

- *reserved* is an integer argument that is currently reserved.

The following example creates a copy trigger function that prints some of its arguments:

```
procedure (copyTriggerPrint (myFunction copyPhaseStr checkOffList supplementList
                           otherFromSpecs otherToSpecs updateList retHint
                           ctxList reserved "stgggggggx"))

let ((retOK)
    retOK = t
    printf("Copy phase is \"%s\"\n" copyPhaseStr)
    printf("Calling options were %L\n", ctxList)
    printf("Pre-copy set is %L\n", checkOffList)
    printf("Post-copy is from %L\n", otherFromSpecs)
    printf("                to %L\n", otherToSpecs)
    retOK
)
)
```

Related Topics

[Copy Preferences Form](#)

ccpRemoveTrigger

```
ccpRemoveTrigger(  
    t_copyPhaseStr  
    s_triggerFunction  
)  
=> t / nil
```

Description

Removes the registered copy trigger function from the copy phase you specify.

Arguments

<i>t_copyPhaseStr</i>	One of the following strings, representing the phase of the copy operation in which the trigger function was registered: <ul style="list-style-type: none">■ "ccpPostExpandTrigger"■ "ccpPreTransferTrigger"■ "ccpPostTransferTrigger"■ "ccpPreUpdateTrigger"■ "ccpPostCopyTrigger"
<i>s_triggerFunction</i>	The registered trigger function, specified as a symbol.

Value Returned

<i>t</i>	The copy trigger was removed from the phase you specified.
<i>nil</i>	The copy trigger could not be removed.

Related Topics

[ccpRegTrigger](#)

Library Manager Functions

This topic provides a list of basic editing Cadence® SKILL functions associated with Virtuoso Library Manager. These functions have the prefix `lmgr`.

Only the functions listed here are supported for public use. All other functions, regardless of their name or prefix, and undocumented aspects of the functions described below, are private and are subject to change at any time.

`lmgrAddMenuItems`

`lmgrCreateMenu`

`lmgrCreateMenuItem`

`lmgrDefineInits`

`lmgrDeleteMenuItems`

`lmgrDisplayMessage`

`lmgrGetObject`

`lmgrInsertMenuItems`

`lmgrLogShowPopup`

`lmgrManageMenuItems`

`lmgrMenuSubsInPopup`

`lmgrQueryNamedObjects`

`lmgrSensitizeMenuItems`

`lmgrSetObject`

`lmgrVerbose`

ImgrAddMenuItems

```
ImgrAddMenuItems (  
    t_menuName  
    t_popupSet  
    l_names  
)  
=> t / nil
```

Description

Appends the named objects to the specified menu. An item can be another menu. Each menu item or menu can be added to only one menu. Likewise, any menu item can appear at most once in every pop-up menu. Menus cannot be added to a pop-up. Pop-ups must remain a flat structure only. Pop-ups cannot be added to menus.

You can add only menus to the main pull-down menu bar. Do this by specifying an empty string "", or the reserved name `menuBar` for the `t_menuName` argument. It is also legal to specify the `t_menuName` argument as `popup` or `nil` when the sole purpose is to add an already added object to an indicated pop-up set.

If radio items are added to a particular menu, then only radio items can be added to that menu. The pull-down menu or submenu cannot contain both radio and non-radio items.

This SKILL API can be used in `cdsLibMgr.il` only.

Arguments

<i>t_menuName</i>	The name of the menu to which items are added.
<i>t_popupSet</i>	A string of characters indicating which pop-ups this item is also to be included in. The pop-up set is a string including 0 or more characters using the following mapping: L = included in library list C = included in cell list V = included in view list l = included in library file list c = included in cell file list v = included in view file list t = included in category list
<i>l_names</i>	List of item names that indicates items to be added.

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

Value Returned

t	All arguments were processed without error.
nil	An error occurred, You might have added a menu item to more than one menu or added a menu item that does not exist.

Examples

Adding myMenuItem1 to the MyPulldown menu and then adding MyPulldown menu to menuBar.

```
; Add into the new pull-down menu and into
; the Library and Cell popups
lmgrAddMenuItems ( "MyPulldown" "LC" '( "myMenuItem1" ) )
=> t
; Add the new pull-down menu into the menu banner
lmgrAddMenuItems ( "menuBar" "" '( "MyPulldown" ) )
=> t
```

Related Topics

[lmgrCreateMenu](#)

[lmgrCreateMenuItem](#)

[lmgrDeleteMenuItems](#)

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

ImgrAddToolBarItems

```
ImgrAddToolBarItems(  
    t_toolbarName  
    l_menuItems  
)  
=> t / nil
```

Description

Adds menu items with the specified names to the Library Manager toolbar and optionally appends additional items with multiple calls. Item icons can be set using `ImgrSetObject`.

Arguments

<i>t_toolbarName</i>	Name of the toolbar.
<i>l_menuItems</i>	List of menu items to be added.

Value Returned

<i>t</i>	The specified menu items are added to the toolbar.
<i>nil</i>	Invalid names were entered for the toolbar.

Examples

Adds predefined menu items `viewSeparator3` and `viewToolbar` to `toolBar`.

```
; This predefined toggle item, when used in toolbar can only be accessed one way -  
to hide it.
```

```
; It is preceded by a predefined separator to be shown ahead of the toggle.
```

```
ImgrAddToolBarItems( "toolBar" '( "viewSeparator3" "viewToolbar" ))
```

Sets an icon to the button items used in the toolbar.

```
; Assigning hierarchy check icon to the predefined toggle which resembles  
; its standard check box image.
```

```
ImgrSetObject( "viewToolbar" '( ("icon" "check-red.png" )))
```

Complex combination creates a custom separator and simple button.

```
; Custom items need their callback function to be defined in Virtuoso.
```

```
; (warn) as the callback here provides demo feedback as the action.
```

```
; Replace "warn" with your callback's name instead.
```


Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
when( and( lmgrCreateMenuItem( "mySeparator" "separator" nil )
          lmgrCreateMenuItem( "myGreenButton" "simple"
                              '( ( "label" "Green Flag" )
                                ( "icon" "flag-green.png" )
                                ( "callback" ( "warn" ) ) ) ) )
      lmgrAddToolBarItems( "toolBar" '( "mySeparator" "myGreenButton" ) )
)
```

; If you decide to exclude a previously added item, it can be removed.

```
lmgrRemoveToolBarItems( "toolBar" '( "viewToolbar" "viewSeparator3" ) )
```

Displays the toolbar automatically when the Library Manager is launched.

```
lmgrShowToolBar( "toolBar" t )
```

Related Topics

[lmgrShowToolBar](#)

[lmgrRemoveToolBarItems](#)

[lmgrValidateIcon](#)

lmgrBeginBatchChange

```
lmgrBeginBatchChange (
    )
    => t
```

Description

Activates batch change mode to improve the performance of Library Manager for handling `lmgrSetLibDisplayOverride` calls.

`lmgrBeginBatchChange` supports a nesting feature that helps control the flow of multiple independent source code blocks using the batch change feature. When `lmgrBeginBatchChange` is called to activate batch change mode to an already active batch mode, a new, nested batch change scope is created. All nested scopes created require an equal number of `lmgrEndBatchChange` calls to be deactivated.

Deactivating the first `lmgrBeginBatchChange` call and all the subsequent nested scopes deactivates batch change mode this final transition triggers the display of the overrides in Library Manager. If all the nested scopes are not deactivated, the status of batch change mode remains active indefinitely and the Library Manager does not display the intended override data.

Using `errset` with `lmgrBeginBatchChange` is recommended to ensure that `lmgrBeginBatchChange` is always followed by a matching call to `lmgrEndBatchChange`.

Arguments

None

Value Returned

t Batch change mode is activated.

Examples

Using `errset` with `set` calls to call a matching `lmgrEndBatchChange`.

```
lmgrBeginBatchChange ()
    errset ( lmgrSetLibDisplayOverride ( list ("US_8ths" "basic") ?icon "test.png"
?color "green") t )
    errset ( lmgrSetLibDisplayOverride ( "cdsDefTechLib" ?color "#ff0000" ?icon
"locked.png") t )
```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

`lmgrEndBatchChange ()`

Related Topics

[lmgrInBatchChange](#)

[lmgrEndBatchChange](#)

ImgrCreateMenu

```
ImgrCreateMenu(  
    t_menuName  
    l_menuAttributes  
)  
=> t / nil
```

Description

Creates a structure for a menu, which can be populated with menu items. Once this menu is created, you can install it into the top menu bar or into another parent menu using `ImgrAddMenuItems`.

You can specify a predefined menu name in order to change its label or to add a single map callback attribute to a predefined menu.

A map callback must finish its execution quickly. Lengthy callback options are automatically ignored. Additionally, the Library Manager may choose to not wait for map callbacks to finish if callbacks require more than 5 seconds elapsed time. The reason behind these restrictions is that the X Window System remains locked for all other programs while a map callback is being processed. Efficient shared usage necessitates fast and efficient execution of map callbacks.

The predefined name `pop-up` refers to all pop-ups started from the main selection lists. The `label` and `font` attributes have no significance within a pop-up menu. This mechanism exists only to allow spThis SKILL API can be used in `cdsLibMgr.il` only.ecifying the map callback of pop-ups.

This SKILL API can be used in `cdsLibMgr.il` only.

Arguments

<i>t_menuName</i>	A unique global name to reference this menu.
-------------------	--

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

<code>l_menuAttributes</code>	<p>List of tagged elements consisting of name-value pairs for the following attributes:</p> <p><code>label</code></p> <p>Paired value is the string displayed with this menu. This attribute is mandatory when specifying a custom (non predefined) menu.</p> <p><code>font</code></p> <p>Paired value is a string for the font to use for this particular menu. If this attribute is not specified, or if <code>nil</code> or an empty string is specified, the global default fonts are used.</p> <p><code>mapCallback</code></p> <p>Value is the callback list defining the action, if any, which will be called directly before mapping the menu.</p> <p><code>unmapCallback</code></p> <p>Helps to identify active callbacks when a button is activated without any menu. For the popup menus, combine this attribute with a matching map callback to identify the active menu for any button.</p> <p>You can call unmap in the following way:</p> <pre>list("unmapCallback" list("myUnmapCB" "noOpts"))</pre> <p>It acts as a post notification, an activated command button performs callback before the <code>unmapCallback</code> attribute is received.</p>
-------------------------------	---

Value Returned

<code>t</code>	All arguments were processed without error.
<code>nil</code>	An error occurred. In this case, the menu will <i>not</i> be created.

Examples

Creates a new pulldown menu

```
lmgrCreateMenu ( "MyPulldown" '( ( "label" "My pulldown" ) ) )  
=> t
```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

Related Topics

[Callback Definition List](#)

[ImgrCreateMenuItem](#)

[ImgrInsertMenuItems](#)

[ImgrAddMenuItems](#)

ImgrCreateMenuItem

```
ImgrCreateMenuItem(  
    t_itemName  
    t_itemType  
    l_itemAttributes  
)  
=> t / nil
```

Description

Creates an instance of a menu item, which should be populated into a single menu. Once this menu item is created, you can install it into a menu using `ImgrAddMenuItems()`.

There are four types of menu items: `simple`, `toggle`, `radio`, and `separator`. `simple` is a normal menu item, `toggle` is a menu item with a tick box next to it, `separator` is a line to draw between menu items. You define one radio item for each choice in the set of radio options. All the radio items in the set must be collected in their own pull-down menu or submenu.

This SKILL API can be used in `cdsLibMgr.il` only.

Arguments

<i>t_itemName</i>	A unique global name to reference this menu item.
<i>t_itemType</i>	A standard type, one of <code>simple</code> , <code>toggle</code> , <code>radio</code> , <code>separator</code> .

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

<i>l_itemAttributes</i>	<p>List of tagged elements consisting of name value pairs for the following attributes. None of these attributes are valid for separators:</p> <ul style="list-style-type: none">■ label: Paired value is the string displayed by this item. This attribute is mandatory except when the item type is separator.■ mnemonic: Paired value is a string representing the character mnemonic to use with this object.■ accelerator: This attribute is not supported in the current release.■ font: Paired value is a string for the font to use for this particular item. If this attribute is not specified, or if <i>nil</i> or an empty string is specified, the global default fonts are used.■ callback: Paired value is the callback list defining the action, if any, and the interpretation of results, which will be called when activating this menu item. See the previous section describing callback definitions. For radio items, when the item is selected through the user interface, the callback for both the item being selected and the item being deselected is started.
-------------------------	--

Value Returned

<i>t</i>	All arguments were processed without error.
<i>nil</i>	An error occurred. In this case, the menu item will not be created.

Examples

```
lmgrCreateMenuItem ( "myMenuItem1" "simple"
  '( ( "label" "Do My Thing" )
    ( "callback" ( "myThingCallback" ) )
  )
) => t
```

To set menu access key in Library Manager:

```
lmgrCreateMenuItem (
  "myfunc"
```


Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
"simple"  
list(list("label" "My Function2") list("mnemonic" "F") )  
)  
lmgrCreateMenu( "my_pulldown" list(list( "label" "My Pulldown" ) list( "mnemonic"  
"P") ) ) )  
  
lmgrAddMenuItems("my_pulldown" "LCV" list("myfunc"))  
  
lmgrAddMenuItems("" "" list("my_pulldown"))
```

Related Topics

[Callback Definition List](#)

[lmgrCreateMenuItem](#)

[lmgrInsertMenuItems](#)

[lmgrAddMenuItems](#)

ImgrClearLibDisplayColorOverride

```
ImgrClearLibDisplayColorOverride(  
    g_libNames  
)  
=> t / nil
```

Description

Removes the color display override setting specified by `ImgrSetLibDisplayOverride`. When only color is specified in the override, the entire override for the library is removed.

Arguments

<i>g_libNames</i>	A string or a list of strings. A string must be a valid library name within the current library list. A list of strings can have multiple library names. For example, "basic" or <code>list("basic" "US_8ths"</code>)
-------------------	--

Value Returned

t	Removes the library display override setting for the color specified by <code>ImgrSetLibDisplayOverride</code> .
nil	No value is specified by <i>g_libNames</i> .

Examples

Removes the color display override setting specified by `ImgrSetLibDisplayOverride`.

```
car( errset( ImgrSetLibDisplayOverride( list( "US_8ths" "basic") ?icon "test.png"  
?color "green" ) t ) )  
=>t
```

```
ImgrGetLibDisplayOverride( "basic")  
=>(nil icon ("test.png") color ("green"))
```

```
ImgrClearLibDisplayColorOverride( "basic" )  
=>t
```

```
ImgrGetLibDisplayOverride( "basic")
```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
=>(nil icon ("test.png"))
```

Related Topics

[ImgrSetLibDisplayOverride](#)

[ImgrGetLibDisplayOverride](#)

[ImgrClearLibDisplayOverride](#)

[Display Settings Form](#)

ImgrClearLibDisplayIconOverride

```
ImgrClearLibDisplayIconOverride(  
    g_libNames  
)  
=> t / nil
```

Description

Removes the icon display override setting specified by `ImgrSetLibDisplayOverride`. When only icon is specified in the override, the entire override for the library is removed.

Arguments

<i>g_libNames</i>	A string or a list of strings. A string must be a valid library name within the current library list. A list of strings can have multiple library names. For example, "basic" or <code>list("basic" "US_8ths")</code>
-------------------	---

Value Returned

t	Removes the library display override setting for color specified by <code>ImgrSetLibDisplayOverride</code> .
nil	No value is specified by <i>g_libNames</i> .

Examples

Removes the icon display override setting specified by `ImgrSetLibDisplayOverride`.

```
car( errset( ImgrSetLibDisplayOverride( list( "US_8ths" "basic") ?icon "test.png"  
?color "green" ) t ) )  
=>t
```

```
ImgrGetLibDisplayOverride( "basic")  
=>(nil icon ("test.png") color ("green"))
```

```
ImgrClearLibDisplayIconOverride( "basic" )  
=>t
```

```
ImgrGetLibDisplayOverride( "basic")
```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
=>(nil icon ("green"))
```

Related Topics

[ImgrClearLibDisplayColorOverride](#)

[ImgrClearLibDisplayOverride](#)

[ImgrGetLibDisplayOverride](#)

[ImgrSetLibDisplayOverride](#)

ImgrClearLibDisplayOverride

```
ImgrClearLibDisplayOverride(  
    g_libNames  
)  
=> n_number
```

Description

Removes the display override for a library including the color and icon values specified by `ImgrSetLibDisplayOverride`. When a display override is removed for a library, the default value for the color and icon that is set to Library Manager settings is displayed.

Arguments

<i>g_libNames</i>	A string or a list of strings. A string must be the name of a valid library and it is not necessary for it to be a part of the current library list. A list of strings can have multiple library names and each name is required to be an individual string. For example, "basic" or <code>list("basic" "US_8ths" "not_any_defined_lib")</code>
-------------------	--

Value Returned

<i>n_number</i>	The number of overrides cleared for the specified library name. It can be equal to or less than the number of names in <i>g_libNames</i> .
-----------------	--

Examples

Displays the number of overrides cleared that are specified by `ImgrSetLibDisplayOverride` for "US_8ths", "basic", and "not_any_defined_lib" libraries.

```
car( errset( ImgrSetLibDisplayOverride( list( "US_8ths" "basic" ) ?color "green" )  
t ) )
```

```
=> t
```

```
car( errset( ImgrClearLibDisplayOverride( "US_8ths" ) t ) )
```

```
=> 1
```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
car( errset( lmgrClearLibDisplayOverride( list( "basic" "basic" "undefined" ) ) t ) )
```

```
=> 1
```

```
car( errset( lmgrClearLibDisplayOverride( "not_any_defined_lib" ) t ) )
```

```
=> 0
```

Related Topics

[lmgrClearLibDisplayColorOverride](#)

[lmgrSetLibDisplayOverride](#)

[Display Settings Form](#)

ImgrDefineInits

```
ImgrDefineInits(  
    l_initCallback  
    l_termCallback  
)  
=> t / nil
```

Description

Defines the initialization action to perform when the customization code begins (after parsing the extension file) and the termination action to perform immediately before Library Manager terminates. You must define the callback in the Virtuoso program before it starts. Otherwise, you get an error. No arguments are passed to either callback.

This SKILL API can be used in `cdsLibMgr.il` only.

Arguments

<i>l_initCallback</i>	A callback definition using the syntax described earlier.
<i>l_termCallback</i>	A callback definition using the syntax described earlier.

Value Returned

<i>t</i>	All arguments were processed without error.
<i>nil</i>	An error occurred.

Examples

Defines a callback to be started when Library Manager is started and another when it terminates. This can then do some dynamic customization, depending on the current session.

```
ImgrDefineInits( '( "myInitLibMgr" ) '( "myCloseLibMgr" ) )  
=> t
```


ImgrDeleteMenuItems

```
ImgrDeleteMenuItems (
    l_names
)
=> t / nil
```

Description

Deletes the named objects from the menu/pop-up hierarchy. The object can be either a single item or an entire menu. There is no recovery or undo from this operation. If you merely wish to temporarily disable the view of an object, consider using `ImgrManageMenuItems()` instead.

You can also specify items that have been predefined by Cadence. This function is supplied in the Library Manager local extension file parse environment so you can use it predefined objects. In most cases, newly defined custom items are not deleted. Otherwise, there is no reason to create them in the first place.

This SKILL API can be used in `cdsLibMgr.il` only.

Arguments

<code>l_names</code>	List of item names to be deleted.
----------------------	-----------------------------------

Value Returned

<code>t</code>	All arguments were processed without error.
<code>nil</code>	An error occurred.

Examples

Permanently removes the *Design Manager* menu and all associated menu items. It also removes the menu items from the pop-up sets.

```
ImgrDeleteMenuItems ( "designCascade" )
=> t
```

Related Topics

[ImgrManageMenuItems](#)

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

ImgrSensitizeMenuItems

ImgrDisplayMessage

```
ImgrDisplayMessage(  
    t_text  
    [ g_logOnly ]  
)  
=> t / nil
```

Description

Displays a string in the *Message* area on the Library Manager form and appends it to the Library Manager log file. If desired, the message can be written just to the Library Manager log file and not echoed to the user. Ensure that the string is terminated by a newline character, or the string might be confused with the output from other Library Manager commands or other calls to this function.

Arguments

<i>t_text</i>	The string to output in the Library Manager log file.
<i>g_logOnly</i>	Delivers the string to the message window and writes it to the log file if the string is not specified or is specified as <code>nil</code> , and writes the string just to the log file otherwise.

Value Returned

<i>t</i>	The string is successfully transmitted to the Library Manager.
<i>nil</i>	Either no Library Manager process is running or an error occurred in transmitting the string.

Examples

This example writes a short message to the log file.

```
ImgrDisplayMessage( "Virtuoso talking to libManager" )  
=> t
```

Related Topics

[ImgrVerbose](#)

lmgrEndBatchChange

```
lmgrEndBatchChange (
    )
    => t / nil
```

Description

Deactivates batch change mode of Library Manager for the `lmgrSetLibDisplayOverride` calls. The function is required to deactivate batch change mode to display the override settings from `lmgrSetLibDisplayOverride`, which are being deferred by `lmgrBeginBatchChange`.

The ending of batch change mode by `lmgrEndBatchChange` is prevented at times due to additional calls made to `lmgrBeginBatchChange` to create a nested scope.

Using `errset` with `lmgrEndBatchChange` is recommended to ensure that `lmgrBeginBatchChange` is always followed by a matching call to `lmgrEndBatchChange`.

Arguments

None

Value Returned

<code>t</code>	Deactivated the active batch change mode.
<code>nil</code>	Batch change mode was not active and a warning message is displayed.

Examples

Using `errset` with `set` calls to call a matching `lmgrEndBatchChange`.

```
lmgrBeginBatchChange ()
    errset( lmgrSetLibDisplayOverride( list("US_8ths" "basic") ?icon "test.png"
?color "green") t )
    errset( lmgrSetLibDisplayOverride( "cdsDefTechLib" ?color "#ff0000" ?icon
"locked.png") t )
lmgrEndBatchChange ()
```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

Related Topics

[ImgrBeginBatchChange](#)

[ImgrInBatchChange](#)

ImgrGetLibDisplayOverride

```
ImgrGetLibDisplayOverride(  
    t_libName  
)  
=> l_dpl/ nil
```

Description

Returns the color and icon display override settings specified by `ImgrSetLibDisplayOverride` and related `ImgrClear` functions called earlier in Virtuoso Studio.

Arguments

<i>t_libName</i>	A string specifying a library name.
------------------	-------------------------------------

Value Returned

<i>l_dpl</i>	Lists the override settings specified for color and icon. The values returned are copied from the database and they can be modified without affecting the database.
<i>nil</i>	No display override settings exist for the specified library name.

Examples

Returns the icon and color for `basic` and `US_8ths` libraries specified by `ImgrSetLibDisplayOverride`.

```
ImgrSetLibDisplayOverride ( list( "US_8ths" "basic") ?icon "test.png" ?color  
"green")  
=>t
```

```
ImgrSetLibDisplayOverride ( "US_8ths" ?color "#00ffff")  
=>t
```

```
ImgrGetLibDisplayOverride ( "basic" )  
=>(nil icon ("test.png") color ("green"))
```

```
ImgrGetLibDisplayOverride( "US_8ths" )
```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
=>(nil icon ("test.png") color ("#00ffff"))
```

```
lmgrGetLibDisplayOverride( "no_override_for_library" )  
=>nil
```

Related Topics

[ImgrSetLibDisplayOverride](#)

[ImgrClearLibDisplayColorOverride](#)

[ImgrClearLibDisplayIconOverride](#)

[ImgrClearLibDisplayOverride](#)

[Display Settings Form](#)

ImgrGetObject

```
ImgrGetObject(  
    t_objName  
)  
=> l_attrList / nil
```

Description

Returns a list describing the state of the single named object or `nil` if the object does not exist. The format of the attribute list will be variable length list of tags (strings) paired with matching values that are either a string or Boolean value.

This SKILL API can be used in Virtuoso and `cdsLibMgr.il`.

Arguments

<i>t_objName</i>	Name of a menu or menu item.
------------------	------------------------------

Value Returned

<i>l_attrList</i>	An associated list of tags (strings) paired with values to reflect the status of the named object.
-------------------	--

The example below shows how this associated list appears. The possible tags are `parent`, `type`, `managed`, `sensitive`, `state`, `label`, `mnemonic`, and `font`.

The `state` value can be `nil` for objects that have no state, such as for separators or simple buttons. The state uses `nil` for off/false, and `t` for on/true. This also applies to the Boolean `managed` and `sensitive` values.

The `sensitive` value returned is the logical AND combination of the current value for the object and the values of the menus. For example, menu `M` contains menu item `I`. `M` is not sensitive, but `I` is sensitive, so the `sensitive` value returned for `I` would be `nil`.

<code>nil</code>	The named object does not exist.
------------------	----------------------------------

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

Examples

Retrieves the settings of the *View – Filters* menu item.

```
lmgrGetObject( "viewFilterButton" ) =>

(( "parent" "viewCascade" )
  ( "type" "simple" )
  ( "managed" t )
  ( "sensitive" t )
  ( "label" "Filters... " )
  ( "font" nil )
  ( "mnemonic" nil )
)
```

Related Topics

[lmgrSetObject](#)

ImgrInsertMenuItems

```
ImgrInsertMenuItems (  
    t_menuItem  
    t_popupSet  
    l_names  
)  
=> t / nil
```

Description

Inserts the named objects into the menu directly before the indicated menu item. An object can be an entire menu. Each menu item or menu can be inserted or added to only one menu. Likewise, any menu item can appear at most once in each pop-up menu. Menus can not be inserted (added) to a pop-up. Pop-ups must remain a flat structure only. You cannot insert or add pop-ups to menus. This function is similar to `ImgrAddMenuItems()`, except in the meaning of the first argument.

Only menus can be added to the main pull-down menubar. This is indicated by specifying an empty string "" or the reserved name `menuBar` for the `t_menuName` argument. It is also legal to specify the `t_menuItem` argument as `pop-up` or `nil` when the sole purpose is to add an already added user-defined object to an indicated pop-up set.

If radio items are added to a particular menu, then only radio items may be added to that menu. The pull-down menu or submenu may not contain both radio and non-radio items.

This SKILL API can be used in `cdsLibMgr.il` only.

Arguments

<i>t_menuName</i>	The name of the menu to which the items are added.
-------------------	--

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

t_popupSet

A string of characters indicating which pop-ups this item is to be included in.

The pop-up set is a string including 0 or more characters using the following mapping:

- L = included in library list
- C = included in cell list
- V = included in view list
- l = included in library file list
- c = included in cell file list
- v = included in view file list
- t = included in category list

l_names

List of item names that indicates items to be added.

Value Returned

t

All arguments were processed without error.

nil

An error occurred. You might have added a menu item to more than one menu or added a menu item that does not exist.

Examples

```
; Add into the Edit pull-down menu, before the Copy item
; and not into any popups
lmgrInsertMenuItems ( "copySimpleButton" "" '( "myMenuItem2" ) ) => t
```

Related Topics

[lmgrCreateMenu](#)

[lmgrCreateMenuItem](#)

[lmgrDeleteMenuItems](#)

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

ImgrInBatchChange

```
ImgrInBatchChange (
    )
=> t / nil
```

Description

Checks the cumulative state of batch change mode including that of the active nested scopes. Batch change mode can improve the performance of Library Manager for `ImgrSetLibDisplayOverride` calls.

If the batch change mode is constantly showing the status as active, a loop using `ImgrInBatchChange` can assist in ending batch change mode to set the status as inactive.

Arguments

None

Value Returned

<code>t</code>	Batch change mode is active including the active nested scopes.
<code>nil</code>	Batch change mode is inactive.

Examples

`ImgrInBatchChange` detecting an intentional error, with a forced reset for recovery.

```
let ( ( preInBatch ImgrInBatchChange() ) postInBatch )
```

```
    ; Using errset with set calls to prevent skipping of calling a matching
    ImgrEndBatchChange
```

```
    ImgrBeginBatchChange()
```

```
    ImgrBeginBatchChange() ; Intentional duplicate call error
```

```
        errset( ImgrSetLibDisplayOverride( list("US_8ths" "basic") ?icon "test.png"
?color "green") t )
```

```
        errset( ImgrSetLibDisplayOverride( "cdsDefTechLib" ?color "#ff0000" ?icon
"locked.png") t )
```

```
    ImgrEndBatchChange()
```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
; Basic check for maintaining matching pairs of calls
postInBatch = lmgrInBatchChange()
unless( null( postInBatch ) == null( preInBatch )
    warn( "Issue detected for matching lmgrBeginBatchChange and
lmgrEndBatchChange calls.\n" )
    when( postInBatch

; Reset all is not a perfect solution, but may be preferable over no
display updates.
    while( lmgrInBatchChange()
        lmgrEndBatchChange() )

    error("Forced a reset by lmgrEndBatchChange to end all batch change
modes.\n")
    )
    )
)
```

Related Topics

[lmgrEndBatchChange](#)

[lmgrBeginBatchChange](#)

ImgrLogShowPopup

```
ImgrLogShowPopup ( )  
=> t / nil
```

Description

Restores the context for popup menus for Library Manager replay. This function is only intended for supporting replay and cannot be called from other SKILL engine programs. You do not need to use this function directly.

Arguments

None

Value Returned

<code>t</code>	All popup menu context restored for Library Manager replay.
<code>nil</code>	An error occurred.

ImgrManageMenuItems

```
ImgrManageMenuItems (
    l_names
    g_manageOn
)
=> t / nil
```

Description

Manages the named objects (enabling the display of named objects) inside their menu hierarchy and pop-up sets. Objects can be either a single item or an entire menu.

You can also specify items that have been predefined by Cadence.

This function has the same effect as specifying the `managed` attribute in `ImgrSetObject()`.

This SKILL API can be used in Virtuoso and `cdsLibMgr.il`.

Arguments

<i>l_names</i>	List of item names that indicates items to be deleted.
<i>g_manageOn</i>	A Boolean that sets unmanaged (invisible) if it is <code>nil</code> , and managed otherwise.

Value Returned

<code>t</code>	All arguments were processed without error because the named objects exist.
<code>nil</code>	An error occurred.

Examples

This example causes the separators on the *File* menu to be made invisible.

```
ImgrManageMenuItems ( list ( "fileSeparator1" "fileSeparator2"
"fileSeparator3" "fileSeparator4" ) nil ) => t
```

Related Topics

ImgrDeleteMenuItems

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

ImgrSensitizeMenuItems

ImgrMenuSubsInPopup

```
ImgrMenuSubsInPopup(  
    t_menuName  
    g_isSubMenu  
)  
=> t / nil
```

Description

This API is used only in the Library Manager's `cdsLibMgr.il` file for menu customization. The named menu may be placed into a sub-menu of a popup menu, which appears on clicking the right mouse button (RMB) in the Library Manager's window that lists the library, cell, and view items being browsed. This will be placed in a sub-popup if the boolean value was set to be `true`. In addition, menu items tagged for adding to the popup menus are displayed within its menu's sub-popup (if any). Sub-popup menus may be hierarchically nested per menu as they have been setup/defined through the customized menus' hierarchy.

This SKILL API can only be used in `cdsLibMgr.il`.

Arguments

<i>t_menuName</i>	String for menu's name.
<i>g_isSubMenu</i>	Sets the menu to be shown in the popup as a sub-menu within the popup. When set to <code>nil</code> , the menu will not be displayed and its items will be flattened into its owner's level, i.e. the previous behavior.

Value Returned

<i>t</i>	The previous value set for the sub-menu attribute.
<i>nil</i>	An invalid menu name was specified.

Examples

In this example the menu name is `designCascade`. This places the Cadence standard and topmost Design Manager (labeled) menu's items into a sub-menu for the RMB popup.

```
ImgrMenuSubsInPopup( "designCascade" t)  
=> t
```

ImgrQueryNamedObjects

```
ImgrQueryNamedObjects(  
    [ t_menuName ]  
)  
=> l_list / nil
```

Description

Returns a list containing the names of all menu items in the Library Manager menu named *t_menuName*.

If *t_menuName* is not specified, the names of all menus and menu items in the Library Manager are returned. The order in the list is arbitrary. The list will contain the names of any standard Library Manager objects as well as any objects which have been specified in the `cdsLibMgr.il` file.

Arguments

<i>t_menuName</i>	The option menu name to query.
-------------------	--------------------------------

Value Returned

<i>l_list</i>	The list of menu names found.
<i>nil</i>	Either no Library Manager process is running or an error occurred in retrieving the information, for example, a nonexistent menu name was specified.

Examples

Retrieves the menu items for the *View* menu.

```
ImgrQueryNamedObjects( "viewCascade" )  
=>( "viewFilterButton" "viewSeparator1" "viewRefreshButton" )
```

ImgrRemoveToolBarItems

```
ImgrRemoveToolBarItems (
    t_toolbarName
    l_menuItems
)
=> t / nil
```

Description

Removes the specified items from the given toolbar that were previously added using `ImgrAddToolBarItems`.

Arguments

<i>t_toolbarName</i>	Name of the toolbar.
<i>l_menuItems</i>	List of items to be removed.

Value Returned

<i>t</i>	The specified items were removed from the toolbar.
<i>nil</i>	Invalid toolbar name or a listed item is not a character string.

Examples

Removes `viewToolBar` and `viewSeparator3` menu items from `toolBar`.

```
ImgrRemoveToolBarItems ( "toolBar" '( "viewToolBar" "viewSeparator3" ))
```

Related Topics

[ImgrAddToolBarItems](#)

[ImgrShowToolBar](#)

[ImgrValidatelcon](#)

ImgrSensitizeMenuItems

```
ImgrSensitizeMenuItems(  
    l_names  
    g_sensitive  
)  
=> t / nil
```

Description

Sensitizes the named objects (enabling the active state of named objects) inside their menu hierarchy and pop-up sets. Objects can be either a single item or an entire menu.

You can also specify items that have been predefined by Cadence.

This function has the same effect as specifying the `sensitive` attribute in `ImgrSetObject()`.

Note: Some Cadence predefined simple items can become sensitive or insensitive dynamically whenever a selection is made. For example, the *Check In* and *Check Out* menu items are only sensitive when over a library under design management. Consequently, you might want to permanently disable these menu items by making them unmanaged instead, to avoid your customization being overridden automatically by the Library Manager itself.

This SKILL API can be used in Virtuoso and `cdsLibMgr.il`.

Arguments

<code>l_names</code>	List of item names to be deleted.
<code>g_sensitive</code>	If <code>nil</code> , the menu or menu item is shown grayed-out so that it cannot be selected. Otherwise, it is drawn as normal and can be selected.

Value Returned

<code>t</code>	All arguments were processed without error because the named objects exist.
<code>nil</code>	An error occurred.

Examples

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

This example causes the *View – Filter* menu item to be grayed-out.

```
lmgrSensitizeMenuItems( list ( "viewFilterButton" ) nil ) => t
```

Related Topics

[lmgrDeleteMenuItems](#)

[lmgrSensitizeMenuItems](#)

ImgrSetLCVFilter

```
ImgrSetLCVFilter(  
    t_libfilter  
    t_cellfilter  
    t_viewfilter  
)  
=> t / nil
```

Description

Sets values to filter the libraries, cells, and views listed in the Library Manager.

Arguments

<i>t_libfilter</i>	Specifies a value to filter libraries.
<i>t_cellfilter</i>	Specifies a value to filter cells.
<i>t_viewfilter</i>	Specifies a value to filter views.

Value Returned

<i>t</i>	The specified filters are set for the Library Manager.
<i>nil</i>	The specified filters could not be set because either the Library manager process is missing or an error occurred.

Examples

Opens the Library Manager and sets filters for libraries to "a*", cells to "vdc", and no filter for views.

```
ddsOpenLibManager()  
ImgrSetLCVFilter("a*" "vdc" "")  
=> t
```

Related Topics

[Filter and Search Options](#)

ImgrSetLibDisplayOverride

```
ImgrSetLibDisplayOverride
    g_libNames
    [?color g_color]
    [?icon g_icon]
)
=> t / nil
```

Description

Sets color, icon, or both for a library or a group of libraries to display in the Library Manager. This SKILL function can override the color and icon library attributes settings in the Library Manager.

The database settings of Library Manager take precedence for its defined libraries if this SKILL function targets the same library. When a target library is specified under both systems, the settings specified by `ImgrSetLibDisplayOverride` is displayed if the targeting attribute from the Display Options is set to allow overrides.

The display override values from `ImgrSetLibDisplayOverride` are retained in memory only and are not saved permanently. The settings persist in memory until removed by `ImgrClearLibDisplayOverride`.

Arguments

<i>g_libNames</i>	<p>A string or a list of strings. A string must be a valid library name within the current library list. A list of strings can have multiple library names.</p> <p>For example, "basic" or <code>list("basic" "US_8ths")</code></p>
<i>?color g_color</i>	<p>A string, a symbol, or nil. A string can be a number triplet consisting of 2 hex digits for each of red, green, and blue component color values from 00 to ff, and must be prefixed by #. It can also be a string having a SVG standard color name.</p> <p>The symbol 'standard is accepted and correspondes to the Cadence UI style foreground value.</p> <p>The default value is nil that represents no change to the specified icon setting.</p> <p>For example, "#ff7f50" [having RGB values of 255 127 80] or "coral" or 'standard</p>

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

`?icon g_icon`

A string, a symbol, or `nil`. A string can be either a full path to an icon file or the relative file name that resolves to match using the CSF search mechanism.

You can set the symbol `'standard` to use the default icon of any library displayed in the respective list or tree widget display style.

The default value is `nil` that represents no change to the specified icon setting.

For example, `"warning.png"` or `'standard`

Value Returned

`t`

The specified values are set for the Library Manager.

`nil`

The specified values could not be set because no value is specified in `g_libNames`.

Examples

This includes wrapping example calls within `errset` to avoid potential bypassing of any code occurring after the `errset`, it is recommended for specific batch change cases when an error may occur, such as icon not found via CSF. Adding `errset` to each `lmgrSetLibDisplayOverride` call allows the remaining ones be called in case error occurs in one of them.

```
errset( progn(
  lmgrSetLibDisplayOverride( "workLibrary" ?color "#00ffff" )
  lmgrSetLibDisplayOverride( "testLibrary" ?icon "test.png" ?color "coral" )
  lmgrSetLibDisplayOverride( list( "lib1" "lib2" "lib3" ) ?color "green" ?icon "/"
  usr1/shared/libicons/greenLib.png" )
) t )
```

Related Topics

[hiLoadIconFile](#)

[Display Settings Form](#)

[lmgrClearLibDisplayColorOverride](#)

[lmgrClearLibDisplayOverride](#)

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

ImgrGetLibDisplayOverride

ImgrSetObject

```
ImgrSetObject(  
    t_objName  
    l_attrList  
    t_iconName  
)  
=> t / nil
```

Description

Accepts a list describing the state of the named object. Returns `nil` if the object does not exist. The format of the attribute list is a variable-length list of tags (strings) paired with matching string or Boolean values.

This SKILL API can be used in Virtuoso and `cdsLibMgr.il`.

Arguments

<i>t_objName</i>	Name of a menu or menu item.
------------------	------------------------------

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

l_attrList

List of attribute names and paired values.

Valid values are managed, sensitive, label, mnemonic, font, and state.

The following attributes are recognized but are silently ignored accelerator, parent, and type. Not all attribute values need to be specified in *l_attrList*. Unspecified values are left unchanged.

Any other attribute specifications are illegal and generate an error.

Examples

```
( "managed"          t)
( "sensitive"        t)
( "label"            "Copy" )
( "mnemonic"         "C" )
( "state"            t)
( "icon"             "cut.png" )
```

Sets the file name.

```
( "icon"             "custom.png" "iconMaxLabel" n)
```

Sets the file name and the max label length. Icons are shown in the toolbar in one of the following ways:

- Specified valid icon
- Only label because icon is invalid or is not specified.
- Error image because icon is invalid and the label length is greater than the specified maximum value.

The default value for `iconMaxLabel` is 0, which means no length is specified. If you specify a positive integer to this attribute and the icon is invalid, then only the label is visible when the length is within the specified range. An error icon is displayed if the length exceeds the specified range. An error message is displayed for invalid icon.

An icon set on any standard menu is not displayed. Only custom menus can display an icon when specified. Icon labels are not displayed in menus located in the menu bar.

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

Value Returned

t	The function was called correctly.
nil	The named object does not exist, or invalid attributes are specified.

Examples

Sets the font of the Design Manager pull-down to a large bold courier font.

```
lmgrSetObject ( "designCascade" '( ( "font" "-adobe-courier-bold-o-  
normal--25-180-100-100-m-150-iso8859-1" ) ) ) => t
```

Related Topics

[lmgrGetObject](#)

ImgrShowToolBar

```
ImgrShowToolBar(  
    t_toolbarName  
    g_show  
)  
=> t / nil
```

Description

Displays the specified toolbar when the Library Manager is launched and returns the previous show state specified.

Arguments

<i>t_toolbarName</i>	Name of the toolbar.
<i>g_show</i>	Shows the toolbar in the Library Manager.

Value Returned

<i>t</i>	Returns the previous show state.
<i>nil</i>	The toolbar was previously set to be hidden or invalid name was specified.

Examples

Displays the toolbar named `toolBar` when the Library Manager is launched and returns the previous show state for the toolbar.

```
ImgrShowToolBar( "toolBar" t )
```

Related Topics

[ImgrAddToolBarItems](#)

[ImgrRemoveToolBarItems](#)

[ImgrValidateIcon](#)

ImgrValidateIcon

```
ImgrValidateIcon(  
    t_iconName  
)  
=> t_string
```

Description

Checks whether an icon file exists in the Library Manager for the specified icon name before creating a menu item.

Arguments

<i>t_iconName</i>	Name of the icon file.
-------------------	------------------------

Value Returned

<i>t_string</i>	Returns the file name of the icon.
-----------------	------------------------------------

Examples

Checking whether an icon file exists for the `delete.png` icon.

```
iconName = ImgrValidateIcon( "delete.png" )
```

Related Topics

[ImgrAddToolBarItems](#)

[ImgrRemoveToolBarItems](#)

[ImgrShowToolBar](#)

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

ImgrVerbose

```
ImgrVerbose (
    x_level
)
=> x_level / nil
```

Description

Aids in debugging the callbacks registered in the `cdsLibMgr.il` file. It is possible to get additional informational messages to be shown in the CIW.

Arguments

<code>x_level</code>	An integer representing the verbose level to use. 0 means no messages are written and 1 means that messages are written to the CIW. Any other value is reserved for future use.
----------------------	---

Value Returned

<code>x_level</code>	The verbose level if a valid value was specified.
<code>nil</code>	An invalid verbose level was specified.

Examples

The example shows the effect of selecting several menus after setting verbose to 1.

```
ImgrVerbose ( 1 ) => 1
( Imgr ) Calling: abCopyEnableCallback ( "popup_1" "andrew" "" "" "" "" )
( Imgr ) Calling: abRadioExample ( "RadioOption1" "andrew" "" "" "" "" )
( Imgr ) Calling: abRadioExample ( "RadioOption2" "andrew" "" "" "" "" )
( Imgr ) Calling: abShowAllCheckOuts ( "ShowAllCheckOuts" "andrew" "" "" "" "" )
```

Related Topics

[Library Manager Customization Using Imgr SKILL Functions](#)

Library Manager Customization Using Imgr SKILL Functions

Each of these examples demonstrates some aspect of the Library Manager customization. Some examples solve a particular requirement. Others just demonstrate a principle.

Each example includes both the code you add to the `cdsLibMgr.il` file and the functions you need to define in the Virtuoso Studio design environment.

Example 1: Checking for Startup of Virtuoso in a Design Management System

In this example, the initialization procedure is used to check whether Virtuoso Studio design environment has been started from a design management workarea. If not, the *Design Manager* pull-down menu and all of the menu items contained within it are set to be unmanaged. This simplifies the appearance of the Library Manager menus for those not using design management.

1. Add the following code to the `cdsLibMgr.il` file:

```
; specify names of functions to call at startup and exit
lmgrDefineInits('("abLibMgrInitProc")' ("abLibMgrCloseProc"))
```

2. Define the following functions in Virtuoso, such as in the `.cdsinit` file:

```

/*****
*
*          abLibMgrInitProc()
*
*  When Library Manager is initialized, this gets invoked.
*  It checks to see if we're in a DM workarea, and if not, removes
*  all the DM menus from the libManager.
*
*****/

procedure ( abLibMgrInitProc ( )
  let ( ( path dm filePD )
    path = simplifyFilename ( getWorkingDir ( ) )
    dm    = ddGetPathDMSys ( path )
    ; if you're not in a DM workarea, then remove the Design
Manager
    ; menu
    when ( null ( dm ) || equal ( dm "none" )
      lmgrManageMenuItems ( list ( "designCascade" ) nil )
      lmgrDisplayMessage ( "Not in DM workarea, so DM menus
removed\n" )
    )
    t
  )
)

/*****
*
*          abLibMgrCloseProc ( )
*
*  Sample close procedure.
*
*****/

```


Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
*
*****/

procedure ( abLibMgrCloseProc ( )
    ; no reason to display lib manager, since it has been closed.
    printf ( "My closing procedure was called\n" )
)
```

Example 2: Displaying Checked-Out Library Manager Cellviews and Files

This example uses a script, `tdmfindallcheckouts`, to display all files and cellviews in a library selected within the Library Manager that are checked out and opened by any user.

The menu command starts the callback in Virtuoso, which then uses asynchronous techniques to start the script that uses SKILL IPC. Because the program does not block the user interface, you do not need to wait for it to finish. When the results are available, they are postprocessed and displayed in a Show File window.

This example demonstrates the principles of using an external program via IPC and of displaying the results to the user using a Virtuoso applet.

1. Add the following code to the `cdsLibMgr.il` file:

```
lmgrCreateMenuItem ( "ShowAllCheckOuts" "simple"
    '( ( "label" "Show All CheckOuts" )
      ( "callback" ("abShowAllCheckOuts" ) )
    )
)

; show the pop-up in library (L) list box only, and on the
; design manager pull-down menu
lmgrAddMenuItems ( "designCascade" "L" '( "ShowAllCheckOuts" ) )
```

2. Define the following code in the Virtuoso session:

```
; define the command to execute to find out the checkout information
unless ( boundp( 'abShowAllCheckOutsCommand )
    abShowAllCheckOutsCommand="tdmfindallcheckouts -lisp"
)

* abListCompare ( a b ) *
*
* Compares two lists of strings, for use in a sort function. *
*
*
*****/

procedure ( abListCompare ( a b )
    let( ( ( status 0 ) )
        while ( status==0 && a && b
            status=strcmp ( car ( a ) car( b ) )
            a=cdr ( a )
            b=cdr ( b )
        )
        status<0
    )
)
```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```

    ))

/*****
*
*      abShowAllCheckOutsPostHandler(childexitStatus) *
*
* Read the results of tdmfindallcheckouts - which is in LISP format
* for parsing. Then sort it and display it neatly in a window to
* the user. This function gets called when the tdmfindallcheckouts *
* command completes.
*
*****/

procedure( abShowAllCheckOutsPostHandler(child exitStatus)
  let( (fileName filePort readData window owner libName cellName viewName)
    fileName=abShowAllCheckOutsFileTable[child]
    if( fileName then
      /* read the data from the tdmfindallcheckouts output file -
      - it's in LISP syntax, so simple to read */
      filePort=infile(fileName)
      when(filePort
        readData=car(lineread(filePort))
        close(filePort)
      )
      /* remove the file - don't want to leave junk around */
      deleteFile(fileName)
      /* remove entry from the file table */
      remove(child abShowAllCheckOutsFileTable)
      if( readData then
        /* create a text window */
        window=hiCreateWindow(list(100:100 500:400) "text"
"Show File")
        /* put the show file menus in */
        hiInsertBannerMenu(window fileMenu 0)
        /* sort the data, user, then lib, cell, view */
        readData=sort(readData 'abListCompare)
        /* put the titles in the window */
        hiTextDisplayString(window sprintf(nil "%-10s %-10s
%-10s %-10s\n"
          "Library" "Cell" "View" "CheckOut") nil)
        hiTextDisplayString(window sprintf(nil "%-10s %-10s
%-10s %-10s\n"
          "=====" "=====" "=====" "=====") nil)
        /* output the entries into the window */
        foreach( entry readData
          /* set the variables to the values in the list -
          do it this way to make sure that each
variable has a default value of "" if the list isn't long enough */
          owner=libName=cellName=viewName=""
          foreach( (val varName) entry '(owner libName
cellName viewName)
            set(varName val)
          )
          /* display the formatted output in the window */
          hiTextDisplayString(window
            sprintf(nil "%-10s %-10s %-10s %-10s\n"
              libName cellName viewName owner) nil)
        ) ; foreach
        /* set the title */
        hiSetWindowName(window "Show All Checkouts")

```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
        /* finally, display the window to the user */
        hiDisplayWindow(window)
    else
        lmgrDisplayMessage("No cellViews checked out\n")
    ) ; if
else
    lmgrDisplayMessage("Couldn't find fileName for show all
checkouts\n")
    ) ; if
    t
))

/*****
*
*      abShowAllCheckOuts(MenuName lib cell view file cat)
*
*      Callback function for show all checkouts. Checks to see
*      if a library has been selected, is under DM, and then
*      starts the script to find all the checkouts. The post
*      handler will take care of reading the results and displaying
*      them in a window. This means that it will behave asynchronously.
*
*****/

procedure( abShowAllCheckOuts(MenuName lib cell view file cat)
    let( (fileName dirName handle)
        cond(
            (lib=="")
                lmgrDisplayMessage("Must have library name
selected\n")
            )
            (ddAmUsingDM(ddGetObj(lib))
                dirName=ddGetObj(lib)~>readPath
                unless( 'abShowAllCheckOutsFileTable )
                    abShowAllCheckOutsFileTable=makeTable(
                        'abShowAllCheckOutsTable nil)
                )
                fileName=makeTempFileName("/tmp/abShowAllCheckOuts")
                ; fire off background process
                handle=ipcBeginProcess(
                    sprintf(nil "%s %s > %s"
                        abShowAllCheckOutsCommand
                        dirName fileName)
                    "" nil nil 'abShowAllCheckOutsPostHandler)
                ; remember where the output was stored
                abShowAllCheckOutsFileTable[handle]=fileName
                lmgrDisplayMessage(
                    sprintf(nil
                        "Finding all checkouts for %s - this may
take some time\n" lib))
                )
            (t
                lmgrDisplayMessage(sprintf(nil "%s is an unmanaged
library\n" lib))
            )
        ) ; cond
    t
))
```

3. Put the script `tdmfindallcheckouts` (shown here) in the UNIX search path:

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
#!/bin/csh -f
#
# Author      John Doe
# Group       Custom IC, Cadence UK
# Machine     SUN
# Date        Mar 13, 1998
# Modified    Mar 26, 1998
# By
#
# script to locate all checkouts from a specified library directories
#
# Usage: tdmfindallcheckouts [-lisp] pathToLibrary [pathToLibrary...]
#
# SCCS Info: @(#) tdmfindallcheckouts 03/26/98.14:50:20 1.2
#

set progName=$0
set progName=$progName:t

#check for -lisp argument
if ("arg$1" == "arg-lisp") then
    set lispMode
    shift
endif

# check sufficient arguments
if ($#argv < 1) then
    echo "Usage: $progName [-lisp] pathToLibrary"
    exit 1
endif

# choose awk in a platform independent way
if (-x /bin/nawk) then
    set awk=/bin/nawk
else
    set awk=/bin/awk
endif

# if the -lisp argument was specified, write out the query in a form
# that's easily readable from SKILL
if ($?lispMode) then
    tdmls -c $* | $awk '\
BEGIN {printf("\n")}\
{\
owner=$4;\
paths[1]=paths[2]=paths[3]="";\
numf=split($1,paths,"/");\
paths[numf+1]=$2;\
if(paths[1]!=lib || paths[2]!=cell || paths[3]!=view) \
printf("\n"%s" \ "%s" \ "%s" \ "%s")\n", \
owner,paths[1],paths[2],paths[3]);\
lib=paths[1];cell=paths[2];view=paths[3]}\
END {printf("\n")}'
else
# otherwise write it out in a human readable form
    echo "The following cellViews and files are checked out by:"
    tdmls -c $* | $awk '{owner=$4;\
paths[1]=paths[2]=paths[3]="";\
numf=split($1,paths,"/");\
paths[numf+1]=$2;\
if(numf<3 || paths[1]!=lib || paths[2]!=cell || paths[3]!=view) \
printf("\n"%s" \ "%s" \ "%s" \ "%s")\n', owner,paths[1],paths[2],paths[3]}'
endif
```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
print owner ":" , paths[1], paths[2], paths[3]; \
lib=paths[1]; cell=paths[2]; view=paths[3]} ' | sort
echo "$progName completed"
endif
```

Example 3: Displaying Cellviews and Files to Be Updated with the Next Update Operation

Use this example to add a new command to display any cellviews and files to be updated when the next update operation is performed.

This example also uses the SKILL IPC to start `tdmupdate -n` on the directory that has been selected in the Library Manager. That is, if a cell is selected, just the updates within that cell will be reported. Rather than displaying the results in a Show File window, the results from `tdmupdate -n` are echoed back into the Library Manager output pane.

1. Add the following code to the `cdsLibMgr.il` file:

```
lmgrCreateMenuItem("ShowUpdates" "simple"
  ' ("label" "Show Updates")
    ("callback" ("abShowWhatWillBeUpdated"))
  )

; show the pop-up in library (L), cell (C) and View (V) list boxes
lmgrAddMenuItems("designCascade" "LCV" ' ("ShowUpdates"))
```

2. Define the following code in the Virtuoso session:

```
/* *****
*
*          abTdmUpdateDataHandler(child data)
*
* Data handler for tdmupdate to echo output into the libManager
*          output pane.
*
* *****/

procedure(abTdmUpdateDataHandler(child data)
  lmgrDisplayMessage(data)
)

/* *****
*
*          abTdmUpdateExitHandler(child status)
*
* When tdmupdate -n exits, put a message into the libManager
*          output pane.
*
* *****/

procedure(abTdmUpdateExitHandler(child status)
  lmgrDisplayMessage("tdmupdate -n completed\n")
)

/* *****
```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```

*
*          abRunTdmUpdateCheck(@optional fileName)
*
*
* Start tdmupdate -check, with a couple of handler functions
*
*****/

procedure( abRunTdmUpdateCheck(@optional fileName)
  let( (tdmUpdateCmd)
    tdmUpdateCmd=if(fileName (strcat "tdmupdate -n " fileName)
                     "tdmupdate -n")
    ipcBeginProcess(tdmUpdateCmd "" 'abTdmUpdateDataHandler nil
                    'abTdmUpdateExitHandler)
  )
)

/*****
*
*          abShowWhatWillBeUpdated(MenuName lib cell view file cat)
*
*
* This will cause tdmupdate -n to be started on either the lib/cell/
* view selected, or on the whole workarea if nothing is selected. It
* uses IPC to start the command, and the results will be displayed
* back into the libManager output pane.
*
*****/

procedure(abShowWhatWillBeUpdated(MenuName lib cell view file cat)
  let((ddObj ddGetObjArgs)
    ddGetObjArgs=setof(lcv list(lib cell view) lcv!="")
    if(ddGetObjArgs
      then
        ddObj=apply('ddGetObj setof(lcv list(lib cell view) lcv!=""))
        lmgrDisplayMessage(
          sprintf(nil
            "The following files will be updated by an update operation
for %s:\n"
            buildString(ddGetObjArgs)))
        abRunTdmUpdateCheck(ddObj~>readPath)
      else
        lmgrDisplayMessage("The following files will be updated by an
update for the whole workarea:\n")
        abRunTdmUpdateCheck()
    )
  )
)

```

Example 4: Replacement of File – New – Library in the Library Manager

One potential problem with *File – New – Library* in the Library Manager is that it creates the library itself and then triggers Virtuoso to compile a technology file if needed. Therefore, if you define a `CreateObj` trigger in Virtuoso, the trigger will not be started if the library is created from the Library Manager.

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

You can resolve this problem by removing the existing facility in the Library Manager and creating a new menu item for which the callback is the function that is started from *File – New – Library* in the CIW.

1. Add the following code to the `cdsLibMgr.il` file:

```
; create a new menu item to start the new library in Virtuoso
; directly, without the lib manager version of the form appearing
lmgrCreateMenuItem("abNewLib" "simple"
  (("label" "Library ...")
   ("callback" ("abCreateNewLib")))
)

; Stop the existing new library "button" from being displayed.
; Do this by unmanaging it
lmgrManageMenuItems(list("FileNewLibButton") nil)
; insert the new menu item before the old, now unmanaged, button.
lmgrInsertMenuItems("FileNewLibButton" "" '("abNewLib"))
```

2. Use the following function in the Virtuoso session:

```
/******
*
*          abCreateNewLib(menuName _l _c _v _f _cat)
*
*
* Callback so that the File -> New -> Library from the libManager
* calls Virtuoso's File -> New -> Library. This means that the library
* will be created from within Virtuoso so the postCreateLib trigger
* will get invoked, for example. Most of the arguments here are
* ignored.
*
*****/

procedure( abCreateNewLib(menuName _l _c _v _f _cat)
  when(equal(menuName "abNewLib") ddsHiCreateLibrary())
)
```

Example 5: Dynamically Sensitizing Menu Items in a Design Management Workarea

In this particular example, the capabilities of the function shown in Example 1 are extended so that certain menus can be sensitized within a design management workarea, based on whether the library currently selected is managed or not.

When either the pop-up menu is selected or the design manager pull-down menu is selected, the specified map callback is started in Virtuoso. This then sensitizes the menu items from examples 2 and 3 depending on whether the selected library is under DM control or not. It is vital for this kind of pre-map callback to be fast so that it can make the modification prior to the menu being displayed without blocking the window system.

1. Add the following code to the `cdsLibMgr.il` file:

```
lmgrCreateMenu("popup" '("mapCallback" ("abPopupCallback")))
lmgrCreateMenu("designCascade" '("mapCallback" ("abPopupCallback")))
```

2. Define the following function in Virtuoso:

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
/*
 *
 *      abPopupCallback(_menuName lib _c _v _f _cat)
 *
 * pre-map callback to be started from either pop-up or design manager
 * pull-down. This sensitizes two of the menu items based on whether
 * this library is DM managed or not.
 *
 */

procedure( abPopupCallback( menuName lib _c _v _f _cat)
lmgrSensitizeMenuItems('("ShowAllCheckOuts" "ShowUpdates")
    lib!="" && ddAmUsingDM(ddGetObj(lib)))
    t
)
```

Example 6: Changing Labels and Fonts

You can use this sample function either in Virtuoso or in the `cdsLibMgr.il` file. In the following simple example, the label for *Copy Wizard* is changed to *Advanced Copy* and the font for *File – Open* is changed.

```
; change label for Copy Wizard
lmgrSetObject("editCopyButton" '("label" "Advanced Copy..."))
;; choose silly font for File->Open
lmgrSetObject("FileOpenButton"
'("font"
"-adobe-helvetica-medium-o-normal--12-120-75-75-p-67-iso8859-1"))
)
```

Example 7: Adding Toggles and Radio Button Fields

This example does not perform any useful task, but it demonstrates how you use the other menu types that are available. It creates a new pull-down menu in the menu bar, *GUI Objects*, which contains a toggle menu underneath, and then a submenu containing three radio options. The callback to Virtuoso causes a message to be displayed on the Library Manager output pane reflecting the current settings.

Note: The radio options must be in their own menu.

1. Add the following code to the `cdsLibMgr.il` file:

```
; create the toggle button
lmgrCreateMenuItem("ToggleExample" "toggle"
'(("label" "Toggle Example")
  ("callback" ("abToggleExample")))
)

; create a new pull-down menu, to contain the toggle example
lmgrCreateMenu("GUICascade" '("label" "GUI Objects"))

; Add the toggle example into the new pull-down menu
lmgrAddMenuItems("GUICascade" "" '("ToggleExample"))
```


Cadence Application Infrastructure SKILL Reference

Library Manager Functions

```
; Add the new pull-down menu into the menu banner
lmgrAddMenuItems("menuBar" "" '("GUICascade"))

; Create Three radio options
lmgrCreateMenuItem("RadioOption1" "radio"
  '(("label" "Option 1")
    ("callback" ("abRadioExample"))
  )
)
lmgrCreateMenuItem("RadioOption2" "radio"
  '(("label" "Option 2")
    ("callback" ("abRadioExample"))
  )
)
lmgrCreateMenuItem("RadioOption3" "radio"
  '(("label" "Option 3")
    ("callback" ("abRadioExample"))
  )
)

; Create a pull-down to contain the three radio options
lmgrCreateMenu("RadioPulldown" '(("label" "Radio Pulldown")))
; Add the radio options to the pull-down. Note: The radio options must
; be in their own submenu
lmgrAddMenuItems("RadioPulldown" "" '("RadioOption1" "RadioOption2"
  "RadioOption3"))

lmgrAddMenuItems("GUICascade" "" '("RadioPulldown"))
```

2. Use the following callbacks in Virtuoso:

```
/******
*
*          abToggleExample(_menuName _l _c _v _f _cat)
*
* Just prints a message saying what the current state of the toggle
* setting is
*
* *****/

procedure( abToggleExample(_menuName _l _c _v _f _cat)
  lmgrDisplayMessage(
    sprintf(nil "Toggle set to %L\n"
      ; note - uses assoc to lookup state information
      cadr(assoc("state" lmgrGetObject("ToggleExample"))))
  )
)

/******
*
*          abRadioExample(menuName _l _c _v _f _cat)
*
* Displays which radio option was selected or unselected
*
* *****/

procedure( abRadioExample(menuName _l _c _v _f _cat)
  lmgrDisplayMessage(
    sprintf(nil "Radio %s %sselected\n" menuName
      if( cadr(assoc("state" lmgrGetObject(menuName))) "" "un")
```

Cadence Application Infrastructure SKILL Reference

Library Manager Functions

))
)

Related Topics

[ImgrManageMenuItems](#)

[ImgrDisplayMessage](#)

[ImgrCreateMenuItem](#)

[ImgrVerbose](#)

[ImgrSetObject](#)

Plotter Functions

This topic provides a list of basic editing Cadence® SKILL functions associated with the configuration of plotters. These functions have the prefix `ps`.

Only the functions listed here are supported for public use. All other functions, regardless of their name or prefix, and undocumented aspects of the functions described below, are private and are subject to change at any time.

- `psConfigLoaded`
- `psLoadCdsPlotInit`
- `psQueryPaperSize`
- `psQueryPaperSizes`
- `psQueryPlotters`
- `psQueueStatus`

psConfigLoaded

```
psConfigLoaded( )  
=> t / nil
```

Description

Indicates if the `.cdsplotinit` is already loaded.

Arguments

None

Value Returned

<code>t</code>	The <code>.cdsplotinit</code> is already loaded.
<code>nil</code>	The <code>.cdsplotinit</code> is not loaded.

Related Topics

[psQueryPaperSize](#)

[psQueryPlotters](#)

[psQueueStatus](#)

psLoadCdsPlotInit

```
psLoadCdsPlotInit( )  
=> t / nil
```

Description

Indicates if the `.cdsplotinit` has successfully loaded or not.

Arguments

None

Value Returned

<code>t</code>	The <code>.cdsplotinit</code> successfully loaded.
<code>nil</code>	The <code>.cdsplotinit</code> did not load.

Related Topics

[psQueryPaperSizes](#)

[psConfigLoaded](#)

[psQueueStatus](#)

psQueryPaperSize

```
psQueryPaperSize(  
    t_plotterName  
    t_paperSize  
)  
=> l_dimensions
```

Description

Returns the dimensions of the specified paper size.

Arguments

<i>t_plotterName</i>	Name of the plotter.
<i>l_paperSizes</i>	The paper size to query for dimensions.

Value Returned

<i>l_dimensions</i>	Returns the dimensions of the given paper size in inches.
---------------------	---

Related Topics

[psQueryPaperSizes](#)

[psConfigLoaded](#)

[psQueueStatus](#)

psQueryPaperSizes

```
psQueryPaperSizes(  
    t_plotterName  
)  
=> l_paperSizes
```

Description

Returns the paper sizes (such as A size) and offset of the paper that the plotter uses.

Arguments

<i>t_plotterName</i>	Name of the plotter.
----------------------	----------------------

Value Returned

<i>l_paperSizes</i>	Returns the paper sizes and offset of the paper that the plotter uses.
---------------------	--

Related Topics

[psLoadCdsPlotInit](#)

[psConfigLoaded](#)

[psQueueStatus](#)

psQueryPlotters

```
psQueryPlotters( )  
    => l_plotters
```

Description

Returns a list of plotter names from the loaded `.cdsplotinit` files.

Arguments

None

Value Returned

<code>l_plotters</code>	Returns a list of plotter names from all <code>.cdsplotinit</code> files that are loaded.
-------------------------	---

Related Topics

[psQueryPaperSizes](#)

[psConfigLoaded](#)

[psQueueStatus](#)

[psConfigLoaded](#)

psQueueStatus

```
psQueueStatus( )  
=> t
```

Description

Displays the plot jobs in the spooling queues.

Arguments

None

Value Returned

t Plot Jobs displayed in the spooling queues.

Related Topics

[psQueryPaperSizes](#)

[psConfigLoaded](#)

[psLoadCdsPlotInit](#)