

Cadence SKILL Development Reference

**Product Version IC23.1
June 2023**

© 2023 Cadence Design Systems, Inc.
Printed in the United States of America.

Cadence Design Systems, Inc. (Cadence), 2655 Seely Ave., San Jose, CA 95134, USA.

Open SystemC, Open SystemC Initiative, OSCI, SystemC, and SystemC Initiative are trademarks or registered trademarks of Open SystemC Initiative, Inc. in the United States and other countries and are used with permission.

Trademarks: Trademarks and service marks of Cadence Design Systems, Inc. contained in this document are attributed to Cadence with the appropriate symbol. For queries regarding Cadence's trademarks, contact the corporate legal department at the address shown above or call 800.862.4522. All other trademarks are the property of their respective holders.

Restricted Permission: This publication is protected by copyright law and international treaties and contains trade secrets and proprietary information owned by Cadence. Unauthorized reproduction or distribution of this publication, or any portion of it, may result in civil and criminal penalties. Except as specified in this permission statement, this publication may not be copied, reproduced, modified, published, uploaded, posted, transmitted, or distributed in any way, without prior written permission from Cadence. Unless otherwise agreed to by Cadence in writing, this statement grants Cadence customers permission to print one (1) hard copy of this publication subject to the following conditions:

1. The publication may be used only in accordance with a written agreement between Cadence and its customer.
2. The publication may not be modified in any way.
3. Any authorized copy of the publication or portion thereof must include all original copyright, trademark, and other proprietary notices and this permission statement.
4. The information contained in this document cannot be used in the development of like products or software, whether for internal or external use, and shall not be used for the benefit of any other party, whether or not for consideration.

Disclaimer: Information in this publication is subject to change without notice and does not represent a commitment on the part of Cadence. Except as may be explicitly set forth in such agreement, Cadence does not make, and expressly disclaims, any representations or warranties as to the completeness, accuracy or usefulness of the information contained in this document. Cadence does not warrant that use of such information will not infringe any third party rights, nor does Cadence assume any liability for damages or costs of any kind that may result from use of such information.

Cadence is committed to using respectful language in our code and communications. We are also active in the removal and replacement of inappropriate language from existing content. This product documentation may however contain material that is no longer considered appropriate but still reflects long-standing industry terminology. Such content will be addressed at a time when the related software can be updated without end-user impact.

Restricted Rights: Use, duplication, or disclosure by the Government is subject to restrictions as set forth in FAR52.227-14 and DFAR252.227-7013 et seq. or its successor

Contents

1

Cadence SKILL Development Tools 9

Licensing Requirements 9

2

Profiler Functions 11

profile 12

profileReset 14

profileSummary 16

unprofile 19

3

Lint Functions 21

skDisableMessage 23

skDisableMessageBlock 25

skEnableMessageBlock 27

skIgnoreMessage 29

sklint 31

skUnignoreMessage 37

4

Context Functions 39

callInitProc 40

callUserAutoInitProc 41

checkContextBit 42

defCapDepends 43

defCapPrefixes 45

defInitProc 47

isContextLoaded 49

Cadence SKILL Development Reference

<u>loadContext</u>	50
<u>loadTopContextForms</u>	52
<u>saveContext</u>	54
<u>setContext</u>	56
<u>setSaveContextVersion</u>	58
<u>getCurSaveContextVersion</u>	59
<u>getNativeContextVersion</u>	60
<u>getCompatContextVersion</u>	61

5

Debug Functions 63

<u>break</u>	65
<u>breakpt</u>	66
<u>breakptMethod</u>	69
<u>clear</u>	71
<u>cont, continue</u>	72
<u>count</u>	73
<u>debugQuit</u>	75
<u>debugStatus</u>	76
<u>dump</u>	78
<u>gcsummary</u>	80
<u>getAllLoadedFiles</u>	82
<u>getCallingFunction</u>	83
<u>getFunctions</u>	85
<u>getGFbyClass</u>	86
<u>ilAddTopLevelErrorHandler</u>	87
<u>ilDebugCountLevels</u>	88
<u>ilGetGFbyClass</u>	89
<u>ilGetIdeSessionWindow</u>	90
<u>ilGetTCovFiles</u>	91
<u>ilMergeTCovData</u>	92
<u>ilRemoveMethod</u>	93
<u>ilRemoveTopLevelErrorHandler</u>	95
<u>ilSlotBoundp</u>	96
<u>ilToolBox</u>	97

Cadence SKILL Development Reference

<u>inNext</u>	98
<u>inStepOut</u>	100
<u>installDebugger</u>	102
<u>listAlias</u>	103
<u>listFunctions</u>	105
<u>listVariables</u>	107
<u>memoryAllocated</u>	108
<u>next</u>	109
<u>pp</u>	111
<u>printFunctions</u>	113
<u>printObject</u>	115
<u>printstruct</u>	117
<u>printVariables</u>	118
<u>removeMethod</u>	120
<u>resume</u>	122
<u>skillDebugger</u>	124
<u>skillDevStatus</u>	126
<u>stacktrace</u>	127
<u>step</u>	129
<u>stepend</u>	131
<u>stepout</u>	133
<u>toplevel</u>	135
<u>tracef</u>	137
<u>tracelevlimit</u>	140
<u>tracelevunlimit</u>	142
<u>tracep</u>	143
<u>tracev</u>	144
<u>unbreakpt</u>	146
<u>unbreakptMethod</u>	148
<u>uncount</u>	149
<u>uninstallDebugger</u>	151
<u>untrace</u>	152
<u>untracep</u>	154
<u>untracev</u>	155
<u>unwatch</u>	156
<u>watch</u>	157

Cadence SKILL Development Reference

<u>where</u>	158
<u>whereIs</u>	160

6

Finder Functions 161

<u>findResetDb</u>	162
<u>startFinder</u>	163

7

Tabulator Functions 165

<u>skTabulate</u>	166
<u>skTabulateSKILL</u>	169

8

SKILL IDE Functions 171

<u>ilgAddRecentFiles</u>	173
<u>ilgAppendText</u>	174
<u>ilgCopy</u>	175
<u>ilgCut</u>	176
<u>ilgFindIdent</u>	177
<u>ilgFindParenthesis</u>	179
<u>ilgFoldLine</u>	181
<u>ilgGetCursorLocation</u>	182
<u>ilgGetEditLock</u>	183
<u>ilgGetHighlight</u>	184
<u>ilgGetSelectedLocation</u>	186
<u>ilgGetText</u>	187
<u>ilgInvokeIDE</u>	189
<u>ilgLastDir</u>	190
<u>ilgPaste</u>	191
<u>ilgPositionInComment</u>	192
<u>ilgRegisterSelectionCB</u>	194
<u>ilgResetErrorMarker</u>	195
<u>ilgResetHighlight</u>	196

Cadence SKILL Development Reference

<u>ilgResetWarningMarker</u>	197
<u>ilgRunSKILLIDE</u>	198
<u>ilgScrollToLocation</u>	199
<u>ilgSearchText</u>	200
<u>ilgSelectText</u>	202
<u>ilgSetColor</u>	203
<u>ilgSetCursorLocation</u>	205
<u>ilgSetEditLock</u>	206
<u>ilgSetErrorMarker</u>	208
<u>ilgSetHighlight</u>	209
<u>ilgSetWarningMarker</u>	211
<u>ilgUnfoldLine</u>	212
<u>ilgUnregisterSelectionCB</u>	213

Cadence SKILL Development Reference

Cadence SKILL Development Tools

This manual provides information on using the SKILL Development tools, which include the Lint, Profiler, Finder, Code Browser, Surveyor, and Debugger. These tools, especially the Finder, provide quick reference information for syntax and abstract statements for SKILL language functions and application programming interfaces (APIs). It also provides information on the basic SKILL language functions.

The [Walkthrough](#) topic in this help system identifies and explains the tasks you perform when you develop SKILL programs using the SKILL development tools. Using a demonstration program, it explains the various tools available to help you measure the performance of your code and also look for possible errors and inefficiencies in your code. It includes a section on working in the non-graphical environment.

Licensing Requirements

SKILL uses the Cadence Design Framework II license (License Number 111), which is checked out at the launch of the `skill` executable or the workbench.

When you use the following SKILL development APIs, Virtuoso also checks out the Cadence SKILL Development Environment license (License Number 900): `getLoadLine`, `getLoadByte`, `getLoadFile`, `trace`, `step`, `next`, `stepout`, `stepend`, `meter`, `breakpt`, `tracev`, `tracep`, `watch`, `unwatch`, `profile`, `echo`, `saveContext`, `stacktrace`, `where`, and `gcsummary`.

Related Topics

[SKILL Lint messages](#)

[Message Groups](#)

Cadence SKILL Development Reference

Cadence SKILL Development Tools

Profiler Functions

The SKILL Profiler reports the number of times a SKILL function is called (as an additional column in the table view of the profiler's result).

The following SKILL Profiler functions are available.

- [profile](#)
- [profileReset](#)
- [profileSummary](#)
- [unprofile](#)

Related Topics

[Lint Functions](#)

[Context Functions](#)

[Debug Functions](#)

[Finder Functions](#)

[Tabulator Functions](#)

[SKILL IDE Functions](#)

Cadence SKILL Development Reference

Profiler Functions

profile

```
profile(  
    s_profileField  
)  
=> t
```

Description

Turns on global SKILL profiling for measuring time or memory.

The profiler is interrupt-driven. It walks the SKILL stack and records functions being executed. When `unprofile` or `profileSummary` are called, profiling is stopped. `profileSummary` prints a report of the time spent or memory allocated in the functions executed. Profiling time is cumulative, so you must call `profileReset` to reset the profiled data.

Time measurements are done with UNIX system functions that have coarse granularity at 1/60 of a second, so functions must be executed many times for the CPU times to be reasonably accurate.

SKILL Profiler is not yet supported on the Windows/Wintel platform.

Arguments

<i>s_profileField</i>	Can be one of the following:
'time	Only time is profiled.
'realTime	Profiles real (elapsed) time rather than CPU time.
'memory	Only SKILL memory allocated is profiled.

Value Returned

t	Always returns t.
---	-------------------

Examples

```
profile( 'time)  
for(i 1 10000 i+1)  
profileSummary( ?file "/tmp/profile.results")
```

Cadence SKILL Development Reference

Profiler Functions

Related Topics

[Profiler Functions](#)

[unprofile](#)

[profileReset](#)

[profileSummary](#)

profileReset

```
profileReset(  
    )  
=> t
```

Description

Resets all SKILL profiler data.

Resets all data but keeps SKILL profiling running. Sets the accumulated CPU time and memory for all functions to zero. This is useful if you want to run the same set of profiled functions many times for different inputs so you can compare or average the results. When `profile` is first called, the profiling data is already initialized to zeros and there is no need to do an initial call to `profileReset`.

SKILL Profiler is not yet supported on the Windows/Wintel platform.

Arguments

None

Value Returned

`t` Always returns `t`.

Examples

Prints summary 1.

```
profileSummary( ?file "myReport1" )  
=> t
```

Resets the profiling timer/counter. Now run the same functions on another set of data.

```
profileReset()  
=> t
```

Prints summary 2.

```
profileSummary( ?file "myReport2" )  
=>
```

Cadence SKILL Development Reference

Profiler Functions

Related Topics

Profiler Functions

profile

unprofile

profileSummary

profileSummary

```
profileSummary(  
    [ ?file t_filename ]  
    [ ?sort s_sortKey ]  
    [ ?filters g_filterSpec ]  
    [ ?maxFns x_maxDisplayed ]  
    [ ?minSecs f_minSecs ]  
    [ ?minBytes x_minBytes ]  
    [ ?children g_showChildren ]  
)  
=> t
```

Description

Prints a summary of profiling results, showing either the execution time or memory allocated to SKILL functions that were executed.

You select whether to profile time or memory by the argument you pass to the `profile` function. After executing the functions you are interested in, call `profileSummary` to generate a report of the CPU time spent in the functions or the amount of SKILL memory allocated in those functions. Using `profileSummary` options, you can sort and filter data to see only the functions in which you are interested. All functions are measured so you can create multiple profile summaries at the end of each session.

SKILL Profiler is not yet supported on the Windows/Wintel platform.

Arguments

<code>?file t_filename</code>	Specifies the report file name. Defaults to <code>ilProf_<login>.out</code> in the <code>/tmp</code> directory.				
<code>?sort s_sortKey</code>	Changes the fields the profile summary is sorted by. <table><tr><td><code>'total</code></td><td>Seconds or bytes allocated in functions and children. This is the default.</td></tr><tr><td><code>'inside</code></td><td>Seconds or bytes allocated in function only.</td></tr></table>	<code>'total</code>	Seconds or bytes allocated in functions and children. This is the default.	<code>'inside</code>	Seconds or bytes allocated in function only.
<code>'total</code>	Seconds or bytes allocated in functions and children. This is the default.				
<code>'inside</code>	Seconds or bytes allocated in function only.				
<code>?filters g_filterSpec</code>	<p>Valid values: a regular expression, a symbol, <code>t</code>, <code>binary</code>.</p> <p>A regular expression displays function names indicated by the expression. For example <code>^hi</code> displays all functions beginning with <code>hi</code>.</p>				

Cadence SKILL Development Reference

Profiler Functions

A symbol containing a context displays all functions in that context.

`t` displays user functions (functions which have been loaded by the user and are not read protected).

`'binary` displays only SKILL functions implemented in C.

`?maxFns x_maxDisplayed`

Integer indicating the maximum number of functions to be displayed in the profile summary.

Default value: 1000

`?minSecs f_minSecs`

Floating-point number indicating in seconds the minimum time that a function must have spent executing before it should be displayed. This time cannot be smaller than 1/60 of a second.

Default value: 0.0

`?minBytes x_minBytes`

Integer that indicates the minimum number of bytes that need to be allocated to the function before it should be displayed.

Default value: 0

If both `?minSecs` and `?minBytes` are specified then any function which meets the minimum requirement of either one is displayed.

`?children g_showChildren`

If `t`, then the amount of time spent in each child function and the memory allocated is printed at the bottom of the profile summary report.

Value Returned

`t` Always returns `t`.

Examples

```
profileSummary(?file "/tmp/summary.out"  
?sort 'inside ?children t ?maxFns 100)
```

Cadence SKILL Development Reference

Profiler Functions

Related Topics

[Profiler Functions](#)

[profile](#)

[unprofile](#)

[profileReset](#)

unprofile

```
unprofile(  
    )  
=> t
```

Description

Turns off SKILL profiling but does not reset.

Does not reset the values. `profileSummary` also turns off profiling and then prints a report.

SKILL Profiler is not yet supported on the Windows/Wintel platform.

Arguments

None

Value Returned

t Always returns t.

Examples

```
unprofile()  
=> t
```

Related Topics

[Profiler Functions](#)

[profile](#)

[profileReset](#)

[profileSummary](#)

Cadence SKILL Development Reference

Profiler Functions

Lint Functions

SKILL Lint checks a SKILL file or context and reports potential errors and ways to clean up your code. In particular SKILL Lint is useful for helping programmers find unused local variables, global variables that should be locals, functions that have been passed the wrong number of arguments, and hints about how to improve the efficiency of the user's SKILL code.

SKILL Lint is usually run over a file. If a context is specified and the file is `startup.il` or is not specified, all the files ending with `*.il` or `*.ils` in the directory `your_install_dir/pvt/etc/context/t_contextName` are checked. By default, the SKILL Lint output prints to the Command Interpreter Window but can be printed to an output log file as well or instead. SKILL Lint prints messages about the user's code starting with the file and function name to which the message pertains.

The following SKILL Lint functions are available.

- [`skDisableMessage`](#)
- [`skDisableMessageBlock`](#)
- [`skEnableMessageBlock`](#)
- [`skIgnoreMessage`](#)
- [`sklint`](#)
- [`skUnignoreMessage`](#)

Related Topics

[Profiler Functions](#)

[Context Functions](#)

[Debug Functions](#)

[Finder Functions](#)

Cadence SKILL Development Reference

Lint Functions

Tabulator Functions

SKILL IDE Functions

skDisableMessage

```
skDisableMessage(  
    S_functionName  
    S_messageName  
    [ x_occurrences ]  
)  
=> t
```

Description

Disables a SKILL Lint message from being reported inside a given function definition.

Often a user does not want to disable a SKILL Lint message globally but only an individual case. You can put the call to this function in the `.skinit` file in the user's home directory or the `your_install_dir/local` directory. This function can also be inserted in the file being analyzed, outside of any function definition, before the function is defined, and SKILL Lint will recognize the call. See [SKILL lint messages](#).

Arguments

<i>S_functionName</i>	Function in which the given SKILL Lint error message is not reported.
<i>S_messageName</i>	Name of the message to ignore when SKILL Lint analyzes the file containing the function definition.
<i>x_occurrences</i>	Number of times to ignore the error message inside the function. This defaults to 1 if not given.

Value Returned

t	Always returns t.
---	-------------------

Examples

The following example disables the first occurrence of the SKILL Lint message `Unused` when SKILL Lint analyzes the function definition for `testFunction`.

```
skDisableMessage('testFunction 'Unused 1)
```

Cadence SKILL Development Reference

Lint Functions

Related Topics

[Lint Functions](#)

[sklint](#)

[skIgnoreMessage](#)

[skUnignoreMessage](#)

skDisableMessageBlock

```
skDisableMessageBlock(  
    l_rules  
    g_exp1 ...  
)  
=> g_result
```

Description

Disables one or a list of SKILL Lint messages from being reported by rules within the body of the function. You might want to turn off certain rules temporarily, and not globally, inside a particular block of code. SKILL Lint will recognize a call to this function if inserted inside the block of code being analyzed.

This function does not work for summary or statistic messages generated by SKILL Lint (for example, `message:External`). In these cases, use the `sklint ?depends` and `?ignores` keyed arguments.

Arguments

<i>l_rules</i>	One or more rules to ignore for all the code within the body of this function (that is, <i>g_exp1 ...</i>).
<i>g_exp1</i>	Expressions that compose the function body.

Value Returned

<i>g_result</i>	The result of the last expression evaluated. It can be ignored.
-----------------	---

Examples

To disable the single SKILL Lint message for MEMBER1 from reporting (the parentheses around the message name can be omitted):

```
(procedure (aFunc a b)  
    (skDisableMessageBlock MEMBER1  
        (member a b)  
        (geOpen)  
    )  
    (member 1 a)  
)
```

To disable the SKILL Lint messages for MEMBER1 and `geOpen` from reporting:

Cadence SKILL Development Reference

Lint Functions

```
(procedure (aFunc a b)
  (skDisableMessageBlock (MEMBER1 geOpen)
    (member a b)
    (geOpen)
  )
  (member 1 a)
)
```

Related Topics

[Lint Functions](#)

[skEnableMessageBlock](#)

skEnableMessageBlock

```
skEnableMessageBlock(  
    l_rules  
    g_exp1 ...  
)  
=> g_result
```

Description

Re-enables reporting of one or more SKILL Lint messages that have been globally turned off within the body of this function only.

You can insert the call to this function inside that particular block of code being analyzed and SKILL Lint will recognize the call.

Arguments

<i>l_rules</i>	One or more rules to ignore for all the code within the body of this function (that is, <i>g_exp1 ...</i>).
<i>g_exp1 ...</i>	Expressions that compose the function body.

Value Returned

<i>g_result</i>	The result of the last expression evaluated. It can be ignored.
-----------------	---

Examples

To disable the single SKILL Lint message for MEMBER1 from reporting (the parentheses around the message name can be omitted):

```
(procedure (aFunc a b)  
    (skEnableMessageBlock MEMBER1  
        (member a b)  
        (geOpen)  
    )  
    (member 1 a)  
)
```

To re-enable reporting of the SKILL Lint messages for MEMBER1 and geOpen temporarily inside a particular block of code:

```
(procedure (aFunc a b)  
    (skEnableMessageBlock (MEMBER1 geOpen)  
        (member a b)  
    )  
)
```

Cadence SKILL Development Reference

Lint Functions

```
        (geOpen)
    )
    (member 1 a)
)
```

Related Topics

[Lint Functions](#)

[skDisableMessageBlock](#)

skIgnoreMessage

```
skIgnoreMessage(  
    g_ignoreList  
)  
=> t
```

Description

Turns off the reporting of specified SKILL Lint messages. For a message to appear, both the message and its group have to be unignored.

When a message is ignored, reporting is turned off until a call to `unignore` that same message is made. If the message group `hint` was turned off, all messages in the group `hint` are not printed when SKILL Lint is run. These messages would also not affect the final IQ score. You can put calls to `skIgnoreMessage` in `.skinit`, the SKILL Lint startup file, in either the user's home directory or under

```
your_install_dir/local
```

This startup file executes whenever you run SKILL Lint.

Arguments

<code>g_ignoreList</code>	String or list of messages that SKILL Lint will no longer output.
---------------------------	---

Value Returned

<code>t</code>	Always returns <code>t</code> .
----------------	---------------------------------

Examples

The following example turns off reporting of all `hint` and `unused variable` messages.

```
skIgnoreMessage(' (hint))  
skIgnoreMessage("unused vars")
```

The following example turns on reporting of performance suggestion messages.

```
skUnignoreMessage(' (suggestion))
```

Cadence SKILL Development Reference

Lint Functions

Related Topics

[Lint Functions](#)

[skDisableMessage](#)

[sklint](#)

[skIgnoreMessage](#)

[SKILL Lint messages](#)

[Message Groups](#)

Cadence SKILL Development Reference

Lint Functions

sklint

```
sklint(  
  [ ?file tl_inputFileName ]  
  [ ?context t_contextName ]  
  [ ?outputFile t_outputFileName ]  
  [ ?ignoreGroups l_ignoreGroups ]  
  [ ?globals l_globals ]  
  [ ?depends l_depends ]  
  [ ?rulesFile t_rulesFile ]  
  [ ?ignores l_ignoresMessageList ]  
  [ ?checkNlambda g_checkNlambda ]  
  [ ?noPrintLog g_noPrintLog ]  
  [ ?useGlobalIgnores g_useGlobalIgnores ]  
  [ ?useGlobalRulesFileList g_useGlobalRulesFileList ]  
  [ ?useDisableMessages g_useDisableMessages ]  
  [ ?checkCdsFuncs g_checkCdsFuncs ]  
  [ ?checkPvtFuncs g_checkPvtFuncs ]  
  [ ?checkPubFuncs g_checkPubFuncs ]  
  [ ?prefixes l_prefixList ]  
  [ ?checkCdsPrefixes g_checkCdsPrefixes ]  
  [ ?checkFuncPrefixes g_checkFuncPrefixes ]  
  [ ?tabulate g_tabulate ]  
  [ ?skPath t_skPath ]  
  [ ?codeVersion t_release ]  
)  
=> t / nil
```

Description

Checks a SKILL file or context and reports potential errors and ways to clean up your code.

Arguments

?file *tl_fileFileName*

The name of the file to be processed, or a list of file names.
Each file is read and processed in turn. This option defaults to
startup.il.

?context *t_context*

Cadence SKILL Development Reference

Lint Functions

The name of the context, or an absolute-pathed context name, being processed. SKILL Lint looks under the *install_dir/pvt/etc/context/t_contextName* directory for all files ending with *.il* and *.ile* unless a file other than *startup.il* is given. If a file other than *startup.il* is given along with a context, that file is assumed to belong in that context and global variable package prefixes for that context are used if possible.

?outputfile *t_outputFile*

The name of the reporting log file. Defaults to *context-Name.log*.

?ignoreGroups *l_ignoreGroups*

The list of rule groups that should not be carried out.

?globals *l_globals*

The list of allowed globals not covered by the standard global list and the prefix list. This allows handling of obscure globals cases.

?depends *l_depends*

The list of contexts on which the code under analysis depends. This is used for loading external definitions files.

?rulesFile *t_rulesFile*

The name of an additional rules file to be read prior to processing the code.

?ignores *l_ignoresMessageList*

The list of message IDs to ignore. These messages are neither printed by SKILL Lint nor counted in the summary report at the end of the run. Message groups as well as individual messages can be ignored. For example, all messages about improving the efficiency of SKILL code can be turned off by passing in the list *'(hint suggestion)*.

?checkNlambda *g_checkNlambda*

Specifies whether to check the arguments to *nlambda* functions. This option should only be used by highly experienced users, as it usually leads to results that are difficult to interpret. This option defaults to *nil*.

Cadence SKILL Development Reference

Lint Functions

`?noPrintLog` *g_noPrintLog*

Controls whether printing to the screen/*ciw* should take place. Even if switched off, printing of start and stop messages will take place. This option defaults to *nil*.

`?useGlobalIgnores` *g_useGlobalIgnores*

Controls whether to ignore those message IDs listed in the global variable *skGlobalIgnores*. This option is useful when the list of messages to ignore is constant and is held in a global list somewhere. This option defaults to *nil*.

`?useGlobalRulesFileList` *g_useGlobalRulesFileList*

Specifies whether to use the rules file listed in the global variable *skGlobalRulesFiles*. This option defaults to *nil*.

`?useDisableMessages` *g_useDisableMessages*

Controls whether to turn on or off disable messages to allow integrators to override message suppression put in the code. This option defaults to *t*.

`?checkCdsFuncs` *g_checkCdsFuncs*

Specifies whether to check both Cadence private and public functions (that is, force setting both *checkPvtFuncs* and *checkPubFuncs* to *t*). This option defaults to *nil*.

`?checkPvtFuncs` *g_checkPvtFuncs*

Controls whether to check Cadence private functions. This option defaults to *nil*.

`?checkPubFuncs` *g_checkPubFuncs*

Specifies whether to check Cadence public functions. This option defaults to *nil*.

`?prefixes` *l_prefixes*

The list of symbols whose print names are matched with variable names. The list may consist of functions and global variables not covered by the standard global list and the prefix list. This allows for obscure cases of globals to be handled.

`?checkCdsPrefixes` *g_checkCdsPrefixes*

Cadence SKILL Development Reference

Lint Functions

Specifies whether the prefix checking is for Cadence public function/variables start with a lower-case character. If this argument is not set to `t` (that is, by default), the checking is for customers' function/variables prefixes start with an upper-case character. This option is for Cadence internal use only. This option defaults to `nil`.

`?checkFuncPrefixes` *g_checkFuncPrefixes*

Controls whether function prefixes should also be checked. If this argument is not set to `t` (that is, by default), only customers' global variable prefixes are checked. This option defaults to `nil`.

`?tabulate` *g_tabulate*

Controls whether to tabulate all the functions being called. This option defaults to `nil`.

`?skPath` *t_skPath*

The user-specified SKILL path to the file to be processed. If the option is specified, SKILL Lint will only search this path. Otherwise, the home directory will be searched first by default.

`?codeVersion` *t_release*

The release version of code being checked (for example, 581 for IC6.1.8). If this argument is specified all automatically generated function change messages (from `cdsFuncs.cxt`) that are equal to or before the release specified (through this argument) will be filtered out (that is, will not be reported). By default, all automatically generated function change messages (from `cdsFuncs.cxt`) will be reported.

This argument is useful when the user wants to restrict reporting of function change messages which occurred after the release for which the code being checked was written. When users check the code in IC6.1.8 they will not be interesting in seeing the information about the change in IC6.1.7, since that was before they wrote the code (or perhaps before it was migrated).

Specifying this argument will filter out both function changed and function deleted messages.

Cadence SKILL Development Reference

Lint Functions

Value Returned

<code>t</code>	If SKILL Lint passed 100%.
<code>nil</code>	If SKILL Lint failed. SKILL Lint fails if there are any error or warning messages.

Examples

Runs SKILL Lint over the `testfns.il` file and prints the output to the CIW.

```
sklint(?file "~/testfns.il")
```

Runs SKILL Lint over all files loaded by `your_install_dir/pvt/etc/context/dbRead/startup.il`.

```
sklint(?context "dbRead")
```

Runs SKILL Lint over the `testfns.il` file and prints the output to the `testfns.lint` file but not to the CIW.

```
sklint(?file "~/testfns.il" ?outputFile "~/testfns.lint" ?noPrintLog t)
```

Runs SKILL Lint over the `testfns.il` file and treats all global variables that start with the prefix `tfns` as acceptable global variables. In the given example, SKILL Lint does not print any hints or suggestions for how to make the user's SKILL code more efficient.

```
sklint(?file "~/testfns.il" ?prefixes '(tfns) ?ignores '(hint suggestion))
```

Runs SKILL Lint to check prefixes:

```
sklint( ?file "file.il" ?prefixes '(Pre MIX) )
```

Checks non-Cadence variable prefixes only.

```
sklint( ?file "file.il" ?checkFuncPrefixes t ?prefixes '(Pre MIX) )
```

Checks both non-Cadence function and variable prefixes.

```
sklint( ?file "file.il" ?checkCdsPrefixes t ?prefixes '(le ge) )
```

Checks Cadence variable prefixes only.

```
sklint( ?file "file.il" ?checkCdsPrefixes t ?checkFuncPrefixes t ?prefixes '(le ge) )
```

Checks both Cadence function and variable prefixes.

Runs SKILL Lint on code that contain macros:

```
sklint ?file "dep.il file.il" ?depends '("dep.il")
```

Cadence SKILL Development Reference

Lint Functions

where `dep.il` should contain macro definition(s) only, while `file.il` contains the code that call the macro(s) as defined in `dep.il`. The order of the files specifying in the `?file` option is important that the file(s) contain the macro definition(s) have to be specified first. (that is, `dep.il` must be listed before `file.il`).

Use this command for linting code where the macro definition(s) are contained in different file(s).

```
sklint ?file "file2.il" ?depends ' ("file2.il")
```

where `file2.il` contains both the macro definition(s) and the code that call the macro(s). The macro definition(s) code have to be placed on top of the code that call the macro(s) inside `file2.il`.

Note: Use this command for linting code where the macro definition(s) and the code that call the macro(s) are contained in the same file.

Related Topics

[Lint Functions](#)

[skDisableMessage](#)

[skIgnoreMessage](#)

[SKILL Lint messages](#)

[Message Groups](#)

skUnignoreMessage

```
skUnignoreMessage(  
    g_ignoreList  
)  
=> t
```

Description

Turns on the reporting of specified SKILL Lint messages. For a message to appear, both the message and its group have to be unignored.

When a message is ignored, reporting is turned off until a call to unignore that same message is made. If the message group `hint` was turned off, on all subsequent runs of SKILL Lint all messages in the group `hint` would not be printed. You can put calls to `skUnignoreMessage` in `.skinit`, the SKILL Lint startup file, in either the user's home directory or under the `your_install_dir/local` directory. This startup file executes whenever you run SKILL Lint.

Arguments

<code>g_ignoreList</code>	String or list of messages that SKILL Lint will again output.
---------------------------	---

Value Returned

<code>t</code>	Always returns <code>t</code> .
----------------	---------------------------------

Examples

Turns off reporting of all `hint` and unused variable messages.

```
skIgnoreMessage(' (hint) )  
skIgnoreMessage("unused vars")
```

Turns on reporting of performance suggestion messages.

```
skUnignoreMessage(' (suggestion) )
```

Related Topics

[Lint Functions](#)

[skDisableMessage](#)

Cadence SKILL Development Reference

Lint Functions

[skIgnoreMessage](#)

[sklint](#)

[SKILL Lint messages](#)

[Message Groups](#)

Context Functions

The following SKILL Context functions are available.

[callInitProc](#)

[callUserAutoInitProc](#)

[checkContextBit](#)

[defCapDepends](#)

[defCapPrefixes](#)

[defInitProc](#)

[isContextLoaded](#)

[loadContext](#)

[loadTopContextForms](#)

[saveContext](#)

[setContext](#)

[setSaveContextVersion](#)

[getCurSaveContextVersion](#)

[getNativeContextVersion](#)

[getCompatContextVersion](#)

Related Topics

[Profiler Functions](#)

[Lint Functions](#)

[Debug Functions](#)

[Finder Functions](#)

[Tabulator Functions](#)

[SKILL IDE Functions](#)

callInitProc

```
callInitProc(  
    t_contextName  
)  
=> t
```

Description

Calls all the initialization functions associated with a context.

Takes the same argument as `loadContext` (but without the `.cxt` extension) and causes all the initialization functions associated with the given context to be called. This function need not be used if the loading of the context is happening through the autoload mechanism. Use this function only when calling `loadContext` manually.

Arguments

<code>t_contextName</code>	Name of the context.
----------------------------	----------------------

Value Returned

<code>t</code>	Initialization functions have been successfully called.
----------------	---

Examples

All functions defined through `defInitProc` and `defUserInitProc` are called.

```
loadContext("myContext.cxt")  
=> t  
callInitProc("myContext")  
=> t
```

Related Topics

[Context Functions](#)

[loadContext](#)

[defInitProc](#)

[defUserInitProc](#)

callUserAutoInitProc

```
callUserAutoInitProc(  
    t_contextName  
)  
=> t / g_result
```

Description

Calls the `autoinit` function for the given context name.

If there is no `autoinit` function for the given context name, the function does nothing and returns `t`.

Arguments

<code>t_contextName</code>	Name of the context.
----------------------------	----------------------

Value Returned

<code>g_result</code>	The result of the <code>autoinit</code> function.
<code>t</code>	Returns <code>t</code> otherwise.

Examples

```
callUserAutoInitProc("fake")  
=> t
```

Related Topics

[Context Functions](#)

[loadContext](#)

[defInitProc](#)

[defUserInitProc](#)

checkContextBit

```
checkContextBit(  
    t_contextPath  
)  
=> t_type
```

Description

Checks and returns the context type of the specified context file.

Arguments

<i>t_contextPath</i>	Full path to the SKILL context file.
----------------------	--------------------------------------

Value Returned

<i>t_type</i>	A string (either "32bit" or "64bit") representing the context type. If the specified file is not a context file, the function displays an error message.
---------------	--

Examples

```
checkContextBit("./myContext.cxt")  
=> "32bit"
```

Related Topics

[Context Functions](#)

[loadContext](#)

[defInitProc](#)

defCapDepends

```
defCapDepends (  
    s_context  
    l_dependsList  
)  
=> t
```

Description

Specifies which contexts depend on which other contexts.

This can be specified in the `.skinit` file, which must reside in either the user's home directory or `your_install_dir/local` directory.

We recommend that developers put the `defCapDepends` function call in the beginning of the `startup.il` file because if SKILL Lint sees this call while analyzing the context it will determine the dependent contexts. When SKILL Lint is run on the context `s_context`, it loads all the dependent contexts from which it will be able to effectively type check the function calls made by the context being analyzed.

Arguments

<i>s_context</i>	Context that depends on the contexts specified by <i>l_dependsList</i> .
<i>l_dependsList</i>	List of contexts upon which <i>s_context</i> depends. In other words, <i>l_dependsList</i> should contain all the definitions for all the functions called in <i>s_context</i> that are not defined in <i>s_context</i> .

Value Returned

<i>t</i>	Always returns <i>t</i> .
----------	---------------------------

Examples

Informs SKILL Lint that `myContext` depends on the contexts `skillCore` and `hiBase`.

```
defCapDepends('myContext '(skillCore hiBase))
```

Cadence SKILL Development Reference

Context Functions

Related Topics

Context Functions

loadContext

defInitProc

defCapPrefixes

```
defCapPrefixes (  
    s_context  
    l_prefixList  
)  
=> t
```

Description

Specifies which prefixes are acceptable for a context's global variables.

All global variables that do not start with the stated prefixes are reported as unrecognized global variables. The call to `defCapPrefixes` can be specified in the `.skinit` file, which must reside in either the user's home directory or the `your_install_dir/local` directory.

We recommend that developers put the `defCapPrefixes` function call in the beginning of the `startup.il` file because if SKILL Lint sees this call while analyzing the context, it can determine the acceptable prefixes for the context being analyzed. If you want SKILL Lint to recognize the package prefixes when analyzing a file that contains `defCapPrefixes`, be sure to pass the `s_context` to SKILL Lint as the `?context`.

Arguments

<i>s_context</i>	Context for which the package prefixes should apply.
<i>l_prefixList</i>	List of acceptable package prefixes for <i>s_context</i> . The first letter following the prefix must be a capital. If the prefixes have been specified for a context, many of the unrecognized global variables will probably be variables that the user forgot to declare as locals.

Value Returned

<i>t</i>	Always returns <i>t</i> .
----------	---------------------------

Examples

Informs SKILL Lint to expect any global variables in `myContext` to start with `my` or `_my` and to report all other global variables. Thus `myGlobalVariable` is an example of a legal global variable inside `myContext`.

Cadence SKILL Development Reference

Context Functions

```
defCapPrefixes('myContext '(my))
```

Related Topics

[Context Functions](#)

[loadContext](#)

defInitProc

```
defInitProc(  
    t_contextName  
    s_procName  
)  
=> t
```

Description

Registers a function that the system calls immediately after autoloading a context.

When a context is autoloaded, it is given a chance to perform initialization before control returns to top level. It is during such an initialization that session-dependent objects like ports can be regenerated. This function permits a predefined function *s_procName* to be called whenever the context *t_contextName* is loaded.

Arguments

<i>t_contextName</i>	Primary name of the context file created using <i>saveContext</i> .
<i>s_procName</i>	Predefined function to be called when <i>t_contextName</i> is loaded.

Value Returned

<i>t</i>	Always returns <i>t</i> when set up. The function is not called at this point, but is called when the context <i>t_contextName</i> is autoloaded.
----------	---

Examples

```
defInitProc("myContext" 'myInit)  
=> t
```

Related Topics

[Context Functions](#)

[defCapPrefixes](#)

[defCapDepends](#)

Cadence SKILL Development Reference

Context Functions

setContext

isContextLoaded

```
isContextLoaded(  
    t_cxt  
)  
=> t / nil
```

Description

Returns `t` if a context file with the given base name has been loaded into the current session.

Returns `nil` otherwise.

Arguments

<code>t_cxt</code>	Base name of the context file you want load status on.
--------------------	--

Value Returned

<code>t</code>	The given context has already been loaded into the current environment.
<code>nil</code>	The given context has not been loaded yet.

Examples

```
isContextLoaded( "skillCore" )  
=> t  
isContextLoaded( "hiBase" )  
=> nil
```

Related Topics

Context Functions

loadContext

loadContext

```
loadContext (
    t_contextFileName
    [ g_ignore64bitSubpath ]
)
=> t / nil / error
```

Description

Loads a context file into the current session.

This function uses the SKILL path to find *t_contextFileName*, if you do not supply the full path. Additionally, if the optional argument is specified the function does not add /64bit subpath to the context file path.

Arguments

t_contextFileName Name of the context file you want to load. It must have been created using `saveContext`.

g_ignore64bitSubpath Specifies whether /64bit subpath should be added to the context file path or not. When set to *t* (64bit only), it does not add /64bit to the context file path and the context is loaded from the current directory.

Value Returned

t The context was successfully loaded.

nil Context has already been loaded.

error Signals an error if:

- The system failed to open a file
- Virtual memory is exhausted
- The version of context is incompatible with current software.

This condition usually requires you to regenerate the context file

Cadence SKILL Development Reference

Context Functions

Examples

Loads “64bit/geView.cxt” from the SKILL path.

```
loadContext( "geView.cxt" )
```

Loads “geView.cxt” from the SKILL path.

```
loadContext( "geView.cxt" t)
```

Related Topics

Context Functions

saveContext

setContext

loadTopContextForms

```
loadTopContextForms (
    t_FileName
    [ ?debugMode g_debugMode ]
    [ ?writeProtect g_writeProtect ]
    [ ?writeProtectAll g_writeProtectAll ]
    [ ?lazyComp g_lazyComp ]
    [ ?printinfix g_printinfix ]
    [ ?integermode g_integermode ]
    [ ?mergemode g_mergemode ]
    [ ?readProtect g_readProtect ]
)
=> t / nil
```

Description

Loads top-level SKILL or Scheme forms from a file. If the `setContext` mode is set, these forms are saved in a context. After the context is loaded, these forms are evaluated at the top-level, as if these were loaded from an `.il` or `.ils` file.

Arguments

t_FileName Name of the context file you want to load.

?debugMode g_debugMode
 Sets debug mode

?writeProtect g_writeProtect
 Sets write protect
 Default value: `t`

?writeProtectAll g_wirteProtectAll
 Sets write protect all
 Default value: `t`

?lazyComp g_lazyComp
 Sets the lazy compilation status

?printinfix g_printinfix
 Sets the printinfix status
 Default value: `t`

Cadence SKILL Development Reference

Context Functions

`?integermode g_integermode`

Sets the integer mode

`?mergemode g_mergemode`

Sets the merge mode

Default value: `t`

`?readProtect g_readProtect`

Sets the read protect mode

Default value: `t`

Value Returned

<code>t</code>	When the file is loaded successfully.
<code>nil</code>	When the file is not loaded.

Examples

```
setContext("testc.cxt")
loadTopContextForms("./testFile.il")
saveContext("testc.cxt")
```

Related Topics

[Context Functions](#)

[saveContext](#)

[setContext](#)

saveContext

```
saveContext (
    t_contextFileName
    [ g_ignore64bitSubpath ]
)
=> t / nil
```

Description

Saves the current state of the SKILL language interpreter as a binary file. This function must be used in conjunction with `setContext`.

If the optional argument is specified the function does not add /64bit subpath to the context file path.

Saves all function and variable definitions that occur, usually due to file loading, between the calls to `setContext` and `saveContext`. Those definitions can then be loaded into a future session much faster in the form of a context using the `loadContext` function.

By default all functions defined in a context are read and write protected unless the `writeProtect` system switch was turned off (by setting (`sstatus writeProtect nil`)) when the function in question was defined between the calls to `setContext` and `saveContext`.

Arguments

t_contextFileName Name of binary file to which the current state of the interpreter is written. To load or set the saved context using `loadContext` or `setContext` respectively, ensure that this name is specified.

g_ignore64bitSubpath Specifies whether /64bit should be added to the context file path or not. If set to `t`, the context is saved in the current directory and /64bit is not added to the context file path.

Value Returned

`t` Context was successfully saved.

Cadence SKILL Development Reference

Context Functions

`nil`

If the saving process failed due to one of the following conditions: failed to open/create a file, exhaustion of virtual memory, presence of bad objects (such as port, db handles, and so forth)

Examples

```
setContext("myContext")
=> t

load("mySkillCode.il")
=> t

defInitProc("myContext" 'myInit)
=> t
```

Saves as “64bit/myContext.cxt” in the SKILL path

```
saveContext("myContext.cxt")
=> t
```

Saves as “myContext.cxt” in the SKILL path

```
saveContext("myContext.cxt" t)
=> t
```

Related Topics

[Context Functions](#)

[defInitProc](#)

[loadContext](#)

[setContext](#)

setContext

```
setContext (
    t_contextName
)
=> t
```

Description

Allows contexts to be saved incrementally, creating micro contexts from a session's SKILL context.

To understand this, think of the SKILL interpreter space as being linear; the function call `setContext` sets markers along the linear path. Any SKILL files loaded between a `setContext` and a `saveContext` are saved in the file named in the `saveContext` call. This function can be used more than once during a session.

Arguments

<code>t_contextName</code>	Primary name of the binary file to which the context was saved used <code>saveContext</code> .
----------------------------	--

Value Returned

<code>t</code>	Always returns <code>t</code> .
----------------	---------------------------------

Examples

```
setContext("myContext")
=> t
load("mySkillCode.il")
=> t
defInitProc("myContext" 'myInit)
=> t
saveContext("myContext.cxt")
=> t
```

Related Topics

[Context Functions](#)

[defInitProc](#)

[loadContext](#)

Cadence SKILL Development Reference

Context Functions

setContext

setSaveContextVersion

```
setSaveContextVersion(  
    x_newVers  
)  
=> x_oldVers
```

Description

Resets the current `saveContext` version to *x_newVers* and returns the previous context version. If *x_newVers* has an unsupported value or the function is called between `setContext` and `saveContext`, it returns an error.

Arguments

<i>x_newVers</i>	Specifies the new context version.
------------------	------------------------------------

Value Returned

<i>x_oldVers</i>	Returns the old context version.
------------------	----------------------------------

Examples

```
setSaveContextVersion(getCompatContextVersion())  
601  
setSaveContextVersion(0)  
*Error* setSaveContextVersion: unsupported context version - 0
```

Related Topics

[Context Functions](#)

[defInitProc](#)

[loadContext](#)

[setContext](#)

getCurSaveContextVersion

```
getCurSaveContextVersion(  
    )  
=> x_curVers
```

Description

Returns the current `saveContext` version (the version which the new context will have.) The possible return values are, 601 for compatible contexts and 602 for native contexts (for IC 6.1.6/CAT 33.00)

Arguments

None

Value Returned

`x_curVers` Returns the current `saveContext` version.

Examples

```
setSaveContextVersion(getNativeContextVersion())  
601  
getCurSaveContextVersion()  
602
```

Related Topics

[Context Functions](#)

[defInitProc](#)

[loadContext](#)

[setContext](#)

getNativeContextVersion

```
getNativeContextVersion(  
    )  
    => x_nativeVers
```

Description

Returns the native context version (for IC 6.1.6/CAT 33.00, the native context version is 602).

Arguments

None

Value Returned

x_nativeVers Returns the native context version.

Examples

```
getNativeContextVersion()  
602
```

Related Topics

[Context Functions](#)

[defInitProc](#)

[loadContext](#)

[setContext](#)

getCompatContextVersion

```
getCompatContextVersion(  
    )  
    => x_compatVers
```

Description

Returns the compatible context version (for IC 6.1.6/CAT 33.00, the compatible context version is 601).

Do not use the 601 or 602 context version values directly in SKILL functions. Use `getCompatContextVersion`, `getNativeContextVersion`, or `getCurSaveContextVersion` instead to retrieve the values of context versions.

Arguments

None

Value Returned

x_compatVers Returns the compatible context version.

Examples

```
getCompatContextVersion()  
601
```

Related Topics

[Context Functions](#)

[defInitProc](#)

[loadContext](#)

[setContext](#)

Cadence SKILL Development Reference

Context Functions

Debug Functions

The debug capabilities become available for use only after you stop the profiler.

You can export the debug settings of your current session to a SKILL file for future use. The saved debug settings includes current line and function breakpoints, their conditions, traced functions, variables, and properties.

The following SKILL Debug functions are available.

<u>break</u>	<u>breakpt</u>	<u>breakptMethod</u>
<u>clear</u>	<u>cont, continue</u>	<u>count</u>
<u>debugQuit</u>	<u>debugStatus</u>	<u>dump</u>
<u>gcsummary</u>	<u>getAllLoadedFiles</u>	<u>getCallingFunction</u>
<u>getFunctions</u>	<u>getGFbyClass</u>	<u>ilAddTopLevelErrorHandler</u>
<u>ilDebugCountLevels</u>	<u>ilGetGFbyClass</u>	<u>ilGetIdeSessionWindow</u>
<u>ilGetTCovFiles</u>	<u>ilMergeTCovData</u>	<u>ilRemoveMethod</u>
<u>ilRemoveTopLevelErrorHandler</u>	<u>ilSlotBoundp</u>	<u>ilToolBox</u>
<u>inNext</u>	<u>inStepOut</u>	<u>installDebugger</u>
<u>listAlias</u>	<u>listFunctions</u>	<u>listVariables</u>
<u>memoryAllocated</u>	<u>next</u>	<u>pp</u>
<u>printFunctions</u>	<u>printObject</u>	<u>printstruct</u>
<u>printVariables</u>	<u>removeMethod</u>	<u>resume</u>
<u>skillDebugger</u>	<u>skillDevStatus</u>	<u>stacktrace</u>
<u>step</u>	<u>stepend</u>	<u>stepout</u>
<u>toplevel</u>	<u>tracef</u>	<u>tracelevlimit</u>
<u>tracelevunlimit</u>	<u>tracep</u>	<u>tracev</u>
<u>unbreakpt</u>	<u>unbreakptMethod</u>	<u>uncount</u>

Cadence SKILL Development Reference

Debug Functions

[uninstallDebugger](#)

[untrace](#)

[untracep](#)

[untracev](#)

[unwatch](#)

[watch](#)

[where](#)

[whereIs](#)

Related Topics

[Profiler Functions](#)

[Lint Functions](#)

[Context Functions](#)

[Finder Functions](#)

[Tabulator Functions](#)

[SKILL IDE Functions](#)

break

```
break(  
    )  
=> none
```

Description

Forces entry to the break handler if inserted directly into a SKILL function. The default break handler is the debugger.

This function is useful if you want to stop at a particular place in a function.

Arguments

None

Value Returned

None

Related Topics

[Debug Functions](#)

[breakpt](#)

[cont, continue](#)

[unbreakpt](#)

breakpt

```
breakpt (
    [ u_function
    [ break_condition ] ]
)
where break_condition can be either
(break_tag
g_condition
)
or
(
(break_tag
g_condition)...
)
=> g_result
```

Description

Sets breakpoints on one or more functions or function objects.

The SKILL debugger is the default break handler and is entered automatically when a breakpoint is encountered. The functions `breakpt` and `unbreakpt` set and clear breakpoints on the given functions or function objects.

Another way to enter the break handler is to insert the `break` function directly into a SKILL function at the point desired. Once you are in the break handler, you can examine the state of the program. If the function was loaded under `debugMode` (see `installDebugger`), you can use single stepping functions such as `step`, `next`, `stepout`, or `continue`.

If *break_condition* is not specified, the breakpoint is called *unconditional*. The behavior of an unconditional breakpoint is as follows: if the function is read-protected or not yet defined under `debugMode`, the breakpoint is assumed to be set at the *call* point. Otherwise, it is assumed to be set at the *entry* point of the function.

Arguments

<i>u_function...</i>	List of functions or function objects.
<i>break_tag</i>	Valid values: <i>call</i> Breaks at the calling point after evaluating all arguments in the caller's context. <i>entry</i> Breaks at the entry point after binding all formal parameters in the callee's context.

Cadence SKILL Development Reference

Debug Functions

	<code>exit</code> Breaks at the exit point in the callee's context.
	<code>return</code> Breaks at the returning point in the caller's context.
<code>g_condition</code>	Condition expression to be evaluated in the associated break context.

Value Returned

<code>g_result</code>	List of functions or function objects on which the breakpoints have been set.
-----------------------	---

Examples

The following example sets a breakpoint, enters the break handler, continues, and finally clears the breakpoint.

```
installDebugger( )           ; Make sure debug mode is on.
breakpt( times )             ; Sets a breakpoint on times.
times(2 plus( 2 3 ))         ; Invokes the break handler.
cont( )                      ; Continue executing.
unbreakpt( times )           ; Clear the breakpoint.
```

This example sets a conditional breakpoint.

```
(breakpt myFun hisFun)
(breakpt myFun1 (entry n > 5))
(breakpt myFun2 ((entry n > 5) (exit result != 0)) hisFun)
```

The following example sets breakpoint on a function object.

```
(installDebugger)           ; Make sure debug mode is on
=> t

(defun test (x) (printf "test : x == %L\n" x))

=> test

(putd 'test1 (getd 'test))   ;test and test1 are the same functions
=> funobj:test

(funcall 'breakpt (getd 'test)) ;set breakpoint on the funobject
(funobj:test)

(test1 8)

<<< Break >>> on entering test
Entering new debug toplevel due to breakpoint:
Debug 2> cont
test : x == 8
=> t
```

Cadence SKILL Development Reference

Debug Functions

Related Topics

[break](#)

[cont, continue](#)

[unbreakpt](#)

[installDebugger](#)

[next](#)

[step](#)

[stepout](#)

breakptMethod

```
breakptMethod(  
  [ S_name ]  
  [ l_specializer [ @before | @after | @around ] ]  
  [ break_condition ] )  
where break_condition can be either  
  (break_tag  
   g_condition  
  )  
or  
  (  
   (break_tag  
    g_condition)...  
  )  
=> t / nil
```

Description

Sets breakpoint on the specified method's `defmethod` declaration.

If *break_condition* is not specified, the breakpoint is called *unconditional*. The behavior of an unconditional breakpoint is as follows: if the function is read-protected or not yet defined under `debugMode`, the breakpoint is assumed to be set at the *call* point. Otherwise, it is assumed to be set at the *entry* point of the function.

Arguments

<i>S_name</i>	Specifies the name of the method on which the breakpoint needs to be set.
<i>l_specializer</i>	Specifies a list of specializers of the method to set breakpoint on. It can include <code>@before</code> , <code>@after</code> , and <code>@around</code> qualifiers.
<i>break_tag</i>	Valid values: <code>call</code> Breaks at the calling point after evaluating all arguments in the caller's context. <code>entry</code> Breaks at the entry point after binding all formal parameters in the callee's context. <code>exit</code> Breaks at the exit point in the callee's context. <code>return</code> Breaks at the returning point in the caller's context.
<i>g_condition</i>	Specifies the condition expression to be evaluated in the associated break context.

Cadence SKILL Development Reference

Debug Functions

Value Returned

t	List of breakpoints set on the specified method.
nil	If the specified method is not defined.

Examples

```
breakptMethod()  
; when specified without arguments, lists all the breakpoints  
breakptMethod(S_name)  
; sets breakpoint on "S_name" function, behaves the same way as breakpt()  
breakptMethod(S_name nil)  
; sets breakpoint on the "generic" method of S_name.  
breakptMethod(S_name @before (classA classB))  
; sets breakpoint on "@before" method specialized on (classA classB) of "S_name"  
breakptMethod(S_name @after (classA t))  
; sets breakpoint on "@after" method specialized on (classA t) of "S_name"
```

Related Topics

Debug Functions

break

breakpt

cont, continue

unbreakpt

clear

```
clear(  
    )  
=> t
```

Description

Clears all tracing and breakpoints.

This function undoes the effects of `tracef`, `tracep`, `tracev`, and `breakpt`.

Arguments

None

Value Returned

`t` Always returns `t`.

Examples

Untraces all functions and variables and clears all breakpoints.

```
clear()  
=> t
```

Related Topics

[Debug Functions](#)

[breakpt](#)

[tracef](#)

[tracep](#)

[tracev](#)

cont, continue

```
cont(  
    )  
    => no return value  
continue(  
    )  
    => no return value
```

Description

Continues execution from a breakpoint. `cont` and `continue` are identical.

These functions work only within the break handler (which defaults to the SKILL debugger).

Arguments

None

Value Returned

None

Examples

```
break( ) ; puts you in the break handler  
cont( ) ; exits the break handler
```

Related Topics

[Debug Functions](#)

[break](#)

[breakpt](#)

count

```
count(
    [ s_function ... | t ]
)
=> g_result / t
```

Description

Counts the number of times a function has been called. This is an `nlambda` function. Returns the functions marked for counting.

Measures function call frequency and also serves as a valuable debugging aid. Both `count` and `uncount` accept a list of functions, or `t` for counting/uncounting all functions. To examine the number of times a function has been counted, call the `uncount` function. A list containing the number of times each function was called, along with the function name, is returned in the form of a list of (number functionName) pairs, such as,

```
((20 plus) (10 times) (5 greaterp))
```

The sublists are sorted by their first elements, using `sortcar`, so the most frequently executed functions always appear at the head of the list.

Arguments

<code><i>s_function</i> ... <i>t</i></code>	Turns on counting for the functions given, or for all functions if <code>t</code> .
---	---

Value Returned

<code><i>g_result</i></code>	Returns the functions marked for counting.
<code><i>t</i></code>	If no arguments are given and all functions are being counted.

Examples

<code>count(plus greaterp)</code>	<code>; Counts plus and greaterp</code>
<code>setq(x plus(2 3))</code>	<code>; Use the functions being counted.</code>
<code>uncount(plus greaterp)</code>	
<code>=> ((1 plus) (0 greaterp))</code>	<code>; Number of times each</code>
	<code>; function was called.</code>

Cadence SKILL Development Reference

Debug Functions

Related Topics

Debug Functions

uncount

debugQuit

```
debugQuit(  
    [ g_all ]  
)  
=> nil
```

Description

Exits one level of the SKILL debugger.

Arguments

None

Value Returned

nil Always returns nil.

Examples

```
installDebugger()            ; Installs the SKILL debugger.  
4 / 0                        ; Generates an error and enters  
                             ; the SKILL debugger.  
debugQuit()                 ; Exits the debugger.  
uninstallDebugger( )        ; No longer enters the debugger upon error.
```

The following example unwinds all error stack entries and return the prompt to 1>.

```
debugQuit(all)
```

Related Topics

[Debug Functions](#)

[installDebugger](#)

[uninstallDebugger](#)

debugStatus

```
debugStatus(  
    )  
=> nil
```

Description

Prints the functions and variables being traced, functions that have breakpoints set, functions being counted, and the line breakpoints statistics.

Line breakpoints statistics include the file name and the line number on which line breakpoints have been set.

Arguments

None

Value Returned

`nil` Always returns `nil`.

Examples

Returns `nil` and prints the debugging status of all functions.

```
debugStatus()  
=> nil
```

Sample output looks like:

```
Traced functions      (mytest)  
Traced variables     (nil)  
Traced properties    (nil)  
Breakpoints          (myFunction1)  
Counted functions    nil  
Line Breakpoints     (40 (("/home/deeptik/demo.il")))
```

Related Topics

[breakpt](#)

[clear](#)

[count](#)

Cadence SKILL Development Reference

Debug Functions

tracef

tracev

tracep

unbreakpt

dump

```
dump (
  [ x_variables ]
)
=> nil
```

Description

Prints the current value of all the local variables on the stack. SKILL++ variables are not displayed by this function. For SKILL++ use `where` to see the lexical bindings on the stack.

`dump` is usually called from within the break or error handler.

Arguments

<i>x_variables</i>	Number of local variables on the stack to print, starting from the top. Defaults to printing all local variables on the stack.
--------------------	--

Value Returned

<code>nil</code>	Always returns <code>nil</code> .
------------------	-----------------------------------

Examples

Suppose `/tmp/color.il` defines function `initColor`:

```
(defun initColor (object)
  (let ((colorList '(red green yellow)) color)
    (setq color (concat (get object 'color)))
    (if (memq color colorList)
        (printf "color %s initialized" (get object 'name))))
  )
)
```

Try this file in the debugger:

```
installDebugger
=> t
1> load "/tmp/color.il"
=> t

1> (putprop 'object1 "green" 'color)
=> "green"

1> breakpt(initColor (entry (null object)) concat)
=> concat(initColor)
```

Cadence SKILL Development Reference

Debug Functions

```
1> (initColor 'object1)
*** Error in routine fprintf/sprintf:
Message: *Error* fprintf/sprintf: format spec. incompatible
with data
Debug 2> dump
colorList = (red green yellow)
color = green
object = object1
nil
```

Related Topics

Debug Functions

tracev

where

Cadence SKILL Development Reference

Debug Functions

gcsummary

```
gcsummary(  
    )  
=> t
```

Description

Prints a summary of memory allocation and garbage collection statistics in the current SKILL run.

Arguments

None

Value Returned

t Always returns t.

Examples

```
***** SUMMARY OF MEMORY ALLOCATION *****  
Maximum Process Size (i.e., voMemoryUsed) = 3589448  
Total Number of Bytes Allocated by IL = 2366720  
Total Number of Static Bytes            = 1605632  
-----  
Type            Size    Allocated      Free          Static      GC count  
-----  
list            12       339968      42744       1191936       9  
fixnum           8       36864      36104       12288          0  
flonum          16       4096       2800       20480          0  
string          8       90112      75008       32768          0  
symbol          28          0          0       303104          0  
binary          16          0          0       8192           0  
port            60       8192       7680          0           0  
array           16       20480      8288       8192           0  
wtype           16       16384      16224          0           0  
TOTALS          --      516096     188848     1576960          9  
-----  
User Type (ID)                      Allocated      Free          GC count  
-----  
hiField                      (20)       8192       7504           0  
hiToggleItem                  (21)       8192       7900           0  
hiMenu                        (22)       8192       7524           0  
hiMenuItem                    (23)       8192       5600           0  
TOTALS                        --       32768      28528           0  
-----  
Bytes allocated for :  
    arrays            = 38176  
    strings           = 43912
```


Cadence SKILL Development Reference

Debug Functions

```
strings(perm)= 68708
IL stack      = 49140
(Internal)    = 12288
TOTAL GC COUNT 9
----- Summary of Symbol Table Statistics -----
Total Number of Symbols = 11201
Hash Buckets Occupied = 4116 out of 4499
Average chain length = 2.721331
t
```

How to Interpret the Summary Report

Column	Contains
Type	Data type names.
Size	Size of each atom representing the data type in bytes.
Allocated	Total number of bytes allocated in the pool for the data type.
Free	Number of bytes that are free and available for allocation.
Static	Memory allocated in static pools that are not subject to GC. This memory is usually generated when contexts are built. When variables are write protected, their contents are shifted to static pools.
GC Count	Number of GC cycles triggered because the pool for this data type was exhausted.

Related Topics

[Debug Functions](#)

[profileSummary](#)

getAllLoadedFiles

```
getAllLoadedFiles(  
    [ t_path ]  
)  
=> l_files / nil
```

Description

Returns a list of all files loaded since debug mode was turned on.

Arguments

<i>t_path</i>	Path to a SKILL file.
---------------	-----------------------

Value Returned

<i>l_files</i>	List of files.
<i>nil</i>	If no files have been loaded.

Examples

Returns a list of files loaded since debug mode was turned on.

```
getAllLoadedFiles()  
=> ("loop6.il" "demo.il"  
)
```

Returns a list of files, with their full paths, loaded since debug mode was turned on.

```
getAllLoadedFiles("demo.il")  
=> ("/home/user1/demo.il" "/home/user1/loop6.il"  
)
```

Related Topics

[Debug Functions](#)

[debugQuit](#)

[installDebugger](#)

getCallingFunction

```
getCallingFunction(  
    [ tx_nestingLevel ]  
)  
=> s_functionName / nil
```

Description

Returns the name of the calling function or procedure at the specified level in the call stack.

Arguments

<i>tx_nestingLevel</i>	Indicates the nesting level of the procedure or function name to be returned. If not specified, the name of the current function is returned.
------------------------	---

Value Returned

<i>s_functionName</i>	The name of the calling function or procedure.
<i>nil</i>	If the specified level exceeds the call stack level, or the function at the specified level is unnamed, <i>nil</i> is returned.

Examples

The following returns the name of the function one level up in the nest of calls. This is the same as `getCallingFunction(1)`

```
getCallingFunction()
```

The following returns the name of the current function.

```
getCallingFunction(0)
```

The following returns the name of the function one level up in the nest.

```
getCallingFunction(1)
```

The following returns the name of the function *n* levels up in the nest, or the top level function if *n-1* is the top, or *nil*.

```
getCallingFunction(n)
```

The following example returns the names of the functions in a list.

Cadence SKILL Development Reference

Debug Functions

```
(defun Child () (list (getCallingFunction 3)
                     (getCallingFunction 2)
                     (getCallingFunction 1)
                     (getCallingFunction)))
(defun Parent () (Child))
(defun GrandParent () (Parent))
(defun GreatGrandParent () (GrandParent))

(GreatGrandParent)
=> (GreatGrandParent GrandParent Parent Child)
```

Related Topics

Debug Functions

getFunctions

```
getFunctions(  
    t_fileName  
)  
=> l_functions / nil
```

Description

Returns functions defined in a file loaded after debug mode is turned on.

Returns the functions that were defined the last time that the file was loaded. Only the file name should be used and not its full path. If no extension is given, `.il` is assumed.

You must turn on debug mode before loading the file.

Arguments

<code>t_fileName</code>	File name loaded after debug mode was turned on.
-------------------------	--

Value Returned

<code>l_functions</code>	A list of functions.
<code>nil</code>	If no functions were defined in that file or if the file was not loaded after debug mode was turned on.

Examples

Returns the functions defined in `testfns.il`.

```
getFunctions( "testfns" )
```

Related Topics

[Debug Functions](#)

[getAllLoadedFiles](#)

[installDebugger](#)

getGFbyClass

```
getGFbyClass(  
    s_ClassName  
    [ g_nonExistent ]  
    [ g_clearGFcache ]  
)  
=> l_methods
```

Description

Returns a list of generic functions specializing on a given class.

Arguments

<i>s_ClassName</i>	Name of the class for which you want to view the list of specializing functions.
<i>g_nonExistent</i>	Lists all the generic functions specializing only on non-defined classes.
<i>g_clearGFcache</i>	Specifies whether to clear the method dispatch cache. The default is <code>nil</code> .

Value Returned

<i>l_methods</i>	A list of generic functions.
------------------	------------------------------

Examples

```
getGFbyClass('systemObject)
```

returns

```
(printObject)
```

Returns the specializing function of the specified class.

Related Topics

[Debug Functions](#)

[getAllLoadedFiles](#)

ilAddTopLevelErrorHandler

```
ilAddTopLevelErrorHandler(  
    [ s_handler ]  
)  
=> t
```

Description

Registers a new top-level error-handler. This error-handler is called after stacktrace, when an error occurs. If an error-handler already exists, the function displays a warning message.

Arguments

<i>s_handler</i>	A SKILL function that accepts 0 or 1 argument. When an error is raised, the error message string is passed to the handler.
------------------	--

Value Returned

t	The error-handler is successfully registered.
---	---

Examples

To define an error handler and then register it:

```
defun(myhandler(x)  
printf("TOP LEVEL ERROR HANDLER : %L" x) );  
ilAddTopLevelErrorHandler('myHandler)
```

Related Topics

[Debug Functions](#)

ilDebugCountLevels

```
ilDebugCountLevels(  
    )  
    => x_levels
```

Description

Returns the number of top-level debug and error frames present in the SKILL stack if SKILL is in breakpoint or error top level. Otherwise, the function returns 1.

Arguments

None

Value Returned

<i>x_levels</i>	Number of top-level error and debug frames present in the SKILL stack.
-----------------	--

Examples

To return the number of top-level error frames debugged in the SKILL stack:

```
ilDebugCountLevels();
```

Related Topics

[Debug Functions](#)

ilGetGFbyClass

```
ilGetGFbyClass(  
    s_ClassName  
    [ g_nonExistent ]  
    [ g_clearGFcache ]  
)  
=> l_methods
```

Description

Returns a list of generic functions specializing on a given class.

An alias to this function with the name getGFbyClass exists.

Arguments

<i>s_ClassName</i>	Name of the class for which you want to view the list of specializing functions.
<i>g_nonExistent</i>	Lists all the generic functions specializing only on non-defined classes.
<i>g_clearGFcache</i>	Specifies whether to clear the method dispatch cache. The default is <code>nil</code> .

Value Returned

<i>l_methods</i>	A list of generic functions.
------------------	------------------------------

Examples

```
ilGetGFbyClass('systemObject)
```

returns

```
(printObject)
```

Returns the specializing function of the specified class.

Related Topics

[Debug Functions](#)

ilGetIdeSessionWindow

```
ilGetIdeSessionWindow(  
    [ g_force ]  
)  
=> w_IDE / nil
```

Description

Returns the SKILL IDE session window ID. If *g_force* is set to a value other than `nil`, the function creates an IDE window and displays it on the screen.

Arguments

<i>g_force</i>	Creates an IDE window and displays it on the screen.
----------------	--

Value Returned

<i>w_IDE</i>	Returns the SKILL IDE session window.
<code>nil</code>	No IDE session window exists.

Examples

To return the SKILL IDE session window:

```
ilGetIdeSessionWindow()  
=> nil  
ilGetIdeSessionWindow(t)  
=> swindow:1
```

Related Topics

[Debug Functions](#)

ilGetTCovFiles

```
ilGetTCovFiles(  
    )  
=> l_tCovFiles / nil
```

Description

Returns the list of files processed when you run an application in test coverage mode using the command line option `-ilTCov <fileList>`.

Arguments

None

Value Returned

<code>l_tCovFiles</code>	List of files processed during SKILL test coverage using the command line option <code>-ilTCov <fileList></code> .
<code>nil</code>	The test coverage mode is not active.

Examples

If Virtuoso is run in test coverage mode with files `file1.il` and `file2.ils` by using the command line option `-ilTCov <fileList>`, you can use the `ilGetTCovFiles` function to retrieve the list of files.

```
virtuoso -ilTCov 'file1.il file2.ils'  
ilGetTCovFiles()  
=> ("file1.il file2.ils")
```

Related Topics

[Debug Functions](#)

ilMergeTCovData

```
ilMergeTCovData(  
    l_tCovDirs  
    t_resultDir  
)  
=> t
```

Description

Merges `tCov` files from several directories and stores them in a single directory.

Arguments

<code>l_tCovDirs</code>	List of directories with <code>tCov</code> data. Each element in the list must be a string.
<code>t_resultDir</code>	The name of resulting <code>tCov</code> directory where the merged data is stored.

Value Returned

<code>t</code>	Always returns <code>t</code> .
----------------	---------------------------------

Examples

To merge the `tCov` data in `./tCov` and `./tCov2` and store the merged versions in `./merged_tCovData`

```
ilMergeTCovData('("./tCov"  
"./tCov2") "./merged_tCovData")  
=> t
```

Related Topics

[Debug Functions](#)

ilRemoveMethod

```
ilRemoveMethod(  
    s_genFunction  
    g_className  
    [ g_method ]  
)  
=> t / nil
```

Description

Removes a given method from a generic function.

An alias to this function with the name removeMethod exists.

Arguments

<i>s_genFunction</i>	Name of the generic function from which the method needs to be removed.
<i>g_className</i>	Name of the class or a list of classes to which the generic function belongs.
<i>g_method</i>	Specifies the method qualifier. It can have one of the following values: '@before', '@after, and '@around. If this value is not provided or is specified as <code>nil</code> , then the primary method is removed.

Value Returned

<code>t</code>	The method is successfully removed.
<code>nil</code>	The method is not removed.

Examples

To remove the object `myClass` from the function `myFunction`:

```
ilRemoveMethod('myFunction 'myClass)  
ilRemoveMethod('myFunB '(classX classY) '@after)
```

Cadence SKILL Development Reference

Debug Functions

Related Topics

[Debug Functions](#)

ilRemoveTopLevelErrorHandler

```
ilRemoveTopLevelErrorHandler(  
    )  
=> t
```

Description

Unregisters the top-level error handler previously registered by the `ilAddTopLevelErrorHandler` function.

Arguments

None

Value Returned

`t` Always returns `t`.

Examples

To unregister the top-level error-handler:

```
ilRemoveTopLevelErrorHandler()
```

Related Topics

[Debug Functions](#)

ilSlotBoundp

```
ilSlotBoundp(  
    obj  
    t_slotName  
)  
=> t / nil
```

Description

Checks if a named slot is bound (has been assigned a value) to an instance.

Arguments

<i>obj</i>	An instance of some class.
<i>t_slotName</i>	Slot name.

Value Returned

t	The slot is bound.
nil	The slot is unbound.

Note: It throws an error if *obj* or *t_slotName* is invalid.

Examples

```
myObject->slotX = 20  
ilSlotBoundp(myObject "slotX")=> t
```

Related Topics

[Debug Functions](#)

ilToolBox

```
ilToolBox(  
    )  
=> t
```

Description

Brings up the SKILL Development toolbox, which lets you debug SKILL programs using a form-based graphical user interface.

Arguments

None

Value Returned

t Always returns t.

Examples

```
ilToolBox() => t
```

Related Topics

[Debug Functions](#)

inNext

```
inNext (
    )
    => t / nil
```

Description

Returns `t` if the function is called in the expression that is executed in the debugged code on the `next()` SKILL function.

Arguments

None

Value Returned

<code>t</code>	The current debugged expression is executed on <code>next()</code> .
<code>nil</code>	The current debugged expression is not executed on <code>next()</code> .

Examples

```
installDebugger()
Loading skillDev.cxt
t
1> defun( callInNext () printf("inNext() => %N\n" inNext())
)
callInNext
1> defun( test (x)
    x = list(x x)
    callInNext()
    x = list(x x)
)
test
1> breakpt test
(test)
1> test(4)
<<< Break >>> on entering test
Entering new debug toplevel due to breakpoint:
Type (help "debug") for a list of commands or debugQuit to exit the toplevel.
```

Cadence SKILL Development Reference

Debug Functions

```
Debug 2> next
stopped before evaluating (x = list(x x))
Debug 2> next
stopped before evaluating callInNext()
Debug 2> next
inNext() => t
stopped before evaluating (x = list(x x))
Debug 2> callInNext()
inNext() => nil
t
Debug 2> cont
((4 4)
  (4 4)
)
```

Related Topics

[Debug Functions](#)

inStepOut

```
inStepOut(  
    )  
=> t / nil
```

Description

Returns `t` if the function is called in the `stepout()` SKILL function.

Arguments

None

Value Returned

<code>t</code>	If called in <code>stepout()</code> .
<code>nil</code>	If not called in <code>stepout()</code> .

Examples

```
installDebugger()  
Loading skillDev.cxt  
t  
1> breakpt test  
(test)  
1> defun( callInStepOut () printf("inStepOut() => %N\n" inStepOut()))  
callInStepOut  
1> defun( test (x)  
x = list(x x)  
callInStepOut()  
)  
function test redefined  
test  
1> test(4)  
<<< Break >>> on entering test  
Entering new debug toplevel due to breakpoint:  
Debug 2> callInStepOut()  
inStepOut() => nil  
t  
Debug 2> next  
stopped before evaluating (x = list(x x))  
Debug 2> callInStepOut()  
inStepOut() => nil  
t  
Debug 2> next  
stopped before evaluating callInStepOut()  
Debug 2> stepout
```

Cadence SKILL Development Reference

Debug Functions

```
inStepOut () => t  
t
```

Related Topics

[Debug Functions](#)

Cadence SKILL Development Reference

Debug Functions

installDebugger

```
installDebugger(  
    )  
=> t / nil
```

Description

Installs the SKILL debugger as the error handler so that the debugger is entered automatically upon error.

`installDebugger` also turns on debug mode and allows all functions, including those that are write protected, to be redefined. Debug mode stores cross-referencing information about functions and files as well as more information for stacktraces. Debug mode also changes the prompt to display the number of nested debuggers plus one. You might find it desirable to put the `installDebugger` function in your initialization file while you are developing your code.

Arguments

None

Value Returned

<code>t</code>	The debugger is successfully installed.
<code>nil</code>	The debugger is not installed.

Examples

<code>installDebugger()</code>	<code>; Installs the SKILL debugger.</code>
<code>4 / 0</code>	<code>; Generates an error and enters</code>
	<code>; the SKILL debugger.</code>
<code>stacktrace</code>	<code>; Displays the SKILL stack.</code>
<code>debugQuit()</code>	<code>; Exits the debugger.</code>

Related Topics

[uninstallDebugger](#)

[debugQuit](#)

[stacktrace](#)

listAlias

```
listAlias(  
    [ s_aliasName ]  
)  
=> s_functionName / l_propertyList / nil
```

Description

Prints a (property) list of all current aliases and associated function symbols, or the function symbol for which the given alias is defined.

Arguments

<i>s_aliasName</i>	Symbol name of the alias
--------------------	--------------------------

Value Returned

<i>s_functionName</i>	Function symbol for which the given alias name is defined.
<i>l_propertyList</i>	Property list of all current aliases and associated function symbols. This is printed when no argument is specified.
nil	The given alias name is not an alias for any function, or there are no aliases defined for any function at all.

Examples

```
;; Defines 'lf' and 'e' as the aliases of the listFunctions()  
;; and edit() functions, respectively  
alias(lf listFunctions) => lf  
alias(e edit) => e  
  
;; Prints the name of the function that 'lf' aliases to  
listAlias('lf') => listFunctions  
  
;; Prints A property list of all current aliases and associated  
;; function symbols  
listAlias() => (e edit lf listFunctions)  
  
;; The given alias name is not an alias for any function  
listAlias('bogus') => nil  
  
;; Remove 'lf' and 'e' as aliases  
unalias(lf) => (lf)  
unalias(e) => (e)  
  
;; There's no alias defines for any function anymore  
listAlias() => nil
```

Cadence SKILL Development Reference

Debug Functions

Related Topics

[Debug Functions](#)

listFunctions

```
listFunctions(  
    t_pattern  
    [ g_listAllFuncs ]  
)  
=> l_functions / nil
```

Description

Returns all public function names that contain the given substring or match the given regular expression. If the second (optional) argument is specified as `t` (or a non-nil value), `listFunctions` looks at the SKILL virtual machine, rather than the `cdsFinder` database, and returns all `isCallable` Cadence public functions and user-defined SKILL functions that contain the given substring or match the given regular expression.

By default, the source of the returned values is the SKILL directory in the SKILL Finder database, which is located in the doc hierarchy under `your_install_dir/doc/finder/SKILL`. `listFunctions` will also look in the `your_install_dir/local/finder/SKILL` directory, as well as directories specified in `CDS_FINDER_PATH` for any personal functions you may have created and placed there in the appropriate SKILL Finder format. For usage of `CDS_FINDER_PATH`, see [Environment Variable for Additional Finder Data Directories](#).

The returned function names can be used for passing a list of function names that match a given pattern to another function.

Arguments

<code>t_pattern</code>	Pattern to search for.
<code>g_listAllFuncs</code>	If specified as <code>t</code> (or a non-nil value), all <code>isCallable</code> Cadence public and user-defined function names that contain the given substring or match the given regular expression are returned. Default is <code>nil</code> .

Value Returned

<code>l_functions</code>	All public function names that match the given <code>t_pattern</code> .
<code>nil</code>	No functions are found that match the pattern.

Cadence SKILL Development Reference

Debug Functions

Examples

Calls the `tracef` function with all the functions that contain the substring `hi`.

```
apply( 'tracef listFunctions( "hi" ) )
```

Calls the `tracef` function with all `isCallable` Cadence public and user-defined functions that contain the substring `x`

```
apply( 'tracef listFunctions( "x" t ) )
```

Lists all the functions that begin with `hi`

```
listFunctions("^hi")
```

Lists all the functions that begin with `db` and have `Copy` in their names.

```
listFunctions("^db.*Copy")
```

Related Topics

[Debug Functions](#)

[listVariables](#)

[rexCompile](#)

[rexMatchp](#)

listVariables

```
listVariables(  
    t_pattern  
)  
=> l_variables
```

Description

Returns all variable names that match the given substring or regular expression as part or all of their print name.

This can be used for passing a list of variable names that match a given pattern to a function.

Arguments

<i>t_pattern</i>	Pattern to search for.
------------------	------------------------

Value Returned

<i>l_variables</i>	All variable names that match the given <i>t_pattern</i> .
--------------------	--

Examples

Traces the variables that match the pattern `myVars`.

```
apply( 'tracev listVariables( "myVars" ) )
```

Related Topics

[Debug Functions](#)

[listFunctions](#)

[rexCompile](#)

memoryAllocated

```
memoryAllocated(  
    )  
=> f_megabytesAllocated
```

Description

Returns the amount of memory allocated by a process. The returned value is an approximation in megabytes and might not include the memory that has been allocated, but the amount that is unused.

The returned value is intended to be larger than the value returned from a previous invocation of this function, in case, a large amount of memory has been allocated.

Arguments

None

Arguments

f_megabytesAllocated

Approximate amount of memory that the process has allocated.

Examples

```
memoryAllocated() => 1.743386
```

Related Topics

[Debug Functions](#)

Cadence SKILL Development Reference

Debug Functions

next

```
next (
    [ x_steps ]
)
```

Description

Allows execution to proceed until the next expression. This function only works if executed from within a break handler and if the code you want to step through was loaded under `debugMode`. See `installDebugger`.

`next` reenters the break handler after completing `x_step` expressions, as long as the program has not finished.

You cannot execute the `next` function inside functions that are read-protected.

Arguments

<code>x_steps</code>	Number of SKILL expressions to execute at or above the current stack depth.
----------------------	---

Value Returned

None

Examples

Suppose `/tmp/color.il` defines function `initColor`:

```
(defun initColor (object)
  (let ((colorList '(red green yellow)) color)
    (setq color (concat (get object 'color)))
    (if (memq color colorList)
        (printf "color %s initialized" (get object 'name)))
  )
)
```

Try this file in debugger:

```
installDebugger
=> t
(ssstatus sourceTracing t)           ; Turns on sourceTracing
                                      ; to get line numbers.
=> t
1> load "/tmp/color.il"
=> t
```

Cadence SKILL Development Reference

Debug Functions

```
1> (putprop 'object1 "green" 'color)
=> "green"

1> breakpt(initColor (entry (null object)) concat)
=> concat(initColor)

1> (initColor 'object1)
<<< Break >>> on calling concat with args ("green")
at line 3 in file /tmp/color.il

Debug 2> next                                ; Proceeds to 'if' form
stopped at line 4 in file /tmp/color.il
before evaluating if(memq(color colorList) printf("color %s initialized"...

Debug 2> step                                ; Steps into 'if' form
stopped at line 4 in file /tmp/color.il
before evaluating memq(color colorList)

Debug 2> next                                ; Proceeds to 'printf' form
stopped at line 5 in file /tmp/color.il
before evaluating printf("color %s initialized" get(object 'name))
```

Related Topics

[Debug Functions](#)

[breakpt](#)

[installDebugger](#)

[step](#)

Cadence SKILL Development Reference

Debug Functions

pp

```
pp (
    s_functionName
    [ p_outputPort ]
)
=> nil
```

Description

Pretty prints the definition of a function. The function must not be read-protected. This is an `nlambda` function.

Each function definition is printed in a manner that allows it to be read back into SKILL. `pp` does not evaluate its first argument but does evaluate the second argument, if given.

Arguments

<i>s_functionName</i>	Name of the function to be pretty printed.
<i>p_outputPort</i>	Output port to print to. Default is <code>poport</code> .

Value Returned

<code>nil</code>	Pretty prints the function.
------------------	-----------------------------

Examples

Defines the factorial function `fac` then pretty prints it to `poport`.

```
procedure(fac(n) if(n <= 1 1 n*fac(n-1)))=> fac
pp fac
procedure(fac(n)
    if((n <= 1) 1
        (n * fac(n - 1))
    )
)
=> nil
```

Related Topics

[Debug Functions](#)

[profile](#)

Cadence SKILL Development Reference

Debug Functions

printFunctions

printFunctions

```
printFunctions(  
    t_pattern  
    [ p_outport ]  
    [ g_listAllFuncs ]  
)  
=> t
```

Description

Prints all function names that contain the given substring or match the given regular expression.

These functions are useful for finding functions that contain the same substring or finding an individual function when you know only part of the name.

By default, the source of the returned values is the SKILL directory in the SKILL Finder database, which is located in the doc hierarchy under *your_install_dir/doc/finder/SKILL*. `printFunctions` will also look in the *your_install_dir/local/finder/SKILL* directory, as well as directories specified in `CDS_FINDER_PATH` for any personal functions you may have created and placed there in the appropriate SKILL Finder format. For usage of `CDS_FINDER_PATH`, see [Environment Variable for Additional Finder Data Directories](#).

If the third (optional) argument is specified to `t`, `printFunctions` looks at the SKILL virtual machine, rather than the `cdsFinder` database, and returns all `isCallable` Cadence public functions and user-defined SKILL functions that contain the given substring or match the given regular expression.

Arguments

<i>t_pattern</i>	Pattern to search for.
<i>p_outport</i>	Optional output port. Default is <code>poport</code> .
<i>g_listAllFuncs</i>	If specified to <code>t</code> , all <code>isCallable</code> Cadence public and user-defined function names that contain the given substring or match the given regular expression are returned. Default is <code>nil</code> .

Cadence SKILL Development Reference

Debug Functions

Value Returned

`t` Always returns `t` (after printing all the function names that contain the given substring or match the given regular expression).

Examples

Returns `t` and prints all the function names that contain the substring `installDebug`.

```
printFunctions( "installDebug" ) => t
```

Returns `t` and prints all `isCallable` Cadence public and user-defined function names that contain the substring `x`.

```
printFunctions( "x" nil t)
```

Returns `t` and writes all `isCallable` Cadence public and user-defined function names that contain the substring `x` to outfile.

```
p = outfile( "outfile" ) => port:"outfile"
printFunctions( "x" p t )
```

Related Topics

[Debug Functions](#)

[listFunctions](#)

[printVariables](#)

[rexCompile](#)

printObject

```
printObject(  
    g_object  
    [ p_outputPort ]  
)  
=> g_result
```

Description

Writes a description of an object to an output port.

If you define a method for this generic function, it should call one or more of the SKILL print functions. See [Generic Functions](#).

Arguments

<i>g_object</i>	Object whose print representation you want.
<i>p_outputPort</i>	Specified output port.

Value Returned

<i>g_result</i>	The return value of the method that was called.
-----------------	---

Examples

```
P = makeInstance( 'Point ?name "P" ?x 3 ?y 4 )  
=> stdobj:0x1d003c  
ILS-<2> defmethod( printObject ((p Point)  
    @optional ( port poport ))  
    fprintf( poport "%s @ %n:%n\n" p->name p->x p->y )  
    nil  
    )  
t  
ILS-<2> printObject( P )  
P @ 3:4  
nil
```

Prints P @ 3:4, the location of P.

```
ILS-<2> defstruct( card rank suit )  
t  
ILS-<2> mycard = make_card( ?rank 2 ?suit "spades" )  
array[4]:2304000  
ILS-<2> addDefstructClass( card )  
funobj:0x1c98f8  
ILS-<2> printObject( mycard )
```

Cadence SKILL Development Reference

Debug Functions

```
Loading skillDev.cxt
Structure of type card:
  rank: 2
  suit: "spades"
t
```

Related Topics

[Debug Functions](#)

printstruct

```
printstruct(  
    g_object  
)  
=> t
```

Description

Prints the contents of an association table or defstruct in a tabular format.

For debugging purposes, the `printstruct` function prints the contents of a structure in a readable form. It recursively prints nested structures.

Arguments

<i>g_object</i>	Defstruct or association table to be printed.
-----------------	---

Value Returned

t	Contents of the defstruct or association table.
---	---

Example

```
defstruct(myStruct slot1 slot2) => t  
struct = make_myStruct(?slot1 "one" ?slot2 'two)=> array[4]:3872800  
printstruct(struct)  
Structure of type myStruct:  
slot1: "one"  
slot2: two => t
```

Related Topics

[Debug Functions](#)

printVariables

```
printVariables(  
    t_pattern  
    [ p_output ]  
)  
=> t
```

Description

Prints all variable names that contain the given substring or match the given regular expression, along with their values.

This function is useful for finding variables that contain the same substring or finding an individual variable when you know only part of the name. The `printVariables` function also prints the value of each variable it finds.

Arguments

<code>t_pattern</code>	Pattern to search for.
<code>p_output</code>	Optional output port. The default is <code>poport</code> .

Value Returned

<code>t</code>	Always returns <code>t</code> and prints the value of each variable it finds.
----------------	---

Examples

Prints all the variables with their values that contain the substring `stack` and returns `t`. The underscore (`_`) at the beginning of `_stacktrace` indicates that it is an internal system variable.

```
printVariables( "stack" )  
                _stacktrace 0  
=> t
```

Related Topics

[Debug Functions](#)

[listVariables](#)

Cadence SKILL Development Reference

Debug Functions

printFunctions

removeMethod

```
removeMethod(  
    s_genFunction  
    g_className  
    [ g_role ]  
)  
=> t / nil
```

Description

Removes a given method from a generic function.

For compatibility with previous releases, this function is aliased to `lRemoveMethod`.

Arguments

<i>s_genFunction</i>	Name of the generic function from which the method needs to be removed.
<i>g_className</i>	Name of the class or a list of classes to which the generic function belongs.
<i>g_role</i>	Specifies the method qualifier. It can have one of the following values: '@before', '@after', '@around', or <code>nil</code> . If this value is not provided or is specified as <code>nil</code> , then the primary method is removed.

Value Returned

<code>t</code>	If the method is successfully removed.
<code>nil</code>	If the method is not removed.

Examples

To remove the object `myClass` from the function `myFunction`:

```
removeMethod('myFunction 'myClass)  
removeMethod('myFunB '(classX classY) '@after)
```

Related Topics

Cadence SKILL Development Reference

Debug Functions

Debug Functions

resume

```
resume(  
    [ g_result ]  
)  
=> g_toplevel
```

Description

Exits the interactive top-level loop started with the most recently invoked `toplevel` function and returns its argument to the caller of `toplevel`. Do not use this function programmatically; use it only as an interactive command.

The `resume` function itself does not return. It returns value of the `toplevel` function.

- To start a top-level interactive loop in SKILL++ mode, type

```
toplevel( 'ils )
```

- To start a top-level interactive loop in SKILL mode, type

```
toplevel( 'il )
```

Arguments

<i>g_result</i>	Optional value to be returned as the result from the previous <code>toplevel</code> calls.
-----------------	--

Value Returned

<i>toplevel</i>	Returns the return value of the <code>toplevel</code> function. The <code>resume</code> function itself does not return.
-----------------	--

Examples

Following is a transcript of a brief session, including prompts.

```
> R = toplevel( 'ils )  
ILS-<2> resume( 1 )  
1  
> R  
1
```

Related Topics

Cadence SKILL Development Reference

Debug Functions

Debug Functions

toplevel

skillDebugger

```
skillDebugger(  
    )  
=> nil
```

Description

Activates the SKILL Debugger. Usually invoked by a break or error handler.

You do not normally call it; instead it is invoked by the break or error handler. The SKILL debugger is the default break handler, and can also be used as the current error handler by calling the `installDebugger` function.

When you enter the debugger, the prompt changes to `debug #>` where # is a number identifying the number of nested debuggers plus one. Once in the SKILL debugger, you can examine the stack and local variables with functions such as `stacktrace`, `dump`, and `where`. You can also execute any SKILL function normally available because the debugger calls the SKILL top level. To quit the function, use `debugQuit`.

If the SKILL debugger is entered from a breakpoint, the following functions can be used to resume execution: `step`, `next`, `stepout`, and `continue`. If an error occurs and an `errset` is on the stack, the SKILL Debugger will not be invoked. To debug errors in this case, set `_stacktrace` to an integer value greater than zero or set breakpoints before the error occurs.

Arguments

None

Value Returned

`nil` Always returns `nil`.

Examples

```
skillDebugger()      ; Calls the debugger.  
debugQuit()          ; Exits the debugger.  
alias q debugQuit    ; Alias used for faster typing.
```

Cadence SKILL Development Reference

Debug Functions

Related Topics

[debugQuit](#)

[dump](#)

[cont, continue](#)

[installDebugger](#)

[next](#)

[stacktrace](#)

[uninstallDebugger](#)

skillDevStatus

```
skillDevStatus(  
    )  
=> t / nil
```

Description

Returns the current status of the Cadence SKILL Development Environment license.

Arguments

None

Value Returned

t	Cadence SKILL Development Environment license is checked out.
nil	Cadence SKILL Development Environment license is not checked out.

Examples

```
skillDevStatus()  
=> nil
```

Related Topics

[Debug Functions](#)

stacktrace

```
stacktrace(  
    [ g_unevaluated ]  
    [ x_depth ]  
    [ x_skip ]  
    [ p_port ]  
)  
=> x_result
```

Description

Prints the functions on the stack and their arguments to the depth specified, or to the bottom of the stack if no depth is specified.

The function observes the following rules:

- When debug mode is on `stacktrace`, it prints the evaluated function arguments by default if the status switch `traceArgs` has been set to `t`.
- When debug mode is off, `stacktrace` always prints the unevaluated arguments.
- If the status switch `stacktrace` is set (using the `sstatus` function) to an integer, it prints that number of stack frames automatically whenever an error occurs.
- If there are no functions on the stack, that is, you are at the top, then `stacktrace` does not print anything and returns 0.

Note: `stacktrace` has a more flexible interface for user convenience. Thus if the first argument is a number it will interpret it to be `x_depth`, otherwise if it is non-`nil` it will take it to be `g_unevaluated`.

This function is usually used inside the break or error handler.

Arguments

<i>g_unevaluated</i>	Always prints the unevaluated function parameters.
<i>x_depth</i>	Number of stack levels to print. The default is all.
<i>x_skip</i>	<code>stacktrace</code> skips over the number of function calls specified by <i>x_skip</i> . This argument defaults to 1.
<i>p_port</i>	Port for the <code>stacktrace</code> output. The default is error port.

Cadence SKILL Development Reference

Debug Functions

Value Returned

x_result The number of stack frames printed.

Examples

Prints all the functions on the stack.

```
stacktrace()
```

Prints the top five functions on the stack.

```
stacktrace( 5 )
```

Prints the five functions on the stack that come after the first three to the trace port.

```
stacktrace( t 5 3 ptport )
```

Prints the first six stack frames every time an error occurs.

```
sstatus( stacktrace 6 )
```

Related Topics

[breakpt](#)

[cont, continue](#)

[installDebugger](#)

[step](#)

[stepend](#)

[stepout](#)

[unbreakpt](#)

[uninstallDebugger](#)

Cadence SKILL Development Reference

Debug Functions

step

```
step(  
    [ x_steps ]  
)
```

Description

Steps into functions and executes a given number of SKILL functions. This function only works if executed from within a break handler and if the code you want to step through was loaded under `debugMode`. See [installDebugger](#).

The number of steps defaults to 1 if there is no argument given. After completing `x_steps`, `step` re-enters the break handler before executing its next function, as long as the program has not finished. You cannot step inside functions that are read-protected.

Arguments

<code>x_steps</code>	Number of SKILL commands to execute.
----------------------	--------------------------------------

Value Returned

None

Examples

Suppose `/tmp/color.il` defines function `initColor`:

```
(defun initColor (object)  
  (let ((colorList '(red green yellow)) color)  
    (setq color (concat (get object 'color)))  
    (if (memq color colorList)  
        (printf "color %s initialized" (get object 'name)))  
  )  
)
```

Try this file in debugger:

```
installDebugger  
=> t
```

```
1> (sstatus sourceTracing t)  
                                ; Turns on sourceTracing to get line numbers  
=> t
```

Cadence SKILL Development Reference

Debug Functions

```
1> load "/tmp/color.il"
=> t
```

```
1> (putprop 'object1 "green" 'color)
=> "green"
```

```
1> breakpoint (initColor (entry (null object)) concat)
=> concat(initColor)
```

```
1> (initColor 'object1)
<<< Break >>> on calling concat with args ("green")
at line 3 in file /tmp/color.il
```

```
Debug 2> next
stopped at line 4 in file /tmp/color.il
before evaluating if(memq(color colorList) printf("color %s initialized"...
```

```
Debug 2> step
stopped at line 4 in file /tmp/color.il
before evaluating memq(color colorList)
```

```
Debug 2> next
stopped at line 5 in file /tmp/color.il
before evaluating printf("color %s initialized" get(object 'name))
```

```
Debug 2> step
stopped at line 5 in file /tmp/color.il
before evaluating get(object 'name)
```

Related Topics

[breakpt](#)

[cont, continue](#)

[dump](#)

[next](#)

[stepend](#)

[stepout](#)

[unbreakpt](#)

[where](#)

stepend

```
stepend(  
    [ x_stepN ]  
)
```

Description

Allows execution to proceed to the end of the `n`th enclosing form and displays its result. `stepend` cannot proceed past the end of the current function. This function only works if executed from within a break handler and if the code you want to step through was loaded under `debugMode`. See [installDebugger](#).

Comparing `step` and `stepend`:

- `step` proceeds to the “beginning” of the $(n + 1)$ th possibly enclosed form and displays the next form to be evaluated.
- `stepend` proceeds to the end of the `n`th enclosing form and displays its result. `stepend` cannot proceed past the end of the current function.

Arguments

<code>x_stepN</code>	Number of forms to step through.
----------------------	----------------------------------

Value Returned

None

Examples

Suppose `/tmp/color.il` defines function `initColor`:

```
(defun initColor (object)  
  (let ((colorList '(red green yellow)) color)  
    (setq color (concat (get object 'color)))  
    (if (memq color colorList)  
        (printf "color %s initialized" (get object 'name)))  
  )  
)
```

Try this file in debugger:

```
installDebugger  
=> t
```

Cadence SKILL Development Reference

Debug Functions

```
1> (sstatus sourceTracing t)
; Turns on sourceTracing to get line numbers
=> t

1> load "/tmp/color.il"
=> t

1> (putprop 'object1 "green" 'color)
=> "green"

1> breakpt(initColor (entry (null object)) concat)
=> concat(initColor)

1> (initColor 'object1)
<<< Break >>> on calling concat with args ("green")
at line 3 in file /tmp/color.il

Debug 2> next
stopped at line 4 in file /tmp/color.il
before evaluating if(memq(color colorList) printf("color %s initialized"...

Debug 2> step
stopped at line 4 in file /tmp/color.il
before evaluating memq(color colorList)

Debug 2> stepend
stopped at line 4 in file /tmp/color.il
after evaluating memq(color colorList)
==> (green yellow)

Debug 2> stepend
stopped at line 5 in file /tmp/color.il
after evaluating get(object 'name)
==> nil
```

Related Topics

Debug Functions

step

stepout

Cadence SKILL Development Reference

Debug Functions

stepout

```
stepout(  
    [ x_steps ]  
)
```

Description

Allows execution to proceed until the evaluator returns from the current function.

It reenters the break handler when the current function returns to its caller.

Arguments

<i>x_steps</i>	Number of function call levels to return from before reentering the break handler. Defaults to 1.
----------------	---

Value Returned

None

Examples

Suppose `/tmp/color.il` defines function `initColor`:

```
(defun initColor (object)  
  (let ((colorList '(red green yellow)) color)  
    (setq color (concat (get object 'color)))  
    (if (memq color colorList)  
        (printf "color %s initialized" (get object 'name)))  
    )  
  )  
)
```

Try this file in debugger:

```
installDebugger  
=> t  
  
1> (sstatus sourceTracing t)  
                                ; Turns on sourceTracing to get line numbers  
=> t  
  
1> load "/tmp/color.il"  
=> t  
  
1> (putprop 'object1 "green" 'color)  
=> "green"
```

Cadence SKILL Development Reference

Debug Functions

```
=> initColor

1> (putprop 'object1 "green" 'color)
=> "green"

1> breakpt(initColor (entry (null object)) get)
=> (get initColor)

1> (initColor 'object1)
<<< Break >>> on calling get with args (object1 color)
at line 3 in file /tmp/color.il

Debug 2> stepout
<<< Break >>> on calling get with args (object1 name)
at line 5 in file /tmp/color.il
                                ; stop at next 'get'
```

Related Topics

Debug Functions

breakpt

cont, continue

toplevel

```
toplevel(  
    [ s_langMode ]  
    [ e_envobj ]  
)  
=> g_result
```

Description

Starts an interactive top-level loop in either SKILL or SKILL++ mode.

All expressions you enter while the loop is in progress are evaluated with the specified language mode and optional environment. If you do not specify a language mode, then classic-SKILL is the default.

The defining forms (such as `define`, `defun`, `procedure`) entered at the top-level prompt are treated as “toplevel” definitions, not as local ones, even if a non-top-level environment is supplied. (The same is true for `eval` with an explicit environment.)

Arguments

<i>s_langMode</i>	Must be a symbol. Valid values: ' <i>ils</i> Indicates SKILL++. ' <i>il</i> Indicates SKILL.
<i>e_envobj</i>	When the given <i>s_langMode</i> is for SKILL++, an optional environment object can be supplied, and the forms entered will be evaluated within the given (lexical) environment (except for the defining forms, like <code>define</code> , <code>defun</code> , and <code>procedure</code> , which will always add definitions to the top-level environment).

Value Returned

<i>g_result</i>	Argument passed to a call to <code>resume</code> .
-----------------	--

Examples

Starts an interactive loop, with prompt `ILS-<2>` and immediately returns the value 1 to the outer top level.

Cadence SKILL Development Reference

Debug Functions

```
> R = toplevel( 'ils )
ILS-<2> resume( 1 )
1
> R
1
```

Starts an interactive loop, with prompt `ILS-<3>`, in the environment established by the `let` expression. The `resume` function returns the current value of the local variable `x` to the outer top level, with prompt

`ILS-<2>`.

```
ILS-<2> R = let( ( ( x 1 ) ( y 2 ) )
toplevel( 'ils theEnvironment() )
)
ILS-<3> x
1
ILS-<3> y
2
ILS-<3> x = 4
4
ILS-<3> resume( x )
4
ILS-<2> R
4
```

Related Topics

Debug Functions

[resume](#)

[errset](#)

tracef

```
tracef(  
    [ s_function | t_filename ... | t ]  
)  
=> g_result
```

Description

Turns on tracing of specified functions. Shows the functions called with their evaluated arguments and return values. This is an `nlambda` function.

The output port for tracing is `ptport`, which defaults to `poport`.

- If `t` is passed in, all functions are traced. However, this probably produces more information than you want and your program runs much more slowly.
- If you do not give `tracef` an argument, it returns a list of all functions being traced.
- If the argument is a string, `tracef` assumes it is a file name. `tracef` checks to see if a file was loaded after debug mode was turned on and if so, traces all functions defined in that file.
- If the symbol `debugFiles` is passed in, all functions in all files loaded since debug mode was turned on are traced.

If you want to force certain functions not to be traced even though you have turned on tracing for many or all functions, you can add the property `notrace` with a non-`nil` value on the name of the function. For example, to prevent `plus` from being traced use `putprop('plus t 'notrace)` or `plus.notrace = t`.

Arguments

<i>s_function</i>	Any function that you want to trace.
<i>t_filename</i>	Any file containing functions that you want to trace.
<i>t</i>	Turns tracing on for all functions.

Value Returned

<i>g_result</i>	Functions or files traced.
-----------------	----------------------------

Cadence SKILL Development Reference

Debug Functions

Examples

```
(defun f (x) (add1 x))      ; Defines a function f.  
=> f
```

```
(tracef f                      ; Turns on tracing for f.  
=> (f)
```

```
f(3)  
|f(3)  
|f --> 4  
=> 4
```

```
(tracef t                      ; Turns on tracing for all functions.  
|tracef --> t  
=> t
```

```
f(3)  
|f(3)  
||add1(3)  
||add1 --> 4  
|f --> 4  
=> 4
```

Suppose `testfuns.il` defines functions `f1` and `f2`:

```
(defun f1 (x) x+1)  
(defun f2 (y) f1(y)+1)  
  
installDebugger                ; debug was turned on before loading a file  
=> t
```

```
1> load "testfuns.il"  
=> t
```

```
1> tracef("testfuns.il")  
("testfuns.il")              ; tracing for all functions in the file
```

```
1> f2 3  
|f2(3)  
||f1(3)  
||f1 --> 4  
|f2 --> 5  
5
```

Related Topics

Debug Functions

tracev

untrace

Cadence SKILL Development Reference

Debug Functions

untracev

tracelevlimit

```
tracelevlimit(  
    [ x_depth ]  
)  
=> t
```

Description

Limits the indentation level and hence the call depth while tracing functions, arrays, or variables.

Specifying *x_depth* traces the properties till level x.

Arguments

<i>x_depth</i>	Indentation level to which properties should be traced.
----------------	---

Value Returned

t	Always returns t.
---	-------------------

Examples

If we define several functions, such that each function in turn calls another function, the call depth can be limited using `tracelevlimit(x_depth)`.

```
defun(func_a() var_a=1 putprop('var_aa 1 'prop_x) println("A") t)  
defun(func_b() var_b=2 putprop('var_bb 1 'prop_x) println("B") func_a() t)  
defun(func_c() var_c=3 putprop('var_cc 1 'prop_x) println("C") func_b() t)  
defun(func_d() var_d=4 putprop('var_dd 1 'prop_x) println("D") func_c() t)
```

We can set the indentation level as 2:

```
tracelevlimit(2) => t
```

So, when we call `func_d()`, the output will be:

```
|func_d()  
||putprop(var_dd 1 prop_x)  
||putprop => 1  
||println("D")  
D
```

Cadence SKILL Development Reference

Debug Functions

```
||println  
=> nil  
||func_c()  
"C"  
"B"  
"A"  
||func_c  
=> t  
|fun_d  
=> t  
t
```

Related Topics

[Debug Functions](#)

tracelevunlimit

```
tracelevunlimit(  
    )  
=> t
```

Description

Turns off limiting of the indentation level and hence the call depth while tracing functions, arrays, or variables.

Arguments

None

Value Returned

t Always returns t.

Examples

```
tracelevunlimit()  
=> t
```

Related Topics

[Debug Functions](#)

tracep

```
tracep(  
    [ s_property... | t ]  
)  
=> g_result
```

Description

Turns on tracing of assignments to specified properties. This is an `nlambda` function.

If `t` is passed in, all properties are traced.

Passing `t` as an argument to the `tracep` function is allowed only if you set the internal system variable `traceTEnable` to `t` by typing `sstatus(traceTEnable t)` in the CIW.

If no argument is given, all properties being traced are returned. `tracep` prints the evaluated value assigned to the property and its previous value. The output port for tracing is `ptport`, which defaults to `poport`.

Arguments

<code>s_property</code>	Names of properties to be traced.
<code>t</code>	Traces all properties.

Value Returned

<code>g_result</code>	Properties successfully marked for tracing.
-----------------------	---

Examples

```
tracep myProp  
putprop( 'foo 5 'myProp)  
|Property myProp on foo set to 5, was nil => 5  
untracep( myProp ) => ( myProp )
```

Related Topics

[Debug Functions](#)

[untracep](#)

tracev

```
tracev(  
    [ s_variable ... | t ]  
)  
=> g_result
```

Description

Turns on tracing of assignments to specified variables. This is an `nlambda` function.

If `t` is passed in, all variables are traced.

Passing `t` as an argument to the `tracev` function is allowed only if you set the internal system variable `traceTEnable` to `t` by typing `sstatus(traceTEnable t)` in the CIW.

If no argument is given, all variables being traced are returned. `tracev` prints the unevaluated and evaluated value assigned to the variable. The output port for tracing is `ptport`, which defaults to `poport`.

SKILL++ variables currently cannot be traced with `tracev`.

Arguments

<i>s_variable</i>	Names of the variables to be traced.
<i>t</i>	Traces all variables.

Value Returned

<i>g_result</i>	Variables successfully marked for tracing.
-----------------	--

Examples

```
tracev x           ; Traces the variable x.  
x = 5              ; Shows the old and new value of x.  
untracev x         ; Clears tracing for the variable x.  
tracev t           ; Traces all variable assignments.  
untracev t         ; Clears all variable tracing.
```

Related Topics

[Debug Functions](#)

Cadence SKILL Development Reference

Debug Functions

tracef

untrace

untracev

unbreakpt

```
unbreakpt (
    [ u_function... | t ]
)
=> g_result
```

Description

Clears breakpoints. This is an `nlambda` function.

The SKILL debugger is the default break handler and is entered automatically before evaluating functions or function objects with breakpoints set. The functions `breakpt` and `unbreakpt` set and clear breakpoints on the given functions and function objects. Once you are in the break handler, you can examine the state of the program and use single stepping functions such as `step`, `next`, `stepout`, or `continue`.

We recommend that you turn debug mode on before using the break handler with `sstatus (debugMode t)` to change the prompts to tell you when you enter and exit the break handler. Another way to enter the break handler is to insert the `break` function directly into a SKILL function at the point desired.

Arguments

<i>u_function</i>	Function or <code>t</code> to <code>unbreakpt</code> all functions.
-------------------	---

Value Returned

<i>g_result</i>	List of functions or function objects whose breakpoints have been cleared.
-----------------	--

Examples

This example sets a breakpoint, enters the break handler, continues, and finally clears the breakpoint.

```
breakpt( times )           ; Sets a breakpoint on times.
sstatus( debugMode t )    ; Make sure debug mode is on.
times(2 plus( 2 3 ))       ; Invokes the break handler.
cont                       ; Continue executing.
unbreakpt( times )         ; Clear the breakpoint.
```

This example sets a breakpoint on a function object and later clears the breakpoint.

Cadence SKILL Development Reference

Debug Functions

```
(installDebugger)           ; Make sure debug mode is on
=> t

(defun test (x) (printf "test : x == %L\n" x))
=> test

(putd 'test1 (getd 'test))   ;test and test1 are the same functions
=> funobj:test

(funcall 'breakpt (getd 'test)) ;set breakpoint on the funobject
(funobj:test)
(test1 8)
<<< Break >>> on entering test
Entering new debug toplevel due to breakpoint:
Debug 2> cont
test : x == 8
=> t

(funcall 'unbreakpt (getd 'test)) ;remove breakpoint
(funobj:test)
(test1 8)
test : x == 8
=> t
```

Related Topics

[break](#)

[breakpt](#)

[cont, continue](#)

[next](#)

[step](#)

[stepend](#)

[stepout](#)

unbreakptMethod

```
unbreakptMethod(  
    [ s_name [ @before | @after ] ]  
    [ l_specializer ]  
)  
=> t
```

Description

Removes breakpoints set on the specified method.

Arguments

<i>s_name</i>	The method for which the breakpoint has to be cleared.
<i>l_specializer</i>	List of specializers of the specified method. It can include @before, @after, and @around qualifiers.

Value Returned

<i>t</i>	List of removed breakpoints.
----------	------------------------------

Examples

```
unbreakptMethod(S_name)  
; removes the breakpoint on "S_name" function, behaves the same way as unbreakpt()  
unbreakptMethod(S_name nil)  
; removes the breakpoint on "generic" method of S_name.  
unbreakptMethod(S_name @after (classA t))  
; removes the breakpoint on "@after" method specialized on (classA t) of "S_name"  
unbreakptMethod(S_name (classB t))  
; removes the breakpoint on primary method specialized on (classB t) of "S_name".  
unbreakptMethod()  
; when specified without arguments, returns t
```

Related Topics

Debug Functions

uncount

```
uncount(  
    [ s_function ... | t ]  
)  
=> g_result
```

Description

Turns off counting and returns the current count results. This is an `nlambda` function.

`count` allows you to count the number of times a function has been called. `count` and `uncount` measure function call frequency and also serve as a valuable debugging aid. Both `count` and `uncount` accept more than one function argument, or `t` for counting/uncounting all functions.

To examine the number of times a function has been counted, call the `uncount` function. A list containing the number of times each function was called, along with the function name, is returned in the form of a list of (`number functionName`) pairs, such as,

```
((20 plus) (10 times) (5 greaterp))
```

The sublists are sorted by their first elements, using `sortcar`, so the most frequently executed functions always appear at the head of the list.

Arguments

<i>s_function</i>	Turns off counting for the functions given.
<i>t</i>	Turns off counting for all functions.

Value Returned

<i>g_result</i>	List containing the number of times each function was called, along with the function name.
-----------------	---

Examples

```
count( plus greaterp )      ; Counts plus and greaterp  
setq( x plus( 2 3 ))        ; Use the functions being counted.  
uncount( plus greaterp)  
=> ((1 plus)(0 greaterp))    ; Number of times each  
                               ; function was called.
```

Cadence SKILL Development Reference

Debug Functions

Related Topics

Debug Functions

count

uninstallDebugger

```
uninstallDebugger(  
    )  
=> t / nil
```

Description

Uninstalls the SKILL debugger as the error handler. Turns off debug mode.

Restores the normal system error handler, which prints the error message and returns to the nearest top-level. Also turns debug mode off and restores write protection on all functions.

Arguments

None

Value Returned

t	The debugger is successfully uninstalled.
nil	The debugger is not installed.

Examples

```
installDebugger()      ; Installs the SKILL debugger.  
4 / 0                  ; Generates an error and enters  
                        ; the SKILL debugger.  
debugQuit()           ; Exits the debugger.  
uninstallDebugger( )  ; Restores the old error handler.
```

Related Topics

[Debug Functions](#)

[debugQuit](#)

[installDebugger](#)

untrace

```
untrace(  
    [ s_function | t_fileName ... | t ]  
)  
=> g_result
```

Description

Turns tracing off for all functions specified that were traced using the `tracef` function. This is an `nlambda` function.

If the argument is a string, `untrace` assumes it is a file name and checks if the file was loaded after debug mode was turned on. If it was, it untraces all functions defined in that file.

Arguments

<i>s_function</i>	Any function that should no longer be traced.
<i>t_filename</i>	Any file containing functions that should no longer be traced.
<i>t</i>	Turns off tracing for all functions that had tracing turned on.

Value Returned

<i>g_result</i>	List of the functions or files that were untraced.
-----------------	--

Examples

Turn off tracing for the `plus` function.

```
untrace( plus)
```

Turns off tracing for all functions in the `testfns` file assuming it was loaded after debug mode was turned on.

```
untrace( "testfns")
```

Clears all tracing.

```
untrace( t )
```

Related Topics

Debug Functions

Cadence SKILL Development Reference

Debug Functions

tracef

tracev

untracev

Cadence SKILL Development Reference

Debug Functions

untracep

```
untracep(  
    [ { S_property... | t } ]  
)  
=> g_result
```

Description

Turns off tracing of the specified properties. This is an `nlambda` function.

Arguments

<i>S_property</i>	Names of the properties to be untraced.
<i>t</i>	Untrace all properties.

Value Returned

<i>g_result</i>	Properties successfully marked for untracing.
-----------------	---

Examples

```
tracep myProp  
putprop( 'foo 5 'myProp)  
|Property myProp on foo set to 5, was nil  
=> 5  
untracep( myProp ) => ( myProp )
```

Related Topics

[Debug Functions](#)

[tracep](#)

Cadence SKILL Development Reference

Debug Functions

untracev

```
untracev(  
    [ { s_variable ... | t } ]  
)  
=> g_result
```

Description

Turns off tracing for assignments to specified variables. This is an `nlambda` function.

Arguments

<i>s_variable</i>	Names of the variables to be untraced.
<i>t</i>	Untrace all variables.

Value Returned

<i>g_result</i>	Variables successfully marked for untracing.
-----------------	--

Examples

<code>tracev x</code>	<code>; Traces the variable x.</code>
<code>x = 5</code>	<code>; Shows the old and new value of x.</code>
<code>untracev x</code>	<code>; Clears tracing for the variable x.</code>
<code>tracev t</code>	<code>; Traces all variable assignments.</code>
<code>untracev t</code>	<code>; Clears all variable tracing.</code>

Related Topics

[Debug Functions](#)

[tracev](#)

[tracef](#)

[untrace](#)

unwatch

```
unwatch(  
    [ s_symbol...]  
)  
=> t
```

Description

Clears watchpoints set on the specified variables.

Arguments

<i>s_symbol</i>	Names of the variables for which the watchpoints need to be cleared.
-----------------	--

Value Returned

t	Watchpoints successfully cleared.
---	-----------------------------------

Examples

```
unwatch( x ) => t
```

Related Topics

[Debug Functions](#)

watch

```
watch(  
    [ s_symbol... ]  
)  
=> t / l_watchedVars / nil
```

Description

Sets watchpoints on the specified variables. If `watch()` is called without arguments, it returns the list of variables being watched. If no variables are being watched, it returns `nil`.

Arguments

<i>s_symbol</i>	The variables to be watched.
-----------------	------------------------------

Value Returned

<i>t</i>	Variables successfully marked for watching.
<i>l_watchedVars</i>	List of variables being watched.
<i>nil</i>	No variables are being watched.

Examples

```
watch(x) => t  
watch()=> (x)  
watch() => nil
```

Related Topics

[Debug Functions](#)

where

```
where (
    [ g_unevaluated ]
    [ x_depth ]
    [ x_skip ]
    [ p_port ]
)
=> x_result
```

Description

Prints the functions on the stack and their arguments to the depth specified, or to the bottom of the stack, including the local variables and their bindings.

It is similar to `stacktrace`, but in addition to printing out the functions on the stack, it also prints out the local variables and their bindings. The `where` function observes the following rules:

- When debug mode is on and the `traceArgs` status switch has been set to `non-nil`, prints the evaluated function arguments unless `g_unevaluated` is set to `t`.
- When debug mode is off, `where` always prints the unevaluated arguments.
- `where` skips over the number of function calls specified by `x_skip`.
- If there are no functions on the stack (you are at the top, for example) `where` does not print anything and returns 0.

This function is usually used inside the break or error handler.

Arguments

<i>g_unevaluated</i>	Prints the unevaluated function parameters.
<i>x_depth</i>	Number of stack levels to print. The default is <code>all</code> .
<i>x_skip</i>	Number of levels to skip. The default is <code>1</code> .
<i>p_port</i>	Output port. Defaults to the error port if not specified.

Value Returned

<i>x_result</i>	Number of stack frames printed.
-----------------	---------------------------------

Cadence SKILL Development Reference

Debug Functions

Examples

Suppose `/tmp/color.il` defines function `initColor`:

```
(defun initColor (object)
  (let ((colorList '(red green yellow)) color)
    (setq color (concat (get object 'color)))
    (if (memq color colorList)
        (printf "color %s initialized" (get object 'name)))
  )
)
```

Try this file in debugger:

```
installDebugger
=> t
1> (sstatus sourceTracing t)
                                ; Turns on sourceTracing to get line numbers
=> t

1> load "/tmp/color.il"
=> t

1> (putprop 'object1 "green" 'color)
=> "green"

1> (initColor 'object1)
*** Error in routine fprintf/sprintf:
Message: *Error* fprintf/sprintf: format spec. incompatible
with data

Debug 2> where
<<< Stack Trace >>>
errorHandler("fprintf/sprintf" 0 t nil ("*Error* fprintf/sprintf: format spec.
incompatible with data" nil))
printf("color %s initialized" get(object 'name))
at line 5 in file /tmp/color.il
if(memq(color colorList) printf("color %s initialized" get(object 'name)))
let((colorList '&) color) (color = concat(get(object &))) if(memq(color colorList)
printf("color %s initialized" get(object &)))
    colorList = (red green yellow)
    color = green
    object = object1
initColor('object1)
5
```

Related Topics

Debug Functions

sstatus

stacktrace

Cadence SKILL Development Reference

Debug Functions

whereIs

```
whereIs(  
    s_function  
)  
=> t / nil
```

Description

Prints the last file loaded in debug mode in which a function was defined, as well as the starting line number.

You must turn on debug mode before loading the file.

Arguments

<i>s_function</i>	Function whose file you want to locate.
-------------------	---

Value Returned

t	The function is found.
nil	The function is not found.

Examples

Returns t if the function was found and prints the file and starting line number of the myFunction function if it was loaded after debug mode was turned on.

```
whereIs( myFunction )  
=> t
```

A sample output is:

```
Function myFunction was loaded from file ~/myFunctions.il at line 126.
```

Related Topics

[Debug Functions](#)

[getFunctions](#)

Finder Functions

Quick reference information for syntax and abstract statements for SKILL language functions and application procedural interfaces (APIs) is available using the Cadence SKILL API Finder, which is accessible from the SKILL IDE window, CIW, or from the UNIX command line.

The following SKILL API Finder functions are available.

- [fndResetDb](#)
- [startFinder](#)

Related Topics

[Profiler Functions](#)

[Lint Functions](#)

[Context Functions](#)

[Debug Functions](#)

[Tabulator Functions](#)

[SKILL IDE Functions](#)

fndResetDb

```
fndResetDb(  
    )  
=> t
```

Description

Resets a previously loaded Finder database.

Arguments

None

Value Returned

t	Finder database is successfully reset.
---	--

Examples

```
help('myFunction')  
=> nil  
; documentation for myFunction is not yet loaded (added after finder init).  
  
fndResetDb()  
;reset database  
  
help('myFunction')  
; documentation is available now
```

Related Topics

[Finder Functions](#)

[startFinder](#)

startFinder

```
startFinder(  
    [ ?funcName t_funcName ]  
)  
=> t / nil
```

Description

Starts the SKILL API Finder utility. If the *t_funcName* argument is provided, the corresponding documentation of the function is displayed in the Finder. If a Finder window is already open, it will be updated or a new window will be displayed. The Finder window remains open, unless specifically closed, even after the parent window has been closed.

Arguments

?funcName t_funcName

Name of the function to be searched in the SKILL API Finder.

Value Returned

<i>t</i>	Cadence SKILL API Finder is launched successfully and documentation of <i>t_funcName</i> is returned.
<i>nil</i>	Unable to launch the Cadence SKILL API Finder.

Examples

To start the SKILL API Finder utility.

```
startFinder  
=> 0
```

To display the documentation of the function in the SKILL API Finder utility.

```
startFinder(?funcName "")  
=> t
```

Related Topics

Finder Functions

fndResetDb

Cadence SKILL Development Reference

Finder Functions

Tabulator Functions

The SKILL Tabulator creates a non-proprietary snap-shot of your SKILL environment and reports the Cadence functions called from your SKILL code. It ignores all user functions to preserve confidentiality.

The following SKILL tabulator functions are available.

- [skTabulate](#)
- [skTabulateSKILL](#)

Related Topics

[Profiler Functions](#)

[Lint Functions](#)

[Context Functions](#)

[Debug Functions](#)

[Finder Functions](#)

[SKILL IDE Functions](#)

skTabulate

```
skTabulate(  
    ?fileNames g_tabulatedFileNames  
    [ ?reportFile t_reportFile ]  
    [ ?showFile g_showFile ]  
    [ ?dontResolveSymLink g_dontResolveSymLink ]  
    [ ?customerInfo l_customerInfo ]  
    [ ?printFiltered g_printFiltered ]  
    [ ?ext l_ext ]  
    [ ?infoFile g_infoFile ]  
    [ ?defnFile g_defnFile ]  
    [ ?recurse g_recurse ]  
    [ ?exclude g_exclude ]  
    [ ?recurseExclude g_recurseExclude ]  
    [ ?sendReport g_sendReport ]  
=> t
```

Description

Runs the SKILL Tabulator in batch mode.

Arguments

?fileNames g_tabulatedFileNames

The names of the files or directories to be tabulated. Should be a string or a list of strings.

?reportFile t_reportFile

The name of the generated report file. Defaults to `"./skillTab.out"`.

?showFile g_showFile

Specifies whether to display the generated report file. Defaults to `nil`.

?dontResolveSymLink g_dontResolveSymLink

Specifies whether to resolve symbolic links. Defaults to `nil`.

?customerInfo l_customerInfo

Cadence SKILL Development Reference

Tabulator Functions

A disembodied property list containing customer information, in the following form:

```
(nil customerEmail <t_email>
customerName <t_name>
companyLocation <t_location>
companyName <t_compName>
customerPhone <t_phone>
custProjName <t_projName>
custProjInfo <t_projInfo>)
```

`?printFiltered` *g_printFiltered*

Specifies whether to print user defined functions. Defaults to `t`.

`?ext` *l_ext*

List of file extensions to be tabulated. The default options are `".il"`, `"ile"`, and `"cdsinit"`.

`?infoFile` *g_infoFile*

The file name for the information file, which contains the names of the files that refer each function.

`?defnFile` *g_defnFile*

The file name for the definition file, which contains the names of the files that define each function.

`?recurse` *g_recurse*

Specifies whether to recurse directories. Defaults to `t`.

`?exclude` *g_exclude*

List of files to be excluded from tabulation. Defaults to `nil`.

`?recurseExclude` *g_recurseExclude*

List of recursively excluded files. Defaults to `nil`.

`?sendReport` *g_sendReport*

Specifies whether to send the generated report to Cadence. Defaults to `nil`.

Cadence SKILL Development Reference

Tabulator Functions

Value Returned

t Always returns t.

Examples

```
skTabulate(  
    list("./file1.il" "file2.il")  
    ?reportFile "./myTabOutput.txt"  
    ?showFile nil  
    ?dontResolveSymLink nil  
    ?customerInfo '(nil customerEmail "user@xyz.com" customerName "AN"  
        companyLocation "SJ" companyName "myCompany" customerPhone "123456"  
        custProjName "" custProjInfo "")  
    ?printFiltered t  
    ?defnFile "./myDefnFile.txt"  
    ?recurseExclude nil  
    ?infoFile "./myInfoFile.txt"  
    ?ext '("il")  
    ?sendReport t  
);
```

Related Topics

[Tabulator Functions](#)

skTabulateSKILL

```
skTabulateSKILL(  
    )  
=> t
```

Description

Brings up the SKILL Tabulator UI form.

The SKILL Tabulator is part of the SKILL Surveyor program. Users should access the SKILL Tabulator through SKILL Surveyor, part of the Conversion tool box.

Arguments

None

Value Returned

t	Always returns t.
---	-------------------

Examples

```
skTabulateSKILL()  
=> t
```

Related Topics

[Tabulator Functions](#)

Cadence SKILL Development Reference

Tabulator Functions

SKILL IDE Functions

Virtuoso® SKILL IDE is a development tool that helps you develop, test, and refine SKILL programs. The core of SKILL IDE is a multi-file that provides common editing and debugging capabilities. These capabilities include auto indenting, auto completion of function names, syntax highlighting, single stepping through SKILL programs (that is, executing the program statements one by one), setting up and stopping at breakpoints, saving and loading debugging information, tracing and editing the values of variables during program execution, and displaying variables and stack trace.

You can load and debug only SKILL and SKILL++ programs in SKILL IDE.

The following SKILL IDE functions are available.

<u>ilgAddRecentFiles</u>	<u>ilgAppendText</u>	<u>ilgCopy</u>
<u>ilgCut</u>	<u>ilgFindIdent</u>	<u>ilgFindParenthesis</u>
<u>ilgFoldLine</u>	<u>ilgGetCursorLocation</u>	<u>ilgGetEditLock</u>
<u>ilgGetHighlight</u>	<u>ilgGetSelectedLocation</u>	<u>ilgGetText</u>
<u>ilgInvokeIDE</u>	<u>ilgLastDir</u>	<u>ilgPaste</u>
<u>ilgPositionInComment</u>	<u>ilgRegisterSelectionCB</u>	<u>ilgResetHighlight</u>
<u>ilgSetColor</u>	<u>ilgResetWarningMarker</u>	<u>ilgRunSKILLIDE</u>
<u>ilgScrollToLocation</u>	<u>ilgSearchText</u>	<u>ilgSelectText</u>
<u>ilgSetColor</u>	<u>ilgSetCursorLocation</u>	<u>ilgSetEditLock</u>
<u>ilgSetErrorMarker</u>	<u>ilgSetHighlight</u>	<u>ilgSetWarningMarker</u>
<u>ilgUnfoldLine</u>	<u>ilgUnregisterSelectionCB</u>	

Related Topics

[Profiler Functions](#)

[Lint Functions](#)

Cadence SKILL Development Reference

SKILL IDE Functions

Context Functions

Debug Functions

Finder Functions

Tabulator Functions

ilgAddRecentFiles

```
ilgAddRecentFiles(  
    l_fileList  
)  
=> t
```

Description

Adds the files listed in *l_fileList* to the SKILL IDE *File* menu.

Arguments

<i>l_fileList</i>	The list of files to be added to the SKILL IDE <i>File</i> menu.
-------------------	--

Value Returned

t	The listed files were successfully added to the SKILL IDE <i>File</i> menu.
---	---

Examples

```
ilgAddRecentFiles('("loop2.il"))  
=> t
```

Related Topics

[SKILL IDE Functions](#)

ilgAppendText

```
ilgAppendText(  
    t_text  
    [ w_tab ]  
)  
=> t / nil
```

Description

Inserts text into the SKILL IDE editor window at the current cursor location.

Arguments

<i>t_text</i>	The text to be inserted.
<i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.

Value Returned

<i>t</i>	The text was inserted.
<i>nil</i>	The text was not inserted.

Examples

```
ilgAppendText("hello IDE")  
=> t
```

Related Topics

[SKILL IDE Functions](#)

ilgCopy

```
ilgCopy(  
    [ w_tab ]  
)  
=> t
```

Description

Copies the selected text into public text buffer. This function does not work on read-only files.

Arguments

<i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.
--------------	--

Value Returned

<i>t</i>	The text was copied.
<i>nil</i>	The operation was not successful because the file is read-only.

Examples

```
ilgCopy( )  
=> t  
; text copied into public text buffer
```

Related Topics

[SKILL IDE Functions](#)

ilgCut

```
ilgCut(  
    [ w_tab ]  
)  
=> t / nil
```

Description

Cuts and pastes the selected text into public text buffer. This function does not work on read-only files.

Arguments

<i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.
--------------	--

Value Returned

<i>t</i>	The text was cut.
<i>nil</i>	The text was not cut because the file was read-only.

Examples

```
ilgCut( )  
=> t
```

Related Topics

[SKILL IDE Functions](#)

ilgFindIdent

```
ilgFindIdent(  
    x_column  
    x_row  
    [ ?tab w_tab ]  
)  
=> l_coord / nil
```

Description

Returns the nearest identifiers from a given opening parenthesis location '(' in the SKILL IDE editor tab.

Arguments

<i>x_column</i>	Column coordinates of the opening parenthesis '('.
<i>x_row</i>	Row coordinates of the opening parenthesis '('.
?tab <i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.

Value Returned

<i>l_coord</i>	List containing two identifier strings, one before the opening parenthesis and the other after it.
nil	<i>x_column</i> and <i>x_row</i> are not coordinates of '('.

Examples

If the first row in SKILL IDE tab is: a (b ((c))) d ("e")

```
ilgFindIdent(1 1)  
=> nil  
  
ilgFindIdent(3 1)  
=> ("a" "b")  
  
ilgFindIdent(4 1)  
=> nil  
  
ilgFindIdent(7 1)  
=> ("b" "")  
  
ilgFindIdent(8 1)  
=> (" " "c")
```

Cadence SKILL Development Reference

SKILL IDE Functions

```
ilgFindIdent(17 1)  
=> ("d" "\e\"")
```

Related Topics

[SKILL IDE Functions](#)

ilgFindParenthesis

```
ilgFindParenthesis(  
    x_column  
    x_row  
    [ ?level S_level ]  
    [ ?direction S_direction ]  
    [ ?tab w_tab ]  
)  
=> l_coord / nil
```

Description

Returns the closest parenthesis in a file currently open in the SKILL IDE editor.

Arguments

<code>x_column</code>	Column coordinates of the specified location.
<code>x_row</code>	Row coordinates of the specified location.
<code>?level S_level</code>	Specifies whether to search the closest <code>outer</code> or <code>inner</code> parenthesis in a file. Default is <code>outer</code> .
<code>?direction S_direction</code>	Search direction (symbol). Valid values are <code>forward</code> and <code>backward</code> . Default is <code>forward</code> .
<code>?tab w_tab</code>	The window ID of the SKILL IDE editor window. Default is the current tab window.

Value Returned

<code>l_coord</code>	List containing the coordinates of the pair of parenthesis.
<code>nil</code>	No parenthesis pair was found.

Examples

If the first row in SKILL IDE tab is: "a (b ((c))) d"

```
ilgFindParenthesis(1 1)  
=> nil
```

Cadence SKILL Development Reference

SKILL IDE Functions

```
ilgFindParenthesis(1 1 ?level 'inner)
=> ((3 1) (9 1))

ilgFindParenthesis(4 1 ?level 'outer)
=> ((3 1) (9 1))

ilgFindParenthesis(10 1 ?level 'inner ?direction 'backward)
=> ((3 1) (9 1))
```

Related Topics

SKILL IDE Functions

ilgFoldLine

```
ilgFoldLine(  
    [ x_column ]  
    [ x_row ]  
)  
=> t / nil
```

Description

Folds a document block in SKILL IDE at (*x_column x_row*) where (*x_column x_row*) is the location of an opening parenthesis. If this function is called without arguments, the current cursor location is used for computing (*x_column x_row*).

Arguments

<i>x_column</i>	Column coordinates of the opening parenthesis '('.
<i>x_row</i>	Row coordinates of the opening parenthesis '('.

Value Returned

t	The document block was successfully folded.
nil	The fold of document block was unsuccessful.

Examples

```
[~]defun(test (x y "xx")  
"test function"  
x + y  
4 )  
ilgFoldLine(6 1)  
=> t
```

Related Topics

[SKILL IDE Functions](#)

ilgGetCursorLocation

```
ilgGetCursorLocation(  
    [ w_tab ]  
)  
=> l_location
```

Description

Returns the location of the cursor in the SKILL IDE editor window.

Arguments

<i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.
--------------	--

Value Returned

<i>l_location</i>	Cursor location in the current or specified tab.
-------------------	--

Examples

```
ilgGetCursorLocation( )  
=> (9 11)
```

Related Topics

[SKILL IDE Functions](#)

ilgGetEditLock

```
ilgGetEditLock(  
    [ w_tab ]  
)  
=> s_mode
```

Description

Returns the read-only property for a SKILL IDE editor window.

Arguments

<i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.
--------------	--

Value Returned

<i>s_mode</i>	<p>The read-only status of the specified window. This can be one of the following:</p> <p><i>lock</i>: Cannot edit text in the tab.</p> <p><i>partialLock</i>: Cannot edit the text manually, but can edit it programmatically with <code>ilgAppendText</code>, <code>ilgCut</code>, and <code>ilg-Paste</code>.</p> <p><i>unlock</i>: Text in the tab is editable.</p>
---------------	---

Examples

```
ilgGetEditLock( )  
=> unlock
```

Related Topics

[SKILL IDE Functions](#)

ilgGetHighlight

```
ilgGetHighlight(  
    [ ?loc l_location ]  
    [ ?tab w_tab ]  
)  
=> l_highlightIDs / nil
```

Description

Returns the list of highlight IDs for the text highlighted in the SKILL IDE editor window.

Arguments

<code>?loc l_location</code>	Location (<i>x_column x_row</i>) of the area highlighted in the SKILL IDE editor window.
<code>?tab w_tab</code>	The window ID of the SKILL IDE editor window. Default is the current tab window.

Value Returned

<code>l_highlightIDs</code>	A list representing the highlight IDs of the highlighted text.
<code>nil</code>	Nothing is highlighted in the given area.

Examples

```
ilgSetHighlight('(4 11) '(18 12) "orange")  
=> (nil 11 (4 11) 12 (18 12)  
color "orange" fullWidth nil)  
;highlights the area between (4 11) and (18 12)  
ilgGetHighlight(?loc '(4 11))  
=> ((nil 11  
    (4 11) 12  
    (18 12)  
    color "#ffa500" fullWidth nil  
    )  
    (nil 11  
    (4 11) 12  
    (2 13)  
    color "#ffa500" fullWidth nil  
    )  
    )
```


Cadence SKILL Development Reference

SKILL IDE Functions

Related Topics

SKILL IDE Functions

ilgGetSelectedLocation

```
ilgGetSelectedLocation(  
    [ w_tab ]  
)  
=> l_location / nil
```

Description

Returns the location coordinates of the current selection in the SKILL IDE editor window.

Arguments

<i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.
--------------	--

Value Returned

<i>l_location</i>	Location coordinates of the current selection in the SKILL IDE editor window.
<i>nil</i>	Nothing is selected in the SKILL IDE editor window.

Examples

```
ilgGetSelectedLocation( )  
=> ((1 11)  
    (4 11)  
    )
```

Related Topics

[SKILL IDE Functions](#)

ilgGetText

```
ilgGetText (
    [ l_location_begin ]
    [ l_location_end ]
    [ w_tab ]
)
=> t_text
```

Description

Returns the text between *l_location_begin* and *l_location_end*. If these locations are not provided, the entire text in the SKILL IDE editor window is returned.

Arguments

<i>l_location_begin</i>	Column coordinates of the cursor location.
<i>l_location_end</i>	Row coordinates of the cursor location.
<i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.

Value Returned

<i>t_text</i>	The text between <i>l_location_begin</i> and <i>l_location_end</i> . If <i>l_location_begin</i> and <i>l_location_end</i> are not provided, the entire text in the SKILL IDE editor window is returned.
---------------	--

Examples

```
ilgGetText ()
=> "hello ide!"
```

Note: If the specified locations are such that *l_location_end* precedes *l_location_begin*, the *l_location_begin* and *l_location_end* coordinates are swapped, so that *ilgGetText* returns the text between *l_location_begin* and *l_location_end*. For Examples:

```
ilgGetText ( ' (1 1) ' (5 1) )
=> "(pro"

ilgGetText ( ' (5 1) ' (1 1) )
=> "(pro"
```

Cadence SKILL Development Reference

SKILL IDE Functions

Related Topics

SKILL IDE Functions

ilgInvokeIDE

```
ilgInvokeIDE(  
    )  
=> t
```

Description

Displays the SKILL IDE main window.

Arguments

None

Value Returned

t	Always returns t.
---	-------------------

Examples

```
ilgInvokeIDE()  
=> t
```

Related Topics

[SKILL IDE Functions](#)

ilgLastDir

```
ilgLastDir(  
    )  
=> t_dirPath
```

Description

Returns the directory path of the file currently open in SKILL IDE.

Arguments

None

Value Returned

<i>t_dirPath</i>	Directory path of the file currently open in SKILL IDE.
------------------	---

Examples

```
ilgLastDir()  
=> /home/usr1
```

Related Topics

[SKILL IDE Functions](#)

ilgPaste

```
ilgPaste(  
    [ w_tab ]  
)  
=> t / nil
```

Description

Pastes the text from the clipboard/buffer to the cursor location in the SKILL IDE editor window. This function does not work on read-only files.

Arguments

<i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.
--------------	--

Value Returned

<i>t</i>	The text was pasted to the current cursor location.
<i>nil</i>	The document in the SKILL IDE editor window is read-only.

Examples

```
ilgPaste()  
=> t
```

Related Topics

[SKILL IDE Functions](#)

ilgPositionInComment

```
ilgPositionInComment(  
    x_column  
    x_row  
    [ ?tab w_tab ]  
)  
=> t / nil
```

Description

Checks if the specified coordinates (*x_column* *x_row*) fall within a comments block in the SKILL IDE document.

Arguments

<i>x_column</i>	Column coordinates of the specified location.
<i>x_row</i>	Row coordinates of the specified location.
<i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.

Value Returned

t	The specified coordinates (<i>x_column</i> <i>x_row</i>) fall within a comments block in the SKILL IDE document.
nil	The specified coordinates (<i>x_column</i> <i>x_row</i>) do not fall within a comments block in the SKILL IDE document.

Examples

If the SKILL IDE editor window has the following text:

```
defun(test (x y "xx")  
/* function test */  
x + y  
) ; return sum x and y  
ilgPositionInComment(1 1)  
=> nil  
ilgPositionInComment(10 2)  
=> t  
ilgPositionInComment(8 4)  
=> t
```


Cadence SKILL Development Reference

SKILL IDE Functions

Related Topics

SKILL IDE Functions

ilgRegisterSelectionCB

```
ilgRegisterSelectionCB(  
    g_name  
)  
=> t
```

Description

Registers a SKILL callback for SKILL IDE, which is called when some text is selected in the SKILL IDE editor window.

Arguments

<i>g_name</i>	The function to be registered as a callback. It can be either a symbol, function name, or a lambda function. The function being registered should accept 3 arguments: two lists (begin and end selection location) and window variable (current tab window).
---------------	--

Value Returned

t	The function has been registered as a callback.
---	---

Examples

To register a selection callback:

```
defun(mySelCallback (l_begin l_end wTab)  
    printf("Selected text %L - %L in tab window %L\n"  
        l_begin l_end wTab))  
    ilgRegisterSelectionCB('mySelCallback)  
=> t
```

Related Topics

[SKILL IDE Functions](#)

ilgResetErrorMarker

```
ilgResetErrorMarker(  
    x_line  
    [ w_tab ]  
)  
=> t
```

Description

Clears the error marker that was set by `ilgSetErrorMarker()` on line *x_line* in the SKILL IDE editor window.

Arguments

<i>x_line</i>	Line number from which the error marker needs to be cleared.
<i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.

Value Returned

t	The error marker has been cleared.
---	------------------------------------

Examples

```
ilgResetErrorMarker(4)  
; clears the error marker at line 4
```

Related Topics

[SKILL IDE Functions](#)

ilgResetHighlight

```
ilgResetHighlight(  
    l_highlightID  
    [ w_tab ]  
)  
=> t
```

Description

Resets a specified highlight in a SKILL IDE document between location *l_location_begin* and *l_location_end*.

Arguments

<i>l_highlightID</i>	ID from which the highlight needs to be cleared.
<i>w_tab</i>	The window ID of the SKILL IDE editor window. The default is the current tab window.

Value Returned

<i>t</i>	The highlights were cleared.
----------	------------------------------

Examples

```
ilgResetHighlight(myHighlightID_1)  
=> t
```

Related Topics

[SKILL IDE Functions](#)

ilgResetWarningMarker

```
ilgResetWarningMarker(  
    x_line  
    [ w_tab ]  
)  
=> t
```

Description

Clears the warning marker that was set by `ilgSetWarningMarker()` on line *x_line* in the SKILL IDE editor window.

Arguments

<i>x_line</i>	Line number from which the warning marker needs to be cleared.
<i>w_tab</i>	The window ID of the SKILL IDE editor window. The default is the current tab window.

Value Returned

t	The warning marker has been cleared.
---	--------------------------------------

Examples

```
ilgResetWarningMarker(4)  
; clears the warning marker at line 4
```

Related Topics

[SKILL IDE Functions](#)

ilgRunSKILLIDE

```
ilgRunSKILLIDE(  
    [ ?fileList lt_fileList ]  
)  
=> t / nil
```

Description

Launches SKILL IDE and opens the files listed in *lt_fileList*.

Arguments

?fileList lt_fileList

A list of file names that need to be opened in SKILL IDE.

Value Returned

<i>t</i>	SKILL IDE was launched successfully.
<i>nil</i>	SKILL IDE could not be launched.

Examples

```
ilgRunSKILLIDE(?fileList (list "demo.il"))  
=> t
```

Related Topics

[SKILL IDE Functions](#)

ilgScrollToLocation

```
ilgScrollToLocation(  
    l_location  
    [ w_tab ]  
)  
=> t / nil
```

Description

Scrolls to the specified location in the specified SKILL IDE editor window or tab.

Arguments

<i>l_location</i>	Coordinates of the location to scroll to. The list is in the format <i>x_column x_row</i> .
<i>w_tab</i>	ID of the SKILL IDE editor window or tab. If not specified, the current tab is considered.

Value Returned

<i>t</i>	Scrolls to the specified location.
<i>nil</i>	Unable to scroll to the specified location.

Examples

To scroll to column 2 and row 30 in the current SKILL IDE window:

```
ilgScrollToLocation(' (2 30))  
=> t
```

Related Topics

[SKILL IDE Functions](#)

ilgSearchText

```
ilgSearchText(  
    t_text  
    [ ?loc l_location ]  
    [ ?direction s_direction ]  
    [ w_tab ]  
)  
=> l_location / nil
```

Description

Searches the specified text in a SKILL IDE document.

Arguments

<i>t_text</i>	Text to be searched.
<i>?loc l_location</i>	Location coordinates of the search area. By default, the search area is the whole document.
<i>?direction s_direction</i>	Search direction (symbol). Valid values are <code>forward</code> and <code>backward</code> . Default is <code>forward</code> .
<i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.

Value Returned

<i>l_location</i>	List of the locations of all occurrences of <i>t_text</i> in the search area.
<i>nil</i>	No occurrences of <i>t_text</i> are found in the search area.

Examples

To search for the word IDE in the SKILL IDE window

```
ilgSearchText("IDE")  
=>
```


Cadence SKILL Development Reference

SKILL IDE Functions

```
((7 1)
  (11 4)
  (1 7)
  (1 9)
)
```

Related Topics

SKILL IDE Functions

ilgSelectText

```
ilgSelectText(  
    l_location_begin  
    l_location_end  
    [ w_tab ]  
)  
=> t
```

Description

Selects the text between location *l_location_begin* and *l_location_end* in the SKILL IDE editor window.

Arguments

<i>l_location_begin</i>	Begin location (<i>x_column x_row</i>) of the text to be selected.
<i>l_location_end</i>	End location (<i>x_column x_row</i>) of the text to be selected.
<i>w_tab</i>	The window ID of the SKILL IDE editor window. Default is the current tab window.

Value Returned

<i>t</i>	The text was successfully selected.
----------	-------------------------------------

Examples

To select the text from (line 2 column 1) to (line 10 column 8) in the current SKILL IDE window.

```
ilgSelectText('(1 2) '(8 10))  
=> t
```

Related Topics

[SKILL IDE Functions](#)

ilgSetColor

```
ilgSetColor(  
    t_text  
    t_value  
    [ x_alpha ]  
)  
=> t / nil
```

Description

Sets a custom color for the given SKILL IDE GUI control.

Arguments

t_text

SKILL IDE GUI control name. Can be one of the following:

Step, Error, Cross, SelectPattern, MatchParent, MismatchParent, Keyword, KeywordBg, Comment, CommentBg, Number, NumberBg, String, StringBg, Text, TextBg, TextArea, Highlight1, Highlight2, Highlight3, Highlight4, Highlight5

t_value

A string representing the color name.

- #RGB (each of R, G, and B is a single hex digit)
- #RRGGBB
- #RRRGGBBB
- #RRRRGGGGBBBB
- A name from the list of colors defined in the list of SVG color keyword names provided by the World Wide Web Consortium. For example, "steelblue" or "gainsboro". These color names work on all platforms.

These color names are not the same as defined by Qt. GlobalColor enums, for example, green and Qt:green do not refer to the same color.

- Transparent - Represents the absence of a color.
- X11 only: Any valid X11 color name.

The color is invalid if name cannot be parsed.

Cadence SKILL Development Reference

SKILL IDE Functions

x_alpha A value representing the alpha color component (in range 0 - 255).

Value Returned

t The color was successfully set.
nil The color setting was unsuccessful.

Examples

To set the color of text in the current SKILL IDE window to “steelblue”

```
ilgSetColor("Text" "steelblue")  
=> t
```

Related Topics

[SKILL IDE Functions](#)

ilgSetCursorLocation

```
ilgSetCursorLocation(  
    l_location  
    [ w_tab ]  
)  
=> t / nil
```

Description

Sets the cursor location in a SKILL IDE document.

Arguments

<i>l_location</i>	Location coordinates of the cursor.
<i>w_tab</i>	Window ID of the SKILL IDE editor window. Default is the current tab window.

Value Returned

<i>t</i>	Sets the cursor location.
<i>nil</i>	Unable to set the cursor location.

Examples

To set the cursor location in the SKILL IDE window:

```
ilgSetCursorLocation('(9 11))  
=> t  
  
ilgSetCursorLocation('(37 4))  
=> nil
```

Related Topics

[SKILL IDE Functions](#)

ilgSetEditLock

```
ilgSetEditLock(  
    s_mode  
    [ w_tab ]  
)  
=> t
```

Description

Changes the read-only property for a SKILL IDE editor window.

Arguments

<i>s_mode</i>	Edit lock mode. Valid values are: lock: Cannot edit text in the tab. partialLock: Cannot edit the text manually, but can edit it programmatically with <code>ilgAppendText</code> , <code>ilgCut</code> , and <code>ilgPaste</code> . unlock: Document is editable. The mode cannot be set to <code>unlock</code> or <code>partialLock</code> for a read-only file.
<i>w_tab</i>	Window ID of the SKILL IDE editor window. Default is the current tab window

Value Returned

t	The operation was successful.
nil	The operation was unsuccessful.

Examples

To lock the SKILL IDE editor window:

```
ilgSetEditLock('lock)  
=> t
```

Cadence SKILL Development Reference

SKILL IDE Functions

Related Topics

SKILL IDE Functions

ilgSetErrorMarker

```
ilgSetErrorMarker(  
    x_line  
    t_description  
    [ w_tab ]  
)  
=> t
```

Description

Sets the error marker with the pop-up description *t_description* on line *x_line* of the SKILL IDE editor window.

Arguments

<i>x_line</i>	Line number on which the error marker needs to be set.
<i>t_description</i>	Description of the error marker.
<i>w_tab</i>	The window ID of the SKILL IDE editor window. The default is the current tab window.

Value Returned

t	The error marker has been set.
---	--------------------------------

Examples

```
ilgSetErrorMarker(4 "this line is marked")  
=> t  
; Sets the error marker on line 4.
```

Related Topics

[SKILL IDE Functions](#)

ilgSetHighlight

```
ilgSetHighlight (
    l_location_begin
    l_location_end
    t_color
    [ ?fullWidth g_fullWidth ]
    [ w_tab ]
)
=> l_highlightID / nil
```

Description

Highlights the area within *l_location_begin* and *l_location_end* in the color specified by *t_color*.

Arguments

<i>l_location_begin</i>	Begin location (<i>x_column</i> <i>x_row</i>) of the area to be highlighted.
<i>l_location_end</i>	End location (<i>x_column</i> <i>x_row</i>) of the area to be highlighted.
<i>t_color</i>	A string representing the color name, which can either be a predefined color (for Examples, Highlight[1-5]) set by <code>ilgSetColor</code> or a color value understood by QT.
<i>?fullWidth g_fullWidth</i>	When set to <code>t</code> , the entire line is highlighted. The default value is <code>nil</code> .
<i>w_tab</i>	The window ID of the SKILL IDE editor window. The default is the current tab window.

Value Returned

<i>l_highlightID</i>	A list representing the highlight operation; this value can be passed to <code>ilgResetHighlight()</code> .
<code>nil</code>	The highlight operation fails.

Cadence SKILL Development Reference

SKILL IDE Functions

Examples

```
ilgSetHighlight('(4 11) '(18 12) "orange")
=> (nil 11 (4 11) 12 (18 12)
color "orange" fullWidth nil)
;highlights the area between (4 11) and (18 12)

ilgSetHighlight('(5 22) '(15 24) "forest green" ?fullWidth t)
=> (nil 11 (5 22) 12 (15 24)
color "forest green" fullWidth t
)
;highlights the entire line starting at (5 22)
```

Related Topics

SKILL IDE Functions

ilgSetWarningMarker

```
ilgSetWarningMarker(  
    x_line  
    t_description  
    [ w_tab ]  
)  
=> t
```

Description

Sets the warning marker with pop-up description *t_description* on line *x_line* of the SKILL IDE editor window.

Arguments

<i>x_line</i>	Line number on which the warning marker needs to be set.
<i>t_description</i>	Description of the warning marker.
<i>w_tab</i>	The window ID of the SKILL IDE editor window. The default is the current tab window.

Value Returned

<i>t</i>	The warning marker has been set.
----------	----------------------------------

Examples

```
ilgSetWarningMarker(4 "this line is marked")  
=> t  
; Sets the warning marker on line 4.
```

Related Topics

[SKILL IDE Functions](#)

ilgUnfoldLine

```
ilgUnfoldLine(  
    [ x_column ]  
    [ x_row ]  
)  
=> t / nil
```

Description

This function unfolds a document block in SKILL IDE at position (*x_column* *x_row*), if it was folded. Here (*x_column* *x_row*) is the location of an opening parenthesis. If this function is called without arguments, the current cursor location is used for computing (*x_column* *x_row*).

Arguments

<i>x_column</i>	Column coordinates of the opening parenthesis '('.
<i>x_row</i>	Row coordinates of the opening parenthesis '('.

Value Returned

t	The document block was successfully unfolded.
nil	The unfold of document block was unsuccessful.

Examples

If code block at line 1 is folded:

```
[+]defun(test (x y)  
)  
ilgUnfoldLine(6 1)  
=> t
```

Related Topics

SKILL IDE Functions

ilgUnregisterSelectionCB

```
ilgUnregisterSelectionCB(  
    [ S_name ]  
)  
=> t / nil
```

Description

Unregisters a selection callback that was previously registered using `ilgRegisterSelectionCB`.

Arguments

<i>S_name</i>	Name of the callback function.
---------------	--------------------------------

Value Returned

t	The function was unregistered.
nil	The function is registered.

Examples

To unregister a selection callback:

```
ilgUnregisterSelectionCB('mySelCallback)  
=> t
```

To unregister all selection callbacks:

```
ilgUnregisterSelectionCB() ;call without arguments  
=> t
```

Related Topics

[SKILL IDE Functions](#)